

# Minimising a Noisy Expensive Function Using Active Learning



**Ross Brown**

Supervisor: Dr. O. Orhobor

Department of Chemical Engineering and Biotechnology  
University of Cambridge

This dissertation is submitted for the degree of  
*Master of Engineering*



## **Declaration**

I hereby declare that except where specific reference is made to the work of others, the contents of this dissertation are original and have not been submitted in whole or in part for consideration for any other degree or qualification in this, or any other university. This dissertation is my own work and contains nothing which is the outcome of work done in collaboration with others, except as specified in the text and Acknowledgements. This dissertation contains fewer than 65,000 words including appendices, bibliography, footnotes, tables and equations and has fewer than 150 figures.

Ross Brown  
September 2021



## **Abstract**

This is where you write your abstract ...



# Table of contents

<b>List of figures</b>	<b>ix</b>
<b>List of tables</b>	<b>xi</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Problem Definition . . . . .	1
<b>2 Simple 1-Dimensional Problem</b>	<b>3</b>
2.1 Outlining of Basic Principles . . . . .	3
2.1.1 Algorithms . . . . .	3
2.1.2 Comparison One . . . . .	5
2.2 Deeper Analysis . . . . .	5
2.2.1 Random Function . . . . .	5
<b>3 My third chapter</b>	<b>11</b>
3.1 First section of the third chapter . . . . .	11
3.1.1 First subsection in the first section . . . . .	11
3.1.2 Second subsection in the first section . . . . .	11
3.1.3 Third subsection in the first section . . . . .	11
3.2 Second section of the third chapter . . . . .	12
3.3 The layout of formal tables . . . . .	12
<b>References</b>	<b>15</b>
<b>Appendix A How to install L<sup>A</sup>T<sub>E</sub>X</b>	<b>17</b>
<b>Appendix B Installing the CUED class file</b>	<b>21</b>





# List of figures

2.1	First Function . . . . .	4
2.2	First Comparison . . . . .	6
2.3	Best Animations . . . . .	9



# List of tables

3.1	A badly formatted table . . . . .	13
3.2	A nice looking table . . . . .	13
3.3	Even better looking table using booktabs . . . . .	13



# Chapter 1

## Introduction

Finding the global minimum of a function within a set of boundaries is a problem of major import. From optimising a synthetic pathway in drug development, to minimising the error in a neural network, minimisation is vitally important to mathematics. Within the numerical field, the goal is usually two fold: reduce the error,  $\varepsilon$ , to the true value *and* reduce the processing time. With these goals in mind, the majority of algorithms exploit the commonality of the cheapness of the target function. However, this is not always the case. Take as an example an experimentation of sand grain size,  $d$ , on the strength of concrete,  $\tau$ . An underlying function of the form  $\tau = f(d)$  exists, but each call to this function takes at least a day, and is labour and material expensive. The target of this paper is to explore how to minimise such a function with the fewest function calls.

### 1.1 Problem Definition

$$y = f(\mathbf{x}) \tag{1.1}$$

Given an equation  $y = f(\mathbf{x})$  where  $\mathbf{x}$  is a vector with  $x_i[\alpha_i, \beta_i]$ , and  $y$  is scalar, find the solution to  $\text{argmin}[f(\mathbf{x})]$ . The algorithm will be able to invoke  $g(\mathbf{x})$  as shown in [] with  $\varepsilon$  representing an unknown random error.

$$g(\mathbf{x}) = f(\mathbf{x}) + \varepsilon \tag{1.2}$$



# Chapter 2

## Simple 1-Dimensional Problem

### 2.1 Outlining of Basic Principles

By constraining  $x$  to one dimension allows for the problem to be simplified. Suppose  $f(x) = \sin(x) + 0.05x^2$  with  $x \in [-10, 10]$  as shown in Figure 2.1. In this range, there are multiple minima with only one global minima. The task here is to successfully locate the minima situated at -1.428 (found through analytical differentiation and solving  $10\cos(x) + x = 0$ ). This will be compared against two benchmarks: linear spacing and the fminbound method available in the scipy package given the same number of function calls.  $\epsilon$  will be chosen to be independent of  $x$  and  $y$  and fit a normal distribution such that  $\epsilon \sim N(0, 0.2^2)$ .

#### 2.1.1 Algorithms

##### Linear Selection

The least intelligent method while not being deliberately obtuse is linearly spacing sampled values and choosing  $x$  equal to the lowest sampled value. This does have the advantage that all experimentations may be construed asynchronously. Thus, where material and labour cost is low, this may be beneficial.

##### Active Learning

This methodology has two underlying core principles: sparse areas reveal the most information and minimal areas reveal information to the location of the minima. Combining these allows for better decision making with regards to the next sample to choose.

There are several methods that may be used to enhance this strategy. Firstly, a smoothing spline between points allows for a non-parametric fit of the data to be used. Alternatively, a




Fig. 2.1  $y = \sin(x) + 0.005x^2$  with  $x \in [-10, 10]$



local regression fit may be used allowing for changes in sample density. Advanced methods using Bayesian Statistics and advanced information theory may be used, although have been omitted due to time restraints.

In this paper, three functions are found:  $e(x)$ ,  $p(x)$  and  $h(x)$ , denoting a guessed fit, the sparsity, and the height respectively.  $p(x)$  is defined between adjacent samples,  $s_i$ .

$$h(x) = -e(x) + \max[e(x)] \quad (2.1)$$

$$p(s_i \leq x \leq s_{i+1}) = \min[x - s_i, s_{i+1} - x] \quad (2.2)$$

The next sample is then taken as  $\operatorname{argmax}_x [h(x)p(x)]$ .

### fminbound

fminbound is a function included in the scipy optimisation library. It uses Brent's method allowing it to be quick in situations where labeling is quick and error is low.

#### 2.1.2 Comparison on $\sin(x) + 0.005x^2$

Each method discussed in [] was executed 50 times for each sample size between 2 and 15. Of note, the active learning method was used in combination with a smoothing spline (using splrep) with  $s = \frac{\text{Number of Samples}^2}{200}$ . This is an arbitrary choice, although it does lead to better results than fminbound on all explored metrics within this example when between 7 and 13 samples are used.

## 2.2 Deeper Analysis

### 2.2.1 Random Function

To fully test these methods, random functions should be used. For this, several basic assumptions are made:

- The function and the first derivative are continuous and smooth.
- The second derivative is continuous
- $x \in [-10, 10]$ .
- $f(-10) = 0$ .
- $f'(-10) \sim U(-4, 4)$ .




Fig. 2.2 Comparison of the three methods discussed. The top left shows the standard deviation of each method, the top right shows the square of the residues, and the bottom shows the result of each sample with an average of the residue drawn on to guide the eye.

- $f''(-10) \sim U(-4, 4)$ .
- $f'''(x) \sim U(-4, 4)$ .

A simple script for this is given below

**The first topic** is dull

**The second topic** is duller

**The first subtopic** is silly

**The second subtopic** is stupid

**The third topic** is the dullest

## 2.3 Hidden section




Fig. 2.3 Best Animations

Subplots

I can cite Wall-E (see Fig. 2.3b) and Minions in despicable me (Fig. 2.3c) or I can cite the whole figure as Fig. 2.3



# Chapter 3

## My third chapter

### 3.1 First section of the third chapter

And now I begin my third chapter here ...

And now to cite some more people Read [2], Ancey et al. [1]

#### 3.1.1 First subsection in the first section

...and some more

#### 3.1.2 Second subsection in the first section

...and some more ...

##### First subsub section in the second subsection

...and some more in the first subsub section otherwise it all looks the same doesn't it? well we can add some text to it ...

#### 3.1.3 Third subsection in the first section

...and some more ...

##### First subsub section in the third subsection

...and some more in the first subsub section otherwise it all looks the same doesn't it? well we can add some text to it and some more and some more and some more and some more and some more and some more and some more ...

### Second subsub section in the third subsection

... and some more in the first subsub section otherwise it all looks the same doesn't it? well we can add some text to it ...

## 3.2 Second section of the third chapter

and here I write more ...

## 3.3 The layout of formal tables

This section has been modified from “Publication quality tables in L<sup>A</sup>T<sub>E</sub>X<sup>\*</sup>” by Simon Fear.

The layout of a table has been established over centuries of experience and should only be altered in extraordinary circumstances.

When formatting a table, remember two simple guidelines at all times:

1. Never, ever use vertical rules (lines).
2. Never use double rules.

These guidelines may seem extreme but I have never found a good argument in favour of breaking them. For example, if you feel that the information in the left half of a table is so different from that on the right that it needs to be separated by a vertical line, then you should use two tables instead. Not everyone follows the second guideline:

There are three further guidelines worth mentioning here as they are generally not known outside the circle of professional typesetters and subeditors:

3. Put the units in the column heading (not in the body of the table).
4. Always precede a decimal point by a digit; thus 0.1 *not* just .1.
5. Do not use ‘ditto’ signs or any other such convention to repeat a previous value. In many circumstances a blank will serve just as well. If it won't, then repeat the value.

A frequently seen mistake is to use ‘`\begin{center}`’ ... ‘`\end{center}`’ inside a figure or table environment. This center environment can cause additional vertical space. If you want to avoid that just use ‘`\centering`’



Table 3.1 A badly formatted table

	Species I		Species II	
Dental measurement	mean	SD	mean	SD
I1MD	6.23	0.91	5.2	0.7
I1LL	7.48	0.56	8.7	0.71
I2MD	3.99	0.63	4.22	0.54
I2LL	6.81	0.02	6.66	0.01
CMD	13.47	0.09	10.55	0.05
CBL	11.88	0.05	13.11	0.04

Table 3.2 A nice looking table

Dental measurement	Species I		Species II	
	mean	SD	mean	SD
I1MD	6.23	0.91	5.2	0.7
I1LL	7.48	0.56	8.7	0.71
I2MD	3.99	0.63	4.22	0.54
I2LL	6.81	0.02	6.66	0.01
CMD	13.47	0.09	10.55	0.05
CBL	11.88	0.05	13.11	0.04

Table 3.3 Even better looking table using booktabs

Dental measurement	Species I		Species II	
	mean	SD	mean	SD
I1MD	6.23	0.91	5.2	0.7
I1LL	7.48	0.56	8.7	0.71
I2MD	3.99	0.63	4.22	0.54
I2LL	6.81	0.02	6.66	0.01
CMD	13.47	0.09	10.55	0.05
CBL	11.88	0.05	13.11	0.04



# References

- [1] Ancey, C., Coussot, P., and Evesque, P. (1996). Examination of the possibility of a fluid-mechanics treatment of dense granular flows. *Mechanics of Cohesive-frictional Materials*, 1(4):385–403.
- [2] Read, C. J. (1985). A solution to the invariant subspace problem on the space  $l_1$ . *Bull. London Math. Soc.*, 17:305–317.



# Appendix A

## How to install L<sup>A</sup>T<sub>E</sub>X

### Windows OS

#### TeXLive package - full version

1. Download the TeXLive ISO (2.2GB) from  
<https://www.tug.org/texlive/>
2. Download WinCDEmu (if you don't have a virtual drive) from  
<http://wincdemu.sysprogs.org/download/>
3. To install Windows CD Emulator follow the instructions at  
<http://wincdemu.sysprogs.org/tutorials/install/>
4. Right click the iso and mount it using the WinCDEmu as shown in  
<http://wincdemu.sysprogs.org/tutorials/mount/>
5. Open your virtual drive and run setup.pl

or

#### Basic MikTeX - T<sub>E</sub>X distribution

1. Download Basic-MiK<sub>T</sub>E<sub>X</sub>(32bit or 64bit) from  
<http://miktex.org/download>
2. Run the installer
3. To add a new package go to Start » All Programs » MikTeX » Maintenance (Admin)  
and choose Package Manager

4. Select or search for packages to install

## **TexStudio - T<sub>E</sub>X editor**

1. Download TexStudio from  
<http://texstudio.sourceforge.net/#downloads>
2. Run the installer

## **Mac OS X**

### **MacTeX - T<sub>E</sub>X distribution**

1. Download the file from  
<https://www.tug.org/mactex/>
2. Extract and double click to run the installer. It does the entire configuration, sit back and relax.

### **TexStudio - T<sub>E</sub>X editor**

1. Download TexStudio from  
<http://texstudio.sourceforge.net/#downloads>
2. Extract and Start

## **Unix/Linux**

### **TeXLive - T<sub>E</sub>X distribution**

#### **Getting the distribution:**

1. TeXLive can be downloaded from  
<http://www.tug.org/texlive/acquire-netinstall.html>.
2. TeXLive is provided by most operating system you can use (rpm,apt-get or yum) to get TeXLive distributions

## Installation

1. Mount the ISO file in the mnt directory

```
mount -t iso9660 -o ro,loop,noauto /your/texlive####.iso /mnt
```

2. Install wget on your OS (use rpm, apt-get or yum install)
3. Run the installer script install-tl.

```
cd /your/download/directory
./install-tl
```

4. Enter command 'i' for installation
5. Post-Installation configuration:  
<http://www.tug.org/texlive/doc/texlive-en/texlive-en.html#x1-320003.4.1>
6. Set the path for the directory of TexLive binaries in your .bashrc file

### For 32bit OS

For Bourne-compatible shells such as bash, and using Intel x86 GNU/Linux and a default directory setup as an example, the file to edit might be

```
edit ~/.bashrc file and add following lines
PATH=/usr/local/texlive/2011/bin/i386-linux:$PATH;
export PATH
MANPATH=/usr/local/texlive/2011/texmf/doc/man:$MANPATH;
export MANPATH
INFOPATH=/usr/local/texlive/2011/texmf/doc/info:$INFOPATH;
export INFOPATH
```

### For 64bit OS

```
edit ~/.bashrc file and add following lines
PATH=/usr/local/texlive/2011/bin/x86_64-linux:$PATH;
export PATH
MANPATH=/usr/local/texlive/2011/texmf/doc/man:$MANPATH;
export MANPATH
```

```
INFOPATH=/usr/local/texlive/2011/texmf/doc/info:$INFOPATH;  
export INFOPATH
```

**Fedora/RedHat/CentOS:**

```
sudo yum install texlive  
sudo yum install psutils
```

**SUSE:**

```
sudo zypper install texlive
```

**Debian/Ubuntu:**

```
sudo apt-get install texlive texlive-latex-extra  
sudo apt-get install psutils
```



# Appendix B

## Installing the CUED class file

$\text{\LaTeX}$ .cls files can be accessed system-wide when they are placed in the  $\langle\text{texmf}\rangle/\text{tex}/\text{latex}$  directory, where  $\langle\text{texmf}\rangle$  is the root directory of the user's  $\text{\TeX}$  installation. On systems that have a local  $\text{texmf}$  tree ( $\langle\text{texmflocal}\rangle$ ), which may be named “ $\text{texmf-local}$ ” or “ $\text{localtexmf}$ ”, it may be advisable to install packages in  $\langle\text{texmflocal}\rangle$ , rather than  $\langle\text{texmf}\rangle$  as the contents of the former, unlike that of the latter, are preserved after the  $\text{\LaTeX}$  system is reinstalled and/or upgraded.

It is recommended that the user create a subdirectory  $\langle\text{texmf}\rangle/\text{tex}/\text{latex}/\text{CUED}$  for all CUED related  $\text{\LaTeX}$  class and package files. On some  $\text{\LaTeX}$  systems, the directory look-up tables will need to be refreshed after making additions or deletions to the system files. For  $\text{\TeX}$ Live systems this is accomplished via executing “ $\text{texhash}$ ” as root.  $\text{MikTeX}$  users can run “ $\text{initexmf -u}$ ” to accomplish the same thing.

Users not willing or able to install the files system-wide can install them in their personal directories, but will then have to provide the path (full or relative) in addition to the filename when referring to them in  $\text{\LaTeX}$ .

