

Contents

1	Aliases	2
1.1	Alias Commands	2
1.2	Helpful Aliases	2
1.2.1	Git	2
1.2.2	Server	2
2	Servers	2
2.1	Connecting to Servers	2
2.2	Moving Files	2
2.3	Running processes in background	3
2.3.1	Screens	3
2.3.2	tmux	3

1 Aliases

1.1 Alias Commands

- `alias` - Can call at any point to see a list of available Aliases
- `~/.zshrc` - Location of aliases

1.2 Helpful Aliases

1.2.1 Git

- `alias gs='git status'`
- `alias ga='git add .'`
- `alias gc='git commit .'`
- `alias gp='git push'`
- `alias gr='git pull'`

1.2.2 Server

Tip: anytime I need to run something on the server, I put the code/resources in a local folder called 'server_package', always stored in the same spot. That way I can run the aliases below to easily load those files into the server, and easily pull them back locally afterwards.

- `server() {ssh USERNAME@stat-$1.byu.edu}` - type `server g02` to join the g02 server
- `pull_server_package() {scp -r USERNAME@stat-$1.byu.edu:server_package FILE_PATH}`
 - Type `pull_server_package g02` to retrieve the 'server_package' folder from server g02
- `push_server_package() {scp -r FILE_PATH USERNAME@stat-$1.byu.edu:}`
 - Type `push_server_package g02` to send the 'server_package' folder to server g02

2 Servers

2.1 Connecting to Servers

`ssh USERNAME@stat-g01.byu.edu` - Full line for connecting to the server (just replace the number with the corresponding server number, and USERNAME with your username)

2.2 Moving Files

Move file from local machine to server: `scp FILE_PATH USERNAME@stat-g02.byu.edu:FILE_PATH`

Move file from server to local machine: `scp USERNAME@stat-g02.byu.edu:FILE_PATH FILE_PATH`

To move a full directory, include the recursive `-r`. Example: `scp -r rjcass13@...`

2.3 Running processes in background

2.3.1 Screens

Running a program in a screen allows it to run in the background even when you disconnect from the server

1. Login to the server
2. Start a screen session: `screen -S my_session_name`
3. Navigate to and run the desired program
4. Detach from the screen session: On a Mac: CTRL+A (nothing should change), then D (if it worked it will take you back to the original SSH session and say detached)
5. To rejoin the session, while logged in to the server, do: `screen -r my_session_name`. If you forgot what the session is called, do `screen -ls` to see all session names.
6. To end the screen session (completely kill it, no coming back), just enter `exit`. If the session is frozen and the previous method doesn't work, you can use `screen -d my_session_name` in the main SSH session.

2.3.2 tmux

Very similar to screen, running a program in a tmux allows it to run in the background even when you disconnect from the server. May not be included on all servers.

1. Login to the server
2. Start a screen session: `tmux new -s my_session_name`
3. Navigate to and run the desired program
4. Detach from the screen session: On a Mac: CTRL+B (nothing should change), then D (if it worked it will take you back to the original SSH session and say detached)
5. To rejoin the session, while logged in to the server, do: `tmux attach -t my_session`. If you forgot what the session is called, do `tmux ls` to see all tmux sessions names.
6. To end the screen session (completely kill it, no coming back), just enter `exit`. If the session is frozen and the previous method doesn't work, you can use `tmux kill-session -t session_name` in the main SSH session.