

(Inglês (EN))

## DoP n.º: GPBL001.1

## **Declaration of Performance**



4. Adress:

Zona Industrial de Aveiro - Ap. 3002 3801- 101 Aveiro - Portugal

Telefone: + 351 234 303 030 Fax: +351 234 303 031

email: bloom@grespanaria.pt

- 1. Product identification: Dry-Pressed Ceramic Tiles, with low water absorption (Eb  $\leq$  0.5 %)
- 2. Product Type: Porcelain glazed
- 3. Intended use: Floor tiles for indoors and/or outdoors  ${\mathfrak D}$  and wall tiles for indoors and/or outdoors  ${\mathfrak D}$
- Name and contact address of the authorised representative: N.A.
- 6. System of Assessment and verification of constancy of performance:4
- Notified Body: N.A.

www.dropbox.com/sh/gw35zk1eqesb0nx/ga\_jnPnnvP 8. European Technical Assessment: N.A.

www.dropbox.com/sh/gwoszkredesbon/yga_ni nin/ 6. European Technical Assessment. 14.44.			
9. Characteristics		Harmonized standard:	Performance
a) Reaction to Fire			Class A <sub>Ifl</sub> ①/A <sub>1</sub> ② Without Testing (Decision 96/603/EC)
<b>b)</b> Emission of Dangerous	Release of lead (*)		NPD
Substances	Release of cadmium(*)	,	NPD
c1) Modulus of Rupture		1	≥ 35N/mm²
c2) Breaking Strength			≥ 700N
d) Slipperiness (*)			NPD
e) Bond Strength/Adhesion	Cementitious Adhesives	EN 14411:2012	>2,0 N/mm²
	Dispersion Adhesives		>0,6 N/mm²
	Reaction resin adhesives		>18,4 N/mm²
	Mortar		NPD
f) Thermal Shock resistance		!	Pass
g) Durability for:	Internal Use		Pass
	external use: Freeze-thaw resistance		Pass
NPD - No Performance Determined			

N.A. - Not Applicable

 $(\ast)$  – If necessary, for further information please contact Gres Panaria Portugal

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Administrator Date

01-Jul-2013

(Marco Mussini)

lumm / lower



