

An Offline Delegatable Cryptocurrency System

Rujia Li^{1,2}, [Qin Wang](#)^{3,4}, Xinrui Zhang⁵,
Qi Wang¹, David Galindo², Yang Xiang³

1 Southern University of Science and Technology, Shenzhen, China

2 University of Birmingham, Birmingham, United Kingdom

3 Swinburne University of Technology, Melbourne, Australia

4 CSIRO Data61, Sydney, Australia.

5 Nankai University, Tianjin, China

May 2021

Cryptocurrency System




- Cryptocurrencies facilitate the convenience of payment.
- Online processing of transactions confronts the problems of **low performance** and **high congestion**.

Cryptocurrency Delegation

- Delegation enables users to exchange the coin *without* having to connect to an online blockchain platform.
- Delegation confronts risks caused by **unreliable participants**.
- The misbehaviours may easily happen due to *the absence of effective supervision*.



Delegation Example




- **Coin-Transfer.** Alex asks for Bob's BTC address, and then *transfers a specific amount of coins* to Bob's address.



- **Ownership-Transfer.** Alex directly *gives his own private key to Bob*. Then, Bob can freely spend the coins using such a private key.

Delegation Drawbacks


Coin-Transfer




Coin-transfer requires *a strict consistency (global view)* of the blockchain, which makes it **time-consuming**.

Delegation Drawbacks

Ownership-Transfer.



A malicious coin owner could spend the delegated transaction **before** the delegate uses it.




A malicious delegatee may spend all coins in the address for **other purposes**.

Research Problem

Is it possible to build a secure offline peer-to-peer delegatable system for decentralized cryptocurrencies?

Challenges


Without A Third Party



The coin might be **spent twice** after another successful delegation.


Challenges

With A Third Party



- The approach with a third party is **centralized**.
- The third party faces the threat of being **compromised** or provided with **misleading assure**.


TEEs Background



TEE implementation: *TrustZone[®]*, *SGX[®]*


- Sealing Technology
- Local Attestation.
- Remote Attestation.

Remote Attestation




A remote party can verify whether a piece of code is running in an enclave of the Intel SGX platform.

Our Solution



- The enclaves are as trusted agents between the coin owner and coin delegatee.
- Each coin owner has his own enclave. The agents are **decentralized**.

System Overview




- System Setup
- Coin Deposit
- Coin Delegation
- Coin Spend

The TEEs are as **decentralized** trusted agents.


System Setup

In this phase, the coin owner O and the delegatee D initialize their TEEs to provide environments for the operations with respect to the further delegation.




Coin Deposit

The coin owner O generates an address and its corresponding private key. Afterwards, O sends coins to this address in the form of fund deposits.




Coin Delegation

In this phase, neither O nor D interacts with blockchain. O can instantly complete the coin delegation through offline transactions.




Coin Delegation

If any abort or halt happens, a re-initiated enclave starts to reload the missing information.




Coin Spend

The delegatee decrypts the encrypted transaction, and then spends coins by forwarding the transaction to the blockchain network.



Formal Treatment

- TEEs are treated as black-box programs
- Simulation based approach to capture the security



Security Discussion

- The *private key* of a delegated transaction and the delegated transaction itself *are protected against the public*.
- The spendable amount of delegated coins must be *less than (or equal to)* original coins.
- The delegation *records are securely stored* to guarantee consistency considering accidental TEEs failures or malicious TEEs compromises.

Implementation

- C++
- Intel SGX SDK 1.6
- Ubuntu 20.04.1 LTS
- Bitcoin testnet
- SHA-256, ECDSA
with secp256k1

Implementation codes are available at:

<https://github.com/TEEs-projects/DelegaCoin>


```
http://cloc.sourceforge.net v 1.64 T=0.39 s (70.0 files/s, 17206.3 lines/s)
```

Language	files	blank	comment	code
C++	6	413	607	2211
C/C++ Header	17	300	402	1426
C	2	150	63	754
make	1	57	49	188
XML	1	0	1	11
SUM:	27	920	1122	4590

Evaluation

Phase	Operation	Average Time / ms
<i>System setup</i>	Enclave initiation	13.18940
	Public key generation (Tx)	0.34223
	Private key generation (Tx)	0.01119
<i>Coin deposit</i>	Address creation	0.00690
	Coin deposit	—
<i>Coin delegation</i>	Transaction generation	0.78565
	Remote attestation	19.50990
	State update	0.00366
	State seal	5.43957
<i>Coin spend</i>	Transaction decryption	—
	Transaction confirmation	—

Performance



Disk space

Summary

- Identify the challenge of current decentralized delegation
- Propose an offline delegatable payment solution
- Formally define our protocols with security analysis
- Implement the system with Intel's SGX
- Conduct a series of experiments

References

- Gavin Wood et al. Ethereum: A secure decentralised generalised transaction ledger. In Ethereum Project Yellow Paper, 2014
- Muneeb Ali, Jude Nelson, Ryan Shea, and Michael J Freedman. Blockstack: A global naming and storage system secured by blockchains. In 2016 USENIX Annual Technical Conference (USENIX ATC), pages 181–194, 2016.
- Ben Fisch, Dhinakaran Vinayagamurthy, Dan Boneh, and Sergey Gorbunov. Iron: functional encryption using intel sgx. In Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security (CCS), pages 765–782, 2017.
- Jan-Erik Ekberg, Kari Kostiainen, and N Asokan. Trusted execution environments on mobile devices. In Proceedings of the 2013 ACM SIGSAC conference on Computer and Communications Security (CCS), pages 1497–1498, 2013.
- Dayeol Lee, David Kohlbrenner, Shweta Shinde, Krste Asanovic, and Dawn Song. Keystone: An open framework for architecting trusted execution environments. In Proceedings of the Fifteenth European Conference on Computer Systems (EuroSys), pages 1–16, 2020.
- Sinisa Matetic, Moritz Schneider, Andrew Miller, Ari Juels, and Srdjan Capkun. Delegatee: Brokered delegation using trusted execution environments. In 27th fUSENIXg Security Symposium (USENIX Security), pages 1387–1403, 2018.
- Victor Costan and Srinivas Devadas. Intel sgx explained. IACR Cryptology ePrint Archive, 2016(086):1–118, 2016.
- David Bernhard, Véronique Cortier, David Galindo, Olivier Pereira, and Bogdan Warinschi. SoK: A comprehensive analysis of game-based ballot privacy definitions. In IEEE Symposium on Security and Privacy (SP), pages 499–516. IEEE, 2015.
- Kiffer, Lucianna, Rajmohan Rajaraman, and Abhi Shelat. “A better method to analyze blockchain consistency.” Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security. 2018.
- Bitcoin testnet. In <https://coinfaucet.eu/en/btc-testnet/>, 2020.

Thanks

An Offline Delegatable Cryptocurrency System

Rujia Li^{1,2}, [Qin Wang](#)^{3,4}, Xinrui Zhang⁵,
Qi Wang¹, David Galindo², Yang Xiang³

1 Southern University of Science and Technology, Shenzhen, China

2 University of Birmingham, Birmingham, United Kingdom

3 Swinburne University of Technology, Melbourne, Australia

4 CSIRO Data61, Sydney, Australia.

5 Nankai University, Tianjin, China

May 2021