

Converting LaTeX Legacy R Journal Articles into R Markdown Articles using texor and rebib

by Abhishek Ulayil, Dianne Cook, Heather Turner, Mitchell O'Hara-Wild, and Christophe Dervieux

Abstract In 2021 the R Journal made a change of templates for article writing to R Markdown instead of LaTeX. The reasons were to encourage better reproducibility of articles using dynamic documents, enable interactivity in articles, and to make the articles more accessible for print-disabled readers. A resulting challenge was to explore whether legacy articles might be suitably converted into HTML output. This paper describes the process of converting an R Journal article from LaTeX to HTML format via R Markdown, and the two new R packages, *texor* and *rebib*, that can be used to achieve the conversion.

1 Introduction

The R Journal is the primary open-access outlet for publications produced by the R community. It was started in 2009, evolving from the R News newsletter that ran from 2001, to become a more formal publication that encourages and provides credit for the documentation of statistical computing research.

The tooling behind the production of the R Journal is regularly updated. Early articles were typeset using LaTeX ([The LaTeX Project, 2023](#)), based on a specific, but changing, template. Using LaTeX requires that code is separated from the documentation, and there is a chance that code chunks in the paper don't reproduce the results reported. With the emergence of dynamic document systems such as R Markdown ([Xie et al., 2018](#)), a tight coupling of code and documentation is possible. Code chunks are dynamically executed when the document is typeset using a system like *knitr* ([Xie, 2015](#)), making reporting of computing research more reproducible.

In 2019, with the help of funding from the R Consortium, work began to update operations to adopt an R Markdown template, that would produce both HTML and PDF versions of the paper. In mind, was also to develop, adopt and encourage good standards for R Journal articles.

There are numerous benefits of HTML format:

1. Articles can include interactive graphics (to allow readers to query, re-focus, and watch an animation, for example) and interactive tables (enabling re-sorting in different ways to better digest the information).
2. It is the best format for accessibility ([The Daisy Consortium, 2023](#)). Screen readers and other assistive technologies can deliver the content to print-disabled readers. (See [Byrne-Haber et al. \(2023\)](#) for current guidelines.)
3. HTML provides a more comfortable reading experience on mobile devices, which are increasingly used as researchers work on the move and share work via social media.
4. Search engines can easily access the full text of articles, facilitating the discovery of published articles.

These provide the motivations for converting all of the legacy R Journal articles into HTML.

A key decision when designing the conversion software was whether to convert the LaTeX source to HTML; the PDF output to HTML; or the LaTeX source to R Markdown, which would then be converted to HTML using the current journal tools. The latter approach was decided to be the most versatile and useful. If an article can be converted from LaTeX to R Markdown, it would help authors make the transition to reproducible publishing, beyond

what the R Journal needed. Once an article is in R Markdown format it can be adapted to include the code for dynamic execution.

In addition to the article format, changes to the website structure were important for delivering the publication. Website architectures are also constantly evolving, and the emergence of [distill](#) ([Dervieux et al., 2022](#)) allows the journal website to optimally deliver R Markdown articles.

The [rjtools](#) was developed to create articles using R Markdown for the R Journal and to embed them into the journal website. The packages described here, [texor](#) and [rebib](#), describe software to convert legacy LaTeX format articles into R Markdown, so that they can be rendered in HTML in the new website.

The paper is organised as follows. Section 2 gives an overview of the conversion process, which includes pre-processing using regular expressions, post-processing using Lua filters, and handling of figures, tables and equations. Section 3 describes the [texor](#) package that handles most of the conversion. Section 4 describes tools for special handling of bibliography files. The supplementary materials have folders containing specific examples that can be used for understanding how the conversions are done.

2 The internals of converting from LaTeX to R Markdown

The decision to convert to R Markdown format means that the final output to PDF and HTML will depend on Pandoc ([MacFarlane et al., 2023](#)). Pandoc is a versatile document conversion program written in Haskell that is core to numerous documentation systems, including R Markdown and Quarto. Pandoc first converts a document into an abstract syntax tree. From this, it can convert to a different format, including custom ones.

Pandoc can be used to do the conversion from LaTeX to R Markdown also. However, some pre-processing is necessary to handle special R Journal LaTeX styling. And further post-processing is necessary to handle specific R Journal R Markdown styling. The [texor](#) package contains functionality to handle this pre- and post-processing of the document, in a workflow illustrated in [Figure 1](#).

2.1 Pre-processing using regular expressions

LaTeX is a very descriptive language, that allows authors substantial freedom for customization. Markdown ([Gruber, 2002](#)), on which R Markdown is based, is more restrictive and was designed to make it easier to create web pages without the distraction of a gazillion HTML tags. The beauty of Markdown is that it allows the author to focus on writing, without format cluttering the text. The drawback is that it is simple typesetting, optimized for web delivery.

While Pandoc can do most of the heavy lifting, it cannot cope with all the freedom with which LaTeX documents are written. An example of this is with formatting of code. Pandoc only handles the `verbatim` environment, but there are many ways to format code in LaTeX, and the R Journal template has a special `\code{}` command. If the code environment is not `verbatim`, then Pandoc will also try to process the actual code content as LaTeX commands and will likely lose details. It is better to convert these synonyms into `verbatim` environments prior to passing the document to Pandoc.

The functions in [texor](#) that handle the pre-processing using regular expressions are:

- `stream_editor()`: operates like the `sed` function in unix ([Ritchie and Thompson, 1978](#)) and allows generic text pattern matching and replacement.
- `patch_code_env()`: replaces the common code environments, `code`, `example`, `Sin`, `Sout`, `Scode`, `Sinput`, `smallverbatim`, `boxedverbatim`, `smallexample` with `verbatim`.
- `patch_equations()`: handles various equation environments.
- `patch_figure_env()`: handles various figure environments.
- `patch_table_env()`: handles various table environments.




Figure 1: Workflow of the document conversion conducted by texor. (Note: AST is pandoc’s abstract syntax tree.)

These functions are verbose and describe all the changes being made. They also create a backup of the original file before making the changes.

2.2 Post-processing using Lua filters

Lua (Ierusalimschy et al., 1996) is a programming language, that is lightweight and fast: ideal for procedural operations. It is embedded in many other applications to allow custom scripting for extensibility. Pandoc allows users to provide custom Lua filters to produce custom output formats. The `texor` package handles the post-processing of the R Markdown document into the special format for the R Journal using a suite of Lua filters.

Here is an example of a Lua filter available in `texor`:

```
function Div(el)
  if el.classes[1] == 'thebibliography' then
    return { }
  end
end
```

This filter reads the abstract syntax tree, selecting all the Div elements. Then it looks for the class “thebibliography.” This Div element contains the LaTeX bibliographic records, that appear at the very end of papers. It should not be in the document when using the “RJ-web-article” layout, because it is added from meta-data when the R Markdown is knitted. So the Lua filter removes this section.

2.3 Figures

Standard, single figure

Figure definitions in LaTeX are many and varied! The standard, single-figure definition with the figure environment and raster image format such as PNG or JPG, is handled by Pandoc. It will convert:

```
\begin{figure}[htbp]
  \centering
  \includegraphics[width=0.35\textwidth]{Rlogo-5.png}
  \caption{The logo of R.}
  \label{figure:rlogo}
\end{figure}
```

to

```
<figure id="figure:rlogo">

<figcaption>Figure 1: The logo of R.</figcaption>
</figure>
```

PDF format images

Images in PDF format are converted to PNG, in the pre-processing of the LaTeX document, and then post-processed using Pandoc as described above.

Multiple figures

Multiple figures are supported with the latest versions of Pandoc, so definitions like:

```
\begin{figure*}[htbp]
  \centering
  \includegraphics[width=0.45\textwidth]{Rlogo-5.png}
  \includegraphics[width=0.45\textwidth]{normal}
  \caption{Images side by side}
  \label{fig:twoimages}
\end{figure*}
```

will be converted to:

```
<figure id="fig:twoimages">
<p></p>
<figcaption>Figure 3: Images side by side</figcaption>
</figure>
```

tikz format images

Some legacy articles define images using tikz commands, such as:

```
\begin{figure}

%% Generated Image will included as a PNG above automatically
  \centering
  \tikzstyle{process} = [rectangle, rounded corners,
minimum width=3cm,
minimum height=1cm,
text centered,
draw=black]
  \tikzstyle{arrow} = [thick,->,>=stealth]
  \begin{tikzpicture}[node distance=4cm]
  %Nodes
  ...
```

This is handled by pre-processing the LaTeX to create the image, as both PDF, and then PNG, for inclusion in the R Markdown document using:

```
<figure id="fig:tikz">


<figcaption>Figure 5: Tikz Image example</figcaption>
</figure>
```

Algorithm2e graphics as figures

Algorithm2e graphics using the algorithm2e package in LaTeX are supported, and the following description will yield the result in Figure 2.

```
\begin{algorithm}[htbp]
\SetAlgoLined
\KwData{this text}
\KwResult{how to write algorithm with \LaTeX2e }
initialization\;
\While{not at end of this document}{
read current\;
\If{understand}{
```

```

Data: this text
Result: how to write algorithm with LATEX2e
initialization;
while not at end of this document do
  read current;
  if understand then
    go to next section;
    current section becomes this one;
  else
    go back to the beginning of current section;
  end
end

```

Figure 2: How to write algorithms.

```

go to next section\;
current section becomes this one\;
}{
go back to the beginning of current section\;
}
}
\caption{How to write algorithms}
\label{alg:how}
\end{algorithm}

<figure id="alg:how">


<figcaption>Algorithm 1: How to write algorithms</figcaption>
</figure>

```

2.4 Equations

Math is handled primarily by Pandoc. The inline math and equation descriptions are unchanged between LaTeX and R Markdown.

The HTML output renders math using MathJax. This does mean that some functionality, like `\bm`, `\boldmath` and `\mathbbm` are not supported, and special definitions can only be handled in a limited capacity.

The numbering of equations is a bit trickier. LaTeX automatically numbers equations, unless specifically instructed not to. Equation numbering in R Markdown requires specific labeling using `(\#eq:xx)` as described in Xie (2023). The `texor` helps by adding the labeling using a Lua filter to convert the existing `\label{. . }` to `(\#eq:xx)`.

2.5 Tables

Tables form one of the biggest challenges in migrating from LaTeX to R Markdown, because the sophistication is not completely replicated. However, there have been many improvements in table definitions for R Markdown that are increasingly producing the beautifully crafted tables possible in LaTeX. The conversion in `texor` can mostly handle the simple tables, and for producing more complex tables it may be necessary to manually edit the resulting Rmd file to make conditional tables, one to render specifically for HTML output using packages such as `kableExtra` (Zhu, 2021), `gt` (Iannone et al., 2023), `htmlTable` (Gordon et al., 2022), `tableHTML` (Boutaris et al., 2023), `tables` (Murdoch, 2023) or `DT` (Xie et al., 2023). A benefit of using conditional markup is that it can take advantage of HTML-specific features, such as sortable columns or paged tables.

Generic tables

Simple LaTeX tables are converted into traditional markdown format tables by Pandoc. So this table definition:

```
\begin{table}[htbp]
\centering
\begin{tabular}{l | llll }
\hline
Graphics Format & LaTeX & Markdown & Rmarkdown & HTML \\
\hline
PNG & Yes & Yes & Yes & Yes \\
JPG & Yes & Yes & Yes & Yes \\
PDF & Yes & No & No & No \\
SVG & No & Yes & Yes & Yes \\
Tikz & Yes & No & Yes & No \\
Algorithm & Yes & No & No & No \\
\hline
\end{tabular}
\caption{Image Format support in various Markup/Typesetting Languages}
\label{table:1}
\end{table}
```

will be converted to:

```
::: {#table:1}
```

Graphics Format	LaTeX	Markdown	Rmarkdown	HTML
PNG	Yes	Yes	Yes	Yes
JPG	Yes	Yes	Yes	Yes
PDF	Yes	No	No	No
SVG	No	Yes	Yes	Yes
Tikz	Yes	No	Yes	No
Algorithm	Yes	No	No	No

```
: Table 1: Image Format support in various Markup/Typesetting
Languages
```

```
:::
```

Multicolumn tables

A multicolumn table requires:

1. The stream editor modifies the `\multicolumn{..}` to `\multicolumnx{..}`.
2. A LaTeX macro is used to redefine the `\multicolumnx{..}` to `\multicolumn{---}` (which is accepted by pandoc).
3. Pandoc reads the table and transforms it to markdown.

EXAMPLE	X		Y	
	1	2	1	2
EX1	X11	X12	Y11	Y12
EX2	X21	X22	Y21	Y22
EX3	X31	X32	Y31	Y32
EX4	X41	X42	Y41	Y42
EX5	X51	X52	Y51	Y52

Table 1: An example multicolumn table.

Also note that the stream editor is used to rename `table*` environment to `table` environment because the HTML format is single column, so the asterisk indicating that the table should be drawn over the full width of the page is redundant in this case.

Other tables

Tables with images, math, code or links in the cells are generally handled. Also `widetable` tables that allow for specific width or wrapping of tables into blocks are also partially handled.

3 Using `texor`

The package `texor` can be installed from CRAN and the development version from <https://github.com/Abhi-1U/texor>. The website for the package, <https://abhi-1u.github.io/texor>, has vignettes documenting usage.

Note that you will need to use **Pandoc Version > 3.0.0 (if possible latest)** for the best results. You can check your version with:

```
rmarkdown::pandoc_version()
```

The only function that a user will typically require is `latex_to_web()`. This creates the R Journal style R Markdown file from a given R Journal style LaTeX file. This is achieved by several sequential steps: `convert_to_markdown()`, `generate_rmd()`, and `produce_html()`.

For converting the 14 years of legacy R Journal articles, batch processing of issues was conducted.

For individuals who are interested in submitting their paper to the R Journal but have written their article using the legacy LaTeX format and wish to convert it to the current R Markdown format, you can use the `latex_to_web()` function on your paper directory. This will get you about 80% of the way to an R Markdown version of your paper. You will then want to:

- Edit the lines where figures are included. The conversion will create HTML code to define the image. This should be changed into Markdown description `![Caption](Image)` or using `knitr::include_graphic(Image)` in an R code chunk, in order for both HTML and PDF versions of the paper to be created when the `rjtools` article template is knitted.
- Edit the tables for aesthetics. The conversion will create Markdown tables, which will convert appropriately to HTML and PDF. However, to have more control and to create more elegant tables using `knitr::kable` provides a finer level of control.
- Include your R code to dynamically do the computing described in your article. If any code block is time-consuming to complete, saving intermediate output, or caching would be recommended.

4 Managing the bibliography using **rebib**

Typically bibliographies are generated during the processing of a LaTeX article using the BibTeX software (Feder, 2006) operating on a .bib list of references. The current R Journal template requires the inclusion of the .bib file. But LaTeX actually uses a .bbl format for references, which is what BibTeX generates as an intermediate format during the article processing.

The instructions for R Journal authors have changed over time. Initially, authors were instructed to run BibTeX on their article and to include the .bbl formatted references directly in the .tex file. This was to avoid clashes in citation keys between multiple articles in an issue. Later on, authors were instructed to provide a .bib file instead. During the conversion of legacy articles, it was discovered that some papers had references in both the .tex file and in separate .bbl or .bib files. Usually, the different files were equivalent, but sometimes references were only found in one source and in some cases the files contained conflicting information! While LaTeX can technically handle either .bbl or .bib formatted references, R Markdown can only handle .bib.

The **rebib** package was developed to handle these tricky situations. It converts embedded LaTeX bibliographies into a close BibTeX equivalent. The features of the package are:

- extracting embedded bibliographic entries from a .tex file;
- creating the mandatory title and author fields;
- creating the optional URL, ISBN, publisher, pages and year fields, when available;
- storing remaining information in "journal" (internally) and "publisher" (when writing BibTeX file);
- ignoring commented LaTeX code;
- tracking citations included in the document, and
- aggregating references from embedded bibliographic entries with references from supplementary .bbl and .bib files.

The package **rebib** can be installed from CRAN and the development version from <https://github.com/Abhi-1U/rebib>. The website for the package, <https://abhi-1u.github.io/rebib>, has vignettes documenting usage.

5 The process of converting all the legacy articles

The R Journal has been operating since 2009 and has published 682 articles through 2022 in addition to numerous editorials and news items. These LaTeX articles are the main focus of the conversions made with **texor** and **rebib**.

5.1 Batch processing

The code is designed to process all the articles in an issue at a time, by operating on all the files in the directory housing the issue. Each processing function, from pre-processing the text in the LaTeX file to post-processing accepts a directory name as the argument. Generally, if a problem is encountered with one article, the processing will skip to the next. The vignette [Introduction to texor](#) provides more details.

5.2 Known problems requiring manual fixes

The problems encountered with some articles are many and varied, and include:

- The table format is often not as neat in the HTML as in the LaTeX. It can be made close to the original with extra effort in the R Markdown description.
- Some of the figure files are missing - so the figure may need to be extracted from the pdf file and included with `knitr::include_graphics()`.

- Figures and equations may need some resizing. Sometimes the figure or equation might extend outside the text region in the HTML, which can be fixed by specifying the preferred size, or breaks in the equation lines.
- Alignment in multi-line equations may need adjusting.
- Alignment of columns in a table may not be the same as the original, for example, the text might be center-aligned, instead of the original left-aligned.
- Specialty LaTeX definitions included by an author for their article may not be recognized by Pandoc, leaving the original command as is, in the article.

5.3 Plan for release

The HTML versions of all successfully converted legacy articles will be on the [R Journal website](#) late in 2023. The final step in the integration requires the R Markdown file to be knitted in place to capture the metadata for each article.

5.4 Reporting problems

As a consequence of this project, the journal website has been furnished with an additional link titled “CONTRIBUTE”. Visiting this link will give you details on how to report a problem with an article that you are reading, or even to make a suggestion on improving operations.

6 Summary

The original motivation for the [texor](#) and [rebib](#) packages was to convert legacy LaTeX articles into HTML format for accessibility. Thus it only creates an .Rmd (R Markdown) file which is used to produce only an HTML version. The original PDF remains as published. The goal is to use the packages for future articles where the authors have chosen to submit only in the legacy LaTeX template.

However, the software can also be used by authors themselves to convert to dynamic documents, by providing an initial R Markdown version of their LaTeX, that with some modification, such as including their R code for computations directly in the document, will produce both PDF and HTML versions of their submitted paper.

Adopting the new R Markdown template also provides better standards for R Journal articles. It encourages authors to be more conscious that their work is reproducible. There is more standardization of file names and file structure, and this helps the editors and reviewers check papers. This in turn makes it easier to build the issues, eliminating some common errors that authors make that cause compilation failure.

There are many benefits of providing good standards, though, and an important one is that this can have positive spillover effects for the R community. Authors can become more aware of good practice. For example, one of the useful elements when an article is in HTML format is that figures can be made richer with an alt-text (alternative text) element. In an R Markdown code chunk generating a figure, this can be set using `fig.alt`. Alt-text provides a textual alternative to non-text content in HTML documents, and serves various purposes: screen readers can deliver the content to print-disabled people, it is displayed in place of the image if it fails to load, and can serve to assist search engines. It is a work in progress: to encourage adoption by authors of new article submissions, and it would be useful to edit into the converted legacy articles at a later date.

There are many other journals that have a similar backlog of legacy articles. A current and ongoing project is being conducted by [arXiv Accessibility Project \(2023\)](#) to convert their collection of articles from LaTeX (shared as PDF) to HTML, utilizing LaTeXML ([Miller and Ginev, 2023](#)). The work conducted for the R Journal might be of interest to similarly small journals that operate without paid staff. Converting legacy articles provides accessibility to a wealth of educational material.

After the change was made to use R Markdown, a new development for the open-source scientific and technical publishing community has emerged: `quarto` (Allaire et al., 2024). Although R Markdown would suggest a focus on R, it was always possible to include code chunks written in other languages. But Quarto makes this cleaner, and thus more appealing for non-R developers. It also provides a cleaner typesetting. At some point, the R Journal will likely shift to a Quarto template, which is reasonably straightforward, but for the present R Markdown is a suitable dynamic document delivery system for the R Journal.

Acknowledgments

The authors wish to thank the [Google Summer of Code](#) program for financially supporting Abhishek Ulayil's work on this project, and the R Project organization for their support. Heather Turner was supported by the Engineering and Physical Sciences Research Council [EPSRC EP/V052128/1] during this project. Also in the initial stages of the development, Zola Batsaikhan carefully checked the conversion of articles, listing and fixing the problems after the conversion. This helped to refine the software to catch these problems and fix in the automatic conversion.

Supplementary materials

The supplementary materials has example folders containing LaTeX documents that allow the reader to see how different common patterns in the legacy documents are handled with the conversion. These include:

- `code-env`: Explains how different code environments defined by the R Journal style are handled, and additional details such as code in figure environments, and code in table environments.
- `math-env`: Examples of inline math, display math, and how equation numbering is handled by a Lua filter to convert from LaTeX labeling to R Markdown labeling.
- `figure-env`: Explains how the variety of figure definitions are handled in the conversion, including different image formats, numbering, captions, labeling, multiple images, and `tikz` images with an example adapted from (Cassidy, 2013).
- `table-env`: Examples of how a variety of table types are converted, including multi-column, complex and wide tables.
- `lua-filters`: Overview and lots of small examples of Lua filters to handle the custom output needed for the R Markdown format.
- `metadata`: This has a collection of additional format handling including extracting metadata like author names and affiliations, article identifiers used in the review process, and handling citations, footnotes and links.
- `bibliography`: The bibliography was handled differently over the years of the journal, and this details how to use the `rebib` functionality to handle `bb1` files, embedded `bb1`, to convert into the standard `.bib` format.

In each of these folders there is a `RJwrapper.tex`, and `.tex` file, with the extra template files `RJournal.sty` and `Rlogo-5.png` and `.bib` files. These match the legacy template file structure, from which the `RJwrapper.pdf` file is created. To test the conversion for each of these examples, set the path directory to one of the folders and use the `latex_to_web()` function as follows:

```
article_dir <- "path-to-this supplementary folder"
texor::latex_to_web(article_dir)
```

This will create an `.Rmd` and `.html` files in the same directory, that demonstrate the converted R Markdown version and the HTML output format.

You'll need to ensure that you have the latest versions of [texor](#) and [rebib](#), and Pandoc (at least later than version 3.0.0).

Source materials

The **texor** and **rebib** source code and materials to reproduce this paper are available at:

- **texor**: Version 1.3.0 <https://abhi-1u.github.io/texor>
- **rebib**: Version 0.3.2 <https://abhi-1u.github.io/rebib/>
- This paper: <https://github.com/Abhi-1U/texor-rjarticle>
- More details on **rjtools** are at <https://rjournal.github.io/rjtools/>

References

- J. Allaire, C. Teague, C. Scheidegger, Y. Xie, C. Dervieux, and G. Woodhull. Quarto, Nov. 2024. URL <https://github.com/quarto-dev/quarto-cli>. [p40]
- arXiv Accessibility Project. HTML as an accessible format for papers, 2023. URL https://info.arxiv.org/about/accessible_HTML.html. [p39]
- T. Boutaris, C. Zauchner, and D. Jomar. *tableHTML: A Tool to Create HTML Tables*, 2023. URL <https://CRAN.R-project.org/package=tableHTML>. R package version 2.1.2. [p35]
- S. Byrne-Haber, D. Fazio, C. LaPierre, and J. Sajka. W3C accessibility maturity model, 2023. URL <https://www.w3.org/TR/maturity-model/>. [p30]
- J. Cassidy. *LaTeX Graphics using TikZ: A Tutorial for Beginners (Part 3)—Creating Flowcharts*. Overleaf tutorials, 2013. URL <https://www.overleaf.com/learn/latex/>. [p40]
- C. Dervieux, J. Allaire, R. Iannone, A. P. Hill, and Y. Xie. *distill: ‘R Markdown’ Format for Scientific and Technical Writing*, 2022. URL <https://CRAN.R-project.org/package=distill>. R package version 1.5. [p31]
- A. Feder. BibTeX: Reference management software. <https://www.bibtex.org>, 2006. [p38]
- M. Gordon, S. Gragg, and P. Konings. *htmlTable: Advanced Tables for Markdown/HTML*, 2022. URL <https://CRAN.R-project.org/package=htmlTable>. R package version 2.4.1. [p35]
- J. Gruber. Markdown. <https://daringfireball.net/projects/markdown/>, 2002. [p31]
- R. Iannone, J. Cheng, B. Schloerke, E. Hughes, A. Lauer, and J. Seo. *gt: Easily Create Presentation-Ready Display Tables*, 2023. URL <https://CRAN.R-project.org/package=gt>. R package version 0.9.0. [p35]
- R. Ierusalimsky, L. H. de Figueiredo, and W. C. Filho. Lua—an extensible extension language. *Software: Practice and Experience*, 26(6):635–652, 1996. [p33]
- J. MacFarlane, A. Krewinkel, and J. Rosenthal. Pandoc. <https://github.com/jgm/pandoc>, 2023. [p31]
- B. Miller and D. Ginev. LaTeXXML: A LaTeX to XML/HTML/MathML converter, 2023. URL <https://math.nist.gov/~BMiller/LaTeXXML/>. [p39]
- D. Murdoch. *tables: Formula-Driven Table Generation*, 2023. URL <https://CRAN.R-project.org/package=tables>. R package version 0.9.17. [p35]
- O. M. Ritchie and K. Thompson. The UNIX time-sharing system. *The Bell System Technical Journal*, 57(6):1905–1929, 1978. doi: 10.1002/j.1538-7305.1978.tb02136.x. [p31]
- The Daisy Consortium. Creating the best way to read and publish, 2023. URL <https://daisy.org>. [p30]
- The LaTeX Project. LaTeX – a document preparation system. <https://www.latex-project.org>, 2023. [p30]

- Y. Xie. *Dynamic Documents with R and knitr*. Chapman and Hall/CRC, Boca Raton, Florida, 2nd edition, 2015. URL <https://yihui.org/knitr/>. ISBN 978-1498716963. [p30]
- Y. Xie. *bookdown: Authoring Books and Technical Documents with R Markdown*. Chapman and Hall/CRC, Boca Raton, Florida, 2023. URL <https://bookdown.org/yihui/bookdown/markdown-extensions-by-bookdown.html>. [p35]
- Y. Xie, J. Allaire, and G. Golemund. *R Markdown: The Definitive Guide*. Chapman and Hall/CRC, Boca Raton, Florida, 2018. ISBN 9781138359338. URL <https://bookdown.org/yihui/rmarkdown>. [p30]
- Y. Xie, J. Cheng, and X. Tan. *DT: A Wrapper of the JavaScript Library 'DataTables'*, 2023. URL <https://CRAN.R-project.org/package=DT>. R package version 0.28. [p35]
- H. Zhu. *kableExtra: Construct Complex Table with 'kable' and Pipe Syntax*, 2021. URL <https://CRAN.R-project.org/package=kableExtra>. R package version 1.3.4. [p35]

Abhishek Ulayil
Institute of Actuaries of India (student)
Mumbai, India
ORCID: 0009-0000-6935-8690
abhishek.ulayil.m@gmail.com

Dianne Cook
Monash University
Melbourne, Australia
ORCID: 0000-0002-3813-7155
dicook@monash.edu

Heather Turner
University of Warwick
Coventry, United Kingdom
ORCID: 0000-0002-1256-3375
ht@heatherturner.net

Mitchell O'Hara-Wild
Monash University
Melbourne, Australia
ORCID: 0000-0001-6729-7695
mail@mitchelloharawild.com

Christophe Dervieux
Posit PBC
Paris, France
ORCID: 0000-0003-4474-2498
christophe.dervieux@gmail.com