

Cryptography – Homework 3


Discussed on Wednesday, 28th of November, 2018.

Exercise 3.1

Let F be a PRP.

- (a) Show that F -rCBC is not CCA-secure.
- (b) Show that F -CBC-CIV (with chained IV—see lecture slides) is *not* CPA-secure.

Exercise 3.2



Let $f : \{0, 1\}^* \rightarrow \{0, 1\}^*$ be some function s.t. $|f(x)| = |x|$ for all $x \in \{0, 1\}^*$. A *single-round Feistel network* FN_f is defined by

$$\text{FN}_f(x||y) := y||x \oplus f(y) \text{ for all } x, y \in \{0, 1\}^* \text{ with } |x| = |y|.$$

Similarly, given functions f_1, \dots, f_j a *j-round Feistel network* is inductively defined by

$$\text{FN}_{f_1, f_2, \dots, f_j}(x||y) := \text{FN}_{f_j}(\text{FN}_{f_1, f_2, \dots, f_{j-1}}(x||y))$$

- (a) Show that independent of the choice of f_1, \dots, f_j the function $\text{FN}_{f_1, \dots, f_j}$ is invertible if f_1, \dots, f_j are known.
- (b) Let F be a PRF of key and block length n and $P_{k_1, k_2}(x||y) := \text{FN}_{F_{k_1}, F_{k_2}}(x||y)$ be a two-round Feistel network using F .
 - i) Compute $P_{k_1, k_2}(0^n||y)$ and $P_{k_1, k_2}(F_{k_1}(0^n) \oplus z||0^n)$.
 - ii) Show that PPT-Eve can compute P_{k_1, k_2}^{-1} when given oracle access to P_{k_1, k_2} .
- (c) Is $\text{FN}_{F_{k_1}, F_{k_2}, F_{k_3}}$ with three independent keys $k_1, k_2, k_3 \stackrel{u}{\in} \{0, 1\}^n$ a PRP? Is it a PRF? (y/n)

Exercise 3.3 **MAC or no MAC?**

- (a) Does rOFB mode yield a secure MAC?
- (b) Show that if the IV in the CBC-MAC-Algorithm is not fixed (but chosen randomly and pre-pended to the CBC-output), the MAC becomes insecure.

Exercise 3.4 **MACs using hash-functions done wrong**

Before NMAC and HMAC, several ad-hoc solutions for constructing MACs were used. For instance, given a (hash) function $H : \{0, 1\}^* \rightarrow \{0, 1\}^l$, the tag was defined to be $\text{Mac}_k(m) := H(k||m)$, i.e. the outer encryption used in NMAC and HMAC is missing.

Assume a PRF F with (for simplicity) $n = l_{\text{in}}(n) = l_{\text{out}}(n)$. Using the padding function $\text{pad}(m) := m||10^p||\lfloor |m| \rfloor$, set $\text{Mac}_k(m) := H(k||m) := F_k^*(\text{pad}(m))$ for $k \in \{0, 1\}^n$.

Show that $\text{Mac}_k(m)$ is not secure.

Hint: Recall that the outer encryption used by NMAC and HMAC is to restrict the adversary to prefix-free queries.

Exercise 3.5

Let F be some secure block cipher with key and block length n (think of AES-128).

Consider the following deterministic MAC:

- **Gen**: as usual, in input 1^n , output $k \xleftarrow{u} \{0,1\}^n$.

- **Mac**: given $m \in \{0,1\}^+$ and k ,

first pad m to a multiple of n by appending a minimal number of 0,

then break the padded message into n -bit blocks $m^{(i)}$.

Starting with $k^{(0)} := 0^n$, compute $k^{(i)} = F_{k^{(i-1)}}(m^{(i)})$ for i from 1 to d where $d = \frac{|m|}{n}$.

Finally, output $t := F_{k^{(d)}}(k)$.

(Draw a picture! Note that the key is appended in this case.)

- **Vrf**: given m , t , and k , check that $\text{Mac}_k(m) = t$.

Is this MAC secure?