

# Concrete Semantics

with Isabelle/HOL

Peter Lammich (slides adopted from Tobias Nipkow)

Fakultät für Informatik  
Technische Universität München

2018-12-16

# Part II

## Semantics

# Chapter 7

IMP:

A Simple Imperative Language

- ① IMP Commands
- ② Big-Step Semantics
- ③ Small-Step Semantics

① IMP Commands

② Big-Step Semantics

③ Small-Step Semantics

# Terminology

**Statement:** declaration of fact or claim

# Terminology

**Statement:** declaration of fact or claim

*Semantics is easy.*

# Terminology

**Statement:** declaration of fact or claim

*Semantics is easy.*

**Command:** order to do something



# Terminology

**Statement:** declaration of fact or claim

*Semantics is easy.*

**Command:** order to do something

*Study the book until you have understood it.*

# Terminology

**Statement:** declaration of fact or claim

*Semantics is easy.*

**Command:** order to do something

*Study the book until you have understood it.*

Expressions are *evaluated*, commands are *executed*

# Commands

Concrete syntax:

$$\begin{array}{l} com ::= \text{SKIP} \\ \quad | \quad string ::= aexp \\ \quad | \quad com \ ; \ ; \ com \\ \quad | \quad \text{IF } bexp \text{ THEN } com \text{ ELSE } com \\ \quad | \quad \text{WHILE } bexp \text{ DO } com \end{array}$$

# Commands

Abstract syntax:

**datatype** *com* = *SKIP*  
| *Assign string aexp*  
| *Seq com com*  
| *If bexp com com*  
| *While bexp com*

Com.thy

① IMP Commands

② Big-Step Semantics

③ Small-Step Semantics

# Big-step semantics

Concrete syntax:

$$(com, initial-state) \Rightarrow final-state$$

# Big-step semantics

Concrete syntax:

$$(com, initial-state) \Rightarrow final-state$$

Intended meaning of  $(c, s) \Rightarrow t$ :



# Big-step semantics

Concrete syntax:

$$(com, initial-state) \Rightarrow final-state$$

Intended meaning of  $(c, s) \Rightarrow t$ :

Command  $c$  started in state  $s$  terminates in state  $t$

# Big-step semantics

Concrete syntax:

$$(com, initial-state) \Rightarrow final-state$$

Intended meaning of  $(c, s) \Rightarrow t$ :

Command  $c$  started in state  $s$  terminates in state  $t$

“ $\Rightarrow$ ” here not type!

## Big-step rules

$$(SKIP, s) \Rightarrow s$$

# Big-step rules

$$(SKIP, s) \Rightarrow s$$

$$(x ::= a, s) \Rightarrow s(x := \text{aval } a \ s)$$

# Big-step rules

$$(SKIP, s) \Rightarrow s$$

$$(x ::= a, s) \Rightarrow s(x := \text{aval } a \ s)$$

$$\frac{(c_1, s_1) \Rightarrow s_2 \quad (c_2, s_2) \Rightarrow s_3}{(c_1;; c_2, s_1) \Rightarrow s_3}$$

## Big-step rules

$$\frac{bval\ b\ s \quad (c_1, s) \Rightarrow t}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \Rightarrow t}$$

## Big-step rules

$$\frac{bval\ b\ s \quad (c_1, s) \Rightarrow t}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \Rightarrow t}$$

$$\frac{\neg\ bval\ b\ s \quad (c_2, s) \Rightarrow t}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \Rightarrow t}$$

## Big-step rules

$$\frac{\neg \text{bval } b \ s}{(\text{WHILE } b \text{ DO } c, s) \Rightarrow s}$$



# Big-step rules

$$\frac{\neg \textit{bval } b \ s}{(\textit{WHILE } b \textit{ DO } c, s) \Rightarrow s}$$

$$\frac{\begin{array}{c} \textit{bval } b \ s_1 \\ (c, s_1) \Rightarrow s_2 \end{array} \quad (\textit{WHILE } b \textit{ DO } c, s_2) \Rightarrow s_3}{(\textit{WHILE } b \textit{ DO } c, s_1) \Rightarrow s_3}$$

## Examples: derivation trees

$$\frac{\vdots}{("x" ::= N\ 5;;\ "y" ::= V\ "x",\ s) \Rightarrow ?}$$

## Examples: derivation trees

$$\frac{\vdots}{("x'' ::= N\ 5;; "y'' ::= V\ "x'',\ s) \Rightarrow ?} \qquad \frac{\vdots}{(w,\ s_i) \Rightarrow ?}$$

where

- $w = \text{WHILE } b \text{ DO } c$
- $b = \text{NotEq } (V\ "x'')\ (N\ 2)$
- $c = "x'' ::= \text{Plus } (V\ "x'')\ (N\ 1)$
- $s_i = s("x'' := i)$

## Examples: derivation trees

$$\frac{\vdots}{("x'' ::= N\ 5;;\ "y'' ::= V\ "x'',\ s) \Rightarrow\ ?} \qquad \frac{\vdots}{(w,\ s_i) \Rightarrow\ ?}$$

where

$$\begin{aligned} w &= \textit{WHILE}\ b\ \textit{DO}\ c \\ b &= \textit{NotEq}\ (V\ "x'')\ (N\ 2) \\ c &= "x'' ::= \textit{Plus}\ (V\ "x'')\ (N\ 1) \\ s_i &= s("x'' := i) \end{aligned}$$

$$\begin{aligned} \textit{NotEq}\ a_1\ a_2 &= \\ \textit{Not}(\textit{And}\ (&\textit{Not}(\textit{Less}\ a_1\ a_2))\ (\textit{Not}(\textit{Less}\ a_2\ a_1)))) \end{aligned}$$

Logically speaking

$$(c, s) \Rightarrow t$$

is just infix syntax for

$$\textit{big\_step} \ (c,s) \ t$$

Logically speaking

$$(c, s) \Rightarrow t$$

is just infix syntax for

$$big\_step\ (c,s)\ t$$

where

$$big\_step :: com \times state \Rightarrow state \Rightarrow bool$$

is an inductively defined predicate.

# Big\_Step.thy

Semantics

# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t$  ?



# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t$  ?       $t = s$

# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t \text{ ?}$        $t = s$
- $(x ::= a, s) \Rightarrow t \text{ ?}$

# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t \ ? \quad t = s$
- $(x ::= a, s) \Rightarrow t \ ? \quad t = s(x := \text{aval } a \ s)$

# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t \ ? \quad t = s$
- $(x ::= a, s) \Rightarrow t \ ? \quad t = s(x := \text{aval } a \ s)$
- $(c_1;; c_2, s_1) \Rightarrow s_3 \ ?$

# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t \text{ ?} \quad t = s$
- $(x ::= a, s) \Rightarrow t \text{ ?} \quad t = s(x := \text{aval } a \ s)$
- $(c_1;; c_2, s_1) \Rightarrow s_3 \text{ ?}$   
 $\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3$

# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t \text{ ? } \quad t = s$
- $(x ::= a, s) \Rightarrow t \text{ ? } \quad t = s(x := \text{aval } a \ s)$
- $(c_1;; c_2, s_1) \Rightarrow s_3 \text{ ?}$   
 $\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3$
- $(IF \ b \ THEN \ c_1 \ ELSE \ c_2, s) \Rightarrow t \text{ ?}$

# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t \quad ? \quad t = s$
- $(x ::= a, s) \Rightarrow t \quad ? \quad t = s(x := \text{aval } a \ s)$
- $(c_1;; c_2, s_1) \Rightarrow s_3 \quad ?$   
 $\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3$
- $(IF \ b \ THEN \ c_1 \ ELSE \ c_2, s) \Rightarrow t \quad ?$   
 $bval \ b \ s \wedge (c_1, s) \Rightarrow t \ \vee$   
 $\neg \ bval \ b \ s \wedge (c_2, s) \Rightarrow t$

# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t \quad ? \quad t = s$
- $(x ::= a, s) \Rightarrow t \quad ? \quad t = s(x := \text{aval } a \ s)$
- $(c_1;; c_2, s_1) \Rightarrow s_3 \quad ?$   
 $\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3$
- $(IF \ b \ THEN \ c_1 \ ELSE \ c_2, s) \Rightarrow t \quad ?$   
 $\text{bval } b \ s \wedge (c_1, s) \Rightarrow t \vee$   
 $\neg \text{bval } b \ s \wedge (c_2, s) \Rightarrow t$
- $(w, s) \Rightarrow t \text{ where } w = WHILE \ b \ DO \ c \quad ?$



# Rule inversion

What can we deduce from

- $(SKIP, s) \Rightarrow t \quad ? \quad t = s$
- $(x ::= a, s) \Rightarrow t \quad ? \quad t = s(x := \text{aval } a \ s)$
- $(c_1;; c_2, s_1) \Rightarrow s_3 \quad ?$   
 $\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3$
- $(IF \ b \ THEN \ c_1 \ ELSE \ c_2, s) \Rightarrow t \quad ?$   
 $\text{bval } b \ s \wedge (c_1, s) \Rightarrow t \vee$   
 $\neg \text{bval } b \ s \wedge (c_2, s) \Rightarrow t$
- $(w, s) \Rightarrow t \text{ where } w = WHILE \ b \ DO \ c \quad ?$   
 $\neg \text{bval } b \ s \wedge t = s \vee$   
 $\text{bval } b \ s \wedge (\exists s'. (c, s) \Rightarrow s' \wedge (w, s') \Rightarrow t)$

# Automating rule inversion

Isabelle command **inductive\_cases** produces theorems that perform rule inversions automatically.

We reformulate the inverted rules. Example:

$$\frac{(c_1;; c_2, s_1) \Rightarrow s_3}{\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3}$$

We reformulate the inverted rules. Example:

$$\frac{(c_1;; c_2, s_1) \Rightarrow s_3}{\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3}$$

is logically equivalent to

$$\frac{\bigwedge s_2. \llbracket (c_1, s_1) \Rightarrow s_2; (c_2, s_2) \Rightarrow s_3 \rrbracket \Longrightarrow P}{P}$$

We reformulate the inverted rules. Example:

$$\frac{(c_1;; c_2, s_1) \Rightarrow s_3}{\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3}$$

is logically equivalent to

$$\frac{\bigwedge s_2. [(c_1, s_1) \Rightarrow s_2; (c_2, s_2) \Rightarrow s_3] \Longrightarrow P}{P}$$

Replaces assem  $(c_1;; c_2, s_1) \Rightarrow s_3$  by two assems  
 $(c_1, s_1) \Rightarrow s_2$  and  $(c_2, s_2) \Rightarrow s_3$

We reformulate the inverted rules. Example:

$$\frac{(c_1;; c_2, s_1) \Rightarrow s_3}{\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3}$$

is logically equivalent to

$$\frac{\bigwedge s_2. \llbracket (c_1, s_1) \Rightarrow s_2; (c_2, s_2) \Rightarrow s_3 \rrbracket \Longrightarrow P}{P}$$

Replaces assem  $(c_1;; c_2, s_1) \Rightarrow s_3$  by two assems  $(c_1, s_1) \Rightarrow s_2$  and  $(c_2, s_2) \Rightarrow s_3$  (with a new fixed  $s_2$ ).

We reformulate the inverted rules. Example:

$$\frac{(c_1;; c_2, s_1) \Rightarrow s_3}{\exists s_2. (c_1, s_1) \Rightarrow s_2 \wedge (c_2, s_2) \Rightarrow s_3}$$

is logically equivalent to

$$\frac{\bigwedge s_2. [(c_1, s_1) \Rightarrow s_2; (c_2, s_2) \Rightarrow s_3] \implies P}{P}$$

Replaces assem  $(c_1;; c_2, s_1) \Rightarrow s_3$  by two assems  $(c_1, s_1) \Rightarrow s_2$  and  $(c_2, s_2) \Rightarrow s_3$  (with a new fixed  $s_2$ ).

No  $\exists$  and  $\wedge$ !

The general format: *elimination rules*

$$\frac{asm \quad asm_1 \Rightarrow P \quad \dots \quad asm_n \Rightarrow P}{P}$$



The general format: *elimination rules*

$$\frac{asm \quad asm_1 \Longrightarrow P \quad \dots \quad asm_n \Longrightarrow P}{P}$$

(possibly with  $\bigwedge \bar{x}$  in front of the  $asm_i \Longrightarrow P$ )

The general format: *elimination rules*

$$\frac{asm \quad asm_1 \Longrightarrow P \quad \dots \quad asm_n \Longrightarrow P}{P}$$

(possibly with  $\bigwedge \bar{x}$  in front of the  $asm_i \Longrightarrow P$ )

Reading:

To prove a goal  $P$  with assumption  $asm$ ,  
prove all  $asm_i \Longrightarrow P$

The general format: *elimination rules*

$$\frac{asm \quad asm_1 \Longrightarrow P \quad \dots \quad asm_n \Longrightarrow P}{P}$$

(possibly with  $\bigwedge \bar{x}$  in front of the  $asm_i \Longrightarrow P$ )

Reading:

To prove a goal  $P$  with assumption  $asm$ ,  
prove all  $asm_i \Longrightarrow P$

Example:

$$\frac{F \vee G \quad F \Longrightarrow P \quad G \Longrightarrow P}{P}$$

## *elim* attribute

- Theorems with *elim* attribute are used automatically by *blast*, *fastforce* and *auto*

## *elim* attribute

- Theorems with *elim* attribute are used automatically by *blast*, *fastforce* and *auto*
- Can also be added locally, eg (*blast elim: ...*)

## *elim* attribute

- Theorems with *elim* attribute are used automatically by *blast*, *fastforce* and *auto*
- Can also be added locally, eg (*blast elim: ...*)
- Variant: *elim!* applies elim-rules eagerly.

# Big\_Step.thy

Rule inversion

# Command equivalence

Two commands have the same input/output behaviour:



# Command equivalence

Two commands have the same input/output behaviour:

$$c \sim c' \equiv (\forall s\ t. (c, s) \Rightarrow t \longleftrightarrow (c', s) \Rightarrow t)$$

# Command equivalence

Two commands have the same input/output behaviour:

$$c \sim c' \equiv (\forall s\ t. (c, s) \Rightarrow t \longleftrightarrow (c', s) \Rightarrow t)$$

## Example

$$w \sim w'$$

where  $w = \text{WHILE } b \text{ DO } c$

$w' = \text{IF } b \text{ THEN } c;; w \text{ ELSE SKIP}$

# Equivalence proof

$$(w, s) \Rightarrow t$$

# Equivalence proof

$$(w, s) \Rightarrow t$$

$$\longleftrightarrow$$

$$bval\ b\ s \wedge (\exists s'. (c, s) \Rightarrow s' \wedge (w, s') \Rightarrow t)$$

$$\vee$$

$$\neg bval\ b\ s \wedge t = s$$

# Equivalence proof

$$\begin{aligned} & (w, s) \Rightarrow t \\ & \longleftrightarrow \\ & bval\ b\ s \wedge (\exists s'. (c, s) \Rightarrow s' \wedge (w, s') \Rightarrow t) \\ & \quad \vee \\ & \neg bval\ b\ s \wedge t = s \\ & \longleftrightarrow \\ & (w', s) \Rightarrow t \end{aligned}$$

# Equivalence proof

$$\begin{aligned} & (w, s) \Rightarrow t \\ & \longleftrightarrow \\ & bval\ b\ s \wedge (\exists s'. (c, s) \Rightarrow s' \wedge (w, s') \Rightarrow t) \\ & \quad \vee \\ & \neg\ bval\ b\ s \wedge t = s \\ & \longleftrightarrow \\ & (w', s) \Rightarrow t \end{aligned}$$

Using the rules and rule inversions for  $\Rightarrow$ .

# Big\_Step.thy

Command equivalence

# Execution is deterministic

Any two executions of the same command in the same start state lead to the same final state:

$$(c, s) \Rightarrow t \implies (c, s) \Rightarrow t' \implies t = t'$$



# Execution is deterministic

Any two executions of the same command in the same start state lead to the same final state:

$$(c, s) \Rightarrow t \implies (c, s) \Rightarrow t' \implies t = t'$$

Proof by rule induction, for arbitrary  $t'$ .

# Big\_Step.thy

Execution is deterministic

# The boon and bane of big steps

We cannot observe intermediate states/steps

# The boon and bane of big steps

We cannot observe intermediate states/steps

Example problem:

# The boon and bane of big steps

We cannot observe intermediate states/steps

Example problem:

$(c, s)$  does not terminate iff  $\nexists t. (c, s) \Rightarrow t$ ?

# The boon and bane of big steps

We cannot observe intermediate states/steps

Example problem:

$(c, s)$  does not terminate iff  $\nexists t. (c, s) \Rightarrow t$ ?

Needs a formal notion of nontermination to prove it.

# The boon and bane of big steps

We cannot observe intermediate states/steps

Example problem:

$(c, s)$  does not terminate iff  $\nexists t. (c, s) \Rightarrow t$ ?

Needs a formal notion of nontermination to prove it.  
Could be wrong if we have forgotten a  $\Rightarrow$  rule.

Big-step semantics cannot directly describe

- nonterminating computations,



Big-step semantics cannot directly describe

- nonterminating computations,
- parallel computations.

Big-step semantics cannot directly describe

- nonterminating computations,
- parallel computations.

We need a finer grained semantics!

① IMP Commands

② Big-Step Semantics

③ Small-Step Semantics

# Small-step semantics

Concrete syntax:

$$(com, state) \rightarrow (com, state)$$

# Small-step semantics

Concrete syntax:

$$(com, state) \rightarrow (com, state)$$

Intended meaning of  $(c, s) \rightarrow (c', s')$ :

# Small-step semantics

Concrete syntax:

$$(com, state) \rightarrow (com, state)$$

Intended meaning of  $(c, s) \rightarrow (c', s')$ :

*The first step in the execution of  $c$  in state  $s$  leaves a “remainder” command  $c'$  to be executed in state  $s'$ .*

# Small-step semantics

Concrete syntax:

$$(com, state) \rightarrow (com, state)$$

Intended meaning of  $(c, s) \rightarrow (c', s')$ :

*The first step in the execution of  $c$  in state  $s$  leaves a “remainder” command  $c'$  to be executed in state  $s'$ .*

Execution as finite or infinite reduction:

$$(c_1, s_1) \rightarrow (c_2, s_2) \rightarrow (c_3, s_3) \rightarrow \dots$$

# Terminology

- A pair  $(c,s)$  is called a *configuration*.



# Terminology

- A pair  $(c,s)$  is called a *configuration*.
- If  $cs \rightarrow cs'$  we say that  $cs$  *reduces* to  $cs'$ .

# Terminology

- A pair  $(c,s)$  is called a *configuration*.
- If  $cs \rightarrow cs'$  we say that  $cs$  *reduces* to  $cs'$ .
- A configuration  $cs$  is *final* iff  $\nexists cs'. cs \rightarrow cs'$

The intention:

$(SKIP, s)$  is final

The intention:

$(SKIP, s)$  is final

Why?

*SKIP* is the empty program.

The intention:

$(SKIP, s)$  is final

Why?

*SKIP* is the empty program. Nothing more to be done.

# Small-step rules

$$(x ::= a, s) \rightarrow$$

# Small-step rules

$$(x ::= a, s) \rightarrow (SKIP, s(x := \text{aval } a \ s))$$

# Small-step rules

$$(x ::= a, s) \rightarrow (SKIP, s(x := \text{aval } a \ s))$$

$$(SKIP;; c, s) \rightarrow$$



# Small-step rules

$$(x ::= a, s) \rightarrow (SKIP, s(x := \text{aval } a \ s))$$

$$(SKIP;; c, s) \rightarrow (c, s)$$

# Small-step rules

$$(x ::= a, s) \rightarrow (SKIP, s(x := \text{aval } a \ s))$$

$$(SKIP;; c, s) \rightarrow (c, s)$$

$$\frac{(c_1, s) \rightarrow (c'_1, s')}{(c_1;; c_2, s) \rightarrow}$$

# Small-step rules

$$(x ::= a, s) \rightarrow (SKIP, s(x := \text{aval } a \ s))$$

$$(SKIP;; c, s) \rightarrow (c, s)$$

$$\frac{(c_1, s) \rightarrow (c'_1, s')}{(c_1;; c_2, s) \rightarrow (c'_1;; c_2, s')}$$

# Small-step rules

$$\frac{bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow}$$

# Small-step rules

$$\frac{bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_1, s)}$$

# Small-step rules

$$\frac{bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_1, s)}$$
$$\frac{\neg\ bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_2, s)}$$

# Small-step rules

$$\frac{bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_1, s)}$$

$$\frac{\neg\ bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_2, s)}$$

$$(WHILE\ b\ DO\ c, s) \rightarrow$$

## Small-step rules

$$\frac{bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_1, s)}$$

$$\frac{\neg\ bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_2, s)}$$

$$(WHILE\ b\ DO\ c, s) \rightarrow (IF\ b\ THEN\ c;;\ WHILE\ b\ DO\ c\ ELSE\ SKIP, s)$$



## Small-step rules

$$\frac{bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_1, s)}$$

$$\frac{\neg\ bval\ b\ s}{(IF\ b\ THEN\ c_1\ ELSE\ c_2, s) \rightarrow (c_2, s)}$$

$$(WHILE\ b\ DO\ c, s) \rightarrow (IF\ b\ THEN\ c;;\ WHILE\ b\ DO\ c\ ELSE\ SKIP, s)$$

**Fact**  $(SKIP, s)$  is a final configuration.

## Small-step examples

$$("z'' ::= V "x'';; "x'' ::= V "y'';; "y'' ::= V "z'', s) \rightarrow$$

...

where  $s = \langle "x'' := 3, "y'' := 7, "z'' := 5 \rangle$ .

## Small-step examples

$$("z'' ::= V "x'';; "x'' ::= V "y'';; "y'' ::= V "z'', s) \rightarrow \dots$$

where  $s = \langle "x'' := 3, "y'' := 7, "z'' := 5 \rangle$ .

$$(w, s_0) \rightarrow \dots$$

where

$$\begin{aligned} w &= \text{WHILE } b \text{ DO } c \\ b &= \text{Less } (V "x'') (N 1) \\ c &= "x'' ::= \text{Plus } (V "x'') (N 1) \\ s_n &= \langle "x'' := n \rangle \end{aligned}$$

# Small\_Step.thy

Semantics

Are big and small-step semantics equivalent?

From  $\Rightarrow$  to  $\rightarrow^*$

From  $\Rightarrow$  to  $\rightarrow^*$

**Theorem**  $cs \Rightarrow t \implies cs \rightarrow^* (SKIP, t)$

From  $\Rightarrow$  to  $\rightarrow^*$

**Theorem**  $cs \Rightarrow t \implies cs \rightarrow^* (SKIP, t)$

Proof by rule induction



## From $\Rightarrow$ to $\rightarrow^*$

**Theorem**  $cs \Rightarrow t \implies cs \rightarrow^* (SKIP, t)$

Proof by rule induction (of course on  $cs \Rightarrow t$ )

## From $\Rightarrow$ to $\rightarrow^*$

**Theorem**  $cs \Rightarrow t \implies cs \rightarrow^* (SKIP, t)$

Proof by rule induction (of course on  $cs \Rightarrow t$ )

In two cases a lemma is needed:

## From $\Rightarrow$ to $\rightarrow^*$

**Theorem**  $cs \Rightarrow t \implies cs \rightarrow^* (SKIP, t)$

Proof by rule induction (of course on  $cs \Rightarrow t$ )

In two cases a lemma is needed:

**Lemma**

$$(c_1, s) \rightarrow^* (c_1', s') \implies (c_1;; c_2, s) \rightarrow^* (c_1';; c_2, s')$$

## From $\Rightarrow$ to $\rightarrow^*$

**Theorem**  $cs \Rightarrow t \implies cs \rightarrow^* (SKIP, t)$

Proof by rule induction (of course on  $cs \Rightarrow t$ )

In two cases a lemma is needed:

**Lemma**

$(c_1, s) \rightarrow^* (c_1', s') \implies (c_1;; c_2, s) \rightarrow^* (c_1';; c_2, s')$

Proof by rule induction.

From  $\rightarrow^*$  to  $\Rightarrow$

From  $\rightarrow^*$  to  $\Rightarrow$

**Theorem**  $cs \rightarrow^* (SKIP, t) \implies cs \Rightarrow t$

## From $\rightarrow^*$ to $\Rightarrow$

**Theorem**  $cs \rightarrow^* (SKIP, t) \implies cs \Rightarrow t$

Proof by rule induction on  $cs \rightarrow^* (SKIP, t)$ .

## From $\rightarrow^*$ to $\Rightarrow$

**Theorem**  $cs \rightarrow^* (SKIP, t) \implies cs \Rightarrow t$

Proof by rule induction on  $cs \rightarrow^* (SKIP, t)$ .

In the induction step a lemma is needed:



## From $\rightarrow^*$ to $\Rightarrow$

**Theorem**  $cs \rightarrow^* (SKIP, t) \implies cs \Rightarrow t$

Proof by rule induction on  $cs \rightarrow^* (SKIP, t)$ .

In the induction step a lemma is needed:

**Lemma**  $cs \rightarrow cs' \implies cs' \Rightarrow t \implies cs \Rightarrow t$

## From $\rightarrow^*$ to $\Rightarrow$

**Theorem**  $cs \rightarrow^* (SKIP, t) \implies cs \Rightarrow t$

Proof by rule induction on  $cs \rightarrow^* (SKIP, t)$ .

In the induction step a lemma is needed:

**Lemma**  $cs \rightarrow cs' \implies cs' \Rightarrow t \implies cs \Rightarrow t$

Proof by rule induction on  $cs \rightarrow cs'$ .

# Equivalence

**Corollary**  $cs \Rightarrow t \iff cs \rightarrow^* (SKIP, t)$

# Small\_Step.thy

Equivalence of big and small

# Can execution stop prematurely?

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .



## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .

- Case  $c_1;; c_2$ : by case distinction:

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .

- Case  $c_1;; c_2$ : by case distinction:
  - $c_1 = SKIP$

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .

- Case  $c_1;; c_2$ : by case distinction:
  - $c_1 = SKIP \implies \neg final(c_1;; c_2, s)$

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .

- Case  $c_1;; c_2$ : by case distinction:
  - $c_1 = SKIP \implies \neg final(c_1;; c_2, s)$
  - $c_1 \neq SKIP$

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .

- Case  $c_1;; c_2$ : by case distinction:
  - $c_1 = SKIP \implies \neg final(c_1;; c_2, s)$
  - $c_1 \neq SKIP \implies \neg final(c_1, s)$

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .

- Case  $c_1;; c_2$ : by case distinction:
  - $c_1 = SKIP \implies \neg final(c_1;; c_2, s)$
  - $c_1 \neq SKIP \implies \neg final(c_1, s)$  (by IH)

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .

- Case  $c_1;; c_2$ : by case distinction:
  - $c_1 = SKIP \implies \neg final(c_1;; c_2, s)$
  - $c_1 \neq SKIP \implies \neg final(c_1, s)$  (by IH)  
 $\implies \neg final(c_1;; c_2, s)$

## Can execution stop prematurely?

That is, are there any final configs except  $(SKIP, s)$  ?

**Lemma**  $final(c, s) \implies c = SKIP$

We prove the contrapositive

$$c \neq SKIP \implies \neg final(c, s)$$

by induction on  $c$ .

- Case  $c_1;; c_2$ : by case distinction:
  - $c_1 = SKIP \implies \neg final(c_1;; c_2, s)$
  - $c_1 \neq SKIP \implies \neg final(c_1, s)$  (by IH)  
 $\implies \neg final(c_1;; c_2, s)$
- Remaining cases: trivial or easy



By rule inversion:  $(SKIP, s) \rightarrow ct \implies False$

By rule inversion:  $(SKIP, s) \rightarrow ct \implies False$

Together:

**Corollary**  $final(c, s) = (c = SKIP)$

# Infinite executions

$\Rightarrow$  yields final state iff  $\rightarrow$  terminates

# Infinite executions

$\Rightarrow$  yields final state iff  $\rightarrow$  terminates

**Lemma**  $(\exists t. cs \Rightarrow t) = (\exists cs'. cs \rightarrow^* cs' \wedge \text{final } cs')$

# Infinite executions

$\Rightarrow$  yields final state iff  $\rightarrow$  terminates

**Lemma**  $(\exists t. cs \Rightarrow t) = (\exists cs'. cs \rightarrow^* cs' \wedge \text{final } cs')$

Proof:  $(\exists t. cs \Rightarrow t)$

# Infinite executions

$\Rightarrow$  yields final state iff  $\rightarrow$  terminates

**Lemma**  $(\exists t. cs \Rightarrow t) = (\exists cs'. cs \rightarrow^* cs' \wedge \text{final } cs')$

Proof:  $(\exists t. cs \Rightarrow t)$   
=  $(\exists t. cs \rightarrow^* (SKIP, t))$

# Infinite executions

$\Rightarrow$  yields final state iff  $\rightarrow$  terminates

**Lemma**  $(\exists t. cs \Rightarrow t) = (\exists cs'. cs \rightarrow^* cs' \wedge \text{final } cs')$

Proof:  $(\exists t. cs \Rightarrow t)$   
=  $(\exists t. cs \rightarrow^* (\text{SKIP}, t))$   
(by big = small)

# Infinite executions

$\Rightarrow$  yields final state iff  $\rightarrow$  terminates

**Lemma**  $(\exists t. cs \Rightarrow t) = (\exists cs'. cs \rightarrow^* cs' \wedge final\ cs')$

Proof:  $(\exists t. cs \Rightarrow t)$   
=  $(\exists t. cs \rightarrow^* (SKIP, t))$   
    (by big = small)  
=  $(\exists cs'. cs \rightarrow^* cs' \wedge final\ cs')$



# Infinite executions

$\Rightarrow$  yields final state iff  $\rightarrow$  terminates

**Lemma**  $(\exists t. cs \Rightarrow t) = (\exists cs'. cs \rightarrow^* cs' \wedge final\ cs')$

Proof:  $(\exists t. cs \Rightarrow t)$   
=  $(\exists t. cs \rightarrow^* (SKIP, t))$   
    (by big = small)  
=  $(\exists cs'. cs \rightarrow^* cs' \wedge final\ cs')$   
    (by final = SKIP)

# Infinite executions

$\Rightarrow$  yields final state iff  $\rightarrow$  terminates

**Lemma**  $(\exists t. cs \Rightarrow t) = (\exists cs'. cs \rightarrow^* cs' \wedge \text{final } cs')$

Proof:  $(\exists t. cs \Rightarrow t)$   
=  $(\exists t. cs \rightarrow^* (\text{SKIP}, t))$   
    (by big = small)  
=  $(\exists cs'. cs \rightarrow^* cs' \wedge \text{final } cs')$   
    (by final = SKIP)

Equivalent:

$\Rightarrow$  does not yield final state iff  $\rightarrow$  does not terminate

# May versus Must

→ is deterministic:

# May versus Must

$\rightarrow$  is deterministic:

**Lemma**  $cs \rightarrow cs' \implies cs \rightarrow cs'' \implies cs'' = cs'$

# May versus Must

$\rightarrow$  is deterministic:

**Lemma**  $cs \rightarrow cs' \implies cs \rightarrow cs'' \implies cs'' = cs'$   
(Proof by rule induction)

# May versus Must

$\rightarrow$  is deterministic:

**Lemma**  $cs \rightarrow cs' \implies cs \rightarrow cs'' \implies cs'' = cs'$   
(Proof by rule induction)

Therefore: no difference between

**may** terminate (there is a terminating  $\rightarrow$  path)

**must** terminate (all  $\rightarrow$  paths terminate)

# May versus Must

$\rightarrow$  is deterministic:

**Lemma**  $cs \rightarrow cs' \implies cs \rightarrow cs'' \implies cs'' = cs'$   
(Proof by rule induction)

Therefore: no difference between

**may** terminate (there is a terminating  $\rightarrow$  path)

**must** terminate (all  $\rightarrow$  paths terminate)

Therefore:  $\Rightarrow$  correctly reflects termination behaviour.

# May versus Must

$\rightarrow$  is deterministic:

**Lemma**  $cs \rightarrow cs' \implies cs \rightarrow cs'' \implies cs'' = cs'$   
(Proof by rule induction)

Therefore: no difference between

**may** terminate (there is a terminating  $\rightarrow$  path)

**must** terminate (all  $\rightarrow$  paths terminate)

Therefore:  $\Rightarrow$  correctly reflects termination behaviour.

With nondeterminism: may have both  $cs \Rightarrow t$  and a nonterminating reduction  $cs \rightarrow cs' \rightarrow \dots$



# Chapter 8

## Hoare Logic

- ④ Weakest Preconditions
- ⑤ Towards Simpler Verification of Programs
- ⑥ Example Verifications
- ⑦ Advanced Verification

④ Weakest Preconditions

⑤ Towards Simpler Verification of Programs

⑥ Example Verifications

⑦ Advanced Verification

## ④ Weakest Preconditions

### Introduction

We have proved functional programs correct

We have proved functional programs correct

We have modeled semantics of imperative languages

We have proved functional programs correct

We have modeled semantics of imperative languages

But how do we prove imperative programs correct?

An example program:

```
program exp {  
  a := 1  
  while ( $0 < n$ ) do {  
    a := a + a;  
    n := n - 1  
  }  
}
```



An example program:

```
program exp {  
  a := 1  
  while (0 < n) do {  
    a := a + a;  
    n := n - 1  
  }  
}
```

At the end of the execution, variable  $a$  should contain  $2^n$ ,

An example program:

```
program exp {  
  a := 1  
  while (0 < n) do {  
    a := a + a;  
    n := n - 1  
  }  
}
```

At the end of the execution, variable  $a$  should contain  $2^n$ , where  $n$  is the original value of variable  $n$ !

An example program:

```
program exp {  
  a := 1  
  while (0 < n) do {  
    a := a + a;  
    n := n - 1  
  }  
}
```

At the end of the execution, variable  $a$  should contain  $2^n$ ,  
where  $n$  is the original value of variable  $n$ !  
and  $0 \leq n!$

In general: If *precondition* holds for initial state then, program terminates, and final state satisfies *postcondition*

In general: If *precondition* holds for initial state then, program terminates, and final state satisfies *postcondition*

Formally

In general: If *precondition* holds for initial state then, program terminates, and final state satisfies *postcondition*

Formally?

In general: If *precondition* holds for initial state then, program terminates, and final state satisfies *postcondition*

Formally?

$$P\ s \Longrightarrow \exists t. (c, s) \Rightarrow t \wedge Q\ t$$

In general: If *precondition* holds for initial state then, program terminates, and final state satisfies *postcondition*

Formally?

$$P \ s \Longrightarrow \exists t. (c, s) \Rightarrow t \wedge Q \ t$$

The RHS of this implication is called *weakest precondition*

$$wp \ c \ Q \ s \equiv \exists t. (c, s) \Rightarrow t \wedge Q \ t$$



In general: If *precondition* holds for initial state then, program terminates, and final state satisfies *postcondition*

Formally?

$$P \ s \Longrightarrow \exists t. (c, s) \Rightarrow t \wedge Q \ t$$

The RHS of this implication is called *weakest precondition*

$$wp \ c \ Q \ s \equiv \exists t. (c, s) \Rightarrow t \wedge Q \ t$$

Weakest condition on state, such that program  $c$  will satisfy postcondition  $Q$ .

Some obvious facts:

Some obvious facts:

*Consequence rule:*

$$\llbracket wp\ c\ P\ s; \bigwedge s. P\ s \implies Q\ s \rrbracket \implies wp\ c\ Q\ s$$

Some obvious facts:

*Consequence rule:*

$$\llbracket wp\ c\ P\ s; \bigwedge s. P\ s \implies Q\ s \rrbracket \implies wp\ c\ Q\ s$$

$wp$  of equivalent programs is equal

$$c \sim c' \implies wp\ c = wp\ c'$$

Correctness of *exp*

Correctness of *exp*?

Correctness of *exp*?

$$0 \leq s \text{ ''}n'' \implies wp \ exp \ (\lambda s'. \ s' \text{ ''}a'' = 2^{nat \ (s \text{ ''}n'')}) \ s$$

Correctness of *exp*?

$$0 \leq s \text{ ''}n'' \implies wp \ exp \ (\lambda s'. s' \text{ ''}a'' = 2^{nat \ (s \text{ ''}n'')}) \ s$$

$nat::int \Rightarrow nat$  required b/c  $(\hat{\ })::'a \Rightarrow nat \Rightarrow 'a$  only defined on  $nat$ .



Correctness of *exp*?

$$0 \leq s \text{ ''}n'' \implies wp \ exp \ (\lambda s'. s' \text{ ''}a'' = 2^{nat \ (s \text{ ''}n'')}) \ s$$

$nat::int \Rightarrow nat$  required b/c  $(\hat{\ })::'a \Rightarrow nat \Rightarrow 'a$  only defined on  $nat$ .

In general:  $P \ s \implies wp \ c \ Q \ s$

How to prove correctness of programs?

$$P \text{ } s \Longrightarrow wp \text{ } c \text{ } Q \text{ } s$$

How to prove correctness of programs?

$$P \text{ } s \Longrightarrow wp \text{ } c \text{ } Q \text{ } s$$

$$wp \text{ } SKIP \text{ } Q \text{ } s =$$

How to prove correctness of programs?

$$P \text{ } s \Longrightarrow wp \text{ } c \text{ } Q \text{ } s$$

$$wp \text{ } SKIP \text{ } Q \text{ } s = Q \text{ } s$$

How to prove correctness of programs?

$$P \text{ } s \Longrightarrow wp \text{ } c \text{ } Q \text{ } s$$

$$wp \text{ } SKIP \text{ } Q \text{ } s = Q \text{ } s$$

$$wp \text{ } (x ::= a) \text{ } Q \text{ } s =$$

How to prove correctness of programs?

$$P \ s \Longrightarrow \ wp \ c \ Q \ s$$

$$\wp \ SKIP \ Q \ s = Q \ s$$

$$\wp \ (x ::= a) \ Q \ s = Q \ (s(x := \text{aval } a \ s))$$

How to prove correctness of programs?

$$P\ s \Longrightarrow wp\ c\ Q\ s$$

$$wp\ SKIP\ Q\ s = Q\ s$$

$$wp\ (x ::= a)\ Q\ s = Q\ (s(x := \text{aval } a\ s))$$

$$wp\ (c_1;; c_2)\ Q\ s =$$

How to prove correctness of programs?

$$P\ s \Longrightarrow\ wp\ c\ Q\ s$$

$$wp\ SKIP\ Q\ s = Q\ s$$

$$wp\ (x ::= a)\ Q\ s = Q\ (s(x := \text{aval } a\ s))$$

$$wp\ (c_1;; c_2)\ Q\ s = wp\ c_1\ (wp\ c_2\ Q)\ s$$



How to prove correctness of programs?

$$P\ s \Longrightarrow\ wp\ c\ Q\ s$$

$$wp\ SKIP\ Q\ s = Q\ s$$

$$wp\ (x ::= a)\ Q\ s = Q\ (s(x := \text{aval } a\ s))$$

$$wp\ (c_1;; c_2)\ Q\ s = wp\ c_1\ (wp\ c_2\ Q)\ s$$

$$wp\ (IF\ b\ THEN\ c_1\ ELSE\ c_2)\ Q\ s$$

=

How to prove correctness of programs?

$$P\ s \Longrightarrow wp\ c\ Q\ s$$

$$wp\ SKIP\ Q\ s = Q\ s$$

$$wp\ (x ::= a)\ Q\ s = Q\ (s(x := aval\ a\ s))$$

$$wp\ (c_1;; c_2)\ Q\ s = wp\ c_1\ (wp\ c_2\ Q)\ s$$

$$\begin{aligned} wp\ (IF\ b\ THEN\ c_1\ ELSE\ c_2)\ Q\ s \\ =\ if\ bval\ b\ s\ then\ wp\ c_1\ Q\ s\ else\ wp\ c_2\ Q\ s \end{aligned}$$

How to prove correctness of programs?

$$P\ s \Longrightarrow\ wp\ c\ Q\ s$$

$$wp\ SKIP\ Q\ s = Q\ s$$

$$wp\ (x ::= a)\ Q\ s = Q\ (s(x := \text{aval } a\ s))$$

$$wp\ (c_1;; c_2)\ Q\ s = wp\ c_1\ (wp\ c_2\ Q)\ s$$

$$\begin{aligned} wp\ (IF\ b\ THEN\ c_1\ ELSE\ c_2)\ Q\ s \\ =\ if\ bval\ b\ s\ then\ wp\ c_1\ Q\ s\ else\ wp\ c_2\ Q\ s \end{aligned}$$

Reasoning along syntax of program!

That was easy!

That was easy! But what about *While*?

That was easy! But what about *While*?

$wp \ (WHILE \ b \ DO \ c) \ Q \ s$   
=

That was easy! But what about *While*?

$$\begin{aligned} & wp \ (WHILE \ b \ DO \ c) \ Q \ s \\ &= if \ bval \ b \ s \ then \ wp \ c \ (wp \ (WHILE \ b \ DO \ c) \ Q) \ s \ else \\ & \quad Q \ s \end{aligned}$$

That was easy! But what about *While*?

$$\begin{aligned} & wp \ (WHILE \ b \ DO \ c) \ Q \ s \\ & = if \ bval \ b \ s \ then \ wp \ c \ (wp \ (WHILE \ b \ DO \ c) \ Q) \ s \ else \\ & \quad Q \ s \end{aligned}$$

Unfolding will continue forever!



That was easy! But what about *While*?

$$\begin{aligned} & wp \ (WHILE \ b \ DO \ c) \ Q \ s \\ & = if \ bval \ b \ s \ then \ wp \ c \ (wp \ (WHILE \ b \ DO \ c) \ Q) \ s \ else \\ & \quad Q \ s \end{aligned}$$

Unfolding will continue forever!

Obviously, need some inductive argument!

That was easy! But what about *While*?

$$\begin{aligned} & wp \ (WHILE \ b \ DO \ c) \ Q \ s \\ & = if \ bval \ b \ s \ then \ wp \ c \ (wp \ (WHILE \ b \ DO \ c) \ Q) \ s \ else \\ & \quad Q \ s \end{aligned}$$

Unfolding will continue forever!

Obviously, need some inductive argument!

But, let's get less ambitious (for first)

Weakest liberal precondition

$$wlp\ c\ Q\ s \equiv \forall t. (c, s) \Rightarrow t \longrightarrow Q\ t$$

Weakest **liberal** precondition

$$wlp\ c\ Q\ s \equiv \forall t. (c, s) \Rightarrow t \longrightarrow Q\ t$$

If  $c$  terminates on  $s$ , then new state satisfies  $Q$

Weakest **liberal** precondition

$$wlp\ c\ Q\ s \equiv \forall t. (c, s) \Rightarrow t \longrightarrow Q\ t$$

If  $c$  terminates on  $s$ , then new state satisfies  $Q$

Cannot reason about termination. This is called ***partial correctness***.

Some obvious facts:

$$c \sim c' \implies wlp\ c = wlp\ c'$$

$$\llbracket wlp\ c\ P\ s; \bigwedge s. P\ s \implies Q\ s \rrbracket \implies wlp\ c\ Q\ s$$

Some obvious facts:

$$c \sim c' \implies wlp\ c = wlp\ c'$$

$$\llbracket wlp\ c\ P\ s; \bigwedge s. P\ s \implies Q\ s \rrbracket \implies wlp\ c\ Q\ s$$

Relation between  $wp$  and  $wlp$

$$wp\ c\ Q\ s \implies wlp\ c\ Q\ s$$

$$wlp\ c\ Q\ s \wedge (c, s) \Rightarrow t \implies wp\ c\ Q\ s$$

Some obvious facts:

$$c \sim c' \implies wlp\ c = wlp\ c'$$

$$\llbracket wlp\ c\ P\ s; \bigwedge s. P\ s \implies Q\ s \rrbracket \implies wlp\ c\ Q\ s$$

Relation between  $wp$  and  $wlp$

$$wp\ c\ Q\ s \implies wlp\ c\ Q\ s$$

$$wlp\ c\ Q\ s \wedge (c, s) \Rightarrow t \implies wp\ c\ Q\ s$$

Unfold rules still hold:

$$wlp\ SKIP\ Q\ s = Q\ s$$

$$wlp\ (x ::= a)\ Q\ s = Q\ (s(x := aval\ a\ s))$$

$$wlp\ (c_1;; c_2)\ Q\ s = wlp\ c_1\ (wlp\ c_2\ Q)\ s$$

$$wlp\ (IF\ b\ THEN\ c_1\ ELSE\ c_2)\ Q\ s = \\ (if\ bval\ b\ s\ then\ wlp\ c_1\ Q\ s\ else\ wlp\ c_2\ Q\ s)$$



$$\begin{aligned} \text{wlp } (WHILE\ b\ DO\ c)\ Q\ s = \\ (if\ bval\ b\ s\ then\ \text{wlp}\ c\ (\text{wlp}\ (WHILE\ b\ DO\ c)\ Q)\ s\ else \\ Q\ s) \end{aligned}$$

$$\begin{aligned} \text{wlp } (WHILE\ b\ DO\ c)\ Q\ s = \\ (if\ \text{bval}\ b\ s\ \text{then}\ \text{wlp}\ c\ (\text{wlp}\ (WHILE\ b\ DO\ c)\ Q)\ s\ \text{else} \\ Q\ s) \end{aligned}$$

Let's try to find predicate  $I$ , such that

$$\bigwedge s. I\ s \implies if\ \text{bval}\ b\ s\ \text{then}\ \text{wp}\ c\ I\ s\ \text{else}\ Q\ s$$

$$\begin{aligned} \text{wlp } ( \text{WHILE } b \text{ DO } c ) \ Q \ s = \\ ( \text{if } \text{bval } b \ s \text{ then } \text{wlp } c \ ( \text{wlp } ( \text{WHILE } b \text{ DO } c ) \ Q ) \ s \text{ else } \\ Q \ s ) \end{aligned}$$

Let's try to find predicate  $I$ , such that

$$\bigwedge s. I \ s \implies \text{if } \text{bval } b \ s \text{ then } \text{wp } c \ I \ s \text{ else } Q \ s$$

and  $I$  holds for start state.

$$\text{wlp } (\text{WHILE } b \text{ DO } c) \ Q \ s = \\ (\text{if } \text{bval } b \ s \text{ then } \text{wlp } c \ (\text{wlp } (\text{WHILE } b \text{ DO } c) \ Q) \ s \text{ else } \\ Q \ s)$$

Let's try to find predicate  $I$ , such that

$$\bigwedge s. I \ s \implies \text{if } \text{bval } b \ s \text{ then } \text{wp } c \ I \ s \text{ else } Q \ s$$

and  $I$  holds for start state.

Intuition:  $I$  holds initially, is preserved by iteration, and implies  $Q$  at end of loop.

$$\text{wlp } (\text{WHILE } b \text{ DO } c) \ Q \ s = \\ (\text{if } \text{bval } b \ s \text{ then } \text{wlp } c \ (\text{wlp } (\text{WHILE } b \text{ DO } c) \ Q) \ s \text{ else } \\ Q \ s)$$

Let's try to find predicate  $I$ , such that

$$\bigwedge s. I \ s \implies \text{if } \text{bval } b \ s \text{ then } \text{wp } c \ I \ s \text{ else } Q \ s$$

and  $I$  holds for start state.

Intuition:  $I$  holds initially, is preserved by iteration, and implies  $Q$  at end of loop.  $I$  is called *loop invariant*

While-rule for partial correctness

$$\begin{aligned} & \llbracket I \ s_0; \bigwedge s. I \ s \implies \textit{if } b \textit{val } b \ s \textit{ then } wlp \ c \ I \ s \textit{ else } Q \ s \rrbracket \\ & \implies wlp \ ( \textit{WHILE } b \ \textit{DO } c ) \ Q \ s_0 \end{aligned}$$

Wp\_Demo.thy

Weakest Precondition

Now we can start proving programs ...



Now we can start proving programs ...

$$P \ s \Longrightarrow \ wlp \ c \ Q \ s$$

Now we can start proving programs ...

$$P \ s \Longrightarrow \textit{wlp} \ c \ Q \ s$$

If  $c = \textit{WHILE} \ \_ \ \textit{DO} \ \_$ , provide invariant and apply while rule

Now we can start proving programs ...

$$P \ s \Longrightarrow \textit{wlp} \ c \ Q \ s$$

If  $c = \textit{WHILE} \ \_ \textit{DO} \ \_$ , provide invariant and apply while rule

Otherwise, use unfold rules.

Now we can start proving programs ...

$$P \ s \Longrightarrow \textit{wlp} \ c \ Q \ s$$

If  $c = \textit{WHILE} \ \_ \textit{DO} \ \_$ , provide invariant and apply while rule

Otherwise, use unfold rules.

Iterate, until all *wlps* gone!

$wlp\_if\_eq$  and  $wlp\_whileI'$  produce *if-then-else*

$wlp\_if\_eq$  and  $wlp\_whileI'$  produce *if-then-else* which we have to split.

*wlp\_if\_eq* and *wlp\_whileI'* produce *if-then-else*  
which we have to split.

Combine rule with splitting!

# Wp\_Demo.thy

Proving Partial Correctness



But how about termination?

But how about termination?

An (ordering) relation  $<$  is *well-founded*, iff every non-empty set has a minimal element.

But how about termination?

An (ordering) relation  $<$  is *well-founded*, iff every non-empty set has a minimal element.

Equivalently: No infinite sequence with  $x_1 > x_2 > \dots$

But how about termination?

An (ordering) relation  $<$  is *well-founded*, iff every non-empty set has a minimal element.

Equivalently: No infinite sequence with  $x_1 > x_2 > \dots$

Well-foundedness implies induction principle

But how about termination?

An (ordering) relation  $<$  is *well-founded*, iff every non-empty set has a minimal element.

Equivalently: No infinite sequence with  $x_1 > x_2 > \dots$

Well-foundedness implies induction principle

$$\frac{wf\ r \quad \bigwedge x. \frac{\forall y. (y, x) \in r \longrightarrow P\ y}{P\ x}}{P\ a}$$

Wellfounded\_Demo.thy

For while loop: Find  $wf$  relation  $<$  such that state decreases in each iteration

For while loop: Find  $wf$  relation  $<$  such that state decreases in each iteration

$$\bigwedge s. I\ s \implies \text{if } bval\ b\ s \text{ then } wp\ c\ (\lambda s'. I\ s' \wedge s' < s)\ s \\ \text{else } Q\ s$$



For while loop: Find  $wf$  relation  $<$  such that state decreases in each iteration

$$\bigwedge s. I\ s \implies \text{if } bval\ b\ s \text{ then } wp\ c\ (\lambda s'. I\ s' \wedge s' < s)\ s \\ \text{else } Q\ s$$

Then use wf-induction to prove:

$$\begin{aligned} & \llbracket wf\ R; I\ s_0; \\ & \bigwedge s. I\ s \implies \text{if } bval\ b\ s \text{ then } wp\ c\ (\lambda s'. I\ s' \wedge (s', s) \in \\ & R)\ s \text{ else } Q\ s \rrbracket \\ & \implies wp\ (WHILE\ b\ DO\ c)\ Q\ s_0 \end{aligned}$$

Or, equivalently

**assumes**  $WF: wf\ R$

**assumes**  $INIT: I\ s_0$

**assumes**  $STEP: \bigwedge s. \llbracket I\ s; bval\ b\ s \rrbracket$   
 $\implies wp\ c\ (\lambda s'. I\ s' \wedge (s', s) \in R)\ s$

**assumes**  $FINAL: \bigwedge s. \llbracket I\ s; \neg bval\ b\ s \rrbracket \implies Q\ s$

**shows**  $wp\ (WHILE\ b\ DO\ c)\ Q\ s_0$

Or, equivalently

**assumes**  $WF: wf\ R$

**assumes**  $INIT: I\ s_0$

**assumes**  $STEP: \bigwedge s. \llbracket I\ s; bval\ b\ s \rrbracket$   
 $\implies wp\ c\ (\lambda s'. I\ s' \wedge (s', s) \in R)\ s$

**assumes**  $FINAL: \bigwedge s. \llbracket I\ s; \neg bval\ b\ s \rrbracket \implies Q\ s$

**shows**  $wp\ (WHILE\ b\ DO\ c)\ Q\ s_0$

Now we can prove total correctness ...

Wp\_Demo.thy

Total Correctness

**lemma** *ASSUME\_Θ<sub>alt</sub>*:

$$ASSUME\_Θ \pi f_0 s_0 R \Theta = (\forall (f, (P, c, Q)) \in \Theta. HT' \pi (\lambda s. (f s, f_0 s_0) \in R \wedge P s) c Q)$$

**unfolding** *ASSUME\_* $\Theta$ *\_def HT'set\_r\_def ..*

- ④ Weakest Preconditions
- ⑤ Towards Simpler Verification of Programs
- ⑥ Example Verifications
- ⑦ Advanced Verification

Let's make our VCG more usable

Let's make our VCG more usable

Add standard arithmetic operators to IMP



Let's make our VCG more usable

Add standard arithmetic operators to IMP

Add nice syntax for programs

Let's make our VCG more usable

Add standard arithmetic operators to IMP

Add nice syntax for programs

Make VCs more readable

Let's make our VCG more usable

Add standard arithmetic operators to IMP

Add nice syntax for programs

Make VCs more readable

Simplify specification of pre/postcondition, and  
invariants

# Standard operators

We add generic syntax for any unary/binary operator

# Standard operators

We add generic syntax for any unary/binary operator

$$Unop::(int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp$$

# Standard operators

We add generic syntax for any unary/binary operator

$$Unop::(int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp$$
$$Binop::(int \Rightarrow int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp \Rightarrow aexp$$

# Standard operators

We add generic syntax for any unary/binary operator

$$Unop::(int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp$$
$$Binop::(int \Rightarrow int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp \Rightarrow aexp$$
$$Cmpop::(int \Rightarrow int \Rightarrow bool) \Rightarrow aexp \Rightarrow aexp \Rightarrow bexp$$

# Standard operators

We add generic syntax for any unary/binary operator

$Unop::(int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp$

$Binop::(int \Rightarrow int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp \Rightarrow aexp$

$Cmpop::(int \Rightarrow int \Rightarrow bool) \Rightarrow aexp \Rightarrow aexp \Rightarrow bexp$

$BBinop::(bool \Rightarrow bool \Rightarrow bool) \Rightarrow bexp \Rightarrow bexp \Rightarrow bexp$



# Standard operators

We add generic syntax for any unary/binary operator

$Unop::(int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp$

$Binop::(int \Rightarrow int \Rightarrow int) \Rightarrow aexp \Rightarrow aexp \Rightarrow aexp$

$Cmpop::(int \Rightarrow int \Rightarrow bool) \Rightarrow aexp \Rightarrow aexp \Rightarrow bexp$

$BBinop::(bool \Rightarrow bool \Rightarrow bool) \Rightarrow bexp \Rightarrow bexp \Rightarrow bexp$

For example:

$Cmpop (\leq) (Binop (+) (Unop uminus (V "x"))) (N 42)) (N 50)$

# IMP2/Introduction.thy

Adding more Operators

# C-like syntax

## Operators

# C-like syntax

## Operators

Arith:  $+$ ,  $-$ ,  $*$ ,  $/$  with usual binding

# C-like syntax

## Operators

Arith:  $+, -, *, /$  with usual binding

Boolean:  $\neg, \wedge, \vee$  and  $=, \neq, \leq, <, >, \geq$

# C-like syntax

## Operators

Arith:  $+, -, *, /$  with usual binding

Boolean:  $\neg, \wedge, \vee$  and  $=, \neq, \leq, <, >, \geq$

## Commands

# C-like syntax

## Operators

Arith:  $+, -, *, /$  with usual binding

Boolean:  $\neg, \wedge, \vee$  and  $=, \neq, \leq, <, >, \geq$

## Commands

*skip*,  $v = aexp$ ,  $\{c\}$ ,  $c_1; c_2$

# C-like syntax

## Operators

Arith:  $+, -, *, /$  with usual binding

Boolean:  $\neg, \wedge, \vee$  and  $=, \neq, \leq, <, >, \geq$

## Commands

*skip*,  $v = aexp$ ,  $\{c\}$ ,  $c_1; c_2$

*if bexp then*  $c_1$  [*else*  $c_2$ ]



# C-like syntax

## Operators

Arith:  $+, -, *, /$  with usual binding

Boolean:  $\neg, \wedge, \vee$  and  $=, \neq, \leq, <, >, \geq$

## Commands

*skip*,  $v = aexp$ ,  $\{c\}$ ,  $c_1; c_2$

*if bexp then*  $c_1$  [*else*  $c_2$ ]    else part is optional

# C-like syntax

## Operators

Arith:  $+, -, *, /$  with usual binding

Boolean:  $\neg, \wedge, \vee$  and  $=, \neq, \leq, <, >, \geq$

## Commands

*skip*,  $v = aexp$ ,  $\{c\}$ ,  $c_1; c_2$

*if bexp then*  $c_1$  [*else*  $c_2$ ]     else part is optional

*while* ( $bexp$ )  $c$

# IMP2/Introduction.thy

Program Syntax

## More Readable VCs

Idea: Replace  $s$  " $x$ " by (Isabelle) variable  $x$ .

## More Readable VCs

Idea: Replace  $s \text{ ''}x\text{'}$  by (Isabelle) variable  $x$ .

Similar:  $s_0 \text{ ''}x\text{'}$  by  $x_0$ .

## More Readable VCs

Idea: Replace  $s \text{ ''}x\text{''}$  by (Isabelle) variable  $x$ .

Similar:  $s_0 \text{ ''}x\text{''}$  by  $x_0$ .

If subgoal can still be proved for arbitrary (Isabelle) variable  $x$ , it can, in particular, be proved for  $s \text{ ''}x\text{''}$ .

$$(\bigwedge x. P \ x) \Longrightarrow P \ (s \text{ ''}x\text{''})$$

# IMP2/Introduction.thy

More Readable VCs

# More Readable Annotations

Can we do similar trick for pre/postconditions and invariants?



# More Readable Annotations

Can we do similar trick for pre/postconditions and invariants?

E.g. write  $c \leq n_0 \wedge a = c * c$  for

$$s \text{ ''}c\text{''} \leq s_0 \text{ ''}n\text{''} \wedge s \text{ ''}a\text{''} = s \text{ ''}c\text{''} * s \text{ ''}c\text{''}$$

# More Readable Annotations

Can we do similar trick for pre/postconditions and invariants?

E.g. write  $c \leq n_0 \wedge a = c * c$  for

$$s \text{ ''}c\text{''} \leq s_0 \text{ ''}n\text{''} \wedge s \text{ ''}a\text{''} = s \text{ ''}c\text{''} * s \text{ ''}c\text{''}$$

Which variables to interpret?

# More Readable Annotations

Can we do similar trick for pre/postconditions and invariants?

E.g. write  $c \leq n_0 \wedge a = c * c$  for

$$s \text{ ''}c\text{''} \leq s_0 \text{ ''}n\text{''} \wedge s \text{ ''}a\text{''} = s \text{ ''}c\text{''} * s \text{ ''}c\text{''}$$

Which variables to interpret? over which states?

# More Readable Annotations

Can we do similar trick for pre/postconditions and invariants?

E.g. write  $c \leq n_0 \wedge a = c * c$  for

$$s \text{ ''}c\text{''} \leq s_0 \text{ ''}n\text{''} \wedge s \text{ ''}a\text{''} = s \text{ ''}c\text{''} * s \text{ ''}c\text{''}$$

Which variables to interpret? over which states?

All variables that occur in the program!

# More Readable Annotations

Can we do similar trick for pre/postconditions and invariants?

E.g. write  $c \leq n_0 \wedge a = c * c$  for

$$s \text{ ''}c\text{''} \leq s_0 \text{ ''}n\text{''} \wedge s \text{ ''}a\text{''} = s \text{ ''}c\text{''} * s \text{ ''}c\text{''}$$

Which variables to interpret? over which states?

All variables that occur in the program!

Precondition:  $x$  interpreted as  $s \text{ ''}x\text{''}$

# More Readable Annotations

Can we do similar trick for pre/postconditions and invariants?

E.g. write  $c \leq n_0 \wedge a = c * c$  for

$$s \text{ ''}c\text{''} \leq s_0 \text{ ''}n\text{''} \wedge s \text{ ''}a\text{''} = s \text{ ''}c\text{''} * s \text{ ''}c\text{''}$$

Which variables to interpret? over which states?

All variables that occur in the program!

Precondition:  $x$  interpreted as  $s \text{ ''}x\text{''}$

Postcondition/Invariant:  $x$  as  $s \text{ ''}x\text{''}$ ,  $x_0$  as  $s_0 \text{ ''}x\text{''}$

# IMP2/Introduction.thy

More Readable Annotations

- ④ Weakest Preconditions
- ⑤ Towards Simpler Verification of Programs
- ⑥ Example Verifications
- ⑦ Advanced Verification



## ⑥ Example Verifications

Loop Patterns

Euclid's Algorithm

# Common Loop Patterns

We've seen a few loop's already:

# Common Loop Patterns

We've seen a few loop's already:

$a=1; c=0; \text{ while } (c < n) \{ a=2*a; c=c+1 \}$

Compute operation by iterating weaker operation

# Common Loop Patterns

We've seen a few loop's already:

$a=1; c=0; \text{ while } (c < n) \{ a=2*a; c=c+1 \}$

Compute operation by iterating weaker operation

e.g.  $2^n = 2 * \dots * 2$

# Common Loop Patterns

We've seen a few loop's already:

$a=1; c=0; \text{ while } (c < n) \{ a=2*a; c=c+1 \}$

Compute operation by iterating weaker operation

e.g.  $2^n = 2 * \dots * 2$

Use accumulator  $a$  and increment counter (count-up)

# Common Loop Patterns

We've seen a few loop's already:

$a=1; c=0; \text{ while } (c < n) \{ a=2*a; c=c+1 \}$

Compute operation by iterating weaker operation

e.g.  $2^n = 2 * \dots * 2$

Use accumulator  $a$  and increment counter (count-up)

Or decrement counter (e.g.  $n$ ) (count down)

# Common Loop Patterns

We've seen a few loop's already:

$a=1; c=0; \text{ while } (c < n) \{ a=2*a; c=c+1 \}$

Compute operation by iterating weaker operation

e.g.  $2^n = 2 * \dots * 2$

Use accumulator  $a$  and increment counter (count-up)

Or decrement counter (e.g.  $n$ ) (count down)

Invariant:  $a = 2^c \wedge \dots$  (accumulator = f(iterations))

# Common Loop Patterns

We've seen a few loop's already:

$a=1; c=0; \text{ while } (c < n) \{ a=2*a; c=c+1 \}$

Compute operation by iterating weaker operation

e.g.  $2^n = 2 * \dots * 2$

Use accumulator  $a$  and increment counter (count-up)

Or decrement counter (e.g.  $n$ ) (count down)

Invariant:  $a = 2^c \wedge \dots$  (accumulator = f(iterations))

Applications:  $*$  by  $+$ , exp, Fibonacci, factorial, ...



# IMP2/Examples.thy

Count-up, Count-Down

# Approximate Naively

Invert monotonic function, by naively trying all values:

# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while* ( $r*r \leq n$ ) {  $r=r+1$  };  $r=r-1$

# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while* ( $r*r \leq n$ ) {  $r=r+1$  };  $r=r-1$

What does this compute

# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while* ( $r*r \leq n$ ) {  $r=r+1$  };  $r=r-1$

What does this compute?

# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while* ( $r*r \leq n$ ) {  $r=r+1$  };  $r=r-1$

What does this compute? square root, rounded down!

# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while* ( $r*r \leq n$ ) {  $r=r+1$  };  $r=r-1$

What does this compute? square root, rounded down!

Idea: Iterate until we overshoot by one. Then decrement.

# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while* ( $r*r \leq n$ ) {  $r=r+1$  };  $r=r-1$

What does this compute? square root, rounded down!

Idea: Iterate until we overshoot by one. Then decrement.

Invariant:



# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while* ( $r*r \leq n$ ) {  $r=r+1$  };  $r=r-1$

What does this compute? square root, rounded down!

Idea: Iterate until we overshoot by one. Then decrement.

Invariant: ?

# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while*  $(r*r \leq n)$   $\{r=r+1\}$ ;  $r=r-1$

What does this compute? square root, rounded down!

Idea: Iterate until we overshoot by one. Then decrement.

Invariant:  $?$   $(r-1)^2 \leq n \wedge \dots$  ( $r-1$  below or equal result)

# Approximate Naively

Invert monotonic function, by naively trying all values:

$r=1$ ; *while*  $(r*r \leq n)$   $\{r=r+1\}$ ;  $r=r-1$

What does this compute? square root, rounded down!

Idea: Iterate until we overshoot by one. Then decrement.

Invariant:  $?$   $(r-1)^2 \leq n \wedge \dots$  ( $r-1$  below or equal result)

Applications: sqrt, log, ...

# IMP2/Examples.thy

Approximate from Below

# Bisection

We can compute  $\text{sqrt}$  more efficiently.

# Bisection

We can compute sqrt more efficiently.

```
l=0; h=n+1;
while (l+1 < h)
  m = (l + h) / 2;
  if m*m ≤ n then l=m else h=m
;
r=l
```

# Bisection

We can compute sqrt more efficiently.

```
l=0; h=n+1;
while (l+1 < h)
    m = (l + h) / 2;
    if m*m ≤ n then l=m else h=m
;
r=l
```

Idea: Half range in each step

# Bisection

We can compute sqrt more efficiently.

```
l=0; h=n+1;
while (l+1 < h)
    m = (l + h) / 2;
    if m*m ≤ n then l=m else h=m
;
r=l
```

Idea: Half range in each step

Invariant



# Bisection

We can compute sqrt more efficiently.

```
l=0; h=n+1;  
while (l+1 < h)  
    m = (l + h) / 2;  
    if m*m ≤ n then l=m else h=m  
;  
r=l
```

Idea: Half range in each step

Invariant?

# Bisection

We can compute sqrt more efficiently.

```
l=0; h=n+1;
while (l+1 < h)
  m = (l + h) / 2;
  if m*m ≤ n then l=m else h=m
;
r=l
```

Idea: Half range in each step

Invariant?  $l^2 \leq n < h^2 \wedge \dots$  (range contains solution)

# Bisection

We can compute sqrt more efficiently.

```
l=0; h=n+1;
while (l+1 < h)
    m = (l + h) / 2;
    if m*m ≤ n then l=m else h=m
;
r=l
```

Idea: Half range in each step

Invariant?  $l^2 \leq n < h^2 \wedge \dots$  (range contains solution)

This program is actually tricky to get right!

# IMP2/Examples.thy

Bisection

## ⑥ Example Verifications

Loop Patterns

Euclid's Algorithm

# Euclid Intro

Compute gcd of positive numbers  $a, b$

# Euclid Intro

Compute gcd of positive numbers  $a, b$

Reminder: Divides:  $(b \text{ dvd } a) = (\exists k. a = b * k)$

Greatest Common Divisor:  $gcd::int \Rightarrow int \Rightarrow int$  such that

$gcd\ a\ b\ \text{dvd}\ a$  and  $gcd\ a\ b\ \text{dvd}\ b$  and

$\llbracket a \neq 0; b \neq 0; c\ \text{dvd}\ a; c\ \text{dvd}\ b \rrbracket \implies c \leq gcd\ a\ b$

# Euclid Variants

By subtraction. Using  $\gcd(m - n, n) = \gcd(m, n)$



# Euclid Variants

By subtraction. Using  $\gcd(m - n) \ n = \gcd \ m \ n$

By modulo. Using:  $\gcd \ x \ y = \gcd \ y \ (x \bmod y)$

# IMP2/Examples.thy

Euclid

- ④ Weakest Preconditions
- ⑤ Towards Simpler Verification of Programs
- ⑥ Example Verifications
- ⑦ Advanced Verification

# Modified Variables

Program:  $a=1; i=0; \text{while } (i < n) \{ a=a*2; i=i+1 \}$

## Modified Variables

Program:  $a=1; i=0; \text{while } (i < n) \{ a=a*2; i=i+1 \}$

Pre:  $n \geq 0$  Post:  $a = 2^{n_0}$

## Modified Variables

Program:  $a=1; i=0; \text{while } (i < n) \{ a=a*2; i=i+1 \}$

Pre:  $n \geq 0$  Post:  $a = 2^{n_0}$  and only  $a, i$  changed.

## Modified Variables

Program:  $a=1; i=0; \text{while } (i < n) \{ a=a*2; i=i+1 \}$

Pre:  $n \geq 0$  Post:  $a = 2^{n_0}$  and only  $a, i$  changed.

Invariant:  $a = 2^i \wedge 0 \leq i \wedge i \leq n$  and only  $a, i$  changed.

## Modified Variables

Program:  $a=1; i=0; \text{while } (i < n) \{ a=a*2; i=i+1 \}$

Pre:  $n \geq 0$  Post:  $a = 2^{n_0}$  and only  $a, i$  changed.

Invariant:  $a = 2^i \wedge 0 \leq i \wedge i \leq n$  and only  $a, i$  changed.

Only  $a, i$  changed:  $\forall x. x \notin \{ "a", "i" \} \longrightarrow s\ x = s'\ x$



## Modified Variables

Program:  $a=1; i=0; \text{while } (i < n) \{ a=a*2; i=i+1 \}$

Pre:  $n \geq 0$  Post:  $a = 2^i n_0$  and only  $a, i$  changed.

Invariant:  $a = 2^i \wedge 0 \leq i \wedge i \leq n$  and only  $a, i$  changed.

Only  $a, i$  changed:  $\forall x. x \notin \{ "a", "i" \} \longrightarrow s \ x = s' \ x$

*modifies vars*  $s_1 \ s_2 = (\forall x. x \notin \text{vars} \longrightarrow s_1 \ x = s_2 \ x)$

# Modified Variables

Program:  $a=1; i=0; \text{while } (i < n) \{ a=a*2; i=i+1 \}$

Pre:  $n \geq 0$  Post:  $a = 2^{i_0}$  and only  $a, i$  changed.

Invariant:  $a = 2^i \wedge 0 \leq i \wedge i \leq n$  and only  $a, i$  changed.

Only  $a, i$  changed:  $\forall x. x \notin \{ "a", "i" \} \longrightarrow s \ x = s' \ x$

*modifies vars*  $s_1 \ s_2 = (\forall x. x \notin \text{vars} \longrightarrow s_1 \ x = s_2 \ x)$

Program modifies at most variables it assigns to

$\pi: (c, s) \Rightarrow t \implies \text{modifies} (\text{lhsv } \pi \ c) \ t \ s$

## Modified Variables

We can strengthen correctness statement (automatically)

$$wp \ \pi \ c \ Q \ s \Longrightarrow wp \ \pi \ c \ (\lambda s'. Q \ s' \wedge \text{modifies} \ (lhsv \ \pi \ c) \ s' \ s) \ s$$

# Modified Variables

We can strengthen correctness statement (automatically)

$$wp \ \pi \ c \ Q \ s \Longrightarrow wp \ \pi \ c \ (\lambda s'. Q \ s' \wedge \text{modifies} \ (lhsv \ \pi \ c) \ s' \ s) \ s$$

For while-rule, we get

**lemma** *wp\_whileI\_modset*:

**fixes** *c*

**defines** [*simp*]: *modset*  $\equiv$  *lhsv c*

**assumes** *WF*: *wf R*

**assumes** *INIT*: *I s<sub>0</sub>*

**assumes** *STEP*:  $\bigwedge s. \llbracket \text{modifies modset } s \ s_0; I \ s; bval \ b \ s \rrbracket$

$\Longrightarrow wp \ c \ (\lambda s'. I \ s' \wedge (s', s) \in R) \ s$

**assumes** *FINAL*:  $\bigwedge s. \llbracket \text{modifies modset } s \ s_0; I \ s; \neg bval \ b \ s \rrbracket$

$\Longrightarrow Q \ s$

**shows** *wp (WHILE b DO c) Q s<sub>0</sub>*

# Modified Variables

The VCG will automatically rewrite with rule

$$\llbracket \textit{modifies } vs \ s \ s'; \ x \notin \ vs \rrbracket \Longrightarrow \ s \ x = \ s' \ x$$

# Modified Variables

The VCG will automatically rewrite with rule

$$\llbracket \textit{modifies } vs \ s \ s'; x \notin vs \rrbracket \implies s \ x = s' \ x$$

**program\_spec** computes *lhs*-variables:

$$HT\_mods \ \pi \ mods \ P \ c \ Q \equiv HT \ \pi \ P \ c \ (\lambda s_0 \ s. \ \textit{modifies} \\ mods \ s \ s_0 \wedge Q \ s_0 \ s)$$

# IMP2/Examples.thy

Euclid – show modified sets

# Modular Proofs

Consider program

```
a=1;  
while (m>0) {  
  n=a; a = 1;  
  while (n>0) {  
    a=2*a; n=n-1  
  };  
  m=m-1  
}
```

What does this compute



# Modular Proofs

Consider program

```
a=1;  
while (m>0) {  
  n=a; a = 1;  
  while (n>0) {  
    a=2*a; n=n-1  
  };  
  m=m-1  
}
```

What does this compute?

# Modular Proofs

Consider program

```
a=1;
while (m>0) {
  n=a; a = 1;
  while (n>0) {
    a=2*a; n=n-1
  };
  m=m-1
}
```

What does this compute?

Power-tower function:  $2^{2^{\cdot^{\cdot^2}}}$  ( $m$  times)

# Modular Proofs

Inner loop invariant: Would like to refer to  $n$  right before loop!

# Modular Proofs

Inner loop invariant: Would like to refer to  $n$  right before loop!

In our simple VCG, we can't!

# Modular Proofs

Inner loop invariant: Would like to refer to  $n$  right before loop!

In our simple VCG, we can't!

Still, we already have verified inner loop!

# Modular Proofs

Inner loop invariant: Would like to refer to  $n$  right before loop!

In our simple VCG, we can't!

Still, we already have verified inner loop!

Idea: Split and verify separately!

# Modular Proofs

```
a=1;  
while (m>0) {  
  n=a;  
  inline exp_count_down;  
  m=m−1  
}
```

# Modular Proofs

```
a=1;  
while (m>0) {  
  n=a;  
  inline exp_count_down;  
  m=m-1  
}
```

Reuse existing proof of exp-count-down program!



# Modular Proofs

Re-using proofs:

# Modular Proofs

Re-using proofs:

$$\begin{aligned} & \llbracket HT \pi P c Q; \bigwedge s. P' s \implies P s; \bigwedge s_0 s. \llbracket P s_0; P' s_0; Q \\ & s_0 s \rrbracket \implies Q' s_0 s \rrbracket \\ & \implies HT \pi P' c Q' \end{aligned}$$

# Modular Proofs

Re-using proofs:

$$\begin{aligned} & \llbracket HT \ \pi \ P \ c \ Q; \bigwedge s. P' \ s \implies P \ s; \bigwedge s_0 \ s. \llbracket P \ s_0; P' \ s_0; Q \\ & \ s_0 \ s \rrbracket \implies Q' \ s_0 \ s \rrbracket \\ & \implies HT \ \pi \ P' \ c \ Q' \end{aligned}$$

with modified sets:

$$\begin{aligned} & \llbracket HT\_mods \ \pi \ mods \ P \ c \ Q; P \ s; \bigwedge s'. \llbracket modifies \ mods \ s' \\ & \ s; Q \ s \ s' \rrbracket \implies Q' \ s' \rrbracket \\ & \implies wp \ \pi \ c \ Q' \ s \end{aligned}$$

# Modular Proofs

Re-using proofs:

$$\begin{aligned} & \llbracket HT \ \pi \ P \ c \ Q; \bigwedge s. P' \ s \implies P \ s; \bigwedge s_0 \ s. \llbracket P \ s_0; P' \ s_0; Q \\ & \ s_0 \ s \rrbracket \implies Q' \ s_0 \ s \rrbracket \\ & \implies HT \ \pi \ P' \ c \ Q' \end{aligned}$$

with modified sets:

$$\begin{aligned} & \llbracket HT\_mods \ \pi \ mods \ P \ c \ Q; P \ s; \bigwedge s'. \llbracket modifies \ mods \ s' \\ & \ s; Q \ s \ s' \rrbracket \implies Q' \ s' \rrbracket \\ & \implies wp \ \pi \ c \ Q' \ s \end{aligned}$$

VCG will automatically use this rule.

# Modular Proofs

Re-using proofs:

$$\begin{aligned} & \llbracket HT \ \pi \ P \ c \ Q; \bigwedge s. P' \ s \implies P \ s; \bigwedge s_0 \ s. \llbracket P \ s_0; P' \ s_0; Q \\ & \ s_0 \ s \rrbracket \implies Q' \ s_0 \ s \rrbracket \\ & \implies HT \ \pi \ P' \ c \ Q' \end{aligned}$$

with modified sets:

$$\begin{aligned} & \llbracket HT\_mods \ \pi \ mods \ P \ c \ Q; P \ s; \bigwedge s'. \llbracket modifies \ mods \ s' \\ & \ s; Q \ s \ s' \rrbracket \implies Q' \ s' \rrbracket \\ & \implies wp \ \pi \ c \ Q' \ s \end{aligned}$$

VCG will automatically use this rule.

If inlined program has been proved with **program\_spec**

# IMP2/Examples.thy

Power-Tower

## ⑦ Advanced Verification

Arrays

Data Refinement

Local Variables

Recursion

# Arrays

Every variable is of type  $int \Rightarrow int$ .



# Arrays

Every variable is of type  $int \Rightarrow int$ .

Arithmetic Expressions:

$Vidx::char\ list \Rightarrow aexp \Rightarrow aexp$   
 $aval\ (Vidx\ x\ i)\ s = s\ x\ (aval\ i\ s)$

# Arrays

Every variable is of type  $int \Rightarrow int$ .

Arithmetic Expressions:

$Vidx::char\ list \Rightarrow aexp \Rightarrow aexp$   
 $aval\ (Vidx\ x\ i)\ s = s\ x\ (aval\ i\ s)$

Commands:

$AssignIdx::char\ list \Rightarrow aexp \Rightarrow aexp \Rightarrow com$   
 $\pi: (x[i] ::= a, s) \Rightarrow s(x := (s\ x)(aval\ i\ s := aval\ a\ s))$

# Arrays

Every variable is of type  $int \Rightarrow int$ .

Arithmetic Expressions:

$Vidx::char\ list \Rightarrow aexp \Rightarrow aexp$   
 $aval\ (Vidx\ x\ i)\ s = s\ x\ (aval\ i\ s)$

Commands:

$AssignIdx::char\ list \Rightarrow aexp \Rightarrow aexp \Rightarrow com$   
 $\pi: (x[i] ::= a, s) \Rightarrow s(x := (s\ x)(aval\ i\ s := aval\ a\ s))$   
 $ArrayCpy::char\ list \Rightarrow char\ list \Rightarrow com$   
 $\pi: (x[] ::= y, s) \Rightarrow s(x := s\ y)$

# Arrays

Every variable is of type  $int \Rightarrow int$ .

Arithmetic Expressions:

$Vidx::char\ list \Rightarrow aexp \Rightarrow aexp$   
 $aval\ (Vidx\ x\ i)\ s = s\ x\ (aval\ i\ s)$

Commands:

$AssignIdx::char\ list \Rightarrow aexp \Rightarrow aexp \Rightarrow com$   
 $\pi: (x[i] ::= a, s) \Rightarrow s(x := (s\ x)(aval\ i\ s := aval\ a\ s))$

$ArrayCpy::char\ list \Rightarrow char\ list \Rightarrow com$   
 $\pi: (x[] ::= y, s) \Rightarrow s(x := s\ y)$

$ArrayClear::char\ list \Rightarrow com$   
 $\pi: (CLEAR\ x[], s) \Rightarrow s(x := \lambda_.\ 0)$

# Arrays

By default, we use index 0.

# Arrays

By default, we use index 0.

Abbreviations:

$$V\ x = \text{Vidx}\ x\ (N\ 0)$$

# Arrays

By default, we use index 0.

Abbreviations:

$$V\ x = Vid\ x\ (N\ 0)$$

$$Assign\ x\ a = AssignIdx\ x\ (N\ 0)\ a$$

# Arrays

By default, we use index 0.

Abbreviations:

$$V\ x = Vid\ x\ (N\ 0)$$

$$Assign\ x\ a = AssignIdx\ x\ (N\ 0)\ a$$



# Arrays

By default, we use index 0.

Abbreviations:

$$V\ x = Vid\ x\ (N\ 0)$$

$$Assign\ x\ a = AssignIdx\ x\ (N\ 0)\ a$$

VCG: Guess type from variable usage

# Arrays

By default, we use index 0.

Abbreviations:

$$V\ x = Vid\ x\ (N\ 0)$$
$$Assign\ x\ a = AssignIdx\ x\ (N\ 0)\ a$$

VCG: Guess type from variable usage

Only with index 0: Bind  $VAR\ (s\ "x"\ 0)\ (\lambda x. \dots)$

# Arrays

By default, we use index 0.

Abbreviations:

$V\ x = Vid\ x\ (N\ 0)$

$Assign\ x\ a = AssignIdx\ x\ (N\ 0)\ a$

VCG: Guess type from variable usage

Only with index 0:  $Bind\ VAR\ (s\ "x"\ 0)\ (\lambda x. \dots)$

Otherwise:  $Bind\ VAR\ (s\ "x")\ (\lambda x. \dots)$

# Arrays

By default, we use index 0.

Abbreviations:

$V\ x = Vid\ x\ (N\ 0)$

$Assign\ x\ a = AssignIdx\ x\ (N\ 0)\ a$

VCG: Guess type from variable usage

Only with index 0:  $Bind\ VAR\ (s\ "x"\ 0)\ (\lambda x. \dots)$

Otherwise:  $Bind\ VAR\ (s\ "x")\ (\lambda x. \dots)$

# IMP2/Examples.thy

Array-Sum

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

Examples:

$\forall i \in \{0..<42\}. a\ i > 0$



# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

Examples:

$\forall i \in \{0..<42\}. a[i] > 0$  means?

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

Examples:

$\forall i \in \{0..<42\}. a\ i > 0$  means?

Elements 0 to 41 are positive

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

Examples:

$\forall i \in \{0..<42\}. a\ i > 0$  means?

Elements 0 to 41 are positive

$\forall i \in \{l..<h\}. \forall j \in \{l..<h\}. i \leq j \longrightarrow a\ i \leq a\ j$

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

Examples:

$\forall i \in \{0..<42\}. a\ i > 0$  means?

Elements 0 to 41 are positive

$\forall i \in \{l..<h\}. \forall j \in \{l..<h\}. i \leq j \longrightarrow a\ i \leq a\ j$  means?

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

Examples:

$\forall i \in \{0..<42\}. a\ i > 0$  means?

Elements 0 to 41 are positive

$\forall i \in \{l..<h\}. \forall j \in \{l..<h\}. i \leq j \longrightarrow a\ i \leq a\ j$  means?

Elements  $l$  to  $<h$  are sorted

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

Examples:

$\forall i \in \{0..<42\}. a\ i > 0$  means?

Elements 0 to 41 are positive

$\forall i \in \{l..<h\}. \forall j \in \{l..<h\}. i \leq j \longrightarrow a\ i \leq a\ j$  means?

Elements  $l$  to  $<h$  are sorted

# Reasoning about Arrays

Usually, use function  $int \Rightarrow int$  directly.

Set interval notation:

$\{l..h\}$ ,  $\{l..<h\}$ ,  $\{l<..h\}$ ,  $\{l<..<h\}$

Examples:

$\forall i \in \{0..<42\}. a\ i > 0$  means?

Elements 0 to 41 are positive

$\forall i \in \{l..<h\}. \forall j \in \{l..<h\}. i \leq j \longrightarrow a\ i \leq a\ j$  means?

Elements  $l$  to  $<h$  are sorted

Theory *IMP2/IMP2\_Aux\_Lemmas* provides useful lemmas and definitions

# IMP2/Examples.thy

Sortedness Check



# Binary Search Algorithm

Find element in sorted array. In time  $O(\log n)$ .

# Binary Search Algorithm

Find element in sorted array. In time  $O(\log n)$ .

Idea: Halve interval in each step.

# Binary Search Algorithm

Find element in sorted array. In time  $O(\log n)$ .

Idea: Halve interval in each step.

This algorithm is **tricky** to implement correctly!

# Binary Search Algorithm

Find element in sorted array. In time  $O(\log n)$ .

Idea: Halve interval in each step.

This algorithm is **tricky** to implement correctly!

*Although the basic idea of binary search is comparatively straightforward, the details can be surprisingly tricky ...*

— Donald Knuth

# Binary Search Algorithm

Find element in sorted array. In time  $O(\log n)$ .

Idea: Halve interval in each step.

This algorithm is *tricky* to implement correctly!

*Although the basic idea of binary search is comparatively straightforward, the details can be surprisingly tricky ...*

— Donald Knuth

Only 5 out of 20 surveyed textbooks had correct implementations


— Richard E. Pattis, 1988

# Binary Search Algorithm

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$


```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

# Binary Search Algorithm



```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

# Binary Search Algorithm



```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```




# Binary Search Algorithm

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$
					$\uparrow$		$\uparrow$		
					$l$		$h$		

```
while ( $l < h$ ) {  
     $m = (l + h) / 2$ ;  
    if ( $a[m] < x$ )  $l = m + 1$   
    else  $h = m$   
}
```

# Binary Search Algorithm



```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

# Binary Search Algorithm

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$
					$l$	$h$			

```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

# Binary Search Algorithm

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$

$\uparrow$        $\uparrow$   
 $l$        $h$

```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

# Binary Search Algorithm

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$

↑  
 $l, h$

```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

# Binary Search Algorithm

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$

↑  
 $l, h$

```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

Returns **smallest**  $i$  with  $x \leq a[i]$

## Notes on Binary Search

```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

## Notes on Binary Search

```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

Note: Our language has arbitrary large integers.



# Notes on Binary Search

```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

Note: Our language has arbitrary large integers.

Otherwise,  $m = (l + h)/2$  may overflow!

## Notes on Binary Search

```
while (l < h) {  
    m = (l + h) / 2;  
    if (a[m] < x) l = m + 1  
    else h = m  
}
```

Note: Our language has arbitrary large integers.

Otherwise,  $m = (l + h)/2$  may overflow!

Bug in Java Standard Library for  $> 9$  years!

# Proving Binary Search

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$
					$\uparrow$	$\uparrow$			
					$l$	$h$			

Invariant:

# Proving Binary Search

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$
					$\uparrow$	$\uparrow$			
					$l$	$h$			

Invariant:

- $i < l \implies a[i] < x$  (strictly smaller than  $x$ )

# Proving Binary Search

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$
					$\uparrow$	$\uparrow$			
					$l$	$h$			

Invariant:

- $i < l \implies a[i] < x$  (strictly smaller than  $x$ )
- $i \geq h \implies x \leq a[i]$  (greater or equal to  $x$ )

# Proving Binary Search

0	1	2	3	4	5	6	7	8	
2	3	5	7	11	13	17	19		$x = 13$
					$\uparrow$	$\uparrow$			
					$l$	$h$			

Invariant:

- $i < l \implies a[i] < x$  (strictly smaller than  $x$ )
- $i \geq h \implies x \leq a[i]$  (greater or equal to  $x$ )
- and the usual bounds

# IMP2/Examples.thy

Binary Search

# Insertion Sort

```
j = l + 1;
while (j < h) {
    key = a[j];
    i = j - 1;
    while (i >= l && a[i] > key) {
        a[i + 1] = a[i];
        i = i - 1;
    };
    a[i + 1] = key;
    j = j + 1;
}
```

Idea: Build sorted array from start.

In each iteration, move next element to its position



# Specifying Sorting Algorithms

Precondition:  $l \leq h$

# Specifying Sorting Algorithms

Precondition:  $l \leq h$

Postcondition:

# Specifying Sorting Algorithms

Precondition:  $l \leq h$

Postcondition:

- Array is sorted

# Specifying Sorting Algorithms

Precondition:  $l \leq h$

Postcondition:

- Array is sorted *ran\_sorted a l h*

# Specifying Sorting Algorithms

Precondition:  $l \leq h$

Postcondition:

- Array is sorted *ran\_sorted a l h*
- Array contains same elements

# Specifying Sorting Algorithms

Precondition:  $l \leq h$

Postcondition:

- Array is sorted *ran\_sorted a l h*
- Array contains same elements  
 $mset\_ran\ a\ \{l..<h\} = mset\_ran\ a_0\ \{l..<h\}$

# Specifying Sorting Algorithms

Precondition:  $l \leq h$

Postcondition:

- Array is sorted *ran\_sorted a l h*
- Array contains same elements  
 $mset\_ran\ a\ \{l..<h\} = mset\_ran\ a_0\ \{l..<h\}$

# Specifying Sorting Algorithms

Precondition:  $l \leq h$

Postcondition:

- Array is sorted  $ran\_sorted\ a\ l\ h$
- Array contains same elements  
 $mset\_ran\ a\ \{l..<h\} = mset\_ran\ a_0\ \{l..<h\}$

where

$$ran\_sorted\ a\ l\ h \equiv \forall i \in \{l..<h\}. \forall j \in \{l..<h\}. i \leq j \longrightarrow a\ i \leq a\ j$$

$$mset\_ran\ a\ r = (\sum_{i \in r}. \{\#a\ i\# \})$$



# Multisets in Isabelle

**imports** *HOL–Library.Multiset*

# Multisets in Isabelle

**imports** *HOL–Library.Multiset*

*'a multiset*: **Finite** multiset

# Multisets in Isabelle

**imports** *HOL–Library.Multiset*

*'a multiset*: **Finite** multiset

Some functions and syntax:

# Multisets in Isabelle

**imports** *HOL-Library.Multiset*

*'a multiset*: **Finite** multiset

Some functions and syntax:

$\{\#\}$  — empty multiset

# Multisets in Isabelle

**imports** *HOL-Library.Multiset*

*'a multiset*: **Finite** multiset

Some functions and syntax:

$\{\#\}$  — empty multiset

*add\_mset*  $x\ m$  — add element (cf. *insert* on sets)

# Multisets in Isabelle

**imports** *HOL-Library.Multiset*

*'a multiset*: **Finite** multiset

Some functions and syntax:

$\{\#\}$  — empty multiset

*add\_mset*  $x\ m$  — add element (cf. *insert* on sets)

$m_1 + m_2$  — union of multisets

# Multisets in Isabelle

**imports** *HOL-Library.Multiset*

'a multiset: **Finite** multiset

Some functions and syntax:

$\{\#\}$  — empty multiset

*add\_mset*  $x\ m$  — add element (cf. *insert* on sets)

$m_1 + m_2$  — union of multisets

$a \in\# m$  — membership query

# Multisets in Isabelle

**imports** *HOL-Library.Multiset*

'a multiset: **Finite** multiset

Some functions and syntax:

$\{\#\}$  — empty multiset

$add\_mset\ x\ m$  — add element (cf. *insert* on sets)

$m_1 + m_2$  — union of multisets

$a \in\# m$  — membership query

$\{\#a, b, c, c\#\}$  — Syntax for *add\_mset* and  $\{\#\}$



# Multisets in Isabelle

**imports** *HOL-Library.Multiset*

'a multiset: **Finite** multiset

Some functions and syntax:

$\{\#\}$  — empty multiset

$add\_mset\ x\ m$  — add element (cf. *insert* on sets)

$m_1 + m_2$  — union of multisets

$a \in\# m$  — membership query

$\{\#a, b, c, c\#\}$  — Syntax for *add\_mset* and  $\{\#\}$

$mset\_ran\ a\ r = (\sum_{i \in r}. \{\#a\ i\# \})$

**Multiset** of elements at indexes in finite **set**  $r$

# Proving Insertion Sort

Separate proof for inner loop!

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
    inline inner_loop;  
    j=j+1  
}
```

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
    inline inner_loop;  
    j=j+1  
}
```

Specification of inner loop:

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
    inline inner_loop;  
    j=j+1  
}
```

Specification of inner loop: ?

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
    inline inner_loop;  
    j=j+1  
}
```

Specification of inner loop: ?

**assumes** *ran\_sorted a l j*

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
    inline inner_loop;  
    j = j + 1;  
}
```

Specification of inner loop: ?

**assumes** *ran\_sorted a l j*  
**ensures** *ran\_sorted a l (j + 1)*

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
  inline inner_loop;  
  j = j + 1;  
}
```

Specification of inner loop: ?

**assumes** *ran\_sorted a l j*

**ensures** *ran\_sorted a l (j + 1)* and



# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
  inline inner_loop;  
  j=j+1  
}
```

Specification of inner loop: ?

**assumes** *ran\_sorted a l j*

**ensures** *ran\_sorted a l (j + 1)* and

**ensures** *mset\_ran a {l..j} = mset\_ran a<sub>0</sub> {l..j}*

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
    inline inner_loop;  
    j=j+1  
}
```

Specification of inner loop: ?

**assumes** *ran\_sorted a l j*

**ensures** *ran\_sorted a l (j + 1)* and

**ensures** *mset\_ran a {l..j} = mset\_ran a<sub>0</sub> {l..j}*

Invariant of outer loop:

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
    inline inner_loop;  
    j=j+1  
}
```

Specification of inner loop: ?

**assumes** *ran\_sorted a l j*

**ensures** *ran\_sorted a l (j + 1)* and

**ensures** *mset\_ran a {l..j} = mset\_ran a<sub>0</sub> {l..j}*

Invariant of outer loop:

*ran\_sorted a l j*

# Proving Insertion Sort

Separate proof for inner loop!

```
j = l + 1;  
while (j < h) {  
    inline inner_loop;  
    j = j + 1;  
}
```

Specification of inner loop: ?

**assumes**  $\text{ran\_sorted } a \ l \ j$

**ensures**  $\text{ran\_sorted } a \ l \ (j + 1)$  and

**ensures**  $\text{mset\_ran } a \ \{l..j\} = \text{mset\_ran } a_0 \ \{l..j\}$

Invariant of outer loop:

$\text{ran\_sorted } a \ l \ j$

$\wedge \text{mset\_ran } a \ \{l..<h\} = \text{mset\_ran } a_0 \ \{l..<h\}$

## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

Intuition:

## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

Intuition: ?

## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

Intuition: ?

$a[j]$  is moved backwards



## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

Intuition: ?

$a[j]$  is moved backwards until

## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

Intuition: ?

$a[j]$  is moved backwards until  
previous element is  $\leq a[j]$

## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

Intuition: ?

$a[j]$  is moved backwards until  
previous element is  $\leq a[j]$  or

## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

Intuition: ?

$a[j]$  is moved backwards until  
previous element is  $\leq a[j]$  or  
begin of array is reached

## Insert: Inner Loop

```
key = a[j];  
i = j - 1;  
while (i >= 0 && a[i] > key) {  
    a[i + 1] = a[i];  
    i = i - 1;  
};  
a[i + 1] = key
```

Intuition: ?

$a[j]$  is moved backwards until  
previous element is  $\leq a[j]$  or  
begin of array is reached

Short: Move  $a[j]$  backwards over greater elements.

## Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

Let's specify this intuition!

# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

Let's specify this intuition!

It implies sortedness and mset-preservation



# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

Let's specify this intuition!

It implies sortedness and mset-preservation

But is closer to what algorithm does

# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

Let's specify this intuition!

It implies sortedness and mset-preservation

But is closer to what algorithm does

Invariants easier to find!

## Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

## Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

assumes  $l < j$ , let  $key = a[j]$

# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

assumes  $l < j$ , let  $key = a[j]$

ensures  $i \in \{l - 1 .. j\}$

# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

assumes  $l < j$ , let  $key = a_0 j$

ensures  $i \in \{l - 1..<j\}$

ensures  $\forall k \in \{l..i\}. a k = a_0 k$  and

# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

assumes  $l < j$ , let  $key = a[j]$

ensures  $i \in \{l - 1..j\}$

ensures  $\forall k \in \{l..i\}. a[k] \geq key$  and  
 $a[i + 1] = key$  and

# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

assumes  $l < j$ , let  $key = a_0 j$

ensures  $i \in \{l - 1..<j\}$

ensures  $\forall k \in \{l..i\}. a\ k = a_0\ k$  and

$a\ (i + 1) = key$  and

$\forall k \in \{i + 2..j\}. a\ k = a_0\ (k - 1)$



# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

assumes  $l < j$ , let  $key = a_0 j$

ensures  $i \in \{l - 1..<j\}$

ensures  $\forall k \in \{l..i\}. a k = a_0 k$  and

$a (i + 1) = key$  and

$\forall k \in \{i + 2..j\}. a k = a_0 (k - 1)$

ensures  $l \leq i \longrightarrow a i \leq key$  and

# Insert: Inner Loop

Move  $a[j]$  backwards over greater elements.

assumes  $l < j$ , let  $key = a_0 j$

ensures  $i \in \{l - 1..<j\}$

ensures  $\forall k \in \{l..i\}. a k = a_0 k$  and

$a (i + 1) = key$  and

$\forall k \in \{i + 2..j\}. a k = a_0 (k - 1)$

ensures  $l \leq i \longrightarrow a i \leq key$  and

$\forall k \in \{i + 2..j\}. key < a k$

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	13	17	19	11
$\uparrow$						$\uparrow$	$\uparrow$
$l$						$i$	$j$

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	13	17	11	19
$\uparrow$					$\uparrow$		$\uparrow$
$l$					$i$		$j$

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	13	11	17	19
$\uparrow$				$\uparrow$			$\uparrow$
$l$				$i$			$j$

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	11	13	17	19
$\uparrow$			$\uparrow$				$\uparrow$
$l$			$i$				$j$

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	11	13	17	19
$\uparrow$			$\uparrow$				$\uparrow$
$l$			$i$				$j$

Consider intermediate situation

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	13	11	17	19
$\uparrow$				$\uparrow$			$\uparrow$
$l$				$i$			$j$

Consider intermediate situation



## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	13	11	17	19
$\uparrow$				$\uparrow$			$\uparrow$
$l$				$i$			$j$

Consider intermediate situation

- indexes  $\leq i$  unchanged:  $\forall k \in \{l..i\}. a_k = a_0 k$

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	13	11	17	19
$\uparrow$				$\uparrow$			$\uparrow$
$l$				$i$			$j$

Consider intermediate situation

- indexes  $\leq i$  unchanged:  $\forall k \in \{l..i\}. a[k] = a_0[k]$
- indexes  $\geq i+2$  correctly shifted  
 $\forall k \in \{i+2..j\}. a[k] = a_0[k-1]$

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	13	11	17	19
$\uparrow$				$\uparrow$			$\uparrow$
$l$				$i$			$j$

Consider intermediate situation

- indexes  $\leq i$  unchanged:  $\forall k \in \{l..i\}. a[k] = a_0[k]$
- indexes  $\geq i+2$  correctly shifted  
 $\forall k \in \{i+2..j\}. a[k] = a_0[k-1]$
- and elements greater than  $key$   
 $\forall k \in \{i+2..j\}. key < a[k]$

## Insert: Finding Invariant

0	1	2	3	4	5	6	7
2	3	5	7	13	11	17	19
$\uparrow$				$\uparrow$			$\uparrow$
$l$				$i$			$j$

Consider intermediate situation

- indexes  $\leq i$  unchanged:  $\forall k \in \{l..i\}. a[k] = a_0[k]$
- indexes  $\geq i+2$  correctly shifted  
 $\forall k \in \{i+2..j\}. a[k] = a_0[k-1]$
- and elements greater than  $key$   
 $\forall k \in \{i+2..j\}. key < a[k]$
- + the usual bounds:  $l-1 \leq i \wedge i < j$

# IMP2/Examples.thy

## Insertion Sort

# Summary so Far

Understand what program does!

# Summary so Far

Understand what program does!

Split program into handy parts

# Summary so Far

Understand what program does!

Split program into handy parts

Specify what parts do (independently of users)



# Summary so Far

Understand what program does!

Split program into handy parts

Specify what parts do (independently of users)

Prove that this implies expectations of users

# Summary so Far

Understand what program does!

Split program into handy parts

Specify what parts do (independently of users)

Prove that this implies expectations of users

Prove parts separately and assemble to bigger parts

## ⑦ Advanced Verification

Arrays

Data Refinement

Local Variables

Recursion

# Abstract View

Model  $int \Rightarrow int$  not always appropriate

# Abstract View

Model  $int \Rightarrow int$  not always appropriate

E.g., list: Understand  $a [l..<h]$  as  $int\ list$

# Abstract View

Model  $int \Rightarrow int$  not always appropriate

E.g., list: Understand  $a [l..<h]$  as  $int\ list$

Idea: Do proof at level of understanding **first**

# Abstract View

Model  $int \Rightarrow int$  not always appropriate

E.g., list: Understand  $a [l..<h]$  as  $int\ list$

Idea: Do proof at level of understanding **first**  
**then** show that implementation is correct!

# Abstract View

Model  $int \Rightarrow int$  not always appropriate

E.g., list: Understand  $a [l..<h]$  as  $int\ list$

Idea: Do proof at level of understanding **first**  
**then** show that implementation is correct!

Instead of one proof, get two



# Abstract View

Model  $int \Rightarrow int$  not always appropriate

E.g., list: Understand  $a[l..<h]$  as  $int\ list$

Idea: Do proof at level of understanding **first**  
**then** show that implementation is correct!

Instead of one proof, get two ???

# Abstract View

Model  $int \Rightarrow int$  not always appropriate

E.g., list: Understand  $a[l..<h]$  as  $int\ list$

Idea: Do proof at level of understanding **first**  
**then** show that implementation is correct!

Instead of one **complex** proof, get two **simple** proofs !

# IMP2/Examples.thy

Filter, Merge, dedup

## ⑦ Advanced Verification

Arrays

Data Refinement

Local Variables

Recursion

# Local Variables

Introduce local variables

# Local Variables

Introduce local variables

Why?

# Local Variables

Introduce local variables

Why? Better modularity.

# Local Variables

Introduce local variables

Why? Better modularity.

Don't worry about name-clashes with subroutine's auxiliary variables



# Local Variables

Partition variable names into local and global names

# Local Variables

Partition variable names into local and global names

*is\_global* — Variable name starts with "G"

# Local Variables

Partition variable names into local and global names

*is\_global* — Variable name starts with "G"

```
fun is_global :: vname  $\Rightarrow$  bool where  
  is_global []  $\longleftrightarrow$  True  
| is_global (CHR "G"#_)  $\longleftrightarrow$  True  
| is_global _  $\longleftrightarrow$  False
```

# Local Variables

Partition variable names into local and global names

*is\_global* — Variable name starts with "G"

```
fun is_global :: vname  $\Rightarrow$  bool where  
  is_global []  $\longleftrightarrow$  True  
| is_global (CHR "G"#_)  $\longleftrightarrow$  True  
| is_global _  $\longleftrightarrow$  False
```

*is\_local* *a* =  $\neg$ *is\_global* *a*

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle n = (\text{if } is\_local\ n \text{ then } s\ n \text{ else } t\ n)$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle n = (\text{if } is\_local\ n \text{ then } s\ n \text{ else } t\ n)$

Some rules:  $\langle s | s \rangle = s$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle n = (\text{if } is\_local\ n \text{ then } s\ n \text{ else } t\ n)$

Some rules:  $\langle s | s \rangle = s$

$\langle s | \langle s' | t \rangle \rangle$



# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle n = (\text{if } is\_local\ n \text{ then } s\ n \text{ else } t\ n)$

Some rules:  $\langle s | s \rangle = s$

$\langle s | \langle s' | t \rangle \rangle =$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle n = (\text{if } is\_local\ n \text{ then } s\ n \text{ else } t\ n)$

Some rules:  $\langle s | s \rangle = s$

$\langle s | \langle s' | t \rangle \rangle = \langle s | t \rangle$

$\langle \langle s | t' \rangle | t \rangle = \langle s | t \rangle$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle n = (\text{if } is\_local\ n \text{ then } s\ n \text{ else } t\ n)$

Some rules:  $\langle s | s \rangle = s$

$\langle s | \langle s' | t \rangle \rangle = \langle s | t \rangle$

$\langle \langle s | t' \rangle | t \rangle = \langle s | t \rangle$

$is\_local\ x \implies \langle s | t \rangle\ x =$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle n = (\text{if } is\_local\ n \text{ then } s\ n \text{ else } t\ n)$

Some rules:  $\langle s | s \rangle = s$

$\langle s | \langle s' | t \rangle \rangle = \langle s | t \rangle$

$\langle \langle s | t' \rangle | t \rangle = \langle s | t \rangle$

$is\_local\ x \implies \langle s | t \rangle\ x = s\ x$

$is\_global\ x \implies \langle s | t \rangle\ x = t\ x$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle \ n = (\text{if } is\_local \ n \text{ then } s \ n \text{ else } t \ n)$

Some rules:  $\langle s | s \rangle = s$

$\langle s | \langle s' | t \rangle \rangle = \langle s | t \rangle$

$\langle \langle s | t' \rangle | t \rangle = \langle s | t \rangle$

$is\_local \ x \implies \langle s | t \rangle \ x = s \ x$

$is\_global \ x \implies \langle s | t \rangle \ x = t \ x$

$is\_local \ x \implies \langle s | t \rangle (x := v) =$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle \ n = (\text{if } is\_local \ n \text{ then } s \ n \text{ else } t \ n)$

Some rules:  $\langle s | s \rangle = s$

$\langle s | \langle s' | t \rangle \rangle = \langle s | t \rangle$

$\langle \langle s | t' \rangle | t \rangle = \langle s | t \rangle$

$is\_local \ x \implies \langle s | t \rangle \ x = s \ x$

$is\_global \ x \implies \langle s | t \rangle \ x = t \ x$

$is\_local \ x \implies \langle s | t \rangle (x := v) = \langle s(x := v) | t \rangle$

# State Combination

$\langle s_1 | s_2 \rangle$  – State with locals from  $s_1$ , globals from  $s_2$

$\langle s | t \rangle n = (\text{if } is\_local\ n \text{ then } s\ n \text{ else } t\ n)$

Some rules:  $\langle s | s \rangle = s$

$\langle s | \langle s' | t \rangle \rangle = \langle s | t \rangle$

$\langle \langle s | t' \rangle | t \rangle = \langle s | t \rangle$

$is\_local\ x \implies \langle s | t \rangle x = s\ x$

$is\_global\ x \implies \langle s | t \rangle x = t\ x$

$is\_local\ x \implies \langle s | t \rangle (x := v) = \langle s(x := v) | t \rangle$

$is\_global\ x \implies \langle s | t \rangle (x := v) = \langle s | t(x := v) \rangle$

# Scope Command

*SCOPE*  $c$  — Execute  $c$  with fresh set of local variables.  
Restore original local variables afterwards



# Scope Command

*SCOPE*  $c$  — Execute  $c$  with fresh set of local variables.  
Restore original local variables afterwards

Semantics:

$$\pi: (c, \langle \langle \rangle \rangle | s \rangle) \Rightarrow s' \implies \pi: (SCOPE\ c, s) \Rightarrow \langle s | s' \rangle$$

# Scope Command

*SCOPE*  $c$  — Execute  $c$  with fresh set of local variables.  
Restore original local variables afterwards

Semantics:

$$\pi: (c, \langle \langle \rangle \rangle | s \rangle) \Rightarrow s' \implies \pi: (\text{SCOPE } c, s) \Rightarrow \langle s | s' \rangle$$

$$\text{Unfold rule: } wp \ \pi \ (\text{SCOPE } c) \ Q \ s \\ =$$

# Scope Command

*SCOPE*  $c$  — Execute  $c$  with fresh set of local variables.  
Restore original local variables afterwards

Semantics:

$$\pi: (c, \langle \langle \rangle \rangle | s \rangle) \Rightarrow s' \implies \pi: (\text{SCOPE } c, s) \Rightarrow \langle s | s' \rangle$$

Unfold rule:  $wp \ \pi \ (\text{SCOPE } c) \ Q \ s$   
= ?

# Scope Command

*SCOPE*  $c$  — Execute  $c$  with fresh set of local variables.  
Restore original local variables afterwards

Semantics:

$$\pi: (c, \langle \langle \rangle \rangle | s \rangle) \Rightarrow s' \implies \pi: (\text{SCOPE } c, s) \Rightarrow \langle s | s' \rangle$$

$$\text{Unfold rule: } wp \ \pi \ (\text{SCOPE } c) \ Q \ s \\ =$$

# Scope Command

*SCOPE*  $c$  — Execute  $c$  with fresh set of local variables.  
Restore original local variables afterwards

Semantics:

$$\pi: (c, \langle \langle \rangle \rangle | s \rangle) \Rightarrow s' \implies \pi: (\text{SCOPE } c, s) \Rightarrow \langle s | s' \rangle$$

$$\begin{aligned} \text{Unfold rule: } wp \ \pi \ (\text{SCOPE } c) \ Q \ s \\ = wp \ \pi \ c \ (\lambda s'. Q \ \langle s | s' \rangle) \ \langle \langle \rangle \rangle | s \rangle \end{aligned}$$

# Parameter Passing

Pass information over scope boundaries by globals

# Parameter Passing

Pass information over scope boundaries by globals

Non-recursive procedure call:  $r = f(a_1, \dots, a_n)$

# Parameter Passing

Pass information over scope boundaries by globals

Non-recursive procedure call:  $r = f(a_1, \dots, a_n)$

$G_1 = a_1; \dots; G_n = a_n; \text{inline } f; r = G$



# Parameter Passing

Pass information over scope boundaries by globals

Non-recursive procedure call:  $r = f(a_1, \dots, a_n)$

$G_1 = a_1; \dots; G_n = a_n; \text{inline } f; r = G$

Procedure:  $f(p_1, \dots, p_n) \{ \text{body}; \text{return } x \}$

# Parameter Passing

Pass information over scope boundaries by globals

Non-recursive procedure call:  $r = f(a_1, \dots, a_n)$

$G_1 = a_1; \dots; G_n = a_n; \text{inline } f; r = G$

Procedure:  $f(p_1, \dots, p_n) \{ \text{body}; \text{return } x \}$

$\text{scope } \{ p_1 = G_1; \dots; p_n = G_n; \text{body}; G = x \}$

# Wrapping Specification

Given specification of body:  $HT\ P\ body\ Q$   
and parameters  $p_1, \dots, p_n$  and return variable  $x$

# Wrapping Specification

Given specification of body:  $HT\ P\ body\ Q$   
and parameters  $p_1, \dots, p_n$  and return variable  $x$

How to derive specification for procedure?

$HT\ P'\ (scope\ \{ p_1 = G_1; \dots; p_n = G_n; body; G=x \})\ Q'$

# Wrapping Specification

Given specification of body:  $HT\ P\ body\ Q$   
and parameters  $p_1, \dots, p_n$  and return variable  $x$

How to derive specification for procedure?

$HT\ P'\ (scope\ \{ p_1 = G_1; \dots; p_n = G_n; body; G=x \})\ Q'$

Recall:

$HT\ \pi\ P\ c\ Q \equiv \forall s_0. P\ s_0 \longrightarrow wp\ \pi\ c\ (Q\ s_0)\ s_0$

# Prologue

$$\begin{aligned} HT \pi P \text{ body } Q &\implies \\ HT \pi (wp \pi \text{ prologue } P) (\text{prologue};; \text{body}) \\ &(\lambda s_0 s. wp \pi \text{ prologue } (\lambda s_0. Q s_0 s) s_0) \end{aligned}$$

Intuition: Weakest precondition to enforce  $P$  after prologue

# Epilogue

$$\begin{aligned} & \llbracket HT \pi P \textit{body} Q; \forall s. \exists t. \pi: (\textit{epilogue}, s) \Rightarrow t \rrbracket \\ & \implies HT \pi P (\textit{body};; \textit{epilogue}) (\lambda s_0. sp \pi (Q s_0) \\ & \textit{epilogue}) \end{aligned}$$

Intuition: Strongest postcondition we get from  $Q$  after epilogue

# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$



# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t$$

# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow$$

# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow \exists vx. \textit{let}\ s = t(x := vx)\ \textit{in}\ t\ x = s\ y \wedge P\ s$$

# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow \exists vx. \textit{let}\ s = t(x := vx)\ \textit{in}\ t\ x = s\ y \wedge P\ s$$

$$sp\ \pi\ P\ (x[] ::= y)\ t$$

# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow \exists vx. \textit{let}\ s = t(x := vx)\ \textit{in}\ t\ x = s\ y \wedge P\ s$$

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow$$

# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow \exists vx. \textit{let}\ s = t(x := vx)\ \textit{in}\ t\ x = s\ y \wedge P\ s$$

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow t\ x = t\ y \wedge (\exists vx. P\ (t(x := vx, y := t\ x)))$$

# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow \exists vx. \textit{let}\ s = t(x := vx)\ \textit{in}\ t\ x = s\ y \wedge P\ s$$

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow t\ x = t\ y \wedge (\exists vx. P\ (t(x := vx, y := t\ x)))$$

$$sp\ \pi\ P\ (c_1;; c_2)\ t$$

# Strongest Postconditions

$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow \exists vx. \textit{let}\ s = t(x := vx)\ \textit{in}\ t\ x = s\ y \wedge P\ s$$

$$sp\ \pi\ P\ (x[] ::= y)\ t \longleftrightarrow t\ x = t\ y \wedge (\exists vx. P\ (t(x := vx, y := t\ x)))$$

$$sp\ \pi\ P\ (c_1;;\ c_2)\ t \longleftrightarrow$$



# Strongest Postconditions



$$sp\ \pi\ P\ c\ t \equiv \exists s. P\ s \wedge \pi: (c, s) \Rightarrow t$$

Selected rules:

$$sp\ \pi\ P\ (x[] ::= y)\ t \xleftrightarrow{\text{[icon]}} \exists vx. \text{let } s = t(x := vx) \text{ in } t\ x = s\ y \wedge P\ s$$

$$sp\ \pi\ P\ (x[] ::= y)\ t \xleftrightarrow{\text{[icon]}} t\ x = t\ y \wedge (\exists vx. P\ (t(x := vx, y := t\ x)))$$

$$sp\ \pi\ P\ (c_1;; c_2)\ t \xleftrightarrow{\text{[icon]}} sp\ \pi\ (sp\ \pi\ P\ c_1)\ c_2\ t$$

# Wrapping Specification

$HT\ P' (scope\ \{ p_1 = G_1; \dots; p_n = G_n; body; G=x \})\ Q'$

# Wrapping Specification

$HT\ P' (scope\ \{ p_1 = G_1; \dots; p_n = G_n; body; G=x \})\ Q'$

Derive specification for

# Wrapping Specification

$HT\ P' (scope\ \{ p_1 = G_1; \dots; p_n = G_n; body; G=x \})\ Q'$

Derive specification for

Parameter assignments:  $HT\ \pi\ P\ c\ Q \implies$

$HT\ \pi\ (\lambda s. P\ (s(x := s\ y)))\ (x[] ::= y;; c)\ (\lambda s_0. Q\ (s_0(x := s_0\ y)))$

# Wrapping Specification

$$HT\ P' \ (scope\ \{ p_1 = G_1; \dots; p_n = G_n; body; G=x \})\ Q'$$

Derive specification for

Parameter assignments:  $HT\ \pi\ P\ c\ Q \implies$

$$HT\ \pi\ (\lambda s. P\ (s(x := s\ y)))\ (x[] ::= y;; c)\ (\lambda s_0. Q\ (s_0(x := s_0\ y)))$$

Return value assignment:  $HT\ \pi\ P\ c\ Q \implies$

$$HT\ \pi\ P\ (c;; x[] ::= y)\ (\lambda s_0\ s. \exists vx. Q\ s_0\ (s(x := vx, y := s\ x)))$$

# Wrapping Specification

$$HT\ P' \ (scope \ \{ \ p_1 = G_1; \ \dots; \ p_n = G_n; \ body; \ G=x \} ) \ Q'$$

Derive specification for

Parameter assignments:  $HT\ \pi\ P\ c\ Q \implies$

$$HT\ \pi\ (\lambda s. P\ (s(x := y)))\ (x[] ::= y;;\ c)\ (\lambda s_0. Q\ (s_0(x := s_0\ y)))$$

Return value assignment:  $HT\ \pi\ P\ c\ Q \implies$

$$HT\ \pi\ P\ (c;;\ x[] ::= \text{value})\ (\lambda s_0\ s. \exists vx. Q\ s_0\ (s(x := vx, y := s\ x)))$$

Scope:  $HT\ \pi\ P\ c\ Q \implies$

$$HT\ \pi\ (\lambda s. P\ \langle \langle \rangle | s \rangle )\ (SCOPE\ c)\ (\lambda s_0\ s. \exists l. \langle \langle \rangle | s_0 \rangle \langle l | s \rangle )$$

# IMP2/Examples.thy



Merge as Procedure

## ⑦ Advanced Verification

Arrays

Data Refinement

Local Variables

Recursion



# Recursive Procedures

Program is map  $pname \rightarrow com$

# Recursive Procedures

Program is map  $pname \rightarrow com$

Procedure call command  $PCall::char\ list \Rightarrow com$

# Recursive Procedures

Program is map  $pname \rightarrow com$

Procedure call command  $PCall::char\ list \Rightarrow com$

Big-Step semantics:  $\pi: (c, s) \Rightarrow t$   
parameterized with program  $\pi$

# Recursive Procedures

Program is map  $pname \rightarrow com$

Procedure call command  $PCall::char\ list \Rightarrow com$

Big-Step semantics:  $\pi: (c, s) \Rightarrow t$   
parameterized with program  $\pi$

$$\llbracket \pi\ p = Some\ c; \pi: (c, s) \Rightarrow t \rrbracket \Longrightarrow \pi: (PCall\ p, s) \Rightarrow t$$

# Recursive Procedures

Program is map  $pname \rightarrow com$

Procedure call command  $PCall::char\ list \Rightarrow com$

Big-Step semantics:  $\pi: (c, s) \Rightarrow t$   
parameterized with program  $\pi$

$$\llbracket \pi\ p = Some\ c; \pi: (c, s) \Rightarrow t \rrbracket \Longrightarrow \pi: (PCall\ p, s) \Rightarrow t$$

Note: Gets stuck if procedure does not exist!



# Recursive Procedures

Program is map  $pname \rightarrow com$

Procedure call command  $PCall::char\ list \Rightarrow com$

Big-Step semantics:  $\pi: (c, s) \Rightarrow t$   
parameterized with program  $\pi$

$$\llbracket \pi\ p = Some\ c; \pi: (c, s) \Rightarrow t \rrbracket \implies \pi: (PCall\ p, s) \Rightarrow t$$

Note: Gets stuck if procedure does not exist!  
No problem when proving **total** correctness

## Proof Rules for Recursion

Unfolding:  $\pi \ p = \textit{Some } c \implies \textit{wp } \pi \ (\textit{PCall } p) \ Q \ s = \textit{wp } \pi \ c \ Q \ s$

## Proof Rules for Recursion

Unfolding:  $\pi \ p = \textit{Some } c \implies \textit{wp } \pi \ (\textit{PCall } p) \ Q \ s = \textit{wp } \pi \ c \ Q \ s$

Idea: Well-Founded induction on state



# Proof Rules for Recursion

Unfolding:  $\pi \ p = \text{Some } c \implies wp \ \pi \ (PCall \ p) \ Q \ s = wp \ \pi \ c \ Q \ s$


Idea: Well-Founded induction on state

**assumes**  $wf \ R$

$$\bigwedge s. \llbracket HT \ \pi \ (\lambda s'. (s', s) \in R \wedge P \ s') \ (PCall \ p) \ Q; P \ s \rrbracket \\ \implies wp \ \pi \ (PCall \ p) \ (Q \ s) \ s$$


**shows**  $HT \ \pi \ P \ (PCall \ p) \ Q$

# Proof Rules for Recursion

Unfolding:   $\pi p = \text{Some } c \implies wp \pi (PCall p) Q s = wp \pi c Q s$

Idea: Well-Founded induction on state

**assumes**  $wf R$

$\bigwedge s. \llbracket HT \pi (\lambda s'. \text{ (s, s) \in R \wedge P s') (PCall p) Q; P s \rrbracket$   
 $\implies wp \pi (PCall p) (Q s) s$

**shows**  $HT \pi P (PCall p) Q$

Show specification for  state  $s$ , assuming it holds for smaller states  $s'$ .

# Mutual Recursion

Same idea, but for sets of specifications.

# Mutual Recursion

Same idea, but for sets of specifications.

$HT'_{set} \pi \Theta \equiv \forall (n, P, c, Q) \in \Theta. HT' \pi P c Q$

All Hoare-Triples in  $\Theta$  valid. Annotation  $n$  ignored!

# Mutual Recursion

Same idea, but for sets of specifications.

$HT'_{set} \pi \Theta \equiv \forall (n, P, c, Q) \in \Theta. HT' \pi P c Q$


All Hoare-Triples in  $\Theta$  valid. Annotation  $n$  ignored!

$ASSUME_{\Theta} \pi f_0 s_0 R \Theta =$

$(\forall (f, P, c, Q) \in \Theta. HT' \pi (\lambda s. (f s, f_0 s_0) \in R \wedge P s) c Q)$

Hoare-triples valid for states less than  $f_0 s_0$ . Annotation is **variant**.

# Mutual Recursion


Same idea, but for sets of specifications. 

$HT'_{set} \pi \Theta \equiv \forall (n, P, c, Q) \in \Theta. HT' \pi P c Q$

All Hoare-Triples in  $\Theta$  valid. Annotation  $n$  ignored!

$ASSUME_{\Theta} \pi f_0 s_0 R \Theta =$

$(\forall (f, P, c, Q) \in \Theta. HT' \pi (\lambda s. (f s, f_0 s_0) \in R \wedge P s) c Q)$

Hoare-triples  valid for states less than  $f_0 s_0$ . Annotation is **variant**.

$PROVE_{\Theta} \pi f_0 s_0 \Theta \equiv$

$\forall P c Q. (f_0, P, c, Q) \in \Theta \wedge P s_0 \longrightarrow wp \pi (c s_0) (Q s_0) s_0$

Hoare-triples valid for fixed variant  $f_0$  and state  $s_0$ .

# Mutual Recursion

**lemma**  $vcg\_HT'setI$ :  
**assumes**  $wf\ R$   
**assumes**  $RL: \bigwedge f_0\ s_0. \llbracket ASSUME\_Θ\ \pi\ f_0\ s_0\ R\ Θ \rrbracket \implies$   
 $PROVE\_Θ\ \pi\ f_0\ s_0\ Θ$   
**shows**  $HT'set\ \pi\ Θ$

Fix variant and state,  
assume that Hoare-triples hold for smaller states  
prove that Hoare-triples hold for this state.

# Mutual Recursion

**lemma** *vcg\_HT'setI*:  
**assumes** *wf R*  
**assumes** *RL*:  $\bigwedge f_0\ s_0. \llbracket \text{ASSUME\_}\Theta\ \pi\ f_0\ s_0\ R\ \Theta \rrbracket \implies$   
*PROVE\_* $\Theta\ \pi\ f_0\ s_0\ \Theta$   
**shows** *HT'set*  $\pi\ \Theta$

Fix variant and state,  
assume that Hoare-triples hold for smaller states  
prove that Hoare-triples hold for this state.


$$\llbracket \pi\ p = \text{Some } c; \text{HT\_mods } \pi\ \text{mods } P\ c\ Q \rrbracket \implies \text{HT\_mods } \pi\ \text{mods } P\ (\text{PCall } p)\ Q$$

Maps Hoare-Triples to procedure calls



# Local Procedures

Idea: Recursive procedure names only valid locally!

# Local Procedures

Idea: Recursive procedure names only valid locally!

No need to worry about name clashes!

# Local Procedures

Idea: Recursive procedure names only valid locally!

No need to worry about name clashes!

$$\llbracket \pi' p = \textit{Some } c; \pi': (c, s) \Rightarrow t \rrbracket \Longrightarrow \pi: (P\textit{Scope } \pi' p, s) \Rightarrow t$$

Call procedure with local procedure environment

# Local Procedures

Idea: Recursive procedure names only valid locally!

No need to worry about name clashes!

$$\llbracket \pi' p = \text{Some } c; \pi': (c, s) \Rightarrow t \rrbracket \Longrightarrow \pi: (P\text{Scope } \pi' p, s) \Rightarrow t$$

Call procedure with local procedure environment

$$HT\_mods \pi \text{ mods } P (P\text{Call } p) Q \Longrightarrow HT\_mods \pi' \text{ mods } P \\ (P\text{Scope } \pi p) Q$$

Wrap current procedure environment

# Specification of Mutual Recursive Procedures

The IMP2 tools take care of

- wf-relation. Default *less\_than*

# Specification of Mutual Recursive Procedures

The IMP2 tools take care of

- wf-relation. Default *less\_than*
- parameters and return values.


# Specification of Mutual Recursive Procedures

The IMP2 tools take care of

- wf-relation. Default *less\_than*
- parameters and return values.
- variants: expression over parameters.

# Specification of Mutual Recursive Procedures

The IMP2 tools take care of

- wf-relation. Default *less\_than* 
- parameters and return values.
- variants: expression over parameters.
- localization of procedure environment.



# IMP2/Examples.thy

Ackermann, Odd/Even, Merge Sort



# Completeness

Consider program with  $HT \pi P c Q$

# Completeness

Consider program with  $HT \pi P c Q$

Can we always find annotations to get provable VCs?

# Completeness

Consider program with  $HT \pi P c Q$

Can we always find annotations to get provable VCs?

Only consider while-rule here

# Partial Correctness

$$\begin{aligned} & \llbracket I \ s_0; \bigwedge s. I \ s \implies \textit{if } b \textit{val } b \ s \textit{ then } wlp \ \pi \ c \ I \ s \textit{ else } Q \ s \rrbracket \\ & \implies wlp \ \pi \ (\textit{WHILE } b \textit{ DO } c) \ Q \ s_0 \end{aligned}$$

# Partial Correctness

$$\llbracket I \ s_0; \bigwedge s. I \ s \implies \textit{if } b \textit{val } b \ s \textit{ then } wlp \ \pi \ c \ I \ s \textit{ else } Q \ s \rrbracket \\ \implies wlp \ \pi \ (\textit{WHILE } b \textit{ DO } c) \ Q \ s_0$$

What invariant shall we use?

# Partial Correctness

$$\llbracket I \ s_0; \bigwedge s. I \ s \Longrightarrow \textit{if } b \textit{val } b \ s \textit{ then } wlp \ \pi \ c \ I \ s \textit{ else } Q \ s \rrbracket \\ \Longrightarrow wlp \ \pi \ (\textit{WHILE } b \ \textit{DO } c) \ Q \ s_0$$

What invariant shall we use?

$$wlp \ \pi \ c \ Q!$$

# Total Correctness

$$\begin{aligned} & \llbracket wf\ R; \ I\ s_0; \\ & \bigwedge s. I\ s \implies \text{if } bval\ b\ s \text{ then } wp\ \pi\ c\ (\lambda s'. I\ s' \wedge (s', s) \\ & \in R) \ s \text{ else } Q\ s \rrbracket \\ & \implies wp\ \pi\ (WHILE\ b\ DO\ c)\ Q\ s_0 \end{aligned}$$

Invariant:  $wp\ \pi\ c\ Q$



# Total Correctness

$$\begin{aligned} & \llbracket wf\ R; \ I\ s_0; \\ & \bigwedge s. I\ s \implies \text{if } bval\ b\ s \text{ then } wp\ \pi\ c\ (\lambda s'. I\ s' \wedge (s', s) \\ & \in R) \ s \text{ else } Q\ s \rrbracket \\ & \implies wp\ \pi\ (WHILE\ b\ DO\ c)\ Q\ s_0 \end{aligned}$$

Invariant:  $wp\ \pi\ c\ Q$

Variant?

# Total Correctness

$$\begin{aligned} & \llbracket wf\ R; \ I\ s_0; \\ & \bigwedge s. I\ s \implies \text{if } bval\ b\ s \text{ then } wp\ \pi\ c\ (\lambda s'. I\ s' \wedge (s', s) \\ & \in R) \ s \text{ else } Q\ s \rrbracket \\ & \implies wp\ \pi\ (WHILE\ b\ DO\ c)\ Q\ s_0 \end{aligned}$$

Invariant:  $wp\ \pi\ c\ Q$

Variant?

Number of iterations until termination!



# IMP2/Examples.thy

Completeness of While-Rule

# Conclusions

IMP2: Verification of simple programs in Isabelle/HOL  
while-language, arrays, local-vars, recursive procedures  
Tools: concrete syntax for programs and specs, VCG

# Conclusions

IMP2: Verification of simple programs in Isabelle/HOL  
while-language, arrays, local-vars, recursive procedures  
Tools: concrete syntax for programs and specs, VCG

Not supported:  
types (char, float, records), pointers, concurrency, ...  
Tools: ghost variables, compiler, ...

# Conclusions

IMP2: Verification of simple programs in Isabelle/HOL  
while-language, arrays, local-vars, recursive procedures  
Tools: concrete syntax for programs and specs, VCG

Not supported:  
types (char, float, records), pointers, concurrency, ...  
Tools: ghost variables, compiler, ...

Caveats:  
Procedures+Recursion tools not well-tested  
VCG is slow for many procedures/inlines