

**15-410**

***“...Should we “crash”?...”***

**Errors**  
**Jan. 31, 2011**

**Dave Eckhardt**

# Outline

**Three kinds of error**

**Important to classify & react appropriately**

# Outline

## Three kinds of error

- Hmm...
- That's not right...
- Uh-oh...

**Important to classify & react appropriately**

# “New Player” - Take 1

```
// Improve memory locality:
// store players in array; use index, not ptr
struct player players[MAX];
int new_player(int team, int num)
{
    int i;
    if ((i = emptyslot()) == -1) {
        /* OH NO!!! */
        MAGIC_BREAK;
    }
    ...
}
```

# “New Player” - Take 2

```
// Improve memory locality:
// store players in array; use index, not ptr
struct player players[MAX];
int new_player(int team, int num)
{
    int i;
    if ((i = emptyslot()) == -1) {
        /* OH NO!!! */
        while(1);
    }
    ...
}
```

# What's Going On?

## **“Out of table slots” - what kind of thing?**

- Should really never happen?
- Might happen sometimes?
- Likely to happen once a day?

# What's Going On?

## “Out of table slots” - what kind of thing?

- Should really never happen?
- Might happen sometimes?
- Likely to happen once a day?
  - Remember: users always want 110%!

## What to do?

- **Resolve** reasonable issues when possible
  - How to resolve this one?

# “New Player” - Take 3

```
struct player *players;
int playerslots;
int new_player(int team, int num)
{
    int i;
    if ((i = emptyslot()) == -1) {
        if ((i = grow_table_and_alloc()) == -1)
            /* OH NO!!! */
            while(1);
    }
    ...
}
```



# What's Going On?

## **“Out of heap space” - what kind of thing?**

- Should really never happen?
- Might happen sometimes?
- Likely to happen once a day?

# What's Going On?

## **“Out of heap space” - what kind of thing?**

- Should really never happen?
- Might happen sometimes?
- Likely to happen once a day?

## **My suggestion**

- “Might happen sometimes”

## **What to do?**

- Hard to say what the right thing is for all clients
  - Is it fatal or not?
- Often: pass the buck

# “New Player” - Take 4

```
struct player *players;
int playerslots;
int new_player(int team, int num)
{
    int i;
    if ((i = emptyslot()) == -1) {
        if ((i = grow_table_and_alloc()) == -1)
            return (-1);
    }
    ...
}
```

# “Free Player” - Take 1

```
void free_player(int slot)
{
    struct player *p = &players[slot];
    switch(p->role) {
    case CONTENDER:
        free(p->cstate); break;
    case REFEREE:
        free(p->refstate); break;
    }
    free(p->generic);
    mark_slot_available(slot);
}
```

# What's Wrong?

**There is a sanity-check missing...**

- Probably somebody will make a mistake eventually
- Let's catch it

# “Free Player” - Take 2

```
void free_player(int slot)
{
    struct player *p = &players[slot];
    switch(p->role) {
        case CONTENDER:
            free(p->cstate); break;
        case REFEREE:
            free(p->refstate); break;
        default: return;
    }
    free(p->generic);
    mark_slot_available(slot);
}
```

14

# All Fixed?

**No!**

- The program *has a bug*
  - Maybe the client is passing us random player pointers
  - Maybe we are handing out invalid p->role values
- We happened to catch the bug this time
- We might not catch it every time!
  - A random player pointer might have a “valid” p->role

**The program is *broken***

- Hiding the problem isn't our job
- Hiding the problem isn't even *defensible*

# Should We “Crash”?

**If the program is “broken”, should we “crash”?**

- **Often: yes**
  - **Dumping core allows debugger inspection of the problem**
  - **Throwing running program into a debugger is probably nicer**



# Summary

## Three kinds of error

- Hmm...
  - Try to *resolve*
- That's not right...
  - Try to *report*
- Uh-oh...
  - Try to *help the developer* find the problem faster