

Experimental study on round trip times of web applications

Rafi Khaled, Rui Meireles
{rkhaled, rui.meireles}@vassar.edu

Department of Computer Science, Vassar College, USA

Abstract—Replace by concrete abstract.

I. INTRODUCTION

Introduction.

Figure 1 is an example figure.

II. RELATED WORK

Related work.

III. METHODOLOGY

Collection of data was conducted using two Python libraries: `pytyping` and `PycURL`. `PycURL` is a Python interface to `libcurl`, which is a client-side URL transfer library. `PycURL` allows one to fetch various objects identified by a URL: in our case, objects corresponding to the URLs of various websites hosted on servers across the world. [1]

First, we wanted to calculate the RTT as measured by a calculation involving, at the highest level, a websites pretransfer time and time to first byte: the RTT was calculated as the pretransfer time subtracted from the time to first byte, both of which were obtained with `PycURL`. Knowing this, it is as simple as creating a new `Curl Object` from `PycURL`, setting the relevant options, i.e. the name of the website and the `FOLLOWLOCATION` to 1. Setting the `FOLLOWLOCATION` to 1 tells the library to follow any `Location:` header that the server sends as part of a HTTP header in a 3xx response. The `Location:` header can specify a relative or an absolute URL to follow. The library will issue another request for the new URL and follow new `Location:` headers all the way until no more such headers are returned. [2]

IV. EVALUATION

Evaluation.

V. CONCLUSIONS

Conclusions.