R.K. Instruments & Controls

TECHNICAL DATASHEET

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Honeywell Elster RABO G40 DN50 Rotary Gas Meter

Brand: Honeywell Elster | Code/Part No.: RABO G40 DN50 CLASS150 | Category: GAS FLOW METERS

Specifications

Model	**RABO G40 DN50 CLASS150**
Meter Size (G-Rating)	**G40 (Qmax 65 m³/h per EN 12480)**
Measuring Principle	**Rotary Piston (Positive Displacement)**
Connection Size	**DN50 (2"), flanged**
Minimum Flow Rate (Qmin)	**0.32 m³/h**
Maximum Flow Rate (Qmax)	**65 m³/h**
Cyclic Volume (Vcyc)	**0.97 dm³**
Internal Volume	**1.36 L**
Maximum Operating Pressure (PS)	**20 bar**
Storage Temperature Range (TS)	**-40°C to +70°C**
Operating Temperature Range	**-25°C to +70°C**
Index Ratio	**1 m³ = 10 Imp**
Index / Readout	**Mechanical roller counter, reading in m³**
Optional Output	**ENCODER S1D low-frequency pulse encoder (as shown)**
Standard Compliance	**EN 12480:2015, AC 10**
Hazardous Area Rating	**II 2G Ex h IIC T4 Gb, IECEx TUR 16.0042X**
Approvals	**CE 0085, ATEX**
Manufacturer	**Elster GmbH, Uelzen, Germany (Honeywell Elster)**



Description

The Honeywell Elster RABO G40 DN50 CLASS150 is a rotary-piston (positive-displacement) gas meter for industrial and commercial metering, sized DN50 with a flow range of 0.32 to 65 m³/h (Qmin to Qmax, EN 12480:2015 accuracy class AC 10). Two counter-rotating rotary pistons sweep a fixed cyclic volume of 0.97 dm³ per revolution, driving a mechanical roller-counter index that reads directly in m³ (1 m³ = 10 Imp on the low-frequency pulse output). Rated to a maximum operating pressure of 20 bar with an internal volume of 1.36 L, it covers a storage temperature range of -40°C to +70°C and an operating range of -25°C to +70°C, and is ATEX certified for use in hazardous areas — hazardous area rating II 2G Ex h IIC T4 Gb, IECEx TUR 16.0042X, CE 0085. The unit shown is fitted with the optional ENCODER S1D low-frequency pulse output module for remote/electronic reading; a plain mechanical-index version without the encoder is also available. Manufactured by Elster GmbH, Uelzen, Germany (Honeywell Elster); commonly used for custody-transfer and allocation metering on industrial and commercial gas supplies.

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.