

Introduction to Cython - Week 1

Richard Killam

Friday 30th October, 2015

Outline



- 1 Motivation
- 2 I/O
 - Exercise
- 3 Conditionals
 - if, else, and elif
 - While
- 4 Iteration
 - Arrays
 - for loop
 - Exercise
- 5 Functions
 - Exercise
- 6 Importing
 - From Python Path
 - From Current Folder
- 7 Classes

Motivation



Sum the numbers from 1 to 100,000,000

Python 12.898s

Compiled Python 12.177s

Cython 0.432s

C 0.406s

Hello World



hello_world.py

```
1      print("Hello World")
```

Hello World



hello_world.py

```
1      print("Hello World")
```

python hello_world.py

```
>> Hello World
```

My name is...



my_name_is.py

```
1     name = raw_input("Name > ")
2     print("Hello World, my name is
           {NAME}".format(NAME=name))
```



My name is...

my_name_is.py

```
1     name = raw_input("Name > ")
2     print("Hello World, my name is
           {NAME}".format(NAME=name))
```

python my_name_is.py

>>> Name >

>>> Name > Richard

>>> Hello World, my name is Richard

Exercise - My full name is...





Exercise - My full name is...

my_full_name_is.py

```
1 first_name = raw_input("First name > ")
2 last_name = raw_input("Last name > ")
3
4 print("Hello World, my name is {FIRST} {LAST}".format(
5     FIRST=first_name,
6     LAST=last_name
7 ))
```



Getting numbers in

name_and_age.py

```

1  name = raw_input("Name > ")
2  year_of_birth = int(raw_input("Year of Birth > "))
3
4  print("{NAME} is {YEARS} old.".format(
5      NAME=name,
6      YEARS=2015 - year_of_birth
7  ))

```

if, else



True_False.py

```
1  if True:
2      print("The conditional was True")
3
4  else:
5      print("The conditional was False")
```

if, else



True_False.py

```
1  if True:
2      print("The conditional was True")
3
4  else:
5      print("The conditional was False")
```

Note the indentation.



if, else with input

even_or_odd.py

```
1  num = int(raw_input("Number > "))
2
3  if num % 2 == 0:
4      print("{NUM} is even".format(NUM=num))
5
6  else:
7      print("{NUM} is odd".format(NUM=num))
```

elif



a_or_b.py

```
1 choice = raw_input("Choose a or b ")
2
3 if choice == "a":
4     print("You chose a")
5
6 elif choice == "b":
7     print("You chose b")
8
9 else:
10    print("You did not follow instructions...")
```



While + and

force_a_or_b.py

```
1  choice = ""
2
3  while choice != "a" and choice != "b":
4      choice = raw_input("Choose a or b >")
5
6  if choice == "a":
7      print("You chose a")
8  elif choice == "b":
9      print("You chose b")
10 else:
11     # Dead code
12     print("How did you get here?!?!")
```



While + or + not

force_a_or_b.py

```
1 choice = ""
2
3 while not (choice == "a" or choice == "b"):
4     choice = raw_input("Choose a or b >")
5
6 if choice == "a":
7     print("You chose a")
8 elif choice == "b":
9     print("You chose b")
10 else:
11     # Dead code
12     print("How did you get here?!?!")
```




Array declaration

array_declaration.py

```

1  a = [1, 2, 3, 4, 5]
2  print(a) # >> [1, 2, 3, 4, 5]
3
4  a = range(1, 6)
5  print(a) # >> [1, 2, 3, 4, 5]
6
7  a = range(5)
8  print(a) # >> [0, 1, 2, 3, 4]

```



Array indexing

array_indexing.py

```
1  a = range(5)
2
3  print(a) # >> [0, 1, 2, 3, 4]
4  print(a[0]) # >> 0
5
6  print(a[len(a) - 1]) # >> 4
7  print(a[-1]) # >> 4
8
9  print(a[len(a) - 2]) # >> 3
10 print(a[-2]) # >> 3
```

C-Style for loop



c_style_for_loop.py

```
1  a = range(5, 10)
2
3  for i in range(len(a)):
4      print("a[{I}] = {AI}".format(I=i, AI=a[i]))
```

Python-Style for loop



python_style_for_loop.py

```
1  a = range(5, 10)
2
3  for ai in a:
4      print("AI = {AI}".format(AI=a[i]))
5
```



Python-Style for loop

python_style_for_loop.py

```

1  a = range(5, 10)
2
3  for ai in a:
4      print("AI = {AI}".format(AI=a[i]))
5
6  for i, ai in enumerate(a):
7      print("a[{I}] = {AI}".format(I=i, AI=ai))

```

Exercise - Sum the Numbers from 1 to n



`sum_nums.py`



Exercise - Sum the Numbers from 1 to n

sum_nums.py

```

1  n = int(raw_input("n (-1 to quit) > "))
2  while n > 1:
3      s = 0
4
5      # n + 1 because range goes to n - 1
6      for i in range(1, n+1):
7          s += i
8
9      print("n = {N} -> {S}".format(N=n, S=s))
10
11 n = int(raw_input("n (-1 to quit) > "))

```



def

sum_nums_func.py

```

1  def sum_nums(n):
2      s = 0
3
4      # n + 1 because range goes to n - 1
5      for i in range(1, n+1):
6          s += i
7
8      return s
9
10 print("sum_nums({N}) => {SNN}".format(
11     N=10,
12     SNN=sum_nums(10)
13 )) # >> 55

```




Default Arguments

func_default_args.py

```

1  def default_args(a=1, b=3):
2      print("a was {A}; b was {B}".format(A=a, B=b))
3
4  default_args()           # >> a was 1; b was 3
5  default_args(7)         # >> a was 7; b was 3
6  default_args(7, 11)     # >> a was 7; b was 11
7  default_args(7, b=12)   # >> a was 7; b was 12
8  default_args(a=8, b=12) # >> a was 8; b was 12
9  default_args(b=13, a=5) # >> a was 5; b was 13
10 default_args(a=10, 14)  # >> SyntaxError: non-keyword
    arg after keyword arg

```

Exercise - Sum the Numbers from low to high

`sum_range.py`

Exercise - Sum the Numbers from low to high

sum_range.py

```
1  def sum_range(low=1, high=10):  
2      s = 0  
3  
4      # high + 1 because range goes to high - 1  
5      for i in range(low, high + 1):  
6          s += i  
7  
8      return s
```

Basics

basic_import_from_python_path.py

```
1  # imports that math library and references it as math
2  import math
3  print(math.log(100, 10)) # >> 2.0 (log 100 base 10)
4
5  # sys.argv allows for command line arguments
6  import sys
7  print(sys.argv)
```

Different styles of importing

```
1      # imports the sparse module from the scipy library as
      scipy.sparse
2  import scipy.sparse
3
4      # imports the sparse module from the scipy library as
      sp_sparse
5  import scipy.sparse as sp_sparse
6
7      # imports the sparse module from the scipy library as
      sparse
8  from scipy import sparse
```

From sum_range.py

import_sum_range.py

```

1      # This is the only style that I will use in the
      workshop
2      import sum_range # Note that there is no .py
3      print(sum_range.sum_range(low=2, high=10)) # >> 54
4
5      import sum_range as sr
6      print(sr.sum_range(low=2, high=10)) # >> 54
7
8      from sum_range import sum_range
9      print(sum_range(low=2, high=10)) # >> 54
10
11     from sum_range import sum_range as sr
12     print(sr(low=2, high=10)) # >> 54

```

Definition, Instantiation, and Usage

animal.py

```

1  # Explicit inheritance from object class
2  class Animal(object):
3      # Explicit (and necessary) passing of self object
4      def __init__(self, name_in, noise_in):
5          self.name = name_in # ≠ name = name_in
6          self.noise = noise_in # ≠ noise = noise_in
7
8  dog = Animal("Rex", "woof")
9  print("{DOG} makes a {NOISE} noise".format(
10      DOG=dog.name,
11      NOISE=dog.noise
12  ))

```

Inheritance

animal.py

```

1  class Dog(Animal):
2      def __init__(self, name):
3          # This gets better in Python 3
4          super(Dog, self).__init__(name, "woof")
5
6      # NEED to accept self
7      def wag_tail(self):
8          print("{NAME} is
          happy".format(NAME=self.name))
9
10     rex = Dog("Rex")
11     rex.wag_tail() # DON'T need to explicitly pass self

```