

# Introduction to Cython - Week 2

Richard Killam

Sunday 1<sup>st</sup> November, 2015

# Outline

## 1 Cython as a Module

sum\_nums.pyx

## sum\_nums.pyx

```
1 cdef unsigned long long sum_nums(unsigned long n):  
2     cdef unsigned long long s = 0  
3     cdef unsigned long i  
4     for i in range(1, n+1):  
5         s += i  
6     return s
```

run\_sum\_nums.py

## run\_sum\_nums.py

```
1 import sum_nums as sn
2
3 print(sn.sum_nums(10))
```

## run\_sum\_nums.py

```
1 import sum_nums as sn
2
3 print(sn.sum_nums(10))
```

```
python setup.py build_ext -inplace
python run_sum_nums.py
```

## run\_sum\_nums.py

```
1 import sum_nums as sn
2
3 print(sn.sum_nums(10))
```

python setup.py build\_ext -inplace

python run\_sum\_nums.py

>> AttributeError: 'module' object has no attribute 'sum\_nums'



# The Fix

sum\_nums.pyx

```
1 def sum_nums_wrapper(n):  
2     return sum_nums(int(n))
```

# The Fix

sum\_nums.pyx

```
1 def sum_nums_wrapper(n):  
2     return sum_nums(int(n))
```

run\_sum\_nums.py

```
1 import sum_nums as sn  
2  
3 print(sn.sum_nums_wrapper(10))
```

# Testing The Fix

```
python setup.py build_ext --inplace  
python run_sum_nums.py
```

# Testing The Fix

```
python setup.py build_ext -inplace  
python rum_sum_nums.py  
>> 55
```

# The Sugar

sum\_nums.pyx

```
1  cpdef unsigned long long sum_nums(unsigned long n):
2      cdef unsigned long long s = 0
3      cdef unsigned long i
4      for i in range(1, n+1):
5          s += i
6      return s
```

# Using The Sugar

run\_sum\_nums.py

```
1 import sum_nums as sn
2
3 print(sn.sum_nums(10))
```

## Using The Sugar

run\_sum\_nums.py

```
1 import sum_nums as sn
2
3 print(sn.sum_nums(10))
```

```
python setup.py build_ext -inplace
python run_sum_nums.py
```

## Using The Sugar

run\_sum\_nums.py

```
1 import sum_nums as sn
2
3 print(sn.sum_nums(10))
```

python setup.py build\_ext -inplace

python run\_sum\_nums.py

>> 55