# Sheet Metal Gauge Chart

Thickness by gauge and material · millimetres and inches

**GAUGE 3–36**
4 material systems
1 page

| GAUGE MSG | OZ / FT² NOMINAL | CARBON STEEL MM | CARBON STEEL INCH | GALVANIZED MM | STAINLESS MM | AL · BRASS · CU MM · B&S |
|---|---|---|---|---|---|---|
| 3 | 160 | 6.073 | 0.2391 | 6.170 | 6.350 | 5.827 |
| 4 | 150 | 5.695 | 0.2242 | 5.789 | 5.954 | 5.189 |
| 5 | 140 | 5.314 | 0.2092 | 5.410 | 5.555 | 4.620 |
| 6 | 130 | 4.935 | 0.1943 | 5.029 | 5.159 | 4.115 |
| 7 | 120 | 4.554 | 0.1793 | 4.651 | 4.763 | 3.665 |
| **8** | 110 | 4.176 | 0.1644 | 4.270 | 4.366 | 3.264 |
| **9** | 100 | 3.797 | 0.1495 | 3.891 | 3.967 | 2.906 |
| **10** | 90 | 3.416 | 0.1345 | 3.510 | 3.571 | 2.588 |
| **11** | 80 | 3.038 | 0.1196 | 3.132 | 3.175 | 2.304 |
| **12** | 70 | 2.657 | 0.1046 | 2.753 | 2.779 | 2.052 |
| **13** | 60 | 2.278 | 0.0897 | 2.372 | 2.380 | 1.829 |
| **14** | 50 | 1.897 | 0.0747 | 1.994 | 1.984 | 1.628 |
| **15** | 45 | 1.709 | 0.0673 | 1.803 | 1.786 | 1.450 |
| **16** | 40 | 1.519 | 0.0598 | 1.613 | 1.588 | 1.290 |
| **17** | 36 | 1.367 | 0.0538 | 1.461 | 1.427 | 1.151 |
| **18** | 32 | 1.214 | 0.0478 | 1.311 | 1.270 | 1.024 |
| **19** | 28 | 1.062 | 0.0418 | 1.158 | 1.110 | 0.912 |
| **20** | 24 | 0.912 | 0.0359 | 1.006 | 0.953 | 0.813 |
| **21** | 22 | 0.836 | 0.0329 | 0.930 | 0.874 | 0.724 |
| **22** | 20 | 0.759 | 0.0299 | 0.853 | 0.792 | 0.643 |
| **23** | 18 | 0.683 | 0.0269 | 0.777 | 0.714 | 0.574 |
| **24** | 16 | 0.607 | 0.0239 | 0.701 | 0.635 | 0.511 |
| 25 | 14 | 0.531 | 0.0209 | 0.627 | 0.556 | 0.455 |
| 26 | 12 | 0.455 | 0.0179 | 0.551 | 0.475 | 0.404 |
| 27 | 11 | 0.417 | 0.0164 | 0.513 | 0.437 | 0.361 |
| 28 | 10 | 0.378 | 0.0149 | 0.475 | 0.396 | 0.320 |
| 29 | 9 | 0.343 | 0.0135 | 0.437 | 0.358 | 0.287 |
| 30 | 8 | 0.305 | 0.0120 | 0.399 | 0.318 | 0.254 |
| 31 | 7 | 0.267 | 0.0105 | 0.361 | 0.277 | – |
| 32 | 6.5 | 0.246 | 0.0097 | 0.343 | – | – |
| 33 | 6 | 0.229 | 0.0090 | 0.323 | – | – |
| 34 | 5.5 | 0.208 | 0.0082 | 0.305 | – | – |
| 35 | 5 | 0.191 | 0.0075 | 0.284 | – | – |
| 36 | 4.5 | 0.170 | 0.0067 | 0.267 | – | – |

### 16 GAUGE IS NOT ONE THICKNESS

The number alone does not determine thickness — the material does. At 16 ga the four systems give:

carbon **1.519 mm** · galvanized **1.613 mm** · stainless **1.588 mm** · aluminium **1.290 mm**

That is a **25.0% spread** across four answers that are all correct. Always state the material, not just the gauge.

### HOW THESE NUMBERS ARE DEFINED

**Carbon (MSG)** — nominal weight in oz/ft² divided by 41.82 lb/ft²/in.

**Galvanized** — MSG weight plus 2.5 oz/ft² of zinc coating.

**Stainless** — US Standard Gauge, n/64 in steps.

**Al / brass / Cu** — B&S (AWG) geometric law, $d = 0.127 \times 92^{(36-n)/39}$ mm.

**Rounding** — inch to 4 dp from the defined value, mm derived from that inch × 25.4. Shaded rows 8–24 are the common fabrication range.