

Advanced Persistent Threats (APT)

Rohan Kirti

Bipul Kumar

April 30, 2025

1 Introduction

1.1 Persistent Threat

In the digital world we live in today, many organizations and individuals face threats from hackers and cybercriminals. Some of these attacks are quick and cause immediate damage, but others are much more serious because they happen slowly and quietly over time. These are called persistent threats ([Talib et al., 2022](#)). A persistent threat is when an attacker enters a computer system or network and stays there for a long time without being noticed. The main goal of such an attack is not to destroy data right away but to secretly collect information, monitor activity, or find ways to cause more damage later.

What makes persistent threats especially dangerous is how quietly they work. Attackers do not always try to cause big problems right away. Instead, they study their target carefully, learn how the system works, and look for weak points to get in. Once they gain access, they try to stay hidden by using normal-looking tools and user accounts. They avoid being detected by acting like regular users and may even watch and wait for the best time to act. These kinds of attacks can go on for months or even years without anyone knowing, which makes them very hard to stop.

1.2 Advanced Persistent Threat

Now, when a persistent threat becomes more organized, skilled, and targeted, it is called an Advanced Persistent Threat ([Tatam et al., 2021](#)), or APT. APTs are not carried out by random hackers, but usually by expert groups with special knowledge and tools. These groups are often supported by governments or powerful organizations, which means they have the time, money, and resources to carry out long and complex attacks. The word "advanced" means they use high-level methods like

custom-made viruses, unknown software bugs (called zero-day exploits), and tricky social engineering techniques to fool people into giving up access.

APTs are planned with a clear purpose. The attackers know exactly what they want whether it's secret government information, military plans, private company data, or control of critical systems like electricity or water. They carefully choose their targets and work step by step to reach their goal. Because they use smart and quiet methods, many APTs go unnoticed for a long time (Cho and Nam, 2019). When they are finally discovered, they may have already stolen large amounts of information or caused serious damage. This is why APTs are a major concern for cybersecurity experts around the world. To protect against them, we must understand how these threats work, how they stay hidden, and how we can detect and stop them in time.

APTs have evolved significantly over the years. Early examples of APTs were focused on military and government systems, but now they have expanded into sectors like healthcare, energy, banking, and technology. As more devices are connected to the internet and digital systems become more complex, the chances of being targeted by an APT increase. Small businesses are not immune either many APT attackers use smaller companies as a way to access larger organizations they are connected to.

It is also important to note that APTs are not just technical problems they involve human weaknesses as well. Attackers often use social engineering to trick employees into clicking harmful links or sharing passwords. That is why cybersecurity awareness and training are just as important as firewalls and antivirus software. By educating users and building a culture of security, organizations can reduce the chances of falling victim to these long-term threats.

In addition to the technical complexity and long-term nature of APTs, the legal and ethical challenges surrounding these threats have become a topic of global discussion. Many APT attacks originate from foreign nations, leading to political tension and accusations of cyber espionage. Governments are now taking steps to improve their cybersecurity laws and collaborate internationally to fight against APT groups. Organizations must follow best practices and sometimes even legal regulations to report breaches and take preventive measures.

Moreover, the financial impact of APTs cannot be ignored. Companies that suffer from such attacks often face large financial losses due to data breaches, damaged reputation, lawsuits, and the cost of incident response. In some industries, a single APT attack can result in the loss of customer trust, reduced stock prices, or exposure of confidential intellectual property (Xing et al., 2020). Therefore, managing the risk of APTs is not just the responsibility of IT departments but of senior leadership as well.

In summary, persistent threats and APTs represent some of the most serious dangers in today's cybersecurity environment. Their ability to stay hidden, steal information quietly, and operate over

long periods makes them hard to detect and even harder to stop. They require a combined approach involving technology, employee training, legal support, and leadership awareness. The rest of this paper will explore how APTs work, how they have affected real-world targets, and what can be done to defend against them effectively.



Figure 1: APT Threat Characteristics

2 Literature review

Over the years, cybersecurity experts and researchers have studied Advanced Persistent Threats (APTs) to understand how they work and how to protect against them. APTs are not like regular cyberattacks—they are more targeted, organized, and often carried out by skilled attackers, sometimes with support from governments. This section looks at what different studies and experts have found about APTs, including how these threats happen, the tools and tricks attackers use, and how we can defend against them.

One of the first major APT attacks was known as Titan Rain in the early 2000s. It targeted U.S. defense companies and was believed to be carried out by hackers from China. After that, many other APT cases came to light, like the famous Stuxnet attack, which targeted Iran's nuclear program, and APT29, which was linked to Russian hackers. Researchers who studied these attacks found that APTs are carefully planned and can go on for a long time before being discovered.

Many experts describe APT attacks in stages. First, attackers collect information about their target

(reconnaissance). Then they find a way into the system, often using phishing emails or software bugs. Once inside, they try to stay hidden while gaining more access. Finally, they carry out their mission, like stealing data or spying. This step-by-step method has been described in studies like the one by Hutchins et al., which talks about something called the "kill chain"—a way to understand and stop cyberattacks at each stage.

Researchers have also found that APT groups often use advanced malware and unknown software flaws (called zero-day vulnerabilities) to sneak into systems. For example, reports from cybersecurity companies like Symantec and FireEye show that phishing remains one of the easiest ways for attackers to trick users and get inside networks. Malware like Flame and Duqu were used in past APTs and could spy on users, steal files, and even take control of devices remotely.

2.1 Tools and Tricks Used by APT Attackers

APT groups use advanced tools and tactics to infiltrate systems and maintain long-term, undetected access. Unlike general cyberattacks, APTs are highly targeted, often focusing on government, critical infrastructure, or large corporations using custom malware and social engineering.

2.1.1 Exploits and Malware

Malware plays a pivotal role in the success of an APT attack. This type of malware is highly customized and specifically designed to evade detection by conventional security systems, such as antivirus software. Unlike basic malware, which is easily identified by standard tools, APT malware often uses techniques like polymorphism (changing its code) and encryption to avoid detection. Furthermore, it is often designed to operate in the background, causing little to no disruption to the targeted system, which allows the attackers to maintain control for extended periods.

The complexity of APT malware is evident in examples like the Stuxnet worm, which was responsible for sabotaging Iran's nuclear facilities. Stuxnet targeted industrial control systems and specifically manipulated the centrifuges controlling the nuclear enrichment process ([Khalid, Al-Kadhimi and Singh, 2023](#)). The malware was designed to remain undetected while damaging the equipment, making it one of the first well-known cyberattacks aimed at physical infrastructure. Another example is Flame, which was discovered in 2012 and was capable of stealing a wide range of sensitive data, including documents, screenshots, and even recording audio from the compromised systems. The malware used in APT attacks is often equipped with multiple functionalities, including remote access to systems, data exfiltration, and network reconnaissance. APT actors typically modify the malware over time, ensuring it adapts to avoid detection by evolving security measures.

Table 1: Tools and Tricks Used by APT Attackers

Category	Description
Exploits and Malware	Customized malware that avoids detection using techniques like polymorphism, encryption, and stealth operation. Advanced threats like Stuxnet target specific systems such as industrial control systems. These tools can operate silently for long durations, enabling data theft, surveillance, and system sabotage. Attackers continuously modify malware to evade evolving security tools.
Social Engineering and Phishing	Psychological tactics used to trick users into compromising security. APT actors craft spear-phishing emails after researching targets, often impersonating trusted individuals or organizations. These emails may carry malware or redirect to credential harvesting sites. This technique exploits human error, bypassing even the most advanced technical defenses.
Defensive Strategies and Frameworks	Multi-layered security strategies such as Defense-in-Depth combine tools like firewalls, intrusion detection systems, access control, and endpoint monitoring. Frameworks like NIST Cybersecurity Framework and ISO/IEC 27001 guide organizations in structuring robust cyber defense systems against APTs.
Threat Detection and Intelligence	Involves the use of AI, machine learning, and big data analytics to monitor network behavior and detect anomalies. Threat intelligence feeds provide real-time updates on known APT tactics. Platforms such as MITRE ATT&CK help map attack patterns and inform proactive defenses. Continuous monitoring and early warning systems are critical for minimizing impact.
Incident Response and Mitigation	Procedures followed when an APT is detected, including containment, eradication, and recovery. Involves disconnecting affected systems, analyzing the root cause, and restoring operations securely. Also includes post-incident reviews, patch management, and updating training for users. Simulation exercises like red teaming improve response readiness.
Command and Control Infrastructure	APT groups establish remote communication channels with compromised systems, often using encrypted protocols and compromised legitimate services. This infrastructure allows them to issue commands, receive data, and maintain control over infected networks for long periods.
Lateral Movement and Privilege Escalation	Once inside a network, attackers move laterally across systems to locate valuable assets. Tools like Mimikatz and Pass-the-Hash techniques are used to escalate privileges and access secured areas of the network. This stage is critical for full network compromise.

2.1.2 Social Engineering and Phishing

While technical exploits are crucial for gaining access to a target system, social engineering remains one of the most effective methods for APT groups to gain an initial foothold. Social engineering involves manipulating individuals into performing actions that lead to a security breach, such as clicking on a malicious link or downloading an infected attachment. Phishing, which is the most common form of social engineering, is often used to lure victims into providing sensitive information like login credentials or opening malicious files.

APT attackers typically invest considerable time researching their target, crafting convincing phishing emails that appear legitimate. For example, they may impersonate trusted colleagues or send emails that appear to come from reputable institutions like banks, government agencies, or business partners. These emails often include attachments or links that, when opened, install malware on the victim's computer or lead to a fake login page designed to steal sensitive information.

Phishing is particularly dangerous because it exploits the human element of cybersecurity. Even the most advanced security systems can be bypassed if an employee inadvertently provides access to an attacker. Data from Verizon's Data Breach Investigations Report (DBIR) highlights that phishing remains one of the top entry methods for APTs. Once a single employee interacts with the phishing email, it can open the door for further exploitation, often compromising an entire network.

2.2 Defensive Strategies and Frameworks

In response to the growing threat of APTs, researchers and cybersecurity experts have developed several defense strategies designed to prevent, detect, and mitigate these sophisticated attacks. Defending against APTs requires a multi-layered approach, combining advanced detection techniques, proactive defense mechanisms, and well-defined incident response strategies. A key strategy is the implementation of the Defense-in-Depth approach, which employs multiple layers of security across all aspects of an IT environment to ensure that even if one layer is breached, others can provide protection.

2.2.1 Threat Detection and Intelligence

The first and most critical defense against APTs is detection. Due to the persistent nature of these attacks, it is essential to identify APT activity as early as possible to limit the damage. Traditional security measures such as firewalls and antivirus programs are not enough to detect these advanced threats. To combat this, many organizations have adopted continuous monitoring and threat detection tools that analyze network traffic for signs of abnormal behavior.

Advanced techniques such as behavioral analysis and anomaly detection are increasingly being used to spot APTs. These systems look for unusual patterns that could indicate a breach, such as unexpected data transfers, access to sensitive files, or communication with external servers. Machine learning and artificial intelligence are playing a pivotal role in enhancing threat detection. AI systems can analyze vast amounts of data quickly, identifying hidden threats that traditional methods might miss.

Threat intelligence sharing is another essential part of a robust defense strategy. By sharing information about the latest APT tactics, techniques, and procedures (TTPs), organizations can stay ahead of emerging threats. Frameworks like MITRE ATT&CK provide a detailed catalog of common APT tactics, allowing security teams to better understand attack strategies and develop proactive defenses.

2.2.2 Incident Response and Mitigation

Despite best efforts, some APTs will inevitably breach defenses. In such cases, having a comprehensive incident response plan is critical. An incident response plan is a set of predefined steps an organization takes when an attack is detected, aimed at containing the damage, removing the threat, and recovering from the attack. A good plan includes immediate actions such as isolating compromised systems, identifying how the attack occurred, and eliminating any malware from the network. Post-incident recovery is just as important. After containing the threat, organizations must analyze the root cause of the breach to prevent future attacks. This may involve patching vulnerabilities, improving security controls, and strengthening employee training programs. Red team exercises, where security experts simulate APT attacks, are also useful for testing an organization's defenses and response capabilities.

In conclusion, defending against APTs requires a comprehensive strategy that incorporates advanced threat detection, continuous monitoring, and a well-practiced incident response plan. By using a combination of technology, threat intelligence, and employee awareness, organizations can better protect themselves from these highly sophisticated and persistent attacks.

3 Theory

This section explains how the study on Advanced Persistent Threats (APTs) was carried out. The main aim is to understand how APTs work, what tools they use, and how we can defend against them. This study uses a combination of different research methods, focusing mostly on reading and analyzing information from trusted sources. These include cybersecurity reports, case studies, and expert analyses. The research is mainly descriptive and tries to explain what APTs are, how they




Figure 2: Origin of APT attackers

behave, and how we can stop them.

3.1 Approach

This adopts a mixed-methods approach, combining both qualitative and exploratory elements to provide a comprehensive understanding of Advanced Persistent Threats. The qualitative aspect focuses on examining detailed descriptions and real-world scenarios from secondary data sources, such as case studies and technical reports. Meanwhile, the exploratory element allows for the identification of new patterns and strategies used by APT actors, helping to keep the study relevant in a fast-evolving cyber landscape.

The rationale behind this approach is to not only describe APT behavior but also to explore the motivations and operational frameworks behind these sophisticated threats. Using this method ensures a holistic view of APT operations, from entry tactics to long-term persistence and data exfiltration strategies.

The core objectives includes:

- To provide a clear, structured overview of how APTs are typically executed.
- To analyze the evolution of APT tactics, techniques, and procedures (TTPs).
- To identify common vulnerabilities exploited by APT groups.

-
- To evaluate the effectiveness of current defensive strategies.
 - To suggest improvements in detection and response mechanisms using industry standards and frameworks like MITRE ATT&CK.

This approach was chosen due to its flexibility in dealing with complex cybersecurity issues. It allows for an in-depth investigation of both historical and current APT incidents, offering valuable insights for both academic researchers and cybersecurity practitioners.

3.2 Data Collection

The information for this study comes from reliable secondary sources. These include:

- Academic articles and books on cybersecurity.
- Cybersecurity company reports (like FireEye, CrowdStrike, etc.).
- Government documents and white papers.
- News articles and case studies about real APT attacks.

These sources help to give a clear picture of how APTs work in the real world. Most of the information is from the past 10 years, so it is up-to-date and relevant.

3.3 Data Analysis

Once the information was collected, it was reviewed to find common patterns. This process is called thematic analysis. For example, the study looked for repeated methods used by attackers, like phishing or using malware to get into systems.

The research also compares different defense methods used by organizations. This helps to see which methods work best against APTs. Examples include behavior monitoring, firewalls, and employee training. The study also looks at how well-known frameworks like MITRE ATT&CK are used to fight these threats.

3.4 Case Study Analysis

To make it more practical, real APT attack cases were included. These case studies show how different attacker groups (like APT28 ([Niakanlahiji, Wei and Chu, 2018](#)) or Lazarus Group) operated, how they got into systems, what damage they did, and how companies responded.




Figure 3: APT Detection Mechanism

One example is the Stuxnet attack, which targeted Iran’s nuclear facilities. Another is the Solar-Winds attack, which affected many U.S. government agencies. These real examples help explain the methods and impact of APTs.

3.5 Execution Mechanism of APTs

APTs follow a highly organized execution mechanism that consists of several well-planned steps. Each step is carefully designed to avoid detection and achieve long-term access to the target system. The execution mechanism typically includes:

1. **Reconnaissance:** Attackers gather information about the target using open-source tools and social engineering techniques. This helps them identify vulnerabilities and entry points.
2. **Initial Access:** APT actors use spear-phishing emails, malicious attachments, or exploit known software vulnerabilities to gain a foothold in the network.
3. **Establishing a Foothold:** Once inside, attackers install malware such as Remote Access Trojans (RATs) or backdoors to maintain their presence.
4. **Privilege Escalation:** After gaining access, attackers attempt to increase their privileges within the system by exploiting weak passwords, vulnerabilities, or misconfigurations.
5. **Lateral Movement:** With higher privileges, attackers move laterally through the network, accessing more systems and gathering sensitive data.
6. **Data Collection and Exfiltration:** Once valuable information is found, attackers package and transfer the data out of the network, often using encrypted channels to avoid detection.

-
7. **Maintaining Presence:** APTs are known for maintaining access to systems for long periods. Attackers set up multiple access points, so even if one is detected and removed, they can re-enter the system.

This execution cycle is not linear but adaptable. Attackers may revisit earlier stages as needed to adjust their strategies. The main focus remains on staying hidden and extracting as much valuable data as possible without alerting the victim.

3.6 Ethical Considerations

This Study only uses public information, so it does not involve any risk to people. All sources are properly credited, and no secret or personal data is used. The study is done for learning purposes and to help improve cybersecurity awareness.

3.7 Limitations

There are some limitations to this study:

- It depends on published reports, which may not include full details.
- Some APT attacks are never made public.
- Cyber threats change quickly, so some information may become outdated soon.

Still, this helps to provide a clear and updated understanding of how APTs work and how to defend against them.

4 Analysis

This section presents a clear and simplified analysis of Advanced Persistent Threats (APTs) based on the findings from the literature review and the research methodology. The goal is to understand common attack behaviors, identify key weaknesses in cybersecurity defenses, and recommend better practices.

4.1 Common Patterns in APT Behavior

Through analyzing various APT incidents, certain common patterns of behavior emerge that can be observed across different threat actors. The first phase of an APT attack usually involves careful reconnaissance, often conducted by scanning open-source intelligence (OSINT) and social media

platforms. Attackers gather information about the target, such as employee names, organizational structure, and vulnerabilities within the IT infrastructure (Jia et al., 2023). This stage is critical for attackers as it provides the necessary data to craft convincing spear-phishing emails or exploit known vulnerabilities.

Once attackers have identified potential entry points, they move to the next phase, where they typically use phishing emails or malicious attachments to initiate the attack. These emails often appear to come from trusted sources, making them highly effective in deceiving employees into clicking on malicious links or opening infected attachments. After the initial breach, attackers deploy Remote Access Trojans (RATs) or similar tools to maintain persistent access to the compromised system.

In the later stages of the attack, the attackers aim to escalate privileges and move laterally within the network to expand their control over various systems. They may exploit weak passwords or unpatched vulnerabilities to gain administrative privileges, enabling them to access sensitive data and other critical systems. Ultimately, the attackers exfiltrate valuable information, often maintaining stealthy access to the network for extended periods. This pattern demonstrates the careful and methodical approach of APT groups, which distinguishes them from more opportunistic and fast-moving cybercriminals.

Advanced Persistent Threat (APT) Lifecycle




Figure 4: Life cycle of Advanced Persistent Threat

4.2 Weaknesses in Defense Systems

The analysis reveals several key weaknesses in the defense systems of many organizations that contribute to their vulnerability to APTs. One of the most significant vulnerabilities is the lack of timely software updates and patch management. Many APTs rely on exploiting unpatched software vulnerabilities to gain access to networks. When organizations fail to keep their systems updated, they essentially leave the door open for attackers to exploit known weaknesses.

Another critical weakness lies in employee awareness and training. Phishing attacks remain one of the most common vectors for APT entry, yet many organizations fail to provide comprehensive security awareness training. Without proper training, employees are more likely to fall victim to phishing emails or social engineering tactics, allowing attackers to gain a foothold in the system. Even when employees are trained, the sophistication of APT phishing campaigns makes them harder to detect, leading to successful intrusions.

A lack of real-time monitoring and an inefficient incident response strategy also pose significant threats. Many organizations only discover APTs after the attackers have already exfiltrated critical data or have caused considerable damage. Inadequate or nonexistent security operations centers (SOCs) result in a delayed response to incidents, further allowing attackers to exploit their position within the network. Additionally, many organizations still use a siloed approach to cybersecurity, where different departments and tools are not integrated, creating gaps in the overall defense.

The analysis also reveals that traditional security tools such as firewalls and antivirus software, while necessary, are often not sufficient to defend against APTs. These tools primarily rely on signature-based detection, which is ineffective against the advanced, custom-made malware often used by APT groups. As a result, organizations must focus on implementing more advanced and proactive security measures that go beyond these traditional tools.

4.3 Case Study Insights

The analysis of case studies, such as the SolarWinds attack and the Stuxnet worm, offers valuable insights into the methods and impacts of APT attacks. In the SolarWinds attack, cybercriminals gained access to the software development process of a popular IT management tool, which was then used as a launchpad to infiltrate the networks of thousands of organizations worldwide. This sophisticated supply chain attack demonstrated the vulnerability of even well-secured software infrastructure and the complex nature of APT strategies.

The Stuxnet worm is another high-profile case that shows the extreme sophistication of APTs. Stuxnet targeted industrial control systems (ICS), specifically designed to sabotage Iran's nuclear enrich-

ment program. The worm was capable of manipulating industrial equipment while hiding its tracks, causing physical damage without alerting the operators. This attack emphasized the risks of APTs targeting critical infrastructure and highlighted the growing convergence between cyberattacks and national security.

Both case studies underline the importance of strengthening defense mechanisms across all stages of the attack lifecycle. Organizations must ensure that they not only monitor their internal systems but also consider vulnerabilities in their supply chains and external partners. Additionally, these incidents highlight the need for a broader focus on securing critical infrastructure, as APTs increasingly target sectors that are vital to national security, energy, and finance.

4.4 Recommendations

Based on the analysis of the APT attack lifecycle and common defense weaknesses, several recommendations are proposed to mitigate the risks associated with APTs. Firstly, organizations should prioritize regular software updates and patch management as a fundamental security practice. Automated patching systems can significantly reduce the time between the release of security patches and their application, minimizing the window of opportunity for attackers.

Secondly, enhancing employee training and awareness is crucial. Employees should be regularly educated about the latest phishing techniques and social engineering tactics, as these are the primary methods of APT entry. Phishing simulations can also be conducted to test and improve employee vigilance in recognizing suspicious emails.

Furthermore, the implementation of behavior-based monitoring tools is highly recommended. Traditional signature-based detection methods are no longer enough to detect sophisticated APT activities. Tools that monitor system behaviors for abnormal activities, such as sudden privilege escalation or unusual data access patterns, can help detect APTs at earlier stages of the attack lifecycle.

Organizations should also adopt a multi-layered security approach that includes network segmentation, access control, and the principle of least privilege. A zero-trust architecture, where all users and devices are considered untrusted until proven otherwise, provides an additional layer of security and can help contain attacks within limited sections of the network. Lastly, organizations should use threat intelligence frameworks such as MITRE ATT&CK to enhance their detection and response capabilities. This framework allows organizations to understand attacker tactics and predict potential attack vectors, making it easier to defend against specific APT groups. By focusing on these areas, organizations can strengthen their cybersecurity posture and improve their ability to detect and mitigate APT attacks before they cause significant damage.

5 Conclusion

Advanced Persistent Threats (APTs) represent one of the most sophisticated and prolonged types of cyberattacks that continue to pose significant challenges for organizations worldwide. This paper has explored the complex nature of APTs, starting with an in-depth review of their characteristics and behaviors, followed by an examination of their execution mechanisms, defense weaknesses, and the effectiveness of current defense strategies. By analyzing well-documented APT incidents and applying the MITRE ATT&CK framework, this study offers insights into the recurring tactics, techniques, and procedures (TTPs) used by these threat actors.

APTs are unique in that they involve a prolonged and strategic approach to cyberattacks, with attackers gaining stealthy access to networks, escalating privileges, and exfiltrating sensitive data over extended periods. These attacks are not opportunistic but methodical, making them harder to detect and stop with traditional cybersecurity measures. Through case studies such as SolarWinds and Stuxnet, it is clear that APTs can not only cause significant financial damage but can also have serious political and national security ramifications.

It highlights that many organizations remain vulnerable to APTs due to several common weaknesses. These include outdated software, a lack of employee awareness, insufficient real-time monitoring, and inadequate incident response plans. Additionally, traditional security systems, such as firewalls and antivirus software, while necessary, often fail to detect the advanced and custom-made malware used in APT attacks.

To combat these threats, the paper has proposed a comprehensive set of recommendations. These include regular software updates and patch management, continuous employee training on phishing and social engineering tactics, behavior-based monitoring systems, multi-layered security defenses, and the use of intelligence frameworks like MITRE ATT&CK for better threat detection and response. By adopting a proactive and strategic approach to cybersecurity, organizations can better defend themselves against APTs and mitigate the risks posed by these persistent and evolving threats.

In conclusion, APTs are a major cybersecurity challenge that requires coordinated, multi-faceted defense strategies. While the threat landscape continues to evolve, organizations that stay informed, continuously update their systems, and adopt best practices in threat detection and response will be better prepared to defend against these advanced attacks. The findings from this study contribute to a greater understanding of APTs and offer practical insights that can help strengthen defenses in the face of growing cyber threats.

References

- Cho, Do Xuan and Ha Hai Nam. 2019. "A method of monitoring and detecting APT attacks based on unknown domains." *Procedia Computer Science* 150:316–323.
- Jia, Mingdi, Licheng Yu, Xiaoxuan Li, Yijun Li, Xiwen He, Langxing Chen and Yukui Zhang. 2023. "An aptamer-functionalized photonic crystal sensor for ultrasensitive and label-free detection of aflatoxin B1." *Talanta* 260:124638.
- Khalid, Mohd Nor Akmal, Amjed Ahmed Al-Kadhimi and Manmeet Mahinderjit Singh. 2023. "Recent developments in game-theory approaches for the detection and defense against advanced persistent threats (APTs): a systematic review." *Mathematics* 11(6):1353.
- Niakanlahiji, Amirreza, Jinpeng Wei and Bei-Tseng Chu. 2018. A natural language processing based trend analysis of advanced persistent threat techniques. In *2018 IEEE International Conference on Big Data (Big Data)*. IEEE pp. 2995–3000.
- Talib, Manar Abu, Qassim Nasir, Ali Bou Nassif, Takua Mokhamed, Nafisa Ahmed and Bayan Mahfood. 2022. "APT beaconing detection: A systematic review." *Computers & Security* 122:102875.
- Tatam, Matt, Bharanidharan Shanmugam, Sami Azam and Krishnan Kannoorpatti. 2021. "A review of threat modelling approaches for APT-style attacks." *Heliyon* 7(1).
- Xing, Kai, Aiping Li, Rong Jiang and Yan Jia. 2020. A review of APT attack detection methods and defense strategies. In *2020 IEEE Fifth International Conference on Data Science in Cyberspace (DSC)*. IEEE pp. 67–70.

Statutory Declaration

We hereby declare that the paper presented is our own work and that we have not called upon the help of a third party. In addition, we affirm that neither us nor anybody else has submitted this paper or parts of it to obtain credits elsewhere before. We have clearly marked and acknowledged all quotations or references that have been taken from the works of others. All secondary literature and other sources are marked and listed in the bibliography. The same applies to all charts, diagrams and illustrations as well as to all internet resources. Moreover, We consent to our paper being electronically stored and sent anonymously in order to be checked for plagiarism.