PENTESTER ACADEMYTOOL BOX PENTESTING

OF THE PENTESTER ACADEMYTOOL BOX PENTESTING

OF THE PENTESTING HACKER PENTESTER

TEAM LABSPENTES TO THE PENTESTER

TEAM LABSPENTES TO THE PENTESTER

OF THE PENTESTING HACKER

THE PENTESTING HACKER

TOOL BOX

OF THE PENTESTING

Name	Wrong Locale
URL	https://www.attackdefense.com/challengedetails?cid=587
Туре	Secure Coding : Python

**Important Note:** This document illustrates all the important steps required to complete this lab. This is by no means a comprehensive step-by-step solution for this exercise. This is only provided as a reference to various commands needed to complete this exercise and for your further research on this topic.

A vulnerable python source code file (script.py) is given in student's home directory.

Objective: Execute the script in such a manner that it prints "Locale based bypass successful!"

## Solution

On executing the python script, one can observe that the program prints the present locale information.

```
student@attackdefense:~$ python script.py
('en_US', 'ISO8859-1')
student@attackdefense:~$
```

Check the given python script. It is clear that the unreachable code will only be executed if value for local locale is set to wrong values.

```
student@attackdefense:~$ cat script.py
import locale
try:
    loc = locale.getdefaultlocale()
    print loc
except ValueError:
    print "Locale based bypass successful!"
student@attackdefense:~$
```

Make sure that the value of the locale is set to wrong i.e. export LC\_All=en\_XX

Execute the script to get the desired output.

```
student@attackdefense:~$ LC_ALL=en_XX
bash: warning: setlocale: LC_ALL: cannot change locale (en_XX): No such file or directory
student@attackdefense:~$ python script.py
Locale based bypass successful!
student@attackdefense:~$
```