




<b>Name</b>	GraphQL Basics IV
<b>URL</b>	<a href="https://attackdefense.com/challengedetails?cid=1993">https://attackdefense.com/challengedetails?cid=1993</a>
<b>Type</b>	REST: GraphQL

**Important Note:** This document illustrates all the important steps required to complete this lab. This is by no means a comprehensive step-by-step solution for this exercise. This is only provided as a reference to various commands needed to complete this exercise and for your further research on this topic. Also, note that the IP addresses and domain names might be different in your lab.


When the lab is launched, the Insomnia app is launched.



This application would be used to write the GraphQL queries in this lab.


**Step 1:** Create a New Request.

Click on the New Request button:



Provide a name to the New Request, eg: GraphQL Demo and then click on Create.

That would lead to the following view:



**Step 2:** Determine the IP address of the target server running GraphQL.

**Command:** ifconfig

```
root@attackdefense:~# ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.1.1.5 netmask 255.255.255.0 broadcast 10.1.1.255
    ether 02:42:0a:01:01:05 txqueuelen 0 (Ethernet)
    RX packets 5943 bytes 559634 (546.5 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 5377 bytes 3179981 (3.0 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

eth1: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.135.215.2 netmask 255.255.255.0 broadcast 192.135.215.255
    ether 02:42:c0:87:d7:02 txqueuelen 0 (Ethernet)
    RX packets 26 bytes 2012 (1.9 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1000 (Local Loopback)
    RX packets 18874 bytes 41975307 (40.0 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 18874 bytes 41975307 (40.0 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0


root@attackdefense:~#
```

The IP address of the machine is 192.135.215.2.


So the target GraphQL endpoint must be located at 192.135.215.3 on port 8080.


**Step 3:** Interacting with the GraphQL endpoint.

Now, since the IP address of the GraphQL endpoint is known, specify the IP address and the port number in the top bar:



Click on the Body tab and select the option "GraphQL Query" from the dropdown.






As it is mentioned in the challenge description that the introspection queries are not disabled. That means that the GraphQL schema could be accessed from the console and auto-completion would also work.


### Exploring the GraphQL Schema:

Click on the schema button on the top right of the console window.





Click on Show Documentation:



The Schema panel could be used to view the GraphQL schema.

Notice that we have Query and Mutation types.

1. **Query Type:** Used to make queries to get data from the server.
2. **Mutations:** Used to make changes to server-side data.

Click on Queries.

That leads to the following page:

< Schema

Query

x

*no description*

## Fields

```
node(  
  id: ID!  
): Node  
  The ID of the object  
  
searchPerson(  
  name: String  
  email: String  
  friends: [PersonInput]  
  subscribedMovies: [MoviesInput]  
): [Person]  
  
searchMovies(  
  name: String  
  rating: String  
  releaseYear: Int  
): [Movies]  
  
person(  
  sort: [PersonSortEnum]  
  before: String  
  after: String  
  
movies(  
  sort: [MoviesSortEnum]  
  before: String  
  after: String  
  first: Int  
  last: Int  
): MoviesConnection
```

So, there are 5 fields: node, searchPerson, searchMovies, person and movies.

For instance, searchMovies accepts movie name, rating and releaseYear.

Go back to the starting page of the explorer and explore the mutations:



## Schema

x

A GraphQL schema provides a root type for each kind of operation.

## Root Types

query: Query

mutation: Mutation

Click on Mutations.

< Schema

## Mutation

x

*no description*

## Fields

```
addPerson(  
  subscribedMovies: [MoviesInput]  
  friends: [PersonInput]  
  email: String!  
  name: String!  
): AddPerson  
  
addMovie(  
  rating: String!  
  name: String!  
  releaseYear: Int!  
): AddMovie
```

We have 2 mutations:

addPerson and addMovie to add a new Person and a new movie to the database, respectively.

#### Step 4: Making queries to the backend database.


Writing queries in the console window to fetch the desired results from the backend database:

1. Use the following query to fetch all the movies objects and display the name, rating, and releaseYear fields.

#### Query:

```
{
  movies {
    edges {
      node {
        name
        rating
        releaseYear
      }
    }
  }
}
```

Send the above request by clicking the Send button:



Response:

```
Preview ▾ Header 4 Cookie Timeline
1 {
2   "data": {
3     "movies": {
4       "edges": [
5         {
6           "node": {
7             "name": "Inception",
8             "rating": "8.8/10",
9             "releaseYear": 2010
10          }
11        },
12        {
13          "node": {
14            "name": "Interstellar",
15            "rating": "8.6/10",
16            "releaseYear": 2014
17          }
18        },
19        {
20          "node": {
21            "name": "The Godfather",
22            "rating": "9.2/10",
23            "releaseYear": 1972
24          }
25        },
26        {
27          "node": {
28            "name": "Forrest Gump",
29            "rating": "8.8/10",
30            "releaseYear": 1994
31          }
32        },
33        {
34          "node": {
35            "name": "Venom",
36            "rating": "6.7/10",
37            "releaseYear": 2018
38          }
39        },

```

2. Use the following query to fetch all the person objects and display their name, email, name of subscribed movies and the name of their friends.

### Query:

```
{
  person {
    edges {
      node {
        name
        email
        subscribedMovies {
          edges {
            node {
              name
            }
          }
        }
        friends {
          edges {
            node {
              name
            }
          }
        }
      }
    }
  }
}
```

Send the request with this query.

### Response:

```
{
  "data": {
    "person": {
      "edges": [
        {
          "node": {
            "name": "John Doe",
            "email": "johndoe@example.com",
            "subscribedMovies": {
              "edges": [
                {
                  "node": {
                    "name": "Inception"
                  }
                },
                {
                  "node": {
                    "name": "Interstellar"
                  }
                },
                {
                  "node": {
                    "name": "The Godfather"
                  }
                }
              ]
            }
          },
          "friends": {
            "edges": [
              {
                "node": {
                  "name": "David Smith"
                }
              },
              {
                "node": {
                  "name": "Michael Jones"
                }
              }
            ]
          }
        }
      ]
    }
  }
},
```

...

```

    },
    {
      "node": {
        "name": "James Williams",
        "email": "jameswilliams@example.com",
        "subscribedMovies": {
          "edges": [
            {
              "node": {
                "name": "Interstellar"
              }
            },
            {
              "node": {
                "name": "Harry Potter and the Sorcerer's Stone"
              }
            },
            {
              "node": {
                "name": "Rocky"
              }
            }
          ]
        },
        "friends": {
          "edges": [
            {
              "node": {
                "name": "John Doe"
              }
            },
            {
              "node": {
                "name": "Michael Jones"
              }
            }
          ]
        }
      }
    }
  ]
}

```

**Note:** While typing the queries, the editor would provide suggestions (auto-completion) since the Introspection Queries are not disabled (in default settings).




## Step 5: Modifying the backend database using mutations.

1. Use the following mutation to add a new movie to the backend database:

### Mutation:

```
mutation {  
  addMovie(name: "Jumanji: The Next Level", rating: "6.8/10", releaseYear: 2019) {  
    movies {  
      name  
      rating  
      releaseYear  
    }  
  }  
}
```

### Response:



The screenshot shows a GraphQL IDE with a dark theme. The 'Preview' tab is active, displaying the JSON response of the mutation. The response is a nested object with 'data' containing 'addMovie', which in turn contains 'movies'. The 'movies' array has one element with the details of the added movie.

```
1 {  
2   "data": {  
3     "addMovie": {  
4       "movies": {  
5         "name": "Jumanji: The Next Level",  
6         "rating": "6.8/10",  
7         "releaseYear": 2019  
8       }  
9     }  
10  }  
11 }
```

The movie got successfully added to the list of movies.

Notice that just like in queries, if the mutation field returns an object type, we can ask for nested fields. This can be useful for fetching the new state of an object without making multiple requests to the backend.

Making a query to fetch all the movies would confirm that the above movie was added to the database:

### Query:

```
{
  movies {
    edges {
      node {
        name
        rating
        releaseYear
      }
    }
  }
}
```

### Response:

```
{
  "data": {
    "movies": {
      "edges": [
        {
          "node": {
            "name": "Inception",
            "rating": "8.8/10",
            "releaseYear": 2010
          }
        },
        {
          "node": {
            "name": "Interstellar",
            "rating": "8.6/10",
            "releaseYear": 2014
          }
        },
        {
          "node": {
            "name": "The Godfather",
            "rating": "9.2/10",
            "releaseYear": 1972
          }
        }
      ]
    }
  }
}
```

...

```

{
  "node": {
    "name": "Jumanji: The Next Level",
    "rating": "6.8/10",
    "releaseYear": 2019
  }
}
}
}
}
}
}
}

```

2. Use the following mutation to add a new Person to the backend database, providing a list of friends and a list of subscribed movies:

### **Mutation:**

```

mutation {
  addPerson(
    name: "James Williams",
    email: "jameswilliams@example.com",
    friends: [
      {
        name: "John Doe"
      },
      {
        email: "michaeljones@example.com"
      }
    ],
    subscribedMovies: [
      {
        name: "Rocky"
      },
      {
        name: "Interstellar"
      },
      {
        name: "Harry Potter and the Sorcerer's Stone"
      }
    ]
  ) {
    person {
      name
      email
    }
  }
}


```

```

    friends {
      edges {
        node {
          name
          email
        }
      }
    }
    subscribedMovies {
      edges {
        node {
          name
          rating
          releaseYear
        }
      }
    }
  }
}

```

**Response:**



```

1 {
2   "data": {
3     "addPerson": {
4       "person": {
5         "name": "James Williams",
6         "email": "jameswilliams@example.com",
7         "friends": {
8           "edges": [
9             {
10              "node": {
11                "name": "John Doe",
12                "email": "johndoe@example.com"
13              }
14            },
15            {
16              "node": {
17                "name": "Michael Jones",
18                "email": "michaeljones@example.com"
19              }
20            }
21          ]
22        },

```

```
...
39 {
40   "node": {
41     "name": "Rocky",
42     "rating": "8.1/10",
43     "releaseYear": 1976
44   }
45 }
46 ]
47 }
48 }
49 }
50 }
51 }
```

A new Person object has been added to the database and its details are also displayed in the response.

**Conclusion:** In this lab we have used "Insomnia" for interacting with the GraphQL endpoint and making different queries and adding objects using mutations.

#### References:

1. GraphQL (<https://graphql.org>)
2. Insomnia (<https://insomnia.rest>)