Spin Glasses and Neural Networks: Multilayer Sherrington–Kirkpatrick Model

Akinzhala Rodion & Ibragimova Kseniia
Moscow Institute of Physics and Technology (MIPT)

Motivation

Analogy between Neural Networks and Spin Glasses:

- Both systems seek out stable configurations by minimizing a cost functional or energy.

Physical perspective:

- Statistical-physics tools (e.g. replica analysis, TAP equations) can describe their evolution and assess stability.

Motivation:

Leverage rigorous physical methods to deepen our understanding of complex ML landscapes

What Is a Spin Glass?

A magnetic system where spins interact through random, competing couplings, preventing uniform order—even at low temperature.

Key features :

- Exponentially many local energy minima
- Mixture of short- and long-range order
- Exponential number of metastable states

Interaction types:

- Positive (ferromagnetic)
- Negative (antiferromagnetic)

The Sherrington–Kirkpatrick Model (MSK)

An Ising spin system with an infinite radius of interaction - each spin interacts with all the others with a random coefficient

$$H_{MSK} = -\sum_{i<j} J_{ij}\,\sigma_i\sigma_j, \quad J_{ij} \sim \mathcal{N}\left(0, \frac{1}{N}\right)$$ [1]

Paramagnetic phase:

- At high T, spins are uncorrelated and flip rapidly—system behaves chaotically

Freezing transition:

- the system becomes non-ergodic, trapping into metastable states

Replica-symmetric solution:

Loses stability for T<Tc, leading to negative entropy at zero temperature

Parisi Ansatz → **RSB**

1)D. Sherrington and S. Kirkpatrick, “Solvable model of a spin-glass”, Phys. Rev. Lett. 35,1792–1796 (1975).

Neural Network as Multilayer Spin Model

Edwards–Anderson (EA): local lattice couplings

(EA) + (MSK) = (MCM)


Neuron as spin $\sigma_i = \pm 1$

Weight as coupling $W_{ij}^{(k)} \to J_{ij}^{(k)}$

Hamiltonian (Multi-Layer Spin Model, MSM):

$$H_{\mathrm{MSK}} = -\sum_{k=1}^{L}\sum_{i=1}^{N_{k-1}}\sum_{j=1}^{N_k} J_{ij}^{(k)}\,\sigma_i^{(k-1)}\,\sigma_j^{(k)}$$

$$J = \begin{pmatrix} 0 & J^{(1)} & 0 & \cdots & 0 \\ (J^{(1)})^T & 0 & J^{(2)} & \cdots & 0 \\ 0 & (J^{(2)})^T & 0 & \cdots & 0 \\ \vdots & \vdots & \vdots & \ddots & J^{(L)} \\ 0 & 0 & 0 & (J^{(L)})^T & 0 \end{pmatrix}$$



Simulated Annealing in Spin Systems

Simulation of the dynamic process of spin flips using the **Monte Carlo** method:

1. Start in a high-temperature, random state.
2. Propose random spin flips (Monte Carlo)
3. Compute energy change ΔE.
4. **The Metropolis Criterion:**
    - If ΔE < 0 — accept
    - If ΔE > 0 — accept with probability: $e^{-\frac{\Delta E}{kT}}$
5. Gradually lower temperature
6. System "freezes" into one of the energy minima

Visualizing Annealing

- **High T (Paramagnet):**


Rapid, random flips; no long-range order.

- **Phase transition:**

Emergence of stable clusters as T drops.

- **Low T:**

Configuration stabilizes into a glassy or ordered state.



Training of system

Stochastic Gradient Descent minimizes a loss function → gradually improves predictions.

- **Initial state:** Weights random ⇒ analogous to paramagnetic spins.
- • **During training:** Loss decreases ⇒ “energy” of the spin model lowers, leading to a more stable configuration.
- • **Effectively:** Cooling allows the network to settle into a metastable, task-relevant state.




График с D. J. Thouless, P. W. Anderson, and R. G. Palmer, “Solution of ‘solvable model of a spin glass’”, Philosophical Magazine 35, 593–601 (1977).

Recipe for the Binarized Network

L2-hinge loss :

$$L = \frac{1}{N} \sum_{i=1}^{N} \sum_{j \neq y_i} \max\left(0, 1 - \hat{y}_{y_i} + \hat{y}_j\right)^2$$

SGD with momentum:

1. **Initialization**: Random weights (Kaiming normal).
2. **Forward pass**: Binary activations.
3. **Backward pass**: Straight-Through Estimator (STE) for gradients through sign: surrogate hard-tanh.
4. **Weight update**: SGD with momentum
5. **Iterate** until convergence.

Optionally combine with simulated-annealing-style temperature scheduling

Straight-Through Estimator (STE)

Activation is non-differentiable ⇒ zero gradient almost everywhere.

STE - method of direct approximation of the gradient through a surrogate continuous function

$$\varphi_{\text{forward}}(x) = \text{sign}(x) \xrightarrow{\textbf{STE}} \varphi_{\text{back}}(x) = \text{htanh}(x) = \begin{cases} -1, & x < -1 \\ x, & -1 \le x \le 1 \\ 1, & x > 1 \end{cases}$$

- **Forward pass:** use hard sign
- **Backward pass:** pretend derivative is that of hard-tanh surrogate

$$\delta^{(l)} = (\delta^{(l+1)} \cdot W^{(l+1)}) \cdot \varphi\prime(z^{(l)})$$

$$\frac{\partial L}{\partial W_{ij}} = a_i \cdot \delta_j \qquad v_t = \mu\, v_{t-1} - \eta \nabla L, \quad W \to W + v_t$$

Critical Temperature & Replica/TAP Analysis

Replica method (MSK)[1]:

Ensemble-average yields critical Tc via stability of the replica-symmetric solution

$$T_c = \left[2C \cos \frac{\pi}{L+2}\right]^{-1/2} \quad \Longrightarrow \quad T_c \approx \sqrt{2C}, L \to \infty.$$

TAP (Thouless-Anderson-Palmer)[2]:

Free energy:

$$F[m] \;=\; -\frac{1}{2}\sum_{ij} J_{ij}\, m_i m_j \;-\; \frac{\beta}{4}\sum_{ij} J_{ij}^2 (1-m_i^2)(1-m_j^2) \;+\; \frac{T}{2}\sum_i \left\{(1+m_i)\ln\frac{1+m_i}{2} + (1-m_i)\ln\frac{1-m_i}{2}\right\}$$

- In a real trained network, the weights J_{ij} are fixed
- It is necessary to analyze the energy landscape for a specific set

$$m_i = \langle \sigma_i \rangle \quad \overset{1}{\Longrightarrow} \quad \tanh^{-1}(m_i) = \beta \sum_j J_{ij}\, m_j - \beta^2\, m_i \sum_j J_{ij}^2\,(1-m_j^2)$$

1) Barney R., Winer M., Galitski V. Neural Networks as Spin Models: From Glass to Hidden Order Through Training
2) D. J. Thouless, P. W. Anderson, and R. G. Palmer, “Solution of ‘solvable model of a spin glass’”, Philosophical Magazine 35, 593–601 (1977).

Calculation of the critical temperature

Linearization near $m_i \approx 0$:

$$m_i \approx \beta \sum_j J_{ij} m_j - \beta^2 \sum_j J_{ij}^2 m_i$$

The solution of this system provides a criterion for the appearance of a non–trivial solution - determines Tc


We are looking for the minimum eigenvalue of the matrix:

$$(I_N - M)m = 0, \quad M_{ij} = \beta J_{ij} - \delta_{ij}\beta^2 \sum_\ell J_{i\ell}^2$$


Algorithm for Tc:

1. Form a matrix of weights
2. Calculating the minimum eigenvalue $\lambda_{\min}$
3. The critical temperature corresponds to β_c , at which $\lambda_{\min}$ becomes zero: $T_c = \frac{1}{\beta_c}$


Results: Before




Results: Critical




Results: training




MNIST dataset






Results: training



Results: training



Conclusions

- A randomly initialized network is formally **equivalent** to a layered SK spin glass with replica-symmetry breaking and a well-defined critical temperature Tc.
- Replica-method stability analysis and the **TAP** equations accurately predict Tc and identify the glass-to-ordered phase transition in the loss landscape.
- **SGD with momentum** and **STE** performs a gradual “cooling,” driving the system out of its initial glassy state into a single symmetry-broken configuration (*hidden order*).
- Throughout training, the effective Tc grows **monotonically**—signaling that the learned solution resides in ever-deeper, more robust minima less susceptible to perturbations.
- Viewing training through the lens of spin-glass physics opens new diagnostic tools (eigenvalue spectra, TAP-based stability checks) and suggests **physics-inspired regularizers** and annealing schedules to improve optimization and generalization in deep networks.

Bibliography

1. J. J. Hopfield, “Neural networks and physical systems with emergent collective computational abilities,” Proc. Natl. Acad. Sci. U. S. A. 79, 2554–2558 (1982).
2. D. J. Thouless, P. W. Anderson, and R. G. Palmer, “Solution of ‘solvable model of a spin glass’,” Philosophical Magazine 35, 593–601 (1977).
3. E. Agliari, L. Albanese, F. Alemanno, and A. Fachechi, “Pattern recognition in Deep Boltzmann machines,” arXiv preprint (2021), arXiv:2106.08978, DOI:10.48550/arXiv.2106.08978.
4. Y. LeCun, L. Bottou, Y. Bengio, and P. Haffner, “Gradient-based learning applied to document recognition,” Proceedings of the IEEE 86, 2278–2324 (1998).
5. R. Barney, M. Winer, and V. Galitski, “Neural Networks as Spin Models: From Glass to Hidden Order Through Training,” arXiv preprint (2024), arXiv:2408.06421, DOI:10.48550/arXiv.2408.06421.
6. D. J. Amit, H. Gutfreund, and H. Sompolinsky, “Spin-glass models of neural networks,” Phys. Rev. A 32, 1007–1018 (1985).
7. N. Zhang, S. Ding, J. Zhang, and Y. Xue, “An overview on restricted Boltzmann machines,” Neurocomputing 275, 1186–1199 (2018).
8. G. Parisi, “Toward a mean field theory for spin glasses,” Phys. Lett. A 73, 203–205 (1979).
9. T. Plefka, “Convergence condition of the TAP equation for the infinite-ranged Ising spin glass model,” J. Phys. A: Math. Gen. 15, 1971 (1982).
10. S. S. Du, X. Zhai, B. Poczos, and A. Singh, “Gradient descent provably optimizes over-parameterized neural networks,” in International Conference on Learning Representations (ICLR, 2019).
11. M. Thamm, M. Staats, and B. Rosenow, “Random matrix analysis of deep neural network weight matrices,” Phys. Rev. E 106, 054124 (2022).