Is Poisson-like spiking essential for general-purpose neural computation?

Rich Pang

rkp.science/snufa

Spike trains in the brain often look like a Poisson process. What is the role of Poisson-like spiking in neural computation?


- Classic networks models produce Poisson-like irregular spiking but are limited in the types of computations they can perform [1].
- Despite the spiking nonlinearity, their population firing rate dynamics approach linearity in large networks [1,2].
- Ongoing efforts have sought to make irregular-spiking networks produce nonlinear dynamics, but approaches remain actively debated [2].
- Most models of computation through dynamics in the brain treat Poisson-spiking as observation noise [3].
- Here we show proof-of-concept for how Poisson-like irregular spiking can power nonlinear dynamics well suited for computation [4].

Main findings (Pang 2025. *PLoS CB*)

- A new spiking network model produces flexible nonlinear firing rate dynamics well posed for memory-dependent computation.
- These dynamics are powered by synaptic input fluctuations sustained by irregular spiking.
- The firing rate dynamics are well described by concise, differentiable mean-field equations, and can be trained or fit.

A new spiking network model based on winner-take-all competition among cell types

Network architecture and update equations



Inputs

$$x_{id}^t = \sum_{d'=1}^{D} \sum_{j=1}^{N} J_{ij}^{dd'} y_{jd'}^{t-1} + u_{id}^t$$

Activations (winner-take-all)


$$\mathbf{y}_i^t = \mathrm{WTA}[\mathbf{x}_i^t]$$


Neuron with largest input "spikes"


Gaussian weights

$$J_{ij}^{dd'} \sim \mathcal{N}\left(\mu_J(d,d')\frac{D}{N}, \sigma_J^2(d,d')\frac{D}{N}\right)$$

Emergent chaotic dynamics produce Poisson-like irregular spiking







Mean-field equations for firing rate dynamics

Synaptic input means

$$\mu_d \approx D \sum_{d'} \mu_J(d,d') r_{d'}^{t-1} + u_d^t$$

Synaptic input variances

$$\sigma_d^2 \approx D \sum_{d'} \sigma_J^2(d,d') r_{d'}^{t-1} + v_d^t$$


Firing rates

$$r_d^t \approx \int_x \mathcal{N}\left(x; \mu_d, \sigma_d^2\right) \prod_{d' \neq d} \Phi\left(x; \mu_{d'}, \sigma_{d'}^2\right) dx$$


*differentiable

Theory predicts diverse, purely fluctuation-driven dynamics


$\mu_J = 0 \Rightarrow \mu_d = 0$ Zero synaptic input means



Mean-driven dynamics lead to saturated firing rates



Complex memory-dependent dynamics sustained by irregular spike trains emerge from editing only weight variances



Acknowledgments

This work was supported in part by the National Science Foundation through the Center for the Physics of Biological Function (PHY-1734030).

References

1. Van Vreeswijk & Sompolinsky 1996, 1998; Brunel 2001. 2. Thalmeier et al 2016; Gilra & Gerstner 2017; Alemi et al 2018; Ahmadian & Miller 2019; Baker et al 2020; Podlaski & Machens 2024. 3. Vyas et al 2020; Duncker and Sahani 2021; Pandarinath et al 2018. 4. Pang 2025.