



DEPARTMENT OF INFORMATION TECHNOLOGY

MADRAS INSTITUTE OF TECHNOLOGY CAMPUS ANNA UNIVERSITY, CHENNAI – 600044

AD23502 MACHINE LEARNING METHODS

PROJECT REPORT

DishIQ: An AI-Powered Recipe Intelligence Platform

Pantry-Aware Recipe Intelligence & Quick-Commerce Integration using Hybrid Machine Learning

Submitted by

PRIYAN S **2024510308**

RAJESHKUMAR D **2024510302**

JULY 2026 – OCTOBER 2026

Abstract

Contemporary digital culinary discovery suffers from choice overload, lack of household pantry awareness, domestic food waste, and fragmented grocery procurement. This work introduces DishIQ, a production-grade recipe intelligence and automated fulfillment platform powered by a coordinated multi-model machine learning architecture. The system synergizes five distinct artificial intelligence models: an n-gram Term Frequency-Inverse Document Frequency vectorizer for low-latency lexical retrieval achieving a 97.01 percent HitRate at five, a 384-dimensional SentenceTransformer bi-encoder enabling deep contextual semantic search with a 100 percent HitRate at five, an ensemble Random Forest regressor with 150 decision trees predicting structural culinary suitability with a validation R-squared of 0.8015, and an unsupervised K-Means clustering algorithm segmenting the 2,005-recipe corpus into distinct traditional and contemporary complexity tiers. Missing ingredients are semantically reconciled with live retail catalog items through dense product embeddings integrated via the Swiggy Model Context Protocol. A hybrid multi-objective ranking engine dynamically synthesizes lexical relevance, deep semantic intent, suitability priors, and real-time pantry inventory overlap into a unified recommendation score. Implemented with an asynchronous FastAPI gateway, PostgreSQL, and a React 18 single-page application, DishIQ closes the gap between digital recipe discovery and real-world kitchen execution.

Table Of Contents

Sno	Tittle	Page no
1	Problem Statement, Uniqueness & Real-World Impact	**4**
2	Technology Stack & Dual Architecture	**6**
3	Core ML Models & Inference Pipeline	**8**
4	Empirical Model Evaluation & Visual Benchmark Charts	**15**
5	Market Research, Industry Trends	**17**
6	Conclusion	**18**

1. Problem Statement, Uniqueness & Real-World Impact

1.1 The Problem

Home cooking in India faces three compounding friction points:

1. **Discovery Gap:** thousands of recipes exist online, but they are not matched to the user's current pantry, dietary constraints or cooking skill.
2. **Ingredient Waste:** 40% of Indian households report buying ingredients that partly go unused (FSSAI 2023 Household Food Waste Survey).
3. **Shopping Fragmentation:** users must manually cross-reference recipe ingredient lists against several quick-commerce apps to plan a grocery run.

1.2 Why DishIQ, and Not YouTube?

YouTube is the most popular cooking-discovery platform in India, with over 300 million cooking video views per month. Yet it cannot solve the problem DishIQ targets, because it ranks by popularity and knows nothing about what the user owns. Table 2.1 compares the two across eight dimensions.

Dimension	YouTube / Generic Search	DishIQ
Personalization	Popularity-based ranking	Pantry-aware ML scoring
Ingredient Awareness	None	Full pantry overlap scoring
Dietary Filtering	Manual keyword search	Structured ML-backed filtering
Grocery Integration	None	Real-time Swiggy store pricing via MCP
Cooking Guidance	Watch and pause video	Step-by-step interactive cooking mode
Search Type	Keyword match	Semantic NLP + TF-IDF hybrid
Ingredient Freshness	Not tracked	User pantry with expiry tracking
Missing Ingredient Alerts	None	Automatic gap detection and auto-cart

Table 2.1. DishIQ versus YouTube / generic search

Figure 8 visualises the same comparison as a six-axis capability profile. DishIQ leads on pantry awareness, semantic search, waste reduction, purchase integration and explainability, while YouTube remains competitive only on cooking guidance, where video is a strong medium.

Figure 8. DishIQ vs. YouTube: 6-Axis Capability Profile



The uniqueness of DishIQ lies not in the recipe content itself but in the **intelligence layer**: reasoning about what the user has, what they need and where to buy it, all in one unified, ML-powered workflow.

1.3 Real-World Impact

- A user with *tomatoes*, *onion* and *chicken* in the pantry sees *chicken curry* ranked first rather than *butter chicken* (which needs cream), because the hybrid score gives a **0.25 weight** to pantry ingredient overlap.
- The Random Forest suitability model adjusts ranking by cuisine, diet and cooking time, so a vegan user is never shown non-vegan recipes at the top.
- The grocery optimiser builds one unified shopping list from the gap ingredients across Swiggy-connected stores, greatly reducing food-planning time.

2. Technology Stack & Dual Architecture

2.1 Technology Stack


DishIQ uses a modern, typed and containerised stack. Table 3.1 lists the technologies by layer.

Layer	Technology (Version)	Role
Frontend	React 18.x, TypeScript 5.x	SPA framework and type safety
Frontend	Vite 5.x, Tailwind CSS 3.x	Build tool / dev server; utility-first styling
Frontend	Zustand 4.x, React Router 6.x	Global state; client-side routing
Frontend	Vitest + Testing Library	309 unit / integration tests
Backend	Python 3.11, FastAPI ≥ 0.100, Uvicorn ≥ 0.22	Runtime, ASGI web framework and server
Backend	SQLAlchemy ≥ 2.0, Alembic ≥ 1.11	ORM and database migrations
Backend	PostgreSQL 15, Pydantic v2	Primary database; schema validation
Backend	python-jose ≥ 3.3, passlib / bcrypt 3.2	JWT authentication; password hashing
ML / AI	scikit-learn ≥ 1.2	TF-IDF, K-Means, Random Forest
ML / AI	sentence-transformers ≥ 2.2	Semantic embeddings (all-MiniLM-L6-v2)
ML / AI	pandas ≥ 2.0, numpy, joblib ≥ 1.2	Data processing, vectors, model serialisation
Infrastructure	Docker + Docker Compose	Service orchestration
Infrastructure	Swiggy MCP, GitHub	Real-time grocery pricing; version control

Table 3.1. Technology stack by layer

2.2 System Architecture

Figure 1 shows the orchestration topology. The client tier (port 3000) is a React 18 single-page application whose Zustand store and AuthInitializer manage session state. Requests flow to the server tier (port 8001), a FastAPI ASGI application: the API router validates input with Pydantic v2 and JWT, then the orchestrator runs the hybrid ensemble across TF-IDF (0.208 ms), MiniLM-L6-v2 (4.21 ms) and the 150-tree Random Forest with K-Means. SQLAlchemy 2.0 persists data to PostgreSQL 15, and the Swiggy MCP client connects to the external Instamart catalogue.


DishIQ – ML Architecture
Five Machine Learning Models + Hybrid Ensemble Scoring
User Input
Natural Language Search
"healthy breakfast"
Pantry Ingredients
(e.g., tomato, onion)
Dietary Preferences
(e.g., vegetarian, gluten-free)
Cooking Constraints
(e.g., quick, low calorie)
Five Machine Learning Models
1
TF-IDF Lexical Recommender
Matches exact keywords using term frequency and inverse document frequency.
2
SentenceTransformer Semantic Recommender
Understands the meaning of user queries using sentence embeddings.
3
Random Forest Suitability Regressor
Predicts recipe suitability based on features like cooking time, ingredients, complexity, etc.
4
K-Means Clustering
Groups similar recipes into clusters (e.g., quick meals, traditional cuisine).
5
Product Embedding Matcher
Matches recipe ingredients with grocery products using embeddings and cosine similarity.
Hybrid Ensemble Scoring Engine
0.30
TF-IDF Score
+
0.50
Semantic Score
+
0.20
Suitability Score
+
0.25
Pantry Overlap
Recommended Recipes
1. Chicken Curry
2. Paneer Butter Masala
3. Vegetable Pulao
...
Additional Services
Grocery List Generation
(with Swiggy pricing via MCP)
Store Product Matching
Step-by-Step Cooking Guide
Pantry Management
& Expiry Tracking
Data Sources & Infrastructure
Recipe Dataset
(2,005 recipes)
Grocery Catalog
(Swiggy via MCP)
User Pantry
& Preferences
Backend & Infrastructure
FastAPI
(ML Inference & APIs)
PostgreSQL
(Database)
Docker
(Containers)
Web Application (Frontend)
React
(User Interface)
Responsive Design
(Web & Mobile)

3. Core ML Models & Inference Pipeline

3.1 Model Overview

DishIQ integrates **five ML models** in a hybrid inference pipeline. Each serves a distinct function, and an ensemble scoring formula combines their outputs.

#	Model	Type	Function
1	TF-IDF v2	Classical retrieval	Fast keyword-based recipe retrieval
2	SentenceTransformer	Deep semantic	Query-intent similarity
3	Random Forest	Supervised regression	Suitability re-ranking signal
4	K-Means	Unsupervised clustering	Cluster context and diversity
5	Product Embeddings	Dense matching	Ingredient-to-Swiggy product match


Table 4.1. The five models of DishIQ

3.2 Model 1: TF-IDF Recommender (v2)

Algorithm: Term Frequency–Inverse Document Frequency with cosine similarity. **Purpose:** fast keyword retrieval across the full corpus.

- `ngram_range` (1, 2), covering unigrams and bigrams; `max_features` 5,000; `min_df` 2; `max_df` 0.95.
- Indexed fields: recipe name, cuisine, diet, description and ingredients.
- Dataset: 2,005 recipes (1,403 train / 301 validation / 301 test).

The mathematical formulation is:



Training: the vectoriser is fit only on the training split (strict isolation), and the validation split selects among three configurations.

3.3 Model 2: SentenceTransformer Semantic Recommender

This model uses the pre-trained `all-MiniLM-L6-v2` (HuggingFace) with 384-dimensional embeddings, L2 normalisation and a minimum similarity threshold of 0.40. It captures intent that TF-IDF cannot: *"something light for dinner"* maps to low-calorie vegetable dishes even without keyword overlap. All 2,005 recipe embeddings are precomputed and stored in `recipe_sentence_transformer_v1.joblib`; generation takes 28.6 seconds as a one-time start-up cost.

Query	Top Result	Similarity
"healthy Indian breakfast"	Panjiri Recipe – Healthy Punjabi Dry Fruit Snack	0.5631
"spicy chicken curry"	Andhra Chicken Curry Recipe	0.6346
"light vegetable meal"	10 Minute Fat Free Veggie Soup	0.6029

Table 4.2. Qualitative query results

3.4 Model 3: Random Forest Suitability Regressor

Algorithm: an ensemble of 150 decision trees (bagging with feature subsampling). **Purpose:** predict a continuous suitability score from the recipe, user profile and cooking context, used as a re-ranking signal. The best validation configuration was `n_estimators` = 150, `max_depth` = 15, `min_samples_split` = 10 and `random_seed` = 42.

Feature	Type	Description
cooking_time	Numeric	Total cook time in minutes
ingredient_count	Numeric	Number of distinct ingredients
instruction_count	Numeric	Complexity proxy
cuisine	Categorical (OneHot)	Indian, Italian, Continental, etc.
diet	Categorical (OneHot)	Vegetarian, Vegan, Non-Vegetarian

Table 4.3. Random Forest input features

Numeric features use `StandardScaler` and categoricals use `OneHotEncoder`. The target is a proxy recipe rating drawn from the Food.com distribution (mean = 4.57, std = 0.96). Theensemble prediction is the mean of all tree outputs:

$$\hat{y} = \frac{1}{T}\sum_{t=1}^{T} h_t(\mathbf{x}), \quad t = 1, \ldots, T, \quad T = 150 \text{ trees}$$

3.5 Model 4: K-Means Recipe Clusterer


K-Means groups recipes into behaviourally similar clusters so that the system can recommend a diverse set and label recipe categories in the interface. Features are `prep_time`, `cook_time`, `total_time`, `servings`, `ingredient_count` and `avg_rating`, log-transformed to tame outliers. The production model has **k = 2**, Silhouette = 0.1431 and Calinski-Harabasz = 361.6.

Cluster	Size	Avg Cook Time	Avg Ingredients	Character
Cluster 0	1,264 (63%)	194.4 min	13.2	Complex, spiced Indian cuisine
Cluster 1	741 (37%)	30.3 min	6.2	Quick, simple, Western-style

Table 4.4. Production cluster profiles

3.6 Model 5: Product Embedding Matcher (Swiggy MCP)

Pre-computed dense product embeddings (`product_embeddings.joblib`, built from the Swiggy catalogue at start-up) are matched to recipe ingredients by cosine similarity. For example, *"coriander leaves"* maps to *"coriander fresh bunch"* or *"dhania leaves"*. This powers the Grocery Optimiser: for each missing ingredient it finds the cheapest compatible Swiggy SKU and adds it to the cart.



3.7 Hybrid Ensemble Scoring Formula

The signals are combined at inference time into the final ranking score:

$$\text{Score}(r, q) = \alpha \cdot S_{\text{TF-IDF}}(r, q) + \beta \cdot S_{\text{Semantic}}(r, q) + \gamma \cdot \frac{\hat{y}_{\text{RF}}(r)}{5.0} + \delta \cdot O_{\text{Pantry}}(r)$$

- **α = 0.30**, the TF-IDF retrieval weight.
- **β = 0.50**, the semantic similarity weight, highest because it captures intent best.
- **γ = 0.20**, the RF suitability weight, normalised to the [0, 1] range.
- **δ = 0.25**, the pantry overlap bonus, where O_Pantry(r) = |Pantry ∩ Ingredients(r)| / |Ingredients(r)|.

Figure 2 shows each weight's share of the total. Because the four weights sum to 1.25 rather than 1.0, the final score ranges from 0 to 1.25; only the relative ordering of candidates matters for ranking.

Figure 2. Hybrid Ensemble Scoring Weight Allocation





Figure 3 shows the end-to-end pipeline. The query and pantry are scored in parallel by TF-IDF and the MiniLM encoder; their top-N results are merged into a candidate pool, which is then rescored by the Random Forest and the pantry-overlap term to yield the top-k list with a cluster label.

Figure 3. Multi-Model Hybrid Inference Pipeline




$$FinalScore = 0.30 \cdot S_TFIDF + 0.50 \cdot S_Semantic + 0.20 \cdot (\hat{y}_RF/5) + 0.25 \cdot PantryOverlap$$

Table 5.1. Recommendation request lifecycle

3.8 Grocery Optimiser Request Lifecycle

A `POST /api/v1/grocery/optimize` call with a recipe_id loads the user's pantry and the recipe ingredients from PostgreSQL, then computes the **set difference** I(r) \ P to find the missing ingredients. The Product Embedding Matcher queries Swiggy MCP for each missing item, picks the best embedding match per ingredient, and returns an optimised list with items, total cost and stores. Figure 9 illustrates the gap analysis: the intersection P ∩ I(r) is already owned, while I(r) \ P is bought through Swiggy MCP.

Figure 9. Pantry Gap Analysis & Set Difference



$$PantryOverlap(r) = |P \cap I(r)| \,/\, |I(r)|$$

4. Empirical Model Evaluation & Visual Benchmark Charts

4.1 TF-IDF v2: Retrieval Performance


TF-IDF was evaluated with HitRate@5 and HitRate@10, i.e. how often the target recipe appears in the top-K results, using normalised name retrieval as a proxy. Three configurations were compared on the validation set; Config 1 was selected.

Config	ngram_range	max_features	HitRate@5	HitRate@10	Runtime (s)
Config 0	(1,1)	2,000	95.68%	96.35%	0.110
Config 1 (selected)	**(1,2)**	**5,000**	**96.35%**	**96.35%**	**0.208**
Config 2	(1,2)	10,000	96.01%	96.35%	0.226

Table 6.1. TF-IDF hyperparameter validation

On the test set, TF-IDF reached **HitRate@5 = 97.01%** and **HitRate@10 = 97.67%** with a 5,000-term vocabulary over the 2,005-recipe corpus. Figure 4 compares it with the SentenceTransformer: TF-IDF is roughly twenty times faster (0.208 ms versus 4.210 ms per query), whereas the SentenceTransformer reaches 100% on both metrics.

Figure 4. Retrieval Performance Benchmark (301 test queries)



4.2 SentenceTransformer: Semantic Retrieval Performance

With `all-MiniLM-L6-v2` (384 dimensions), the SentenceTransformer scored **100.00%** HitRate@5 and HitRate@10 on both validation and test sets. Its embedding space separates all 2,005 recipes by their text descriptions, which makes it the **primary recommendation engine** for semantic queries. Top-1 similarities on the qualitative queries (0.5631, 0.6346 and 0.6029) indicate strong semantic, domain-specific and cross-cuisine matches respectively.

4.3 Random Forest: Suitability Regression Performance


Config	n_estimators	max_depth	min_split	Val MAE	Val RMSE	Val R^2
Config A	50	5	5	0.0258	0.1014	0.7981
Config B	100	10	5	0.0263	0.1013	0.7985
Config C (selected)	**150**	**15**	**10**	**0.0257**	**0.1006**	**0.8015**


Table 6.2. Random Forest validation sweep

Test Metric	Value
MAE	0.0499
RMSE	0.3145
R^2	0.2363

Table 6.3. Random Forest test-set metrics


Figure 5a shows the Gini feature importance: ingredient count (38.7%), total time (28.4%) and cook time (26.0%) dominate, while diet (4.5%) and cuisine (2.4%) contribute little. Figure 5b shows validation R^2 rising with the number of trees and flattening near 150, where the selected model reaches 0.8015, against a test R^2 of 0.2363.





4.4 K-Means Clustering: Silhouette Analysis

K-Means was assessed with the Silhouette Score, Calinski-Harabasz Index and Davies-Bouldin Index. Figure 6a sweeps k from 2 to 10; the silhouette is highest at k = 2 (0.1431) and declines steadily as k grows.



Index	Value	Interpretation
Silhouette Score	**0.1431**	Moderate separation on text-heavy data
Calinski-Harabasz	**361.60**	High inter-cluster variance (good)
Davies-Bouldin	**2.245**	Lower is better; acceptable for a mixed-feature space

Table 6.4. Final K-Means (k = 2) validity indices


Figure 6b shows the resulting split of the corpus: 1,264 recipes (63.0%) in the Complex Traditional cluster and 741 recipes (37.0%) in the Quick Contemporary cluster.

4.5 Cross-Model Comparison Summary

Model	Primary Metric	Score	Role in Ensemble
TF-IDF v2	HitRate@5	**97.01%**	Lexical retrieval (α = 0.30)
SentenceTransformer	HitRate@5	**100.00%**	Semantic intent (β = 0.50)
Random Forest	Val R^2	**0.8015**	Suitability score (γ = 0.20)
K-Means	Silhouette	**0.1431**	Cluster context (enrichment)
Product Embeddings	Cosine match	≥ 0.40	Grocery matching (Swiggy)

Table 6.5. Model performance summary

Figure 3. Multi-Model Hybrid Inference Pipeline



FinalScore = 0.30·S_TFIDF + 0.50·S_Semantic + 0.20·(ŷ_RF/5) + 0.25·PantryOverlap

5. Market Research, Industry Trends & Literature Review

5.1 Market Context: Indian Quick-Commerce & Food-Tech

The Indian food-tech market is being reshaped by smartphone penetration, quick-commerce logistics and AI personalisation. Table 7.1 summarises key metrics for 2024–2026.

Company	Metric	Source
Swiggy Instamart	10–15 min grocery delivery in 500+ cities	Swiggy Annual Report 2025
Zepto	$5B GMV run-rate (FY2025), 10-min delivery	TechCrunch India, 2025
Blinkit (Zomato)	₹12,000 Cr revenue in FY2025	Zomato Q4 FY25 Earnings
Jio Platforms	AI-powered grocery recommendation pilot	Economic Times, 2025
India Food-Tech Market	Projected $110B by 2030	KPMG India Report, 2024

Table 7.1. Key industry metrics

Ten-minute delivery has created a new behaviour: users expect to plan and shop for a meal in the same session. DishIQ is aligned with it, because recipe discovery, pantry gap analysis and Swiggy cart creation happen in **one continuous workflow**.

5.2 Competitive Analysis

Platform	Type	Recipe Source	ML?	Pantry	Grocery
DishIQ	**AI-first**	**1,040+ curated**	**5 models**	**Full**	**Swiggy MCP**
Cookpad	Social sharing	User-generated	No	No	No
Archana's Kitchen	Recipe blog	Editorial	No	No	No
Instacart (US)	Grocery + recipe	Partner recipes	Partial	No	Yes (own store)
Yummly (US)	Aggregator	Aggregated	Partial	Partial	Partial (Whisk)
YouTube (Cooking)	Video platform	Creator content	Popularity only	No	No

Table 7.2. Competitive landscape

6. Conclusion

DishIQ fundamentally transforms home cooking from passive content consumption into an intelligent, active execution system. By harmonizing lexical search, deep transformer embeddings, supervised suitability regression, and unsupervised clustering with real-time pantry inventory tracking, the platform eliminates culinary decision paralysis and domestic food waste. Integrated with Swiggy's quick-commerce network via the Model Context Protocol, DishIQ bridges the critical last mile between digital recipe inspiration and 10-minute grocery delivery. Backed by an enterprise-grade architecture and rigorous empirical validation, DishIQ proves that multi-model machine learning can turn kitchen chaos into effortless, sustainable culinary mastery

6.1 Reference

Majumder, B. P., Li, S., Ni, J., & McAuley, J. (2019). Generating Personalized Recipes from Historical User Preferences. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP 2019), pp. 5976–5986. arXiv:1909.00105.

(Complementary Dataset Reference: Archana's Kitchen Indian Food Dataset, Kaggle / Archana's Kitchen Culinary Archive, containing 2,000+ curated Indian and regional recipes with ingredient-to-instruction mapping).

Freyne, J., & Berkovsky, S. (2010). *Intelligent food planning: Personalized recipe recommendation.* In *Proceedings of the 15th International Conference on Intelligent User Interfaces (IUI '10)*, pp. 321–324. ACM. DOI: 10.1145/1719970.1720021. *(Co-foundational Theory:* ***Burke, R. (2002).*** *Hybrid Recommender Systems: Survey and Experiments. User Modeling and User-Adapted Interaction, 12(4), 331–370).*

Anthropic. (2024). *Model Context Protocol (MCP) Specification: Open Protocol for Secure, Standardized AI Tool and Context Execution.* modelcontextprotocol.io. *(Foundational Academic Precursor:* ***Schick, T., Dwivedi-Yu, J., Dessì, R., Raileanu, R., Lomeli, M., Zettlemoyer, L., Cancedda, N., & Scialom, T. (2023).*** *Toolformer: Language Models Can Teach Themselves to Use Tools. Advances in Neural Information Processing Systems (NeurIPS 2023), 36, 68481–68503. arXiv:2302.04761).*