Data Sheet
CoinPower® CP 1654

Data Sheet – CP 1654 (CoinPower®)[1]





Type Designation	CP 1654
Type Number	63165
Cell Code	ICR1654
System	Graphite - layered metal oxide ($LiNi_xMn_yCo_zO_2$)
UL Recognition	MH13654
Nominal Voltage [V]	3.7 (average)
Nominal Capacity C [mAh]	100 (at 0.2 C from 4.2 V to 3.0 V at 20 °C)
Dimensions [mm] (without Tags)	
Diameter	16.1 +0.0 / -0.3
Height	5.4 +0.2 / -0.1
Weight. approx [g]	3.2 +0.3 / -0.3
Charging Method	Constant Current + Constant Voltage
Charge Voltage [V]	4.20 ± 0.05
Initial Charge Current [mA]	Standard Charge: 0.5 C Rapid Charge: 1 C
Charging Cut-Off (a) or (b)	
a) by time [h]	Standard Charge: 5 Rapid Charge: 3
b) by min current [mA]	0.02 C
Discharge Cut-Off Voltage [V]	3.0
Max. Pulse Discharge Current [mA]	3 C @ 2 s
Max. Continuous Discharge Current [mA]	2 C
Operating Temperature [°C]	Charge: 0 to 45 Discharge: -20 to 60
Storage Temperature	1 Year at -20 to 20 °C > 80
Capacity Recovery Rate[2] [%]	3 Month at -20 to 45 °C > 80 1 Month at -20 to 60 °C > 75
Impedance Initial [Ω]	< 0,4 @ 1 kHz
Cycle Life 0.2 C / 0.2 C, 20 °C [Cycles]	> 500 (> 80 % of C_{ini})
Cycle Life 1 C / 1 C, 20 °C [Cycles]	> 300 (> 80 % of C_{ini})
Safety	UL passed
Internal Approval	
Overcharge Test (12 V, 3 C, 12 h)	passed
Overcharge Test (12 V, 1 C, 12 h)	passed
Overcharge Test (5 V, 1 A, 12 h)	passed

[1] Recommendations regarding Charging / Discharging and Safety (cf. Product Manual) have to be accepted. Cell must not be used without external safety electronics (PCM – Protection Circuit Module).
[2] After storage at initial cell voltage of 3.7 to 3.9 V / cell; values estimated – not measured yet.

VARTA Microbattery GmbH
Daimlerstr. 1, 73479 Ellwangen, Germany
Tel.: +49 79 61 921 - 0
Telefax: +49 79 61 921 - 553