

Lab Assignment 4

Selectors, the Cascade & Specificity — take control of your stylesheet

CS445 · Web Programming · Campus Event Board

#	Name	Roll No.
1	Rakshit kumar	20261651069
2	Sakshi kuntal	20261651076
3	Ravi singh singal	20261651072
4	Yash anand	20261651099
5	Ankit chaturvedi	20261651013

Part B — Cascade, Specificity & Inheritance

1. Score the ten selectors from B1 as (ids, classes, tags), and name the winner.

#	Selector	ids	classes	tags	Specificity
1	p	0	0	1	(0,0,1)
2	.events	0	1	0	(0,1,0)
3	nav .events	0	1	1	(0,1,1)
4	#site-header	1	0	0	(1,0,0)
5	#site-header .events	1	1	0	(1,1,0)
6	a:hover	0	1	1	(0,1,1)
7	ul li a	0	0	3	(0,0,3)
8	input[type="email"]	0	1	1	(0,1,1)
9	*	0	0	0	(0,0,0)
10	:not(.active)	0	1	0	(0,1,0)

Part 2 — which colour wins? For `<p class="events">` inside `<nav id="site-header">`:

Rule	Specificity
p { color: red }	(0,0,1)
.events { color: green }	(0,1,0)
#site-header .events { color: blue }	(1,1,0)

Blue wins. Highest specificity.

2. In B2, which rule won, and which reason decided it — source order or specificity?

Conflict: Upcoming Events heading.

Rule	Specificity
.section-title { color: var(--brand); }	(0,1,0)
#upcoming-events .section-title { color: #7c2d12; }	(1,1,0)

ID rule wins. Specificity decides.

3. Why does !important break the cascade, and what should you do instead?

It overrides normal rules. Use specificity or order.

4. Descendant (A B) vs child (A > B) — a one-line difference, with an example from your page.

Descendant: anywhere inside. Child: one level only. Example: `main > section`.

5. Adjacent (A + B) vs general sibling (A ~ B) — a one-line difference.

Adjacent: next sibling. General: all following siblings.

6. Name one property that inherited from body and one that did not; how did inherit / initial / unset help you?

Inherited: color, font-family, line-height, text-align. Not inherited: margin, background, border, width.

Property	Inherits?	Property	Inherits?
color	Yes	line-height	Yes
font-family	Yes	border	No
margin	No	text-align	Yes
background	No	width	No

Keywords: `inherit` keeps the parent font. `initial` resets alignment. `unset` removes the last border.

- `inherit` : parent value.
- `initial` : browser default.
- `unset` : inherit or initial.

7. What does the universal selector * score, and why is a * reset so easily overridden?

Score: (0,0,0). Any selector overrides it.

8. :is() vs :where() — the one important difference, and when you would use :where().

`:is()` keeps specificity. `:where()` is zero. Use `:where()` for easy overrides.

9. What does @layer give you that fighting specificity does not?

Organized cascade order, without specificity battles.

10. Paste three of your selectors with their specificity scores — are they as low as they could be?

Selector	Specificity
main > section	(0,0,2)
h2 + p	(0,0,2)
a[href^="https"]	(0,1,1)

Yes. Low specificity, no IDs.

```
}  
#upcoming-events .section-title {  
  color: #7c2d12;  
}  
  
.section-title {  
  margin-top: 0;  
  color: var(--brand);  
}  
  
h2 {  
  font-size: 1.5rem;  
  color: var(--text);  
}
```

A6 — Striped schedule table

Full Schedule			
All upcoming events at a glance			
Event	Date	Venue	Time
Independence Day Celebration	15 August 2026	College Ground	9:00 AM
Technical Fest	20 August 2026	Seminar Hall	10:00 AM
Coding Competition	25 August 2026	Computer Lab	11:00 AM
Sports Day	30 August 2026	College Ground	8:00 AM
Cultural Fest	5 September 2026	Auditorium	4:00 PM
AI workshop	10 September 2026	College Campus	2:00 PM

Submit an Event

First Name:

Name

Last Name:

sumame

Student id:

eg. 20261651072

Proposed event date:

dd/mm/yyyy

select your interest :

Independence day celebration

SELECT YOUR GENDER

- ☐ Male
☐ Female

CHOOSE YOUR DEPARTMENT

☐ Btech ☐ Mtech ☐ Mca

CONTACT DETAILS

Whatsapp number :

your email id

you@example.com

address :

Street, city, PIN

Age :

Add an Event



The W3C CSS Validation Service

W3C CSS Validator results for style.css (CSS level 3 + SVG)

[Jump to:](#) [Warnings \(1\)](#) [Validated CSS](#)

W3C CSS Validator results for style.css (CSS level 3 + SVG)

Congratulations! No Error Found.

This document validates as [CSS level 3 + SVG](#) ![↑ TOP](#)

Warnings (1)

URI : style.css

16

-apple-system,BlinkMacSystemFont,"Segoe UI",Roboto,sans-serif is a vendor extension

[↑ TOP](#)

Valid CSS information

@charset "UTF-8";

[↑ TOP](#)