

JOIN.md

```

1  Once the teacher clicks the GO button, pass the conditions expressed by the selections the
   teacher made with the sliders and dropdown menus to JOIN.
2
3  The conditions selected by the teacher in the GUI are passed here to determine how to filter
   and calculate from the scores.csv BOOLEAN table.
4
5  <table>
6  <tr><th>condition_1</th><th>condition_2</th><th>condition_3</th><th>BOOLEAN query</th></tr>
7  <tr><td>student</td><td>sID</td><td>null</td><td>SELECT only the sID record, SELECT only
   fields ending with _fi1 or _fi2 suffix, and run TUTOR QUERY</td></tr>
8  <tr><td>class</td><td>pair</td><td>cohort</td><td>SELECT only records with class=cohort, and
   run PAIR QUERY</td></tr>
9  <tr><td>class</td><td>reteach</td><td>cohort</td><td>SELECT only records with class=cohort,
   SELECT only fields ending with _fi1 or _fi2 suffix, and run RETEACH QUERY</td></tr>
10 </table>
11 <hr>
12 <query id="1">TUTOR QUERY
13
14     1. <step>LIST any *field code* with a FALSE value.</step>
15
16     2. <step>Use DICT.md to translate the field codes into ordinary language.</step>
17
18     <example>If **sID**=148 then generate the following list:
19     - **3i_fi1** -> Feet & Inches Homework #1, Question #3
20     - **6i_fi1** -> Feet & Inches Homework #1, Question #6
21     - **1i_fi2** -> Feet & Inches Homework #2, Question #1
22     - **4f_fi2** -> Feet & Inches Homework #2, Question #4
23     - **5f_fi2** -> Feet & Inches Homework #2, Question #5
24
25     </example>
26 </query>
27 <hr>
28 <query id="2">PAIR QUERY
29
30     1. <step>COUNT all TRUE values for each *student record*.</step>
31     2. <step>DELETE any *student record* from this query that has a total is LESS THAN 50.
   </step>
32     3. <step>Create a two column array, where the first column starts with the **sID** with the
   highest TRUE total, the next **sID** with the second highest TRUE total, and so on.
33     The second column will start with the **sID** with the lowest TRUE total, the next **sID**
   with the second lowest TRUE total, and so on.
34
35     <example>If **class**='GCP-20' then generate the following array:
36
37     <table>
38     <tr><td>231</td><td>226</td></tr>
39     <tr><td>223</td><td>221</td></tr>
40     <tr><td>237</td><td>236</td></tr>
41     <tr><td>220</td><td>235</td></tr>

```

```

42     <tr><td>224</td><td>230</td></tr>
43     <tr><td>227</td><td>225</td></tr>
44     <tr><td>219</td><td>222</td></tr>
45     <tr><td>232</td><td>233</td></tr>
46     <tr><td>228</td><td>229</td></tr>
47 </table>
48
49 </example>
50 </query>
51 <hr>
52 <query id="3"> RETEACH QUERY
53
54     1. <step>COUNT all TRUE values in each *field code*.</step>
55     2. <step>Create a list of the three lowest TRUE totals.</step>
56     3. <step>Use DICT.md to translate the listed *field codes* into ordinary language.</step>
57
58     <example>If **class**='BCP-180' then generate the following list:
59
60     - **3i_fi1** -> Feet & Inches Homework #1, Question #3
61     - **4f_fi1** -> Feet & Inches Homework #1, Question #4
62     - **2f_fi2** -> Feet & Inches Homework #2, Question #2
63
64     </example>
65 </query>
66
67 The query results are passed back to the right side of the GUI.
68

```