Use an S3 bucket to contain website static content

Overview

Pre-requisites/Steps

1. Setup a VPC endpoint (Gateway) to S3 in the VPC where the server exists
2. Add a policy to the instance role to allow access to the bucket
3. Verify that `mod_proxy` and `mod_proxy_http` are enabled
4. Verify that the bucket has been setup for static website access
5. Create an Apache rewrite rule to proxy requests
6. Create a bucket policy to restrict access to VPC

Apache Configuration

```
RewriteEngine On
RequestHeader unset Authorization
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^/foo/(.+)$ http://s3.amazonaws.com/treasurersbriefcase-test-bucket/$1 [P]
```

Note that the URL is `http`, not `https`

Bucket Policy

```
{
    "Version": "2012-10-17",
    "Id": "Policy1517439098546",
    "Statement": [
        {
            "Sid": "Stmt1517439068860",
            "Effect": "Allow",
            "Principal": "*",
            "Action": "s3:GetObject",
            "Resource": "arn:aws:s3:::treasurersbriefcase-test-bucket/*",
            "Condition": {
                "StringEquals": {
                    "aws:sourceVpce": "vpce-42ea6c2b"
                }
            }
        }
    ]
}
```

History

-- RobLauer - 2018-02-01

- Initial page creation

Topic revision: r2 - 2022-06-07 - RobLauer

Copyright © 2008-2025 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.
Ideas, requests, problems regarding TWiki? Send feedback