HTML Notes

Basic Tags and Lists • Class Notes with Interview Questions

1. Heading Tags

HTML provides six heading tags, from **<h1>** to **<h6>**.

• **<h1>** is used for the main heading.
• **<h2>** is used for a subheading.
• **<h3>** to **<h6>** are used for headings of different levels.

```
<h1>Main Heading</h1>
<h2>Sub Heading</h2>
<h3>Nested Sub Heading</h3>
<h4>Heading 4</h4>
<h5>Heading 5</h5>
<h6>Heading 6</h6>
```

Interview Question: What are heading tags in HTML?
Heading tags are used to define headings on a webpage. HTML has six heading tags, from <h1> to <h6>. The <h1> tag represents the highest-level heading, and <h6> represents the lowest-level heading.

Remember: Headings show the structure and importance of content. They are not just used to change text size.

2. Paragraph Tag

The **<p>** tag is used to write a paragraph on a webpage.

```
<p>Hello, we are learning HTML.</p>
```

Interview Question: What is the use of the paragraph tag?
The <p> tag is used to display a block of text as a paragraph. Browsers normally add some space before and after a paragraph.

3. Text Formatting Tags

HTML provides different tags to format text or show its importance.

Tag	Use
<b>	Makes text bold.
	Marks text as important, usually shown in bold.
<i>	Displays text in italic style.
	Emphasizes text, usually shown in italic style.
<ins>	Represents inserted text, usually shown with an underline.

```
<p>
  <b>Bold Text</b>
  <strong>Important Text</strong>
  <i>Italic Text</i>
  <em>Emphasized Text</em>
  <ins>Inserted Text</ins>
</p>
```

Interview Question: What is the difference between <b> and ?
The <b> tag makes text bold without adding importance by itself. The tag indicates that the text is important. Browsers usually display both in bold.

Interview Question: What is the difference between <i> and ?
The <i> tag displays text in an alternate voice or style, usually italic. The tag adds emphasis to the text and is

usually displayed in italic.

4. Line Break and Horizontal Rule

The
 Tag

The **
** tag is used to move text to the next line without starting a new paragraph.

```
<p>Hello<br>Welcome to HTML</p>
```

The <hr> Tag

The **<hr>** tag represents a thematic break between sections. It is usually displayed as a horizontal line.

```
<p>First Section</p>
<hr>
<p>Second Section</p>
```

Interview Question: What is the difference between <br> and <hr>?

 creates a line break, whereas <hr> represents a thematic break between sections.

Remember: Both <br> and <hr> are void elements. They do not need closing tags.

5. Superscript and Subscript

Superscript — <sup>

The **<sup>** tag displays text slightly above the normal text line.

```
<p>2<sup>3</sup> = 8</p>
```

Output: $2^3 = 8$

Subscript — <sub>

The **<sub>** tag displays text slightly below the normal text line.

```
<h4>H<sub>2</sub>O</h4>
```

Output: H■O

Interview Question: What is the difference between <sup> and <sub>?
<sup> displays text above the normal line, while <sub> displays text below the normal line.

6. HTML Lists

HTML provides three main types of lists:

1. Ordered List — **<ol>**
2. Unordered List — **<ul>**
3. Description List — **<dl>**

A. Ordered List (<ol>)

An ordered list displays items in a sequence, usually using numbers or letters. The **<li>** tag defines each list item.

```
<ol>
  <li>HTML</li>
  <li>CSS</li>
  <li>JavaScript</li>
</ol>
```

Changing the starting number

The **start** attribute specifies the starting number of an ordered list.

```
<ol start="101">
  <li>HTML</li>
  <li>CSS</li>
  <li>JavaScript</li>
</ol>
```

The list starts from 101.

Changing the numbering style

The **type** attribute can change the numbering style.

```
<ol type="A">
  <li>HTML</li>
  <li>CSS</li>
  <li>JavaScript</li>
</ol>
```

Common values of the **type** attribute: **1** = numbers (default), **A** = uppercase letters, **a** = lowercase letters, **I** = uppercase Roman numerals, and **i** = lowercase Roman numerals.

B. Unordered List (<ul>)

An unordered list displays items with bullets instead of a numbered sequence.

```
<ul>
  <li>JavaScript</li>
  <li>React</li>
  <li>Node.js</li>
</ul>
```

Changing the bullet style

```
<ul type="square">
  <li>JavaScript</li>
  <li>React</li>
  <li>Node.js</li>
</ul>
```

Common bullet styles are **disc**, **circle**, and **square**. Note: The **type** attribute for <ul> is outdated in HTML5. CSS **list-style-type** is the recommended way to change bullet styles.

```
<ul style="list-style-type: square;">
  <li>JavaScript</li>
  <li>React</li>
</ul>
```

C. Description List (<dl>)

A description list is used to display terms and their descriptions.

• **<dl>** — Defines the description list.
• **<dt>** — Defines the term.
• **<dd>** — Defines the description.

```
<dl>
  <dt>HTML</dt>
  <dd>Used to structure web pages.</dd>

  <dt>CSS</dt>
  <dd>Used to style web pages.</dd>
</dl>
```

Interview Question: What is the difference between ordered and unordered lists?
An ordered list (<ol>) displays items in a sequence, usually with numbers or letters. An unordered list (<ul>) displays items with bullets.

Interview Question: What is the purpose of the <li> tag?
The <li> tag defines an item inside an ordered or unordered list.