# Cross-Dialect Information Retrieval: Information Access in Low-Resource and High-Variance Languages

Robert Litschko, Oliver Kraus, Verena Blaschke, Barbara Plank













icons by OpenMoji - CC BY-SA 4.0







#### Wikipedia

https://de.wikipedia.org > wiki > München

#### München

Sie ist mit gut 1,5 Millionen Einwohnern die bevölke Gemeinde Deutschlands und mit 4.861 Einwohnern

Casabiabta Münahana - Altatadt (Münahan) - Landk



What about culture-specific knowledge that can often be found in dialect Wikis?





#### Wikipedia

https://de.wikipedia.org > wiki > München

#### München


Sie ist mit gut 1,5 Millionen Einwohnern die bevölke Gemeinde Deutschlands und mit 4.861 Einwohnern

Coophighta Münghang - Altatadt (Münghan) - Landk


# München ("Munich")






















Lexical retrieval falls short: Normalizers do not exists for most dialects.





Low German (nds)

Alemannic (als)

Bavarian (bar)

North Frisian (frr)


Saterfrisian (stq)


Ripuarian (ksh)

Rhine Franconian (pfl)

10







Low German (nds)

Alemannic (als)

Bavarian (bar)

North Frisian (frr)


Saterfrisian (stq)


Ripuarian (ksh)

Rhine Franconian (pfl)

Standard German: 2.9M Wiki articles







Low German (nds)

Alemannic (als)

Bavarian (bar)

North Frisian (frr)

Saterfrisian (stq)

Ripuarian (ksh)

Rhine Franconian (pfl)




Low-resource: Very Limited resources data to train neural retrieval models.

#### Contribution

- New task: Cross-dialect information retrieval
- New dataset: WikiDIR
- Dialect variation dictionaries
- Evaluation of IR models on WikiDIR

#### Example





## Agenda

#### 1. Motivation

- 2. WikiDIR dataset
- 3. Dialect dictionaries
- 4. Models
- 5. Results

## Agenda

1. Motivation

#### 2. WikiDIR dataset

- 3. Dialect dictionaries
- 4. Models
- 5. Results








Query  $q_i$ 












Corpus  $\mathcal{D}$ 
















#### **Lexical Similarity Scores**










$$\mathcal{D}_{ ext{rel}}^{q_i} = \{d_j \in \mathcal{D} \ | \ d_j ext{ contains } q_i \}$$

#### **Monolingual Relevance Labels**










$$\mathcal{D}_{ ext{rel}}^{q_i} = \{d_j \in \mathcal{D} \, | \, d_j ext{ contains } q_i \}$$

#### Monolingual Relevance Labels









$$\mathcal{D}_{ ext{rel}}^{q_i} = \{d_j \in \mathcal{D} \ | \ d_j ext{ contains } q_i \}$$

#### Monolingual Relevance Labels



23



Query  $q_i$ 




Corpus  $\mathcal{D}$ 





Labels




24










Train


Dev

Test

Set of rel. docs.

All documents that contain a query.







Train Dev Test An.

### **Analysis Split**

All documents that contain a query or any of its dialect variations.








Where do dialect variations come from?


## Agenda


- 1. Motivation
- 2. WikiDIR Dataset
- 3. Dialect dictionaries
- 4. Models
- 5. Results











### Example Record (Bavarian dictionary)

```
{
  "de_id": "3215",
  "de_title": "München",
  "dial_id": "12259",
  "dial_title": "Minga",
  "variants": ["Münch'n", "Minkcha", "Minkn", "Minchn", "Mingna", "Minkhn", "Münchn"]
}
```

# Agenda

- 1. Motivation
- 2. WikiDIR dataset
- 3. Dialect dictionaries
- 4. Models
- 5. Results



======= LLM-RERANKING ========

system: You are RankGPT, an intelligent assistant that can rank passages based on their relevancy to the query.

user: I will provide you with num passages, each indicated by number identifier []. Rank them based on their relevance to query: {{query}}.


(Sun et al., 2023)




system: You are RankGPT, an intelligent assistant that can rank passages based on their relevancy to the query.


user: I will provide you with num passages, each indicated by number identifier []. Rank them based on their relevance to query: {{query}}.


(Sun et al., 2023)



(Nogueira et al., 2019)









(Sun et al., 2023) (Nogueira et al., 2019)

(Santhanam et al., 2022)

#### Rerank top 100






(Santhanam et al., 2022)



system: You are RankGPT, an intelligent assistant that can rank passages based on their relevancy to the query.


user: I will provide you with num passages, each indicated by number identifier []. Rank them based on their relevance to query: {{query}}.


(Sun et al., 2023)



(Nogueira et al., 2019)

#### Retrieval






======= LLM-RERANKING ========


**system:** You are RankGPT, an intelligent assistant that can rank passages based on their relevancy to the query.

**user**: I will provide you with num passages, each indicated by number identifier []. Rank them based on their relevance to query: {{query}}.

(Sun et al., 2023)



(Nogueira et al., 2019)



(Santhanam et al., 2022)

#### Zero-shot Transfer



#### Fine-tuning



# Agenda


- 1. Motivation
- 2. WikiDIR dataset
- 3. Dialect dictionaries
- 4. Models
- 5. Results






<sup>\*</sup>average over 7 dialects






<sup>\*</sup>average over 7 dialects






<sup>\*</sup>average over 7 dialects






<sup>\*</sup>average over 7 dialects






<sup>\*</sup>average over 7 dialects











<sup>\*</sup>average over 5 dialects






\*average over 5 dialects










\*average over 5 dialects




#### Document translation results






#### Document translation results





#### Document translation results



There are still large gaps!

#### Conclusion

- We introduce WikiDIR, a cross-dialect information retrieval dataset.
- We release dialect variation dictionaries for German dialects.
- More results and analyses in the paper.

# GitHub

#### Conclusion

- We introduce WikiDIR, a cross-dialect information retrieval dataset.
- We release dialect variation dictionaries for German dialects.
- More results and analyses in the paper.

#### CDIR is novel and challenging task!

- → Low-resource
- → High-Variance

The gaps are still large.

# GitHub