

The `skrapport` class*

Simon Sigurdhsson
`ssimon@student.chalmers.se`

December 13, 2012

1 Introduction

This document class is intended for simple reports submitted by the author at Chalmers University of Technology. It is small, straightforward and basically a restyling of the standard L^AT_EX `article` class. It does, however, offer a different set of options.

2 Usage

2.1 Options

`a4paper,a5paper` Paper size. Only these two are available; use the `geometry` package to utilize american or otherwise esoteric paper sizes. Default is `a4paper`.

`10pt,11pt,12pt` Font size, exactly like the standard `article` document class. Default is `11pt`.

`draft,final` Trigger (or untrigger) draft mode, like the standard `article` class. Default is `final`.

`fleqn,leqno` Included for compatibility with `article`.

`bftitles,rmtitles` Decides whether to typeset titles using bold fonts or regular ones. Default is `rmtitles` (i.e. non-bold titles).

`swe,eng` Tells `babel` what language to load as the primary one. Both languages are loaded regardless. Default is `swe`.

`lmodern,palatino` Decides what font to use. Default is `lmodern`.

`indent,noindent` Decides whether to use paragraph indentation or `parskip`-style paragraphs. Default is `noindent`.

*This document corresponds to `skrapport` v0.09, dated 2012/06/07.

`onecolumn,twocolumn` Decides whether the document has one column (default) or two (implemented using the excellent `multicol` package).

`color,nocolor` Enables or disables colors and color themes in the document. Default is `color`.

2.2 Useful macros

In general, the class defines the same macros as the `article` class.

`\regarding` The class does add a `\regarding` macro, which is used like the standard `\author` and `\title` macros and should be given an accurate but short description of the purpose of the report (i.e. course name or similar). This is printed along with the date on the top of the title/first page.

`onecol` In `twocolumn` mode, the package defines an environment `onecol` which typesets its contents in a single column. Additionally, it redefines `figure` and `table` as

`\colortheme` non-floats, leaving the starred versions intact. If the package is loaded with the `color` option, changing the color theme is possible using `colortheme`, which loads an appropriate package. At the moment, four color themes are available: `default`, `unscathed`, `cruelwater` and `violet`.

3 Additional information

3.1 Included packages

The document class includes `babel`, `fontenc`, `icomma`, `amsmath`, `amssymb`, `microtype` and `hyperref` by default, and `skmath` if it exists.

4 Implementation

Start by including `kvoptions` and defining some variables for future use.

```
1 \RequirePackage{xstring}
2 \RequirePackage{kvoptions}
3 \SetupKeyvalOptions{family=skrapport,prefix=skrapport@}
4 \newcommand\@ptsize{}
5 \IfFileExists{ifxetex.sty}{%
6   \RequirePackage{ifxetex}%
7 }{%
8   \newif\ifxetex\xetexfalse%
9 }
```

Declare the paper size options.

```
10 \DeclareStringOption[a4paper]{paper}
11 \DeclareVoidOption{a4paper}{\skrapport@SetupPaper}
12 \DeclareVoidOption{a5paper}{\skrapport@SetupPaper}
13 \newcommand*\skrapport@SetupPaper{\xexpandafter\skrapport@SetupPaper\expandafter{\CurrentOpti
14 \newcommand*\skrapport@SetupPaper}[1]{\setkeys{skrapport}{paper={#1}}}
```

Declare point size options.

```

15 \DeclareStringOption[11pt]{ptsize}
16 \DeclareVoidOption{10pt}{\skrapport@SetupPtsize}
17 \DeclareVoidOption{11pt}{\skrapport@SetupPtsize}
18 \DeclareVoidOption{12pt}{\skrapport@SetupPtsize}
19 \newcommand*{\skrapport@SetupPtsize}{\expandafter\@skrapport@SetupPtsize\expandafter{\CurrentOp
20 \newcommand*{\@skrapport@SetupPtsize}[1]{\setkeys{skrapport}{ptsize={#1}}}
```

Declare column options.

```

21 \DeclareBoolOption[false]{twocolumn}
22 \DeclareComplementaryOption{onecolumn}{twocolumn}
```

Declare draft and final options.

```

23 \DeclareBoolOption[false]{draft}
24 \DeclareComplementaryOption{final}{draft}
```

Declare the fleqn and leqno options for compatibility with the article class.

```

25 \DeclareBoolOption[false]{leqno}
26 \DeclareBoolOption[false]{fleqn}
```

Declare options for bold/roman section titles.

```

27 \DeclareStringOption[rm]{titles}
28 \DeclareVoidOption{rmtitles}{\skrapport@SetupTitles}
29 \DeclareVoidOption{bftitles}{\skrapport@SetupTitles}
30 \DeclareVoidOption{sftitles}{\skrapport@SetupTitles}
31 \newcommand*{\skrapport@SetupTitles}{\expandafter\@skrapport@SetupTitles\expandafter{\CurrentOp
32 \newcommand*{\@skrapport@SetupTitles}[1]{%
33 \IfStrEq{#1}{bftitles}{%
34 \setkeys{skrapport}{titles={bf}}}%
35 }\IfStrEq{#1}{sftitles}{%
36 \setkeys{skrapport}{titles={sf}}}%
37 }{
38 \setkeys{skrapport}{titles={rm}}}%
39 }}}}
```

Declare options for swedish/english babel support.

```

40 \DeclareBoolOption[false]{eng}
41 \DeclareComplementaryOption{swe}{eng}
```

Declare font options.

```

42 \DeclareStringOption[kpfonts]{font}
43 \DeclareVoidOption{kpfonts}{\skrapport@SetupFont}
44 \DeclareVoidOption{lmodern}{\skrapport@SetupFont}
45 \DeclareVoidOption{palatino}{\skrapport@SetupFont}
46 \DeclareVoidOption{nofont}{\skrapport@SetupFont}
47 \newcommand*{\skrapport@SetupFont}{\expandafter\@skrapport@SetupFont\expandafter{\CurrentOption
48 \newcommand*{\@skrapport@SetupFont}[1]{\setkeys{skrapport}{font={#1}}}
```

Declare indentation options.

```

49 \DeclareBoolOption[false]{indent}
50 \DeclareComplementaryOption{noindent}{indent}
```

Declare color option.

```

51 \DeclareBoolOption[true]{color}
52 \DeclareComplementaryOption[nocolor]{color}

Execute default options and process given options.
53 \ProcessKeyvalOptions*

Require packages as per given options.
54 \IfStrEq{\skrapport@paper}{a4paper}{%
55 \RequirePackage[a4paper]{geometry}
56 \setlength\paperheight {297mm}
57 \setlength\paperwidth {210mm}
58 }{\IfStrEq{\skrapport@paper}{a5paper}{%
59 \RequirePackage[a5paper]{geometry}
60 \setlength\paperheight {210mm}
61 \setlength\paperwidth {148mm}
62 }{%
63 \ClassError{skrapport}{%
64 Option 'paper' has unknown value '\skrapport@paper'
65 }{}
66 }}
67 \IfStrEq{\skrapport@ptsize}{10pt}{%
68 \renewcommand\@ptsize{0}
69 }{%
70 \IfStrEq{\skrapport@ptsize}{11pt}{%
71 \renewcommand\@ptsize{1}
72 }{%
73 \IfStrEq{\skrapport@ptsize}{12pt}{%
74 \renewcommand\@ptsize{2}
75 }{%
76 \ClassError{skrapport}{%
77 Option 'ptsize' has unknown value '\skrapport@ptsize'
78 }{}
79 }
80 }
81 }
82 \ifskrapport@draft
83 \setlength\overfullrule{5pt}
84 \else
85 \setlength\overfullrule{0pt}
86 \fi
87 \ifskrapport@leqno\input{leqno.clo}\fi
88 \ifskrapport@fleqn\input{fleqn.clo}\fi
89 \IfStrEq{\skrapport@titles}{bf}{%
90 \let\@titstyle\bfseries%
91 }{\IfStrEq{\skrapport@titles}{sf}{%
92 \let\@titstyle\sffamily\bfseries%
93 }{%
94 \let\@titstyle\relax%
95 }}

```

```

96 \ifxetex
97   \RequirePackage[quiet]{fontspec}
98 \DeclareRobustCommand\nobreakspace{\leavevmode\nobreak\space}
99 \else
100   \RequirePackage[T1]{fontenc}
101 \fi
102 \ifskrapport@color
103 \RequirePackage{etoolbox}
104 \RequirePackage{xcolor}
105 \fi
106 \IfStrEq{\skrapport@font}{nofont}{}{%
107 \IfStrEq{\skrapport@font}{kpfonts} {%
108 \RequirePackage[easyscs1,intlimits,sumlimits]{kpfonts}
109 }{%
110 \IfStrEq{\skrapport@font}{palatino} {%
111 \IfFileExists{tgpagella.sty} {%
112 \RequirePackage{tgpagella}
113 }{%
114 \RequirePackage[sc]{mathpazo}
115 }
116 }{%
117 \IfStrEq{\skrapport@font}{lmodern} {%
118 \RequirePackage{lmodern}
119 }{%
120 \ClassError{skrapport}{%
121 Option 'font' has unknown value '\skrapport@font'
122 }{}
123 }
124 }
125 }
126 }
127 \ifskrapport@eng
128 \ifxetex
129 \RequirePackage{xkeyval}
130 \RequirePackage{polyglossia}
131 \setmainlanguage[variant=british]{english}
132 \setotherlanguage{swedish}
133 \else
134 \RequirePackage[swedish,british]{babel}
135 \fi
136 \else
137 \ifxetex
138 \RequirePackage{xkeyval}
139 \RequirePackage{polyglossia}
140 \setmainlanguage{swedish}
141 \setotherlanguage[variant=british]{english}
142 \else
143 \RequirePackage[british,swedish]{babel}
144 \fi
145 \fi

```

```

146 \ifskrapport@twocolumn
147 \RequirePackage{etoolbox}
148 \RequirePackage{multicol}
149 \fi

    Include some essential packages per default.

150 \RequirePackage{calc}
151 \AtEndOfClass{
152     \RequirePackage{microtype}
153 \RequirePackage{icomma}
154 \IfStrEq{\skrapport@font}{kpfonts}{}{\RequirePackage[intlimits]{amsmath}}
155 \let\Finv\relax
156 \let\Game\relax
157 \let\beth\relax
158 \let\gimel\relax
159 \let\daleth\relax
160 \IfStrEq{\skrapport@font}{kpfonts}{}{\RequirePackage{amssymb}}
161 \IfStrEq{\skrapport@font}{kpfonts}{}{\RequirePackage{textcomp}}
162 \IfFileExists{skmath.sty}{\RequirePackage{skmath}}{}
163 }
164 \AtBeginDocument{
165 \@ifundefined{urlstyle}{}{\urlstyle{same}}
166 }

    Include the correct point size .clo file from the article class.

167 \input{size1\@ptsize.clo}

    Set some default measurements.

168 \addtolength\textwidth{0.5\oddsidemargin}
169 \addtolength\textwidth{0.5\evensidemargin}
170 \addtolength\oddsidemargin{-0.5\oddsidemargin}
171 \addtolength\evensidemargin{-0.5\evensidemargin}
172 \setlength\lineskip{1\p@}
173 \setlength\normallineskip{1\p@}
174 \renewcommand\baselinestretch{}

    Indentation code. Undo the indentation set by the article class if indentation
    was requested by the user. See the parskip package for further information. Enable
    french spacing as well.

175 \ifskrapport@indent\else
176     \setlength\parskip{0.5\baselineskip \@plus 2pt}
177 \parindent=\z@
178 \setlength\parfillskip{30\p@ \@plus 1fil}
179 \def\@listI{\leftmargin\leftmarginI
180     \topsep\z@ \parsep\parskip \itemsep\z@}
181 \let\@listI\@listI
182 \@listI
183 \def\@listii{\leftmargin\leftmarginii
184     \labelwidth\leftmarginii\advance\labelwidth-\labelsep
185     \topsep\z@ \parsep\parskip \itemsep\z@}
186 \def\@listiii{\leftmargin\leftmarginiii

```

```

187 \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
188 \topsep\z@ \parsep\parskip \itemsep\z@}
189 \partopsep=\z@
190 \@ifundefined{CheckCommand}{-}{%
191 \CheckCommand*{\@starttoc}[1]{%
192 \begingroup
193 \makeatletter
194 \@input{\jobname.#1}%
195 \if@filesw
196 \expandafter\newwrite\csname tf@#1\endcsname
197 \immediate\openout \csname tf@#1\endcsname \jobname.#1\relax
198 \fi
199 \@nobreakfalse
200 \endgroup}}
201 \renewcommand*{\@starttoc}[1]{%
202 \begingroup
203 \makeatletter
204 \parskip\z@
205 \@input{\jobname.#1}%
206 \if@filesw
207 \expandafter\newwrite\csname tf@#1\endcsname
208 \immediate\openout \csname tf@#1\endcsname \jobname.#1\relax
209 \fi
210 \@nobreakfalse
211 \endgroup}
212 \fi
213 \frenchspacing
214 \penalties and float settings.
215 \lowpenalty 51
216 \medpenalty 151
217 \highpenalty 301
218 \setcounter{topnumber}{2}
219 \setcounter{bottomnumber}{1}
220 \setcounter{totalnumber}{4}
221 \setcounter{dbltopnumber}{2}
222 \renewcommand\topfraction{.75}
223 \renewcommand\bottomfraction{.5}
224 \renewcommand\textfraction{.25}
225 \renewcommand\floatpagefraction{.625}
226 \renewcommand\dbltopfraction{.75}
227 \renewcommand\dblfloatpagefraction{.625}

```

\regarding This macro is used by \maketitle to insert a simple text into the header on the title page.

```

227 \def\@regarding{\relax}
228 \newcommand{\regarding}[1]{\gdef\@regarding{#1}}

```

\license This macro is used by \maketitle to insert a license into the footer on the title page.

```

229 \def\@copyright{\relax}
230 \newcommand{\license}[1]{\gdef\@copyright{#1}}

```

The standard \maketitle command as taken from the article class but with some basic restyling.

```

231 \let\@smallprintstyle\relax
232 \newcommand\maketitle{\par%
233   \begin{group}
234     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
235     \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
236     \long\def\@makefntext##1{\parindent 1em\noindent%
237       \hb@xt@1.8em{\hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
238     \newpage
239     \global\@topnum\z@
240     \@maketitle
241     \thispagestyle{plain}\@thanks
242   \end{group}
243   \setcounter{footnote}{0}%
244 }
245 \def\@maketitle{%
246   \newpage
247   \null
248   \begin{flushleft}%
249   \vspace{-\headsep}
250     {\small%
251       \@smallprintstyle
252       \if\@regarding\relax\else\@regarding{, }\fi%
253       \@date\par%
254     }%
255     \vspace{1.5cm}%
256     {\Huge\@titstyle\@title\par}%
257     \vspace{.125cm}%
258     {\Large\@titstyle\@author}%
259     \vspace{.75cm}%
260   \end{flushleft}%
261   \par%
262 }

```

Sectioning commands.

```

263 \setcounter{secnumdepth}{3}
264 \newcounter{section}
265 \newcounter{subsection}[section]
266 \newcounter{subsubsection}[subsection]
267 \newcounter{paragraph}[subsubsection]
268 \newcounter{subparagraph}[paragraph]
269 \renewcommand\thesection{\@arabic\c@section}
270 \renewcommand\thesubsection{\thesection.\@arabic\c@subsection}
271 \renewcommand\thesubsubsection{\thesubsection.\@arabic\c@subsubsection}
272 \renewcommand\theparagraph{\thesubsubsection.\@arabic\c@paragraph}
273 \renewcommand\thesubparagraph{\theparagraph.\@arabic\c@subparagraph}

```



```

274 \newcommand\section{\@startsection{section}{1}{\z@}%
275   {-4ex \@plus 1ex \@minus -1ex}%
276   {.5ex \@plus .5ex}%
277   {\normalfont\LARGE\@titstyle}}
278 \newcommand\subsection{\@startsection{subsection}{2}{\z@}%
279   {-3ex \@plus 1ex \@minus -1ex}%
280   {.25ex \@plus .25ex}%
281   {\normalfont\Large\@titstyle}}
282 \newcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
283   {-2ex \@plus .5ex \@minus -.5ex}%
284   {.125ex \@plus .125ex}%
285   {\normalfont\large\@titstyle}}
286 \newcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
287   {1ex \@plus .25ex \@minus -.25ex}%
288   {-1em}%
289   {\normalfont\normalsize\bfseries}}
290 \newcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
291   {1ex \@plus .25ex \@minus -.25ex}%
292   {-1em}%
293   {\normalfont\normalsize\itshape}}

```

Itemization commands.

```

294 \setlength\leftmargini{2em}
295 \leftmargin\leftmargini
296 \setlength\leftmarginii{2em}
297 \setlength\leftmarginiii{1.5em}
298 \setlength\leftmarginiv{1.5em}
299 \setlength\leftmarginv{1em}
300 \setlength\leftmarginvi{1em}
301 \setlength\labelsep{.5em}
302 \setlength\labelwidth{\leftmargini}
303 \addtolength\labelwidth{-\labelsep}
304 \@beginparpenalty -\@lowpenalty
305 \@endparpenalty -\@lowpenalty
306 \@itempenalty -\@lowpenalty
307 \renewcommand\theenumi{\@arabic\c@enumi}
308 \renewcommand\theenumii{\@alph\c@enumii}
309 \renewcommand\theenumiii{\@roman\c@enumiii}
310 \renewcommand\theenumiv{\@Alph\c@enumiv}
311 \newcommand\labelenumi{\theenumi.}
312 \newcommand\labelenumii{\theenumii.}
313 \newcommand\labelenumiii{\theenumiii.}
314 \newcommand\labelenumiv{\theenumiv.}
315 \renewcommand\p@enumii{\theenumi}
316 \renewcommand\p@enumiii{\theenumii(\theenumii)}
317 \renewcommand\p@enumiv{\p@enumiii\theenumiii}
318 \newcommand\labelitemi{\textbullet}
319 \newcommand\labelitemii{\textopenbullet}
320 \newcommand\labelitemiii{\normalfont\bfseries\textendash}
321 \newcommand\labelitemiv{\textrightarrow}

```

```

322 \newenvironment{description}
323   {\list{}{\labelwidth\z@ \itemindent-\leftmargin
324     \let\makelabel\descriptionlabel}}{\endlist}
325 \newcommand*{descriptionlabel}[1]{\hspace\labelsep\normalfont\bfseries #1}
      Standard restyled abstract environment from the article class.
326 \newenvironment{abstract}{\newlength\skrapport@abstract@tw\newlength\skrapport@abstract@aw\sett
      Quotation environments.
327 \newenvironment{quote}{\list{}{\rightmargin\leftmargin}\item\relax\itshape}{\endlist}
328 \newenvironment{quotation}{\bigskip\begin{quote}}{\end{quote}\bigskip}
329 \newenvironment{verse}{\begin{quote}}{\end{quote}}
      Titlepage environment.
330 \newcommand\ps@skrapport@titlepage{\def\@oddhead{}\def\@evenhead{}\def\@oddfoot{\begin{minipage
331 \newenvironment{titlepage}{\cleardoublepage\setcounter{page}\@one}{\thispagestyle{skrapport@titl
      Appendix macro.
332 \newcommand\appendix{\par\setcounter{section}{0}\setcounter{subsection}{0}\gdef\thesection{\@Al
      Figure and table floats.
333 \setlength\arraycolsep{5\p@}
334 \setlength\tabcolsep{6\p@}
335 \setlength\arrayrulewidth{.4\p@}
336 \setlength\doublerulesep{2\p@}
337 \setlength\tabbingsep{\labelsep}
338 \skip\@mpfootins=\skip\footins
339 \setlength\fbboxsep{3\p@}
340 \setlength\fbboxrule{.4\p@}
341 \renewcommand\theequation{\@arabic\c@equation}
342 \newcounter{figure}\renewcommand\thefigure{\@arabic\c@figure}
343 \def\fps@figure{tb}
344 \def\ftype@figure{1}
345 \def\ext@figure{lof}
346 \def\fnum@figure{\figurename~\thefigure}
347 \newenvironment{figure}{\@float{figure}}{\end@float}
348 \newenvironment{figure*}{\@dblfloat{figure}}{\end@dblfloat}
349 \newcounter{table}\renewcommand\thetable{\@arabic\c@table}
350 \def\fps@table{tb}
351 \def\ftype@table{2}
352 \def\ext@table{lot}
353 \def\fnum@table{\tablename~\thetable}
354 \newenvironment{table}{\@float{table}}{\end@float}
355 \newenvironment{table*}{\@dblfloat{table}}{\end@dblfloat}
      Captions.
356 \let\@captionstyle\relax
357 \newlength\abovecaptionskip\setlength\abovecaptionskip{10\p@}
358 \newlength\belowcaptionskip\setlength\belowcaptionskip{10\p@}
359 \long\def\@makecaption#1#2{%
360 \vskip\abovecaptionskip
361 \sbox\@tempboxa{\small{\bfseries#1:} \itshape#2}%

```

```

362 \ifdim \wd\@tempboxa >\hsize
363 \small{\bfseries\@captionstyle#1:} \itshape#2\par
364 \else
365 \global \@minipagefalse
366 \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
367 \fi
368 \vskip\belowcaptionskip}

    Old font commands.
369 \DeclareOldFontCommand{\rm}{\normalfont\rmfamily}{\mathrm}
370 \DeclareOldFontCommand{\sf}{\normalfont\sffamily}{\mathsf}
371 \DeclareOldFontCommand{\tt}{\normalfont\ttfamily}{\mathtt}
372 \DeclareOldFontCommand{\bf}{\normalfont\bfseries}{\mathbf}
373 \DeclareOldFontCommand{\it}{\normalfont\itshape}{\mathit}
374 \DeclareOldFontCommand{\sl}{\normalfont\slshape}{\@nomath\sl}
375 \DeclareOldFontCommand{\sc}{\normalfont\scshape}{\@nomath\sc}

    Redefining the \emph style to be bold when nested.
376 \let\@emstyle\relax
377 \DeclareRobustCommand\em{%
378 \@nomath\em%
379 \ifdim \fontdimen\@ne\font >\z@%
380 \itshape\bfseries%
381 \else%
382 \itshape%
383 \fi%
384 \@emstyle%
385 }

    Table of contents code.
386 \newcommand\@pnumwidth{1.55em}
387 \newcommand\@tocrmarg{2em}
388 \newcommand\@dotsep{1.7}
389 \setcounter{tocdepth}{5}
390 \newcommand\tableofcontents{%
391   \section*{\contentsname
392     \@mkboth{\MakeUppercase\contentsname}{\MakeUppercase\contentsname}
393   }%
394 \vskip\baselineskip%
395   \@starttoc{toc}%
396 }
397 \newcommand*{\l@section{\@dottedtocline{1}{0em}{1.3em}}
398 \newcommand*{\l@subsection{\@dottedtocline{2}{1.3em}{2em}}
399 \newcommand*{\l@subsubsection{\@dottedtocline{3}{3.3em}{3.15em}}
400 \newcommand*{\l@paragraph{\@dottedtocline{4}{6.45em}{4.15em}}
401 \newcommand*{\l@subparagraph{\@dottedtocline{5}{10.6em}{5.15em}}

    Fix for e.g. tocloft package
402 \let\l@figure\@empty
403 \let\l@table\@empty

    Bibliography code.

```

```

404 \newdimen\bibindent
405 \setlength\bibindent{2em}
406 \newenvironment{thebibliography}[1]
407 {\section*{\refname}%
408 \@mkboth{\MakeUppercase\refname}{\MakeUppercase\refname}%
409 \list{\@biblabel{\@arabic\c@enumiv}}%
410 {\settowidth\labelwidth{\@biblabel{#1}}%
411 \leftmargin\labelwidth
412 \advance\leftmargin\labelsep
413 \@openbib@code
414 \usecounter{enumiv}%
415 \let\p@enumiv\empty
416 \renewcommand\theenumiv{\@arabic\c@enumiv}}%
417 \sloppy
418 \clubpenalty4000
419 \@clubpenalty \clubpenalty
420 \widowpenalty4000}%
421 {\def\@noitemerr
422 {\@latex@warning{Empty thebibliography environment}}}%
423 \endlist}
424 \newcommand\newblock{\hskip .11em\@plus.33em\@minus.07em}
425 \let\@openbib@code\empty
426 \newenvironment{theindex}
427 {\twocolumn[\section*{\indexname}]%
428 \@mkboth{\MakeUppercase\indexname}%
429 {\MakeUppercase\indexname}%
430 \thispagestyle{plain}\parindent\z@
431 \parskip\z@ \@plus .3\p@\relax
432 \columnseprule \z@
433 \columnsep 35\p@
434 \let\item\@idxitem}
435 {\onecolumn}
436 \newcommand\@idxitem{\par\hangindent 40\p@}
437 \newcommand\subitem{\@idxitem \hspace*{20\p@}}
438 \newcommand\subsubitem{\@idxitem \hspace*{30\p@}}
439 \newcommand\indexspace{\par \vskip 10\p@ \@plus5\p@ \@minus3\p@\relax}

Footnote code.
440 \renewcommand\footnoterule{%
441 \kern-3\p@
442 \hrule\@width.4\columnwidth
443 \kern2.6\p@}
444 \newcommand\@makefnmark[1]{%
445 \parindent 1em%
446 \noindent
447 \hb@xt@1.8em{\hss\@makefnmark}#1}

Basic translatable texts.
448 \newcommand\contentsname{Innehåll}
449 \newcommand\refname{Referenser}
450 \newcommand\figurename{Figur}

```

```

451 \newcommand\tablename{Tabell}
452 \newcommand\appendixname{Bilaga}
453 \newcommand\abstractname{Sammanfattning}
454 \def\today{\year--\month--\day}

    The twocolumn hacks implemented.

455 \ifskrapport@twocolumn
456 \AtBeginDocument{
457 \IfStrEq{\skrapport@ptsize}{10pt}{
458 \RequirePackage[fontsize=10pt,baseline=12pt]{grid}
459 }{
460 \IfStrEq{\skrapport@ptsize}{11pt}{
461 \RequirePackage[fontsize=11pt,baseline=13.2pt]{grid}
462 }{
463 \RequirePackage[fontsize=12pt,baseline=14.4pt]{grid}
464 }
465 }
466 % Redefining abstract
467 \renewenvironment{abstract}{\section*{\abstractname}}{}
468 % Patching \env{document} and \cs{maketitle}
469 \AfterEndPreamble{\begin{multicols}{2}}
470 \AtEndDocument{\end{multicols}}
471 \pretocmd{\maketitle}{\end{multicols}}{}{}
472 \apptocmd{\maketitle}{\begin{multicols}{2}}{}{}
473 % Patching \env{equation}
474 \BeforeBeginEnvironment{equation}{\begin{gridenv}}
475 \AfterEndEnvironment{equation}{\end{gridenv}}
476 \BeforeBeginEnvironment{equation*}{\begin{gridenv}}
477 \AfterEndEnvironment{equation*}{\end{gridenv}}
478 % Patching \env{multline}
479 \BeforeBeginEnvironment{multline}{\begin{gridenv}}
480 \AfterEndEnvironment{multline}{\end{gridenv}}
481 \BeforeBeginEnvironment{multline*}{\begin{gridenv}}
482 \AfterEndEnvironment{multline*}{\end{gridenv}}
483 % Patching \env{gather}
484 \BeforeBeginEnvironment{gather}{\begin{gridenv}}
485 \AfterEndEnvironment{gather}{\end{gridenv}}
486 \BeforeBeginEnvironment{gather*}{\begin{gridenv}}
487 \AfterEndEnvironment{gather*}{\end{gridenv}}
488 % Patching \env{align}
489 \BeforeBeginEnvironment{align}{\begin{gridenv}}
490 \AfterEndEnvironment{align}{\end{gridenv}}
491 \BeforeBeginEnvironment{align*}{\begin{gridenv}}
492 \AfterEndEnvironment{align*}{\end{gridenv}}
493 % Patching \env{flalign}
494 \BeforeBeginEnvironment{flalign}{\begin{gridenv}}
495 \AfterEndEnvironment{flalign}{\end{gridenv}}
496 \BeforeBeginEnvironment{flalign*}{\begin{gridenv}}
497 \AfterEndEnvironment{flalign*}{\end{gridenv}}
498 % Patching \env{alignat}

```

```

499 \BeforeBeginEnvironment{alignat}{\begin{gridenv}}
500 \AfterEndEnvironment{alignat}{\end{gridenv}}
501 \BeforeBeginEnvironment{alignat*}{\begin{gridenv}}
502 \AfterEndEnvironment{alignat*}{\end{gridenv}}
503 % Patching \env{figure}
504 \renewenvironment{figure}{%
505 \begin{gridenv}%
506 \vspace{\intextsep}%
507 \begin{minipage}{\linewidth}%
508 \def\@capttype{figure}%
509 }{%
510 \end{minipage}%
511 \vspace{\intextsep}%
512 \end{gridenv}%
513 }
514 % Patching \env{table}
515 \renewenvironment{table}{%
516 \begin{gridenv}%
517 \vspace{\intextsep}%
518 \begin{minipage}{\linewidth}%
519 \def\@capttype{table}%
520 \let\@old@caption\caption%
521 \renewcommand{\caption}[1]{%
522 \setlength{\@tempdima}{\abovecaptionskip}%
523 \setlength{\abovecaptionskip}{\belowcaptionskip}%
524 \setlength{\belowcaptionskip}{\@tempdima}%
525 \@old@caption{##1}%
526 \vspace{\belowcaptionskip}%
527 }%
528 }{%
529 \end{minipage}%
530 \vspace{\intextsep}%
531 \end{gridenv}%
532 }
533 \let\oldoldtablest\oldtablest
534 \renewcommand{\oldtablest}{%
535 \oldoldtablest%
536 \let\@old@caption\caption%
537 \renewcommand{\caption}[1]{%
538 \setlength{\@tempdima}{\abovecaptionskip}%
539 \setlength{\abovecaptionskip}{\belowcaptionskip}%
540 \setlength{\belowcaptionskip}{\@tempdima}%
541 \@old@caption{##1}%
542 \vspace{\belowcaptionskip}%
543 }%
544 }
545 % Providing \env{onecol}
546 \newenvironment{onecol}{\end{multicols}}{\begin{multicols}{3}}
547 }
548 \fi

```

Color theme setup. Start by patching commands and declaring default colors.
 Not implemented: background colors for e.g. quote environments and sections
 headings, different colors for the different sectioning levels.

```

549 \ifskrapport@color
550 \apptocmd{\bfseries}{\color{skrapport@boldcolor}}{}{\ClassError{skrapport}{Could not patch \pro
551 \apptocmd{\itshape}{\color{skrapport@italiccolor}}{}{\ClassError{skrapport}{Could not patch \pro
552 \if\@titstyle\relax
553 \def\@titstyle{\color{skrapport@titlecolor}}
554 \else
555 \apptocmd{\@titstyle}{\color{skrapport@titlecolor}}{}{\ClassError{skrapport}{Could not patch \pro
556 \fi
557 \def\@smallprintstyle{\color{skrapport@smallprintcolor}}
558 \AtBeginDocument{%
559 \let\@abstractname\abstractname
560 \def\abstractname{\color{skrapport@titlecolor}\@abstractname}
561 }
562 \apptocmd{\quote}{\color{skrapport@quotecolor}}{}{}
563 \def\@captionstyle{\color{skrapport@captioncolor}}
564 \def\@emstyle{\color{skrapport@emphcolor}}
565 \ifskrapport@twocolumn\AtBeginDocument{%
566 \renewcommand\section{\@startsection {section}{1}{\z@}%
567     {- .999\baselineskip}{0.001\baselineskip}{\bfseries\mathversion{bold}\color{skrapport@t
568 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
569 {- .35\baselineskip}{- .35\baselineskip}{\bfseries\color{skrapport@titlecolor}\unskip}}
570 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
571 {- .35\baselineskip}{- .35\baselineskip}{\itshape\color{skrapport@titlecolor}\unskip}}
572 \fi
573 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
574 {1ex \@plus .25ex \@minus -.25ex}{-1em}{\normalfont\normalsize\bfseries\color{skrapport@titleco
575 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
576 {1ex \@plus .25ex \@minus -.25ex}{-1em}{\normalfont\normalsize\itshape\color{skrapport@titlecol
577 \AtBeginDocument{\@ifpackageloaded{hyperref}{%
578 \hypersetup{%
579 citebordercolor=skrapport@citecolor,citecolor=skrapport@citecolor,%
580 filebordercolor=skrapport@filecolor,filecolor=skrapport@filecolor,%
581 linkbordercolor=skrapport@linkcolor,linkcolor=skrapport@linkcolor,%
582 menubordercolor=skrapport@menucolor,menucolor=skrapport@menucolor,%
583 urlbordercolor=skrapport@urlcolor,urlcolor=skrapport@urlcolor,%
584 runbordercolor=skrapport@runcolor,runcolor=skrapport@runcolor%
585 }
586 }{}
587 \AtBeginDocument{\color{skrapport@defaultcolor}}

Loading color themes
588 \newcommand\colortheme[1]{\usepackage{skrapport-colortheme-#1}}
589 \colortheme{default}
590 \fi

Final page setup
591 \setlength\columnsep{10\p@}

```

```

592 \setlength\columnseprule{0\p@}
593 \pagestyle{plain}
594 \pagenumbering{arabic}
595 \raggedbottom
596 \onecolumn

```

4.1 Color themes

4.1.1 Default color theme

```

597 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
598 \ProvidesPackage{skrapport-colortheme-default}
599 [2012/06/07 v1.0 skrapport color theme default]
600 \definecolor{skrapport@citecolor}{named}{green}
601 \definecolor{skrapport@filecolor}{named}{teal}
602 \definecolor{skrapport@linkcolor}{named}{red}
603 \definecolor{skrapport@menucolor}{named}{red}
604 \definecolor{skrapport@urlcolor}{named}{cyan}
605 \definecolor{skrapport@runcolor}{named}{teal}
606 \definecolor{skrapport@boldcolor}{named}{black}
607 \definecolor{skrapport@titlecolor}{named}{black}
608 \definecolor{skrapport@italiccolor}{named}{black}
609 \definecolor{skrapport@smallprintcolor}{named}{black}
610 \definecolor{skrapport@quotecolor}{named}{black}
611 \definecolor{skrapport@captioncolor}{named}{black}
612 \definecolor{skrapport@emphcolor}{named}{black}
613 \definecolor{skrapport@defaultcolor}{named}{black}

```

4.1.2 Unscathed color theme

```

614 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
615 \ProvidesPackage{skrapport-colortheme-unscathed}
616 [2012/06/07 v1.0 skrapport color theme unscathed]
617 \definecolor{skrapport@citecolor}{named}{skrapport@defaultcolor}
618 \definecolor{skrapport@filecolor}{named}{skrapport@defaultcolor}
619 \definecolor{skrapport@menucolor}{named}{skrapport@defaultcolor}
620 \definecolor{skrapport@runcolor}{named}{skrapport@defaultcolor}
621 \definecolor{skrapport@emphcolor}{HTML}{463335}
622 \definecolor{skrapport@linkcolor}{HTML}{CF5D3B}
623 \definecolor{skrapport@urlcolor}{named}{skrapport@linkcolor}
624 \definecolor{skrapport@titlecolor}{HTML}{B34430}
625 \definecolor{skrapport@captioncolor}{named}{skrapport@titlecolor}
626 \definecolor{skrapport@quotecolor}{HTML}{70524A}
627 \definecolor{skrapport@smallprintcolor}{named}{skrapport@quotecolor}

```

4.1.3 Cruelwater color theme

```

628 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
629 \ProvidesPackage{skrapport-colortheme-cruelwater}
630 [2012/06/07 v1.0 skrapport color theme cruelwater]
631 \definecolor{skrapport@citecolor}{named}{black}
632 \definecolor{skrapport@filecolor}{named}{black}

```



```

633 \definecolor{skrapport@linkcolor}{named}{black}
634 \definecolor{skrapport@menucolor}{named}{black}
635 \definecolor{skrapport@urlcolor}{named}{black}
636 \definecolor{skrapport@runcolor}{named}{black}
637 \definecolor{skrapport@boldcolor}{HTML}{030C22}
638 \definecolor{skrapport@titlecolor}{HTML}{20293F}
639 \definecolor{skrapport@italiccolor}{named}{black}
640 \definecolor{skrapport@smallprintcolor}{HTML}{A9B0B3}
641 \definecolor{skrapport@quotecolor}{HTML}{404749}
642 \definecolor{skrapport@captioncolor}{HTML}{030C22}
643 \definecolor{skrapport@emphcolor}{HTML}{20293F}
644 \definecolor{skrapport@defaultcolor}{named}{black}

```

4.1.4 Violet color theme

```

645 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
646 \ProvidesPackage{skrapport-colortheme-violet}
647   [2012/06/07 v1.0 skrapport color theme violet]
648 \definecolor{skrapport@citecolor}{HTML}{932444}
649 \definecolor{skrapport@filecolor}{HTML}{932444}
650 \definecolor{skrapport@linkcolor}{HTML}{932444}
651 \definecolor{skrapport@menucolor}{HTML}{932444}
652 \definecolor{skrapport@urlcolor}{HTML}{932444}
653 \definecolor{skrapport@runcolor}{HTML}{932444}
654 \definecolor{skrapport@boldcolor}{HTML}{311A2A}
655 \definecolor{skrapport@titlecolor}{HTML}{311A2A}
656 \definecolor{skrapport@italiccolor}{named}{black}
657 \definecolor{skrapport@smallprintcolor}{HTML}{D6CBCF}
658 \definecolor{skrapport@quotecolor}{HTML}{463335}
659 \definecolor{skrapport@captioncolor}{HTML}{311A2A}
660 \definecolor{skrapport@emphcolor}{HTML}{98758D}
661 \definecolor{skrapport@defaultcolor}{named}{black}

```