

# The `skrapport` class\*

Simon Sigurdhsson  
`ssimon@student.chalmers.se`

December 15, 2012

## 1 Introduction

This document class is intended for simple reports submitted by the author at Chalmers University of Technology. It is small, straightforward and basically a restyling of the standard L<sup>A</sup>T<sub>E</sub>X `article` class. It does, however, offer a different set of options.

## 2 Usage

### 2.1 Options

`a4paper,a5paper` Paper size. Only these two are available; use the `geometry` package to utilize american or otherwise esoteric paper sizes. Default is `a4paper`.

`10pt,11pt,12pt` Font size, exactly like the standard `article` document class. Default is `11pt`.

`draft,final` Trigger (or untrigger) draft mode, like the standard `article` class. Default is `final`.

`fleqn,leqno` Included for compatibility with `article`.

`bftitles,rmtitles` Decides whether to typeset titles using bold fonts or regular ones. Default is `rmtitles` (i.e. non-bold titles).

`swe,eng` Tells `babel` what language to load as the primary one. Both languages are loaded regardless. Default is `swe`.

`lmodern,palatino` Decides what font to use. Default is `lmodern`.

`indent,noindent` Decides whether to use paragraph indentation or `parskip`-style paragraphs. Default is `noindent`.

---

\*This document corresponds to `skrapport` v0.09, dated 2012/06/07.

`onecolumn,twocolumn` Decides whether the document has one column (default) or two (implemented using the excellent `multicol` package).

`color,nocolor` Enables or disables colors and color themes in the document. Default is `color`.

`math, nomath` Enables or disables loading the `skmath` package. Default is `math`.

## 2.2 Useful macros

In general, the class defines the same macros as the `article` class.

`\regarding` The class does add a `\regarding` macro, which is used like the standard `\author` and `\title` macros and should be given an accurate but short description of the purpose of the report (i.e. course name or similar). This is printed along with the date on the top of the title/first page.

`onecol` In `twocolumn` mode, the package defines an environment `onecol` which typesets its contents in a single column. Additionally, it redefines `figure` and `table` as

`\colortheme` non-floats, leaving the starred versions intact. If the package is loaded with the `color` option, changing the color theme is possible using `colortheme`, which loads an appropriate package. At the moment, four color themes are available: `default`, `unscathed`, `cruelwater` and `violet`.

## 3 Additional information

### 3.1 Included packages

The document class includes `babel`, `fontenc`, `icomma`, `amsmath`, `amssymb`, `microtype` and `hyperref` by default, and `skmath` if it exists.

## 4 Implementation

Start by including `kvoptions` and defining some variables for future use.

```
1 \RequirePackage{xstring}
2 \RequirePackage{kvoptions}
3 \SetupKeyvalOptions{family=skrapport,prefix=skrapport@}
4 \newcommand\@ptsize{}
5 \IfFileExists{ifxetex.sty}{%
6   \RequirePackage{ifxetex}%
7 }{%
8   \newif\ifxetex\xetexfalse%
9 }
```

Declare the paper size options.

```
10 \DeclareStringOption[a4paper]{paper}
11 \DeclareVoidOption{a4paper}{\skrapport@SetupPaper}
12 \DeclareVoidOption{a5paper}{\skrapport@SetupPaper}
13 \newcommand*\skrapport@SetupPaper{\expandafter\skrapport@SetupPaper\expandafter{\CurrentOpti
```

```

14 \newcommand*{\@skrapport@SetupPaper}[1]{\setkeys{skrapport}{paper={#1}}}
    Declare point size options.
15 \DeclareStringOption[11pt]{ptsize}
16 \DeclareVoidOption{10pt}{\skrapport@SetupPtsize}
17 \DeclareVoidOption{11pt}{\skrapport@SetupPtsize}
18 \DeclareVoidOption{12pt}{\skrapport@SetupPtsize}
19 \newcommand*{\skrapport@SetupPtsize}{\expandafter\@skrapport@SetupPtsize\expandafter{\CurrentOp
20 \newcommand*{\@skrapport@SetupPtsize}[1]{\setkeys{skrapport}{ptsize={#1}}}
    Declare column options.
21 \DeclareBoolOption[false]{twocolumn}
22 \DeclareComplementaryOption{onecolumn}{twocolumn}
    Declare draft and final options.
23 \DeclareBoolOption[false]{draft}
24 \DeclareComplementaryOption{final}{draft}
    Declare the fleqn and leqno options for compatibility with the article class.
25 \DeclareBoolOption[false]{leqno}
26 \DeclareBoolOption[false]{fleqn}
    Declare options for bold/roman section titles.
27 \DeclareStringOption[rm]{titles}
28 \DeclareVoidOption{rmtitles}{\skrapport@SetupTitles}
29 \DeclareVoidOption{bftitles}{\skrapport@SetupTitles}
30 \DeclareVoidOption{sftitles}{\skrapport@SetupTitles}
31 \newcommand*{\skrapport@SetupTitles}{\expandafter\@skrapport@SetupTitles\expandafter{\CurrentOp
32 \newcommand*{\@skrapport@SetupTitles}[1]{%
33 \IfStrEq{#1}{bftitles}{%
34 \setkeys{skrapport}{titles={bf}}}%
35 }{\IfStrEq{#1}{sftitles}{%
36 \setkeys{skrapport}{titles={sf}}}%
37 }{
38 \setkeys{skrapport}{titles={rm}}}%
39 }}}
    Declare options for swedish/english babel support.
40 \DeclareBoolOption[false]{eng}
41 \DeclareComplementaryOption{swe}{eng}
    Declare font options.
42 \DeclareStringOption[kpfonts]{font}
43 \DeclareVoidOption{kpfonts}{\skrapport@SetupFont}
44 \DeclareVoidOption{lmodern}{\skrapport@SetupFont}
45 \DeclareVoidOption{palatino}{\skrapport@SetupFont}
46 \DeclareVoidOption{nofont}{\skrapport@SetupFont}
47 \newcommand*{\skrapport@SetupFont}{\expandafter\@skrapport@SetupFont\expandafter{\CurrentOption
48 \newcommand*{\@skrapport@SetupFont}[1]{\setkeys{skrapport}{font={#1}}}
    Declare indentation options.
49 \DeclareBoolOption[false]{indent}
50 \DeclareComplementaryOption{noindent}{indent}

```

Declare color option.

```

51 \DeclareBoolOption[true]{color}
52 \DeclareComplementaryOption{nocolor}{color}

  Declare math option.
53 \DeclareBoolOption[true]{math}
54 \DeclareComplementaryOption{nomath}{math}

  Execute default options and process given options.
55 \ProcessKeyvalOptions*

  Require packages as per given options.
56 \IfStrEq{\skrapport@paper}{a4paper}{%
57 \RequirePackage[a4paper]{geometry}
58 \setlength\paperheight {297mm}
59 \setlength\paperwidth  {210mm}
60 }{\IfStrEq{\skrapport@paper}{a5paper}{%
61 \RequirePackage[a5paper]{geometry}
62 \setlength\paperheight {210mm}
63 \setlength\paperwidth  {148mm}
64 }{%
65 \ClassError{skrapport}{%
66 Option 'paper' has unknown value '\skrapport@paper'
67 }{}
68 }}
69 \IfStrEq{\skrapport@ptsize}{10pt}{%
70 \renewcommand\@ptsize{0}
71 }{%
72 \IfStrEq{\skrapport@ptsize}{11pt}{%
73 \renewcommand\@ptsize{1}
74 }{%
75 \IfStrEq{\skrapport@ptsize}{12pt}{%
76 \renewcommand\@ptsize{2}
77 }{%
78 \ClassError{skrapport}{%
79 Option 'ptsize' has unknown value '\skrapport@ptsize'
80 }{}
81 }
82 }
83 }
84 \ifskrapport@draft
85 \setlength\overfullrule{5pt}
86 \else
87 \setlength\overfullrule{0pt}
88 \fi
89 \ifskrapport@leqno\input{leqno.clo}\fi
90 \ifskrapport@fleqn\input{fleqn.clo}\fi
91 \IfStrEq{\skrapport@titles}{bf}{%
92 \let\@titstyle\bfseries%
93 }{\IfStrEq{\skrapport@titles}{sf}{%
94 \let\@titstyle\sffamily\bfseries%

```

```

95 }{%
96 \let\@titstyle\relax%
97 }}
98 \ifxetex
99   \RequirePackage[quiet]{fontspec}
100 \DeclareRobustCommand\nobreakspace{\leavevmode\nobreak\space}
101 \else
102   \RequirePackage[T1]{fontenc}
103 \fi
104 \ifskrapport@color
105 \RequirePackage{etoolbox}
106 \RequirePackage{xcolor}
107 \fi
108 \IfStrEq{\skrapport@font}{nofont}{}{%
109 \IfStrEq{\skrapport@font}{kpfonts}{%
110 \RequirePackage[easyscs1,intlimits,sumlimits]{kpfonts}
111 }{%
112 \IfStrEq{\skrapport@font}{palatino}{%
113 \IfFileExists{tgpagella.sty}{%
114 \RequirePackage{tgpagella}
115 }{%
116 \RequirePackage[sc]{mathpazo}
117 }
118 }{%
119 \IfStrEq{\skrapport@font}{lmodern}{%
120 \RequirePackage{lmodern}
121 }{%
122 \ClassError{skrapport}{%
123 Option 'font' has unknown value '\skrapport@font'
124 }{}
125 }
126 }
127 }
128 }
129 \ifskrapport@eng
130 \ifxetex
131 \RequirePackage{xkeyval}
132 \RequirePackage{polyglossia}
133 \setmainlanguage[variant=british]{english}
134 \setotherlanguage{swedish}
135 \else
136 \RequirePackage[swedish,british]{babel}
137 \fi
138 \else
139 \ifxetex
140 \RequirePackage{xkeyval}
141 \RequirePackage{polyglossia}
142 \setmainlanguage{swedish}
143 \setotherlanguage[variant=british]{english}
144 \else

```

```

145 \RequirePackage[british,swedish]{babel}
146 \fi
147 \fi
148 \ifskrapport@twocolumn
149 \RequirePackage{etoolbox}
150 \RequirePackage{multicol}
151 \fi

    Include some essential packages per default.
152 \RequirePackage{calc}
153 \AtEndOfClass{
154     \RequirePackage{microtype}
155 \RequirePackage{icomma}
156 \IfStrEq{\skrapport@font}{kpfonts}{}{\RequirePackage[intlimits]{amsmath}}
157 \let\Finv\relax
158 \let\Game\relax
159 \let\beth\relax
160 \let\gimel\relax
161 \let\daleth\relax
162 \IfStrEq{\skrapport@font}{kpfonts}{}{\RequirePackage{amssymb}}
163 \IfStrEq{\skrapport@font}{kpfonts}{}{\RequirePackage{textcomp}}
164 \ifskrapport@math\IfFileExists{skmath.sty}{\RequirePackage{skmath}}{}{\fi}
165 }
166 \AtBeginDocument{
167 \ifundefined{urlstyle}{}{\urlstyle{same}}
168 }

    Include the correct point size .clo file from the article class.
169 \input{size1\@ptsize.clo}

    Set some default measurements.
170 \addtolength\textwidth{0.5\oddsidemargin}
171 \addtolength\textwidth{0.5\evensidemargin}
172 \addtolength\oddsidemargin{-0.5\oddsidemargin}
173 \addtolength\evensidemargin{-0.5\evensidemargin}
174 \setlength\lineskip{1\p@}
175 \setlength\normallineskip{1\p@}
176 \renewcommand\baselinestretch{}

    Indentation code. Undo the indentation set by the article class if indentation
    was requested by the user. See the parskip package for further information. Enable
    french spacing as well.
177 \ifskrapport@indent\else
178     \setlength\parskip{0.5\baselineskip \@plus 2pt}
179 \parindent=\z@
180 \setlength\parfillskip{30\p@ \@plus 1fil}
181 \def\@listI{\leftmargin\leftmarginI
182     \topsep\z@ \parsep\parskip \itemsep\z@}
183 \let\@listi\@listI
184 \@listi
185 \def\@listii{\leftmargin\leftmarginii

```

```

186 \labelwidth\leftmarginii\advance\labelwidth-\labelsep
187 \topsep\z@ \parsep\parskip \itemsep\z@}
188 \def\@listiii{\leftmargin\leftmarginiii
189 \labelwidth\leftmarginiii\advance\labelwidth-\labelsep
190 \topsep\z@ \parsep\parskip \itemsep\z@}
191 \partopsep=\z@
192 \@ifundefined{CheckCommand}{}{%
193 \CheckCommand*\@starttoc}[1]{%
194 \begingroup
195 \makeatletter
196 \@input{\jobname.#1}%
197 \if@filesw
198 \expandafter\newwrite\csname tf@#1\endcsname
199 \immediate\openout \csname tf@#1\endcsname \jobname.#1\relax
200 \fi
201 \@nobreakfalse
202 \endgroup}}
203 \renewcommand*\@starttoc}[1]{%
204 \begingroup
205 \makeatletter
206 \parskip\z@
207 \@input{\jobname.#1}%
208 \if@filesw
209 \expandafter\newwrite\csname tf@#1\endcsname
210 \immediate\openout \csname tf@#1\endcsname \jobname.#1\relax
211 \fi
212 \@nobreakfalse
213 \endgroup}
214 \fi
215 \frenchspacing
    Penalties and float settings.
216 \@lowpenalty 51
217 \@medpenalty 151
218 \@highpenalty 301
219 \setcounter{topnumber}{2}
220 \setcounter{bottomnumber}{1}
221 \setcounter{totalnumber}{4}
222 \setcounter{dbltopnumber}{2}
223 \renewcommand\topfraction{.75}
224 \renewcommand\bottomfraction{.5}
225 \renewcommand\textfraction{.25}
226 \renewcommand\floatpagefraction{.625}
227 \renewcommand\dbltopfraction{.75}
228 \renewcommand\dblfloatpagefraction{.625}

```

\regarding This macro is used by \maketitle to insert a simple text into the header on the title page.

```

229 \def\@regarding{\relax}
230 \newcommand\regarding[1]{\gdef\@regarding{#1}}

```

`\license` This macro is used by `\maketitle` to insert a license into the footer on the titlepage.

```
231 \def\copyright{\relax}
232 \newcommand{\license}[1]{\gdef\copyright{#1}}
```

The standard `\maketitle` command as taken from the article class but with some basic restyling.

```
233 \let\smallprintstyle\relax
234 \newcommand\maketitle{\par%
235   \begingroup
236     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
237     \def\makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
238     \long\def\makefntext##1{\parindent 1em\noindent%
239       \hb@xt@1.8em{\hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
240     \newpage
241     \global\@topnum\z@
242     \@maketitle
243     \thispagestyle{plain}\@thanks
244   \endgroup
245   \setcounter{footnote}{0}%
246 }
247 \def\@maketitle{%
248   \newpage
249   \null
250   \begin{flushleft}%
251   \vspace{-\headsep}
252   {\small%
253     \@smallprintstyle
254     \if\@regarding\relax\else\@regarding{, }\fi
255     \@date\par%
256   }%
257   \vspace{1.5cm}%
258   {\Huge\@titstyle\@title\par}%
259   \vspace{.125cm}%
260   {\Large\@titstyle\@author}%
261   \vspace{.75cm}%
262   \end{flushleft}%
263   \par%
264 }
```

Sectioning commands.

```
265 \setcounter{secnumdepth}{3}
266 \newcounter{section}
267 \newcounter{subsection}[section]
268 \newcounter{subsubsection}[subsection]
269 \newcounter{paragraph}[subsubsection]
270 \newcounter{subparagraph}[paragraph]
271 \renewcommand\thesection{\@arabic\c@section}
272 \renewcommand\thesubsection{\thesection.\@arabic\c@subsection}
273 \renewcommand\thesubsubsection{\thesubsection.\@arabic\c@subsubsection}
```



```

274 \renewcommand\theparagraph{\thesubsubsection.\@arabic\c@paragraph}
275 \renewcommand\thesubparagraph{\theparagraph.\@arabic\c@subparagraph}
276 \newcommand\section{\@startsection{section}{1}{\z@}%
277   {-4ex \@plus 1ex \@minus -1ex}%
278   {.5ex \@plus .5ex}%
279   {\normalfont\large\@titstyle}}
280 \newcommand\subsection{\@startsection{subsection}{2}{\z@}%
281   {-3ex \@plus 1ex \@minus -1ex}%
282   {.25ex \@plus .25ex}%
283   {\normalfont\Large\@titstyle}}
284 \newcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
285   {-2ex \@plus .5ex \@minus -.5ex}%
286   {.125ex \@plus .125ex}%
287   {\normalfont\large\@titstyle}}
288 \newcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
289   {1ex \@plus .25ex \@minus -.25ex}%
290   {-1em}%
291   {\normalfont\normalsize\bfseries}}
292 \newcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
293   {1ex \@plus .25ex \@minus -.25ex}%
294   {-1em}%
295   {\normalfont\normalsize\itshape}}

```

Itemization commands.

```

296 \setlength\leftmargini{2em}
297 \leftmargin\leftmargini
298 \setlength\leftmarginii{2em}
299 \setlength\leftmarginiii{1.5em}
300 \setlength\leftmarginiv{1.5em}
301 \setlength\leftmarginv{1em}
302 \setlength\leftmarginvi{1em}
303 \setlength\labelsep{.5em}
304 \setlength\labelwidth{\leftmargini}
305 \addtolength\labelwidth{-\labelsep}
306 \@beginparpenalty -\@lowpenalty
307 \@endparpenalty -\@lowpenalty
308 \@itempenalty -\@lowpenalty
309 \renewcommand\theenumi{\@arabic\c@enumi}
310 \renewcommand\theenumii{\@alph\c@enumii}
311 \renewcommand\theenumiii{\@roman\c@enumiii}
312 \renewcommand\theenumiv{\@Alph\c@enumiv}
313 \newcommand\labelenumi{\theenumi.}
314 \newcommand\labelenumii{\theenumii)}
315 \newcommand\labelenumiii{\theenumiii.}
316 \newcommand\labelenumiv{\theenumiv.}
317 \renewcommand\p@enumii{\theenumii}
318 \renewcommand\p@enumiii{\theenumi(\theenumii)}
319 \renewcommand\p@enumiv{\p@enumiii\theenumiii}
320 \newcommand\labelitemi{\textbullet}
321 \newcommand\labelitemii{\textopenbullet}

```

```

322 \newcommand\labelitemiii{\normalfont\bfseries\textendash}
323 \newcommand\labelitemiv{\textrightarrow}
324 \newenvironment{description}
325   {\list{\labelwidth\z@ \itemindent-\leftmargin
326     \let\makelabel\descriptionlabel}}{\endlist}
327 \newcommand*{descriptionlabel}[1]{\hspace\labelsep\normalfont\bfseries #1}
    Standard restyled abstract environment from the article class.
328 \newenvironment{abstract}{\newlength\skrapport@abstract@tw\newlength\skrapport@abstract@aw\sett
    Quotation environments.
329 \newenvironment{quote}{\list{\rightmargin\leftmargin}\item\relax\itshape}{\endlist}
330 \newenvironment{quotation}{\bigskip\begin{quote}}{\end{quote}\bigskip}
331 \newenvironment{verse}{\begin{quote}}{\end{quote}}
    Titlepage environment.
332 \newcommand\ps@skrapport@titlepage{\def\@oddhead{}\def\@evenhead{}\def\@oddfoot{\begin{minipage
333 \newenvironment{titlepage}{\cleardoublepage\setcounter{page}\@ne}{\thispagestyle{skrapport@titl
    Appendix macro.
334 \newcommand\appendix{\par\setcounter{section}{0}\setcounter{subsection}{0}\gdef\thesection{\@Al
    Figure and table floats.
335 \setlength\arraycolsep{5\p@}
336 \setlength\tabcolsep{6\p@}
337 \setlength\arrayrulewidth{.4\p@}
338 \setlength\doublerulesep{2\p@}
339 \setlength\tabbingsep{\labelsep}
340 \skip\@mpfootins=\skip\footins
341 \setlength\fbxsep{3\p@}
342 \setlength\fbxrule{.4\p@}
343 \renewcommand\theequation{\@arabic\c@equation}
344 \newcounter{figure}\renewcommand\thefigure{\@arabic\c@figure}
345 \def\fps@figure{tb}
346 \def\ftype@figure{1}
347 \def\ext@figure{lof}
348 \def\fnum@figure{\figurename~\thefigure}
349 \newenvironment{figure}{\@float{figure}}{\end@float}
350 \newenvironment{figure*}{\@dblfloat{figure}}{\end@dblfloat}
351 \newcounter{table}\renewcommand\thetable{\@arabic\c@table}
352 \def\fps@table{tb}
353 \def\ftype@table{2}
354 \def\ext@table{lot}
355 \def\fnum@table{\tablename~\thetable}
356 \newenvironment{table}{\@float{table}}{\end@float}
357 \newenvironment{table*}{\@dblfloat{table}}{\end@dblfloat}
    Captions.
358 \let\@captionstyle\relax
359 \newlength\abovecaptionskip\setlength\abovecaptionskip{10\p@}
360 \newlength\belowcaptionskip\setlength\belowcaptionskip{10\p@}
361 \long\def\@makecaption#1#2{%

```

```

362 \vskip\abovecaptionskip
363 \sbox\@tempboxa{\small{\bfseries#1:} \itshape#2}%
364 \ifdim \wd\@tempboxa >\hsize
365 \small{\bfseries\@captionstyle#1:} \itshape#2\par
366 \else
367 \global \@minipagefalse
368 \hbext\hsize{\hfil\box\@tempboxa\hfil}%
369 \fi
370 \vskip\belowcaptionskip}

Old font commands.

371 \DeclareOldFontCommand{\rm}{\normalfont\rmfamily}{\mathrm}
372 \DeclareOldFontCommand{\sf}{\normalfont\sffamily}{\mathsf}
373 \DeclareOldFontCommand{\tt}{\normalfont\ttfamily}{\mathtt}
374 \DeclareOldFontCommand{\bf}{\normalfont\bfseries}{\mathbf}
375 \DeclareOldFontCommand{\it}{\normalfont\itshape}{\mathit}
376 \DeclareOldFontCommand{\sl}{\normalfont\slshape}{\@nomath\sl}
377 \DeclareOldFontCommand{\sc}{\normalfont\scshape}{\@nomath\sc}

Redefining the \emph style to be bold when nested.

378 \let\@emstyle\relax
379 \DeclareRobustCommand\em{%
380 \@nomath\em%
381 \ifdim \fontdimen\@ne\font >\z@%
382 \itshape\bfseries%
383 \else%
384 \itshape%
385 \fi%
386 \@emstyle%
387 }

Table of contents code.

388 \newcommand\@pnumwidth{1.55em}
389 \newcommand\@tocrmarg{2em}
390 \newcommand\@dotsep{1.7}
391 \setcounter{tocdepth}{5}
392 \newcommand\tableofcontents{%
393 \section*{\contentsname
394 \mkboth{\MakeUppercase\contentsname}{\MakeUppercase\contentsname}
395 }%
396 \vskip\baselineskip%
397 \@starttoc{toc}%
398 }
399 \newcommand*\l@section{\@dottedtocline{1}{0em}{1.3em}}
400 \newcommand*\l@subsection{\@dottedtocline{2}{1.3em}{2em}}
401 \newcommand*\l@subsubsection{\@dottedtocline{3}{3.3em}{3.15em}}
402 \newcommand*\l@paragraph{\@dottedtocline{4}{6.45em}{4.15em}}
403 \newcommand*\l@subparagraph{\@dottedtocline{5}{10.6em}{5.15em}}

Fix for e.g. tocloft package
404 \let\l@figure\@empty
405 \let\l@table\@empty

```

Bibliography code.

```
406 \newdimen\bibindent
407 \setlength\bibindent{2em}
408 \newenvironment{thebibliography}[1]
409 {\section*{\refname}%
410 \@mkboth{\MakeUppercase\refname}{\MakeUppercase\refname}%
411 \list{\@biblabel{\@arabic\c@enumiv}}%
412 {\settowidth\labelwidth{\@biblabel{#1}}%
413 \leftmargin\labelwidth
414 \advance\leftmargin\labelsep
415 \@openbib@code
416 \usecounter{enumiv}%
417 \let\p@enumiv\empty
418 \renewcommand\theenumiv{\@arabic\c@enumiv}}%
419 \sloppy
420 \clubpenalty4000
421 \@clubpenalty \clubpenalty
422 \widowpenalty4000}%
423 {\def\@noitemerr
424 {\@latex@warning{Empty thebibliography environment}}}%
425 \endlist}
426 \newcommand\newblock{\hskip .11em\@plus.33em\@minus.07em}
427 \let\@openbib@code\empty
428 \newenvironment{theindex}
429 {\twocolumn[\section*{\indexname}]%
430 \@mkboth{\MakeUppercase\indexname}%
431 {\MakeUppercase\indexname}%
432 \thispagestyle{plain}\parindent\z@
433 \parskip\z@ \@plus .3\p@\relax
434 \columnseprule \z@
435 \columnsep 35\p@
436 \let\item\@idxitem}
437 {\onecolumn}
438 \newcommand\@idxitem{\par\hangindent 40\p@}
439 \newcommand\subitem{\@idxitem \hspace*{20\p@}}
440 \newcommand\subsubitem{\@idxitem \hspace*{30\p@}}
441 \newcommand\indexspace{\par \vskip 10\p@ \@plus5\p@ \@minus3\p@\relax}
```

Footnote code.

```
442 \renewcommand\footnoterule{%
443 \kern-3\p@
444 \hrule\@width.4\columnwidth
445 \kern2.6\p@}
446 \newcommand\@makefnmark[1]{%
447 \parindent 1em%
448 \noindent
449 \hb@xt@1.8em{\hss\@makefnmark}#1}
```

Basic translatable texts.

```
450 \newcommand\contentsname{Innehåll}
```

```

451 \newcommand\refname{Referenser}
452 \newcommand\figurename{Figur}
453 \newcommand\tablename{Tabell}
454 \newcommand\appendixname{Bilaga}
455 \newcommand\abstractname{Sammanfattning}
456 \def\today{\year--\month--\day}

    The twocolumn hacks implemented.

457 \ifskrapport@twocolumn
458 \AtBeginDocument{
459 \IfStrEq{\skrapport@ptsize}{10pt}{
460 \RequirePackage[fontsize=10pt,baseline=12pt]{grid}
461 }{
462 \IfStrEq{\skrapport@ptsize}{11pt}{
463 \RequirePackage[fontsize=11pt,baseline=13.2pt]{grid}
464 }{
465 \RequirePackage[fontsize=12pt,baseline=14.4pt]{grid}
466 }
467 }
468 % Redefining abstract
469 \renewenvironment{abstract}{\section*{\abstractname}}{}
470 % Patching \env{document} and \cs{maketitle}
471 \AfterEndPreamble{\begin{multicols}{2}}
472 \AtEndDocument{\end{multicols}}
473 \pretocmd{\maketitle}{\end{multicols}}{}{}
474 \apptocmd{\maketitle}{\begin{multicols}{2}}{}{}
475 % Patching \env{equation}
476 \BeforeBeginEnvironment{equation}{\begin{gridenv}}
477 \AfterEndEnvironment{equation}{\end{gridenv}}
478 \BeforeBeginEnvironment{equation*}{\begin{gridenv}}
479 \AfterEndEnvironment{equation*}{\end{gridenv}}
480 % Patching \env{multline}
481 \BeforeBeginEnvironment{multline}{\begin{gridenv}}
482 \AfterEndEnvironment{multline}{\end{gridenv}}
483 \BeforeBeginEnvironment{multline*}{\begin{gridenv}}
484 \AfterEndEnvironment{multline*}{\end{gridenv}}
485 % Patching \env{gather}
486 \BeforeBeginEnvironment{gather}{\begin{gridenv}}
487 \AfterEndEnvironment{gather}{\end{gridenv}}
488 \BeforeBeginEnvironment{gather*}{\begin{gridenv}}
489 \AfterEndEnvironment{gather*}{\end{gridenv}}
490 % Patching \env{align}
491 \BeforeBeginEnvironment{align}{\begin{gridenv}}
492 \AfterEndEnvironment{align}{\end{gridenv}}
493 \BeforeBeginEnvironment{align*}{\begin{gridenv}}
494 \AfterEndEnvironment{align*}{\end{gridenv}}
495 % Patching \env{flalign}
496 \BeforeBeginEnvironment{flalign}{\begin{gridenv}}
497 \AfterEndEnvironment{flalign}{\end{gridenv}}
498 \BeforeBeginEnvironment{flalign*}{\begin{gridenv}}

```

```

499 \AfterEndEnvironment{flalign*}{\end{gridenv}}
500 % Patching \env{alignat}
501 \BeforeBeginEnvironment{alignat}{\begin{gridenv}}
502 \AfterEndEnvironment{alignat}{\end{gridenv}}
503 \BeforeBeginEnvironment{alignat*}{\begin{gridenv}}
504 \AfterEndEnvironment{alignat*}{\end{gridenv}}
505 % Patching \env{figure}
506 \renewenvironment{figure}{%
507 \begin{gridenv}%
508 \vspace{\intextsep}%
509 \begin{minipage}{\linewidth}%
510 \def\@capttype{figure}%
511 }{%
512 \end{minipage}%
513 \vspace{\intextsep}%
514 \end{gridenv}%
515 }
516 % Patching \env{table}
517 \renewenvironment{table}{%
518 \begin{gridenv}%
519 \vspace{\intextsep}%
520 \begin{minipage}{\linewidth}%
521 \def\@capttype{table}%
522 \let\@old@caption\caption%
523 \renewcommand{\caption}[1]{%
524 \setlength{\@tempdima}{\abovecaptionskip}%
525 \setlength{\abovecaptionskip}{\belowcaptionskip}%
526 \setlength{\belowcaptionskip}{\@tempdima}%
527 \@old@caption{##1}%
528 \vspace{\belowcaptionskip}%
529 }%
530 }{%
531 \end{minipage}%
532 \vspace{\intextsep}%
533 \end{gridenv}%
534 }
535 \let\oldoldtablest\oldtablest
536 \renewcommand{\oldtablest}{%
537 \oldoldtablest%
538 \let\@old@caption\caption%
539 \renewcommand{\caption}[1]{%
540 \setlength{\@tempdima}{\abovecaptionskip}%
541 \setlength{\abovecaptionskip}{\belowcaptionskip}%
542 \setlength{\belowcaptionskip}{\@tempdima}%
543 \@old@caption{##1}%
544 \vspace{\belowcaptionskip}%
545 }%
546 }
547 % Providing \env{onecol}
548 \newenvironment{onecol}{\end{multicols}}{\begin{multicols}{3}}

```

```

549 }
550 \fi

Color theme setup. Start by patching commands and declaring default colors.
Not implemented: background colors for e.g. quote environments and sections
headings, different colors for the different sectioning levels.

551 \ifskrapport@color
552 \apptocmd{\bfseries}{\color{skrapport@boldcolor}}{}{\ClassError{skrapport}{Could not patch \pro
553 \apptocmd{\itshape}{\color{skrapport@italiccolor}}{}{\ClassError{skrapport}{Could not patch \pr
554 \if\@titstyle\relax
555 \def\@titstyle{\color{skrapport@titlecolor}}
556 \else
557 \apptocmd{\@titstyle}{\color{skrapport@titlecolor}}{}{\ClassError{skrapport}{Could not patch \p
558 \fi
559 \def\@smallprintstyle{\color{skrapport@smallprintcolor}}
560 \AtBeginDocument{%
561 \let\@abstractname\abstractname
562 \def\abstractname{\color{skrapport@titlecolor}\@abstractname}
563 }
564 \apptocmd{\quote}{\color{skrapport@quotecolor}}{}{}
565 \def\@captionstyle{\color{skrapport@captioncolor}}
566 \def\@emstyle{\color{skrapport@emphcolor}}
567 \ifskrapport@twocolumn\AtBeginDocument{%
568 \renewcommand\section{\@startsection {section}{1}{\z@}%
569         {- .999\baselineskip}{0.001\baselineskip}{\bfseries\mathversion{bold}\color{skrapport@t
570 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
571 {\baselineskip}{- .35\baselineskip}{\bfseries\color{skrapport@titlecolor}\unskip}}
572 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
573 {\baselineskip}{- .35\baselineskip}{\itshape\color{skrapport@titlecolor}\unskip}}
574 }\fi
575 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
576 {1ex \@plus .25ex \@minus -.25ex}{-1em}{\normalfont\normalsize\bfseries\color{skrapport@titleco
577 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
578 {1ex \@plus .25ex \@minus -.25ex}{-1em}{\normalfont\normalsize\itshape\color{skrapport@titlecol
579 \AtBeginDocument{\@ifpackageloaded{hyperref}{%
580 \hypersetup{%
581 citebordercolor=skrapport@citecolor,citecolor=skrapport@citecolor,%
582 filebordercolor=skrapport@filecolor,filecolor=skrapport@filecolor,%
583 linkbordercolor=skrapport@linkcolor,linkcolor=skrapport@linkcolor,%
584 menubordercolor=skrapport@menucolor,menucolor=skrapport@menucolor,%
585 urlbordercolor=skrapport@urlcolor,urlcolor=skrapport@urlcolor,%
586 runbordercolor=skrapport@runcolor,runcolor=skrapport@runcolor%
587 }
588 }}}
589 \AtBeginDocument{\color{skrapport@defaultcolor}}

Loading color themes
590 \newcommand\colortheme[1]{\usepackage{skrapport-colortheme-#1}}
591 \colortheme{default}
592 \fi

```

Final page setup

```
593 \setlength\columnsep{10\p@}
594 \setlength\columnseprule{0\p@}
595 \pagestyle{plain}
596 \pagenumbering{arabic}
597 \raggedbottom
598 \onecolumn
```

## 4.1 Color themes

### 4.1.1 Default color theme

```
599 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
600 \ProvidesPackage{skrapport-colortheme-default}
601 [2012/06/07 v1.0 skrapport color theme default]
602 \definecolor{skrapport@citecolor}{named}{green}
603 \definecolor{skrapport@filecolor}{named}{teal}
604 \definecolor{skrapport@linkcolor}{named}{red}
605 \definecolor{skrapport@menucolor}{named}{red}
606 \definecolor{skrapport@urlcolor}{named}{cyan}
607 \definecolor{skrapport@runcolor}{named}{teal}
608 \definecolor{skrapport@boldcolor}{named}{black}
609 \definecolor{skrapport@titlecolor}{named}{black}
610 \definecolor{skrapport@italiccolor}{named}{black}
611 \definecolor{skrapport@smallprintcolor}{named}{black}
612 \definecolor{skrapport@quotecolor}{named}{black}
613 \definecolor{skrapport@captioncolor}{named}{black}
614 \definecolor{skrapport@emphcolor}{named}{black}
615 \definecolor{skrapport@defaultcolor}{named}{black}
```

### 4.1.2 Unscathed color theme

```
616 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
617 \ProvidesPackage{skrapport-colortheme-unscathed}
618 [2012/06/07 v1.0 skrapport color theme unscathed]
619 \definecolor{skrapport@citecolor}{named}{skrapport@defaultcolor}
620 \definecolor{skrapport@filecolor}{named}{skrapport@defaultcolor}
621 \definecolor{skrapport@menucolor}{named}{skrapport@defaultcolor}
622 \definecolor{skrapport@runcolor}{named}{skrapport@defaultcolor}
623 \definecolor{skrapport@emphcolor}{HTML}{463335}
624 \definecolor{skrapport@linkcolor}{HTML}{CF5D3B}
625 \definecolor{skrapport@urlcolor}{named}{skrapport@linkcolor}
626 \definecolor{skrapport@titlecolor}{HTML}{B34430}
627 \definecolor{skrapport@captioncolor}{named}{skrapport@titlecolor}
628 \definecolor{skrapport@quotecolor}{HTML}{70524A}
629 \definecolor{skrapport@smallprintcolor}{named}{skrapport@quotecolor}
```

### 4.1.3 Cruelwater color theme

```
630 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
631 \ProvidesPackage{skrapport-colortheme-cruelwater}
```



```

632 [2012/06/07 v1.0 skrapport color theme cruelwater]
633 \definecolor{skrapport@citecolor}{named}{black}
634 \definecolor{skrapport@filecolor}{named}{black}
635 \definecolor{skrapport@linkcolor}{named}{black}
636 \definecolor{skrapport@menucolor}{named}{black}
637 \definecolor{skrapport@urlcolor}{named}{black}
638 \definecolor{skrapport@runcolor}{named}{black}
639 \definecolor{skrapport@boldcolor}{HTML}{030C22}
640 \definecolor{skrapport@titlecolor}{HTML}{20293F}
641 \definecolor{skrapport@italiccolor}{named}{black}
642 \definecolor{skrapport@smallprintcolor}{HTML}{A9B0B3}
643 \definecolor{skrapport@quotecolor}{HTML}{404749}
644 \definecolor{skrapport@captioncolor}{HTML}{030C22}
645 \definecolor{skrapport@emphcolor}{HTML}{20293F}
646 \definecolor{skrapport@defaultcolor}{named}{black}

```

#### 4.1.4 Violet color theme

```

647 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
648 \ProvidesPackage{skrapport-colortheme-violet}
649 [2012/06/07 v1.0 skrapport color theme violet]
650 \definecolor{skrapport@citecolor}{HTML}{932444}
651 \definecolor{skrapport@filecolor}{HTML}{932444}
652 \definecolor{skrapport@linkcolor}{HTML}{932444}
653 \definecolor{skrapport@menucolor}{HTML}{932444}
654 \definecolor{skrapport@urlcolor}{HTML}{932444}
655 \definecolor{skrapport@runcolor}{HTML}{932444}
656 \definecolor{skrapport@boldcolor}{HTML}{311A2A}
657 \definecolor{skrapport@titlecolor}{HTML}{311A2A}
658 \definecolor{skrapport@italiccolor}{named}{black}
659 \definecolor{skrapport@smallprintcolor}{HTML}{D6CBCF}
660 \definecolor{skrapport@quotecolor}{HTML}{463335}
661 \definecolor{skrapport@captioncolor}{HTML}{311A2A}
662 \definecolor{skrapport@emphcolor}{HTML}{98758D}
663 \definecolor{skrapport@defaultcolor}{named}{black}

```