

Table of Contents

- 1 Introduction
 - Policy based Reinforcement Learning
 - Policy Search
 - Finite Difference Policy Gradient
- 2 Monte-Carlo Policy Gradient
 - Likelihood Ratios
 - Policy Gradient Theorem
- 3 Actor-Critic Policy Gradient
 - Compatible Function Approximation
 - Advantage Function Critic
 - Eligibility Traces
 - Natural Policy Gradient

Table of Contents

- 1 Introduction
 - Policy based Reinforcement Learning
 - Policy Search
 - Finite Difference Policy Gradient
- 2 Monte-Carlo Policy Gradient
 - Likelihood Ratios
 - Policy Gradient Theorem
- 3 Actor-Critic Policy Gradient
 - Compatible Function Approximation
 - Advantage Function Critic
 - Eligibility Traces
 - Natural Policy Gradient

Policy-Based Reinforcement Learning

- In the last lecture we approximated the Value or Action-value function (Q-factor) using parameters θ ,

$$V_{\theta}(s) \approx V^{\pi}(s)$$

$$Q_{\theta}(s, a) \approx Q^{\pi}(s, a)$$

- A policy was generated directly from the value function (e.g. using ϵ -greedy)
- In this lecture we will directly parameterize the policy


$$\pi_{\theta}(s, a) = \mathbb{P}[a \mid s, \theta]$$

- We will focus again on model-free reinforcement learning

Value-Based and Policy-Based RL

- Value Based
 - Learnt Value Function
 - Implicit policy (ϵ -greedy)
- Policy Based
 - No Value Function
 - Learnt Policy
- Actor-Critic
 - Learnt Value Function
 - Learnt Policy


Value-Based and Policy-Based RL



Advantages of Policy-Based RL

Advantages:

- Better convergence properties
- Effective in high-dimensional or continuous action spaces
- Can learn stochastic policies



Advantages of Policy-Based RL

Advantages:

- Better convergence properties
- Effective in high-dimensional or continuous action spaces
- Can learn stochastic policies

Disadvantages:

- Typically converge to a local rather than global optimum
- Evaluating a policy is typically inefficient and high variance

Example: Rock-Paper-Scissors

- Two-player game of rock-paper-scissors
 - Scissors beats paper
 - Rock beats scissors
 - Paper beats rock
- Consider policies for *iterated* rock-paper-scissors
 - A deterministic policy is easily exploited
 - A uniform random policy is optimal (i.e. Nash equilibrium)

Policy Objective Functions

- Goal: given policy $\pi_\theta(s, a)$ with parameters θ , find best θ
- But how do we measure the quality of a policy π_θ ?
- In episodic environments we can use the start value

$$J_1(\theta) = V^{\pi_\theta}(s_1) = \mathbb{E}_{\pi_\theta}[v_1]$$

- In continuing environments we can use the average value

$$J_{avV}(\theta) = \sum_s d^{\pi_\theta}(s) V^{\pi_\theta}(s)$$

- Or the average reward per time-step

$$J_{avR}(\theta) = \sum_s d^{\pi_\theta}(s) \sum_a \pi_\theta(s, a) \mathcal{R}_s^a$$

- where $d^{\pi_\theta}(s)$ is stationary distribution of Markov chain for π_θ

Policy Optimization



- Policy based reinforcement learning is an optimization problem
- Find θ that maximises $J(\theta)$
- Some approaches do not use gradient (gradient-free)
 - Hill climbing
 - Simplex / amoeba / Nelder Mead
 - Genetic algorithms
- Greater efficiency often possible using gradient
 - Gradient descent
 - Conjugate gradient
 - Quasi-newton
- We focus on gradient descent, many extensions possible
- And on methods that exploit sequential structure

Policy Gradient

- Let $J(\theta)$ be any policy objective function
- Policy gradient algorithms search for a local maximum in $J(\theta)$ by ascending the gradient of the policy, w. r.t. parameters θ
- Where $\nabla_{\theta} J(\theta)$ is the policy gradient

$$\nabla_{\theta} J(\theta) = \begin{pmatrix} \frac{\partial J(\theta)}{\partial \theta_1} \\ \vdots \\ \frac{\partial J(\theta)}{\partial \theta_n} \end{pmatrix}$$

- and α is a step-size parameter



Computing Gradients By Finite Differences

- To evaluate policy gradient of $\pi_{\theta}(s, a)$
- For each dimension $k \in [1, n]$
 - Estimate k -th partial derivative of objective function w.r.t. θ
 - By perturbing θ by small amount ϵ in k -th dimension

$$\frac{\partial J(\theta)}{\partial \theta_k} \approx \frac{J(\theta + \epsilon u_k) - J(\theta)}{\epsilon}$$

where u_k is unit vector with 1 in k th component, 0 elsewhere

- Uses n evaluations to compute policy gradient in n dimensions
- Simple, noisy, inefficient - but sometimes effective
- Works for arbitrary policies, even if policy is not differentiable

Table of Contents

- 1 Introduction
 - Policy based Reinforcement Learning
 - Policy Search
 - Finite Difference Policy Gradient
- 2 Monte-Carlo Policy Gradient
 - Likelihood Ratios
 - Policy Gradient Theorem
- 3 Actor-Critic Policy Gradient
 - Compatible Function Approximation
 - Advantage Function Critic
 - Eligibility Traces
 - Natural Policy Gradient

Score Function

- We now compute the policy gradient analytically
- Assume policy π_θ is differentiable whenever it is non-zero
- and we know the gradient $\nabla_\theta \pi_\theta(s, a)$
- **Likelihood ratios** exploit the following identity

$$\begin{aligned}\nabla_\theta \pi_\theta(s, a) &= \pi_\theta(s, a) \frac{\nabla_\theta \pi_\theta(s, a)}{\pi_\theta(s, a)} \\ &= \pi_\theta(s, a) \nabla_\theta \log \pi_\theta(s, a)\end{aligned}$$

- The **score function** is $\nabla_\theta \log \pi_\theta(s, a)$

Softmax Policy

- We will use a softmax policy as a running example
- Weight actions using linear combination of features $\phi(s, a)^T \theta$
- Probability of action is proportional to exponential weight

$$\pi_{\theta}(s, a) \propto e^{\phi(s, a)^T \theta}$$

- The score function is

$$\nabla_{\theta} \log \pi_{\theta}(s, a) = \phi(s, a) - \mathbb{E}_{\pi_{\theta}}[\phi(s, \cdot)]$$

Gaussian Policy

- In continuous action spaces, a Gaussian policy is natural
- Mean is a linear combination of state features $\mu(s) = \phi(s)^T \theta$
- Variance may be fixed σ^2 , or can also be parameterized
- Policy is Gaussian, $a \sim \mathcal{N}(\mu(s), \sigma^2)$
- The score function is

$$\nabla_{\theta} \log \pi_{\theta}(s, a) = \frac{(a - \mu(s))\phi(s)}{\sigma^2}$$

One-Step MDPs

- Consider a simple class of one-step MDPs
- Starting in state $s \sim d(s)$
- Terminating after one time-step with reward $r = \mathcal{R}_{s,a}$
- Use likelihood ratios to compute the policy gradient

$$\begin{aligned} J(\theta) &= \mathbb{E}_{\pi_\theta}[r] \\ &= \sum_{s \in \mathcal{S}} d(s) \sum_{a \in \mathcal{A}} \pi_\theta(s, a) \mathcal{R}_{s,a} \\ \nabla_\theta J(\theta) &= \sum_{s \in \mathcal{S}} d(s) \sum_{a \in \mathcal{A}} \pi_\theta(s, a) \nabla_\theta \log \pi_\theta(s, a) \mathcal{R}_{s,a} \\ &= \mathbb{E}_{\pi_\theta}[\nabla_\theta \log \pi_\theta(s, a) r] \end{aligned}$$

Policy Gradient Theorem

- The policy gradient theorem generalises the likelihood ratio approach to multi-step MDPs
- Replaces instantaneous reward r with long-term value $Q^\pi(s, a)$

Policy Gradient Theorem

For any differentiable policy $\pi_\theta(s, a)$, for any of the policy objective functions $J = J_1, J_{avR}$, or $\frac{1}{1-\gamma}J_{aw}$, the policy gradient is

$$\begin{aligned}\nabla_\theta J(\theta) &= \sum_{s \in \mathcal{S}} d^{\pi_\theta}(s) \sum_a \nabla_\theta \pi_\theta(s, a) Q^{\pi_\theta}(s, a) \\ &= \mathbb{E}_{\pi_\theta} \nabla_\theta \log \pi_\theta(s, a) Q^{\pi_\theta}(s, a)\end{aligned}$$

Monte-Carlo Policy Gradient (REINFORCE)

- Update parameters by stochastic gradient ascent
- Using return v_t as an unbiased sample of $Q^{\pi_\theta}(s_t, a_t)$

$$\Delta\theta_t = \alpha \nabla_\theta \log \pi_\theta(s_t, a_t) v_t$$

Algorithm 1 REINFORCE

- 1: Init θ arbitrarily
 - 2: **for** each episode $\{s_1, a_1, r_2, \dots, s_{T-1}, a_{T-1}, r_T\} \sim \pi_\theta$ **do**
 - 3: **for** $t = 1$ to $T - 1$ **do**
 - 4: $\theta \leftarrow \theta + \alpha \nabla_\theta \log \pi_\theta(s_t, a_t) v_t$
 - 5: **end for**
 - 6: **end for**
 - 7: **return** θ
-

Reinforcement Learning

Policy Gradient

Gradient

Theorem

Gradient

Approximation

- Policy based Reinforcement Learning
- Policy Search
- Finite Difference Policy Gradient

- Likelihood Ratios
- Policy Gradient Theorem

- Compatible Function Approximation
- Advantage Function Critic
- Eligibility Traces
- Natural Policy Gradient

Reducing Variance Using a Critic

- Monte-Carlo policy gradient still has high variance
- We use a critic to estimate the action-value function,

$$Q_w(s, a) \approx Q^{\pi_\theta}(s, a)$$

- Actor-critic algorithms maintain *two* sets of parameters
 - Critic** Updates action-value function parameters w
 - Actor** Updates policy parameters θ , in direction suggested by critic
- Actor-critic algorithms follow an *approximate* policy gradient

$$\begin{aligned}\nabla_\theta J(\theta) &\approx \mathbb{E}_{\pi_\theta} [\nabla_\theta \log \pi_\theta(s, a) Q_w(s, a)] \\ \Delta\theta &= \alpha \nabla_\theta \log \pi_\theta(s, a) Q_w(s, a)\end{aligned}$$

Estimating the Action-Value Function

- The critic is solving a familiar problem: policy evaluation
- How good is policy π_θ for current parameters θ ?
- This problem was explored in previous two lectures, e.g.
 - Monte-Carlo policy evaluation
 - Temporal-Difference learning
 - $TD(\lambda)$
- Could also use e.g. least-squares policy evaluation

Action-Value Actor-Critic

Using linear value fn approx. $Q_w(s, a) = \phi(s, a)^T w$

Critic Updates w by linear $TD(0)$

Actor Updates θ by policy gradient

Algorithm 2 QAC

- 1: Init s, θ , Sample $a \sim \pi_\theta$
 - 2: **for** each step **do**
 - 3: Sample reward $r = \mathcal{R}_s^a$, $s' \sim \mathcal{P}_s^a$, and $a' \sim \pi_\theta(s', a')$
 - 4: $\theta = \theta + \alpha \nabla_\theta \log \pi(s, a) Q_w(s, a)$
 - 5: $w \leftarrow w + \beta (r + \gamma Q_w(s', a') - Q_w(s, a)) \phi(s, a)$
 - 6: $a \leftarrow a', s \leftarrow s'$
 - 7: **end for**
-

Bias in Actor-Critic Algorithms

- Approximating the policy gradient introduces bias
- A biased policy gradient may not find the right solution
- Luckily, if we choose value function approximation carefully
- Then we can avoid introducing any bias
- i.e. We can still follow the exact policy gradient

Compatible Function Approximation

Compatible Function Approximation Theorem

If the following two conditions are satisfied:

- Value function approximator is **compatible** to the policy

$$\nabla_w Q_w(s, a) = \nabla_\theta \log \pi_\theta(s, a)$$

- Value function parameters w minimize the mean-squared error

$$\epsilon = \mathbb{E}_{\pi_\theta} [(Q^{\pi_\theta}(s, a) - Q_w(s, a))^2]$$

Then the policy gradient is exact,

$$\nabla_\theta J(\theta) = \mathbb{E}_{\pi_\theta} [\nabla_\theta \log \pi_\theta(s, a) Q_w(s, a)]$$

Proof of Compatible Function Approximation Theorem

If w is chosen to minimise mean-squared error, gradient of ϵ w.r.t. w must be zero,

$$\nabla_w \epsilon = 0$$

$$\mathbb{E}_{\pi_\theta} [(Q^\theta(s, a) - Q_w(s, a)) \nabla_w Q_w(s, a)] = 0$$

$$\mathbb{E}_{\pi_\theta} [(Q^\theta(s, a) - Q_w(s, a)) \nabla_\theta \log \pi_\theta(s, a)] = 0$$

$$\mathbb{E}_{\pi_\theta} [Q^\theta(s, a) \nabla_\theta \log \pi_\theta(s, a)] = \mathbb{E}_{\pi_\theta} [Q_w(s, a) \nabla_\theta \log \pi_\theta(s, a)]$$

So $Q_w(s, a)$ can be substituted directly into the policy gradient,

$$\nabla_\theta J(\theta) = \mathbb{E}_{\pi_\theta} [\nabla_\theta \log \pi_\theta(s, a) Q_w(s, a)]$$

Reducing Variance Using a Baseline

- We subtract a baseline function $B(s)$ from the policy gradient
- This can reduce variance, without changing expectation

$$\begin{aligned}\mathbb{E}_{\pi_{\theta}}[\nabla_{\theta} \log \pi_{\theta}(s, a) B(s)] &= \sum_{s \in \mathcal{S}} d^{\pi_{\theta}}(s) \sum_a \nabla_{\theta} \pi_{\theta}(s, a) B(s) \\ &= \sum_{s \in \mathcal{S}} d^{\pi_{\theta}}(s) B(s) \nabla_{\theta} \sum_{a \in \mathcal{A}} \pi_{\theta}(s, a) = 0\end{aligned}$$

- A good baseline is the state value function $B(s) = V^{\pi_{\theta}}(s)$
- So we can rewrite the policy gradient using the **advantage function** $A^{\pi_{\theta}}(s, a)$

$$\begin{aligned}A^{\pi_{\theta}}(s, a) &= Q^{\pi_{\theta}}(s, a) - V^{\pi_{\theta}}(s) \\ \nabla_{\theta} J(\theta) &= \mathbb{E}_{\pi_{\theta}}[\nabla_{\theta} \log \pi_{\theta}(s, a) A^{\pi_{\theta}}(s, a)]\end{aligned}$$

Estimating the Advantage Function (1)

- The advantage function can significantly reduce variance of policy gradient
- So the critic should really estimate the advantage function
- For example, by estimating *both* $V^{\pi_{\theta}}(s)$ and $Q^{\pi_{\theta}}(s, a)$
- Using two function approximators and two parameter vectors,

$$V_v(s) \approx V^{\pi_{\theta}}(s)$$

$$Q_w(s, a) \approx Q^{\pi_{\theta}}(s, a)$$

$$A(s, a) = Q_w(s, a) - V_v(s)$$

- And updating *both* value functions by e.g. TD learning

Estimating the Advantage Function (2)

- For the true value function $V^{\pi_\theta}(s)$, the TD error δ^{π_θ}

$$\delta^{\pi_\theta} = r + \gamma V^{\pi_\theta}(s') - V^{\pi_\theta}(s)$$

- is an unbiased estimate of the advantage function

$$\begin{aligned}\mathbb{E}_{\pi_\theta}[\delta^{\pi_\theta} | s, a] &= \mathbb{E}_{\pi_\theta}[r + \gamma V^{\pi_\theta}(s') | s, a] - V^{\pi_\theta}(s) \\ &= Q^{\pi_\theta}(s, a) - V^{\pi_\theta}(s) = A^{\pi_\theta}(s, a)\end{aligned}$$

- So we can use the TD error to compute the policy gradient

$$\nabla_\theta J(\theta) = \mathbb{E}_{\pi_\theta}[\nabla_\theta \log \pi_\theta(s, a) \delta^{\pi_\theta}]$$

- In practice we can use an approximate TD error

$$\delta_v = r + \gamma V_v(s') - V_v(s)$$

- This approach only requires one set of critic parameters v

Critics at Different Time-Scales

- Critic can estimate value function $V_\theta(s)$ from many targets at different time-scales

- For MC, the target is the return v_t

$$\Delta\theta = \alpha(v_t - V_\theta(s))\phi(s)$$

- For TD(0), the target is the TD target $r + \gamma V(s')$

$$\Delta\theta = \alpha(r + \gamma V(s') - V_\theta(s))\phi(s)$$

- For forward-view TD(λ), the target is the λ -return v_t^λ

$$\Delta\theta = \alpha(v_t^\lambda - V_\theta(s))\phi(s)$$

- For backward-view TD(λ), we use eligibility traces

$$\delta_t = r_{t+1} + \gamma V(s_{t+1}) - V(s_t)$$

$$e_t = \gamma\lambda e_{t-1} + \phi(s_t)$$

$$\Delta\theta = \alpha\delta_t e_t$$

Actors at Different Time-Scales

- The policy gradient can also be estimated at many time-scales

$$\nabla_{\theta} J(\theta) = \mathbb{E}_{\pi_{\theta}} [\nabla_{\theta} \log \pi_{\theta}(s, a) A^{\pi_{\theta}}(s, a)]$$

- Monte-Carlo policy gradient uses error from complete return

$$\Delta \theta = \alpha (V_t - V_v(s_t)) \nabla_{\theta} \log \pi_{\theta}(s_t, a_t)$$

- Actor-critic policy gradient uses the one-step TD error

$$\Delta \theta = \alpha (r + \gamma V_v(s_{t+1}) - V_v(s_t)) \nabla_{\theta} \log \pi_{\theta}(s_t, a_t)$$

Policy Gradient with Eligibility Traces

- Just like forward-view $TD(\lambda)$, we can mix over time-scales

$$\Delta\theta = \alpha(v_t^\lambda - V_v(s_t))\nabla_\theta \log \pi_\theta(s_t, a_t)$$

- where $v_t^\lambda - V_v(s_t)$ is a biased estimate of advantage fn
- Like backward-view $TD(\lambda)$, we can also use eligibility traces
- By equivalence with $TD(\lambda)$, substituting
 $\phi(s) = \nabla_\theta \log \pi_\theta(s, a)$

$$\delta = r_{t+1} + \gamma V_v(s_{t+1}) - V_v(s_t)$$

$$e_{t+1} = \gamma\lambda e_t + \nabla_\theta \log \pi_\theta(s, a)$$


$$\Delta\theta = \alpha\delta e_t$$

- This update can be applied online, to incomplete sequences

Alternative Policy Gradient Directions

- Gradient ascent algorithms can follow any ascent direction
- A good ascent direction can significantly speed convergence
- Also, a policy can often be reparametrized without changing action probabilities
- For example, increasing score of all actions in a softmax policy
- The vanilla gradient is sensitive to these reparametrizations

Natural Policy Gradient



- The **natural policy gradient** is parametrization independent
- It finds ascent direction that is closest to vanilla gradient, when changing policy by a small, fixed amount

$$\nabla_{\theta}^{\text{nat}} \pi_{\theta}(s, a) = G_{\theta}^{-1} \nabla_{\theta} \pi_{\theta}(s, a)$$

- where G_{θ} is the Fisher information matrix

$$G_{\theta} = \mathbb{E}_{\pi_{\theta}} [\nabla_{\theta} \log \pi_{\theta}(s, a) \nabla_{\theta} \log \pi_{\theta}(s, a)^T]$$

Natural Policy Gradient

- Using compatible function approximation,

$$\nabla_w A_w(s, a) = \nabla_\theta \log \pi_\theta(s, a)$$

- So the natural policy gradient simplifies,

$$\begin{aligned}\nabla_\theta J(\theta) &= \mathbb{E}_{\pi_\theta} [\nabla_\theta \log \pi_\theta(s, a) A^{\pi_\theta}(s, a)] \\ &= \mathbb{E}_{\pi_\theta} [\nabla_\theta \log \pi_\theta(s, a) \nabla_\theta \log \pi_\theta(s, a)^T w] \\ &= G_\theta w \\ \nabla_\theta^{\text{nat}} J(\theta) &= w\end{aligned}$$

- i.e. update actor parameters in direction of critic parameters

Summary of Policy Gradient Algorithms

- The policy gradient has many equivalent forms

$$\nabla_{\theta} J(\theta) = \mathbb{E}_{\pi_{\theta}} [\nabla_{\theta} \log \pi_{\theta}(s, a) v_t] \quad \text{REINFORCE}$$

$$= \mathbb{E}_{\pi_{\theta}} [\nabla_{\theta} \log \pi_{\theta}(s, a) Q_w(s, a)] \quad \text{Actor-Critic}$$

$$= \mathbb{E}_{\pi_{\theta}} [\nabla_{\theta} \log \pi_{\theta}(s, a) A_w(s, a)] \quad \text{Advantage actor-Critic}$$

$$= \mathbb{E}_{\pi_{\theta}} [\nabla_{\theta} \log \pi_{\theta}(s, a) \delta] \quad \text{TD Actor-Critic}$$

$$= \mathbb{E}_{\pi_{\theta}} [\nabla_{\theta} \log \pi_{\theta}(s, a) \delta e] \quad \text{TD}(\lambda) \text{ Actor-Critic}$$

$$G_{\theta}^{-1} \nabla_{\theta} J(\theta) = w \quad \text{Natural Actor-Critic}$$

- Each leads a stochastic gradient ascent algorithm
- Critic uses policy evaluation (e.g. MC or TD learning) to estimate $Q^{\pi}(s, a)$, $A^{\pi}(s, a)$ or $V^{\pi}(s)$

State of the art not yet covered

- Deep Deterministic Policy Gradient (DDPG)
- Asynchronous Advantage Actor-Critic Algorithm (A3C), Importance Weighted Actor-Learner Architectures (IMPALA)
- Trust Region Policy Optimization (TRPO), Proximal Policy Optimization (PPO)
- Soft Actor-Critic

References

- Sutton, Richard S., and Andrew G. Barto. Reinforcement learning: An introduction. MIT press, 2018.
- Sutton, Richard S., et al. "Policy gradient methods for reinforcement learning with function approximation." Advances in neural information processing systems. 2000.
- <https://github.com/dalmia/David-Silver-Reinforcement-learning>, Reinforcement Learning Courses at UCL, David Silver