

Reinforcement Learning: Theory and Algorithms

Alekh Agarwal Kianté Brantley Nan Jiang

Sham M. Kakade Wen Sun

February 7, 2026

WORKING DRAFT

Please email bookrltheory@gmail.com with any typos or errors you find. We appreciate it.

Contents

Notation	ix
I Fundamentals	1
1 Markov Decision Processes	3
1.1 Discounted (Infinite-Horizon) Markov Decision Processes	3
1.1.1 The objective, policies, and values	3
1.1.2 Bellman Consistency Equations for Stationary Policies	5
1.1.3 Bellman Optimality Equations	6
1.2 Finite-Horizon Markov Decision Processes	9
1.3 Computational Complexity	11
1.3.1 Value Iteration	12
1.3.2 Policy Iteration	14
1.3.3 Value Iteration for Finite-Horizon MDPs	15
1.3.4 The Linear Programming Approach	16
1.4 Sample Complexity and Sampling Models	17
1.5 Bonus: Advantages and The Performance Difference Lemma	18
1.6 Bibliographic Remarks and Further Reading	19
2 Sample Complexity with a Generative Model	21
2.1 Warmup: a naive model-based approach	21
2.2 Sublinear Sample Complexity	24
2.3 Minimax Optimal Sample Complexity (and the Model-Based Approach)	26
2.3.1 The Discounted Case	26
2.3.2 Finite-Horizon Setting	27

2.4	Analysis	28
2.4.1	Variance lemmas	28
2.4.2	Completing the proof	30
2.5	Bibliographic Remarks and Further Reading	33
3	RL with Linear Features: When Does It Work, and When Does It Fail?	35
3.1	Setup and an Assumption Ladder	36
3.2	Positive results under Bellman completeness	37
3.2.1	Setup and data model	37
3.2.2	Algorithm: Least-Squares Value Iteration (LSVI)	38
3.2.3	Main guarantee: LSVI with a generative model	38
3.3	Offline extensions under Bellman completeness	41
3.3.1	Offline data model and a coverage condition	42
3.3.2	Offline policy optimization via LSVI	42
3.3.3	Offline policy evaluation via LSPE	43
3.4	Negative Results with Weaker Linear Notions	44
3.4.1	Information-theoretic lower bounds with linearly realizable Q^*	44
3.4.2	Offline impossibility under all-policies linear realizability	45
3.5	Bibliographic Remarks and Further Readings	50
4	Approximate Dynamic Programming in Large MDPs: Offline Learning and Coverage	53
4.1	Fitted Q -Iteration (FQI) in Offline RL	54
4.1.1	Two explicit requirements: coverage and Bellman approximation	54
4.1.2	The FQI algorithm	55
4.1.3	Main guarantee: what you get, and what you pay	55
4.1.4	What breaks without coverage: a minimal impossibility	58
4.2	Optional: Agnostic policy search and the horizon barrier	59
4.3	Bibliographic Remarks and Further Readings	60
II	Strategic Exploration	61
5	Multi-Armed & Linear Bandits	63
5.1	The K -Armed Bandit Problem	63

5.1.1	The Upper Confidence Bound (UCB) Algorithm	63
5.2	Linear Bandits: Handling Large Action Spaces	66
5.2.1	The LinUCB algorithm	66
5.2.2	Upper and Lower Bounds	67
5.3	LinUCB Analysis	68
5.3.1	Regret Analysis	69
5.3.2	Confidence Analysis	71
5.4	Bibliographic Remarks and Further Readings	72
6	Strategic Exploration in Tabular MDPs	73
6.1	On The Need for Strategic Exploration	73
6.2	The UCB-VI algorithm	74
6.3	Analysis	75
6.3.1	Proof of Lemma 6.2	78
6.4	An Improved Regret Bound	80
6.5	Phased Q -learning	83
6.6	Bibliographic Remarks and Further Readings	84
7	Linearly Parameterized MDPs	85
7.1	Setting	85
7.1.1	Low-Rank MDPs and Linear MDPs	85
7.2	Planning in Linear MDPs	86
7.3	Learning Transition using Ridge Linear Regression	87
7.4	Uniform Convergence via Covering	89
7.5	Algorithm	92
7.6	Analysis of UCBVI for Linear MDPs	93
7.6.1	Proving Optimism	93
7.6.2	Regret Decomposition	94
7.6.3	Concluding the Final Regret Bound	94
7.7	Bibliographic Remarks and Further Readings	96
8	Generalization with Bounded Bilinear Rank	97
8.1	Hypothesis Classes	97

8.2	The Bellman Rank	98
8.3	Examples	99
8.3.1	Examples that have small Q -Bellman rank	99
8.3.2	Examples that have small V -Bellman rank	102
8.4	Bilinear Classes	103
8.4.1	Examples	103
8.5	PAC-RL with Bounded Bilinear Rank	104
8.5.1	Algorithm	105
8.5.2	Sample Complexity	105
8.5.3	Analysis	108
8.6	The Eluder Dimension	111
8.7	Bibliographic Remarks and Further Readings	111

III Policy Optimization 113

9 Policy Gradient Methods and Non-Convex Optimization 115

9.1	Policy Gradient Expressions and the Likelihood Ratio Method	116
9.2	(Non-convex) Optimization	117
9.2.1	Gradient ascent and convergence to stationary points	118
9.2.2	Monte Carlo estimation and stochastic gradient ascent	119
9.3	Bibliographic Remarks and Further Readings	121

10 Optimality 123

10.1	Vanishing Gradients and Saddle Points	123
10.2	Policy Gradient Ascent	124
10.3	Log Barrier Regularization	126
10.4	The Natural Policy Gradient	128
10.5	Bibliographic Remarks and Further Readings	132

11 Function Approximation and the NPG 133

11.1	Compatible function approximation and the NPG	133
11.2	Examples: NPG and Q -NPG	135
11.2.1	Log-linear Policy Classes and Soft Policy Iteration	135

11.2.2	Neural Policy Classes	136
11.3	The NPG “Regret Lemma”	136
11.4	Q -NPG: Performance Bounds for Log-Linear Policies	138
11.4.1	Analysis	140
11.5	Q -NPG Sample Complexity	142
11.6	Bibliographic Remarks and Further Readings	142
12	CPI, TRPO, and More	143
12.1	Conservative Policy Iteration	143
12.1.1	The CPI Algorithm	144
12.2	Trust Region Methods and Covariant Policy Search	148
12.2.1	Proximal Policy Optimization	150
12.3	Bibliographic Remarks and Further Readings	151
IV	Further Topics	153
13	Imitation Learning	155
13.1	Setting	155
13.2	Offline IL: Behavior Cloning	155
13.3	The Hybrid Setting: Statistical Benefit and Algorithm	157
13.3.1	Extension to Agnostic Setting	158
13.4	Maximum Entropy Inverse Reinforcement Learning	159
13.4.1	MaxEnt IRL: Formulation and The Principle of Maximum Entropy	160
13.4.2	Algorithm	160
13.4.3	Maximum Entropy RL: Implementing the Planning Oracle in Eq. 13.4	161
13.5	Interactive Imitation Learning: AggreVaTe and Its Statistical Benefit over Offline IL Setting	162
13.6	Bibliographic Remarks and Further Readings	165
14	Linear Quadratic Regulators	167
14.1	The LQR Model	167
14.2	Bellman Optimality: Value Iteration & The Algebraic Riccati Equations	168
14.2.1	Planning and Finite Horizon LQRs	168

14.2.2	Planning and Infinite Horizon LQRs	170
14.3	Convex Programs to find P and K^*	171
14.3.1	The Primal for Infinite Horizon LQR	171
14.3.2	The Dual	171
14.4	Policy Iteration, Gauss Newton, and NPG	172
14.4.1	Gradient Expressions	172
14.4.2	Convergence Rates	174
14.4.3	Gauss-Newton Analysis	174
14.5	System Level Synthesis for Linear Dynamical Systems	177
14.6	Bibliographic Remarks and Further Readings	179
A	Concentration	181
A.1	Scalar concentration	181
A.2	Sub-Gaussian random variables	181
A.3	Martingale concentration	182
A.4	A discrete distribution concentration bound	182
A.5	Self-normalized bounds and least squares	183
A.6	Other Bounds	185
B	Linearly realizable Q^* is exponentially hard	187
B.1	Construction	187
B.2	Key inequalities: a^* is greedy everywhere	189
B.3	Realizability and Bellman optimality	190
B.4	Proof sketch of Theorem B.1	190
	Bibliography	193

Notation

This section collects notation and conventions that will be used throughout the book.

General Mathematical Notation

- For an integer $K \geq 1$, we slightly abuse notation and use 0-based indexing:

$$[K] := \{0, 1, 2, \dots, K - 1\}.$$

- We use $\mathbb{1}\{\mathcal{E}\}$ to denote the indicator function for an event $\mathcal{E}$, which takes value 1 if $\mathcal{E}$ is true and 0 otherwise.
- We use $\tilde{O}(\cdot)$ notation to hide polylogarithmic factors; i.e., $f(x) = \tilde{O}(g(x))$ if $f(x) = O(g(x) \cdot \text{poly}(\log x))$. Unless specified otherwise, $\log$ denotes the natural logarithm.
- For a set $\mathcal{X}$, let $\Delta(\mathcal{X})$ denote the set of probability distributions over $\mathcal{X}$.

Vectors and Norms

- For a vector v , the expressions $(v)^2$, $\sqrt{v}$, and $|v|$ denote the component-wise square, square root, and absolute value operations.
- Inequalities between vectors are understood elementwise. For vectors v, v' , we write $v \leq v'$ if $v(j) \leq v'(j)$ for all coordinates j .
- For a vector v , we refer to its j -th component as either $v(j)$ or $[v]_j$.
- For a vector x and a matrix M , unless stated otherwise, $\|x\|$ and $\|M\|$ denote the Euclidean and spectral norms, respectively. We use $\|x\|_M := \sqrt{x^\top M x}$ (with dimensions understood from context).
- We denote the ℓ_∞ -norm (max norm) by $\|x\|_\infty := \max_i |x_i|$. (Note: In the context of value functions V and Q , contraction arguments typically rely on the ℓ_∞ -norm).

Probability

- For a real-valued function f and a distribution $\mathcal{D}$, define the variance as

$$\text{Var}_{\mathcal{D}}(f) := \mathbb{E}_{x \sim \mathcal{D}}[f(x)^2] - (\mathbb{E}_{x \sim \mathcal{D}}[f(x)])^2.$$

Reinforcement Learning Context

- We write $s \in \mathcal{S}$ for states and $a \in \mathcal{A}$ for actions. Rewards are real-valued; when convenient we treat the reward function as a vector $r \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ indexed by (s, a) .
- The discount factor is $\gamma \in [0, 1)$; for a policy π , the (discounted) value function is $V^\pi : \mathcal{S} \rightarrow \mathbb{R}$ and the action-value function is $Q^\pi : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$.
- We denote a *history* (or *trajectory* prefix) at time t as $\tau_t := (s_0, a_0, r_0, \dots, a_{t-1}, r_{t-1}, s_t)$, which represents the information available to the agent at decision time t . We let $\mathcal{H}$ denote the set of all such finite histories.
- We overload notation so that for a distribution μ over $\mathcal{S}$,

$$V^\pi(\mu) := \mathbb{E}_{s \sim \mu} [V^\pi(s)].$$

- We overload notation and let P also denote a matrix of size $|\mathcal{S}||\mathcal{A}| \times |\mathcal{S}||\mathcal{A}|$ with entries $P_{(s,a),s'} := P(s' \mid s, a)$. We also define P^π to be the transition matrix on state-action pairs induced by a deterministic policy π , namely

$$P_{(s,a),(s',a')}^\pi := \begin{cases} P(s' \mid s, a) & \text{if } a' = \pi(s'), \\ 0 & \text{if } a' \neq \pi(s'). \end{cases}$$

With this notation,

$$\begin{aligned} Q^\pi &= r + \gamma P V^\pi, \\ Q^\pi &= r + \gamma P^\pi Q^\pi, \\ Q^\pi &= (I - \gamma P^\pi)^{-1} r. \end{aligned}$$

- For a vector $Q \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$, define the greedy policy and its induced value as

$$\begin{aligned} \pi_Q(s) &:= \operatorname{argmax}_{a \in \mathcal{A}} Q(s, a), \\ V_Q(s) &:= \max_{a \in \mathcal{A}} Q(s, a). \end{aligned}$$

- For a vector $Q \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$, the *Bellman optimality operator* $\mathcal{T} : \mathbb{R}^{|\mathcal{S}||\mathcal{A}|} \rightarrow \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ is defined by

$$\mathcal{T}Q := r + \gamma P V_Q. \quad (0.1)$$

- For a stationary policy π , the *Bellman evaluation operator* $\mathcal{T}^\pi : \mathbb{R}^{|\mathcal{S}||\mathcal{A}|} \rightarrow \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ is defined by

$$\mathcal{T}^\pi Q := r + \gamma P^\pi Q.$$

- In the finite-horizon setting (with time-dependent transitions P_h and rewards r_h), we define the time-dependent operators $\mathcal{T}_h, \mathcal{T}_h^\pi : \mathbb{R}^{|\mathcal{S}||\mathcal{A}|} \rightarrow \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ (which map the value at step $h+1$ to step h) as:

$$\begin{aligned} \mathcal{T}_h Q &:= r_h + P_h V_Q, \\ \mathcal{T}_h^\pi Q &:= r_h + P_h^\pi Q. \end{aligned}$$

- For a policy π and initial distribution μ , the *discounted state-action occupancy measure* $d_\mu^\pi \in \Delta(\mathcal{S} \times \mathcal{A})$ is defined as:

$$d_\mu^\pi(s, a) := (1 - \gamma) \sum_{t=0}^{\infty} \gamma^t \Pr^\pi(s_t = s, a_t = a \mid s_0 \sim \mu).$$

We similarly define the state occupancy measure $d_\mu^\pi(s) := \sum_{a \in \mathcal{A}} d_\mu^\pi(s, a)$.

Part I

Fundamentals

Chapter 1

Markov Decision Processes

1.1 Discounted (Infinite-Horizon) Markov Decision Processes

In reinforcement learning, the interactions between the agent and the environment are often described by an infinite-horizon, discounted Markov decision process (MDP)

$$M = (\mathcal{S}, \mathcal{A}, P, r, \gamma, \mu),$$

specified as follows:

- A state space $\mathcal{S}$, which may be finite or infinite. For mathematical convenience, we will assume that $\mathcal{S}$ is finite or countably infinite.
- An action space $\mathcal{A}$, which also may be discrete or infinite. For mathematical convenience, we will assume that $\mathcal{A}$ is finite.
- A transition function $P : \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\mathcal{S})$, where $\Delta(\mathcal{S})$ is the space of probability distributions over $\mathcal{S}$ (i.e., the probability simplex). $P(s' \mid s, a)$ is the probability of transitioning into state s' upon taking action a in state s . We use $P_{s,a}$ to denote the vector $P(\cdot \mid s, a)$.
- A reward function $r : \mathcal{S} \times \mathcal{A} \rightarrow [0, 1]$. $r(s, a)$ is the immediate reward associated with taking action a in state s . More generally, $r(s, a)$ could be a random variable (with a distribution that depends on s, a). While we largely focus on the deterministic case, extensions to stochastic rewards are often straightforward.
- A discount factor $\gamma \in [0, 1)$, which defines an effective horizon for the problem.
- An initial state distribution $\mu \in \Delta(\mathcal{S})$, which specifies how the initial state s_0 is generated.

In many cases, we will assume that the initial state is fixed at s_0 , i.e. μ is a distribution supported only on s_0 .

1.1.1 The objective, policies, and values

Policies. In a given MDP $M = (\mathcal{S}, \mathcal{A}, P, r, \gamma, \mu)$, the agent interacts with the environment according to the following protocol: the agent starts at some state $s_0 \sim \mu$; at each time step $t = 0, 1, 2, \dots$, the agent first observes the current state s_t , then selects an action $a_t \in \mathcal{A}$, receives the immediate reward $r_t = r(s_t, a_t)$, and finally observes the next state $s_{t+1} \sim P(\cdot \mid s_t, a_t)$.

It will be convenient to work with the *history* (or trajectory prefix) available at decision time t , which ends with the currently observed state:

$$\tau_t := (s_0, a_0, r_0, s_1, \dots, a_{t-1}, r_{t-1}, s_t).$$

We will refer to τ_t interchangeably as a *history* or a *trajectory* (prefix). Note that τ_t contains exactly the information available to the agent when choosing a_t .

In the most general setting, a policy specifies a decision-making strategy in which the agent chooses actions adaptively based on the history of observations; precisely, a policy is a (possibly randomized) mapping $\pi : \mathcal{H} \rightarrow \Delta(\mathcal{A})$, where $\mathcal{H}$ is the set of all finite trajectories of the form above (i.e. histories of all lengths that end in a state). At time t , the action is sampled as $a_t \sim \pi(\cdot \mid \tau_t)$.

A *stationary* policy $\pi : \mathcal{S} \rightarrow \Delta(\mathcal{A})$ specifies a decision-making strategy in which the agent chooses actions based only on the current state, i.e. $a_t \sim \pi(\cdot \mid s_t)$. A deterministic, stationary policy is of the form $\pi : \mathcal{S} \rightarrow \mathcal{A}$.

Values. We now define values for (general) policies. For a fixed policy and a starting state $s_0 = s$, we define the value function $V_M^\pi : \mathcal{S} \rightarrow \mathbb{R}$ as

$$V_M^\pi(s) = \mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t) \mid \pi, s_0 = s \right].$$

The expectation is with respect to the randomness of the trajectory (state transitions and any stochasticity in π). Since $r(s, a) \in [0, 1]$, we have $0 \leq V_M^\pi(s) \leq 1/(1 - \gamma)$.

Similarly, the action-value (or Q-value) function $Q_M^\pi : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ is defined as

$$Q_M^\pi(s, a) = \mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t) \mid \pi, s_0 = s, a_0 = a \right],$$

and $Q_M^\pi(s, a)$ is also bounded by $1/(1 - \gamma)$.

Goal. Given a state s , the goal of the agent is to find a policy π that maximizes the value:

$$\sup_{\pi} V_M^\pi(s), \tag{1.1}$$

where the supremum is over all (possibly non-stationary and randomized) policies. As we shall see, there exists a stationary deterministic policy which is simultaneously optimal for all starting states s .

We drop the dependence on M and write V^π when it is clear from context.

Example 1.1 (Navigation). Navigation is perhaps the simplest example of reinforcement learning. The state is the agent's current location. The four actions might be moving one step east, west, north, or south. In the simplest setting the transitions are deterministic. Taking the north action moves the agent one step north of its location. The agent might have a goal state g , and the reward is 0 until the agent reaches the goal, and 1 upon reaching g . Since $\gamma < 1$, there is an incentive to reach the goal earlier. As a result, the optimal behavior corresponds to finding a shortest path from the initial to the goal state. If a policy reaches the goal in d steps (and then stays there), the value from the initial state is γ^d .

Example 1.2 (Conversational agent). This is another natural reinforcement learning problem. The state can be the transcript of the conversation so far, along with additional context (e.g., task context, user profile information, or other relevant world state). Actions depend on the domain; in the most basic form, an action is the next utterance.

Sometimes, conversational agents are designed for task completion, such as a travel assistant, tech support agent, or virtual receptionist. In these cases, there may be a predefined set of *slots* that the agent must fill before it can propose

a solution (e.g., travel dates, origin, destination, and mode of travel). Actions can be natural language queries aimed at filling these slots.

In task-completion settings, reward is naturally defined as a binary indicator of whether the task was completed (e.g., whether travel was successfully booked). Depending on the domain, the reward can be refined to reflect quality or cost. In more open-ended conversational settings, the reward may reflect user satisfaction.

Example 1.3 (Strategic games). This is a popular category of applications, where reinforcement learning has achieved human-level performance in Backgammon, Go, Chess, and various forms of Poker. Typically, the state is the current game position, actions are legal moves, and reward is the eventual win/loss outcome (or a more detailed score, when defined). Technically, these are multi-agent settings, yet many successful approaches use methods that do not explicitly model multiple agents.

1.1.2 Bellman Consistency Equations for Stationary Policies

Stationary policies satisfy the following consistency conditions:

Lemma 1.4. *Suppose that π is a stationary policy (possibly randomized). Then V^π and Q^π satisfy the following Bellman consistency equations: for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$,*

$$\begin{aligned} V^\pi(s) &= \mathbb{E}_{a \sim \pi(\cdot|s)}[Q^\pi(s, a)], \\ Q^\pi(s, a) &= r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot|s, a)}[V^\pi(s')]. \end{aligned}$$

In particular, if π is deterministic, then $V^\pi(s) = Q^\pi(s, \pi(s))$.

We leave the proof as an exercise to the reader.

It is helpful to view V^π as a vector of length $|\mathcal{S}|$, and Q^π and r as vectors of length $|\mathcal{S}| \cdot |\mathcal{A}|$. We overload notation and let P also refer to a matrix of size $(|\mathcal{S}| \cdot |\mathcal{A}|) \times |\mathcal{S}|$ where the entry $P_{(s, a), s'}$ is equal to $P(s' | s, a)$.

We also define P^π to be the transition matrix on state-action pairs induced by a stationary policy π , specifically:

$$P_{(s, a), (s', a')}^\pi := P(s' | s, a) \pi(a' | s').$$

In particular, for deterministic policies we have:

$$P_{(s, a), (s', a')}^\pi := \begin{cases} P(s' | s, a) & \text{if } a' = \pi(s'), \\ 0 & \text{if } a' \neq \pi(s'). \end{cases}$$

With this notation, it is straightforward to verify:

$$\begin{aligned} Q^\pi &= r + \gamma P V^\pi, \\ Q^\pi &= r + \gamma P^\pi Q^\pi. \end{aligned}$$

Corollary 1.5. *Suppose that π is a stationary policy. Then*

$$Q^\pi = (I - \gamma P^\pi)^{-1} r, \tag{1.2}$$

where I is the identity matrix.

Proof. To see that $I - \gamma P^\pi$ is invertible, observe that for any non-zero vector $x \in \mathbb{R}^{|\mathcal{S}| \cdot |\mathcal{A}|}$,

$$\begin{aligned} \|(I - \gamma P^\pi)x\|_\infty &= \|x - \gamma P^\pi x\|_\infty \\ &\geq \|x\|_\infty - \gamma \|P^\pi x\|_\infty && \text{(triangle inequality for norms)} \\ &\geq \|x\|_\infty - \gamma \|x\|_\infty && (P^\pi \text{ is row-stochastic}) \\ &= (1 - \gamma)\|x\|_\infty > 0, && (\gamma < 1, x \neq 0) \end{aligned}$$

which implies $I - \gamma P^\pi$ is full rank. □

The following lemma will also be useful:

Lemma 1.6. *We have that*

$$[(1 - \gamma)(I - \gamma P^\pi)^{-1}]_{(s,a),(s',a')} = (1 - \gamma) \sum_{t=0}^{\infty} \gamma^t \mathbb{P}^\pi(s_t = s', a_t = a' \mid s_0 = s, a_0 = a),$$

so we can view the (s, a) -th row of this matrix as an induced distribution over state-action pairs when following π after starting with $s_0 = s$ and $a_0 = a$.

We leave the proof as an exercise to the reader.

1.1.3 Bellman Optimality Equations

A remarkable and convenient property of discounted MDPs is that there exists a stationary and deterministic policy that simultaneously maximizes $V^\pi(s)$ for all $s \in \mathcal{S}$. This is formalized in the following theorem.

Theorem 1.7. *Let Π be the set of all (possibly non-stationary and randomized) policies. Define*

$$\begin{aligned} V^*(s) &:= \sup_{\pi \in \Pi} V^\pi(s), \\ Q^*(s, a) &:= \sup_{\pi \in \Pi} Q^\pi(s, a). \end{aligned}$$

These quantities are finite since $V^\pi(s)$ and $Q^\pi(s, a)$ are bounded between 0 and $1/(1 - \gamma)$.

There exists a stationary and deterministic policy π such that for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$,

$$\begin{aligned} V^\pi(s) &= V^*(s), \\ Q^\pi(s, a) &= Q^*(s, a). \end{aligned}$$

We refer to such a π as an optimal policy.

Proof. For any $\pi \in \Pi$ and time t , π specifies a distribution over actions conditioned on the history of observations. For the purposes of this proof, it is helpful to formally let S_t , A_t , and R_t denote random variables, distinguishing them from realizations denoted by lower-case symbols.

We first show that conditioned on the one-step history $(S_0, A_0, R_0, S_1) = (s, a, r, s')$, the maximum future discounted return from time 1 onwards does not depend on s, a, r . More precisely, we claim that

$$\sup_{\pi \in \Pi} \mathbb{E} \left[\sum_{t=1}^{\infty} \gamma^t r(S_t, A_t) \mid \pi, (S_0, A_0, R_0, S_1) = (s, a, r, s') \right] = \gamma V^*(s'). \quad (1.3)$$

Fix any policy π . Define the “offset” policy $\pi_{(s,a,r)}$ as follows: for all $t \geq 0$ and all histories $(s_0, a_0, r_0, \dots, s_t)$,

$$\begin{aligned} \pi_{(s,a,r)}(A_t = b \mid S_0 = s_0, A_0 = a_0, R_0 = r_0, \dots, S_t = s_t) \\ := \pi(A_{t+1} = b \mid S_0 = s, A_0 = a, R_0 = r, S_1 = s_0, A_1 = a_0, R_1 = r_0, \dots, S_{t+1} = s_t). \end{aligned}$$

By a change of variables on the time index and the definition of $\pi_{(s,a,r)}$, we have

$$\mathbb{E} \left[\sum_{t=1}^{\infty} \gamma^t r(S_t, A_t) \mid \pi, (S_0, A_0, R_0, S_1) = (s, a, r, s') \right] = \gamma \mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t r(S_t, A_t) \mid \pi_{(s,a,r)}, S_0 = s' \right] = \gamma V^{\pi_{(s,a,r)}}(s').$$

Moreover, for each fixed (s, a, r) , the set $\{\pi_{(s,a,r)} : \pi \in \Pi\}$ is equal to Π itself (shifting a policy by one step is a bijection on the class of all history-dependent randomized policies). Therefore,

$$\sup_{\pi \in \Pi} \mathbb{E} \left[\sum_{t=1}^{\infty} \gamma^t r(S_t, A_t) \mid \pi, (S_0, A_0, R_0, S_1) = (s, a, r, s') \right] = \gamma \cdot \sup_{\pi \in \Pi} V^{\pi_{(s,a,r)}}(s') = \gamma \cdot \sup_{\pi \in \Pi} V^{\pi}(s') = \gamma V^*(s'),$$

proving (1.3).

We now define a stationary deterministic policy $\tilde{\pi}$ by choosing, for each state s , any maximizer of the one-step lookahead objective:

$$\tilde{\pi}(s) \in \operatorname{argmax}_{a \in \mathcal{A}} \mathbb{E} \left[r(s, a) + \gamma V^*(S_1) \mid S_0 = s, A_0 = a \right].$$

We claim that $V^{\tilde{\pi}}(s) = V^*(s)$ for all s .

Fix an initial state s_0 . Using the law of iterated expectations,

$$\begin{aligned} V^*(s_0) &= \sup_{\pi \in \Pi} \mathbb{E} \left[r(S_0, A_0) + \sum_{t=1}^{\infty} \gamma^t r(S_t, A_t) \mid S_0 = s_0 \right] \\ &= \sup_{\pi \in \Pi} \mathbb{E} \left[r(s_0, A_0) + \mathbb{E} \left[\sum_{t=1}^{\infty} \gamma^t r(S_t, A_t) \mid \pi, (S_0, A_0, R_0, S_1) = (s_0, A_0, R_0, S_1) \right] \mid S_0 = s_0 \right] \\ &\leq \sup_{\pi \in \Pi} \mathbb{E} \left[r(s_0, A_0) + \sup_{\pi' \in \Pi} \mathbb{E} \left[\sum_{t=1}^{\infty} \gamma^t r(S_t, A_t) \mid \pi', (S_0, A_0, R_0, S_1) = (s_0, A_0, R_0, S_1) \right] \mid S_0 = s_0 \right] \\ &\stackrel{(a)}{=} \sup_{\pi \in \Pi} \mathbb{E} \left[r(s_0, A_0) + \gamma V^*(S_1) \mid S_0 = s_0 \right] \\ &= \sup_{a_0 \in \mathcal{A}} \mathbb{E} \left[r(s_0, a_0) + \gamma V^*(S_1) \mid S_0 = s_0, A_0 = a_0 \right] \\ &\stackrel{(b)}{=} \mathbb{E} \left[r(s_0, A_0) + \gamma V^*(S_1) \mid S_0 = s_0, \tilde{\pi} \right]. \end{aligned}$$

Here, step (a) uses (1.3), and step (b) follows from the definition of $\tilde{\pi}$.

Applying the same argument recursively (conditioning on S_1 , then S_2 , etc.) yields, for all $t \geq 0$,

$$V^*(s_0) \leq \mathbb{E} \left[r(S_0, A_0) + \gamma r(S_1, A_1) + \cdots + \gamma^t V^*(S_{t+1}) \mid S_0 = s_0, \tilde{\pi} \right].$$

Taking $t \rightarrow \infty$ and using dominated convergence (since V^* is bounded), we obtain $V^*(s_0) \leq V^{\tilde{\pi}}(s_0)$. Since by definition $V^{\tilde{\pi}}(s_0) \leq \sup_{\pi \in \Pi} V^{\pi}(s_0) = V^*(s_0)$, we conclude $V^{\tilde{\pi}}(s_0) = V^*(s_0)$. As s_0 was arbitrary, this proves the first claim.

For the same policy $\tilde{\pi}$, an analogous argument starting from $Q^*(s, a)$ shows $Q^{\tilde{\pi}}(s, a) = Q^*(s, a)$ for all (s, a) , completing the proof. $\square$

This shows that we may restrict ourselves to stationary and deterministic policies without any loss in performance. The following theorem, also due to Bellman [1956], gives a precise characterization of the optimal action-value function.

Theorem 1.8 (Bellman optimality equations). *We say that a vector $Q \in \mathbb{R}^{|\mathcal{S}| \times |\mathcal{A}|}$ satisfies the Bellman optimality equations if, for all $(s, a) \in \mathcal{S} \times \mathcal{A}$,*

$$Q(s, a) = r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)} \left[\max_{a' \in \mathcal{A}} Q(s', a') \right].$$

For any $Q \in \mathbb{R}^{|S| \times |A|}$, we have $Q = Q^*$ if and only if Q satisfies the Bellman optimality equations. Furthermore, any deterministic policy defined by

$$\pi(s) \in \operatorname{argmax}_{a \in A} Q^*(s, a)$$

is an optimal policy (with ties broken in an arbitrary but fixed manner).

Before we prove this claim, we introduce a few definitions. Let π_Q denote a greedy policy with respect to a vector $Q \in \mathbb{R}^{|S| \times |A|}$:

$$\pi_Q(s) \in \operatorname{argmax}_{a \in A} Q(s, a),$$

where ties are broken in some arbitrary but fixed manner. With this notation, the optimal policy can be written as

$$\pi^* = \pi_{Q^*}.$$

We also use the following notation to map a vector $Q \in \mathbb{R}^{|S| \times |A|}$ to a vector of length $|S|$:

$$V_Q(s) := \max_{a \in A} Q(s, a).$$

The Bellman optimality operator $\mathcal{T}_M : \mathbb{R}^{|S| \times |A|} \rightarrow \mathbb{R}^{|S| \times |A|}$ is defined as

$$\mathcal{T}Q := r + \gamma P V_Q. \quad (1.4)$$

With this notation, the Bellman optimality equations can be written concisely as

$$Q = \mathcal{T}Q.$$

Thus, the previous theorem states that $Q = Q^*$ if and only if Q is a fixed point of the operator $\mathcal{T}$.

Proof. We begin by showing that

$$V^*(s) = \max_{a \in A} Q^*(s, a). \quad (1.5)$$

Let π^* be an optimal stationary deterministic policy, which exists by Theorem 1.7. Consider the (non-stationary) policy that takes action a in state s at time 0 and then follows π^* thereafter. By definition of V^* as the supremum over all (possibly non-stationary) policies,

$$V^*(s) \geq Q^{\pi^*}(s, a) = Q^*(s, a),$$

where the last equality uses that π^* is optimal for all starting states. Since a is arbitrary, this gives $V^*(s) \geq \max_a Q^*(s, a)$. Conversely, since π^* is deterministic, Lemma 1.4 yields

$$V^*(s) = V^{\pi^*}(s) = Q^{\pi^*}(s, \pi^*(s)) \leq \max_a Q^{\pi^*}(s, a) = \max_a Q^*(s, a),$$

proving (1.5).

First, we show the forward direction, i.e. that Q^* satisfies $Q^* = \mathcal{T}Q^*$. For any (s, a) ,

$$\begin{aligned} Q^*(s, a) &= \sup_{\pi \in \Pi} Q^\pi(s, a) \\ &= r(s, a) + \gamma \sup_{\pi \in \Pi} \mathbb{E}_{s' \sim P(\cdot | s, a)} [V^\pi(s')] \\ &= r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)} \left[\sup_{\pi \in \Pi} V^\pi(s') \right] \\ &= r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)} [V^*(s')] \\ &= r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)} \left[\max_{a'} Q^*(s', a') \right], \end{aligned}$$

where the third line uses that the transition distribution does not depend on π , and the last line uses (1.5). This proves sufficiency.

For the converse, suppose $Q = \mathcal{T}Q$ for some Q . We now show that $Q = Q^*$. Let $\pi = \pi_Q$ be a greedy policy with respect to Q . The identity $Q = \mathcal{T}Q$ means

$$Q(s, a) = r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)}[V_Q(s')] = r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)}[Q(s', \pi(s'))],$$

which in matrix form is $Q = r + \gamma P^\pi Q$. Thus,

$$Q = (I - \gamma P^\pi)^{-1} r = Q^\pi,$$

using Corollary 1.5.

It remains to show that π is optimal. Let π' be any other deterministic stationary policy. First note that

$$[(P^\pi - P^{\pi'})Q^\pi]_{s,a} = \mathbb{E}_{s' \sim P(\cdot | s, a)}[Q^\pi(s', \pi(s')) - Q^\pi(s', \pi'(s'))] \geq 0,$$

since π is greedy with respect to $Q = Q^\pi$. Using $Q^\pi = r + \gamma P^\pi Q^\pi$ and $Q^{\pi'} = (I - \gamma P^{\pi'})^{-1} r$, we have

$$\begin{aligned} Q^\pi - Q^{\pi'} &= (I - \gamma P^{\pi'})^{-1} \left((I - \gamma P^{\pi'}) - (I - \gamma P^\pi) \right) Q^\pi \\ &= \gamma (I - \gamma P^{\pi'})^{-1} (P^\pi - P^{\pi'}) Q^\pi \\ &\geq 0, \end{aligned}$$

where the last step uses that $(I - \gamma P^{\pi'})^{-1}$ has nonnegative entries (indeed, $(I - \gamma P^{\pi'})^{-1} = \sum_{t=0}^{\infty} \gamma^t (P^{\pi'})^t$). Thus $Q^\pi \geq Q^{\pi'}$ for all deterministic stationary π' . Since Theorem 1.7 establishes that an optimal policy exists within the set of stationary deterministic policies, and π dominates all such policies, π must be globally optimal. Therefore $Q = Q^\pi = Q^*$, completing the proof. $\square$

1.2 Finite-Horizon Markov Decision Processes

In some settings, it is more natural to work with finite-horizon (and hence time-dependent) Markov Decision Processes; see the discussion below. A finite-horizon, time-dependent MDP $M = (\mathcal{S}, \mathcal{A}, \{P_h\}_{h=0}^{H-1}, \{r_h\}_{h=0}^{H-1}, H, \mu)$ is specified by:

- A state space $\mathcal{S}$, which may be finite or infinite.
- An action space $\mathcal{A}$, which may be finite or infinite.
- A time-dependent transition kernel $P_h : \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\mathcal{S})$, where $\Delta(\mathcal{S})$ is the set of probability distributions over $\mathcal{S}$. Here $P_h(s' | s, a)$ is the probability of transitioning to state s' after taking action a in state s at time step h . (The stationary setting is recovered when P_h does not depend on h .)
- A time-dependent reward function $r_h : \mathcal{S} \times \mathcal{A} \rightarrow [0, 1]$, where $r_h(s, a)$ is the immediate reward obtained by taking action a in state s at time step h . More generally, one may allow $r_h(s, a)$ to be stochastic, but we focus on deterministic rewards for simplicity.
- A positive integer horizon H .
- An initial state distribution $\mu \in \Delta(\mathcal{S})$, which specifies how s_0 is generated.

A (possibly non-stationary and randomized) policy π specifies, at each time h , a distribution over actions conditioned on the observed history up to time h . (Equivalently, one may restrict attention to Markov policies $\pi(s, h)$ without loss of optimality in finite-horizon MDPs; see the theorem below.)

For a policy π , state s , and time $h \in \{0, \dots, H\}$, define the value function $V_h^\pi : \mathcal{S} \rightarrow \mathbb{R}$ as the expected cumulative reward from time h onward:

$$V_h^\pi(s) = \mathbb{E} \left[\sum_{t=h}^{H-1} r_t(S_t, A_t) \mid \pi, S_h = s \right],$$

where r_t denotes the stage- t reward function and the expectation is over the trajectory induced by π and the transition kernels. Similarly, define the state-action value (Q-value) function $Q_h^\pi : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ by

$$Q_h^\pi(s, a) = \mathbb{E} \left[\sum_{t=h}^{H-1} r_t(S_t, A_t) \mid \pi, S_h = s, A_h = a \right].$$

We also write $V^\pi(s) = V_0^\pi(s)$, and note that $V_H^\pi(s) \equiv 0$ for all s .

In terms of finite horizon *Bellman operators*, we can write this recursion as follows: for a function $f : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$, define the stage- h *optimal* Bellman operator $\mathcal{T}_h$ by

$$(\mathcal{T}_h f)(s, a) := r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} \left[\max_{a' \in \mathcal{A}} f(s', a') \right].$$

Under this definition, the optimal Q-functions satisfy the recursion:

$$\begin{aligned} Q_H^* &\equiv 0 \\ Q_h^* &= \mathcal{T}_h Q_{h+1}^* \quad \text{for } h = H-1, \dots, 0 \end{aligned}$$

Given a starting state s , the goal is to find a policy maximizing the value, i.e.,

$$\max_{\pi} V^\pi(s), \tag{1.6}$$

where the maximum is over all (possibly non-stationary and randomized) policies.

Theorem 1.9 (Bellman optimality equations: finite horizon). *For $h \in \{0, \dots, H\}$, define*

$$Q_h^*(s, a) = \sup_{\pi} Q_h^\pi(s, a),$$

where the sup is over all (possibly non-stationary and randomized) policies, and define $Q_H^(s, a) \equiv 0$ (terminal condition) for all (s, a) .*

Then $\{Q_h^\}_{h=0}^H$ is the unique collection of functions satisfying, for all $h \in \{0, \dots, H-1\}$ and $(s, a) \in \mathcal{S} \times \mathcal{A}$,*

$$Q_h(s, a) = r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} \left[\max_{a' \in \mathcal{A}} Q_{h+1}(s', a') \right]. \tag{1.7}$$

Moreover, any policy π^ defined by*

$$\pi^*(s, h) \in \operatorname{argmax}_{a \in \mathcal{A}} Q_h^*(s, a), \quad h = 0, \dots, H-1,$$

is an optimal policy.

We leave the proof as an exercise to the reader. (It follows by backward induction.)

	Poly?	Strongly Poly?
Value Iteration	$ \mathcal{S} ^2 \mathcal{A} \frac{L(P, r, \gamma) \log \frac{1}{1-\gamma}}{1-\gamma}$	X
Policy Iteration	$(\mathcal{S} ^3 + \mathcal{S} ^2 \mathcal{A}) \frac{L(P, r, \gamma) \log \frac{1}{1-\gamma}}{1-\gamma}$	$(\mathcal{S} ^3 + \mathcal{S} ^2 \mathcal{A}) \cdot \min \left\{ \frac{ \mathcal{A} \mathcal{S} }{ \mathcal{S} }, \frac{ \mathcal{S} ^2 \mathcal{A} \log \frac{ \mathcal{S} ^2}{1-\gamma}}{1-\gamma} \right\}$
LP Algorithms	$ \mathcal{S} ^3 \mathcal{A} L(P, r, \gamma)$	$ \mathcal{S} ^4 \mathcal{A} ^4 \log \frac{ \mathcal{S} }{1-\gamma}$

Table 1.1: Computational complexities of various approaches (universal constants are omitted) to find an *exact* solution. Polynomial-time algorithms may depend on the bit complexity $L(P, r, \gamma)$, while strongly polynomial algorithms do not. Note that value iteration and policy iteration have iteration complexity scaling as $1/(1-\gamma)$; thus, if γ is treated as part of the input (encoded in $L(P, r, \gamma)$), these methods are not polynomial-time in the bit-length model. Similarly, policy iteration is strongly polynomial only when γ is treated as a fixed constant. In contrast, the linear programming approach yields both polynomial-time (in the bit-length model) and strongly polynomial algorithms; the latter can be obtained via interior point methods. See the text and Section 1.6 for references. Here, $|\mathcal{S}|^2 |\mathcal{A}|$ is the assumed runtime per iteration of value iteration, and $|\mathcal{S}|^3 + |\mathcal{S}|^2 |\mathcal{A}|$ is the assumed runtime per iteration of policy iteration; these are consistent with cubic-time linear system solves.

Discussion: stationary vs. time-dependent models. For the purposes of this book, it is natural to study both models: we typically assume stationary dynamics in the infinite-horizon discounted setting and time-dependent dynamics in the finite-horizon setting.

From a theoretical perspective, the finite-horizon *time-dependent* formulation is often more convenient: backward induction avoids contraction arguments, and many sharp statistical rates admit simpler proofs in this setting.

From a practical perspective, explicitly time-dependent models are less common because they lead to policies and value functions whose tabular representations scale as $O(H|\mathcal{S}||\mathcal{A}|)$ and $O(H|\mathcal{S}|)$, respectively, i.e., a factor $O(H)$ larger than in the stationary case. In practice, one often folds temporal information into the state (e.g., augmenting the state with the time index), which recovers a stationary MDP on an expanded state space and can be combined naturally with function approximation to represent policies and value functions compactly.

1.3 Computational Complexity

This section concerns the problem of computing an optimal policy when the MDP $M = (\mathcal{S}, \mathcal{A}, P, r, \gamma)$ is known; this is the classical *planning* problem in reinforcement learning. While much of this book is concerned with statistical limits, understanding computational limits is also informative. We will consider algorithms that return both exact and approximately optimal policies. In particular, we will distinguish polynomial-time (and strongly polynomial-time) algorithms.

Assume that (P, r, γ) are specified with rational entries. Let $L(P, r, \gamma)$ denote the total bit-length of the description of M . We measure running time in the standard bit-complexity model in which basic arithmetic operations $+$, $-$, $\times$, $\div$ on numbers with $O(L(P, r, \gamma))$ bits take unit time.¹ In this setting, one may hope for an algorithm that returns an *exact* optimal policy with running time polynomial in $|\mathcal{S}|$, $|\mathcal{A}|$, and $L(P, r, \gamma)$.

It is also useful to understand which algorithms are *strongly* polynomial. Here, one does not explicitly restrict (P, r, γ) to be rational. An algorithm is strongly polynomial if it returns an optimal policy with running time polynomial in $|\mathcal{S}|$ and $|\mathcal{A}|$ only (with no dependence on $L(P, r, \gamma)$).

¹Equivalently, one can state bounds that scale polynomially with the bit-length of the numbers manipulated by the algorithm. We use the simplified unit-cost model to keep the dependence on $L(P, r, \gamma)$ explicit.

The next two subsections cover classical *iterative* algorithms that compute Q^* . We then discuss the linear programming approach.

1.3.1 Value Iteration

Perhaps the simplest algorithm for discounted MDPs is to iteratively apply the Bellman optimality operator $\mathcal{T}$. Starting from some initialization Q , we repeat

$$Q \leftarrow \mathcal{T}Q.$$

This algorithm is referred to as *Q-value iteration*.

Lemma 1.10 (Contraction). *For any $Q, Q' \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$,*

$$\|\mathcal{T}Q - \mathcal{T}Q'\|_\infty \leq \gamma \|Q - Q'\|_\infty.$$

Proof. First, for any $s \in \mathcal{S}$, we claim

$$|V_Q(s) - V_{Q'}(s)| \leq \max_{a \in \mathcal{A}} |Q(s, a) - Q'(s, a)|.$$

Assume $V_Q(s) \geq V_{Q'}(s)$ (the other case is symmetric), and let $a \in \operatorname{argmax}_{a \in \mathcal{A}} Q(s, a)$ be a greedy action for Q at s . Then

$$\begin{aligned} V_Q(s) - V_{Q'}(s) &= Q(s, a) - \max_{a' \in \mathcal{A}} Q'(s, a') \\ &\leq Q(s, a) - Q'(s, a) \leq \max_{a \in \mathcal{A}} |Q(s, a) - Q'(s, a)|. \end{aligned}$$

Using this bound,

$$\begin{aligned} \|\mathcal{T}Q - \mathcal{T}Q'\|_\infty &= \gamma \|PV_Q - PV_{Q'}\|_\infty = \gamma \|P(V_Q - V_{Q'})\|_\infty \\ &\leq \gamma \|V_Q - V_{Q'}\|_\infty = \gamma \max_s |V_Q(s) - V_{Q'}(s)| \\ &\leq \gamma \max_s \max_a |Q(s, a) - Q'(s, a)| = \gamma \|Q - Q'\|_\infty, \end{aligned}$$

where the inequality $\|Px\|_\infty \leq \|x\|_\infty$ uses that each component of Px is a convex combination of the entries of x . $\square$

The following result bounds the suboptimality of the greedy policy induced by an approximate Q -function.

Lemma 1.11. (*Q-error amplification*) *For any $Q \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$,*

$$V^{\pi_Q} \geq V^* - \frac{2\|Q - Q^*\|_\infty}{1 - \gamma} \mathbf{1},$$

where $\mathbf{1}$ denotes the vector of all ones.

Proof. Fix a state s and let $a = \pi_Q(s)$. Then

$$\begin{aligned} V^*(s) - V^{\pi_Q}(s) &= Q^*(s, \pi^*(s)) - Q^{\pi_Q}(s, a) \\ &= (Q^*(s, \pi^*(s)) - Q^*(s, a)) + (Q^*(s, a) - Q^{\pi_Q}(s, a)). \end{aligned}$$

For the first term, using that a is greedy for Q ,

$$Q(s, \pi^*(s)) \leq Q(s, a) \implies Q^*(s, \pi^*(s)) - Q^*(s, a) \leq (Q^*(s, \pi^*(s)) - Q(s, \pi^*(s))) + (Q(s, a) - Q^*(s, a)) \leq 2\|Q - Q^*\|_\infty.$$

For the second term, Bellman consistency for π_Q gives

$$Q^*(s, a) - Q^{\pi_Q}(s, a) = \gamma \mathbb{E}_{s' \sim P(\cdot|s, a)} [V^*(s') - V^{\pi_Q}(s')] \leq \gamma \|V^* - V^{\pi_Q}\|_\infty.$$

Combining,

$$V^*(s) - V^{\pi_Q}(s) \leq 2\|Q - Q^*\|_\infty + \gamma \|V^* - V^{\pi_Q}\|_\infty.$$

Taking the supremum over s on the left-hand side yields

$$\|V^* - V^{\pi_Q}\|_\infty \leq 2\|Q - Q^*\|_\infty + \gamma \|V^* - V^{\pi_Q}\|_\infty,$$

and rearranging gives

$$\|V^* - V^{\pi_Q}\|_\infty \leq \frac{2}{1-\gamma} \|Q - Q^*\|_\infty.$$

Equivalently, $V^{\pi_Q} \geq V^* - \frac{2}{1-\gamma} \|Q - Q^*\|_\infty \mathbf{1}$. □

Theorem 1.12. (*Q-value iteration convergence*) Set $Q^{(0)} = 0$, and for $k = 0, 1, \dots$ define

$$Q^{(k+1)} = \mathcal{T}Q^{(k)}.$$

Let $\pi^{(k)} = \pi_{Q^{(k)}}$. For

$$k \geq \frac{1}{1-\gamma} \log\left(\frac{2}{(1-\gamma)^2 \epsilon}\right),$$

we have

$$V^{\pi^{(k)}} \geq V^* - \epsilon \mathbf{1}.$$

Proof. Since $\|Q^*\|_\infty \leq 1/(1-\gamma)$, and $Q^{(k)} = \mathcal{T}^k Q^{(0)}$ with $Q^* = \mathcal{T}Q^*$, the contraction property (Lemma 1.10) gives

$$\begin{aligned} \|Q^{(k)} - Q^*\|_\infty &= \|\mathcal{T}^k Q^{(0)} - \mathcal{T}^k Q^*\|_\infty \leq \gamma^k \|Q^{(0)} - Q^*\|_\infty \\ &= \gamma^k \|Q^*\|_\infty \leq \frac{\gamma^k}{1-\gamma} \leq \frac{\exp(-(1-\gamma)k)}{1-\gamma}, \end{aligned}$$

where we used $\gamma^k \leq \exp(-(1-\gamma)k)$. Choosing k as stated ensures $\|Q^{(k)} - Q^*\|_\infty \leq \frac{(1-\gamma)\epsilon}{2}$, and applying Lemma 1.11 yields $V^{\pi^{(k)}} \geq V^* - \epsilon \mathbf{1}$. □

Iteration complexity for an exact solution. The previous results guarantee that Q -value iteration converges geometrically to Q^* , and hence yields an ϵ -optimal policy after $O\left(\frac{1}{1-\gamma} \log \frac{1}{\epsilon}\right)$ iterations. To obtain an *exact* optimal policy in the setting where (P, r, γ) are rational, one can combine this convergence with a standard bit-complexity separation argument. In particular, when the data (P, r, γ) have total description length $L(P, r, \gamma)$, the value of any *fixed* deterministic stationary policy can be written as a rational function of these inputs whose numerator and denominator have bit-length polynomial in $L(P, r, \gamma)$. Consequently, among the finite set of deterministic stationary policies, either two policies have exactly the same value (a true tie) or their values differ by at least $2^{-\text{poly}(L(P, r, \gamma))}$. Thus, once $\|Q^{(k)} - Q^*\|_\infty$ is smaller than a corresponding threshold, any greedy policy with respect to $Q^{(k)}$ must be optimal (up to arbitrary tie-breaking). This yields the polynomial-time bound in Table 1.1 when γ is treated as a fixed constant. Value iteration is not strongly polynomial: as $\gamma \uparrow 1$, the number of iterations required to reach the separation scale can grow arbitrarily large, and moreover the algorithm may never certify exact optimality in finite time without explicitly appealing to such bit-length arguments.

1.3.2 Policy Iteration

Policy iteration for discounted MDPs starts from an arbitrary deterministic stationary policy π_0 and repeats, for $k = 0, 1, 2, \dots$:

1. *Policy evaluation.* Compute the value of the current policy, e.g., compute V^{π_k} by solving the linear system $V^{\pi_k} = r(\cdot, \pi_k(\cdot)) + \gamma P^{\pi_k} V^{\pi_k}$, and then obtain Q^{π_k} via $Q^{\pi_k}(s, a) = r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot|s, a)}[V^{\pi_k}(s')]$. (Equivalently, one may compute Q^{π_k} directly using Equation 1.2.)
2. *Policy improvement.* Update the policy to be greedy w.r.t. Q^{π_k} :

$$\pi_{k+1} = \pi_{Q^{\pi_k}}.$$

The first step is called *policy evaluation* and the second *policy improvement*.

Lemma 1.13 (Monotonicity and contraction of policy iteration). *For all $k \geq 0$,*

1. (*Sandwich bound*) $Q^{\pi_{k+1}} \geq \mathcal{T}Q^{\pi_k} \geq Q^{\pi_k}$ (elementwise).
2. (*Geometric contraction to optimality*)

$$\|Q^* - Q^{\pi_{k+1}}\|_\infty \leq \gamma \|Q^* - Q^{\pi_k}\|_\infty.$$

Proof. We repeatedly use that $\mathcal{T}$ is monotone and a γ -contraction in $\|\cdot\|_\infty$ (Lemma 1.10), and that $Q^* \geq Q^\pi$ elementwise for any policy π .

Step 1: $\mathcal{T}Q^{\pi_k} \geq Q^{\pi_k}$. For deterministic π_k , we have $V^{\pi_k}(s) = Q^{\pi_k}(s, \pi_k(s))$. Moreover, by definition, $V_{Q^{\pi_k}}(s) = \max_a Q^{\pi_k}(s, a) \geq Q^{\pi_k}(s, \pi_k(s)) = V^{\pi_k}(s)$. Therefore, for every (s, a) ,

$$\mathcal{T}Q^{\pi_k}(s, a) = r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot|s, a)}[V_{Q^{\pi_k}}(s')] \geq r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot|s, a)}[V^{\pi_k}(s')] = Q^{\pi_k}(s, a).$$

Step 2: $Q^{\pi_{k+1}} \geq \mathcal{T}Q^{\pi_k}$. Let $\pi' = \pi_{k+1} = \pi_{Q^{\pi_k}}$. Define the (policy-specific) Bellman evaluation operator on state values,

$$(\mathcal{T}^{\pi'} V)(s) := r(s, \pi'(s)) + \gamma \mathbb{E}_{s' \sim P(\cdot|s, \pi'(s))}[V(s')].$$

This operator is monotone and a γ -contraction in $\|\cdot\|_\infty$, with unique fixed point $V^{\pi'}$.

By greediness of π' w.r.t. Q^{π_k} ,

$$(\mathcal{T}^{\pi'} V^{\pi_k})(s) = r(s, \pi'(s)) + \gamma \mathbb{E}_{s' \sim P(\cdot|s, \pi'(s))}[V^{\pi_k}(s')] = Q^{\pi_k}(s, \pi'(s)) = \max_a Q^{\pi_k}(s, a) = V_{Q^{\pi_k}}(s) \geq V^{\pi_k}(s).$$

Applying $\mathcal{T}^{\pi'}$ repeatedly and using monotonicity yields an increasing sequence $V^{\pi_k} \leq (\mathcal{T}^{\pi'})V^{\pi_k} \leq (\mathcal{T}^{\pi'})^2 V^{\pi_k} \leq \dots$, which converges to the fixed point $V^{\pi'}$. Hence,

$$V^{\pi_{k+1}} = V^{\pi'} \geq V_{Q^{\pi_k}} \quad (\text{elementwise}).$$

Now, for any (s, a) ,

$$Q^{\pi_{k+1}}(s, a) = r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot|s, a)}[V^{\pi_{k+1}}(s')] \geq r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot|s, a)}[V_{Q^{\pi_k}}(s')] = \mathcal{T}Q^{\pi_k}(s, a),$$

which proves $Q^{\pi_{k+1}} \geq \mathcal{T}Q^{\pi_k}$ and completes the sandwich bound.

Step 3: contraction. Since $Q^* = \mathcal{T}Q^*$ and $Q^* \geq Q^{\pi_{k+1}} \geq \mathcal{T}Q^{\pi_k}$ elementwise,

$$0 \leq Q^* - Q^{\pi_{k+1}} \leq Q^* - \mathcal{T}Q^{\pi_k} = \mathcal{T}Q^* - \mathcal{T}Q^{\pi_k}.$$

Taking $\|\cdot\|_\infty$ and applying Lemma 1.10 gives

$$\|Q^* - Q^{\pi_{k+1}}\|_\infty \leq \|\mathcal{T}Q^* - \mathcal{T}Q^{\pi_k}\|_\infty \leq \gamma \|Q^* - Q^{\pi_k}\|_\infty,$$

as claimed. $\square$

With Lemma 1.13, a geometric convergence bound follows immediately.

Theorem 1.14 (Policy iteration convergence). *Let π_0 be any initial deterministic stationary policy, and let $\{\pi_k\}$ be generated by policy iteration. Then for all $k \geq 0$,*

$$\|Q^* - Q^{\pi_k}\|_\infty \leq \gamma^k \|Q^* - Q^{\pi_0}\|_\infty \leq \frac{\gamma^k}{1 - \gamma}.$$

In particular, for

$$k \geq \frac{\log\left(\frac{1}{(1-\gamma)\epsilon}\right)}{1 - \gamma},$$

we have the elementwise performance guarantee

$$Q^{\pi_k} \geq Q^* - \epsilon \mathbf{1}.$$

Iteration complexity for an exact solution. Policy iteration improves the value monotonically and converges geometrically, but unlike value iteration it can terminate with an *exact* optimal policy in finitely many iterations because the policy changes only when the greedy action changes. A naive worst-case bound on the number of iterations is the number of deterministic stationary policies, $|\mathcal{A}|^{|\mathcal{S}|}$, since policy iteration never revisits a policy. A modest refinement improves this to $\frac{|\mathcal{A}|^{|\mathcal{S}|}}{|\mathcal{S}|}$. More strongly, when one measures complexity in the *strongly polynomial* model (unit-cost real arithmetic) and treats γ as fixed, substantially better bounds are known: policy iteration finds an optimal policy in a number of iterations polynomial in $|\mathcal{S}|$ and $|\mathcal{A}|$ (see Table 1.1 and Section 1.6 for references and precise statements).

1.3.3 Value Iteration for Finite-Horizon MDPs

We now specify the value iteration algorithm for finite-horizon MDPs. In the finite-horizon (time-dependent) setting, dynamic programming via backward induction computes the optimal value functions exactly, and the natural analogues of value iteration and policy iteration coincide.

Let $Q_H(s, a) \equiv 0$ for all (s, a) . For $h = H - 1, H - 2, \dots, 0$, define

$$Q_h(s, a) = r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot|s, a)} \left[\max_{a' \in \mathcal{A}} Q_{h+1}(s', a') \right]. \quad (1.8)$$

Equivalently, one may initialize $Q_{H-1}(s, a) = r_{H-1}(s, a)$ and then run the same recursion for $h = H - 2, \dots, 0$.

By Theorem 1.9, the resulting functions satisfy $Q_h = Q_h^*$ for all $h \in \{0, \dots, H\}$, and the policy

$$\pi(s, h) \in \operatorname{argmax}_{a \in \mathcal{A}} Q_h^*(s, a)$$

(with arbitrary tie-breaking) is optimal.

1.3.4 The Linear Programming Approach

It is helpful to understand an alternative approach to computing an optimal policy when the MDP is known. In particular, consider a discounted MDP $M = (\mathcal{S}, \mathcal{A}, P, r, \gamma, \mu)$ where P , r , and γ are specified by rational numbers. From a bit-complexity perspective, the iterative algorithms above are not, in general, polynomial-time in the description length of the input because their iteration complexity typically depends polynomially on $1/(1 - \gamma)$, while a rational value of $1 - \gamma$ may be represented with only $O(\log \frac{1}{1-\gamma})$ bits. In contrast, the LP approach yields polynomial-time algorithms in the standard bit model.

The Primal LP

Consider the following linear program in variables $V \in \mathbb{R}^{|\mathcal{S}|}$:

$$\begin{aligned} \min \quad & \sum_{s \in \mathcal{S}} \mu(s) V(s) \\ \text{subject to} \quad & V(s) \geq r(s, a) + \gamma \sum_{s' \in \mathcal{S}} P(s' | s, a) V(s') \quad \forall s \in \mathcal{S}, a \in \mathcal{A}. \end{aligned}$$

The feasible region is exactly the set of value functions that dominate their Bellman optimality backup. The optimal value function V^* is the (unique) minimal feasible vector (componentwise). If μ has full support, then V^* is also the unique optimizer of the above objective (since increasing any coordinate increases the objective).

Computational complexity for an exact solution. Table 1.1 summarizes standard runtime bounds for solving this LP when the coefficients are rational and we measure complexity in the bit model. There are also specialized interior-point methods for discounted MDP LPs with strong guarantees; see Section 1.6 for references and further discussion.

Policy iteration and simplex. Policy iteration can be interpreted as a pivoting method for closely related LP formulations (and, in particular, has a well-known connection to simplex-type methods under appropriate pivot rules). While the simplex method is not strongly polynomial for general LPs, policy-iteration/simplex variants admit strong polynomial-time guarantees for discounted MDPs when the discount factor is treated as fixed; see Ye [2011].

The Dual LP and the State–Action Polytope

We next introduce the discounted occupancy measure, which yields a convenient dual view. For a (possibly randomized) stationary policy π and a fixed starting state s_0 , define the distribution over state–action pairs

$$d_{s_0}^\pi(s, a) := (1 - \gamma) \sum_{t=0}^{\infty} \gamma^t \Pr^\pi(s_t = s, a_t = a | s_0). \quad (1.9)$$

It is straightforward to verify that $d_{s_0}^\pi$ is a probability distribution over $\mathcal{S} \times \mathcal{A}$ (since $(1 - \gamma) \sum_{t \geq 0} \gamma^t = 1$). For a starting distribution μ , we also define the averaged occupancy measure

$$d_\mu^\pi(s, a) := \mathbb{E}_{s_0 \sim \mu} [d_{s_0}^\pi(s, a)].$$

Flow (consistency) constraints. The discounted occupancy satisfies a linear recursion. For a fixed start state s_0 , one has for every $s \in \mathcal{S}$,

$$\sum_{a \in \mathcal{A}} d_{s_0}^\pi(s, a) = (1 - \gamma) \mathbb{1}\{s = s_0\} + \gamma \sum_{s' \in \mathcal{S}} \sum_{a' \in \mathcal{A}} P(s | s', a') d_{s_0}^\pi(s', a'). \quad (1.10)$$

Averaging (1.10) over $s_0 \sim \mu$ yields the corresponding relation for d_μ^π :

$$\sum_{a \in \mathcal{A}} d_\mu^\pi(s, a) = (1 - \gamma)\mu(s) + \gamma \sum_{s' \in \mathcal{S}} \sum_{a' \in \mathcal{A}} P(s | s', a') d_\mu^\pi(s', a') \quad \forall s \in \mathcal{S}. \quad (1.11)$$

Motivated by (1.11), define the *state–action polytope*

$$\mathcal{K}_\mu := \left\{ d \in \mathbb{R}^{|\mathcal{S}| \cdot |\mathcal{A}|} \mid d(s, a) \geq 0 \quad \forall (s, a), \quad \sum_{a \in \mathcal{A}} d(s, a) = (1 - \gamma)\mu(s) + \gamma \sum_{s', a'} P(s | s', a') d(s', a') \quad \forall s \in \mathcal{S} \right\}.$$

Proposition 1.15. $\mathcal{K}_\mu$ is exactly the set of discounted occupancy measures induced by stationary policies: $d \in \mathcal{K}_\mu$ if and only if there exists a stationary (possibly randomized) policy π such that $d_\mu^\pi = d$.

The dual LP. Using the identity

$$V^\pi(\mu) = \mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t) \right] = \frac{1}{1 - \gamma} \sum_{s \in \mathcal{S}} \sum_{a \in \mathcal{A}} d_\mu^\pi(s, a) r(s, a),$$

we can write a dual LP in the variables $d \in \mathbb{R}^{|\mathcal{S}| \cdot |\mathcal{A}|}$:

$$\begin{aligned} & \max && \frac{1}{1 - \gamma} \sum_{s \in \mathcal{S}} \sum_{a \in \mathcal{A}} d(s, a) r(s, a) \\ & \text{subject to} && d \in \mathcal{K}_\mu. \end{aligned}$$

One can verify that this is dual to the primal LP above (and strong duality holds under standard conditions). This dual perspective provides an alternative route to computing an optimal policy.

If d^* is an optimal solution and μ has full support, then an optimal policy can be recovered via

$$\pi^*(a | s) = \frac{d^*(s, a)}{\sum_{a'} d^*(s, a')} \quad \text{whenever } \sum_{a'} d^*(s, a') > 0,$$

with $\pi^*(\cdot | s)$ defined arbitrarily on states with zero occupancy. An alternative optimal policy is $\arg\max_a d^*(s, a)$; these coincide when the optimizer is unique.

1.4 Sample Complexity and Sampling Models

Much of reinforcement learning is concerned with finding a near-optimal policy (or, equivalently, achieving near-optimal return) in settings where the MDP is *not* known to the learner. We will study these questions under several different *sampling models*, which specify how the agent obtains information about the unknown underlying MDP. In each model, we are interested in understanding the number of samples required to compute a near-optimal policy, i.e. the *sample complexity*. Ultimately, we are interested in results that remain meaningful when the number of states and actions is large (or even when $\mathcal{S}$ is countably or uncountably infinite). This is analogous in spirit to generalization in supervised learning, but, as we shall see, it is fundamentally more challenging in reinforcement learning because the data distribution depends on the learner’s behavior.

The episodic setting. In the episodic setting, the learner interacts with the environment in *episodes*. In each episode, the learner starts from an initial state $s_0 \sim \mu$, acts for a finite number of steps, observes the resulting trajectory, and then the environment resets and a new episode begins with a fresh draw $s_0 \sim \mu$. This episodic model of feedback is applicable to both finite-horizon and infinite-horizon MDPs:

- **Finite-horizon MDPs.** Each episode lasts exactly H steps, after which the environment resets to $s_0 \sim \mu$.
- **Infinite-horizon MDPs.** It is often natural to impose an episodic protocol even in the infinite-horizon discounted setting by ending each episode after a random (finite) number of steps. A standard model is to terminate the episode at each time step independently with probability $1 - \gamma$ (equivalently, the episode length has a geometric distribution). After termination, the state resets to $s_0 \sim \mu$. Under this protocol, the undiscounted cumulative reward observed in one episode is an unbiased estimate of the infinite-horizon discounted value $V^\pi(\mu)$.

In this setting, we are often interested either in the number of episodes needed to find a near-optimal policy (a *PAC* guarantee), or in *regret* guarantees (which we study in Chapter 6). Both are statements about the statistical (sample) complexity of learning.

The episodic setting is challenging because the agent must explore to obtain information about relevant state–action pairs. As we shall see in Chapter 6, this exploration must be strategic: simply behaving randomly can be far too inefficient. It is therefore often helpful to also study the statistical complexity of RL in an abstract sampling model that bypasses exploration concerns.

The generative model setting. A *generative model* (or simulator oracle) takes as input a state–action pair (s, a) and returns an independent sample $s' \sim P(\cdot \mid s, a)$ together with the reward $r(s, a)$ (or, in the stochastic-reward setting, an independent sample of the reward). This model allows the learner to sample transitions from any chosen (s, a) directly, and is a convenient abstraction for isolating statistical questions from exploration dynamics.

The offline RL setting. In *offline* RL, the agent is given a fixed dataset collected in advance, typically generated by some (unknown) behavior policy or a mixture of policies. In the simplest model, the dataset consists of tuples $\{(s, a, r, s')\}$, where r corresponds to $r(s, a)$ in the deterministic-reward case (or a reward sample otherwise) and $s' \sim P(\cdot \mid s, a)$. For simplicity, it is often helpful to assume that the state–action pairs (s, a) in the dataset are sampled i.i.d. from some distribution ν over $\mathcal{S} \times \mathcal{A}$, after which (r, s') are drawn from the conditional dynamics given (s, a) . This i.i.d. model captures the core statistical difficulties associated with distribution shift and coverage.

1.5 Bonus: Advantages and The Performance Difference Lemma

Throughout, we will overload notation where, for a distribution μ over $\mathcal{S}$, we write:

$$V^\pi(\mu) = \mathbb{E}_{s \sim \mu} [V^\pi(s)].$$

The *advantage* of a policy π is defined as

$$A^\pi(s, a) := Q^\pi(s, a) - V^\pi(s).$$

Note that for an optimal policy π^* ,

$$A^{\pi^*}(s, a) = Q^{\pi^*}(s, a) - V^{\pi^*}(s) \leq 0$$

for all (s, a) .

Recall the discounted state-action visitation distribution d_μ^π from Equation 1.9. (Equivalently, d_μ^π is the distribution on $\mathcal{S} \times \mathcal{A}$ defined by the normalized discounted occupancy measure.) A basic identity we will repeatedly use is that for any function $f : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$,

$$\mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t f(s_t, a_t) \mid \pi, s_0 \sim \mu \right] = \frac{1}{1-\gamma} \mathbb{E}_{(s,a) \sim d_\mu^\pi} [f(s, a)]. \quad (1.12)$$

This follows immediately from the definition of d_μ^π .

Lemma 1.16. (*The performance difference lemma*) For all policies π, π' and distributions μ over $\mathcal{S}$,

$$V^\pi(\mu) - V^{\pi'}(\mu) = \frac{1}{1-\gamma} \mathbb{E}_{(s,a) \sim d_\mu^\pi} [A^{\pi'}(s, a)].$$

Proof. We first prove the identity for a fixed start state $s_0 = s$, and then average over $s \sim \mu$.

Fix $s_0 = s$ and let $\tau = (s_0, a_0, s_1, a_1, \dots)$ denote the (infinite) trajectory generated by following π . Next, we use a telescoping decomposition. Since $V^{\pi'}$ is bounded and $\gamma \in [0, 1)$,

$$\sum_{t=0}^{\infty} \gamma^t (\gamma V^{\pi'}(s_{t+1}) - V^{\pi'}(s_t)) = -V^{\pi'}(s_0) \quad (\text{almost surely}).$$

Therefore,

$$\begin{aligned} V^\pi(s) - V^{\pi'}(s) &= \mathbb{E}_{\tau \sim \text{Pr}^\pi(\cdot | s_0=s)} \left[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t) \right] - V^{\pi'}(s) \\ &= \mathbb{E}_{\tau \sim \text{Pr}^\pi(\cdot | s_0=s)} \left[\sum_{t=0}^{\infty} \gamma^t (r(s_t, a_t) + \gamma V^{\pi'}(s_{t+1}) - V^{\pi'}(s_t)) \right] \\ &= \mathbb{E}_{\tau \sim \text{Pr}^\pi(\cdot | s_0=s)} \left[\sum_{t=0}^{\infty} \gamma^t (r(s_t, a_t) + \gamma \mathbb{E}[V^{\pi'}(s_{t+1}) \mid s_t, a_t] - V^{\pi'}(s_t)) \right] \\ &= \mathbb{E}_{\tau \sim \text{Pr}^\pi(\cdot | s_0=s)} \left[\sum_{t=0}^{\infty} \gamma^t (Q^{\pi'}(s_t, a_t) - V^{\pi'}(s_t)) \right] \\ &= \mathbb{E}_{\tau \sim \text{Pr}^\pi(\cdot | s_0=s)} \left[\sum_{t=0}^{\infty} \gamma^t A^{\pi'}(s_t, a_t) \right]. \end{aligned}$$

Applying (1.12) with $f = A^{\pi'}$ and averaging over $s_0 = s \sim \mu$ gives the stated result. $\square$

1.6 Bibliographic Remarks and Further Reading

We refer the reader to Puterman [1994] for a comprehensive treatment of dynamic programming and MDPs; this text also contains a thorough treatment of the dual LP formulation and a proof of Lemma 1.15.

Regarding the computational complexity of planning, Ye [2011] provides an excellent summary of various approaches. Notably, Ye [2011] showed that policy iteration is a strongly polynomial-time algorithm for a fixed discount rate.² Mansour and Singh [1999] proved that the number of iterations of policy iteration is bounded by roughly $|\mathcal{A}|^{|\mathcal{S}|}/|\mathcal{S}|$.

²The strongly polynomial runtime stated in Table 1.1 differs slightly from that in Ye [2011] because we assume the cost per iteration of policy iteration is $O(|\mathcal{S}|^3 + |\mathcal{S}|^2|\mathcal{A}|)$ (dominated by solving the linear system).

(improving on the trivial $|\mathcal{A}|^{|S|}$ bound). For general strongly polynomial algorithms (independent of γ), the CIPA algorithm proposed by Ye [2005] is an interior-point method achieving the runtime claimed in Table 1.1.

The error amplification bound (Lemma 1.11) is due to Singh and Yee [1994].

The performance difference lemma (Lemma 1.16) was explicitly stated and utilized by Kakade and Langford [2002], Kakade [2003], though the result (based on a telescoping expansion of advantages) was implicit in the analysis of several prior works.

Chapter 2

Sample Complexity with a Generative Model

This chapter begins our study of *sample complexity* in tabular reinforcement learning. We ask a minimax question: as a function of the problem dimensions $(|\mathcal{S}|, |\mathcal{A}|)$, an accuracy target ϵ , a failure probability δ , and an effective horizon (either H in finite-horizon MDPs or $(1 - \gamma)^{-1}$ in discounted MDPs), how many transition samples are required to (i) estimate the optimal action-value function Q^* , or (ii) output a policy whose performance is ϵ -close to optimal?

Throughout this chapter we work in the *generative model* setting: given any state–action pair (s, a) , we may query a simulator that returns an i.i.d. sample $s' \sim P(\cdot \mid s, a)$ together with the reward. For clarity, we assume rewards are deterministic; this assumption is often mild here because the main statistical difficulty in the tabular setting is learning the transition model P , and allowing stochastic rewards only changes constants (and can be absorbed into the variance terms that appear later).

Our first question is whether we must learn an accurate model of the world in order to act near-optimally. The transition kernel has $|\mathcal{S}|^2|\mathcal{A}|$ parameters, so a naive “learn- P -then-plan” intuition suggests that one might need on the order of $|\mathcal{S}|^2|\mathcal{A}|$ observed transitions. One of the main takeaways of this chapter is that this intuition is overly pessimistic: with a generative model, one can compute a near-optimal policy from a number of samples that is *sublinear* in the model size—scaling (up to horizon and logarithmic factors) like $|\mathcal{S}||\mathcal{A}|$ rather than $|\mathcal{S}|^2|\mathcal{A}|$.

A second, equally important question is how to think about accuracy when the horizon is long. In discounted problems, values naturally live on the scale $1/(1 - \gamma)$, so an additive error ϵ should be interpreted relative to this scale. More importantly, small one-step errors can compound over time: recall the matrix identity

$$Q^\pi = (I - \gamma P^\pi)^{-1} r,$$

which makes it clear that as $\gamma \uparrow 1$, the effective horizon grows and the mapping from one-step quantities to long-run values becomes increasingly sensitive. This raises a central question for the chapter: *what is the correct dependence on the effective horizon for obtaining a desired (relative) accuracy in Q^* or in the value of the learned policy?* And can we avoid paying extra “horizon amplification” factors that arise from worst-case error propagation arguments?

2.1 Warmup: a naive model-based approach

As a warmup, we analyze the most naive “model-based” strategy in the generative model setting. We sample enough transitions to build an accurate empirical transition kernel $\hat{P}$, form the empirical MDP $\hat{M}$ by replacing P with $\hat{P}$, and

then plan in $\widehat{M}$.

Concretely, we query the simulator N times for each state–action pair (s, a) . Let $\text{count}(s', s, a)$ be the number of times these N samples transition to s' . Define the empirical transition model

$$\widehat{P}(s' | s, a) := \frac{\text{count}(s', s, a)}{N}.$$

The total number of simulator calls is $|\mathcal{S}||\mathcal{A}|N$. As in Chapter 1, we will also view P and $\widehat{P}$ as matrices of size $|\mathcal{S}||\mathcal{A}| \times |\mathcal{S}|$.

Since the transition kernel has $|\mathcal{S}|^2|\mathcal{A}|$ parameters, one might expect that on the order of $|\mathcal{S}|^2|\mathcal{A}|$ observed transitions suffice to learn a globally accurate model. The next proposition confirms this intuition, and shows that such global model accuracy implies uniform accuracy of values (simultaneously for all policies), and hence near-optimal planning in $\widehat{M}$.

Proposition 2.1. *There exists an absolute constant c such that the following holds. Fix $\epsilon \in (0, \frac{1}{1-\gamma})$ and $\delta \in (0, 1)$, and suppose we collect N samples per state–action pair, with*

$$\# \text{ samples from generative model} = |\mathcal{S}||\mathcal{A}|N \geq \frac{c}{(1-\gamma)^4} \cdot \frac{|\mathcal{S}|^2|\mathcal{A}| \log(c|\mathcal{S}||\mathcal{A}|/\delta)}{\epsilon^2}.$$

(Equivalently, $N \geq \frac{c|\mathcal{S}| \log(c|\mathcal{S}||\mathcal{A}|/\delta)}{(1-\gamma)^4 \epsilon^2}$.) Then, with probability at least $1 - \delta$, the following hold:

- **(Model accuracy)**

$$\max_{s,a} \|P(\cdot | s, a) - \widehat{P}(\cdot | s, a)\|_1 \leq (1-\gamma)^2 \epsilon.$$

- **(Uniform value accuracy)** For all stationary policies π ,

$$\|Q^\pi - \widehat{Q}^\pi\|_\infty \leq \epsilon.$$

- **(Near-optimal planning)** Let $\widehat{\pi}^*$ be an optimal policy in $\widehat{M}$. Then

$$\|\widehat{Q}^* - Q^*\|_\infty \leq \epsilon, \quad \text{and} \quad \|Q^{\widehat{\pi}^*} - Q^*\|_\infty \leq 2\epsilon.$$

Before proving Proposition 2.1, we record two basic lemmas.

Lemma 2.2. (Simulation lemma) For any stationary policy π ,

$$Q^\pi - \widehat{Q}^\pi = \gamma(I - \gamma\widehat{P}^\pi)^{-1}(P - \widehat{P})V^\pi.$$

Proof. Using $Q^\pi = (I - \gamma P^\pi)^{-1}r$ (Equation 1.2) and the analogous identity $\widehat{Q}^\pi = (I - \gamma\widehat{P}^\pi)^{-1}r$ in $\widehat{M}$, we have

$$\begin{aligned} Q^\pi - \widehat{Q}^\pi &= (I - \gamma P^\pi)^{-1}r - (I - \gamma\widehat{P}^\pi)^{-1}r \\ &= (I - \gamma\widehat{P}^\pi)^{-1} \left((I - \gamma\widehat{P}^\pi) - (I - \gamma P^\pi) \right) (I - \gamma P^\pi)^{-1}r \\ &= \gamma(I - \gamma\widehat{P}^\pi)^{-1}(P^\pi - \widehat{P}^\pi)Q^\pi. \end{aligned}$$

Finally, $(P^\pi Q^\pi)(s, a) = \mathbb{E}_{s' \sim P(\cdot | s, a)}[V^\pi(s')]$ and similarly for $\widehat{P}$, so $(P^\pi - \widehat{P}^\pi)Q^\pi = (P - \widehat{P})V^\pi$, which completes the proof. $\square$

Lemma 2.3. For any stationary policy π and any vector $v \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$,

$$\|(I - \gamma P^\pi)^{-1}v\|_\infty \leq \frac{1}{1-\gamma} \|v\|_\infty.$$

Proof. Let $w = (I - \gamma P^\pi)^{-1}v$, so $v = (I - \gamma P^\pi)w = w - \gamma P^\pi w$. Therefore,

$$\|v\|_\infty = \|w - \gamma P^\pi w\|_\infty \geq \|w\|_\infty - \gamma \|P^\pi w\|_\infty \geq (1 - \gamma)\|w\|_\infty,$$

where $\|P^\pi w\|_\infty \leq \|w\|_\infty$ uses that P^π is row-stochastic. Rearranging gives the claim. $\square$

Proof. (Proof of Proposition 2.1) The first part of the proof is with regards to model accuracy. Fix (s, a) . By Proposition A.8 (applied with $d = |\mathcal{S}|$ and N samples), with probability at least $1 - \delta'$,

$$\|P(\cdot | s, a) - \hat{P}(\cdot | s, a)\|_1 \leq c \sqrt{\frac{|\mathcal{S}| \log(c/\delta')}{N}}.$$

Taking a union bound over all $|\mathcal{S}||\mathcal{A}|$ state-action pairs and setting $\delta' = \delta/(|\mathcal{S}||\mathcal{A}|)$ yields

$$\max_{s,a} \|P(\cdot | s, a) - \hat{P}(\cdot | s, a)\|_1 \leq c \sqrt{\frac{|\mathcal{S}| \log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}}$$

with probability at least $1 - \delta$. Under the stated lower bound on N , the right-hand side is at most $(1 - \gamma)^2 \epsilon$, proving the first bullet.

Now we characterize the uniform value accuracy. Fix any stationary policy π . By Lemma 2.2 and Lemma 2.3,

$$\begin{aligned} \|Q^\pi - \hat{Q}^\pi\|_\infty &\leq \gamma \|(I - \gamma \hat{P}^\pi)^{-1}(P - \hat{P})V^\pi\|_\infty \\ &\leq \frac{\gamma}{1 - \gamma} \|(P - \hat{P})V^\pi\|_\infty. \end{aligned}$$

For each (s, a) , the quantity $[(P - \hat{P})V^\pi](s, a)$ is the difference of expectations of $V^\pi(s')$ under $P(\cdot | s, a)$ and $\hat{P}(\cdot | s, a)$, hence

$$\|(P - \hat{P})V^\pi\|_\infty \leq \left(\max_{s,a} \|P(\cdot | s, a) - \hat{P}(\cdot | s, a)\|_1 \right) \|V^\pi\|_\infty.$$

Since rewards lie in $[0, 1]$, we have $\|V^\pi\|_\infty \leq \frac{1}{1 - \gamma}$. Combining,

$$\|Q^\pi - \hat{Q}^\pi\|_\infty \leq \frac{\gamma}{(1 - \gamma)^2} \max_{s,a} \|P(\cdot | s, a) - \hat{P}(\cdot | s, a)\|_1 \leq \frac{\gamma}{(1 - \gamma)^2} \cdot (1 - \gamma)^2 \epsilon \leq \epsilon,$$

which proves the second bullet (simultaneously for all π on the event from Step 1).

We bound the near-optimal planning accuracy. First, using $|\sup_x f(x) - \sup_x g(x)| \leq \sup_x |f(x) - g(x)|$,

$$|\hat{Q}^*(s, a) - Q^*(s, a)| = \left| \sup_{\pi} \hat{Q}^\pi(s, a) - \sup_{\pi} Q^\pi(s, a) \right| \leq \sup_{\pi} |\hat{Q}^\pi(s, a) - Q^\pi(s, a)| \leq \epsilon.$$

Taking the maximum over (s, a) yields $\|\hat{Q}^* - Q^*\|_\infty \leq \epsilon$.

Finally, since $\hat{\pi}^*$ is optimal in $\hat{M}$, we have $\hat{Q}^{\hat{\pi}^*} = \hat{Q}^*$. Therefore,

$$\|Q^{\hat{\pi}^*} - Q^*\|_\infty \leq \|Q^{\hat{\pi}^*} - \hat{Q}^{\hat{\pi}^*}\|_\infty + \|\hat{Q}^* - Q^*\|_\infty \leq \epsilon + \epsilon = 2\epsilon,$$

where the first term used the uniform value accuracy bound from Step 2. This proves the third bullet. $\square$

What our warmup does (and why it is not the full story). Proposition 2.1 formalizes a very strong guarantee: by learning $\hat{P}$ accurately everywhere, we obtain *uniform* value accuracy, meaning that $\hat{Q}^\pi$ is close to Q^π simultaneously for *every* policy π . This is more than is needed for planning—to act near-optimally, we only need to identify a single near-optimal policy (or, equivalently, approximate Q^* well enough to recover one). The uniform guarantee comes at a cost: it forces us to estimate each transition distribution in ℓ_1 to high accuracy, which leads to a sample requirement scaling like the number of parameters in the transition model, $|\mathcal{S}|^2|\mathcal{A}|$.

The rest of the chapter asks what happens if we target only what planning requires. With a generative model, it turns out that one can do substantially better: the minimax number of samples needed to estimate Q^* (and to find a near-optimal policy) scales, up to horizon and logarithmic factors, like $|\mathcal{S}||\mathcal{A}|$ rather than $|\mathcal{S}|^2|\mathcal{A}|$. This is the first concrete sense in which, in reinforcement learning, we can sometimes “act near-optimally without learning the world model.”

2.2 Sublinear Sample Complexity

In the warmup, we obtained *uniform* value accuracy for all policies, which effectively required learning each transition distribution $P(\cdot \mid s, a)$ in ℓ_1 —hence the $|\mathcal{S}|^2|\mathcal{A}|$ scaling. For planning, however, we do not need to approximate the value of *every* policy. Instead, it is natural to ask for guarantees tailored to the optimal value function Q^* (and to a near-optimal policy).

Throughout this section we measure sample size in terms of

$$\# \text{ samples from generative model} = |\mathcal{S}||\mathcal{A}|N,$$

where N is the number of simulator calls per state–action pair.

We begin with a crude but instructive bound which already yields a *sublinear* dependence on the number of parameters in P .

Proposition 2.4. (Crude value bounds) Fix $\delta \in (0, 1)$. With probability at least $1 - \delta$,

$$\begin{aligned} \|Q^* - \hat{Q}^*\|_\infty &\leq \Delta_{\delta, N}, \\ \|Q^* - \hat{Q}^{\pi^*}\|_\infty &\leq \Delta_{\delta, N}, \end{aligned}$$

where

$$\Delta_{\delta, N} := \frac{\gamma}{(1 - \gamma)^2} \sqrt{\frac{2 \log(2|\mathcal{S}||\mathcal{A}|/\delta)}{N}}.$$

The first inequality gives a sublinear rate for estimating Q^* itself. To translate value-estimation error into a policy guarantee, a generic (and somewhat pessimistic) route is to use the Q -error amplification lemma (Lemma 1.11): since $\hat{\pi}^*$ is greedy w.r.t. $\hat{Q}^*$ (ties broken deterministically),

$$\|V^* - V^{\hat{\pi}^*}\|_\infty \leq \frac{2}{1 - \gamma} \|\hat{Q}^* - Q^*\|_\infty \leq \frac{2}{1 - \gamma} \Delta_{\delta, N}.$$

Equivalently, using $Q^\pi(s, a) = r(s, a) + \gamma \mathbb{E}[V^\pi(s') \mid s, a]$, we also have

$$\|Q^* - Q^{\hat{\pi}^*}\|_\infty \leq \gamma \|V^* - V^{\hat{\pi}^*}\|_\infty \leq \frac{2\gamma}{1 - \gamma} \Delta_{\delta, N}.$$

A note on “horizon amplification” from our second approach. The crude bound already shows sublinear dependence on the model size, but its dependence on the effective horizon can be pessimistic. From Proposition 2.4,

achieving $\|Q^* - \hat{Q}^*\|_\infty \leq \epsilon$ requires

$$N \gtrsim \frac{1}{(1-\gamma)^4} \cdot \frac{\log(|\mathcal{S}||\mathcal{A}|/\delta)}{\epsilon^2}.$$

If we then translate estimation error into a policy guarantee using the generic Q -to-policy bound (Lemma 1.11), we lose an additional factor $1/(1-\gamma)$: to make the value of $\hat{\pi}^*$ ϵ -close to optimal, the same route suggests

$$N \gtrsim \frac{1}{(1-\gamma)^6} \cdot \frac{\log(|\mathcal{S}||\mathcal{A}|/\delta)}{\epsilon^2}.$$

This extra horizon cost is an artifact of worst-case error propagation, and one of the main goals of the sharper analysis later in the chapter is to avoid it: value estimation and near-optimal planning end up having the same effective-horizon dependence (up to constants and logarithmic factors).

We now provide the proof. We start with a planning-focused comparison lemma, which will be useful throughout the chapter.

Lemma 2.5. (Component-wise bounds) *Let π^* be an optimal policy in M , and let $\hat{\pi}^*$ be an optimal policy in $\widehat{M}$. Then*

$$\begin{aligned} Q^* - \hat{Q}^* &\leq \gamma(I - \gamma\hat{P}^{\pi^*})^{-1}(P - \hat{P})V^*, \\ Q^* - \hat{Q}^* &\geq \gamma(I - \gamma\hat{P}^{\hat{\pi}^*})^{-1}(P - \hat{P})V^*. \end{aligned}$$

Proof. Define the Bellman *evaluation* operator in the empirical MDP $\widehat{M}$ for a deterministic policy π by

$$(\hat{\mathcal{T}}^\pi Q)(s, a) := r(s, a) + \gamma \sum_{s'} \hat{P}(s' | s, a) Q(s', \pi(s')).$$

Its unique fixed point is $\hat{Q}^\pi$.

Let us first prove the upper bound. Since $\hat{\pi}^*$ is optimal in $\widehat{M}$, we have $\hat{Q}^* = \hat{Q}^{\hat{\pi}^*} \geq \hat{Q}^{\pi^*}$, and hence

$$Q^* - \hat{Q}^* \leq Q^* - \hat{Q}^{\pi^*}.$$

Because $\hat{Q}^{\pi^*}$ is the fixed point of $\hat{\mathcal{T}}^{\pi^*}$, we can write the exact identity

$$Q^* - \hat{Q}^{\pi^*} = (I - \gamma\hat{P}^{\pi^*})^{-1}(Q^* - \hat{\mathcal{T}}^{\pi^*} Q^*).$$

Using $Q^* = r + \gamma P V^*$ and the fact that π^* is greedy w.r.t. Q^* (so $Q^*(s, \pi^*(s)) = V^*(s)$), we have

$$(\hat{\mathcal{T}}^{\pi^*} Q^*)(s, a) = r(s, a) + \gamma \mathbb{E}_{s' \sim \hat{P}(\cdot | s, a)}[Q^*(s', \pi^*(s'))] = r(s, a) + \gamma \mathbb{E}_{s' \sim \hat{P}(\cdot | s, a)}[V^*(s')],$$

and therefore

$$Q^* - \hat{\mathcal{T}}^{\pi^*} Q^* = \gamma(P - \hat{P})V^*.$$

Combining yields the first inequality.

We now prove the lower bound. Since $\hat{Q}^* = \hat{Q}^{\hat{\pi}^*}$ is the fixed point of $\hat{\mathcal{T}}^{\hat{\pi}^*}$, we similarly have

$$Q^* - \hat{Q}^* = (I - \gamma\hat{P}^{\hat{\pi}^*})^{-1}(Q^* - \hat{\mathcal{T}}^{\hat{\pi}^*} Q^*).$$

Now,

$$\begin{aligned} (Q^* - \hat{\mathcal{T}}^{\hat{\pi}^*} Q^*)(s, a) &= \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)}[V^*(s')] - \gamma \mathbb{E}_{s' \sim \hat{P}(\cdot | s, a)}[Q^*(s', \hat{\pi}^*(s'))] \\ &\geq \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)}[V^*(s')] - \gamma \mathbb{E}_{s' \sim \hat{P}(\cdot | s, a)}[V^*(s')] \\ &= \gamma((P - \hat{P})V^*)(s, a), \end{aligned}$$

where we used $Q^*(s', \hat{\pi}^*(s')) \leq \max_{a'} Q^*(s', a') = V^*(s')$. Since $(I - \gamma\hat{P}^{\hat{\pi}^*})^{-1}$ has nonnegative entries, multiplying preserves the inequality, which gives the second claim. $\square$

Proof of Proposition 2.4. First, by Lemma 2.2 (applied to π^*) and Lemma 2.3,

$$\|Q^* - \hat{Q}^{\pi^*}\|_\infty = \|Q^{\pi^*} - \hat{Q}^{\pi^*}\|_\infty \leq \frac{\gamma}{1-\gamma} \|(P - \hat{P})V^*\|_\infty.$$

Second, Lemma 2.5 implies that

$$|Q^* - \hat{Q}^*| \leq \gamma \max\left\{(I - \gamma\hat{P}^{\pi^*})^{-1}, (I - \gamma\hat{P}^{\hat{\pi}^*})^{-1}\right\} |(P - \hat{P})V^*|,$$

and therefore (using Lemma 2.3 again),

$$\|Q^* - \hat{Q}^*\|_\infty \leq \frac{\gamma}{1-\gamma} \|(P - \hat{P})V^*\|_\infty.$$

It remains to bound $\|(P - \hat{P})V^*\|_\infty$. Fix (s, a) and let $s'_1, \dots, s'_N \sim P(\cdot | s, a)$ be the N simulator samples used to form $\hat{P}(\cdot | s, a)$. Then $\mathbb{E}_{\hat{P}}[V^*(s')] = \frac{1}{N} \sum_{i=1}^N V^*(s'_i)$ and $\mathbb{E}_P[V^*(s')]$ is the true expectation. Since $0 \leq V^* \leq \frac{1}{1-\gamma}$, Hoeffding's inequality gives

$$\Pr\left(\left|\mathbb{E}_{\hat{P}(\cdot|s,a)}[V^*] - \mathbb{E}_{P(\cdot|s,a)}[V^*]\right| \geq \frac{1}{1-\gamma} \sqrt{\frac{2 \log(2|\mathcal{S}||\mathcal{A}|/\delta)}{N}}\right) \leq \frac{\delta}{|\mathcal{S}||\mathcal{A}|}.$$

Taking a union bound over all (s, a) yields, with probability at least $1 - \delta$,

$$\|(P - \hat{P})V^*\|_\infty \leq \frac{1}{1-\gamma} \sqrt{\frac{2 \log(2|\mathcal{S}||\mathcal{A}|/\delta)}{N}}.$$

Substituting into the previous displays proves both inequalities with the stated $\Delta_{\delta,N}$. $\square$

2.3 Minimax Optimal Sample Complexity (and the Model-Based Approach)

We now state the minimax-optimal sample complexity (up to logarithmic factors) in the generative model setting. The main message is that a simple model-based approach — estimate $\hat{P}$ from samples and then plan in the empirical MDP — achieves the optimal dependence on $|\mathcal{S}||\mathcal{A}|$, ϵ , and $(1 - \gamma)$.

2.3.1 The Discounted Case

Upper bounds. The next theorem packages the main quantitative consequence of the refined analysis from Section 2.4 into a clean sample-complexity statement.

Theorem 2.6 (Minimax upper bound: discounted case). *There exists an absolute constant c such that the following holds. Fix $\delta \in (0, 1)$ and suppose we collect N independent samples from the generative model for each state–action pair, so that the total number of samples is $|\mathcal{S}||\mathcal{A}|N$. Let $\hat{\pi}^*$ and $\hat{Q}^*$ denote an optimal policy and optimal Q -function in the empirical MDP $\hat{M}$.*

- **(Value estimation)** If $\epsilon \leq 1$ and

$$|\mathcal{S}||\mathcal{A}|N \geq \frac{c|\mathcal{S}||\mathcal{A}|}{(1-\gamma)^3} \cdot \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{\epsilon^2},$$

then with probability at least $1 - \delta$,

$$\|\hat{Q}^* - Q^*\|_\infty \leq \epsilon.$$

- **(Near-optimal planning)** If $\epsilon \leq 1/\sqrt{1-\gamma}$ and

$$|\mathcal{S}||\mathcal{A}|N \geq \frac{c|\mathcal{S}||\mathcal{A}|}{(1-\gamma)^3} \cdot \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{\epsilon^2},$$

then with probability at least $1 - \delta$,

$$\|Q^{\hat{\pi}^*} - Q^*\|_\infty \leq \epsilon.$$

We only prove the *value estimation* guarantee (the first bullet) in Theorem 2.6; the *planning* guarantee is more delicate. A black-box route using Lemma 1.11 would yield an additional $1/(1-\gamma)$ loss (the “horizon amplification” phenomenon discussed earlier). The second bullet shows that, with a sharper (variance-sensitive) argument, this amplification can be avoided. See Section 2.5 for further discussion, including results that improve the technical “burn-in” restriction on ϵ using different algorithms.

Lower bounds. We next state a matching minimax lower bound (again, up to logarithmic factors). We say that an estimator $\mathcal{A}$ is (ϵ, δ) -good on an MDP M if, given samples from the generative model, it outputs $\hat{Q}^*$ satisfying $\|\hat{Q}^* - Q^*\|_\infty \leq \epsilon$ with probability at least $1 - \delta$.

Theorem 2.7 (Minimax lower bound: discounted case). *There exist absolute constants $\epsilon_0 \in (0, 1)$, $\delta_0 \in (0, 1)$, and $c > 0$ and a class of MDPs $\mathcal{M}$ such that for all $\epsilon \in (0, \epsilon_0)$ and $\delta \in (0, \delta_0)$, any algorithm $\mathcal{A}$ that is (ϵ, δ) -good on every $M \in \mathcal{M}$ must use at least*

$$\# \text{ samples from generative model} \geq \frac{c|\mathcal{S}||\mathcal{A}|}{(1-\gamma)^3} \cdot \frac{\log(c/\delta)}{\epsilon^2}.$$

In other words, the model-based approach is minimax-optimal in its dependence on $|\mathcal{S}||\mathcal{A}|$, $(1-\gamma)$, and ϵ (up to logarithmic factors).

Interpreting the horizon dependence. It is useful to calibrate the target accuracy in discounted problems. Since rewards are bounded in $[0, 1]$, we have $\|Q^*\|_\infty \leq \frac{1}{1-\gamma}$, so an additive error of size $\frac{\epsilon}{1-\gamma}$ corresponds to *relative* accuracy on the scale of ϵ . Equivalently, if we define a normalized value function $\bar{Q}^\pi := (1-\gamma)Q^\pi$, then $\|\bar{Q}^\pi\|_\infty \leq 1$ and asking for additive error ϵ in $\bar{Q}$ is the same as asking for additive error $\epsilon/(1-\gamma)$ in Q .

Plugging this normalization into Theorem 2.6 (and ignoring logarithmic factors and the mild technical restrictions on ϵ), the minimax sample complexity for constant-accuracy estimation of $\bar{Q}^*$ scales like

$$\# \text{ samples} \approx \frac{|\mathcal{S}||\mathcal{A}|}{1-\gamma} \cdot \frac{1}{\epsilon^2}.$$

In this sense, after normalization, the dependence on the effective horizon is essentially linear: the extra powers of $(1-\gamma)^{-1}$ in the unnormalized bounds are largely accounting for the fact that Q^* itself grows like $(1-\gamma)^{-1}$.

2.3.2 Finite-Horizon Setting

Recall the finite-horizon (time-dependent) MDP model from Section 1.2, with horizon H and transition kernels $\{P_h\}_{h=0}^{H-1}$. In the generative-model setting, we can query any triple (s, a, h) and obtain an independent sample $s' \sim P_h(\cdot | s, a)$ (and the reward $r_h(s, a)$, which we treat as deterministic for simplicity).

We consider the natural plug-in model-based estimator: for each (s, a, h) we draw N independent samples and form the empirical transition kernel $\hat{P}_h(\cdot | s, a)$. The total number of samples is therefore

$$\# \text{ samples from generative model} = H|\mathcal{S}||\mathcal{A}|N.$$

We state the resulting performance guarantees without proof.

Upper bounds. The following theorem gives a high-probability error bound for planning in the empirical MDP.

Theorem 2.8 (Model-based planning: finite horizon). *There exists an absolute constant c such that the following holds. For any $\delta \in (0, 1)$, with probability at least $1 - \delta$,*

- (Value estimation)

$$\|Q_0^* - \hat{Q}_0^*\|_\infty \leq cH \sqrt{\frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}} + cH \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}.$$

- (Sub-optimality) letting $\hat{\pi}^*$ be an optimal policy in the empirical MDP,

$$\|Q_0^* - Q_0^{\hat{\pi}^*}\|_\infty \leq cH \sqrt{\frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}} + cH \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}.$$

Equivalently, ignoring lower-order terms, achieving $\|Q_0^* - \hat{Q}_0^*\|_\infty \leq \epsilon$ (or $\|Q_0^* - Q_0^{\hat{\pi}^*}\|_\infty \leq \epsilon$) is guaranteed once

$$N \gtrsim \frac{H^2}{\epsilon^2} \log\left(\frac{|\mathcal{S}||\mathcal{A}|}{\delta}\right), \quad \text{or equivalently} \quad \# \text{ samples from generative model} \gtrsim \frac{H^3 |\mathcal{S}||\mathcal{A}|}{\epsilon^2} \log\left(\frac{|\mathcal{S}||\mathcal{A}|}{\delta}\right).$$

The dependence on H looks different from the discounted case, but it is not directly comparable without specifying how one maps γ to an effective horizon. One rough correspondence is $H \asymp \frac{1}{1-\gamma}$; under this heuristic, the leading-order scalings match up to constants and logarithmic factors.

Lower bounds. In the same minimax sense as Theorem ??, the above model-based rate is optimal (up to constant and logarithmic factors) for finite-horizon MDPs under a generative model. We omit the proof.

2.4 Analysis

We now prove the *value-estimation* guarantee in Theorem ?? (i.e. the first bullet). For convenience, we restate it here.

Theorem 2.9 (Value estimation; restatement of Theorem ??). *Fix $\delta \in (0, 1)$. For an appropriately chosen absolute constant c , with probability at least $1 - \delta$,*

$$\|Q^* - \hat{Q}^*\|_\infty \leq \gamma \sqrt{\frac{c}{(1-\gamma)^3} \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}} + \frac{c\gamma}{(1-\gamma)^3} \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}.$$

2.4.1 Variance lemmas

The sharper dependence on $(1-\gamma)$ comes from replacing a worst-case (Hoeffding-style) deviation bound by a variance-sensitive one (Bernstein), and then exploiting a Bellman-type recursion for variances.

For a real-valued function f and distribution $\mathcal{D}$, define

$$\text{Var}_{\mathcal{D}}(f) := \mathbb{E}_{x \sim \mathcal{D}}[f(x)^2] - \left(\mathbb{E}_{x \sim \mathcal{D}}[f(x)]\right)^2.$$

For a vector $V \in \mathbb{R}^{|\mathcal{S}|}$, define $\text{Var}_P(V) \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$ componentwise by

$$\text{Var}_P(V)(s, a) := \text{Var}_{P(\cdot|s,a)}(V) = \mathbb{E}_{s' \sim P(\cdot|s,a)}[V(s')^2] - \left(\mathbb{E}_{s' \sim P(\cdot|s,a)}[V(s')]\right)^2.$$

Equivalently (with squares understood componentwise),

$$\text{Var}_P(V) = P(V^2) - (PV)^2.$$

A Bernstein deviation bound. We will repeatedly apply Bernstein's inequality to the empirical estimate $\hat{P}(\cdot \mid s, a)$.

Lemma 2.10. *Let $\delta \in (0, 1)$. With probability at least $1 - \delta$, the following holds simultaneously for all (s, a) :*

$$|(P - \hat{P})V^*| \leq \sqrt{\frac{2 \log(2|\mathcal{S}||\mathcal{A}|/\delta)}{N}} \sqrt{\text{Var}_P(V^*)} + \frac{1}{1 - \gamma} \frac{2 \log(2|\mathcal{S}||\mathcal{A}|/\delta)}{3N} \mathbb{1}.$$

Here the absolute value and inequality are componentwise, and $\mathbb{1}$ denotes the all-ones vector in $\mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$.

Proof. Fix (s, a) . Apply Bernstein's inequality to the i.i.d. random variables $V^*(s'_1), \dots, V^*(s'_N)$ with $s'_i \sim P(\cdot \mid s, a)$. Since $0 \leq V^* \leq \frac{1}{1 - \gamma}$, the range is at most $\frac{1}{1 - \gamma}$, and the variance term is exactly $\text{Var}_{P(\cdot \mid s, a)}(V^*)$. A union bound over $|\mathcal{S}||\mathcal{A}|$ state-action pairs yields the stated form. $\square$

The remaining work is to control how the (square-root) variance term propagates through the inverse Bellman operator, e.g. $\|(I - \gamma \hat{P}^{\pi^*})^{-1} \sqrt{\text{Var}_P(V^*)}\|_\infty$.

Variance of the discounted return. For any MDP M and policy π , define $\Sigma_M^\pi(s, a)$ as the conditional variance of the discounted return:

$$\Sigma_M^\pi(s, a) := \mathbb{E} \left[\left(\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t) - Q_M^\pi(s, a) \right)^2 \middle| s_0 = s, a_0 = a \right],$$

where the expectation is over trajectories generated by π in M . Because we assume the one-step reward $r(s, a)$ is deterministic, all randomness in the return comes from future states, hence

$$\|\Sigma_M^\pi\|_\infty \leq \left(\frac{\gamma}{1 - \gamma} \right)^2 = \frac{\gamma^2}{(1 - \gamma)^2}.$$

The next lemma is the variance analogue of Bellman consistency.

Lemma 2.11 (Bellman consistency of Σ). *For any MDP M and policy π ,*

$$\Sigma_M^\pi = \gamma^2 \text{Var}_P(V_M^\pi) + \gamma^2 P^\pi \Sigma_M^\pi, \quad (2.1)$$

where P is the transition model of M .

The proof is left as an exercise to the reader (it follows by writing the return as $r(s, a) + \gamma(\text{future return})$ and applying the law of total variance).

We now prove a bound that turns square-root variances into the desired $(1 - \gamma)^{-3/2}$ scaling.

Lemma 2.12. (Weighted sum of deviations) *For any policy π and MDP M ,*

$$\left\| (I - \gamma P^\pi)^{-1} \sqrt{\text{Var}_P(V_M^\pi)} \right\|_\infty \leq \sqrt{\frac{2}{(1 - \gamma)^3}},$$

where P is the transition model of M .

Proof. Let $v := \text{Var}_P(V_M^\pi) \in \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$, which is entrywise nonnegative. Observe that $(1 - \gamma)(I - \gamma P^\pi)^{-1}$ has nonnegative entries and each row sums to 1, so each row is a probability distribution over next state-action pairs.

Applying Jensen's inequality row-by-row (using concavity of $\sqrt{\cdot}$) gives

$$\|(I - \gamma P^\pi)^{-1} \sqrt{v}\|_\infty = \frac{1}{1-\gamma} \|(1-\gamma)(I - \gamma P^\pi)^{-1} \sqrt{v}\|_\infty \leq \sqrt{\left\| \frac{1}{1-\gamma} (I - \gamma P^\pi)^{-1} v \right\|_\infty}.$$

Next we relate $(I - \gamma P^\pi)^{-1}$ to $(I - \gamma^2 P^\pi)^{-1}$: for any entrywise nonnegative u ,

$$\|(I - \gamma P^\pi)^{-1} u\|_\infty \leq 2 \|(I - \gamma^2 P^\pi)^{-1} u\|_\infty.$$

(We verify this inequality at the end of the proof.) Applying this with $u = v$ yields

$$\left\| \frac{1}{1-\gamma} (I - \gamma P^\pi)^{-1} v \right\|_\infty \leq \left\| \frac{2}{1-\gamma} (I - \gamma^2 P^\pi)^{-1} v \right\|_\infty.$$

Finally, using the Bellman consistency equation (2.1) we have $\Sigma_M^\pi = \gamma^2 (I - \gamma^2 P^\pi)^{-1} v$, hence

$$(I - \gamma^2 P^\pi)^{-1} v = \frac{1}{\gamma^2} \Sigma_M^\pi, \quad \text{so} \quad \left\| \frac{2}{1-\gamma} (I - \gamma^2 P^\pi)^{-1} v \right\|_\infty \leq \frac{2}{1-\gamma} \cdot \frac{1}{\gamma^2} \|\Sigma_M^\pi\|_\infty \leq \frac{2}{(1-\gamma)^3}.$$

Taking square roots completes the proof.

Proof of $\|(I - \gamma P^\pi)^{-1} u\|_\infty \leq 2 \|(I - \gamma^2 P^\pi)^{-1} u\|_\infty$. Let $w = (I - \gamma^2 P^\pi)^{-1} u$. Then

$$(I - \gamma P^\pi)^{-1} u = (I - \gamma P^\pi)^{-1} (I - \gamma^2 P^\pi) w = (I - \gamma P^\pi)^{-1} ((1-\gamma)I + \gamma(I - \gamma P^\pi)) w = (1-\gamma)(I - \gamma P^\pi)^{-1} w + \gamma w.$$

Taking $\|\cdot\|_\infty$ norms and using Lemma 2.3 on the first term gives

$$\|(I - \gamma P^\pi)^{-1} u\|_\infty \leq (1-\gamma) \cdot \frac{1}{1-\gamma} \|w\|_\infty + \gamma \|w\|_\infty \leq 2 \|w\|_\infty = 2 \|(I - \gamma^2 P^\pi)^{-1} u\|_\infty,$$

as claimed. $\square$

2.4.2 Completing the proof

The next lemma relates the (unknown) one-step variance under P to an empirical variance under $\hat{P}$, up to lower-order estimation terms.

Lemma 2.13. Fix $\delta \in (0, 1)$. With probability at least $1 - \delta$, we have the componentwise bounds

$$\text{Var}_P(V^*) \leq 2 \text{Var}_{\hat{P}}(\hat{V}^{\pi^*}) + \Delta'_{\delta, N} \mathbf{1},$$

$$\text{Var}_P(V^*) \leq 2 \text{Var}_{\hat{P}}(\hat{V}^*) + \Delta'_{\delta, N} \mathbf{1},$$

where

$$\Delta'_{\delta, N} := \frac{1}{(1-\gamma)^2} \sqrt{\frac{18 \log(6|\mathcal{S}||\mathcal{A}|/\delta)}{N}} + \frac{1}{(1-\gamma)^4} \frac{4 \log(6|\mathcal{S}||\mathcal{A}|/\delta)}{N}.$$

Proof. We work componentwise in (s, a) , and write $(PV^*)(s, a) = \mathbb{E}_{s' \sim P(\cdot|s, a)}[V^*(s')]$. By definition,

$$\begin{aligned} \text{Var}_P(V^*) &= P((V^*)^2) - (PV^*)^2 \\ &= \hat{P}((V^*)^2) - (\hat{P}V^*)^2 + (P - \hat{P})(V^*)^2 - ((PV^*)^2 - (\hat{P}V^*)^2) \\ &= \text{Var}_{\hat{P}}(V^*) + (P - \hat{P})(V^*)^2 - ((PV^*)^2 - (\hat{P}V^*)^2). \end{aligned}$$

We bound the last two terms via Hoeffding + a union bound over (s, a) .

We now handle term 1: $(P - \hat{P})(V^*)^2$. Since $0 \leq V^* \leq \frac{1}{1-\gamma}$, we have $0 \leq (V^*)^2 \leq \frac{1}{(1-\gamma)^2}$. Thus with probability at least $1 - \delta/3$,

$$\|(P - \hat{P})(V^*)^2\|_\infty \leq \frac{1}{(1-\gamma)^2} \sqrt{\frac{2 \log(6|\mathcal{S}||\mathcal{A}|/\delta)}{N}}.$$

Next, we handle term 2: $(PV^*)^2 - (\hat{P}V^*)^2$. Using $(x^2 - y^2) = (x + y)(x - y)$ componentwise,

$$\begin{aligned} \|(PV^*)^2 - (\hat{P}V^*)^2\|_\infty &\leq \|PV^* + \hat{P}V^*\|_\infty \cdot \|PV^* - \hat{P}V^*\|_\infty \\ &\leq \frac{2}{1-\gamma} \cdot \|(P - \hat{P})V^*\|_\infty. \end{aligned}$$

Again $0 \leq V^* \leq \frac{1}{1-\gamma}$, so by Hoeffding + union bound, with probability at least $1 - \delta/3$,

$$\|(P - \hat{P})V^*\|_\infty \leq \frac{1}{1-\gamma} \sqrt{\frac{2 \log(6|\mathcal{S}||\mathcal{A}|/\delta)}{N}}.$$

Combining gives, with probability at least $1 - \delta/3$,

$$\|(PV^*)^2 - (\hat{P}V^*)^2\|_\infty \leq \frac{2}{(1-\gamma)^2} \sqrt{\frac{2 \log(6|\mathcal{S}||\mathcal{A}|/\delta)}{N}}.$$

We now handle term 3: $\text{Var}_{\hat{P}}(V^*)$. We compare $\text{Var}_{\hat{P}}(V^*)$ to an empirical variance of a nearby value function. Using $\text{Var}(X + Y) \leq 2 \text{Var}(X) + 2 \text{Var}(Y)$ and $\text{Var}_{\hat{P}}(f) \leq \|f\|_\infty^2$,

$$\begin{aligned} \text{Var}_{\hat{P}}(V^*) &= \text{Var}_{\hat{P}}((V^* - \hat{V}^{\pi^*}) + \hat{V}^{\pi^*}) \\ &\leq 2 \text{Var}_{\hat{P}}(V^* - \hat{V}^{\pi^*}) + 2 \text{Var}_{\hat{P}}(\hat{V}^{\pi^*}) \\ &\leq 2\|V^* - \hat{V}^{\pi^*}\|_\infty^2 + 2 \text{Var}_{\hat{P}}(\hat{V}^{\pi^*}). \end{aligned}$$

Since π^* is optimal in M , we have $V^*(s) = Q^*(s, \pi^*(s))$ and $\hat{V}^{\pi^*}(s) = \hat{Q}^{\pi^*}(s, \pi^*(s))$, hence $\|V^* - \hat{V}^{\pi^*}\|_\infty \leq \|Q^* - \hat{Q}^{\pi^*}\|_\infty$. Applying Proposition 2.4 (with failure probability $\delta/3$) gives

$$\|V^* - \hat{V}^{\pi^*}\|_\infty \leq \Delta_{\delta/3, N} \Rightarrow 2\|V^* - \hat{V}^{\pi^*}\|_\infty^2 \leq \frac{4}{(1-\gamma)^4} \frac{\log(6|\mathcal{S}||\mathcal{A}|/\delta)}{N},$$

where we used $\gamma \leq 1$ and the definition of $\Delta_{\delta, N}$.

Putting it together. With probability at least $1 - \delta$ (union bound over the three events),

$$\text{Var}_P(V^*) \leq 2 \text{Var}_{\hat{P}}(\hat{V}^{\pi^*}) + \left(\frac{1}{(1-\gamma)^2} \sqrt{\frac{18 \log(6|\mathcal{S}||\mathcal{A}|/\delta)}{N}} + \frac{1}{(1-\gamma)^4} \frac{4 \log(6|\mathcal{S}||\mathcal{A}|/\delta)}{N} \right) \mathbf{1},$$

which is the first claim.

For the second claim, repeat the same argument but decompose $\text{Var}_{\hat{P}}(V^*) = \text{Var}_{\hat{P}}((V^* - \hat{V}^*) + \hat{V}^*)$ and use $\|V^* - \hat{V}^*\|_\infty \leq \|Q^* - \hat{Q}^*\|_\infty \leq \Delta_{\delta/3, N}$. $\square$

Combining the Bernstein deviation bound with the variance comparison above yields a variance-sensitive control of $(P - \hat{P})V^*$.

Corollary 2.14. Fix $\delta \in (0, 1)$. With probability at least $1 - \delta$, we have the componentwise bounds

$$\begin{aligned} |(P - \hat{P})V^*| &\leq c\sqrt{\frac{\text{Var}_{\hat{P}}(\hat{V}^{\pi^*}) \log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}} + \Delta''_{\delta,N} \mathbf{1}, \\ |(P - \hat{P})V^*| &\leq c\sqrt{\frac{\text{Var}_{\hat{P}}(\hat{V}^*) \log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}} + \Delta''_{\delta,N} \mathbf{1}, \end{aligned}$$

where

$$\Delta''_{\delta,N} := c \frac{1}{1-\gamma} \left(\frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N} \right)^{3/4} + \frac{c}{(1-\gamma)^2} \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N},$$

and c is an absolute constant.

Proof. Apply Lemma 2.10 and substitute the upper bound on $\text{Var}_P(V^*)$ from Lemma 2.13. Then use $\sqrt{a+b} \leq \sqrt{a} + \sqrt{b}$ componentwise to separate the empirical-variance term from $\Delta'_{\delta,N}$. The term involving $\sqrt{\Delta'_{\delta,N}}$ contributes the $(\log/N)^{3/4}$ and $(\log/N)$ pieces, and the additive Bernstein remainder $\frac{1}{1-\gamma} \frac{\log(\cdot)}{N} \mathbf{1}$ is absorbed into the displayed $\Delta''_{\delta,N}$ by adjusting constants. $\square$

Proof of Theorem ??. We bound the two sides in Lemma 2.5.

We first handle the upper deviation. Using the first inequality in Lemma 2.5, monotonicity of $(I - \gamma\hat{P}^{\pi^*})^{-1}$, and Corollary 2.14 (first line), we obtain

$$\begin{aligned} \|Q^* - \hat{Q}^*\|_\infty &\leq \gamma \left\| (I - \gamma\hat{P}^{\pi^*})^{-1} |(P - \hat{P})V^*| \right\|_\infty \\ &\leq c\gamma \sqrt{\frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}} \left\| (I - \gamma\hat{P}^{\pi^*})^{-1} \sqrt{\text{Var}_{\hat{P}}(\hat{V}^{\pi^*})} \right\|_\infty + \gamma \Delta''_{\delta,N} \left\| (I - \gamma\hat{P}^{\pi^*})^{-1} \mathbf{1} \right\|_\infty \\ &\leq c\gamma \sqrt{\frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}} \left\| (I - \gamma\hat{P}^{\pi^*})^{-1} \sqrt{\text{Var}_{\hat{P}}(\hat{V}^{\pi^*})} \right\|_\infty \\ &\quad + \frac{c\gamma}{(1-\gamma)^2} \left(\frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N} \right)^{3/4} + \frac{c\gamma}{(1-\gamma)^3} \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}, \end{aligned}$$

where we used $\|(I - \gamma\hat{P}^{\pi^*})^{-1} \mathbf{1}\|_\infty \leq \frac{1}{1-\gamma}$.

Now apply Lemma 2.12 to $\hat{M}$ and policy π^* (so $P = \hat{P}$ and $V_M^\pi = \hat{V}^{\pi^*}$) to get

$$\left\| (I - \gamma\hat{P}^{\pi^*})^{-1} \sqrt{\text{Var}_{\hat{P}}(\hat{V}^{\pi^*})} \right\|_\infty \leq \sqrt{\frac{2}{(1-\gamma)^3}}.$$

Substituting yields

$$\|Q^* - \hat{Q}^*\|_\infty \leq c\gamma \sqrt{\frac{2}{(1-\gamma)^3}} \sqrt{\frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}} + \frac{c\gamma}{(1-\gamma)^2} \left(\frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N} \right)^{3/4} + \frac{c\gamma}{(1-\gamma)^3} \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}.$$

The middle term can be absorbed into the other two terms using $2ab \leq a^2 + b^2$. Indeed, letting $L := \frac{\log(c|\mathcal{S}||\mathcal{A}|/\delta)}{N}$,

$$\frac{1}{(1-\gamma)^2} L^{3/4} = \left(\frac{1}{(1-\gamma)^{3/2}} L^{1/2} \right) \left(\frac{1}{(1-\gamma)^{1/2}} L^{1/4} \right) \leq \frac{1}{(1-\gamma)^3} L + \frac{1}{1-\gamma} L^{1/2} \leq \frac{1}{(1-\gamma)^3} L + \frac{1}{(1-\gamma)^{3/2}} L^{1/2},$$

and adjusting constants gives the claimed form.

We now handle the lower deviation. Repeat the same argument using the second inequality in Lemma 2.5 (i.e. with $\hat{\pi}^*$ in place of π^*), which yields an identical bound for $\|\hat{Q}^* - Q^*\|_\infty$. Combining the two sides gives the stated ℓ_∞ error bound (with a possibly different absolute constant c). $\square$

2.5 Bibliographic Remarks and Further Reading

The generative model framework (also known as a simulator oracle) was introduced by Kearns and Singh [1999], who established that model-based and model-free methods have comparable sample complexity up to horizon and logarithmic factors. Kakade [2003] provided improved rates analogous to the “crude” bounds presented in Proposition 2.4.

The sharp value estimation bound (the first claim in Theorem 2.6) is due to Azar et al. [2013]; the analysis in Section 2.4 largely follows their technique. Regarding the sub-optimality of the learned policy $\hat{\pi}^*$, a naive analysis suggests an amplification of the error by $(1 - \gamma)^{-1}$. Sidford et al. [2018] provided the first proof that this amplification can be avoided, achieving the optimal rate using a variance-reduced value iteration algorithm. Subsequently, Agarwal et al. [2020c] showed that the naive model-based approach (the “plug-in” estimator) is also sufficient to achieve this optimal rate (the second claim in Theorem 2.6). The minimax lower bound (Theorem 2.7) is due to Azar et al. [2013].

We also note that the sub-optimality bounds presented here require ϵ to be sufficiently small (roughly $\epsilon \lesssim 1/\sqrt{1 - \gamma}$). Li et al. [2020] showed that the optimal rate is achievable for the full range of meaningful accuracy (up to $\epsilon \approx 1/(1 - \gamma)$) using a perturbed model-based algorithm. It remains an open question whether the standard (unperturbed) model-based approach achieves this optimal non-asymptotic behavior for large ϵ .

Finally, this chapter presented optimal sample complexity results for the finite-horizon setting (Section 2.3.2) without proof. These results follow from the line of reasoning in Azar et al. [2013], with the added simplification that the sub-optimality analysis is simpler in the finite-horizon setting with time-dependent transition matrices (see, e.g., Yin et al. [2021]).

Chapter 3

RL with Linear Features: When Does It Work, and When Does It Fail?

Up to now we have focused on tabular Markov decision processes, where both sample complexity and computation scale polynomially with $|\mathcal{S}|$ and $|\mathcal{A}|$. In many problems of interest, however, the state and action spaces are so large that tabular methods are not viable. A standard response is to introduce a feature map

$$\phi : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}^d$$

and to approximate value functions using linear predictors $f_\theta(s, a) = \theta^\top \phi(s, a)$.

A natural hope is that the relevant complexity parameter becomes d rather than $|\mathcal{S}||\mathcal{A}|$. This chapter asks a single organizing question:

When do linear features actually buy you poly(d) sample complexity — and when do they fundamentally not?

The answer is subtle. On the positive side, there are structural conditions under which linear methods reduce reinforcement learning to a sequence of well-conditioned regression problems, yielding $\text{poly}(d, H, 1/\epsilon)$ guarantees without explicit dependence on $|\mathcal{S}|$ or $|\mathcal{A}|$. On the negative side, several seemingly natural “linear realizability” assumptions are *not* enough: even with excellent coverage, and even when an algorithm is given the feature map as input, the sample complexity can be exponential in the horizon.

The chapter is organized around a short ladder of assumptions. We first introduce these assumptions and their relationships at a high level. We then present a sharp positive result under a completeness condition (Least-Squares Value Iteration with a well-conditioned design), followed by information-theoretic lower bounds showing that weaker notions of realizability do not suffice.

Why this is subtle (and why realizability feels tempting). Since most of our discussion so far has focused on the discounted setting, it is worth briefly recalling the finite-horizon dynamic programming picture. For any function $f : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$, the stage- h optimal Bellman operator is

$$(\mathcal{T}_h f)(s, a) := r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot|s, a)} \left[\max_{a' \in \mathcal{A}} f(s', a') \right].$$

The optimal Q -functions satisfy $Q_H^* \equiv 0$ and the backward recursion $Q_h^* = \mathcal{T}_h Q_{h+1}^*$ for $h = H - 1, \dots, 0$.

This recursion suggests a very natural hope. If we can produce accurate estimates $\hat{Q}_{h+1} \approx Q_{h+1}^*$, then we might plug $\hat{Q}_{h+1}$ into the backup to form targets $\mathcal{T}_h \hat{Q}_{h+1}$, fit $\hat{Q}_h$ by regression, and expect errors to propagate in a controlled way across stages. From this perspective it is tempting to believe that a simple *realizability* assumption—for example, $Q_h^* \in \mathcal{F}$ for all h —should already be enough to obtain $\text{poly}(d)$ sample complexity.

The difficulty is that dynamic programming is not a single regression problem but a *composition* of backups: the algorithm repeatedly forms new regression targets using its *own* current estimates. Thus, what matters is not only whether Q^* lies in the hypothesis class, but whether the sequence of targets generated along the way remains learnable from the available data. The assumption ladder introduced next is a way of making precise which structural conditions guarantee this benign behavior—and which apparently natural linear conditions do not.

3.1 Setup and an Assumption Ladder

We work with a fixed feature map $\phi : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}^d$. For a parameter vector $\theta \in \mathbb{R}^d$, define the associated linear function $f_\theta(s, a) = \theta^\top \phi(s, a)$, and let

$$\mathcal{F} := \{f_\theta : \theta \in \mathbb{R}^d\}$$

denote the corresponding linear function class.

There are multiple distinct ways that “linear features” can enter reinforcement learning. The following assumptions form a useful ladder: as we move down the list, the assumptions become stronger and increasingly algorithmically useful.

(A) Agnostic linear approximation (no realizability). The weakest perspective is purely approximation-based: we do *not* assume that any relevant value function is linear. Instead, we measure the best approximation error of $\mathcal{F}$ to some target (e.g. Q^* , or the iterates of a fitted value iteration procedure) under a chosen norm or data distribution. This is the analogue of agnostic supervised learning. We defer this viewpoint—and its attendant distribution-shift / concentrability issues—to the chapter on fitted value iteration. However, this chapter alone shows how the agnostic viewpoint alone can lead to subexponential results (in the relevant parameters).

(B) Linear Q^* realizability. A common structural assumption is that the *optimal* action-value function is linear: for each stage h there exists $\theta_h^* \in \mathbb{R}^d$ such that

$$Q_h^*(s, a) = (\theta_h^*)^\top \phi(s, a) \quad \forall (s, a).$$

This is the most direct analogue of realizable linear regression. A tempting intuition is that this should allow $\text{poly}(d)$ learning. We will see that this intuition is false in a strong information-theoretic sense.

(C) All-policies linear realizability. A stronger assumption requires linear realizability not just for Q^* , but for *every* policy: for each π and each stage h , there exists θ_h^π such that

$$Q_h^\pi(s, a) = (\theta_h^\pi)^\top \phi(s, a) \quad \forall (s, a).$$

This assumption is substantially stronger than (B). Nevertheless, it still does *not* guarantee sample-efficient offline policy evaluation: even with extremely strong feature coverage, any estimator can require exponentially many samples.

(D) Linear Bellman completeness (a closure property). The most algorithmically useful assumption in this chapter is a *closure* condition: roughly, applying the Bellman optimality operator to a linear function yields another linear function (with respect to the same feature map). One convenient way to state this is: for each stage h and each $\theta \in \mathbb{R}^d$, there exists $w \in \mathbb{R}^d$ such that the function

$$(s, a) \mapsto r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} \left[\max_{a'} \theta^\top \phi(s', a') \right]$$

is exactly $w^\top \phi(s, a)$ for all (s, a) . Equivalently, letting $\mathcal{F} := \{(s, a) \mapsto w^\top \phi(s, a) \mid w \in \mathbb{R}^d\}$ denote the class of functions linear in ϕ , the Bellman completeness property can be written as

$$f \in \mathcal{F} \implies \mathcal{T}_h f \in \mathcal{F} \quad \text{for each } h \in [H], \quad (3.1)$$

where $\mathcal{T}_h$ is the stage- h Bellman optimality operator. This assumption turns dynamic programming into a sequence of regression problems, and it is what underlies the positive results in this chapter.

Relationships. A few simple implications are worth keeping in mind. First, linear Bellman completeness immediately implies that rewards are linear in ϕ (take $\theta = 0$ above). It also implies linear Q^* realizability (by backward induction / value iteration carried out within $\mathcal{F}$). In contrast, (C) and (D) are not comparable in general: (C) asserts realizability for *all* policies but does not impose closure under the *optimality* operator, while (D) enforces closure under the optimality operator but does not a priori assert that Q^π is linear for every policy π .

A remark on strength. Bellman completeness should be read as a structural condition on the MDP itself (via the transition kernel and reward), not merely a property of Q^* . We will give concrete examples of model classes satisfying Bellman completeness (e.g. linear MDPs and related low-complexity transition models) later in Chapters 7 and 8, once our algorithmic guarantees are on the table.

With our ladder in place, the remainder of the chapter answers our organizing question by pairing a sharp positive result under (D) with lower bounds showing that (B) and (C) can fail dramatically.

3.2 Positive results under Bellman completeness

This section gives the affirmative path for linear features: under the right structural condition, dynamic programming reduces to a sequence of (supervised) regression problems, yielding sample complexity polynomial in the feature dimension. We state the algorithm in a way that will be reused in both the generative-model and offline settings; the difference will be only in how the stage-wise datasets are obtained.

3.2.1 Setup and data model

Throughout this section we assume the Bellman completeness condition stated earlier (Section 3.1).

We work in the finite-horizon setting with stages $h \in [H] := \{0, 1, \dots, H-1\}$. An MDP is specified by a state space $\mathcal{S}$, an action space $\mathcal{A}$, an initial distribution μ over $\mathcal{S}$, stage-dependent transition kernels $\{P_h(\cdot | s, a)\}_{h=0}^{H-1}$, and stage-dependent rewards $\{r_h(s, a)\}_{h=0}^{H-1}$. Throughout we assume rewards are bounded, $r_h(s, a) \in [0, 1]$.¹

We are given a feature map $\phi : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}^d$, and we consider the linear function class

$$\mathcal{F} := \{f_w : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R} \mid f_w(s, a) = w^\top \phi(s, a), w \in \mathbb{R}^d\}.$$

¹ Allowing stochastic rewards with bounded support is routine; to keep notation light we write rewards as deterministic.

Algorithm 1 Least-Squares Value Iteration (LSVI)

```
1: Input: datasets  $D_0, \dots, D_{H-1}$ , feature map  $\phi$ 
2: Initialize  $\hat{V}_H(s) \leftarrow 0$  for all  $s \in \mathcal{S}$ 
3: for  $h = H - 1, H - 2, \dots, 0$  do
4:    $\hat{\theta}_h \in \arg \min_{\theta \in \mathbb{R}^d} \sum_{(s,a,r,s') \in D_h} \left( \theta^\top \phi(s,a) - r - \hat{V}_{h+1}(s') \right)^2$ 
5:   Define  $\hat{Q}_h(s,a) \leftarrow \hat{\theta}_h^\top \phi(s,a)$  for all  $(s,a)$ 
6:   Define  $\hat{V}_h(s) \leftarrow \max_{a \in \mathcal{A}} \hat{Q}_h(s,a)$  for all  $s$ 
7: end for
8: Return: greedy policy  $\hat{\pi} = \{\hat{\pi}_h\}_{h=0}^{H-1}$  where  $\hat{\pi}_h(s) \in \arg \max_{a \in \mathcal{A}} \hat{Q}_h(s,a)$ 
```

(As usual, one can rescale features so that $\sup_{s,a} \|\phi(s,a)\|_2 \leq 1$; we will be explicit about boundedness assumptions when they matter.)

Stage-wise datasets (offline view). To keep the algorithm reusable, we phrase everything in terms of per-stage datasets. For each $h \in [H]$, let

$$D_h = \{(s_i, a_i, r_i, s'_i)\}_{i=1}^N$$

be a dataset of N transitions at stage h , where each $s'_i \sim P_h(\cdot \mid s_i, a_i)$ is sampled independently conditional on (s_i, a_i) and $r_i = r_h(s_i, a_i)$. In the generative-model setting we will *construct* these datasets; in the offline setting the datasets are given and we will impose an explicit coverage condition.

Bellman operators. Recall from Section 1.2, that for a function $f : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$, we have that our stage- h *optimal* Bellman operator $\mathcal{T}_h$ is defined by

$$(\mathcal{T}_h f)(s,a) := r_h(s,a) + \mathbb{E}_{s' \sim P_h(\cdot \mid s,a)} \left[\max_{a' \in \mathcal{A}} f(s', a') \right].$$

In the finite-horizon problem, the optimal Q -functions satisfy the recursion $Q_H^* \equiv 0$ and $Q_h^* = \mathcal{T}_h Q_{h+1}^*$ for $h = H - 1, \dots, 0$.

The remainder of Section 3.2 shows that, under Bellman completeness, ordinary least squares can drive Bellman residuals uniformly small, which in turn yields a near-optimal greedy policy.

3.2.2 Algorithm: Least-Squares Value Iteration (LSVI)

LSVI runs a backward dynamic program, where each Bellman backup is implemented by a least-squares regression onto the feature class $\mathcal{F}$.

Remark. If the empirical covariance at a stage is singular, one can take a minimum-norm solution (or add a small ridge). In the settings we analyze (D-optimal sampling from a generative model, or explicit coverage assumptions offline), the design is well-conditioned and this technicality is inessential.

3.2.3 Main guarantee: LSVI with a generative model

We now prove the main positive result under Bellman completeness in the generative-model setting. The proof uses three ingredients: (i) a geometric sampling lemma (D-optimal design), (ii) a uniform generalization bound for ordinary

least squares (Appendix), and (iii) a standard approximate dynamic programming lemma converting small Bellman residuals into near-optimality.

Tool lemma: D-optimal design

Let $\Phi := \{\phi(s, a) : (s, a) \in \mathcal{S} \times \mathcal{A}\} \subset \mathbb{R}^d$ denote the set of feature vectors. We assume Φ is bounded and full-dimensional (otherwise we may restrict to $\text{span}(\Phi)$).

Lemma 3.1 (D-optimal design). *There exists a distribution ρ supported on at most $d(d+1)/2$ state–action pairs such that, letting*

$$\Sigma := \mathbb{E}_{(s,a) \sim \rho} [\phi(s, a) \phi(s, a)^\top],$$

we have $\Sigma \succ 0$ and

$$\sup_{(s,a) \in \mathcal{S} \times \mathcal{A}} \phi(s, a)^\top \Sigma^{-1} \phi(s, a) \leq d.$$

One convenient characterization of ρ is as a maximizer of a log-determinant objective:

$$\rho \in \underset{\nu \in \Delta(\mathcal{S} \times \mathcal{A})}{\operatorname{argmax}} \ln \det(\mathbb{E}_{(s,a) \sim \nu} [\phi(s, a) \phi(s, a)^\top]), \quad (3.2)$$

(which is the Kiefer–Wolfowitz Theorem). Equivalently, the ellipsoid $\mathcal{E} = \{v : \|v\|_{\Sigma^{-1}}^2 \leq d\}$ is the unique minimum-volume centered ellipsoid containing Φ , which John’s Theorem. We do not provide a proof of either claim here (both of which lead to the D-optimal design lemma). See Section 3.5 for references and further discussion.

Main theorem

We assume a generative model that can be queried at any stage h and any (s, a) to obtain an independent sample $s' \sim P_h(\cdot | s, a)$ (along with the reward $r_h(s, a)$).

Theorem 3.2 (LSVI under Bellman completeness; generative model). *Assume Bellman completeness (Section ??) and bounded rewards $r_h(s, a) \in [0, 1]$. Let ρ be a D-optimal design as in Lemma 3.1. Fix $\epsilon \in (0, 1)$ and $\delta \in (0, 1)$, and set*

$$N := \left\lceil \frac{c H^6 d^2 \log(H/\delta)}{\epsilon^2} \right\rceil,$$

for a sufficiently large absolute constant c .

Construct datasets $\{D_h\}_{h=0}^{H-1}$ as follows: for each h and each support point $(s, a) \in \text{supp}(\rho)$, query the generative model $n_{s,a} = \lceil N \rho(s, a) \rceil$ times to obtain i.i.d. next-state samples, and include the corresponding tuples in D_h .

Then, with probability at least $1 - \delta$, running LSVI (Algorithm 1) on $\{D_h\}_{h=0}^{H-1}$ returns a greedy policy $\hat{\pi}$ satisfying

$$\mathbb{E}_{s \sim \mu} [V_0^*(s) - V_0^{\hat{\pi}}(s)] \leq \epsilon.$$

Moreover, the total number of samples is at most

$$\sum_{h=0}^{H-1} |D_h| \leq H \left(N + \frac{d(d+1)}{2} \right) = O \left(H d^2 + \frac{H^7 d^2 \log(H/\delta)}{\epsilon^2} \right).$$

Proof of Theorem 3.2

We begin with a standard lemma: small Bellman residuals imply near-optimality of the greedy policy.

For any sequence of functions $\{\hat{Q}_h\}_{h=0}^H$ with $\hat{Q}_H \equiv 0$, define $\hat{V}_h(s) := \max_{a \in \mathcal{A}} \hat{Q}_h(s, a)$ and the greedy policy $\hat{\pi}_h(s) \in \arg \max_a \hat{Q}_h(s, a)$. Define the stage- h Bellman residual

$$\text{Res}_h := \|\hat{Q}_h - \mathcal{T}_h \hat{Q}_{h+1}\|_\infty.$$

Lemma 3.3 (Small residual $\Rightarrow$ good policy). *Assume $\hat{Q}_H \equiv 0$ and that $\text{Res}_h \leq \eta$ for all $h \in [H]$. Then:*

1. For all $h \in [H]$, $\|\hat{Q}_h - Q_h^*\|_\infty \leq (H - h)\eta$.
2. For the greedy policy $\hat{\pi}$, for all $s \in \mathcal{S}$,

$$V_0^*(s) - V_0^{\hat{\pi}}(s) \leq 2H^2\eta.$$

Proof. For (1), we proceed by backward induction. Since $Q_H^* \equiv 0 = \hat{Q}_H$, the claim holds for $h = H$. Suppose it holds for $h + 1$. Then for any (s, a) ,

$$\begin{aligned} |\hat{Q}_h(s, a) - Q_h^*(s, a)| &\leq |\hat{Q}_h(s, a) - (\mathcal{T}_h \hat{Q}_{h+1})(s, a)| + |(\mathcal{T}_h \hat{Q}_{h+1})(s, a) - (\mathcal{T}_h Q_{h+1}^*)(s, a)| \\ &\leq \eta + \mathbb{E}_{s'} [\max_{a'} |\hat{Q}_{h+1}(s', a') - Q_{h+1}^*(s', a')|] \\ &\leq \eta + \|\hat{Q}_{h+1} - Q_{h+1}^*\|_\infty \leq (H - h)\eta, \end{aligned}$$

using that max is 1-Lipschitz in ℓ_∞ .

For (2), fix h and s . Let $a^* \in \arg \max_a Q_h^*(s, a)$ and $\hat{a} \in \arg \max_a \hat{Q}_h(s, a)$. Then

$$Q_h^*(s, a^*) - Q_h^*(s, \hat{a}) \leq (Q_h^*(s, a^*) - \hat{Q}_h(s, a^*)) + (\hat{Q}_h(s, \hat{a}) - Q_h^*(s, \hat{a})) \leq 2\|\hat{Q}_h - Q_h^*\|_\infty \leq 2(H - h)\eta.$$

Unrolling along the trajectory of $\hat{\pi}$ gives

$$V_0^*(s) - V_0^{\hat{\pi}}(s) \leq \sum_{h=0}^{H-1} 2(H - h)\eta \leq 2H^2\eta.$$

□

Proof of Theorem 3.2. We show that, with high probability, each stage regression in LSVI has small *uniform* prediction error, which implies small Bellman residuals; then we invoke Lemma 3.3.

The first step looks at one stage as fixed-design regression. Fix a stage $h \in [H]$ and condition on $\hat{Q}_{h+1}$ (equivalently, $\hat{V}_{h+1}$), which is measurable with respect to data from stages $h + 1, \dots, H - 1$.

Each sample has covariate $x_i := \phi(s_i, a_i)$ and response $y_i := r_h(s_i, a_i) + \hat{V}_{h+1}(s'_i)$. (Optionally clip $\hat{V}_{h+1}$ to $[0, H]$ to strengthen boundedness.)

By Bellman completeness, there exists $\theta_h^* \in \mathbb{R}^d$ such that for all (s, a) ,

$$(\theta_h^*)^\top \phi(s, a) = r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} [\hat{V}_{h+1}(s')] = (\mathcal{T}_h \hat{Q}_{h+1})(s, a).$$

Hence $y_i = (\theta_h^*)^\top x_i + \xi_i$ where $\mathbb{E}[\xi_i | x_i] = 0$ and $\{\xi_i\}$ are independent across samples. Moreover $|\xi_i| \lesssim H$, so ξ_i is $O(H)$ -sub-Gaussian.

Let $\Lambda_h := \sum_{(s,a,r,s') \in D_h} \phi(s,a)\phi(s,a)^\top$ denote the (stage- h) design matrix.

Now we leverage the D-optimal sampling properties. Let $\Sigma = \mathbb{E}_{(s,a) \sim \rho}[\phi(s,a)\phi(s,a)^\top]$. By construction,

$$\Lambda_h = \sum_{(s,a) \in \text{supp}(\rho)} \lceil N\rho(s,a) \rceil \phi(s,a)\phi(s,a)^\top \succeq \sum_{(s,a) \in \text{supp}(\rho)} N\rho(s,a) \phi(s,a)\phi(s,a)^\top = N\Sigma,$$

so $\Lambda_h^{-1} \preceq (N\Sigma)^{-1}$ and Lemma 3.1 implies

$$\sup_{(s,a)} \phi(s,a)^\top \Lambda_h^{-1} \phi(s,a) \leq \frac{d}{N}.$$

Next we characterize the OLS generalization, uniformly. Apply the fixed-design OLS bound from the Appendix (Theorem A.10) with failure probability $\delta' := \delta/(2H)$ and noise scale $O(H)$ to obtain, with probability at least $1 - \delta'$,

$$\|\hat{\theta}_h - \theta_h^*\|_{\Lambda_h} \leq c_1 H \sqrt{d \log(H/\delta)},$$

for an absolute constant c_1 . Therefore, for any (s,a) ,

$$|(\hat{\theta}_h - \theta_h^*)^\top \phi(s,a)| \leq \|\hat{\theta}_h - \theta_h^*\|_{\Lambda_h} \sqrt{\phi(s,a)^\top \Lambda_h^{-1} \phi(s,a)} \leq c_1 H d \sqrt{\frac{\log(H/\delta)}{N}}.$$

Equivalently,

$$\|\hat{Q}_h - \mathcal{T}_h \hat{Q}_{h+1}\|_\infty \leq c_1 H d \sqrt{\frac{\log(H/\delta)}{N}}.$$

Finally, we complete the argument with a union bound. Apply the bound for all $h \in [H]$ and take a union bound: with probability at least $1 - \delta/2$,

$$\max_{h \in [H]} \|\hat{Q}_h - \mathcal{T}_h \hat{Q}_{h+1}\|_\infty \leq c_1 H d \sqrt{\frac{\log(H/\delta)}{N}}.$$

With our choice of N (and c large enough), the right-hand side is at most $\epsilon/(2H^2)$. Lemma 3.3 then yields, for all s , $V_0^*(s) - V_0^{\hat{\pi}}(s) \leq \epsilon$, and hence also $\mathbb{E}_{s \sim \mu}[V_0^*(s) - V_0^{\hat{\pi}}(s)] \leq \epsilon$.

Finally, for each h ,

$$|D_h| = \sum_{(s,a) \in \text{supp}(\rho)} \lceil N\rho(s,a) \rceil \leq N + |\text{supp}(\rho)| \leq N + \frac{d(d+1)}{2},$$

and summing over h gives the stated total sample bound. $\square$

3.3 Offline extensions under Bellman completeness

A notable feature of LSVI (Algorithm 1) is that it is non-adaptive: it operates on a fixed collection of observed transitions and rewards. Hence, it applies directly to the offline setting discussed in Chapter 1.

In this section we discuss two offline objectives: (i) learning a near-optimal policy, and (ii) policy evaluation (estimating the value of a given target policy π). The key additional requirement in the offline setting is *coverage*: the datasets must be sufficiently informative relative to the feature class.

3.3.1 Offline data model and a coverage condition

For each stage $h \in [H]$, we are given a dataset

$$D_h = \{(s_i, a_i, r_i, s'_i)\}_{i=1}^N,$$

where $r_i = r_h(s_i, a_i)$ and each $s'_i \sim P_h(\cdot \mid s_i, a_i)$ is sampled independently conditional on (s_i, a_i) . (The results below also extend to settings where the entire quadruple is i.i.d. from a fixed data-generating distribution; we focus on the above model to keep notation light.)

Let $\Phi := \{\phi(s, a) : (s, a) \in \mathcal{S} \times \mathcal{A}\}$, and recall the D-optimal covariance Σ induced by the maximizer in (3.2) (equivalently, Lemma 3.1). We impose coverage by requiring that the empirical covariance at each stage dominates Σ up to a factor κ .

Assumption 3.4 (Coverage). There exists $\kappa \geq 1$ such that for each stage $h \in [H]$,

$$\widehat{\Sigma}_h := \frac{1}{N} \sum_{(s, a, r, s') \in D_h} \phi(s, a) \phi(s, a)^\top \succeq \frac{1}{\kappa} \Sigma,$$

where $\Sigma = \mathbb{E}_{(s, a) \sim \rho} [\phi(s, a) \phi(s, a)^\top]$ for a D-optimal design ρ (see (3.2)).

Assumption 3.4 is a concise way to ensure that the offline design has uniformly bounded leverage scores relative to the geometry of Φ . Indeed, since $\widehat{\Sigma}_h \succeq \Sigma/\kappa$,

$$\sup_{(s, a)} \phi(s, a)^\top \widehat{\Sigma}_h^{-1} \phi(s, a) \leq \kappa \cdot \sup_{(s, a)} \phi(s, a)^\top \Sigma^{-1} \phi(s, a) \leq \kappa d,$$

using Lemma 3.1.

3.3.2 Offline policy optimization via LSVI

We first consider learning a near-optimal policy from offline data. Under Bellman completeness (Section ??) and coverage, the proof of the generative-model guarantee carries over with only minor changes.

Theorem 3.5 (Offline LSVI under Bellman completeness). *Assume Bellman completeness (Section ??), bounded rewards $r_h(s, a) \in [0, 1]$, and the coverage condition (Assumption 3.4) with parameter κ . Fix $\epsilon \in (0, 1)$ and $\delta \in (0, 1)$, and suppose each stage dataset has size*

$$N \geq \frac{c \kappa H^6 d^2 \log(H/\delta)}{\epsilon^2},$$

for a sufficiently large absolute constant c . Then with probability at least $1 - \delta$, running LSVI (Algorithm 1) on $\{D_h\}_{h=0}^{H-1}$ returns a greedy policy $\widehat{\pi}$ satisfying

$$\mathbb{E}_{s \sim \mu} [V_0^*(s) - V_0^{\widehat{\pi}}(s)] \leq \epsilon.$$

Proof sketch. The argument is identical to the proof of Theorem 3.2, except that leverage control now comes from coverage rather than D-optimal sampling. Concretely, at stage h , the design matrix satisfies $\Lambda_h = \sum_{(s, a, r, s') \in D_h} \phi(s, a) \phi(s, a)^\top = N \widehat{\Sigma}_h$, so Assumption 3.4 implies $\sup_{(s, a)} \phi(s, a)^\top \Lambda_h^{-1} \phi(s, a) \leq (\kappa d)/N$. Applying the same fixed-design OLS generalization bound (Appendix, Theorem A.10) and the same residual-to-policy lemma (Lemma 3.3), and union bounding over stages, yields the stated sample complexity. $\square$

Algorithm 2 Least-Squares Policy Evaluation (LSPE)

- 1: **Input:** policy $\pi = \{\pi_h\}_{h=0}^{H-1}$, datasets $D_0, \dots, D_{H-1}$, feature map ϕ
 - 2: Initialize $\widehat{V}_H^\pi(s) \leftarrow 0$ for all $s \in \mathcal{S}$
 - 3: **for** $h = H-1, H-2, \dots, 0$ **do**
 - 4: $\widehat{\theta}_h \in \arg \min_{\theta \in \mathbb{R}^d} \sum_{(s,a,r,s') \in D_h} \left(\theta^\top \phi(s,a) - r - \widehat{V}_{h+1}^\pi(s') \right)^2$
 - 5: Define $\widehat{V}_h^\pi(s) \leftarrow \widehat{\theta}_h^\top \phi(s, \pi_h(s))$ for all s
 - 6: **end for**
 - 7: **Return:** $\{\widehat{\theta}_h\}_{h=0}^{H-1}$ (equivalently, $\{\widehat{V}_h^\pi\}_{h=0}^H$)
-

3.3.3 Offline policy evaluation via LSPE

We now consider policy evaluation: estimating the value of a *given* policy $\pi = \{\pi_h\}_{h=0}^{H-1}$. For simplicity we assume π is deterministic; the extension to stochastic policies is routine by replacing $\pi_h(s)$ with an action drawn from $\pi_h(\cdot | s)$ (or by working with $\mathbb{E}_{a \sim \pi_h(\cdot | s)} \phi(s, a)$).

LSPE algorithm. LSPE mirrors LSVI but replaces the optimality backup by the π -backup.

Given parameters θ_h , define the induced value estimate $\widehat{V}_h^\pi(s) := \theta_h^\top \phi(s, \pi_h(s))$.

A π -completeness assumption. For policy evaluation, we only need closure under the *policy* Bellman operator.

Let $(\mathcal{T}_h^\pi f)(s, a) := r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} f(s', \pi_{h+1}(s'))$.

Definition 3.6 (Linear completeness for π). We say ϕ satisfies *policy completeness* for π if for each $h \in [H]$ and each $\theta \in \mathbb{R}^d$, there exists $w \in \mathbb{R}^d$ such that

$$(s, a) \mapsto r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} \theta^\top \phi(s', \pi_{h+1}(s'))$$

is exactly $w^\top \phi(s, a)$ for all (s, a) ; equivalently,

$$f \in \mathcal{F} \implies \mathcal{T}_h^\pi f \in \mathcal{F} \quad \text{for each } h \in [H].$$

Residual-to-estimation lemma (policy evaluation). For evaluation, small Bellman residuals control the value error directly (no greedy policy mismatch), yielding a milder horizon dependence.

Lemma 3.7 (Small π -residual $\implies$ accurate evaluation). Let $\{\widehat{V}_h^\pi\}_{h=0}^H$ be any functions with $\widehat{V}_H^\pi \equiv 0$. Define the stage- h π -residual

$$\text{Res}_h^\pi := \sup_{(s,a)} \left| \widehat{Q}_h(s, a) - (\mathcal{T}_h^\pi \widehat{V}_{h+1}^\pi)(s, a) \right|, \quad \widehat{Q}_h(s, a) := \widehat{\theta}_h^\top \phi(s, a).$$

If $\text{Res}_h^\pi \leq \eta$ for all $h \in [H]$, then for all $s \in \mathcal{S}$,

$$|V_0^\pi(s) - \widehat{V}_0^\pi(s)| \leq H\eta.$$

Proof. The proof is the same backward-induction argument as in Lemma 3.3(1), but with max replaced by following π , so there is no additional greedy suboptimality term. $\square$

Theorem 3.8 (Offline LSPE under policy completeness). *Assume bounded rewards $r_h(s, a) \in [0, 1]$, coverage (Assumption 3.4) with parameter κ , and policy completeness for π (Definition 3.6). Fix $\epsilon \in (0, 1)$ and $\delta \in (0, 1)$, and suppose each stage dataset has size*

$$N \geq \frac{c \kappa H^4 d^2 \log(H/\delta)}{\epsilon^2},$$

for a sufficiently large absolute constant c . Then with probability at least $1 - \delta$, the LSPE estimate satisfies

$$\sup_{s \in \mathcal{S}} |V_0^\pi(s) - \widehat{V}_0^\pi(s)| \leq \epsilon.$$

Consequently, $|\mathbb{E}_{s \sim \mu}[V_0^\pi(s)] - \mathbb{E}_{s \sim \mu}[\widehat{V}_0^\pi(s)]| \leq \epsilon$.

Proof sketch. Fix a stage h and condition on $\widehat{V}_{h+1}^\pi$. By policy completeness, the regression target has the form $r_h(s, a) + \mathbb{E}[\widehat{V}_{h+1}^\pi(s') \mid s, a] = (\theta_h^*)^\top \phi(s, a)$ for some θ_h^* . Thus each stage is a fixed-design linear regression with $O(H)$ -sub-Gaussian noise. Coverage gives the uniform leverage bound $\sup_{(s,a)} \phi(s, a)^\top \Lambda_h^{-1} \phi(s, a) \leq (\kappa d)/N$ with $\Lambda_h = N \widehat{\Sigma}_h$. Applying the fixed-design OLS bound (Appendix, Theorem A.10) and union bounding over h yields a uniform residual bound of order

$$\max_h \text{Res}_h^\pi \lesssim Hd \sqrt{\frac{\kappa \log(H/\delta)}{N}}.$$

Choosing N as in the theorem makes this at most ϵ/H , and Lemma 3.7 gives $\sup_s |V_0^\pi(s) - \widehat{V}_0^\pi(s)| \leq \epsilon$. $\square$

Remark on horizon dependence. The improvement from H^6 (offline LSVI) to H^4 (offline LSPE) reflects that for evaluation we only need value accuracy under a *fixed* policy, so we use Lemma 3.7 (which incurs an H factor) rather than the greedy-policy performance bound in Lemma 3.3 (which incurs an additional H factor). As elsewhere in this chapter, we have not optimized the dependence on H .

3.4 Negative Results with Weaker Linear Notions

The positive results in Section 3.2 rely on a closure condition (Bellman completeness) that keeps the algorithm’s regression targets inside the hypothesis class. This section explains why weaker “linear” conditions can be misleading.

We present two complementary impossibility results. First, we show that even the seemingly strong assumption that Q^* is linear in a known feature map does *not* guarantee $\text{poly}(d, H)$ sample complexity, even with a generative model. Second, we give an offline lower bound under an even stronger realizability assumption (linearity of Q^π for *all* policies) and a maximally well-conditioned feature covariance. The offline construction is particularly revealing: it exhibits a concrete mechanism by which errors (or variance) can compound exponentially with the horizon despite excellent “coverage” in the usual linear-regression sense.

3.4.1 Information-theoretic lower bounds with linearly realizable Q^*

We start with the most basic realizability assumption: the optimal Q -function itself lies in the linear span of the features.

Assumption 3.9 (Linear Q^* realizability). For all $h \in [H]$, there exists $\theta_h^* \in \mathbb{R}^d$ such that for all $(s, a) \in \mathcal{S} \times \mathcal{A}$,

$$Q_h^*(s, a) = (\theta_h^*)^\top \phi(s, a).$$

One might hope that Assumption 3.9 is already sufficient for sample-efficient RL when the feature map is known to the learner. The next theorem rules this out in a strong sense.

Theorem 3.10 (Linear Q^* is not enough, even with a generative model). *Consider any algorithm $\mathcal{A}$ with access to a generative model, which takes as input the feature map $\phi : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}^d$. There exists a finite-horizon MDP and a feature map ϕ satisfying Assumption 3.9 such that the action space size is*

$$|\mathcal{A}| = c_1 \left\lceil \min\{d^{1/4}, H^{1/2}\} \right\rceil,$$

and if $\mathcal{A}$ outputs a policy π satisfying

$$\mathbb{E}_{s_0 \sim \mu} [V_0^\pi(s_0)] \geq \mathbb{E}_{s_0 \sim \mu} [V_0^*(s_0)] - 0.05$$

with probability at least 0.1, then $\mathcal{A}$ requires at least $\min\{2^{c_2 d}, 2^{c_2 H}\}$ generative-model samples, where $c_1, c_2 > 0$ are absolute constants.

Theorem 3.10 shows that linear Q^* realizability alone does not prevent exponential sample complexity. Necessarily, such lower bounds rely on state spaces that are exponential in d or H (otherwise one could revert to a tabular algorithm with polynomial dependence on $|\mathcal{S}||\mathcal{A}|$). We provide in Appendix B a proof of a weaker version based on a simpler construction with $|\mathcal{A}| = \exp(d)$.

3.4.2 Offline impossibility under all-policies linear realizability

We now turn to the offline setting. In Section 3.2 we saw that a closure condition (Bellman completeness) yields polynomial guarantees for LSVI and LSPE given suitable data. Here we ask: what can be guaranteed under the *strictly weaker* condition of realizability, even if we strengthen it to hold for *all* policies and even if we assume essentially optimal coverage?

Offline data model. We work in a finite-horizon MDP with horizon H . The learner does not interact with the MDP; instead, for each stage $h \in \{0, \dots, H-1\}$ it receives a dataset D_h of n i.i.d. transition samples

$$(s, a, r, s') \in \mathcal{S}_h \times \mathcal{A} \times \mathbb{R} \times \mathcal{S}_{h+1}, \quad (s, a) \sim \mu_h, \quad r \sim r_h(s, a), \quad s' \sim P_h(\cdot | s, a),$$

for some (unknown) data distribution μ_h over $\mathcal{S}_h \times \mathcal{A}$. (The results can also be stated with stage-dependent sample sizes $\{n_h\}$; we use n for simplicity.)

Offline policy evaluation goal. Given a target policy π (assumed known) and the feature map ϕ , the goal is to estimate $V_0^\pi(s_0)$ (or $\mathbb{E}_{s_0 \sim \mu} [V_0^\pi(s_0)]$) from the offline datasets with as few samples as possible.

Realizability (for all policies). We assume that Q^π is linear in the features *for every* policy.

Assumption 3.11 (All-policies linear realizability). For every policy $\pi : \mathcal{S} \rightarrow \Delta(\mathcal{A})$, there exist parameter vectors $\theta_0^\pi, \dots, \theta_{H-1}^\pi \in \mathbb{R}^d$ such that for all $h \in \{0, \dots, H-1\}$ and all $(s, a) \in \mathcal{S}_h \times \mathcal{A}$,

$$Q_h^\pi(s, a) = (\theta_h^\pi)^\top \phi(s, a).$$

This is substantially stronger than realizability for a single target policy: it postulates a linear representation simultaneously over *all* policies.

Coverage (maximally well-conditioned design). To isolate the effect of compounding across stages, we impose a very strong coverage condition: the feature covariance under the data distribution is as well-conditioned as possible under $\|\phi\|_2 \leq 1$.

Assumption 3.12 (Coverage). Assume $\|\phi(s, a)\|_2 \leq 1$ for all (s, a) . For each stage $h \in \{0, \dots, H-1\}$, the data distribution μ_h satisfies

$$\mathbb{E}_{(s,a) \sim \mu_h} [\phi(s, a)\phi(s, a)^\top] = \frac{1}{d} I.$$

For $H = 1$, Assumptions 3.11 and 3.12 reduce to classical linear regression. The next theorem shows that this intuition fails dramatically once H is large.

Theorem 3.13 (Offline policy evaluation can be exponentially hard). *Suppose Assumption 3.12 holds. Fix any algorithm that, given (π, ϕ) and the offline datasets $\{D_h\}_{h=0}^{H-1}$, outputs an estimate of $V_0^\pi(s_0)$. There exists a finite-horizon MDP satisfying Assumption 3.11 such that for every policy $\pi : \mathcal{S} \rightarrow \Delta(\mathcal{A})$, the algorithm requires*

$$\Omega((d/2)^H)$$

samples to obtain a constant additive approximation to $V_0^\pi(s_0)$ with probability at least 0.9.

Implication for offline control. Although stated for policy evaluation, the hardness also applies to offline control under Assumption 3.11. Indeed, add a new initial state s_{new} in which action a_1 yields reward 0.5 and terminates, while action a_2 transitions into the hard instance from Theorem 3.13. Any algorithm that returns a policy with suboptimality at most 0.5 must distinguish whether entering the hard instance is better than taking a_1 , and therefore inherits the same exponential lower bound.

LSPE (and LSVI) can have exponential variance. Theorem 3.13 is a minimax lower bound: it implies that no offline estimator can avoid an exponential dependence on H under realizability alone. In particular, any unbiased estimator (when it exists) must have variance growing exponentially with H , so Least-Squares Policy Evaluation inherits this pathology despite the strong coverage in Assumption 3.12.

A hard instance for offline policy evaluation

We now describe the hard family used in Theorem 3.13. The key idea is that although the offline data have essentially perfect coverage over the *observed* feature directions, the value of the policy depends on *unobserved* “aggregator” states. Linearity then forces the value at these aggregator states to be an amplified combination of quantities that can only be estimated from the last layer, causing an exponential dependence on the horizon. Figure 3.1 shows this instance.

Let $m \geq 1$ be an integer and set

$$d := 2m, \quad \mathcal{A} := \{a_1, a_2\}.$$

The family is indexed by a scalar parameter $r_\infty \in [0, m^{-H/2}]$; in the lower bound we only need two values, $r_\infty \in \{0, m^{-H/2}\}$.

State space and transitions. For each layer $h \in \{0, 1, \dots, H-1\}$, define

$$\mathcal{S}_h := \{s_h^1, \dots, s_h^m\} \cup \{g_h\},$$

reward params:
 $r_\infty \in \{0, m^{-H/2}\}$
 $\alpha_h := r_\infty m^{(H-h)/2}$

features:
 $\phi(s_h^c, a_1) = e_c$
 $\phi(s_h^c, a_2) = e_{m+c}$
 $\phi(g_h, a) = \frac{1}{\sqrt{m}}(e_1 + e_2 + \dots + e_m)$





Figure 3.1: **Offline policy-evaluation hard instance (schematic).** Each layer h has m “observed” states $\{s_h^i\}_{i=1}^m$ (boxed: states covered by the offline dataset D_h) and one “aggregator” state g_h (never covered by the offline data). Action a_2 (dashed) keeps the trajectory in the observed chain $s_h^i \rightarrow s_{h+1}^i$, while action a_1 (solid) jumps to the aggregator chain $s_h^i \rightarrow g_{h+1}$; from aggregator states, both actions transition to the next aggregator state. Rewards are stage-dependent: on observed states, $r_h = 0$ for $h \leq H-2$ and $r_{H-1} \in \{\pm 1\}$ with $\mathbb{E}[r_{H-1}] = r_\infty$; on aggregator states, $r_h(g_h, \cdot) = \alpha_h - \alpha_{h+1}$ for $h \leq H-2$ and $r_{H-1}(g_{H-1}, \cdot) = \alpha_{H-1} = r_\infty \sqrt{m}$, where $\alpha_h := r_\infty m^{(H-h)/2}$. The lower bound compares two instances with $r_\infty = 0$ versus $r_\infty = m^{-H/2}$, which induce identical offline data on the boxed support but different values at g_0 . See text for further description.

where g_h is an “aggregator” state. The initial state is $s_0 = g_0$. For $h \in \{0, 1, \dots, H-2\}$, transitions are deterministic:

$$\begin{aligned} P(g_{h+1} \mid s, a_1) &= 1 && \text{for all } s \in \mathcal{S}_h, \\ P(s_{h+1}^i \mid s_h^i, a_2) &= 1 && \text{for all } i \in [m], \\ P(g_{h+1} \mid g_h, a_2) &= 1. \end{aligned}$$

Equivalently: action a_1 always jumps to the aggregator chain, while a_2 preserves the index i on the $\{s_h^i\}$ states (and keeps the g -chain on g).

Rewards. Define the shorthand

$$\alpha_h := r_\infty m^{(H-h)/2}, \quad h \in \{0, 1, \dots, H-1\}.$$

(Note $\alpha_0 \leq 1$ since $r_\infty \leq m^{-H/2}$.) For layers $h = 0, 1, \dots, H-2$, rewards are deterministic:

$$\begin{aligned} r_h(s_h^i, a) &= 0 && \text{for all } i \in [m], a \in \{a_1, a_2\}, \\ r_h(g_h, a) &= \alpha_h - \alpha_{h+1} && \text{for all } a \in \{a_1, a_2\}. \end{aligned}$$

At the last layer $h = H-1$, rewards depend only on r_∞ :

$$\begin{aligned} r_{H-1}(s_{H-1}^i, a) &= \begin{cases} 1 & \text{with prob. } (1 + r_\infty)/2, \\ -1 & \text{with prob. } (1 - r_\infty)/2, \end{cases} && \text{for all } i \in [m], a \in \{a_1, a_2\}, \\ r_{H-1}(g_{H-1}, a) &= \alpha_{H-1} = r_\infty \sqrt{m} && \text{for all } a \in \{a_1, a_2\}. \end{aligned}$$

Thus $\mathbb{E}[r_{H-1}(s_{H-1}^i, a)] = r_\infty$ while $r_{H-1}(g_{H-1}, a)$ is deterministic.

Feature map. Let $e_1, \dots, e_{2m}$ be an orthonormal basis of $\mathbb{R}^{2m}$. Define $\phi : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}^{2m}$ by, for each layer h ,

$$\begin{aligned} \phi(s_h^i, a_1) &= e_i, & \phi(s_h^i, a_2) &= e_{m+i} && \text{for all } i \in [m], \\ \phi(g_h, a_1) &= \phi(g_h, a_2) = \frac{1}{\sqrt{m}} \sum_{i=1}^m e_i. \end{aligned}$$

In particular, $\|\phi(s, a)\|_2 \leq 1$ for all (s, a) .

Offline data distributions (isotropic, but miss the aggregators). For each layer $h \in \{0, 1, \dots, H-1\}$, let μ_h be the uniform distribution over

$$\{(s_h^i, a_1), (s_h^i, a_2) : i \in [m]\}.$$

In particular, (g_h, a) is *not* in the support of μ_h for any h or a . A direct calculation gives

$$\mathbb{E}_{(s,a) \sim \mu_h} [\phi(s, a) \phi(s, a)^\top] = \frac{1}{2m} \sum_{j=1}^{2m} e_j e_j^\top = \frac{1}{d} I,$$

so Assumption 3.12 holds.

Where the exponential dependence comes from (informal). The policy value at the initial state is

$$V_0^\pi(g_0) = \alpha_0 = r_\infty m^{H/2},$$

which equals 0 when $r_\infty = 0$ and equals 1 when $r_\infty = m^{-H/2}$. However, the offline data *never* visit g_h , so the only information about r_∞ comes from the last layer rewards at the observed states s_{H-1}^i , whose mean differs by only $m^{-H/2}$. Estimating that tiny mean to constant confidence requires $\Omega(m^H)$ samples, yielding the claimed lower bound.

We now verify Assumption 3.11.

Lemma 3.14. *For every policy $\pi : \mathcal{S} \rightarrow \Delta(\mathcal{A})$, for each $h \in [H]$, there exists $\theta_h^\pi \in \mathbb{R}^{2m}$ such that for all $(s, a) \in \mathcal{S}_h \times \mathcal{A}$,*

$$Q_h^\pi(s, a) = \langle \theta_h^\pi, \phi(s, a) \rangle.$$

Proof. First note that from any aggregator state g_h , the next state is always g_{h+1} (regardless of the action), and rewards at g_h do not depend on the action. Hence $V_h^\pi(g_h) = Q_h^\pi(g_h, a_1) = Q_h^\pi(g_h, a_2)$ for all h and π .

We compute $V_h^\pi(g_h)$ by backward induction. At $h = H - 1$,

$$V_{H-1}^\pi(g_{H-1}) = r_{H-1}(g_{H-1}, \cdot) = \alpha_{H-1}.$$

For $h \leq H - 2$,

$$V_h^\pi(g_h) = r_h(g_h, \cdot) + V_{h+1}^\pi(g_{h+1}) = (\alpha_h - \alpha_{h+1}) + \alpha_{h+1} = \alpha_h.$$

In particular, for $h \leq H - 2$ and any $i \in [m]$,

$$Q_h^\pi(s_h^i, a_1) = r_h(s_h^i, a_1) + V_{h+1}^\pi(g_{h+1}) = \alpha_{h+1}.$$

Also, for any $i \in [m]$ and $h \leq H - 2$,

$$Q_h^\pi(s_h^i, a_2) = r_h(s_h^i, a_2) + V_{h+1}^\pi(s_{h+1}^i) = V_{h+1}^\pi(s_{h+1}^i),$$

which may depend on π but is a scalar that we can represent directly.

Now define, for $h \leq H - 2$,

$$\theta_h^\pi := \sum_{i=1}^m \alpha_{h+1} e_i + \sum_{i=1}^m Q_h^\pi(s_h^i, a_2) e_{m+i}.$$

Then for $i \in [m]$,

$$\langle \theta_h^\pi, \phi(s_h^i, a_1) \rangle = \alpha_{h+1} = Q_h^\pi(s_h^i, a_1), \quad \langle \theta_h^\pi, \phi(s_h^i, a_2) \rangle = Q_h^\pi(s_h^i, a_2).$$

Moreover,

$$\langle \theta_h^\pi, \phi(g_h, \cdot) \rangle = \left\langle \sum_{i=1}^m \alpha_{h+1} e_i, \frac{1}{\sqrt{m}} \sum_{i=1}^m e_i \right\rangle = \alpha_{h+1} \sqrt{m} = r_\infty m^{(H-h-1)/2} \sqrt{m} = \alpha_h = Q_h^\pi(g_h, \cdot).$$

At the last layer $h = H - 1$, we have $Q_{H-1}^\pi(s, a) = \mathbb{E}[r_{H-1}(s, a)]$. For the observed states $\{s_{H-1}^i\}_{i=1}^m$, $\mathbb{E}[r_{H-1}(s_{H-1}^i, a)] = r_\infty$ for both actions; for g_{H-1} , $Q_{H-1}^\pi(g_{H-1}, \cdot) = \alpha_{H-1} = r_\infty \sqrt{m}$. Setting

$$\theta_{H-1}^\pi := \sum_{j=1}^{2m} r_\infty e_j$$

gives $Q_{H-1}^\pi(s, a) = \langle \theta_{H-1}^\pi, \phi(s, a) \rangle$ for all (s, a) , since $\langle \theta_{H-1}^\pi, e_i \rangle = r_\infty$ and $\left\langle \theta_{H-1}^\pi, \frac{1}{\sqrt{m}} \sum_{i=1}^m e_i \right\rangle = r_\infty \sqrt{m}$. $\square$

Proof sketch of Theorem 3.13 (information-theoretic argument)

We reduce policy evaluation to a two-point hypothesis test. Fix any policy π . In this construction, the value at the initial state does not depend on π :

$$V_0^\pi(g_0) = \alpha_0 = r_\infty m^{H/2}.$$

Consider two instances, identical in transitions, features, and data distributions, but with different parameters:

$$r_\infty^{(0)} := 0, \quad r_\infty^{(1)} := m^{-H/2}.$$

Then $V_0^\pi(g_0) = 0$ under $r_\infty^{(0)}$ and $V_0^\pi(g_0) = 1$ under $r_\infty^{(1)}$. Therefore, any algorithm that outputs an estimate $\widehat{V}$ satisfying $|\widehat{V} - V_0^\pi(g_0)| \leq 1/2$ with probability at least 0.9 must distinguish these two instances with probability at least 0.9.

Under both instances, the offline distributions $\{\mu_h\}_{h=0}^{H-1}$ are the same. Moreover, for layers $h \leq H-2$, all rewards on the support of μ_h are identically 0 in both instances. Hence *all information about r_∞ available in the offline data comes from the last layer samples D_{H-1} .*

On the support of μ_{H-1} , rewards are $\{\pm 1\}$ -valued with mean r_∞ : under $r_\infty^{(0)}$,

$$\Pr(r = 1) = 1/2, \quad \Pr(r = -1) = 1/2,$$

while under $r_\infty^{(1)}$,

$$\Pr(r = 1) = (1 + m^{-H/2})/2, \quad \Pr(r = -1) = (1 - m^{-H/2})/2.$$

Let $\Delta := m^{-H/2}$. A direct calculation shows that the KL divergence between a single sample under these two reward distributions satisfies

$$\text{KL}(P_\Delta \| P_0) = -\frac{1}{2} \log(1 - \Delta^2) \leq 2\Delta^2 \quad (\text{for } \Delta \leq 1/2).$$

By independence, the KL divergence between n last-layer samples is at most $2n\Delta^2$. Standard two-point testing inequalities (e.g. Le Cam’s method) imply that any test that distinguishes the two instances with probability at least 0.9 must have total KL at least a constant, and thus requires

$$n\Delta^2 = \Omega(1) \quad \implies \quad n = \Omega(\Delta^{-2}) = \Omega(m^H).$$

Recalling $d = 2m$, this is $\Omega((d/2)^H)$, establishing Theorem 3.13.

3.5 Bibliographic Remarks and Further Readings

The closure idea behind *Bellman completeness* (for general function classes) appears already in early work on error propagation in approximate dynamic programming and batch RL; see, for example, Munos [2005]. In episodic online RL, Zanette et al. [2020] gave statistically efficient algorithms under *linear* Bellman completeness, and Jin et al. [2021] extended the picture to statistically efficient algorithms under Bellman completeness with general function approximation.

The geometric viewpoint on D -optimal design is classical and goes back to John’s theorem on minimum-volume ellipsoids [John, 1948]. The Kiefer–Wolfowitz equivalence between the D -optimal (log-determinant) and G -optimal (maximum variance) formulations is due to Kiefer and Wolfowitz [1960]. For an accessible modern proof and additional context (including connections to bandits and experimental design), see Lattimore and Szepesvári [2020].

The theme that, under the right structural assumptions, reinforcement learning can be reduced to a sequence of supervised learning problems goes back at least to Kearns et al. [2000], which analyzed a “trajectory tree” approach and connected sample complexity to the VC dimension of a policy class. We examine this in the next chapter with importance sampling.

Linear methods for dynamic programming have a long history, going back at least to Shannon [1959], Bellman and Dreyfus [1959]. The modern formulation of the *linear Q^* realizability* assumption appears (at least) in Wen and Van Roy [2017] and is highlighted as a central learnability question in Du et al. [2019]. In the offline (policy evaluation) setting, exponential lower bounds under strong linear realizability assumptions are due to Wang et al. [2020a], Zanette [2021], and we present a variant as Theorem 3.13. With a generative model, the breakthrough impossibility result under linear Q^* realizability is due to Weisz et al. [2021a]. Subsequent work [Weisz et al., 2021b] extends these ideas to yield lower bounds that continue to hold even when the action space is only polynomial in (d, H) ; this is the form we invoke for Theorem 3.10. In Appendix B we also include a simpler (but weaker) proof in the spirit of the original construction of Weisz et al. [2021a], using exponentially many actions.

Finally, Wang et al. [2021] studies the *episodic* (online) setting under linear Q^* realizability, together with an additional *constant suboptimality gap* assumption. As we discuss below, this gap assumption permits sample-efficient learning

with a generative model. However, the main result of Wang et al. [2021] is negative: even with a constant gap, *episodic* interaction alone does not guarantee sample-efficient learning under these two assumptions — they prove an $\exp(\Omega(\min\{d, H\}))$ sample lower bound for obtaining a constant-accuracy guarantee in the online model.

This stands in sharp contrast to the *generative-model* setting, where the same gap assumption can be exploited for *identification*. A backward-induction-style elimination argument can compare actions locally and rule out suboptimal ones using only polynomially many queries, since each is separated from the optimum by a constant margin. Once the optimal action is identified stage by stage, one can propagate *unbiased* estimates of Q^* backward through the horizon, because the Bellman targets are evaluated under the true optimal continuation rather than a biased surrogate—precisely the kind of targeted identification that episodic data do not reliably support.

Chapter 4

Approximate Dynamic Programming in Large MDPs: Offline Learning and Coverage

This chapter studies a complementary regime to Chapter 3. In Chapter 3 we obtained strong (worst-case) sample complexity guarantees in large MDPs by imposing a *structural closure* assumption: the relevant Bellman updates remain within a prescribed (typically low-dimensional) function class (e.g., linear Bellman completeness / linear MDP structure). Under such closure, one can propagate estimation error cleanly and avoid explicit dependence on the size of the state space.

Here, we consider a more classical approach based on *approximate dynamic programming*, but with using *supervised regression* subroutines. Concretely, we will study *fitted* methods that repeatedly regress to Bellman targets and then act greedily with respect to the resulting approximations. This style of algorithm is attractive because it is modular — it reduces reinforcement learning to a sequence of standard prediction problems — and it allows substantial flexibility in the choice of function class. We study this question in the discounted MDP framework in this chapter. Again, we seek guarantees which do not depend on the size of the state and action spaces.

However, this flexibility comes at a price. In the offline setting, the learner does not control data collection: it is restricted to a fixed dataset drawn from some behavior distribution. In such settings, purely worst-case guarantees cannot hold without additional assumptions: the data distribution must provide *coverage* of the state-action pairs that matter for planning. Moreover, even with good coverage, the function class need not be closed under Bellman updates, leading to an irreducible approximation term.

The main message of this chapter is that fitted methods yield meaningful guarantees under two explicit requirements:

1. **Distributional coverage (concentrability).** The offline data distribution must dominate the state-action distributions induced by policies the algorithm might implicitly reason about. This is quantified by a *concentrability coefficient*.
2. **Bellman approximation (inherent Bellman error).** The function class must be able to approximate Bellman updates in an average-case sense under the data distribution.

Under these conditions, fitted Q -iteration (FQI) can be analyzed as a stable approximate value iteration procedure with regression error at each step, propagated through the MDP dynamics via concentrability.

4.1 Fitted Q -Iteration (FQI) in Offline RL

We work with an infinite-horizon discounted MDP $\mathcal{M} = (\mathcal{S}, \mathcal{A}, P, r, \gamma, \mu)$ where $\gamma \in (0, 1)$, the reward is bounded $r(s, a) \in [0, 1]$, and μ is an initial-state distribution. Let

$$V_{\max} := \frac{1}{1 - \gamma}.$$

For any function $f : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$, recall the Bellman optimality operator

$$(\mathcal{T}f)(s, a) := r(s, a) + \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)} \max_{a' \in \mathcal{A}} f(s', a').$$

We write Q^* for the unique fixed point of $\mathcal{T}$ and $V^*(s) := \max_a Q^*(s, a)$, with overall value $V^* := \mathbb{E}_{s_0 \sim \mu}[V^*(s_0)]$. For a policy π , we similarly denote $V^\pi(s_0)$ and $V^\pi := \mathbb{E}_{s_0 \sim \mu}[V^\pi(s_0)]$.

Offline sampling model. We are given a fixed distribution $\nu \in \Delta(\mathcal{S} \times \mathcal{A})$ and an i.i.d. dataset

$$\mathcal{D} := \{(s_i, a_i, r_i, s'_i)\}_{i=1}^n, \quad (s_i, a_i) \sim \nu, \quad r_i = r(s_i, a_i), \quad s'_i \sim P(\cdot | s_i, a_i).$$

The learner must output a policy $\hat{\pi}$ using only $\mathcal{D}$. For any distribution ρ over $\mathcal{S} \times \mathcal{A}$ we use $\|f\|_{2, \rho}^2 := \mathbb{E}_{(s, a) \sim \rho}[f(s, a)^2]$.

4.1.1 Two explicit requirements: coverage and Bellman approximation

Coverage via concentrability. Let d_μ^π denote the discounted state-action occupancy measure of policy π , i.e. the distribution over (s, a) obtained by starting at $s_0 \sim \mu$, then following π , and sampling a time step according to the geometric weights $(1 - \gamma)\gamma^t$. The dataset distribution ν must cover the occupancy measures of the policies that matter for evaluation and improvement.

Assumption 4.1 (Concentrability / coverage). There exists a constant $C \geq 1$ such that for every (possibly non-stationary) policy π ,

$$\sup_{s, a} \frac{d_\mu^\pi(s, a)}{\nu(s, a)} \leq C,$$

with the convention that the ratio is $+\infty$ when $\nu(s, a) = 0$ and $d_\mu^\pi(s, a) > 0$.

This assumption ensures that average-case errors measured under ν control the same errors under the visitation distributions that appear in performance comparisons. Informally: *if the data never visits a region that an evaluated policy might visit, then no offline method can reliably reason about that region.*

Bellman approximation via inherent Bellman error. Fix a bounded function class

$$\mathcal{F} \subseteq \{f : \mathcal{S} \times \mathcal{A} \rightarrow [0, V_{\max}]\}.$$

In fitted methods, regression targets are Bellman updates $\mathcal{T}f$ of previous iterates $f \in \mathcal{F}$. Without closure of $\mathcal{F}$ under $\mathcal{T}$, there is an irreducible approximation error. We quantify this by the standard *inherent Bellman error* under ν .

Assumption 4.2 (Inherent Bellman error under ν). Define

$$\epsilon_{\text{approx}, \nu} := \max_{f \in \mathcal{F}} \min_{f' \in \mathcal{F}} \|f' - \mathcal{T}f\|_{2, \nu}^2.$$

We refer to $\epsilon_{\text{approx}, \nu}$ as the inherent Bellman error (with respect to ν).

When $\epsilon_{\text{approx}, \nu} = 0$, the class is (average-case) Bellman complete under ν ; otherwise, this term will appear additively in the final suboptimality bound.

4.1.2 The FQI algorithm

Fitted Q -iteration (FQI) constructs a sequence $\{f_t\}_{t \geq 0} \subset \mathcal{F}$ by repeatedly regressing to Bellman targets computed from the previous iterate. Starting from an arbitrary $f_0 \in \mathcal{F}$, iterate for $t = 1, 2, \dots, K$:

$$f_t \in \operatorname{argmin}_{f \in \mathcal{F}} \sum_{i=1}^n \left(f(s_i, a_i) - [r_i + \gamma \max_{a' \in \mathcal{A}} f_{t-1}(s'_i, a')] \right)^2. \quad (4.1)$$

After K iterations, output the greedy policy

$$\pi^K(s) \in \operatorname{argmax}_{a \in \mathcal{A}} f_K(s, a).$$

Interpretation. At each iteration, the regression problem in (4.1) has a well-defined conditional expectation target:

$$\mathbb{E} \left[r + \gamma \max_{a'} f_{t-1}(s', a') \mid s, a \right] = (\mathcal{T} f_{t-1})(s, a).$$

Moreover, since $r \in [0, 1]$ and $f_{t-1} \in [0, V_{\max}]$,

$$0 \leq r + \gamma \max_{a'} f_{t-1}(s', a') \leq 1 + \gamma V_{\max} = V_{\max}, \quad \text{and} \quad 0 \leq (\mathcal{T} f_{t-1})(s, a) \leq V_{\max}.$$

Thus, if the regression step returns f_t close to $\mathcal{T} f_{t-1}$ in $\|\cdot\|_{2,\nu}$, and if ν provides coverage so that $\|\cdot\|_{2,\nu}$ controls errors under relevant visitation distributions, then the iterates behave like an approximate value iteration procedure.

4.1.3 Main guarantee: what you get, and what you pay

The following theorem states that the performance loss decomposes into three terms: (i) a *statistical error* term scaling as $1/\sqrt{n}$, (ii) an *approximation error* term governed by $\epsilon_{\text{approx},\nu}$, and (iii) a *finite-iteration* error that decays geometrically in K .

Theorem 4.3 (Performance guarantee for FQI). *Fix $K \in \mathbb{N}^+$. Under Assumptions 4.1 and 4.2, and for a finite function class $\mathcal{F}$, FQI (4.1) satisfies the following: with probability at least $1 - \delta$,*

$$V^* - V^{\pi^K} \leq \frac{2}{(1-\gamma)^2} \left(\sqrt{\frac{22 C V_{\max}^2 \ln(|\mathcal{F}|^2 K / \delta)}{n}} + \sqrt{20 C \epsilon_{\text{approx},\nu}} \right) + \frac{2\gamma^K V_{\max}}{1-\gamma}.$$

Let us now interpret the theorem, which makes the two “prices” explicit: The *coverage price* is the multiplicative factor $\sqrt{C}$ (and hence C inside the square roots). If C is large, average-case regression error under ν can amplify dramatically when translated to the distributions induced by greedy policies. The *Bellman approximation price* is the term $\sqrt{\epsilon_{\text{approx},\nu}}$. Even with infinite data, if the class cannot approximate Bellman updates under ν , the method converges only up to this floor. Finally, the last term $2\gamma^K V_{\max}/(1-\gamma)$ is purely algorithmic: it is the error from running only K fitted iterations.

Proofs for Theorem 4.3

The proof roadmap can be decomposed into two reusable lemmas: First, we have a *one-step regression lemma* showing that each fitted regression step controls the Bellman residual $\|f_t - \mathcal{T} f_{t-1}\|_{2,\nu}$ in terms of (i) a statistical error term and (ii) the inherent Bellman error $\epsilon_{\text{approx},\nu}$. Second, we have a *propagation lemma* showing that if every step has small

Bellman residual in $\|\cdot\|_{2,\nu}$, then the greedy policies π^t become near-optimal, with concentrability translating $\|\cdot\|_{2,\nu}$ control into control under the relevant occupancy measures.

We now develop these lemmas and then combine them to prove Theorem 4.3.

We first record the two key ingredients: (i) how Bellman error along the iteration translates into performance loss, and (ii) a uniform generalization bound for the regression step defining f_{t+1} .

Lemma 4.4 (Bellman residual $\Rightarrow$ performance loss). *Assume that for all $t = 0, 1, \dots, K-1$ we have*

$$\|f_{t+1} - \mathcal{T}f_t\|_{2,\nu} \leq \varepsilon.$$

Let π^t be greedy w.r.t. f_t (i.e. $\pi^t(s) \in \arg \max_a f_t(s, a)$). Then for every $k \in \{0, 1, \dots, K\}$,

$$V^* - V^{\pi^k} \leq \frac{2\sqrt{C}\varepsilon}{(1-\gamma)^2} + \frac{2\gamma^k V_{\max}}{1-\gamma}.$$

Proof. Fix k . Using the performance difference lemma with $\pi = \pi^k$ and $\pi' = \pi^*$,

$$(1-\gamma)(V^* - V^{\pi^k}) = \mathbb{E}_{s \sim d_{\mu}^{\pi^k}} [V^*(s) - Q^*(s, \pi^k(s))] = \mathbb{E}_{s \sim d_{\mu}^{\pi^k}} [Q^*(s, \pi^*(s)) - Q^*(s, \pi^k(s))].$$

Since π^k is greedy w.r.t. f_k ,

$$Q^*(s, \pi^*(s)) - Q^*(s, \pi^k(s)) \leq (Q^*(s, \pi^*(s)) - f_k(s, \pi^*(s))) + (f_k(s, \pi^k(s)) - Q^*(s, \pi^k(s))).$$

Taking expectation and applying Cauchy–Schwarz yields

$$\begin{aligned} (1-\gamma)(V^* - V^{\pi^k}) &\leq \|Q^* - f_k\|_{1, d_{\mu}^{\pi^k} \circ \pi^*} + \|Q^* - f_k\|_{1, d_{\mu}^{\pi^k} \circ \pi^k} \\ &\leq \|Q^* - f_k\|_{2, d_{\mu}^{\pi^k} \circ \pi^*} + \|Q^* - f_k\|_{2, d_{\mu}^{\pi^k} \circ \pi^k}. \end{aligned} \quad (4.2)$$

Thus it suffices to control $\|Q^* - f_k\|_{2,\beta}$ for distributions β of the form $d_{\mu}^{\pi^k} \circ \pi$.

Fix any such β . Decompose

$$Q^* - f_k = (Q^* - \mathcal{T}f_{k-1}) + (\mathcal{T}f_{k-1} - f_k),$$

so by the triangle inequality,

$$\|Q^* - f_k\|_{2,\beta} \leq \|Q^* - \mathcal{T}f_{k-1}\|_{2,\beta} + \|f_k - \mathcal{T}f_{k-1}\|_{2,\beta}. \quad (4.3)$$

For the second term, Assumption 4.1 implies $\beta(s, a) \leq C\nu(s, a)$ pointwise, hence

$$\|f_k - \mathcal{T}f_{k-1}\|_{2,\beta} \leq \sqrt{C}\|f_k - \mathcal{T}f_{k-1}\|_{2,\nu}. \quad (4.4)$$

For the first term, note that for every (s, a) ,

$$(Q^* - \mathcal{T}f_{k-1})(s, a) = \gamma \mathbb{E}_{s' \sim P(\cdot | s, a)} \left[\max_{a'} Q^*(s', a') - \max_{a'} f_{k-1}(s', a') \right].$$

Using $(\mathbb{E}[X])^2 \leq \mathbb{E}[X^2]$ and $(\max_x u_x - \max_x v_x)^2 \leq \max_x (u_x - v_x)^2$ gives

$$\|Q^* - \mathcal{T}f_{k-1}\|_{2,\beta}^2 \leq \gamma^2 \mathbb{E}_{\substack{(s,a) \sim \beta \\ s' \sim P(\cdot | s, a)}} \left[\max_{a'} (Q^*(s', a') - f_{k-1}(s', a'))^2 \right].$$

Define a distribution β' over (s', a') by sampling $(s, a) \sim \beta$, then $s' \sim P(\cdot | s, a)$, and finally choosing

$$a' \in \arg \max_{a \in \mathcal{A}} (Q^*(s', a) - f_{k-1}(s', a))^2.$$

With this definition,

$$\mathbb{E}_{\substack{(s,a) \sim \beta \\ s' \sim P(\cdot|s,a)}} \left[\max_{a'} (Q^*(s', a') - f_{k-1}(s', a'))^2 \right] = \mathbb{E}_{(s', a') \sim \beta'} \left[(Q^*(s', a') - f_{k-1}(s', a'))^2 \right] = \|Q^* - f_{k-1}\|_{2, \beta'}^2,$$

and therefore

$$\|Q^* - \mathcal{T}f_{k-1}\|_{2, \beta} \leq \gamma \|Q^* - f_{k-1}\|_{2, \beta'}. \quad (4.5)$$

Combining (4.3), (4.4), and (4.5) gives

$$\|Q^* - f_k\|_{2, \beta} \leq \gamma \|Q^* - f_{k-1}\|_{2, \beta'} + \sqrt{C} \|f_k - \mathcal{T}f_{k-1}\|_{2, \nu}. \quad (4.6)$$

Iterating (4.6) for k steps yields

$$\|Q^* - f_k\|_{2, \beta} \leq \sqrt{C} \sum_{t=0}^{k-1} \gamma^t \|f_{k-t} - \mathcal{T}f_{k-t-1}\|_{2, \nu} + \gamma^k \|Q^* - f_0\|_{2, \tilde{\beta}},$$

for some distribution $\tilde{\beta}$ over $\mathcal{S} \times \mathcal{A}$. Under the hypothesis $\|f_{t+1} - \mathcal{T}f_t\|_{2, \nu} \leq \varepsilon$ and since $Q^*, f_0 \in [0, V_{\max}]$ pointwise, we obtain

$$\|Q^* - f_k\|_{2, \beta} \leq \frac{\sqrt{C} \varepsilon}{1 - \gamma} + \gamma^k V_{\max}.$$

Applying this bound to both distributions in (4.2) gives

$$(1 - \gamma)(V^* - V^{\pi^k}) \leq 2 \left(\frac{\sqrt{C} \varepsilon}{1 - \gamma} + \gamma^k V_{\max} \right),$$

and dividing by $(1 - \gamma)$ yields the claim. $\square$

Lemma 4.5 (Uniform regression (Bellman error) bound). *With probability at least $1 - \delta$, for all $t = 0, 1, \dots, K - 1$,*

$$\|f_{t+1} - \mathcal{T}f_t\|_{2, \nu}^2 \leq \frac{22V_{\max}^2 \ln(|\mathcal{F}|^2 K / \delta)}{n} + 20 \epsilon_{\text{approx}, \nu}.$$

Proof. Fix $g \in \mathcal{F}$ and consider the regression problem with inputs (s_i, a_i) and targets

$$y_i := r_i + \gamma \max_{a'} g(s'_i, a').$$

Then $\mathbb{E}[y_i | s_i, a_i] = (\mathcal{T}g)(s_i, a_i)$, and, as noted above, $0 \leq y_i \leq V_{\max}$ and $0 \leq (\mathcal{T}g)(s, a) \leq V_{\max}$. By Assumption 4.2,

$$\min_{f \in \mathcal{F}} \|f - \mathcal{T}g\|_{2, \nu}^2 \leq \epsilon_{\text{approx}, \nu}.$$

Applying the least-squares generalization bound from Lemma A.11 (square loss, bounded responses, finite $\mathcal{F}$) yields that, with probability at least $1 - \delta$, for this fixed g ,

$$\|\hat{f}_g - \mathcal{T}g\|_{2, \nu}^2 \leq \frac{22V_{\max}^2 \ln(|\mathcal{F}| / \delta)}{n} + 20 \epsilon_{\text{approx}, \nu},$$

where $\hat{f}_g$ is the ERM over $\mathcal{F}$ for targets y_i .

Now take a union bound over all $g \in \mathcal{F}$ (replacing δ by $\delta / |\mathcal{F}|$), and then a union bound over $t = 0, \dots, K - 1$ (replacing δ by δ / K). Since $f_{t+1} = \hat{f}_{f_t}$ by construction, this yields the stated bound simultaneously for all t . $\square$

Proof of Theorem 4.3. By Lemma 4.5, with probability at least $1 - \delta$, for all $t \leq K - 1$,

$$\|f_{t+1} - \mathcal{T}f_t\|_{2,\nu} \leq \sqrt{\frac{22V_{\max}^2 \ln(|\mathcal{F}|^2 K/\delta)}{n}} + \sqrt{20 \epsilon_{\text{approx},\nu}}.$$

Set

$$\varepsilon := \sqrt{\frac{22V_{\max}^2 \ln(|\mathcal{F}|^2 K/\delta)}{n}} + \sqrt{20 \epsilon_{\text{approx},\nu}}.$$

Applying Lemma 4.4 with this ε and $k = K$ gives

$$V^* - V^{\pi^K} \leq \frac{2\sqrt{C}}{(1-\gamma)^2} \left(\sqrt{\frac{22V_{\max}^2 \ln(|\mathcal{F}|^2 K/\delta)}{n}} + \sqrt{20 \epsilon_{\text{approx},\nu}} \right) + \frac{2\gamma^K V_{\max}}{1-\gamma},$$

which is exactly the theorem statement. $\square$

4.1.4 What breaks without coverage: a minimal impossibility

Assumption 4.1 is not a technical artifact of the analysis: without some form of *coverage* (overlap between the data distribution ν and the occupancy measures of relevant policies), offline RL is information-theoretically impossible. The simplest obstruction is *support mismatch*: if ν assigns zero probability to a state–action pair that an optimal (or even just a competitive) policy may visit, then the offline dataset contains *no information* about what would happen there.

We give a crisp two-action counterexample showing that without concentrability, even the most basic offline learning goal can fail.

Proposition 4.6 (No coverage $\Rightarrow$ offline RL is impossible). *There exists an offline data distribution ν and two discounted MDPs $\mathcal{M}_+$ and $\mathcal{M}_-$ such that:*

1. $\mathcal{M}_+$ and $\mathcal{M}_-$ induce exactly the same distribution over datasets $\mathcal{D}$ drawn i.i.d. from ν (hence no offline algorithm can distinguish them from $\mathcal{D}$), but
2. the optimal policies (and optimal values) differ substantially, so any offline algorithm must incur nontrivial suboptimality on at least one of the two MDPs.

In particular, for any (possibly randomized) offline algorithm $\mathcal{A}$ that maps $\mathcal{D}$ to a policy $\hat{\pi}$, we have

$$\max \left\{ \mathbb{E}_{\mathcal{D} \sim \mathcal{M}_+} [V^* - V^{\hat{\pi}}], \mathbb{E}_{\mathcal{D} \sim \mathcal{M}_-} [V^* - V^{\hat{\pi}}] \right\} \geq \frac{1}{4} V_{\max}.$$

Proof. Consider the one-state MDP with $\mathcal{S} = \{s\}$, two actions $\mathcal{A} = \{a_0, a_1\}$, deterministic self-loop dynamics $P(s | s, a) = 1$, and initial distribution $\mu(s) = 1$. Define the offline data distribution ν to put all of its mass on the single pair (s, a_0) , i.e. $\nu(s, a_0) = 1$ and $\nu(s, a_1) = 0$. Hence every offline dataset $\mathcal{D}$ consists only of samples of (s, a_0) .

Now define two reward functions (keeping the same dynamics):

$$\mathcal{M}_+ : \quad r(s, a_0) = \frac{1}{2}, \quad r(s, a_1) = 1, \quad \mathcal{M}_- : \quad r(s, a_0) = \frac{1}{2}, \quad r(s, a_1) = 0.$$

Under ν , the algorithm only ever observes rewards for (s, a_0) , which are identically $\frac{1}{2}$ in both MDPs. Therefore the distribution of $\mathcal{D}$ is *exactly the same* under $\mathcal{M}_+$ and $\mathcal{M}_-$, and any algorithm $\mathcal{A}$ induces the same distribution over outputs $\hat{\pi}$ under both MDPs.

Since $\mathcal{D}$ has the same distribution under $\mathcal{M}_+$ and $\mathcal{M}_-$, no offline algorithm can reliably tell which MDP it is in, and therefore it cannot reliably choose between a_0 and a_1 . In $\mathcal{M}_+$, choosing a_0 is suboptimal by $V_{\max}/2$ (since $V^* = V_{\max}$ but $V^{a_0} = V_{\max}/2$), while in $\mathcal{M}_-$, choosing a_1 is suboptimal by $V_{\max}/2$ (since $V^* = V_{\max}/2$ but $V^{a_1} = 0$). Consequently, any decision rule that outputs some action (possibly randomized) must incur expected suboptimality at least $V_{\max}/4$ on at least one of the two MDPs (the minimax choice is to randomize 50–50, yielding $V_{\max}/4$ in either case). $\square$

Let us connect this proposition back to concentrability. In Proposition 4.6, the policy that plays a_1 induces occupancy $d_\mu^\pi(s, a_1) = 1$, yet $\nu(s, a_1) = 0$, so the ratio $d_\mu^\pi(s, a_1)/\nu(s, a_1)$ is infinite. This is exactly the failure mode that Assumption 4.1 rules out: it enforces that whenever a policy can place mass on (s, a) , the dataset distribution must also place mass there (with a bounded density ratio).

4.2 Optional: Agnostic policy search and the horizon barrier

The previous sections focused on *discounted* offline learning with concentrability. Here we briefly switch to a *finite-horizon* lens to make a complementary point: without additional structure, even the most basic goal of selecting a near-best policy from a class can require sample sizes that are exponential in the horizon. This “horizon barrier” is the finite-horizon analogue of what goes wrong in offline RL when coverage deteriorates.

Consider a horizon- H MDP with initial distribution μ and finite action set $\mathcal{A}$. Let Π be a finite set of deterministic policies. The *agnostic objective* is

$$\max_{\pi \in \Pi} V_0^\pi(\mu),$$

i.e. compete with the best policy in the class without assuming realizability or Bellman closure.

Importance sampling gives an unbiased estimator, with $|\mathcal{A}|^H$ variance. Collect N trajectories under the behavior policy that acts uniformly at random at each step, denoted $\text{Unif}_{\mathcal{A}}$. For any deterministic π , the standard importance-sampling (IS) estimator is

$$\hat{V}_0^\pi(\mu) := \frac{1}{N} \sum_{n=1}^N w(\tau^{(n)}; \pi) \sum_{t=0}^{H-1} r_t^{(n)}, \quad w(\tau; \pi) = |\mathcal{A}|^H \mathbf{1}(\pi(s_t) = a_t \forall t),$$

which is unbiased: $\mathbb{E}[\hat{V}_0^\pi(\mu)] = V_0^\pi(\mu)$. The difficulty is that $w(\tau; \pi)$ is nonzero only when the behavior trajectory happens to match π ’s entire length- H action sequence, an event of probability $|\mathcal{A}|^{-H}$. Thus the estimator has variance that scales like $|\mathcal{A}|^H$ (up to polynomial factors in H), so concentration requires exponentially many samples.

A simple union-bound argument yields the following representative statement: with probability at least $1 - \delta$, simultaneously for all $\pi \in \Pi$,

$$\left| \hat{V}_0^\pi(\mu) - V_0^\pi(\mu) \right| \lesssim H |\mathcal{A}|^H \sqrt{\frac{\log(|\Pi|/\delta)}{N}}.$$

In particular, selecting a near-best policy in Π from this shared data requires N that is exponential in H in the worst case.

A matching lower bound (needle in a haystack). This exponential dependence is not an artifact of IS. There exist families of horizon- H MDPs (e.g. a balanced $|\mathcal{A}|$ -ary tree in which only one leaf is rewarding) for which any algorithm—even with access to a generative model—must use $\Omega(|\mathcal{A}|^H)$ samples to obtain even a constant additive optimality guarantee with nontrivial probability. Intuitively, unless the algorithm samples the rewarding path, it receives no information about where reward lies.

Taken together, these facts motivate why offline RL analyses must assume some form of overlap/coverage: without it, the effective importance weights needed to reason about candidate policies can be exponentially large, mirroring the $|\mathcal{A}|^H$ barrier in agnostic horizon- H problems.

4.3 Bibliographic Remarks and Further Readings

The notion of *concentrability* (or coverage via occupancy-measure density ratios) was introduced by Munos [2003, 2005] to obtain sharp *average-case* approximation bounds for approximate dynamic programming, under the assumption that the relevant concentrability coefficients are bounded. This line of work also supports sample-based fitted methods, with explicit finite-sample bounds, provided that the data-collection policy induces adequate coverage; see, e.g., Munos [2005], Szepesvári and Munos [2005], Antos et al. [2008], Lazaric et al. [2016]. For further discussion of concentrability-type quantities and their role in offline RL, see Chen and Jiang [2019].

The reduction of reinforcement learning to supervised learning via reusing data across policies was developed early in Kearns et al. [2000]. That work analyzed a related evaluation/selection scheme based on a “trajectory tree” view of policy behavior, and explicitly connected learnability to capacity measures of the policy class (including VC-type dimensions). Our optional agnostic-learning discussion in Section 4.2 is a stripped-down version of this theme, using importance sampling to make the exponential-in- H barrier transparent. The fundamental sample complexity tradeoff — avoiding explicit dependence on the size of the state space at the cost of exponential dependence on the horizon — is explored further in Kakade [2003].

Part II

Strategic Exploration

Chapter 5

Multi-Armed & Linear Bandits

For the case, where $\gamma = 0$ (or $H = 1$ in the undiscounted case), the problem of learning in an unknown MDP reduce to the multi-armed bandit problem. The basic algorithms and proof methodologies here are important to understand in their own right, due to that we will have to extend these with more sophisticated variants to handle the exploration-exploitation tradeoff in the more challenging reinforcement learning problem.

This chapter follows analysis of the LinUCB algorithm from the original proof in Dani et al. [2008], with a simplified concentration analysis due to Abbasi-Yadkori et al. [2011].

Throughout this chapter, we assume reward is stochastic.

5.1 The K -Armed Bandit Problem

The setting is where we have K decisions (the “arms”), where when we play arm $a \in \{1, 2, \dots, K\}$ we obtain a random reward $r_a \in [-1, 1]$ from $R(a) \in \Delta([-1, 1])$ which has mean reward:

$$\mathbb{E}_{r_a \sim R(a)}[r_a] = \mu_a$$

where it is easy to see that $\mu_a \in [-1, 1]$.

Every iteration t , the learner will pick an arm $I_t \in [1, 2, \dots, K]$. Our cumulative regret is defined as:

$$R_T = T \cdot \max_i \mu_i - \sum_{t=0}^{T-1} \mu_{I_t}$$

We denote $a^* = \operatorname{argmax}_i \mu_i$ as the optimal arm. We define gap $\Delta_a = \mu_{a^*} - \mu_a$ for any arm a .

Theorem 5.1. *There exists an algorithm such that with probability at least $1 - \delta$, we have:*

$$R_T = O \left(\min \left\{ \sqrt{KT \cdot \ln(TK/\delta)}, \sum_{a \neq a^*} \frac{\ln(TK/\delta)}{\Delta_a} \right\} + K \right).$$

5.1.1 The Upper Confidence Bound (UCB) Algorithm

We summarize the upper confidence bound (UCB) algorithm in Alg. 3. For simplicity, we allocate the first K rounds to pull each arm once.

Algorithm 3 UCB

```
1: Play each arm once and denote received reward as  $r_a$  for all  $a \in \{1, 2, \dots, K\}$ 
2: for  $t = 1 \rightarrow T - K$  do
3:   Execute arm  $I_t = \arg \max_{i \in [K]} \left( \hat{\mu}_i^t + \sqrt{\frac{\log(TK/\delta)}{N_i^t}} \right)$ 
4:   Observe  $r_t := r_{I_t}$ 
5: end for
```

where every iteration t , we maintain counts of each arm:

$$N_a^t = 1 + \sum_{i=1}^{t-1} \mathbf{1}\{I_i = a\},$$

where I_t is the index of the arm that is picked by the algorithm at iteration t . We main the empirical mean for each arm as follows:

$$\hat{\mu}_a^t = \frac{1}{N_a^t} \left(r_a + \sum_{i=1}^{t-1} \mathbf{1}\{I_i = a\} r_i \right).$$

Recall that r_a is the reward of arm a we got during the first K rounds.

We also main the upper confidence bound for each arm as follows:

$$\hat{\mu}_a^t + 2\sqrt{\frac{\ln(TK/\delta)}{N_a^t}}.$$

The following lemma shows that this is a valid upper confidence bound with high probability.

Lemma 5.2 (Upper Confidence Bound). *For all $t \in [1, \dots, T]$ and $a \in [1, 2, \dots, K]$, we have that with probability at least $1 - \delta$,*

$$|\hat{\mu}_a^t - \mu_a| \leq 2\sqrt{\frac{\ln(TK/\delta)}{N_a^t}}. \quad (5.1)$$

The proof of the above lemma uses Azuma-Hoeffding's inequality (Theorem A.5) for each arm a and iteration t and then apply a union bound over all T iterations and K arms. The reason one needs to use Azuma-Hoeffding's inequality is that here the number of trials of arm a , i.e. N_a^t , itself is a random variable while the classic Hoeffding's inequality only applies to the setting where the number of trials is a fixed number.

Proof. We first consider a fixed arm a . Let us define the following random variables, $X_0 = r_a - \mu_a$, $X_1 = \mathbf{1}\{I_1 = a\}(r_1 - \mu_a)$, $X_2 = \mathbf{1}\{I_2 = a\}(r_2 - \mu_a)$, $\dots$, $X_i = \mathbf{1}\{I_i = a\}(r_i - \mu_a)$, $\dots$.

Regarding the boundedness on these random variables, we have that for i where $\mathbf{1}\{I_i = a\} = 1$, we have $|X_i| \leq 1$, and for i where $\mathbf{1}\{I_i = a\} = 0$, we have $|X_i| = 0$. Now, consider $\mathbb{E}[X_i | \mathcal{H}_{<i}]$, where $\mathcal{H}_{<i}$ is all history up to but not including iteration i . Note that we have $\mathbb{E}[X_i | \mathcal{H}_{<i}] = 0$ since condition on history $\mathcal{H}_{<i}$, $\mathbf{1}\{I_i = a\}$ is a deterministic quantity (i.e., UCB algorithm determines whether or not to pull arm a at iteration i only based on the information from $\mathcal{H}_{<i}$). Thus, we can conclude that $\{X_i\}_{i=0}$ is a Martingale difference sequence. Via Azuma-Hoeffding's inequality, we have that with probability at least $1 - \delta$, for any fixed t , we have:

$$\left| \sum_{i=0}^{t-1} X_i \right| = |N_a^t \hat{\mu}_a^t - N_a^t \mu_a| \leq 2\sqrt{\ln(1/\delta) N_a^t},$$

where we use the fact that $\sum_{i=0}^{t-1} |X_i|^2 \leq N_a^t$. Divide N_a^t on both side, we have:

$$|\hat{\mu}_a^t - \mu_a| \leq 2\sqrt{\ln(1/\delta)/N_a^t}$$

Apply union bound over all $0 \leq t \leq T$ and $a \in \{1, \dots, K\}$, we have that with probability $1 - \delta$, for all t, a :

$$|\hat{\mu}_a^t - \mu_a| \leq 2\sqrt{\ln(1/\delta)/N_a^t} \leq 2\sqrt{\ln(TK/\delta)/N_a^t}$$

This concludes the proof. $\square$

Now we can conclude the proof of the main theorem.

Proof. Below we conditioned on the above inequality 5.1 holds. This gives us the following optimism:

$$\mu_a \leq \hat{\mu}_a^t + 2\sqrt{\frac{\ln(TK/\delta)}{N_a^t}}, \forall a, t.$$

Thus, we can upper bound the regret as follows:

$$\mu_{a^*} - \mu_{I_t} \leq \hat{\mu}_{I_t}^t + 2\sqrt{\frac{\ln(TK/\delta)}{N_{I_t}^t}} - \mu_{I_t} \leq 4\sqrt{\frac{\ln(TK/\delta)}{N_{I_t}^t}}.$$

Sum over all iterations, we get:

$$\begin{aligned} \sum_{t=0}^{T-1} \mu_{a^*} - \mu_{I_t} &\leq 4\sqrt{\ln(TK/\delta)} \sum_{t=0}^{T-1} \sqrt{\frac{1}{N_{I_t}^t}} \\ &= 4\sqrt{\ln(TK/\delta)} \sum_a \sum_{i=1}^{N_a^T} \frac{1}{\sqrt{i}} \leq 8\sqrt{\ln(TK/\delta)} \sum_a \sqrt{N_a^T} \leq 8\sqrt{\ln(TK/\delta)} \sqrt{K \sum_a N_a^T} \\ &\leq 8\sqrt{\ln(TK/\delta)} \sqrt{KT}. \end{aligned}$$

Note that our algorithm has regret K at the first K rounds.

On the other hand, if for each arm a , the gap $\Delta_a > 0$, then, we must have:

$$N_a^T \leq \frac{4\ln(TK/\delta)}{\Delta_a^2}.$$

which is because after the UCB of an arm a is below μ_{a^*} , UCB algorithm will never pull this arm a again (the UCB of a^* is no smaller than μ_{a^*}).

Thus for the regret calculation, we get:

$$\sum_{t=0}^{T-1} \mu_{a^*} - \mu_{I_t} \leq \sum_{a \neq a^*} N_a^T \Delta_a \leq \sum_{a \neq a^*} \frac{4\ln(TK/\delta)}{\Delta_a}.$$

Together with the fact that Inequality 5.1 holds with probability at least $1 - \delta$, we conclude the proof. $\square$

Algorithm 4 The Linear UCB algorithm

Input: λ, β_t

- 1: **for** $t = 0, 1 \dots$ **do**
- 2: Execute

$$x_t = \operatorname{argmax}_{x \in D} \max_{\mu \in \text{BALL}_t} \mu \cdot x$$

and observe the reward r_t .

- 3: Update BALL_{t+1} (as specified in Equation 5.2).
 - 4: **end for**
-

5.2 Linear Bandits: Handling Large Action Spaces

Let $D \subset \mathbb{R}^d$ be a compact (but otherwise arbitrary) set of decisions. On each round, we must choose a decision $x_t \in D$. Each such choice results in a reward $r_t \in [-1, 1]$.

We assume that, regardless of the history $\mathcal{H}$ of decisions and observed rewards, the conditional expectation of r_t is a fixed linear function, i.e. for all $x \in D$,

$$\mathbb{E}[r_t | x_t = x] = \mu^* \cdot x \in [-1, 1],$$

where $x \in D$ is arbitrary. Here, observe that we have assumed the mean reward for any decision is bounded in $[-1, 1]$. Under these assumptions, the *noise sequence*,

$$\eta_t = r_t - \mu^* \cdot x_t$$

is a martingale difference sequence.

The problem is essentially a bandit version of a fundamental geometric optimization problem, in which the agent's feedback on each round t is only the observed reward r_t and where the agent does not know μ^* apriori.

If $x_0, \dots, x_{T-1}$ are the decisions made in the game, then define the *cumulative regret* by

$$R_T = T\mu^* \cdot x^* - \sum_{t=0}^{T-1} \mu^* \cdot x_t$$

where $x^* \in D$ is an optimal decision for μ^* , i.e.

$$x^* \in \operatorname{argmax}_{x \in D} \mu^* \cdot x$$

which exists since D is compact. Observe that if the mean μ^* were known, then the optimal strategy would be to play x^* every round. Since the expected loss for each decision x equals $\mu^* \cdot x$, the cumulative regret is just the difference between the expected loss of the optimal algorithm and the expected loss for the actual decisions x_t . By the Hoeffding-Azuma inequality (see Lemma A.5), the observed reward $\sum_{t=0}^{T-1} r_t$ will be close to their (conditional) expectations $\sum_{t=0}^{T-1} \mu^* \cdot x_t$.

Since the sequence of decisions $x_1, \dots, x_{T-1}$ may depend on the particular sequence of random noise encountered, R_T is a random variable. Our goal in designing an algorithm is to keep R_T as small as possible.

5.2.1 The LinUCB algorithm

LinUCB is based on “optimism in the face of uncertainty,” which is described in Algorithm 4. At episode t , we use all previous experience to define an uncertainty region (an ellipse) BALL_t . The center of this region, $\hat{\mu}_t$, is the solution of

the following regularized least squares problem:

$$\begin{aligned}\hat{\mu}_t &= \arg \min_{\mu} \sum_{\tau=0}^{t-1} \|\mu \cdot x_{\tau} - r_{\tau}\|_2^2 + \lambda \|\mu\|_2^2 \\ &= \Sigma_t^{-1} \sum_{\tau=0}^{t-1} r_{\tau} x_{\tau},\end{aligned}$$

where λ is a parameter and where

$$\Sigma_t = \lambda I + \sum_{\tau=0}^{t-1} x_{\tau} x_{\tau}^{\top}, \text{ with } \Sigma_0 = \lambda I.$$

The shape of the region BALL_t is defined through the feature covariance Σ_t .

Precisely, the uncertainty region, or confidence ball, is defined as:

$$\text{BALL}_t = \left\{ \mu \mid (\hat{\mu}_t - \mu)^{\top} \Sigma_t (\hat{\mu}_t - \mu) \leq \beta_t \right\}, \quad (5.2)$$

where β_t is a parameter of the algorithm.

Computation. Suppose that we have an efficient linear optimization oracle, i.e. that we can efficiently solve the problem:

$$\max_{x \in D} \nu \cdot x$$

for any ν . Even with this, Step 2 of LinUCB may not be computationally tractable. For example, suppose that D is provided to us as a polytope, then the above oracle can be efficiently computed using linear programming, while LinUCB is an NP-hard optimization. Here, we can actually use a wider confidence region, where we can keep track of ℓ_1 ball which contains BALL_t . See Section 5.4 for further reading.

5.2.2 Upper and Lower Bounds

Our main result here is that we have sublinear regret with only a polynomial dependence on the dimension d and, importantly, no dependence on the cardinality of the decision space D , i.e. on $|D|$.

Theorem 5.3. *Suppose that the expected costs are bounded, in magnitude, by 1, i.e. that $|\mu^* \cdot x| \leq 1$ for all $x \in D$; that $\|\mu^*\| \leq W$ and $\|x\| \leq B$ for all $x \in D$; and that the noise η_t is σ^2 sub-Gaussian¹. Set*

$$\lambda = \sigma^2 / W^2, \quad \beta_t := \sigma^2 \left(2 + 4d \log \left(1 + \frac{tB^2W^2}{d} \right) + 8 \log(4/\delta) \right).$$

We have that with probability greater than $1 - \delta$, that (simultaneously) for all $T \geq 0$,

$$R_T \leq c\sigma\sqrt{T} \left(d \log \left(1 + \frac{TB^2W^2}{d\sigma^2} \right) + \log(4/\delta) \right)$$

where c is an absolute constant. In other words, we have that R_T is $\tilde{O}(d\sqrt{T})$ with high probability.

The following shows that no algorithm can (uniformly) do better.

¹Roughly, this assumes the tail probabilities of η_t decay no more slowly than a Gaussian distribution. See Definition A.2.

Theorem 5.4. (Lower bound) *There exists a distribution over linear bandit problems (i.e. a distribution over μ) with the rewards being bounded by 1, in magnitude, and $\sigma^2 \leq 1$, such that for every (randomized) algorithm, we have for $n \geq \max\{256, d^2/16\}$,*

$$\mathbb{E}_\mu \mathbb{E} R_T \geq \frac{1}{2500} d \sqrt{T}.$$

where the inner expectation is with respect to randomness in the problem and the algorithm.

We will only prove the upper bound (See Section bib:bandits).

LinUCB and D -optimal design. Let us utilize the D -optimal design to improve the dependencies in Theorem 5.3. Let Σ_D denote the D -optimal design matrix from Theorem ?? . Consider the coordinate transformation:

$$\tilde{x} = \Sigma_D^{-1/2} x, \quad \tilde{\mu}^* = \Sigma_D^{1/2} \mu^*.$$

Observe that $\tilde{\mu}^* \cdot \tilde{x} = \mu^* \cdot x$, so we still have a linear expected reward function in this new coordinate systems. Also, observe that $\|\tilde{x}\| = \|x\|_{\Sigma_D} \leq d$, which is a property of the D -optimal design, and that

$$\|\tilde{\mu}^*\| = \|\mu^*\|_{\Sigma_D} = \sqrt{(\mu^*)^\top \Sigma_D \mu^*} = \sqrt{\mathbb{E}_{x \sim \rho}[(\mu^* \cdot x)^2]} \leq 1,$$

where the last step uses our assumption that the rewards are bounded, in magnitude, by 1.

The following corollary shows that, without loss of generality, we can remove the dependencies on B and W from the previous theorem, due to that $B \leq \sqrt{d}$ and $W \leq 1$ when working under this coordinate transform.

Corollary 5.5. *Suppose that the expected costs are bounded, in magnitude, by 1, i.e. that $|\tilde{\mu}^* \cdot \tilde{x}| \leq 1$ for all $x \in D$ and that the noise η_t is σ^2 sub-Gaussian. Suppose linUCB is implemented in the $\tilde{x}$ coordinate system, as described above, with the following settings of the parameters.*

$$\lambda = \sigma^2, \quad \beta_t := \sigma^2 \left(2 + 4d \log(1+t) + 8 \log(4/\delta) \right).$$

We have that with probability greater than $1 - \delta$, that (simultaneously) for all $T \geq 0$,

$$R_T \leq c \sigma \sqrt{T} \left(d \log \left(1 + \frac{T}{\sigma^2} \right) + \log(4/\delta) \right)$$

where c is an absolute constant.

5.3 LinUCB Analysis

In establishing the upper bounds there are two main propositions from which the upper bounds follow. The first is in showing that the confidence region is appropriate.

Proposition 5.6. (Confidence) *Let $\delta > 0$. We have that*

$$\Pr(\forall t, \mu^* \in \text{BALL}_t) \geq 1 - \delta.$$

Section 5.3.2 is devoted to establishing this confidence bound. In essence, the proof seeks to understand the growth of the quantity $(\hat{\mu}_t - \mu^*)^\top \Sigma_t (\hat{\mu}_t - \mu^*)$.

The second main step in analyzing LinUCB is to show that as long as the aforementioned high-probability event holds, we have some control on the growth of the regret. Let us define

$$\text{regret}_t = \mu^* \cdot x^* - \mu^* \cdot x_t$$

which denotes the instantaneous regret.

The following bounds the sum of the squares of instantaneous regret.

Proposition 5.7. (*Sum of Squares Regret Bound*) Suppose that $\|x\| \leq B$ for $x \in D$. Suppose β_t is increasing and that $\beta_t \geq 1$. For LinUCB, if $\mu^* \in \text{BALL}_t$ for all t , then

$$\sum_{t=0}^{T-1} \text{regret}_t^2 \leq 8\beta_T d \log \left(1 + \frac{TB^2}{d\lambda} \right)$$

This is proven in Section 5.3.1. The idea of the proof involves a potential function argument on the log volume (i.e. the log determinant) of the “precision matrix” Σ_t (which tracks how accurate our estimates of μ^* are in each direction). The proof involves relating the growth of this volume to the regret.

Using these two results we are able to prove our upper bound as follows:

Proof of Theorem 5.3. By Propositions 5.6 and 5.7 along with the Cauchy-Schwarz inequality, we have, with probability at least $1 - \delta$,

$$R_T = \sum_{t=0}^{T-1} \text{regret}_t \leq \sqrt{T \sum_{t=0}^{T-1} \text{regret}_t^2} \leq \sqrt{8T\beta_T d \log \left(1 + \frac{TB^2}{d\lambda} \right)}.$$

The remainder of the proof follows from using our chosen value of β_T and algebraic manipulations (that $2ab \leq a^2 + b^2$). $\square$

We now provide the proofs of these two propositions.

5.3.1 Regret Analysis

In this section, we prove Proposition 5.7, which says that the sum of the squares of the instantaneous regrets of the algorithm is small, assuming the evolving confidence balls always contain the true mean μ^* . An important observation is that on any round t in which $\mu^* \in \text{BALL}_t$, the instantaneous regret is at most the “width” of the ellipsoid in the direction of the chosen decision. Moreover, the algorithm’s choice of decisions forces the ellipsoids to shrink at a rate that ensures that the sum of the squares of the widths is small. We now formalize this.

Unless explicitly stated, all norms refer to the ℓ_2 norm.

Lemma 5.8. Let $x \in D$. If $\mu \in \text{BALL}_t$ and $x \in D$. Then

$$|(\mu - \hat{\mu}_t)^\top x| \leq \sqrt{\beta_t x^\top \Sigma_t^{-1} x}$$

Proof. By Cauchy-Schwarz, we have:

$$\begin{aligned} |(\mu - \hat{\mu}_t)^\top x| &= |(\mu - \hat{\mu}_t)^\top \Sigma_t^{1/2} \Sigma_t^{-1/2} x| = |(\Sigma_t^{1/2} (\mu - \hat{\mu}_t))^\top \Sigma_t^{-1/2} x| \\ &\leq \|\Sigma_t^{1/2} (\mu - \hat{\mu}_t)\| \|\Sigma_t^{-1/2} x\| = \|\Sigma_t^{1/2} (\mu - \hat{\mu}_t)\| \sqrt{x^\top \Sigma_t^{-1} x} \leq \sqrt{\beta_t x^\top \Sigma_t^{-1} x} \end{aligned}$$

where the last inequality holds since $\mu \in \text{BALL}_t$. $\square$

Define

$$w_t := \sqrt{x_t^\top \Sigma_t^{-1} x_t}$$

which we interpret as the “normalized width” at time t in the direction of the chosen decision. We now see that the width, $2\sqrt{\beta_t}w_t$, is an upper bound for the instantaneous regret.

Lemma 5.9. *Fix $t \leq T$. If $\mu^* \in \text{BALL}_t$ and $\beta_t \geq 1$, then*

$$\text{regret}_t \leq 2 \min(\sqrt{\beta_t}w_t, 1) \leq 2\sqrt{\beta_T} \min(w_t, 1)$$

Proof. Let $\tilde{\mu} \in \text{BALL}_t$ denote the vector which minimizes the dot product $\tilde{\mu}^\top x_t$. By the choice of x_t , we have

$$\tilde{\mu}^\top x_t = \max_{\mu \in \text{BALL}_t} \mu^\top x_t = \max_{x \in D} \max_{\mu \in \text{BALL}_t} \mu^\top x \geq (\mu^*)^\top x^*,$$

where the inequality used the hypothesis $\mu^* \in \text{BALL}_t$. Hence,

$$\begin{aligned} \text{regret}_t &= (\mu^*)^\top x^* - (\mu^*)^\top x_t \leq (\tilde{\mu} - \mu^*)^\top x_t \\ &= (\tilde{\mu} - \hat{\mu}_t)^\top x_t + (\hat{\mu}_t - \mu^*)^\top x_t \leq 2\sqrt{\beta_t}w_t \end{aligned}$$

where the last step follows from Lemma 5.8 since $\tilde{\mu}$ and μ^* are in BALL_t . Since $r_t \in [-1, 1]$, regret_t is always at most 2 and the first inequality follows. The final inequality is due to that β_t is increasing and larger than 1. $\square$

The following two lemmas prove useful in showing that we can treat the log determinant as a potential function, where can bound the sum of widths independently of the choices made by the algorithm.

Lemma 5.10. *We have:*

$$\det \Sigma_T = \det \Sigma_0 \prod_{t=0}^{T-1} (1 + w_t^2).$$

Proof. By the definition of Σ_{t+1} , we have

$$\begin{aligned} \det \Sigma_{t+1} &= \det(\Sigma_t + x_t x_t^\top) = \det(\Sigma_t^{1/2} (I + \Sigma_t^{-1/2} x_t x_t^\top \Sigma_t^{-1/2}) \Sigma_t^{1/2}) \\ &= \det(\Sigma_t) \det(I + \Sigma_t^{-1/2} x_t (\Sigma_t^{-1/2} x_t)^\top) = \det(\Sigma_t) \det(I + v_t v_t^\top), \end{aligned}$$

where $v_t := \Sigma_t^{-1/2} x_t$. Now observe that $v_t^\top v_t = w_t^2$ and

$$(I + v_t v_t^\top) v_t = v_t + v_t (v_t^\top v_t) = (1 + w_t^2) v_t$$

Hence $(1 + w_t^2)$ is an eigenvalue of $I + v_t v_t^\top$. Since $v_t v_t^\top$ is a rank one matrix, all other eigenvalues of $I + v_t v_t^\top$ equal 1. Hence, $\det(I + v_t v_t^\top)$ is $(1 + w_t^2)$, implying $\det \Sigma_{t+1} = (1 + w_t^2) \det \Sigma_t$. The result follows by induction. $\square$

Lemma 5.11. (“Potential Function” Bound) *For any sequence $x_0, \dots, x_{T-1}$ such that, for $t < T$, $\|x_t\|_2 \leq B$, we have:*

$$\log \left(\det \Sigma_{T-1} / \det \Sigma_0 \right) = \log \det \left(I + \frac{1}{\lambda} \sum_{t=0}^{T-1} x_t x_t^\top \right) \leq d \log \left(1 + \frac{TB^2}{d\lambda} \right).$$

Proof. Denote the eigenvalues of $\sum_{t=0}^{T-1} x_t x_t^\top$ as $\sigma_1, \dots, \sigma_d$, and note:

$$\sum_{i=1}^d \sigma_i = \text{Trace} \left(\sum_{t=0}^{T-1} x_t x_t^\top \right) = \sum_{t=0}^{T-1} \|x_t\|^2 \leq TB^2.$$

Using the AM-GM inequality,

$$\begin{aligned} \log \det \left(I + \frac{1}{\lambda} \sum_{t=0}^{T-1} x_t x_t^\top \right) &= \log \left(\prod_{i=1}^d (1 + \sigma_i/\lambda) \right) \\ &= d \log \left(\prod_{i=1}^d (1 + \sigma_i/\lambda) \right)^{1/d} \leq d \log \left(\frac{1}{d} \sum_{i=1}^d (1 + \sigma_i/\lambda) \right) \leq d \log \left(1 + \frac{TB^2}{d\lambda} \right), \end{aligned}$$

which concludes the proof. $\square$

Finally, we are ready to prove that if μ^* always stays within the evolving confidence region, then our regret is under control.

Proof of Proposition 5.7. Assume that $\mu^* \in \text{BALL}_t$ for all t . We have that:

$$\begin{aligned} \sum_{t=0}^{T-1} \text{regret}_t^2 &\leq \sum_{t=0}^{T-1} 4\beta_t \min(w_t^2, 1) \leq 4\beta_T \sum_{t=0}^{T-1} \min(w_t^2, 1) \\ &\leq 8\beta_T \sum_{t=0}^{T-1} \ln(1 + w_t^2) \leq 8\beta_T \log \left(\det \Sigma_{T-1} / \det \Sigma_0 \right) = 8\beta_T d \log \left(1 + \frac{TB^2}{d\lambda} \right) \end{aligned}$$

where the first inequality follow from By Lemma 5.9; the second from that β_t is an increasing function of t ; the third uses that for $0 \leq y \leq 1$, $\ln(1 + y) \geq y/2$; the final two inequalities follow by Lemmas 5.10 and 5.11. $\square$

5.3.2 Confidence Analysis

Proof of Proposition 5.6. Since $r_\tau = x_\tau \cdot \mu^* + \eta_\tau$, we have:

$$\begin{aligned} \hat{\mu}_t - \mu^* &= \Sigma_t^{-1} \sum_{\tau=0}^{t-1} r_\tau x_\tau - \mu^* = \Sigma_t^{-1} \sum_{\tau=0}^{t-1} x_\tau (x_\tau \cdot \mu^* + \eta_\tau) - \mu^* \\ &= \Sigma_t^{-1} \left(\sum_{\tau=0}^{t-1} x_\tau (x_\tau)^\top \right) \mu^* - \mu^* + \Sigma_t^{-1} \sum_{\tau=0}^{t-1} \eta_\tau x_\tau = \lambda \Sigma_t^{-1} \mu^* + \Sigma_t^{-1} \sum_{\tau=0}^{t-1} \eta_\tau x_\tau \end{aligned}$$

For any $0 < \delta_t < 1$, using Lemma A.9, it holds with probability at least $1 - \delta_t$,

$$\begin{aligned} \sqrt{(\hat{\mu}_t - \mu^*)^\top \Sigma_t (\hat{\mu}_t - \mu^*)} &= \|(\Sigma_t)^{1/2} (\hat{\mu}_t - \mu^*)\| \\ &\leq \left\| \lambda \Sigma_t^{-1/2} \mu^* \right\| + \left\| \Sigma_t^{-1/2} \sum_{\tau=0}^{t-1} \eta_\tau x_\tau \right\| \\ &\leq \sqrt{\lambda} \|\mu^*\| + \sqrt{2\sigma^2 \log(\det(\Sigma_t) \det(\Sigma_0)^{-1} / \delta_t)}. \end{aligned}$$

where we have also used the triangle inequality and that $\|\Sigma_t^{-1}\| \leq 1/\lambda$.

We seek to lower bound $\Pr(\forall t, \mu^* \in \text{BALL}_t)$. Note that at $t = 0$, by our choice of λ , we have that BALL_0 contains W^* , so $\Pr(\mu^* \notin \text{BALL}_0) = 0$. For $t \geq 1$, let us assign failure probability $\delta_t = (3/\pi^2)/t^2 \delta$ for the t -th event, which, using the above, gives us an upper bound on the sum failure probability as

$$1 - \Pr(\forall t, \mu^* \in \text{BALL}_t) = \Pr(\exists t, \mu^* \notin \text{BALL}_t) \leq \sum_{t=1}^{\infty} \Pr(\mu^* \notin \text{BALL}_t) < \sum_{t=1}^{\infty} (1/t^2)(3/\pi^2)\delta = \delta/2.$$

This along with Lemma 5.11 completes the proof. $\square$

5.4 Bibliographic Remarks and Further Readings

The original multi-armed bandit model goes back to Robbins [1952]. The linear bandit model was first introduced in Abe and Long [1999]. Our analysis of the LinUCB algorithm follows from the original proof in Dani et al. [2008], with a simplified concentration analysis due to Abbasi-Yadkori et al. [2011]. The first sublinear regret bound here was due to Auer et al. [2002], which used a more complicated algorithm.

The lower bound we present is also due to Dani et al. [2008], which also shows that LinUCB is minimax optimal.

Chapter 6

Strategic Exploration in Tabular MDPs

We now turn to how an agent acting in an unknown MDP can obtain a near-optimal reward over time. Compared with the previous setting with access to a generative model, we no longer have easy access to transitions at each state, but only have the ability to execute trajectories in the MDP. The main complexity this adds to the learning process is that the agent has to engage in exploration, that is, plan to reach new states where enough samples have not been seen yet, so that optimal behavior in those states can be learned.

We will work with finite-horizon MDPs with a fixed start state s_0 (see Section 1.2), and we will assume the agent learns in an episodic setting, as introduced in Chapter 2. Here, in every episode k , the learner acts for H step starting from a fixed starting state s_0 and, at the end of the H -length episode, the state is reset to s_0 . It is straightforward to extend this setting where the starting state is sampled from a distribution, i.e. $s_0 \sim \mu$.

The goal of the agent is to minimize her expected cumulative regret over K episodes:

$$\text{Regret} := \mathbb{E} \left[KV^*(s_0) - \sum_{k=0}^{K-1} \sum_{h=0}^{H-1} r(s_h^k, a_h^k) \right],$$

where the expectation is with respect to the randomness of the MDP environment and, possibly, any randomness of the agent's strategy.

This chapter considers tabular MDPs, where $\mathcal{S}$ and $\mathcal{A}$ are discrete. We will now present a (nearly) sublinear regret algorithm, UCB-Value Iteration. This chapter follows the proof in Azar et al. [2017]. We first give a simplified analysis of UCB-VI that gives a regret bound in the order of $H^2 S \sqrt{AK}$, followed by a more refined analysis that gives a $H^2 \sqrt{SAK} + H^3 S^2 A$ regret bound.

6.1 On The Need for Strategic Exploration

Consider the chain MDP of length $H + 2$ shown in Figure 10.1. The starting state of interest is state s_0 . We consider a uniformly random policy $\pi_h(s)$ that at any time step h and any state s , selects an action from all A many actions uniform randomly. It is easy to see that starting from s_0 , the probability of such uniform random policy hitting the rewarding state s_{H+1} is exponentially small, i.e., $O(A^H)$, since it needs to select the right action that moves one step right at every time step h . This example demonstrates that we need to perform strategic exploration in order to avoid the exponential sample complexity.




Figure 6.1: A deterministic, chain MDP of length $H + 2$. Rewards are 0 everywhere other than $r(s_{H+1}, a_1) = 1$. In this example we have $A = 4$.

Algorithm 5 UCBVI

Input: reward function r (assumed to be known), confidence parameters

- 1: **for** $k = 0 \dots K - 1$ **do**
 - 2: Compute $\hat{P}_h^k$ as the empirical estimates, for all h (Eq. 6.1)
 - 3: Compute reward bonus b_h^k for all h (Eq. 6.2)
 - 4: Run Value-Iteration on $\{\hat{P}_h^k, r + b_h^k\}_{h=0}^{H-1}$ (Eq. 6.3)
 - 5: Set π^k as the returned policy of VI.
 - 6: **end for**
-

6.2 The UCB-VI algorithm

If the learner then executes π^k in the underlying MDP to generate a single trajectory $\tau^k = \{s_h^k, a_h^k\}_{h=0}^{H-1}$ with $a_h = \pi_h^k(s_h^k)$ and $s_{h+1}^k \sim P_h(\cdot | s_h^k, a_h^k)$. We first define some notations below. Consider the very beginning of episode k . We use the history information up to the end of episode $k - 1$ (denoted as $\mathcal{H}_{<k}$) to form some statistics. Specifically, we define:

$$N_h^k(s, a, s') = \sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i, s_{h+1}^i) = (s, a, s')\},$$

$$N_h^k(s, a) = \sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\}, \forall h, s, a.$$

Namely, we maintain counts of how many times s, a, s' and s, a are visited at time step h from the beginning of the learning process to the end of the episode $k - 1$. We use these statistics to form an empirical model:

$$\hat{P}_h^k(s' | s, a) = \frac{N_h^k(s, a, s')}{N_h^k(s, a)}, \forall h, s, a, s'. \quad (6.1)$$

We will also use the counts to define a *reward bonus*, denoted as $b_h(s, a)$ for all h, s, a . Denote $L := \ln(SAHK/\delta)$ (δ as usual represents the failure probability which we will define later). We define reward bonus as follows:

$$b_h^k(s, a) = 2H \sqrt{\frac{L}{N_h^k(s, a)}}. \quad (6.2)$$

With reward bonus and the empirical model, the learner uses *Value Iteration* on the empirical transition $\hat{P}_h^k$ and the combined reward $r_h + b_h^k$. Starting at H (note that H is a fictitious extra step as an episode terminates at $H - 1$), we

perform dynamic programming all the way to $h = 0$:

$$\begin{aligned}\widehat{V}_H^k(s) &= 0, \forall s, \\ \widehat{Q}_h^k(s, a) &= \min \left\{ r_h(s, a) + b_h^k(s, a) + \widehat{P}_h^k(\cdot|s, a) \cdot \widehat{V}_{h+1}^k, H \right\}, \\ \widehat{V}_h^k(s) &= \max_a \widehat{Q}_h^k(s, a), \pi_h^k(s) = \operatorname{argmax}_a \widehat{Q}_h^k(s, a), \forall h, s, a.\end{aligned}\tag{6.3}$$

Note that when using $\widehat{V}_{h+1}^k$ to compute $\widehat{Q}_h^k$, we truncate the value by H . This is because we know that due to the assumption that $r(s, a) \in [0, 1]$, no policy's Q value will ever be larger than H .

Denote $\pi^k = \{\pi_0^k, \dots, \pi_{H-1}^k\}$. Learner then executes π^k in the MDP to get a new trajectory τ^k .

UCBVI repeats the above procedure for K episodes.

6.3 Analysis

We will prove the following theorem.

Theorem 6.1 (Regret Bound of UCBVI). *UCBVI achieves the following regret bound:*

$$\text{Regret} := \mathbb{E} \left[\sum_{k=0}^{K-1} \left(V^*(s_0) - V^{\pi^k}(s_0) \right) \right] \leq 10H^2 S \sqrt{AK \cdot \ln(SAH^2K^2)} = \tilde{O} \left(H^2 S \sqrt{AK} \right)$$

Remark While the above regret is sub-optimal, the algorithm we presented here indeed achieves a sharper bound in the leading term $\tilde{O}(H^2 \sqrt{SAK})$ [Azar et al., 2017], which gives the tight dependency bound on S, A, K . In Section 6.4, we will present a refined analysis that indeed achieves $H^2 \sqrt{SAK}$ regret. The dependency on H is not tight and tightening the dependency on H requires modifications to the reward bonus (use Bernstein inequality rather than Hoeffding's inequality for reward bonus design).

We prove the above theorem in this section.

We start with bounding the error from the learned model $\widehat{P}_h^k$.

Lemma 6.2 (State-action wise model error). *Fix $\delta \in (0, 1)$. For all $k \in [0, \dots, K-1], s \in \mathcal{S}, a \in \mathcal{A}, h \in [0, \dots, H-1]$, with probability at least $1 - \delta$, we have that for any $f : \mathcal{S} \mapsto [0, H]$:*

$$\left| \left(\widehat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a) \right)^\top f \right| \leq 8H \sqrt{\frac{S \ln(SAHK/\delta)}{N_h^k(s, a)}}.$$

Remark The proof of the above lemma requires a careful argument using Martingale difference sequence mainly because $N_h^k(s, a)$ itself is a random quantity. We give a proof the above lemma at the end of this section (Sec. 6.3.1). Using the above lemma will result a sub-optimal regret bound in terms of the dependence on S . In Section 6.4, we will give a different approach to bound $\left| \left(\widehat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a) \right)^\top f \right|$ which leads to an improved regret bound.

The following lemma is still about model error, but this time we consider an average model error with respect to V^* — a deterministic quantity.

Lemma 6.3 (State-action wise average model error under V^*). *Fix $\delta \in (0, 1)$. For all $k \in [1, \dots, K-1]$, $s \in \mathcal{S}$, $a \in \mathcal{A}$, $h \in [0, \dots, H-1]$, and consider $V_h^* : \mathcal{S} \rightarrow [0, H]$, with probability at least $1 - \delta$, we have:*

$$\left| \hat{P}_h^k(\cdot | s, a) \cdot V_{h+1}^* - P_h^*(\cdot | s, a) \cdot V_{h+1}^* \right| \leq 2H \sqrt{\frac{\ln(SAHN/\delta)}{N_h^k(s, a)}}.$$

Note that we can use Lemma 6.2 to bound $\left| \hat{P}_h^k(\cdot | s, a) \cdot V_{h+1}^* - P_h^*(\cdot | s, a) \cdot V_{h+1}^* \right|$. However, the above lemma shows that by leveraging the fact that V^* is a deterministic quantity (i.e., independent of the data collected during learning), we can get a tighter upper bound which does not scale polynomially with respect to S .

Proof. Consider a fixed tuple s, a, k, h first. By the definition of $\hat{P}_h^k$, we have:

$$\hat{P}_h^k(\cdot | s, a) \cdot V_{h+1}^* = \frac{1}{N_h^k(s, a)} \sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\} V_{h+1}^*(s_{h+1}^i).$$

Now denote $\mathcal{H}_{h,i}$ as the entire history from $t = 0$ to iteration $t = i$ where in iteration i , $\mathcal{H}_{h,i}$ includes history from time step 0 up to and including time step h . We define random variables: $X_i = \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\} V_{h+1}^*(s_{h+1}^i) - \mathbb{E}[\mathbf{1}\{(s_h^i, a_h^i) = (s, a)\} V_{h+1}^*(s_{h+1}^i) | \mathcal{H}_{h,i}]$ for $i = 0, \dots, K-1$. These random variables have the following properties. First $|X_i| \leq H$ if $\mathbf{1}\{(s_h^i, a_h^i) = (s, a)\} = 1$, else $|X_i| = 0$, which implies that $\sum_{i=0}^k |X_i|^2 \leq N_h^k(s, a)$. Also we have $\mathbb{E}[X_i | \mathcal{H}_{h,i}] = 0$ for all i . Thus, $\{X_i\}_{i \geq 0}$ is a Martingale difference sequence. Using Azuma-Hoeffding's inequality, we get that for any fixed k , with probability at least $1 - \delta$,

$$\left| \sum_{i=0}^{k-1} X_i \right| = \left| \sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\} V_{h+1}^*(s_{h+1}^i) - N_h^k(s, a) \mathbb{E}_{s' \sim P_h^*(s, a)} V^*(s') \right| \leq 2H \sqrt{N_h^k(s, a) \ln(1/\delta)}.$$

Divide $N_h^k(s, a)$ on both sides and use the definition of $\hat{P}_h^k(\cdot | s, a)^\top V_{h+1}^*$, we get:

$$\left| \hat{P}_h^k(\cdot | s, a)^\top V_{h+1}^* - P_h^*(\cdot | s, a)^\top V_{h+1}^* \right| \leq 2H \sqrt{\ln(1/\delta) / N_h^k(s, a)}.$$

With a union bound over all $s \in \mathcal{S}, a \in \mathcal{A}, k \in [N], h \in [H]$, we conclude the proof. $\square$

We denote the two inequalities in Lemma 6.2 and Lemma 6.3 as event $\mathcal{E}_{model}$. Note that the failure probability of $\mathcal{E}_{model}$ is at most 2δ . Below we condition on $\mathcal{E}_{model}$ being true (we deal with failure event at the very end).

Now we study the effect of reward bonus. Similar to the idea in multi-armed bandits, we want to pick a policy π^k , such that the value of π^k in under the combined reward $r_h + b_h^k$ and the empirical model $\hat{P}_h^k$ is optimistic, i.e., we want $\hat{V}_0^k(s_0) \geq V_0^*(s_0)$ for all s_0 . The following lemma shows that via reward bonus, we are able to achieve this optimism.

Lemma 6.4 (Optimism). *Assume $\mathcal{E}_{model}$ is true. For all episode k , we have:*

$$\hat{V}_0^k(s_0) \geq V_0^*(s_0), \forall s_0 \in \mathcal{S};$$

where $\hat{V}_h^k$ is computed based on VI in Eq. 6.3.

Proof. We prove via induction. At the additional time step H we have $\hat{V}_H^k(s) = V_H^*(s) = 0$ for all s .

Starting at $h+1$, and assuming we have $\hat{V}_{h+1}^k(s) \geq V_{h+1}^*(s)$ for all s , we move to h below.

Consider any $s, a \in \mathcal{S} \times \mathcal{A}$. First, if $Q_h^k(s, a) = H$, then we have $Q_h^k(s, a) \geq Q_h^*(s, a)$.

$$\begin{aligned}\widehat{Q}_h^k(s, a) - Q_h^*(s, a) &= b_h^k(s, a) + \widehat{P}_h^k(\cdot|s, a) \cdot \widehat{V}_{h+1}^k - P_h^*(\cdot|s, a) \cdot V_{h+1}^* \\ &\geq b_h^k(s, a) + \widehat{P}_h^k(\cdot|s, a) \cdot V_{h+1}^* - P_h^*(\cdot|s, a) \cdot V_{h+1}^* \\ &= b_h^k(s, a) + \left(\widehat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a) \right) \cdot V_{h+1}^* \\ &\geq b_h^k(s, a) - 2H \sqrt{\frac{\ln(SAHK/\delta)}{N_h^k(s, a)}} \geq 0.\end{aligned}$$

where the first inequality is from the inductive hypothesis, and the last inequality uses Lemma 6.3 and the definition of bonus.

From $\widehat{Q}_h^k$, one can finish the proof by showing $\widehat{V}_h^k(s) \geq V_h^*(s), \forall s$. □

Before we prove our final result, one more technical lemma will be helpful:

Lemma 6.5. Consider arbitrary K sequence of trajectories $\tau^k = \{s_h^k, a_h^k\}_{h=0}^{H-1}$ for $k = 0, \dots, K-1$. We have

$$\sum_{k=0}^{K-1} \sum_{h=0}^{H-1} \frac{1}{\sqrt{N_h^k(s_h^k, a_h^k)}} \leq 2H\sqrt{SAK}.$$

Proof. We swap the order of the two summation above:

$$\begin{aligned}\sum_{k=0}^{K-1} \sum_{h=0}^{H-1} \frac{1}{\sqrt{N_h^k(s_h^k, a_h^k)}} &= \sum_{h=0}^{H-1} \sum_{k=0}^{K-1} \frac{1}{\sqrt{N_h^k(s_h^k, a_h^k)}} = \sum_{h=0}^{H-1} \sum_{s, a \in \mathcal{S} \times \mathcal{A}} \sum_{i=1}^{N_h^K(s, a)} \frac{1}{\sqrt{i}} \\ &\leq 2 \sum_{h=0}^{H-1} \sum_{s, a \in \mathcal{S} \times \mathcal{A}} \sqrt{N_h^K(s, a)} \leq \sum_{h=0}^{H-1} \sqrt{SA \sum_{s, a} N_h^K(s, a)} = H\sqrt{SAK},\end{aligned}$$

where in the first inequality we use the fact that $\sum_{i=1}^N 1/\sqrt{i} \leq 2\sqrt{N}$, and in the second inequality we use CS inequality. □

The proof of our main theorem now follows:

Proof of Theorem 6.1. Let us consider episode k and denote $\mathcal{H}_{<k}$ as the history up to the end of episode $k-1$. We consider bounding $V^* - V^{\pi^k}$. Using optimism and the simulation lemma, we can get the following result:

$$V^*(s_0) - V^{\pi^k}(s_0) \leq \widehat{V}_0^k(s_0) - V_0^{\pi^k}(s_0) \leq \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} \left[b_h^k(s_h, a_h) + \left(\widehat{P}_h^k(\cdot|s_h, a_h) - P^*(\cdot|s_h, a_h) \right) \cdot \widehat{V}_{h+1}^{\pi^k} \right] \quad (6.4)$$

We prove the above two inequalities in the lecture. We leave the proof of the above inequality (Eq 6.4) as an exercise for readers. Note that this is slightly different from the usual simulation lemma, as here we truncate $\widehat{V}$ by H during VI.

Under $\mathcal{E}_{model}$, we can bound $\left(\widehat{P}_h^k(\cdot|s_h, a_h) - P^*(\cdot|s_h, a_h) \right) \cdot \widehat{V}_{h+1}^{\pi^k}$ (recall Lemma 6.2) with a Holder's inequality:

$$\begin{aligned}\left| \left(\widehat{P}_h^k(\cdot|s_h, a_h) - P^*(\cdot|s_h, a_h) \right) \cdot \widehat{V}_{h+1}^{\pi^k} \right| &\leq \left\| \widehat{P}_h^k(\cdot|s_h, a_h) - P^*(\cdot|s_h, a_h) \right\|_1 \left\| \widehat{V}_{h+1}^{\pi^k} \right\|_\infty \\ &\leq 8H \sqrt{\frac{SL}{N_h^k(s, a)}},\end{aligned}$$

where recall $L := \ln(SAKH/\delta)$. Hence, for the per-episode regret $V^*(s_0) - V^{\pi^k}(s_0)$, we obtain:

$$\begin{aligned} V^*(s_0) - V^{\pi^k}(s_0) &\leq \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} \left[b_h^k(s_h, a_h) + 8H \sqrt{SL/N_h^k(s_h, a_h)} \right] \\ &\leq \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} \left[10H \sqrt{SL/N_h^k(s_h, a_h)} \right] \\ &= 10H \sqrt{SL} \cdot \mathbb{E} \left[\sum_{h=0}^{H-1} \frac{1}{\sqrt{N_h^k(s_h^k, a_h^k)}} \middle| \mathcal{H}_{<k} \right], \end{aligned}$$

where in the last term the expectation is taken with respect to the trajectory $\{s_h^k, a_h^k\}$ (which is generated from π^k) while conditioning on all history $\mathcal{H}_{<k}$ up to and including the end of episode $k-1$.

Now we sum all episodes together and take the failure event into consideration:

$$\begin{aligned} \mathbb{E} \left[\sum_{k=0}^{K-1} V^*(s_0) - V^{\pi^k}(s_0) \right] &= \mathbb{E} \left[\mathbf{1}\{\mathcal{E}_{model}\} \left(\sum_{k=0}^{K-1} V^*(s_0) - V^{\pi^k}(s_0) \right) \right] + \mathbb{E} \left[\mathbf{1}\{\bar{\mathcal{E}}_{model}\} \left(\sum_{k=0}^{K-1} V^*(s_0) - V^{\pi^k}(s_0) \right) \right] \\ &\leq \mathbb{E} \left[\mathbf{1}\{\mathcal{E}_{model}\} \left(\sum_{k=0}^{K-1} V^*(s_0) - V^{\pi^k}(s_0) \right) \right] + 2\delta KH \quad (6.5) \\ &\leq 10H \sqrt{S \ln(SAHK/\delta)} \mathbb{E} \left[\sum_{k=0}^{K-1} \sum_{h=0}^{H-1} \frac{1}{\sqrt{N_h^k(s_h^k, a_h^k)}} \right] + 2\delta KH, \end{aligned}$$

where the last inequality uses the law of total expectation.

We can bound the double summation term above using lemma 6.5. We can conclude that:

$$\mathbb{E} \left[\sum_{k=0}^{K-1} V^*(s_0) - V^{\pi^k}(s_0) \right] \leq 10H^2 S \sqrt{AK \ln(SAHK/\delta)} + 2\delta KH.$$

Now set $\delta = 1/KH$, we get:

$$\mathbb{E} \left[\sum_{k=0}^{K-1} V^*(s_0) - V^{\pi^k}(s_0) \right] \leq 10H^2 S \sqrt{AK \ln(SAH^2 K^2)} + 2 = O \left(H^2 S \sqrt{AK \ln(SAH^2 K^2)} \right).$$

This concludes the proof of Theorem 6.1. □

6.3.1 Proof of Lemma 6.2

Here we include a proof of Lemma 6.2. The proof consists of two steps, first we use Martingale concentration to bound $|(\hat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a))^\top f|$ for all s, a, h, k , but for a fixed $f : \mathcal{S} \mapsto [0, H]$. Note that there are infinitely many such f that maps from $\mathcal{S}$ to $[0, H]$. Thus, the second step is to use a covering argument (i.e., ϵ -net on all $\{f : \mathcal{S} \mapsto [0, H]\}$) to show that $|(\hat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a))^\top f|$ is bounded for all s, a, h, k , and all $f : \mathcal{S} \mapsto [0, H]$.

Proof of Lemma 6.2. We consider a fixed tuple s, a, k, h, f first. Recall the definition of $\hat{P}_h^k(s, a)$, and we have: $\hat{P}_h^k(\cdot|s, a)^\top f = \sum_{i=0}^{k-1} \mathbf{1}\{s_h^i, a_h^i = s, a\} f(s_{h+1}^i) / N_h^k(s, a)$.

Define $\mathcal{H}_{h,i}$ as the history starting from the beginning of iteration 0 all the way up to and include time step h at iteration i . Define random variables X_i as $X_i = \mathbf{1}\{s_h^i, a_h^i = s, a\}f(s_{h+1}^i) - \mathbf{1}\{s_h^i, a_h^i = s, a\}\mathbb{E}_{s' \sim P_h^*(s,a)}f(s')$. We now show that $\{X_i\}$ is a Martingale difference sequence. First we have $\mathbb{E}[X_i | \mathcal{H}_{h,i}] = 0$, since $\mathbf{1}\{s_h^i, a_h^i = s, a\}$ is a deterministic quantity given $\mathcal{H}_{h,i}$. Second, we have $|X_i| = 0$ for $(s_h^i, a_h^i) \neq (s, a)$, and $|X_i| \leq H$ when $(s_h^i, a_h^i) = (s, a)$. Thus, we have shown that it is a Martingale difference sequence.

Now we can apply Azuma-Hoeffding's inequality (Theorem A.5). With probability at least $1 - \delta$, we have:

$$\left| \sum_{i=0}^{k-1} X_i \right| = \left| \sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\}f(s_{h+1}^i) - N_h^k(s, a)\mathbb{E}_{s' \sim P_h^*(s,a)}f(s') \right| \leq 2H\sqrt{N_h^k(s, a) \ln(1/\delta)}.$$

Now apply union bound over all $s \in \mathcal{S}, a \in \mathcal{A}, h \in [0, \dots, H-1], k \in [0, \dots, K-1]$, we have that with probability at least $1 - \delta$, for all s, a, h, k , we have:

$$\left| \sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\}f(s_{h+1}^i) - N_h^k(s, a)\mathbb{E}_{s' \sim P_h^*(s,a)}f(s') \right| \leq 2H\sqrt{N_h^k(s, a) \ln(SAKH/\delta)}. \quad (6.6)$$

Note that the above result only holds for the fixed f that we specified at the beginning of the proof. We are left to perform a covering argument over all functions that map from $\mathcal{S}$ to $[0, H]$. We use a standard ϵ -net argument for that. We abuse notation a bit and denote f as a vector in $[0, H]^S$.

Note that $\|f\|_2 \leq H\sqrt{S}$ for any $f : \mathcal{S} \mapsto [0, H]$. A standard ϵ -net argument shows that we can construct an ϵ -net $\mathcal{N}_\epsilon$ over $[0, H]^S$ with $|\mathcal{N}_\epsilon| \leq (1 + 2H\sqrt{S}/\epsilon)^S$, such that for any $f \in [0, H]^S$, there exists a point $f' \in \mathcal{N}_\epsilon$, such that $\|f - f'\|_2 \leq \epsilon$. Note that the ϵ -net $\mathcal{N}_\epsilon$ is independent of the training data during the learning process.

Now using Eq. 6.6 and a union bound over all f in $\mathcal{N}_\epsilon$, we have that with probability at least $1 - \delta$, for all $s, a, k, h, f \in \mathcal{N}_\epsilon$, we have:

$$\left| \frac{\sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\}f(s_{h+1}^i)}{N_h^k(s, a)} - \mathbb{E}_{s' \sim P_h^*(s,a)}f(s') \right| \leq 2H\sqrt{\frac{S \ln(SAKH(1 + 2H\sqrt{S}/\epsilon)/\delta)}{N_h^k(s, a)}}.$$

Finally, for any $f \in [0, H]^S$, denote its closest point in $\mathcal{N}_\epsilon$ as f' , we have:

$$\begin{aligned} & \left| \frac{\sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\}f(s_{h+1}^i)}{N_h^k(s, a)} - \mathbb{E}_{s' \sim P_h^*(s,a)}f(s') \right| \\ & \leq \left| \frac{\sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\}f'(s_{h+1}^i)}{N_h^k(s, a)} - \mathbb{E}_{s' \sim P_h^*(s,a)}f'(s') \right| + \left| \frac{\sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\}(f(s_{h+1}^i) - f'(s_{h+1}^i))}{N_h^k(s, a)} \right| \\ & \quad + \left| \mathbb{E}_{s' \sim P_h^*(s,a)}(f(s') - f'(s')) \right| \\ & \leq 2H\sqrt{\frac{S \ln(SAKH(1 + 2H\sqrt{S}/\epsilon)/\delta)}{N_h^k(s, a)}} + 2\epsilon, \end{aligned}$$

where in the last inequality we use the fact that if $\|f - f'\|_2 \leq \epsilon$, then $|f(s) - f'(s)| \leq \epsilon, \forall s \in \mathcal{S}$.

Now we can set $\epsilon = 1/K$ and use the fact that $N_h^k(s, a) \leq K$, we have:

$$\begin{aligned} & \left| \frac{\sum_{i=0}^{k-1} \mathbf{1}\{(s_h^i, a_h^i) = (s, a)\}f(s_{h+1}^i)}{N_h^k(s, a)} - \mathbb{E}_{s' \sim P_h^*(s,a)}f(s') \right| \leq 2H\sqrt{\frac{S \ln(SAKH(1 + 2HK\sqrt{S}/\delta))}{N_h^k(s, a)}} + \frac{2}{K} \\ & \leq 4H\sqrt{\frac{S \ln(4H^2S^2K^2A/\delta)}{N_h^k(s, a)}} \leq 8H\sqrt{\frac{S \ln(HSKA/\delta)}{N_h^k(s, a)}}, \end{aligned}$$

where the last inequality uses the simple inequality $\ln(4H^2S^2K^2A) \leq 4\ln(HSKA)$. This concludes the proof. $\square$

6.4 An Improved Regret Bound

In this section, we show that UCB-VI also enjoys the regret bound $\tilde{O}\left(H^2\sqrt{SAK} + H^3S^2A\right)$.

Theorem 6.6 (Improved Regret Bound for UCB-VI). *The total expected regret is bounded as follows:*

$$\begin{aligned} \mathbb{E} \left[KV^*(s_0) - \sum_{k=0}^{K-1} V^{\pi^k}(s_0) \right] \\ \leq 8eH^2\sqrt{SAK} \cdot \sqrt{\ln(SAH^2K^2)} + 2eH^3S^2A \cdot \ln(K) \ln(SAH^2K^2) = \tilde{O}\left(H^2\sqrt{SAK} + H^3S^2A\right). \end{aligned}$$

Note that comparing to the regret bound we had in the previous section, this new regret improves the S dependence in the leading order term (i.e., the term that contains $\sqrt{K}$), but at the cost of introducing a lower order term H^3S^2A .

We first give an improved version of the model error presented in Lemma 6.2.

Lemma 6.7. *With probability at least $1 - \delta$, for all h, k, s, a , and all $f : \mathcal{S} \mapsto [0, H]$, we have:*

$$\left| \left(\hat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a) \right)^\top f \right| \leq \frac{\mathbb{E}_{s' \sim P_h^*(\cdot|s, a)} f(s')}{H} + \frac{3H^2SL}{N_h^k(s, a)}.$$

Below we prove this lemma. Recall the definition of $\hat{P}_h^k(s'|s, a)$ in Eq. 6.1. We can use Azume-Bernstein's inequality to bound $|\hat{P}_h^k(s'|s, a) - P_h^*(s'|s, a)|$.

Lemma 6.8. *With probability at least $1 - \delta$, for all s, a, k, h , we have:*

$$\left| \hat{P}_h^k(s'|s, a) - P_h^*(s'|s, a) \right| \leq \sqrt{\frac{2P_h^*(s'|s, a)L}{N_h^k(s, a)}} + \frac{2L}{N_h^k(s, a)},$$

where $L := \ln(SAKH/\delta)$.

Proof. Consider a fixed tuple (s, a, h, k) . Define $\mathcal{H}_{h,i}$ as the history starting from the beginning of iteration 0 to time step h at iteration i (including step h , i.e., up to s_h^i, a_h^i). Define random variables $\{X_i\}_{i \geq 0}$ as $X_i = \mathbf{1}\{s_h^i, a_h^i, s_{h+1}^i = s, a, s'\} - \mathbf{1}\{s_h^i, a_h^i = s, a\}P_h^*(s'|s, a)$. We now show that $\{X_i\}$ is a Martingale difference sequence. Note that $\mathbb{E}[X_i|\mathcal{H}_{h,i}] = 0$. We have $|X_i| \leq 1$. To use Azuma-Bernstein's inequality, we note that $\mathbb{E}[X_i^2|\mathcal{H}_{h,i}]$ is bounded as:

$$\mathbb{E}[X_i^2|\mathcal{H}_{h,i}] = \mathbf{1}\{s_h^i, a_h^i = s, a\}P_h^*(s'|s, a)(1 - P_h^*(s'|s, a)),$$

where we use the fact that the variance of a Bernoulli with parameter p is $p(1-p)$. This means that $\sum_{i=0}^{k-1} \mathbb{E}[X_i^2|\mathcal{H}_{h,i}] = P_h^*(s'|s, a)(1 - P_h^*(s'|s, a))N_h^k(s, a)$. Now apply Bernstein's inequality on the martingale difference sequence $\{X_i\}$, we have:

$$\begin{aligned} \left| \sum_{i=0}^{k-1} X_i \right| &\leq \sqrt{\frac{2P_h^*(s'|s, a)(1 - P_h^*(s'|s, a)) \ln(1/\delta)}{N_h^k(s, a)}} + \frac{2 \ln(1/\delta)}{N_h^k(s, a)} \\ &\leq \sqrt{\frac{2P_h^*(s'|s, a) \ln(1/\delta)}{N_h^k(s, a)}} + \frac{2 \ln(1/\delta)}{N_h^k(s, a)} \end{aligned}$$

Recall the definition of $L := \ln(SAHK/\delta)$. Apply a union bound over all $s \in \mathcal{S}, a \in \mathcal{A}, h \in [0, \dots, H-1], k \in [0, \dots, K-1]$, we conclude the proof. $\square$

Now we are ready to prove Lemma 6.7.

Proof of Lemma 6.7. Let us condition on the event in Lemma 6.8 being true, of which the probability is at least $1 - \delta$.

Take any function $f : \mathcal{S} \mapsto [0, H]$, we have:

$$\begin{aligned}
& \left| \left(\hat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a) \right)^\top f \right| \\
& \leq \sum_{s' \in \mathcal{S}} \left| \hat{P}_h^k(s'|s, a) - P_h^*(s'|s, a) \right| f(s') \leq \sum_{s' \in \mathcal{S}} \sqrt{\frac{2LP_h^*(s'|s, a)f^2(s')}{N_h^k(s, a)}} + \sum_{s' \in \mathcal{S}} \frac{2Lf(s')}{N_h^k(s, a)} \\
& \leq \sum_{s' \in \mathcal{S}} \sqrt{\frac{2LP_h^*(s'|s, a)f^2(s')}{N_h^k(s, a)}} + \frac{2SHL}{N_h^k(s, a)} \leq \sqrt{S} \sqrt{\frac{\sum_{s' \in \mathcal{S}} 2LP_h^*(s'|s, a)f^2(s')}{N_h^k(s, a)}} + \frac{2SHL}{N_h^k(s, a)} \\
& = \sqrt{\frac{2H^2SL}{N_h^k(s, a)} \cdot \frac{\sum_{s' \in \mathcal{S}} P_h^*(s'|s, a)f^2(s')}{H^2}} + \frac{2SHL}{N_h^k(s, a)} \leq \frac{H^2SL}{N_h^k(s, a)} + \frac{\mathbb{E}_{s' \sim P_h^*(\cdot|s, a)} f^2(s')}{H^2} + \frac{2SHL}{N_h^k(s, a)} \\
& \leq \frac{\mathbb{E}_{s' \sim P_h^*(\cdot|s, a)} f(s')}{H} + \frac{H^2SL}{N_h^k(s, a)} + \frac{2SHL}{N_h^k(s, a)},
\end{aligned}$$

where the third inequality uses that condition that $\|f\|_\infty \leq H$, the fourth inequality uses Cauchy-Schwarz inequality, the fifth inequality uses the inequality that $ab \leq (a^2 + b^2)/2$ for any real numbers a and b , and the last inequality uses the condition that $\|f\|_\infty \leq H$ again. This concludes the proof. $\square$

So far in Lemma 6.7, we have not specify what function f we will use. The following lemma instantiate f to be $\hat{V}_{h+1}^k - V_{h+1}^*$. Recall the bonus definition, $b_h^k(s, a) := 2H\sqrt{L/N_h^k(s, a)}$ where $L := \ln(SAHK/\delta)$.

Lemma 6.9. Assume the events in Lemma 6.7 and Lemma 6.3 are true. For all s, a, k, h , set $f := \hat{V}_{h+1}^k - V_{h+1}^*$, we have:

$$\left| \left(\hat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a) \right)^\top f \right| \leq \xi_h^k(s, a) + \frac{e}{H} \mathbb{E} \left[\sum_{\tau=h+1}^{H-1} (\xi_\tau^k(s_\tau, a_\tau) + b_\tau^k(s_\tau, a_\tau)) \mid s_h = s, a_h = a, \pi^k \right]$$

where $\xi_\tau^i(s, a) = \frac{3H^2SL}{N_\tau^i(s, a)}$, for any $\tau \in [0, \dots, H-1]$, $i \in [0, \dots, K-1]$, and the expectation is with respect to the randomness from the event of following policy π^k from (s, a) starting from time step h .

Proof. Using Lemma 6.7 and the fact that $f := \hat{V}_{h+1}^k - V_{h+1}^*$, we have:

$$\left| \left(\hat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a) \right)^\top f \right| \leq \frac{\mathbb{E}_{s' \sim P_h^*(\cdot|s, a)} (\hat{V}_{h+1}^k(s') - V_{h+1}^*(s'))}{H} + \xi_h^k(s, a). \quad (6.7)$$

Now consider $\widehat{V}_{h+1}^k(s') - V_{h+1}^*(s')$, we have:

$$\begin{aligned}
\widehat{V}_{h+1}^k(s') - V_{h+1}^*(s') &\leq \widehat{V}_{h+1}^k(s') - (r(s', \pi^k(s')) + P_{h+1}^*(\cdot|s', \pi^k(s'))^\top V_{h+2}^*) \\
&\leq r(s', \pi^k(s')) + \widehat{P}_{h+1}^k(\cdot|s', \pi^k(s'))^\top \widehat{V}_{h+2}^k - (r(s', \pi^k(s')) + P_{h+1}^*(\cdot|s', \pi^k(s'))^\top V_{h+2}^*) \\
&= \widehat{P}_{h+1}^k(\cdot|s', \pi^k(s'))^\top \widehat{V}_{h+2}^k - P_{h+1}^*(\cdot|s', \pi^k(s'))^\top \widehat{V}_{h+2}^k + P_{h+1}^*(\cdot|s', \pi^k(s'))^\top (\widehat{V}_{h+2}^k - V_{h+2}^*) \\
&= \left(\widehat{P}_{h+1}^k(\cdot|s', \pi^k(s')) - P_{h+1}^*(\cdot|s', \pi^k(s')) \right)^\top (\widehat{V}_{h+2}^k - V_{h+2}^*) \\
&\quad + \left(\widehat{P}_{h+1}^k(\cdot|s', \pi^k(s')) - P_{h+1}^*(\cdot|s', \pi^k(s')) \right)^\top V_{h+2}^* \\
&\quad + P_{h+1}^*(\cdot|s', \pi^k(s'))^\top (\widehat{V}_{h+2}^k - V_{h+2}^*)
\end{aligned}$$

where the first inequality uses the fact that $V_{h+1}^*(s') = \max_{a'} (r(s', a') + P_{h+1}^*(\cdot|s', a')^\top V_{h+2}^*)$, the second inequality uses the definition of $\widehat{V}_{h+1}^k$ and π^k . Note that the second term in the RHS of the above inequality can be upper bounded exactly by the bonus using Lemma 6.3, and the first term can be further upper bounded using the same operation that we had in Lemma 6.7, i.e.,

$$\left(\widehat{P}_{h+1}^k(\cdot|s', \pi^k(s')) - P_{h+1}^*(\cdot|s', \pi^k(s')) \right)^\top (\widehat{V}_{h+2}^k - V_{h+2}^*) \leq \frac{P_{h+1}^*(\cdot|s', \pi^k(s'))^\top (\widehat{V}_{h+2}^k - V_{h+2}^*)}{H} + \xi_{h+1}^k(s', \pi^k(s')).$$

Combine the above inequalities together, we arrive at:

$$\widehat{V}_{h+1}^k(s') - V_{h+1}^*(s') \leq b_{h+1}^k(s', \pi^k(s')) + \xi_{h+1}^k(s', \pi^k(s')) + \left(1 + \frac{1}{H}\right) \mathbb{E}_{s'' \sim P_{h+1}^*(s', \pi^k(s'))} (\widehat{V}_{h+2}^k(s'') - V_{h+2}^*(s'')).$$

We can recursively apply the same operation on $\widehat{V}_{h+2}^k(s'') - V_{h+2}^*(s'')$ till step H , we have:

$$\begin{aligned}
\widehat{V}_{h+1}^k(s') - V_{h+1}^*(s') &\leq \mathbb{E} \left[\sum_{\tau=h+1}^{H-1} \left(1 + \frac{1}{H}\right)^{\tau-h-1} (\xi_\tau^k(s_\tau, a_\tau) + b_\tau^k(s_\tau, a_\tau)) \mid s_{h+1} = s', \pi^k \right] \\
&\leq e \mathbb{E} \left[\sum_{\tau=h+1}^{H-1} (\xi_\tau^k(s_\tau, a_\tau) + b_\tau^k(s_\tau, a_\tau)) \mid s_{h+1} = s', \pi^k \right],
\end{aligned}$$

where the last inequality uses the fact that $(1 + 1/H)^x \leq e$ for any $x \in \mathbb{N}^+$. Substitute the above inequality into Eq. 6.7, we get:

$$\left| \left(\widehat{P}_h^k(\cdot|s, a) - P_h^*(\cdot|s, a) \right)^\top f \right| \leq \xi_h^k(s, a) + \frac{e}{H} \mathbb{E} \left[\sum_{\tau=h+1}^{H-1} (\xi_\tau^k(s_\tau, a_\tau) + b_\tau^k(s_\tau, a_\tau)) \mid s_h = s, a_h = a, \pi^k \right]$$

□

Now we are ready to derive a refined upper bound for per-episode regret.

Lemma 6.10. Assume the events in Lemma 6.9 and Lemma 6.4 (optimism) hold. For all $k \in [0, K-1]$, we have:

$$V^*(s_0) - V^{\pi^k}(s_0) \leq e \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} [2b_h^k(s_h, a_h) + \xi_h^k(s_h, a_h)].$$

Proof. Via optimism in Lemma 6.4, we have:

$$\begin{aligned}
V^*(s_0) - V^{\pi^k}(s_0) &\leq \widehat{V}_0^k(s_0) - V_0^{\pi^k}(s_0) \leq \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} \left[b_h^k(s_h, a_h) + \left(\widehat{P}_h^k(\cdot | s_h, a_h) - P^*(\cdot | s_h, a_h) \right) \cdot \widehat{V}_{h+1}^k \right] \\
&= \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} \left[b_h^k(s_h, a_h) + \left(\widehat{P}_h^k(\cdot | s_h, a_h) - P^*(\cdot | s_h, a_h) \right)^\top \left(\widehat{V}_{h+1}^k - V_{h+1}^* \right) + \left(\widehat{P}_h^k(\cdot | s_h, a_h) - P^*(\cdot | s_h, a_h) \right)^\top V_{h+1}^* \right] \\
&\leq \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} \left[2b_h^k(s_h, a_h) + \left(\widehat{P}_h^k(\cdot | s_h, a_h) - P^*(\cdot | s_h, a_h) \right)^\top \left(\widehat{V}_{h+1}^k - V_{h+1}^* \right) \right] \\
&\leq \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} \left[2b_h^k(s_h, a_h) + \xi_h^k(s_h, a_h) + \frac{e}{H} \mathbb{E} \left[\sum_{\tau=h+1}^{H-1} (\xi_\tau^k(s_\tau, a_\tau) + b_\tau^k(s_\tau, a_\tau)) \mid \pi^k \right] \right] \\
&\leq e \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim d_h^{\pi^k}} [2b_h^k(s_h, a_h) + \xi_h^k(s_h, a_h)]
\end{aligned}$$

where the first inequality uses optimism, and the fourth inequality uses Lemma 6.9, and the last inequality rearranges by grouping same terms together. $\square$

To conclude the final regret bound, let us denote the event $\mathcal{E}_{model}$ as the joint event in Lemma 6.3 and Lemma 6.8, which holds with probability at least $1 - 2\delta$.

Proof of Theorem 6.6. Following the derivation we have in Eq. 6.5, we decompose the expected regret bound as follows:

$$\begin{aligned}
\mathbb{E} \left[\sum_{k=0}^{K-1} V^*(s_0) - V^{\pi^k}(s_0) \right] &\leq \mathbb{E} \left[\mathbf{1}\{\mathcal{E}_{model}\} \left(\sum_{k=0}^{K-1} V^*(s_0) - V^{\pi^k}(s_0) \right) \right] + 2\delta KH \\
&\leq e \mathbb{E} \left[\sum_{k=0}^{K-1} \sum_{h=0}^{H-1} [2b_h^k(s_h^k, a_h^k) + \xi_h^k(s_h^k, a_h^k)] \right] + 2\delta KH,
\end{aligned}$$

where the last inequality uses Lemma 6.10. Using Lemma 6.5, we have that:

$$\sum_{k=0}^{K-1} \sum_{h=0}^{H-1} 2b_h^k(s_h^k, a_h^k) \leq 4H\sqrt{L} \sum_k \sum_h \frac{1}{\sqrt{N_h^k(s_h^k, a_h^k)}} \leq 8H^2\sqrt{SAKL}.$$

For $\sum_k \sum_h \xi_h^k(s_h^k, a_h^k)$, we have:

$$\begin{aligned}
\sum_{k=0}^{K-1} \sum_{h=0}^{H-1} \xi_h^k(s_h^k, a_h^k) &= 2H^2SL \sum_{k=0}^{K-1} \sum_{h=0}^{H-1} \frac{1}{N_h^k(s_h^k, a_h^k)} = 2H^2SL \sum_{h=0}^{H-1} \sum_{s,a} \sum_{i=1}^{N_h^K(s,a)} \frac{1}{i} \\
&\leq 2H^2SALHS \ln(K) = 2H^3S^2AL \ln(K),
\end{aligned}$$

where in the last inequality, we use the fact that $N_h^K(s, a) \leq K$ for all s, a, h , and the inequality $\sum_{i=1}^t 1/i \leq \ln(t)$. Putting things together, and setting $\delta = 1/(KH)$, we conclude the proof. $\square$

6.5 Phased Q -learning

to be added

6.6 Bibliographic Remarks and Further Readings

The first provably correct PAC algorithm for reinforcement learning (which finds a near optimal policy) was due to Kearns and Singh [2002], which provided the E^3 algorithm; it achieves polynomial sample complexity in tabular MDPs. Brafman and Tennenholtz [2002] presents the Rmax algorithm which provides a refined PAC analysis over E^3 . Both are model based approaches Kakade [2003] improves the sample complexity to be $O(S^2 A)$. Both E^3 and Rmax uses the concept of absorbing MDPs to achieve optimism and balance exploration and exploitation.

Jaksch et al. [2010] provides the first $O(\sqrt{T})$ regret bound, where T is the number of timesteps in the MDP (T is proportional to K in our setting); this dependence on T is optimal. Subsequently, Azar et al. [2017], Dann et al. [2017] provide algorithms that, asymptotically, achieve minimax regret bound in tabular MDPs. By this, we mean that for sufficiently large T (for $T \geq \Omega(|\mathcal{S}|^2)$), the results in Azar et al. [2017], Dann et al. [2017] obtain optimal dependencies on $|\mathcal{S}|$ and $|\mathcal{A}|$. The requirement that $T \geq \Omega(|\mathcal{S}|^2)$ before these bounds hold is essentially the requirement that non-trivial model accuracy is required. It is an open question to remove this dependence.

Lower bounds are provided in Dann and Brunskill [2015], Osband and Van Roy [2016], Azar et al. [2017].

Further exploration strategies. Refs and discussion for Q -learning, reward free, and thompson sampling to be added...

Chapter 7

Linearly Parameterized MDPs

In this chapter, we consider learning and exploration in linearly parameterized MDPs—the linear MDP. Linear MDP generalizes tabular MDPs into MDPs with potentially infinitely many state and action pairs.

This chapter largely follows the model and analysis first provided in Jin et al. [2020].

7.1 Setting

We consider episodic finite horizon MDP with horizon H , $\mathcal{M} = \{\mathcal{S}, \mathcal{A}, \{r_h\}_h, \{P_h\}_h, H, s_0\}$, where s_0 is a fixed initial state, $r_h : \mathcal{S} \times \mathcal{A} \mapsto [0, 1]$ and $P_h : \mathcal{S} \times \mathcal{A} \mapsto \Delta(\mathcal{S})$ are time-dependent reward function and transition kernel. Note that for time-dependent finite horizon MDP, the optimal policy will be time-dependent as well. For simplicity, we overload notations a bit and denote $\pi = \{\pi_0, \dots, \pi_{H-1}\}$, where each $\pi_h : \mathcal{S} \mapsto \mathcal{A}$. We also denote $V^\pi := V_0^\pi(s_0)$, i.e., the expected total reward of π starting at $h = 0$ and s_0 .

We define the learning protocol below. Learning happens in an episodic setting. Every episode k , learner first proposes a policy π^k based on all the history information up to the end of episode $k - 1$. The learner then executes π^k in the underlying MDP to generate a single trajectory $\tau^k = \{s_h^k, a_h^k\}_{h=0}^{H-1}$ with $a_h = \pi_h^k(s_h^k)$ and $s_{h+1}^k \sim P_h(\cdot | s_h^k, a_h^k)$. The goal of the learner is to minimize the following cumulative regret over N episodes:

$$\text{Regret} := \mathbb{E} \left[\sum_{k=0}^{K-1} (V^* - V^{\pi^k}) \right],$$

where the expectation is with respect to the randomness of the MDP environment and potentially the randomness of the learner (i.e., the learner might make decisions in a randomized fashion).

7.1.1 Low-Rank MDPs and Linear MDPs

Note that here we do not assume $\mathcal{S}$ and $\mathcal{A}$ are finite anymore. Indeed in this note, both of them could be continuous. Without any further structural assumption, the lower bounds we saw in the Generalization Lecture forbid us to get a polynomially regret bound.

The structural assumption we make in this note is a linear structure in both reward and the transition.

Definition 7.1 (Linear MDPs). Consider transition $\{P_h\}$ and $\{r_h\}_h$. A linear MDP has the following structures on r_h

and P_h :

$$r_h(s, a) = \theta_h^* \cdot \phi(s, a), \quad P_h(\cdot | s, a) = \mu_h^* \phi(s, a), \forall h$$

where ϕ is a known state-action feature map $\phi : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^d$, and $\mu_h^* \in \mathbb{R}^{|\mathcal{S}| \times d}$. Here ϕ, θ_h^* are **known** to the learner, while μ^* is unknown. We further assume the following norm bound on the parameters: (1) $\sup_{s,a} \|\phi(s, a)\|_2 \leq 1$, (2) $\|v^\top \mu_h^*\|_2 \leq \sqrt{d}$ for any v such that $\|v\|_\infty \leq 1$, and all h , and (3) $\|\theta_h^*\|_2 \leq W$ for all h . We assume $r_h(s, a) \in [0, 1]$ for all h and s, a .

The model essentially says that the transition matrix $P_h \in \mathbb{R}^{|\mathcal{S}| \times |\mathcal{S}| \times |\mathcal{A}|}$ has rank at most d , and $P_h = \mu_h^* \Phi$, where $\Phi \in \mathbb{R}^{d \times |\mathcal{S}| \times |\mathcal{A}|}$ and each column of Φ corresponds to $\phi(s, a)$ for a pair $s, a \in \mathcal{S} \times \mathcal{A}$.

Linear Algebra Notations For real-valued matrix A , we denote $\|A\|_2 = \sup_{x: \|x\|_2=1} \|Ax\|_2$ which denotes the maximum singular value of A . We denote $\|A\|_F$ as the Frobenius norm $\|A\|_F^2 = \sum_{i,j} A_{i,j}^2$ where $A_{i,j}$ denotes the i, j 'th entry of A . For any Positive Definite matrix Λ , we denote $x^\top \Lambda x = \|x\|_\Lambda^2$. We denote $\det(A)$ as the determinant of the matrix A . For a PD matrix Λ , we note that $\det(\Lambda) = \prod_{i=1}^d \sigma_i$ where σ_i is the eigenvalues of Λ . For notation simplicity, during inequality derivation, we will use $\lesssim, \approx$ to suppress all absolute constants. We will use $\tilde{O}$ to suppress all absolute constants and log terms.

7.2 Planning in Linear MDPs

We first study how to do value iteration in linear MDP if μ is given.

We start from $Q_{H-1}^*(s, a) = \theta_{H-1}^* \cdot \phi(s, a)$, and $\pi_{H-1}^*(s) = \operatorname{argmax}_a Q_{H-1}^*(s, a) = \operatorname{argmax}_a \theta_{H-1}^* \cdot \phi(s, a)$, and $V_{H-1}^*(s) = \operatorname{argmax}_a Q_{H-1}^*(s, a)$.

Now we do dynamic programming from $h+1$ to h :

$$Q_h^*(s, a) = \theta_h^* \cdot \phi(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} V_{h+1}^*(s') = \theta_h^* \cdot \phi(s, a) + P_h(\cdot | s, a) \cdot V_{h+1}^* = \theta_h^* \cdot \phi(s, a) + (\mu_h^* \phi(s, a))^\top V_{h+1}^* \quad (7.1)$$

$$= \phi(s, a) \cdot (\theta_h^* + (\mu_h^*)^\top V_{h+1}^*) = \phi(s, a) \cdot w_h, \quad (7.2)$$

where we denote $w_h := \theta_h^* + (\mu_h^*)^\top V_{h+1}^*$. Namely we see that $Q_h^*(s, a)$ is a linear function with respect to $\phi(s, a)$! We can continue by defining $\pi_h^*(s) = \operatorname{argmax}_a Q_h^*(s, a)$ and $V_h^*(s) = \max_a Q_h^*(s, a)$.

At the end, we get a sequence of linear Q^* , i.e., $Q_h^*(s, a) = w_h \cdot \phi(s, a)$, and the optimal policy is also simple, $\pi_h^*(s) = \operatorname{argmax}_a w_h \cdot \phi(s, a)$, for all $h = 0, \dots, H-1$.

One key property of linear MDP is that a Bellman Backup of any function $f : \mathcal{S} \mapsto \mathbb{R}$ is a linear function with respect to $\phi(s, a)$. We summarize the key property in the following claim.

Claim 7.2. Consider any arbitrary function $f : \mathcal{S} \mapsto [0, H]$. At any time step $h \in [0, \dots, H-1]$, there must exist a $w \in \mathbb{R}^d$, such that, for all $s, a \in \mathcal{S} \times \mathcal{A}$:

$$r_h(s, a) + P_h(\cdot | s, a) \cdot f = w^\top \phi(s, a).$$

The proof of the above claim is essentially the Eq. 7.1.

7.3 Learning Transition using Ridge Linear Regression

In this section, we consider the following simple question: given a dataset of state-action-next state tuples, how can we learn the transition P_h for all h ?

Note that $\mu^* \in \mathbb{R}^{|\mathcal{S}| \times d}$. Hence explicitly writing down and storing the parameterization μ^* takes time at least $|\mathcal{S}|$. We show that we can represent the model in a non-parametric way.

We consider a particular episode n . Similar to Tabular-UCBVI, we learn a model at the very beginning of the episode n using all data from the previous episodes (episode 1 to the end of the episode $n - 1$). We denote such dataset as:

$$\mathcal{D}_h^n = \{s_h^i, a_h^i, s_{h+1}^i\}_{i=0}^{n-1}.$$

We maintain the following statistics using $\mathcal{D}_h^n$:

$$\Lambda_h^n = \sum_{i=0}^{n-1} \phi(s_h^i, a_h^i) \phi(s_h^i, a_h^i)^\top + \lambda I,$$

where $\lambda \in \mathbb{R}^+$ (it will be set to 1 eventually, but we keep it here for generality).

To get intuition of Λ_h^n , think about the tabular setting where $\phi(s, a)$ is a one-hot vector (zeros everywhere except that the entry corresponding to (s, a) is one). Then Λ_h^n is a diagonal matrix and the diagonal entry contains $N^n(s, a)$ —the number of times (s, a) has been visited.

We consider the following multi-variate linear regression problem. Denote $\delta(s)$ as a one-hot vector that has zero everywhere except that the entry corresponding to s is one. Denote $\epsilon_h^i = P(\cdot | s_h^i, a_h^i) - \delta(s_{h+1}^i)$. Conditioned on history $\mathcal{H}_h^i$ (history $\mathcal{H}_h^i$ denotes all information from the very beginning of the learning process up to and including (s_h^i, a_h^i)), we have:

$$\mathbb{E}[\epsilon_h^i | \mathcal{H}_h^i] = 0,$$

simply because s_{h+1}^i is sampled from $P_h(\cdot | s_h^i, a_h^i)$ conditioned on (s_h^i, a_h^i) . Also note that $\|\epsilon_h^i\|_1 \leq 2$ for all h, i .

Since $\mu_h^* \phi(s_h^i, a_h^i) = P_h(\cdot | s_h^i, a_h^i)$, and $\delta(s_{h+1}^i)$ is an unbiased estimate of $P_h(\cdot | s_h^i, a_h^i)$ conditioned on s_h^i, a_h^i , it is reasonable to learn μ^* via regression from $\phi(s_h^i, a_h^i)$ to $\delta(s_{h+1}^i)$. This leads us to the following ridge linear regression:

$$\hat{\mu}_h^n = \underset{\mu \in \mathbb{R}^{|\mathcal{S}| \times d}}{\operatorname{argmin}} \sum_{i=0}^{n-1} \|\mu \phi(s_h^i, a_h^i) - \delta(s_{h+1}^i)\|_2^2 + \lambda \|\mu\|_F^2.$$

Ridge linear regression has the following closed-form solution:

$$\hat{\mu}_h^n = \sum_{i=0}^{n-1} \delta(s_{h+1}^i) \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} \quad (7.3)$$

Note that $\hat{\mu}_h^n \in \mathbb{R}^{|\mathcal{S}| \times d}$, so we never want to explicitly store it. Note that we will always use $\hat{\mu}_h^n$ together with a specific s, a pair and a value function V (think about value iteration case), i.e., we care about $\hat{P}_h^n(\cdot | s, a) \cdot V := (\hat{\mu}_h^n \phi(s, a)) \cdot V$, which can be re-written as:

$$\hat{P}_h^n(\cdot | s, a) \cdot V := (\hat{\mu}_h^n \phi(s, a)) \cdot V = \phi(s, a)^\top \sum_{i=0}^{n-1} (\Lambda_h^n)^{-1} \phi(s_h^i, a_h^i) V(s_{h+1}^i),$$

where we use the fact that $\delta(s)^\top V = V(s)$. Thus the operator $\hat{P}_h^n(\cdot|s, a) \cdot V$ simply requires storing all data and can be computed via simple linear algebra and the computation complexity is simply $\text{poly}(d, n)$ —no poly dependency on $|\mathcal{S}|$.

Let us calculate the difference between $\hat{\mu}_h^n$ and μ_h^* .

Lemma 7.3 (Difference between $\hat{\mu}_h$ and μ_h^*). *For all n and h , we must have:*

$$\hat{\mu}_h^n - \mu_h^* = -\lambda \mu_h^* (\Lambda_h^n)^{-1} + \sum_{i=1}^{n-1} \epsilon_h^i \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1}.$$

Proof. We start from the closed-form solution of $\hat{\mu}_h^n$:

$$\begin{aligned} \hat{\mu}_h^n &= \sum_{i=0}^{n-1} \delta(s_{h+1}^i) \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} = \sum_{i=0}^{n-1} (P(\cdot|s_h^i, a_h^i) + \epsilon_h^n) \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} \\ &= \sum_{i=0}^{n-1} (\mu_h^* \phi(s_h^i, a_h^i) + \epsilon_h^i) \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} = \sum_{i=0}^{n-1} \mu_h^* \phi(s_h^i, a_h^i) \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} + \sum_{i=0}^{n-1} \epsilon_h^i \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} \\ &= \sum_{i=0}^{n-1} \mu_h^* \phi(s_h^i, a_h^i) \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} + \sum_{i=0}^{n-1} \epsilon_h^i \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} \\ &= \mu_h^* (\Lambda_h^n - \lambda I) (\Lambda_h^n)^{-1} + \sum_{i=0}^{n-1} \epsilon_h^i \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} = \mu_h^* - \lambda \mu_h^* (\Lambda_h^n)^{-1} + \sum_{i=0}^{n-1} \epsilon_h^i \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1}. \end{aligned}$$

Rearrange terms, we conclude the proof. $\square$

Lemma 7.4. Fix $V : \mathcal{S} \mapsto [0, H]$. For all n and $s, a \in \mathcal{S} \times \mathcal{A}$, and h , with probability at least $1 - \delta$, we have:

$$\left\| \sum_{i=0}^{n-1} \phi(s_h^i, a_h^i) (V^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}} \leq 3H \sqrt{\ln \frac{H \det(\Lambda_h^n)^{1/2} \det(\lambda I)^{-1/2}}{\delta}}.$$

Proof. We first check the noise terms $\{V^\top \epsilon_h^i\}_{h,i}$. Since V is independent of the data (it's a pre-fixed function), and by linear property of expectation, we have:

$$\mathbb{E} [V^\top \epsilon_h^i | \mathcal{H}_h^i] = 0, \quad |V^\top \epsilon_h^i| \leq \|V\|_\infty \|\epsilon_h^i\|_1 \leq 2H, \forall h, i.$$

Hence, this is a Martingale difference sequence. Using the Self-Normalized vector-valued Martingale Bound (Lemma A.9), we have that for all n , with probability at least $1 - \delta$:

$$\left\| \sum_{i=0}^{n-1} \phi(s_h^i, a_h^i) (V^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}} \leq 3H \sqrt{\ln \frac{\det(\Lambda_h^n)^{1/2} \det(\lambda I)^{-1/2}}{\delta}}.$$

Apply union bound over all $h \in [H]$, we get that with probability at least $1 - \delta$, for all n, h :

$$\left\| \sum_{i=0}^{n-1} \phi(s_h^i, a_h^i) (V^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}} \leq 3H \sqrt{\ln \frac{H \det(\Lambda_h^n)^{1/2} \det(\lambda I)^{-1/2}}{\delta}}. \quad (7.4)$$

$\square$

7.4 Uniform Convergence via Covering

Now we take a detour first and consider how to achieve a uniform convergence result over a function class $\mathcal{F}$ that contains infinitely many functions. Previously we know how to get uniform convergence if $\mathcal{F}$ is finite—we simply do a union bound. However, when $\mathcal{F}$ contains infinitely many functions, we cannot simply apply a union bound. We will use the covering argument here.

Consider the following ball with radius R : $\Theta = \{\theta \in \mathbb{R}^d : \|\theta\|_2 \leq R \in \mathbb{R}^+\}$. Fix an ϵ . An ϵ -net $\mathcal{N}_\epsilon \subset \Theta$ is a set such that for any $\theta \in \Theta$, there exists a $\theta' \in \mathcal{N}_\epsilon$, such that $\|\theta - \theta'\|_2 \leq \epsilon$. We call the smallest ϵ -net as ϵ -cover. Abuse notations a bit, we simply denote $\mathcal{N}_\epsilon$ as the ϵ -cover.

The ϵ -covering number is the size of ϵ -cover $\mathcal{N}_\epsilon$. We define the covering dimension as $\ln(|\mathcal{N}_\epsilon|)$

Lemma 7.5. *The ϵ -covering number of the ball $\Theta = \{\theta \in \mathbb{R}^d : \|\theta\|_2 \leq R \in \mathbb{R}^+\}$ is upper bounded by $(1 + 2R/\epsilon)^d$.*

We can extend the above definition to a function class. Specifically, we look at the following function. For a triple of (w, β, Λ) where $w \in \mathbb{R}^d$ and $\|w\|_2 \leq L$, $\beta \in [0, B]$, and Λ such that $\sigma_{\min}(\Lambda) \geq \lambda$, we define $f_{w, \beta, \Lambda} : \mathcal{S} \mapsto [0, R]$ as follows:

$$f_{w, \beta, \Lambda}(s) = \min \left\{ \max_a \left(w^\top \phi(s, a) + \beta \sqrt{\phi(s, a)^\top \Lambda^{-1} \phi(s, a)} \right), H \right\}, \forall s \in \mathcal{S}. \quad (7.5)$$

We denote the function class $\mathcal{F}$ as:

$$\mathcal{F} = \{f_{w, \beta, \Lambda} : \|w\|_2 \leq L, \beta \in [0, B], \sigma_{\min}(\Lambda) \geq \lambda\}. \quad (7.6)$$

Note that $\mathcal{F}$ contains infinitely many functions as the parameters are continuous. However we will show that it has finite covering number that scales exponentially with respect to the number of parameters in (w, β, Λ) .

Why do we look at $\mathcal{F}$? As we will see later in this chapter $\mathcal{F}$ contains all possible $\hat{Q}_h$ functions one could encounter during the learning process.

Lemma 7.6 (ϵ -covering dimension of $\mathcal{F}$). *Consider $\mathcal{F}$ defined in Eq. 7.6. Denote its ϵ -cover as $\mathcal{N}_\epsilon$ with the ℓ_∞ norm as the distance metric, i.e., $d(f_1, f_2) = \|f_1 - f_2\|_\infty$ for any $f_1, f_2 \in \mathcal{F}$. We have that:*

$$\ln(|\mathcal{N}_\epsilon|) \leq d \ln(1 + 6L/\epsilon) + \ln(1 + 6B/(\sqrt{\lambda}\epsilon)) + d^2 \ln(1 + 18B^2\sqrt{d}/(\lambda\epsilon^2)).$$

Note that the ϵ -covering dimension scales quadratically with respect to d .

Proof. We start from building a net over the parameter space (w, β, Λ) , and then we convert the net over parameter space to an ϵ -net over $\mathcal{F}$ under the ℓ_∞ distance metric.

We pick two functions that corresponding to parameters (w, β, Λ) and $(\hat{w}, \hat{\beta}, \hat{\Lambda})$.

$$\begin{aligned}
|f(s) - \hat{f}(s)| &\leq \left| \max_a \left(w^\top \phi(s, a) + \beta \sqrt{\phi(s, a)^\top \Lambda^{-1} \phi(s, a)} \right) - \max_a \left(\hat{w}^\top \phi(s, a) + \hat{\beta} \sqrt{\phi(s, a)^\top \hat{\Lambda}^{-1} \phi(s, a)} \right) \right| \\
&\leq \max_a \left| \left(w^\top \phi(s, a) + \beta \sqrt{\phi(s, a)^\top \Lambda^{-1} \phi(s, a)} \right) - \left(\hat{w}^\top \phi(s, a) + \hat{\beta} \sqrt{\phi(s, a)^\top \hat{\Lambda}^{-1} \phi(s, a)} \right) \right| \\
&\leq \max_a |(w - \hat{w})^\top \phi(s, a)| + \max_a \left| (\beta - \hat{\beta}) \sqrt{\phi(s, a)^\top \Lambda^{-1} \phi(s, a)} \right| \\
&\quad + \max_a \left| \hat{\beta} \left(\sqrt{\phi(s, a)^\top \Lambda^{-1} \phi(s, a)} - \sqrt{\phi(s, a)^\top \hat{\Lambda}^{-1} \phi(s, a)} \right) \right| \\
&\leq \|w - \hat{w}\|_2 + |\beta - \hat{\beta}|/\sqrt{\lambda} + B \sqrt{\left| \phi(s, a)^\top (\Lambda^{-1} - \hat{\Lambda}^{-1}) \phi(s, a) \right|} \\
&\leq \|w - \hat{w}\|_2 + |\beta - \hat{\beta}|/\sqrt{\lambda} + B \sqrt{\|\Lambda^{-1} - \hat{\Lambda}^{-1}\|_F}
\end{aligned}$$

Note that Λ^{-1} is a PD matrix with $\sigma_{\max}(\Lambda^{-1}) \leq 1/\lambda$.

Now we consider the $\epsilon/3$ -Net $\mathcal{N}_{\epsilon/3, w}$ over $\{w : \|w\|_2 \leq L\}$, $\sqrt{\lambda}\epsilon/3$ -net $\mathcal{N}_{\sqrt{\lambda}\epsilon/3, \beta}$ over interval $[0, B]$ for β , and $\epsilon^2/(9B^2)$ -net $\mathcal{N}_{\epsilon^2/(9B^2), \Lambda}$ over $\{\Lambda : \|\Lambda\|_F \leq \sqrt{d}/\lambda\}$. The product of these three nets provide a ϵ -cover for $\mathcal{F}$, which means that that size of the ϵ -net $\mathcal{N}_\epsilon$ for $\mathcal{F}$ is upper bounded as:

$$\begin{aligned}
\ln |\mathcal{N}_\epsilon| &\leq \ln |\mathcal{N}_{\epsilon/3, w}| + \ln |\mathcal{N}_{\sqrt{\lambda}\epsilon/3, \beta}| + \ln |\mathcal{N}_{\epsilon^2/(9B^2), \Lambda}| \\
&\leq d \ln(1 + 6L/\epsilon) + \ln(1 + 6B/(\sqrt{\lambda}\epsilon)) + d^2 \ln(1 + 18B^2 \sqrt{d}/(\lambda\epsilon^2)).
\end{aligned}$$

□

Remark Covering gives a way to represent the complexity of function class (or hypothesis class). Relating to VC, covering number is upper bound roughly by $\exp(d)$ with d being the VC-dimension. However, there are cases where VC-dimension is infinite, but covering number is finite.

Now we can build a uniform convergence argument for all $f \in \mathcal{F}$.

Lemma 7.7 (Uniform Convergence Results). *Set $\lambda = 1$. Fix $\delta \in (0, 1)$. For all n, h , all s, a , and all $f \in \mathcal{F}$, with probability at least $1 - \delta$, we have:*

$$\left| \left(\hat{P}_h^n(\cdot | s, a) - P(\cdot | s, a) \right) \cdot f \right| \lesssim H \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}} \left(\sqrt{d \ln(1 + 6L\sqrt{N})} + d \sqrt{\ln(1 + 18B^2 \sqrt{d}N)} + \sqrt{\ln \frac{H}{\delta}} \right).$$

Proof. Recall Lemma 7.4, we have with probability at least $1 - \delta$, for all n, h , for a pre-fixed V (independent of the random process):

$$\left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (V^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}}^2 \leq 9H^2 \ln \frac{H \det(\Lambda_h^n)^{1/2} \det(\lambda I)^{-1/2}}{\delta} \leq 9H^2 \left(\ln \frac{H}{\delta} + d \ln(1 + N) \right)$$

where we have used the fact that $\|\phi\|_2 \leq 1$, $\lambda = 1$, and $\|\Lambda_h^n\|_2 \leq N + 1$.

Denote the ϵ -cover of $\mathcal{F}$ as $\mathcal{N}_\epsilon$. With an application of a union bound over all functions in $\mathcal{N}_\epsilon$, we have that with probability at least $1 - \delta$, for all $V \in \mathcal{N}_\epsilon$, all n, h , we have:

$$\left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (V^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}}^2 \leq 9H^2 \left(\ln \frac{H}{\delta} + \ln(|\mathcal{N}_\epsilon|) + d \ln(1 + N) \right).$$

Recall Lemma 7.6, substitute the expression of $\ln |\mathcal{N}_\epsilon|$ into the above inequality, we get:

$$\left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (V^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}}^2 \leq 9H^2 \left(\ln \frac{H}{\delta} + d \ln(1 + 6L/\epsilon) + d^2 \ln(1 + 18B^2 \sqrt{d}/\epsilon^2) + d \ln(1 + N) \right).$$

Now consider an arbitrary $f \in \mathcal{F}$. By the definition of ϵ -cover, we know that for f , there exists a $V \in \mathcal{N}_\epsilon$, such that $\|f - V\|_\infty \leq \epsilon$. Thus, we have:

$$\begin{aligned} \left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (f^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}}^2 &\leq 2 \left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (V^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}}^2 + 2 \left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) ((V - f)^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}}^2 \\ &\leq 2 \left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (V^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}}^2 + 8\epsilon^2 N \\ &\leq 9H^2 \left(\ln \frac{H}{\delta} + d \ln(1 + 6L/\epsilon) + d^2 \ln(1 + 18B^2 \sqrt{d}/\epsilon^2) + d \ln(1 + N) \right) + 8\epsilon^2 N, \end{aligned}$$

where in the second inequality we use the fact that $\left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (V - f)^\top \epsilon_h^i \right\|_{(\Lambda_h^n)^{-1}}^2 \leq 4\epsilon^2 N$, which is from

$$\left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (V - f)^\top \epsilon_h^i \right\|_{(\Lambda_h^n)^{-1}}^2 \leq \left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) 2\epsilon \right\|_{(\Lambda_h^n)^{-1}}^2 \leq \frac{4\epsilon^2}{\lambda} \left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) \right\|_2^2 \leq 4\epsilon^2 N.$$

Set $\epsilon = 1/\sqrt{N}$, we get:

$$\begin{aligned} \left\| \sum_{i=1}^{n-1} \phi(s_h^i, a_h^i) (f^\top \epsilon_h^i) \right\|_{(\Lambda_h^n)^{-1}}^2 &\leq 9H^2 \left(\ln \frac{H}{\delta} + d \ln(1 + 6L\sqrt{N}) + d^2 \ln(1 + 18B^2 \sqrt{d}N) + d \ln(1 + N) \right) + 8 \\ &\lesssim H^2 \left(\ln \frac{H}{\delta} + d \ln(1 + 6L\sqrt{N}) + d^2 \ln(1 + 18B^2 \sqrt{d}N) \right), \end{aligned}$$

where we recall $\lesssim$ ignores absolute constants.

Now recall that we can express $(\hat{P}_h^n(\cdot|s, a) - P(\cdot|s, a)) \cdot f = \phi(s, a)^\top (\hat{\mu}_h^n - \mu_h^*)^\top f$. Recall Lemma 7.3, we have:

$$\begin{aligned} |(\hat{\mu}_h^n \phi(s, a) - \mu_h^* \phi(s, a)) \cdot f| &\leq \left| \lambda \phi(s, a)^\top (\Lambda_h^n)^{-1} (\mu_h^*)^\top f \right| + \left| \sum_{i=1}^{n-1} \phi(s, a)^\top (\Lambda_h^n)^{-1} \phi(s_h^i, a_h^i) (\epsilon_h^i)^\top f \right| \\ &\lesssim H \sqrt{d} \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}} + \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}} \sqrt{\left(H^2 \left(\ln \frac{H}{\delta} + d \ln(1 + 6L\sqrt{N}) + d^2 \ln(1 + 18B^2 \sqrt{d}N) \right) \right)} \\ &\approx H \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}} \left(\sqrt{\ln \frac{H}{\delta}} + \sqrt{d \ln(1 + 6L\sqrt{N})} + d \sqrt{\ln(1 + 18B^2 \sqrt{d}N)} \right). \end{aligned}$$

□

7.5 Algorithm

Our algorithm, Upper Confidence Bound Value Iteration (UCB-VI) will use reward bonus to ensure optimism. Specifically, we will use the following reward bonus, which is motivated from the reward bonus used in linear bandit:

$$b_h^n(s, a) = \beta \sqrt{\phi(s, a)^\top (\Lambda_h^n)^{-1} \phi(s, a)}, \quad (7.7)$$

where β contains poly of H and d , and other constants and log terms. Again to gain intuition, please think about what this bonus would look like when we specialize linear MDP to tabular MDP.

Algorithm 6 UCBVI for Linear MDPs

```

1: Input: parameters  $\beta, \lambda$ 
2: for  $n = 1 \dots N$  do
3:   Compute  $\hat{P}_h^n$  for all  $h$  (Eq. 7.3)
4:   Compute reward bonus  $b_h^n$  for all  $h$  (Eq. 7.7)
5:   Run Value-Iteration on  $\{\hat{P}_h^n, r_h + b_h^n\}_{h=0}^{H-1}$  (Eq. 7.8)
6:   Set  $\pi^n$  as the returned policy of VI.
7: end for

```

With the above setup, now we describe the algorithm. Every episode n , we learn the model $\hat{\mu}_h^n$ via ridge linear regression. We then form the quadratic reward bonus as shown in Eq. 7.7. With that, we can perform the following truncated Value Iteration (always truncate the Q function at H):

$$\begin{aligned}
\hat{V}_H^n(s) &= 0, \forall s, \\
\hat{Q}_h^n(s, a) &= \theta^* \cdot \phi(s, a) + \beta \sqrt{\phi(s, a)^\top (\Lambda_h^n)^{-1} \phi(s, a)} + \phi(s, a)^\top (\hat{\mu}_h^n)^\top \hat{V}_{h+1}^n \\
&= \beta \sqrt{\phi(s, a)^\top (\Lambda_h^n)^{-1} \phi(s, a)} + (\theta^* + (\hat{\mu}_h^n)^\top \hat{V}_{h+1}^n)^\top \phi(s, a), \\
\hat{V}_h^n(s) &= \min_a \{\max_a \hat{Q}_h^n(s, a), H\}, \quad \pi_h^n(s) = \operatorname{argmax}_a \hat{Q}_h^n(s, a).
\end{aligned} \quad (7.8)$$

Note that above $\hat{Q}_h^n$ contains two components: a quadratic component and a linear component. And $\hat{V}_h^n$ has the format of $f_{w, \beta, \Lambda}$ defined in Eq. 7.5.

The following lemma bounds the norm of linear weights in $\hat{Q}_h^n$.

Lemma 7.8. Assume $\beta \in [0, B]$. For all n, h , we have $\hat{V}_h^n$ is in the form of Eq. 7.5, and $\hat{V}_h^n$ falls into the following class:

$$\mathcal{V} = \{f_{w, \beta, \Lambda} : \|w\|_2 \leq W + \frac{HN}{\lambda}, \beta \in [0, B], \sigma_{\min}(\Lambda) \geq \lambda\}. \quad (7.9)$$

Proof. We just need to show that $\theta^* + (\hat{\mu}_h^n)^\top \hat{V}_{h+1}^n$ has its ℓ_2 norm bounded. This is easy to show as we always have $\|\hat{V}_{h+1}^n\|_\infty \leq H$ as we do truncation at Value Iteration:

$$\left\| \theta^* + (\hat{\mu}_h^n)^\top \hat{V}_{h+1}^n \right\|_2 \leq W + \left\| (\hat{\mu}_h^n)^\top \hat{V}_{h+1}^n \right\|_2.$$

Now we use the closed-form of $\hat{\mu}_h^n$ from Eq. 7.3:

$$\left\| (\hat{\mu}_h^n)^\top \hat{V}_{h+1}^n \right\|_2 = \left\| \sum_{i=1}^{n-1} \hat{V}_{h+1}^n(s_{h+1}^i) \phi(s_h^i, a_h^i)^\top (\Lambda_h^n)^{-1} \right\|_2 \leq H \left\| (\Lambda_h^n)^{-1} \sum_{i=0}^{n-1} \phi(s_h^i, a_h^i) \right\|_2 \leq \frac{Hn}{\lambda},$$

where we use the fact that $\|\hat{V}_{h+1}^n\|_\infty \leq H$, $\sigma_{\max}(\Lambda^{-1}) \leq 1/\lambda$, and $\sup_{s,a} \|\phi(s, a)\|_2 \leq 1$. $\square$

7.6 Analysis of UCBVI for Linear MDPs

In this section, we prove the following regret bound for UCBVI.

Theorem 7.9 (Regret Bound). *Set $\beta = \tilde{O}(Hd)$, $\lambda = 1$. UCBVI (Algorithm 6) achieves the following regret bound:*

$$\mathbb{E} \left[NV^* - \sum_{i=0}^N V^{\pi^n} \right] \leq \tilde{O} \left(H^2 \sqrt{d^3 N} \right)$$

The main steps of the proof are similar to the main steps of UCBVI in tabular MDPs. We first prove optimism via induction, and then we use optimism to upper bound per-episode regret. Finally we use simulation lemma to decompose the per-episode regret.

In this section, to make notation simple, we set $\lambda = 1$ directly.

7.6.1 Proving Optimism

Proving optimism requires us to first bound model error which we have built in the uniform convergence result shown in Lemma 7.7, namely, the bound we get for $(\hat{P}_h^n(\cdot|s, a) - P(\cdot|s, a)) \cdot f$ for all $f \in \mathcal{V}$. Recall Lemma 7.7 but this time replacing $\mathcal{F}$ by $\mathcal{V}$ defined in Eq. 7.9. With probability at least $1 - \delta$, for all n, h, s, a and for all $f \in \mathcal{V}$,

$$\begin{aligned} \left| (\hat{P}_h^n(\cdot|s, a) - P(\cdot|s, a)) \cdot f \right| &\leq H \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}} \left(\sqrt{\ln \frac{H}{\delta}} + \sqrt{d \ln(1 + 6(W + HN)\sqrt{N})} + d \sqrt{\ln(1 + 18B^2 \sqrt{dN})} \right) \\ &\lesssim Hd \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}} \left(\sqrt{\ln \frac{H}{\delta}} + \sqrt{\ln(WN + HN^2)} + \sqrt{\ln(B^2 dN)} \right) \\ &\lesssim \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}} Hd \underbrace{\left(\sqrt{\ln \frac{H}{\delta}} + \sqrt{\ln(W + H)} + \sqrt{\ln B} + \sqrt{\ln d} + \sqrt{\ln N} \right)}_{:=\beta}. \end{aligned}$$

Denote the above inequality as event $\mathcal{E}_{model}$. Below we are going to condition on $\mathcal{E}_{model}$ being hold. Note that here for notation simplicity, we denote

$$\beta = Hd \left(\sqrt{\ln \frac{H}{\delta}} + \sqrt{\ln(W + H)} + \sqrt{\ln B} + \sqrt{\ln d} + \sqrt{\ln N} \right) = \tilde{O}(Hd).$$

remark Note that in the definition of $\mathcal{V}$ (Eq. 7.9), we have $\beta \in [0, B]$. And in the above formulation of β , note that B appears inside a log term. So we need to set B such that $\beta \leq B$ and we can get the correct B by solving the inequality $\beta \leq B$ for B .

Lemma 7.10 (Optimism). *Assume event $\mathcal{E}_{model}$ is true. for all n and h ,*

$$\hat{V}_h^n(s) \geq V_h^*(s), \forall s.$$

Proof. We consider a fixed episode n . We prove via induction. Assume that $\hat{V}_{h+1}^n(s) \geq V_{h+1}^*(s)$ for all s . For time

step h , we have:

$$\begin{aligned}
& \hat{Q}_h^n(s, a) - Q_h^*(s, a) \\
&= \theta^* \cdot \phi(s, a) + \beta \sqrt{\phi(s, a)^\top (\Lambda_h^n)^{-1} \phi(s, a)} + \phi(s, a)^\top (\hat{\mu}_h^n)^\top \hat{V}_{h+1}^n - \theta^* \cdot \phi(s, a) - \phi(s, a)^\top (\mu_h^*)^\top V_{h+1}^* \\
&\geq \beta \sqrt{\phi(s, a)^\top (\Lambda_h^n)^{-1} \phi(s, a)} + \phi(s, a)^\top (\hat{\mu}_h^n - \mu_h^*)^\top \hat{V}_{h+1}^n,
\end{aligned}$$

where in the last inequality we use the inductive hypothesis that $\hat{V}_{h+1}^n(s) \geq V_{h+1}^*(s)$, and $\mu_h^* \phi(s, a)$ is a valid distribution (note that $\hat{\mu}_h^n \phi(s, a)$ is not necessarily a valid distribution). We need to show that the bonus is big enough to offset the model error $\phi(s, a)^\top (\hat{\mu}_h^n - \mu_h^*)^\top \hat{V}_{h+1}^n$. Since we have event $\mathcal{E}_{model}$ being true, we have that:

$$\left| (\hat{P}_h^n(\cdot|s, a) - P(\cdot|s, a)) \cdot \hat{V}_{h+1}^n \right| \lesssim \beta \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}},$$

as by the construction of $\mathcal{V}$, we know that $\hat{V}_{h+1}^n \in \mathcal{V}$.

This concludes the proof. $\square$

7.6.2 Regret Decomposition

Now we can upper bound the per-episode regret as follows:

$$V^* - V^{\pi_n} \leq \hat{V}_0^n(s_0) - V_0^{\pi_n}(s_0).$$

We can further bound the RHS of the above inequality using simulation lemma. Recall Eq. 6.4 that we derived in the note for tabular MDP (Chapter 6):

$$\hat{V}_0^n(s_0) - V_0^{\pi_n}(s_0) \leq \sum_{h=0}^{H-1} \mathbb{E}_{s, a \sim d_h^{\pi_n}} \left[b_h^n(s, a) + \left(\hat{P}_h^n(\cdot|s, a) - P(\cdot|s, a) \right) \cdot \hat{V}_{h+1}^n \right].$$

(recall that the simulation lemma holds for any MDPs—it's not specialized to tabular).

In the event $\mathcal{E}_{model}$, we already know that for any s, a, h, n , we have $\left(\hat{P}_h^n(\cdot|s, a) - P(\cdot|s, a) \right) \cdot \hat{V}_{h+1}^n \lesssim \beta \|\phi(s, a)\|_{(\Lambda_h^n)^{-1}} = b_h^n(s, a)$. Hence, under $\mathcal{E}_{model}$, we have:

$$\hat{V}_0^n(s_0) - V_0^{\pi_n}(s_0) \leq \sum_{h=0}^{H-1} \mathbb{E}_{s, a \sim d_h^{\pi_n}} [2b_h^n(s, a)] \lesssim \sum_{h=0}^{H-1} \mathbb{E}_{s, a \sim d_h^{\pi_n}} [b_h^n(s, a)].$$

Sum over all episodes, we have the following statement.

Lemma 7.11 (Regret Bound). *Assume the event $\mathcal{E}_{model}$ holds. We have:*

$$\sum_{n=0}^{N-1} (V_0^*(s_0) - V_0^{\pi_n}(s_0)) \leq \sum_{n=0}^{N-1} \sum_{h=0}^{H-1} \mathbb{E}_{s_h^n, a_h^n \sim d_h^{\pi_n}} [b_h^n(s_h^n, a_h^n)]$$

7.6.3 Concluding the Final Regret Bound

We first consider the following elliptical potential argument, which is similar to what we have seen in the linear bandit lecture.

Lemma 7.12 (Elliptical Potential). *Consider an arbitrary sequence of state action pairs s_h^i, a_h^i . Assume $\sup_{s,a} \|\phi(s, a)\|_2 \leq 1$. Denote $\Lambda_h^n = I + \sum_{i=0}^{n-1} \phi(s_h^i, a_h^i) \phi(s_h^i, a_h^i)^\top$. We have:*

$$\sum_{i=0}^{N-1} \phi(s_h^i, a_h^i) (\Lambda_h^i)^{-1} \phi(s_h^i, a_h^i) \leq 2 \ln \left(\frac{\det(\Lambda_h^{N+1})}{\det(I)} \right) \lesssim 2d \ln(N).$$

Proof. By the Lemma 3.7 and 3.8 in the linear bandit lecture note,

$$\begin{aligned} \sum_{i=1}^N \phi(s_h^i, a_h^i) (\Lambda_h^i)^{-1} \phi(s_h^i, a_h^i) &\leq 2 \sum_{i=1}^N \ln(1 + \phi(s_h^i, a_h^i) (\Lambda_h^i)^{-1} \phi(s_h^i, a_h^i)) \\ &\leq 2 \ln \left(\frac{\det(\Lambda_h^{N+1})}{\det(I)} \right) \\ &\leq 2d \ln(1 + \frac{N+1}{d\lambda}) \lesssim 2d \ln(N). \end{aligned}$$

where the first inequality uses that for $0 \leq y \leq 1$, $\ln(1 + y) \geq y/2$. □

Now we use Lemma 7.11 together with the above inequality to conclude the proof.

Proof of main Theorem 7.9. We split the expected regret based on the event $\mathcal{E}_{model}$.

$$\begin{aligned} \mathbb{E} \left[NV^* - \sum_{n=1}^N V^{\pi_n} \right] &= \mathbb{E} \left[\mathbf{1}_{\{\mathcal{E}_{model} \text{ holds}\}} \left(NV^* - \sum_{n=1}^N V^{\pi_n} \right) \right] \\ &\quad + \mathbb{E} \left[\mathbf{1}_{\{\mathcal{E}_{model} \text{ doesn't hold}\}} \left(NV^* - \sum_{n=1}^N V^{\pi_n} \right) \right] \\ &\leq \mathbb{E} \left[\mathbf{1}_{\{\mathcal{E}_{model} \text{ holds}\}} \left(NV^* - \sum_{n=1}^N V^{\pi_n} \right) \right] + \delta NH \\ &\lesssim \mathbb{E} \left[\sum_{n=1}^N \sum_{h=0}^{H-1} b_h^n(s_h^n, a_h^n) \right] + \delta NH. \end{aligned}$$

Note that:

$$\begin{aligned} \sum_{n=1}^N \sum_{h=0}^{H-1} b_h^n(s_h^n, a_h^n) &= \beta \sum_{n=1}^N \sum_{h=0}^{H-1} \sqrt{\phi(s_h^n, a_h^n)^\top (\Lambda_h^n)^{-1} \phi(s_h^n, a_h^n)} \\ &= \beta \sum_{h=0}^{H-1} \sum_{n=1}^N \sqrt{\phi(s_h^n, a_h^n)^\top (\Lambda_h^n)^{-1} \phi(s_h^n, a_h^n)} \\ &\leq \beta \sum_{h=0}^{H-1} \sqrt{N \sum_{n=1}^N \phi(s_h^n, a_h^n) (\Lambda_h^n)^{-1} \phi(s_h^n, a_h^n)} \lesssim \beta H \sqrt{Nd \ln(N)}. \end{aligned}$$

Recall that $\beta = \tilde{O}(Hd)$. This concludes the proof. □

7.7 Bibliographic Remarks and Further Readings

There are number of ways to linearly parameterize an MDP such that it permits for efficient reinforcement learning (both statistically and computationally). The first observation that such assumptions lead to statistically efficient algorithms was due to Jiang et al. [2017] due to that these models have low Bellman rank (as we shall see in Chapter 8). The first statistically and computationally efficient algorithm for a linearly parameterized MDP model was due to Yang and Wang [2019a,b]. Subsequently, Jin et al. [2020] provided a computationally and statistically efficient algorithm for simplified version of this model, which is the model we consider here. The model of Modi et al. [2020b], Jia et al. [2020], Ayoub et al. [2020b], Zhou et al. [2020] provides another linearly parameterized model, which can viewed as parameterizing $P(s'|s, a)$ as a linear combination of feature functions $\phi(s, a, s')$. One notable aspect of the model we choose to present here, where $P_h(\cdot|s, a) = \mu_h^* \phi(s, a)$, is that this model has a number of free parameters that is $|\mathcal{S}| \cdot d$ (note that μ is unknown and is of size $|\mathcal{S}| \cdot d$), and yet the statistical complexity does not depend on $|\mathcal{S}|$. Notably, this implies that accurate model estimation request $O(|\mathcal{S}|)$ samples, while the regret for reinforcement learning is only polynomial in d . The linearly parameterized models of Modi et al. [2020b], Jia et al. [2020], Ayoub et al. [2020b], Zhou et al. [2020] are parameterized by $O(d)$ parameters, and, while $O(d)$ free parameters suggests lower model capacity (where accurate model based estimation requires only polynomial in d samples), these models are incomparable to the linearly parameterized models presented in this chapter;

It is worth observing that all of these models permit statistically efficient estimation due to that they have bounded Bellman rank Jiang et al. [2017] (and bounded Witness rank Sun et al. [2019a]), a point which we return to in the next Chapter.

The specific linear model we consider here was originally introduced by Jin et al. [2020]. The non-parametric model-based algorithm we study here was first introduced by Lykouris et al. [2019] (but under the context of adversarial attacks).

The analysis we present here does not easily extend to infinite dimensional feature ϕ (e.g., RBF kernel); here, Agarwal et al. [2020a] provide an algorithm and an analysis that extends to infinite dimensional ϕ , i.e. where we have a Reproducing Kernel Hilbert Space (RKHS) and the regret is based on the concept of Information Gain.

Chapter 8

Generalization with Bounded Bilinear Rank

Our previous lecture on linear bandits and linear MDPs gave examples of statistically efficient reinforcement learning, where we can obtain a sublinear regret with no dependence on the number of states or actions in the MDP. Obtaining sample size results which are independent of the size of the state space (and possibly the action space) is essentially a question of *generalization*, which is the focus of this chapter. In particular, we now present a more general underlying assumption which permit sample efficient reinforcement learning in various cases.

Recall our lower bounds from Chapter ?? which suggest that assumptions which would permit sample efficient RL may be subtle due to that: (i) agnostic RL is not possible and (ii) any assumption which permits sample efficient requires stronger, and possibly more subtle, conditions than simply assuming Q^* is a linear in some known features. This chapter introduces the Bellman rank condition along with a generalization, the Bilinear rank condition, which permit sample efficient RL.

This chapter follows the ideas in the original introduction of the Bellman rank Jiang et al. [2017], along with a simplified analysis and a generalized concept, the Bilinear class, provided by Du et al. [2021].

Setting and notation and setting. This chapter focuses on PAC RL (see Section 1.4), where our goal is to find a near optimal policy. We work in the episodic setting where we can obtain trajectories under some fixed s_0 (see Section 1.4), and we work in the finite horizon setting. We use the notation $a_{0:h} \sim d^\pi$ to denote the sampling of actions a_0 to a_h from trajectories under π . We also overload notation where we write $s_h, a_h \sim d_h^\pi$ for the sampled state-action pair at timestep h under π , and $s_h \sim d_h^\pi$ as the sampled state at time h under π .

8.1 Hypothesis Classes

We assume access to a hypothesis class $\mathcal{H} = \mathcal{H}_0 \times \dots \times \mathcal{H}_{H-1}$, which can be abstract sets that permit for both *model-based* and *value-based* hypotheses. The only restriction we make is that for all $f \in \mathcal{H}$, we have an associated state-action value function $Q_{h,f}$ and a value function $V_{h,f}$. Furthermore, we assume the hypothesis class is constrained so that $V_{h,f}(s) = \max_a Q_{h,f}(s, a)$ for all $f \in \mathcal{H}$, $h \in [H]$, and $s \in \mathcal{S}$, which is always possible as we can remove hypothesis for which this is not true. We let $\pi_{h,f}$ be the greedy policy with respect to $Q_{h,f}$, i.e., $\pi_{h,f}(s) = \operatorname{argmax}_{a \in \mathcal{A}} Q_{h,f}(s, a)$, and π_f as the sequence of time-dependent policies $\{\pi_{h,f}\}_{h=0}^{H-1}$.

The following provide some examples of value based and model based hypothesis classes:

- An example of *value-based hypothesis class* $\mathcal{H}$ is an explicit set of state-action value Q and value functions V i.e.

$$\mathcal{H}_h \subset \{(Q_h, V_h) \mid Q_h \text{ is a function from } \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R} \text{ and } V_h \text{ is a function from } \mathcal{S} \mapsto \mathbb{R}\}.$$

Note that in this case, for any hypothesis $f := ((Q_0, V_0), (Q_1, V_1), \dots, (Q_{H-1}, V_{H-1})) \in \mathcal{H}$, we can take the associated $Q_{h,f} = Q_h$ and associated $V_{h,f} = V_h$.

- Another example of *value-based hypothesis class* $\mathcal{H}$ is when $\mathcal{H}$ is just a set of state-action value Q functions i.e.

$$\mathcal{H}_h \subset \{Q_h \mid Q_h \text{ is a function from } \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}\}.$$

In this case, for any hypothesis $f := (Q_0, Q_1, \dots, Q_{H-1}) \in \mathcal{H}$, we can take the associated $Q_{h,f} = Q_h$ and the associated $V_{h,f}$ function to be greedy with respect to the $Q_{h,f}$ function i.e. $V_{h,f}(\cdot) = \max_{a \in \mathcal{A}} Q_{h,f}(\cdot, a)$.

- An example of *model-based hypothesis class* is when $\mathcal{H}_h$ is a set of transition models and reward functions, i.e.

$$\mathcal{H}_h \subset \{(P_h, r_h) \mid P_h \text{ is a function from } \mathcal{S} \times \mathcal{A} \mapsto \Delta(\mathcal{S}) \text{ and } r_h \text{ is a function from } \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}\}.$$

In this case, for any hypothesis $f := ((P_0, r_0), (P_1, r_1), \dots, (P_{H-1}, r_{H-1})) \in \mathcal{H}$, we can take the associated $Q_{h,f}$ and $V_{h,f}$ functions to be the optimal value functions corresponding to the transition models $\{P_h\}_{h=0}^{H-1}$ and reward functions $\{r_h\}_{h=0}^{H-1}$.

8.2 The Bellman Rank

We now make assumptions on the Bellman residual error. For the “Q-version” of the Bellman rank, we assume that the Bellman residual error, $Q - \mathcal{T}Q$, has a simple parametric form. In particular,

Definition 8.1 (*Q-Bellman Rank*). For a given MDP, a hypothesis class $\mathcal{H}$ has a *Q-Bellman rank* of dimension d if for all $h \in [H]$, there exist functions $W_h : \mathcal{H} \rightarrow \mathbb{R}^d$ and $X_h : \mathcal{H} \rightarrow \mathbb{R}^d$ with $\sup_{f \in \mathcal{H}} \|W_h(f)\|_2 \leq B_W$ and $\sup_{f \in \mathcal{H}} \|X_h(f)\|_2 \leq B_X$, such that for all $f, g \in \mathcal{H}$

$$\mathbb{E}_{a_0:h \sim d^{\pi_f}} [Q_{h,g}(s_h, a_h) - r(s_h, a_h) - V_{h+1,g}(s_{h+1})] = \langle W_h(g) - W_h(f^*), X_h(f) \rangle.$$

Importantly, the functions W_h and X_h need not be known to the learner.

Instead, of assuming this parametric assumption on the Bellman residual error of the state-action value, we consider a variant which is stated in terms of the values. Note that we can write the Bellman optimality equations (see Equation 1.7) in terms of the value functions as follows:

$$V_h(s) - \max_a (r_h(s, a) + \mathbb{E}_{s' \sim P_h(\cdot|s,a)} [V_{h+1}(s')]) = 0. \quad (8.1)$$

This motivates the following definition:

Definition 8.2 (*V-Bellman Rank*). For a given MDP, a hypothesis class $\mathcal{H}$ has a *V-Bellman rank* of dimension d if for all $h \in [H]$, there exist functions $W_h : \mathcal{H} \rightarrow \mathbb{R}^d$ and $X_h : \mathcal{H} \rightarrow \mathbb{R}^d$ with $\sup_{f \in \mathcal{H}} \|W_h(f)\|_2 \leq B_W$ and $\sup_{f \in \mathcal{H}} \|X_h(f)\|_2 \leq B_X$, such that for all $f, g \in \mathcal{H}$:

$$\mathbb{E}_{a_0:h-1 \sim d^{\pi_f}, a_h = \pi_g(s_h)} [V_{h,g}(s_h) - r(s_h, a_h) - V_{h+1,g}(s_{h+1})] = \langle W_h(g) - W_h(f^*), X_h(f) \rangle.$$

Note that the action a_h is chosen by π_g , and recall that for every g , there corresponds a $Q_{h,g}$, where both $V_{h,g}$ and π_g are the corresponding greedy value function and policy.

Let us remark on a few subtle differences in these two definitions, in terms their usage of functions $V_{h,f}$ vs $Q_{h,f}$. Roughly speaking, the former definition corresponds to an assumption on the Bellman residual error of the state-action value function, while the latter definition corresponds to an assumption on the Bellman residual error of the value functions. A more subtle distinction is that, for the Q -version, the expectation is with respect to $a_{0:h} \sim \pi_f$, while for the V -version, the expectation is with respect to $a_{0:h-1} \sim \pi_f$ and $a_h \sim \pi_g$. The use of π_g is subtly different than the expectation being taken directly on the Bellman residual error of $V_{h,g}$ due to that π_g may not correspond to the true argmax in Equation 8.1. However, as we shall see, we can find estimates of both of the relevant quantities in the Q and the V versions.

Realizability. We say that $\mathcal{H}$ is *realizable* for an MDP $\mathcal{M}$ if, for all $h \in [H]$, there exists a hypothesis $f^* \in \mathcal{H}$ such that $Q_h^*(s, a) = Q_{h,f^*}(s, a)$, where Q_h^* is the optimal state-action value at time step h in the ground truth MDP $\mathcal{M}$. For instance, for the model-based perspective, the realizability assumption is implied if the ground truth transitions $\{P_h\}_{h=0}^{H-1}$ and reward function $\{r_h\}_{h=0}^{H-1}$ belong to our hypothesis class $\mathcal{H}$.

8.3 Examples

8.3.1 Examples that have small Q -Bellman rank

Contextual Linear Bandits

Let us start with the $H = 1$ case and return to the linear bandit model from Chapter 5. Let us consider a contextual model where there is a distribution over states $s_0 \sim \mu$ and where we assume:

$$\mathbb{E}[r(s, a)] = w^* \cdot \phi(s, a).$$

Here, our hypothesis of state-action values is $\mathcal{H} = \{\theta^\top \phi(s, a) : \|\theta\|_2 \leq W\}$.

Take two hypothesis f, g where we denote $Q_{0,f}(s, a) := \theta^\top \phi(s, a)$, $Q_{0,g}(s, a) = w^\top \phi(s, a)$ (we take $h = 0$ due to that $H = 1$). We have:

$$\begin{aligned} \mathbb{E}_{a \sim d_0^{\pi_f}} [w^\top \phi(s, a) - r(s, a)] &= \mathbb{E}_{s \sim \mu, a = \pi_f(s)} [(w - w^*)^\top \phi(s, a)] \\ &= \langle w - w^*, \mathbb{E}_{s \sim \mu, a = \pi_f(s)} [\phi(s, a)] \rangle. \end{aligned}$$

Namely, we can set $W_0(g) = w$, and $X_0(f) = \mathbb{E}_{s \sim \mu, a = \pi_f(s)} [\phi(s, a)]$. Thus, we have the following:

Proposition 8.3. *In the contextual linear bandit model, we have that $\mathcal{H}$, as defined above, has a Q -Bellman rank of d .*

Linear Bellman Completion

Let us now consider the linear Bellman completion setting (Definition ??). We show that linear Bellman completion models have Q -Bellman rank equal to d . In this setting, since $Q_h^*(s, a) = (\theta_h^*)^\top \phi(s, a)$, $\forall s, a, h$, we use linear functions for our hypothesis class, i.e., $\mathcal{H}_h = \{\theta^\top \phi(s, a) : \|\theta\|_2 \leq W, \|\theta^\top \phi(\cdot, \cdot)\|_\infty \leq H\}$ for some $W \in \mathbb{R}^+$ where $\|\theta_h^*\|_2 \leq W$; as in Section 8.1, the set of values are those that are greedy with respect to these Q functions.

Recall from Definition ??, given θ , we use $\mathcal{T}_h(\theta) \in \mathbb{R}^d$ to represent the linear function resulting from the Bellman backup, i.e.,

$$\forall s, a : \mathcal{T}_h(\theta)^\top \phi(s, a) = r(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} [\max_{a'} \theta^\top \phi(s', a')].$$

We further assume feature is normalized, i.e., $\sup_{s,a} \|\phi(s,a)\|_2 \leq 1$, and $\sup_{h,\theta \in \mathcal{H}_h} \|\mathcal{T}_h(\theta)\|_2 \leq W$. Note that this condition holds in linear MDP with $W = 2H\sqrt{d}$.

Take two hypothesis f, g where we denote $Q_{h,f}(s,a) := \theta_h^\top \phi(s,a)$, $Q_{h,g}(s,a) = w_h^\top \phi(s,a)$, $\forall h$. Then for any time step $h \in [0, H-2]$, we have:

$$\begin{aligned} & \mathbb{E}_{s_h, a_h \sim d_h^{\pi_f}, s_{h+1} \sim P_h(\cdot | s_h, a_h)} \left[w_h^\top \phi(s_h, a_h) - r(s_h, a_h) - \max_{a'} w_{h+1}^\top \phi(s_{h+1}, a') \right] \\ &= \mathbb{E}_{s_h, a_h \sim d_h^{\pi_f}} \left[w_h^\top \phi(s_h, a_h) \mathcal{T}_h(w_{h+1})^\top \phi(s_h, a_h) \right] \\ &= \left\langle w_h - \mathcal{T}_h(w_{h+1}), \mathbb{E}_{s_h, a_h \sim d_h^{\pi_f}} [\phi(s_h, a_h)] \right\rangle. \end{aligned}$$

Taking $W_h(g) := w_h - \mathcal{T}_h(w_{h+1})$ (and note that $W_h(f^*) = 0$ due to the Bellman optimality condition) and $X_h(f) := \mathbb{E}_{s_h, a_h \sim d_h^{\pi_f}} [\phi(s_h, a_h)]$, we have shown the following:

Proposition 8.4. *Under the linear Bellman completion assumption, we have that $\mathcal{H}$, as defined above, has a Q -Bellman rank of d . Further more, we have $\sup_{g \in \mathcal{H}} \|W_h(g)\|_2 \leq B_W := 2W$, and $\sup_{f \in \mathcal{H}} \|X_h(f)\|_2 \leq B_X := 1$.*

There are a number of natural models which satisfy the Bellman completeness property, including contextual linear bandits, linear MDPs and Linear Quadratic Regulators (we will cover LQRs in Chapter 14).

Linear Q^* and V^*

Let us now suppose that Q_h^* and V_h^* are functions which are in the span of some given features $\phi : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^d$, $\psi : \mathcal{S} \mapsto \mathbb{R}^d$, i.e. that, for all $h \in [0, \dots, H-1]$, there exist $\theta_h^* \in \mathbb{R}^d$ and $w_h^* \in \mathbb{R}^d$, such that for all s, a , $Q_h^*(s, a) = (\theta_h^*)^\top \phi(s, a)$ and $V_h^*(s) = (w_h^*)^\top \psi(s)$.

Our hypothesis class $\mathcal{H}_h$ is defined as $\mathcal{H}_h = \{(\theta, w) : \|\theta\|_2 \leq W_1, \|w\|_2 \leq W_2, \forall s, \max_a \theta^\top \phi(s, a) = w^\top \psi(s)\}$. Take any f, g where we denote $Q_{h,g}(s, a) = \theta_h^\top \phi(s, a)$, $V_{h,g}(s) = w_h^\top \psi(s)$, we have that:

$$\begin{aligned} & \mathbb{E}_{s,a \sim d_h^{\pi_f}} [\theta_h^\top \phi(s, a) - r(s, a) - \mathbb{E}_{s' \sim P_h(\cdot | s, a)} [w_h^\top \psi(s')]] \\ &= \mathbb{E}_{s,a \sim d_h^{\pi_f}} [\theta_h^\top \phi(s, a) - Q_h^*(s, a) + \mathbb{E}_{s' \sim P_h(\cdot | s, a)} [V_h^*(s')] - \mathbb{E}_{s' \sim P_h(\cdot | s, a)} [w_h^\top \psi(s')]] \\ &= \mathbb{E}_{s,a \sim d_h^{\pi_f}} [(\theta_h - \theta_h^*)^\top \phi(s, a) + (w_h - w_h^*)^\top \mathbb{E}_{s' \sim P_h(\cdot | s, a)} [\psi(s')]] \\ &= \left\langle \begin{bmatrix} \theta_h - \theta_h^* \\ w_h - w_h^* \end{bmatrix}, \mathbb{E}_{s,a \sim d_h^{\pi_f}} \begin{bmatrix} \phi(s, a) \\ \mathbb{E}_{s' \sim P_h(\cdot | s, a)} [\psi(s')] \end{bmatrix} \right\rangle. \end{aligned}$$

Taking $W_h(g) := \begin{bmatrix} \theta_h \\ w_h \end{bmatrix}$, and $X_h(f) := \begin{bmatrix} \phi(s, a) \\ \mathbb{E}_{s' \sim P_h(\cdot | s, a)} [\psi(s')] \end{bmatrix}$, we have shown that:

Proposition 8.5. *Under the above linear Q^* and V^* assumption, our hypothesis class $\mathcal{H}$, as defined above, has a Q -Bellman rank of $2d$.*

The linear Q^* assumption vs. the linear Q^*/V^* assumption. As we saw in Chapter ??, simply assuming that Q^* is linear is not sufficient for sample efficient RL. Thus it may seem surprising that assuming both Q^* and V^* are linear (in different features) permits a sample efficient algorithm (as we shall see). However, it is worthwhile to observe how this is a substantially strong assumption. In particular, note that our hypothesis class must enforce the constraint that $\max_a \theta^\top \phi(s, a) = w^\top \psi(s)$ for all $(\theta, w) \in \mathcal{H}$; this *eliminates* functions from the set of all Q which are linear in ϕ . Furthermore, note that this pruning is done without collecting any data.

Q^* -state abstraction

The Q^* -state abstraction mode is defined as follows. There exists some abstraction function $\xi : \mathcal{S} \mapsto \mathcal{Z}$ where $|\mathcal{Z}| < |\mathcal{S}|$, such that for all h , we have:

$$\forall s, s', \xi(s) = \xi(s') \Rightarrow Q_h^*(s, a) = Q_h^*(s', a), \forall a \in \mathcal{A}, V_h^*(s) = V_h^*(s').$$

We show that this example has low Q -bellman rank by showing that it is a special case of the linear Q^* & V^* model. Specifically, let us define $\phi : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^{|\mathcal{Z}||\mathcal{A}|}$ and $\psi : \mathcal{S} \mapsto \mathbb{R}^{|\mathcal{Z}|}$ as follows:

$$\phi(s, a)_{z, a'} = \mathbf{1}\{\xi(s) = z, a = a'\}, \quad \psi(s)_z = \mathbf{1}\{\xi(s) = z\}.$$

With this feature setup, we have:

$$\begin{aligned} Q_h^*(s, a) &= (w_h^*)^\top \phi(s, a), \text{ where } (w_h^*)_{z, a} = Q^*(s, a) \text{ with } \xi(s) = z, \\ V_h^*(s) &= (\theta_h^*)^\top \psi(s), \text{ where } (\theta_h^*)_z = V^*(s) \text{ with } \xi(s) = z. \end{aligned}$$

Thus, similar to linear Q^*/V^* model above, we can set $\mathcal{H}$ such that $\mathcal{H}_h := \{(\theta, w) : \|\theta\|_2 \leq W_1, \|w\|_2 \leq W_2, \forall s, \max_s \theta^\top \phi(s, a) = w^\top \psi(s)\}$. we demonstrate that this model has Q -Bellman rank at most $|\mathcal{Z}||\mathcal{A}| + |\mathcal{Z}|$.

Proposition 8.6. *Under the above Q^* -state abstraction assumption, our hypothesis class $\mathcal{H}$ has a Q -Bellman rank of $|\mathcal{Z}||\mathcal{A}| + |\mathcal{Z}|$.*

Low-occupancy measure

An MDP has **low (state-action) occupancy measure** if the following is true. For all h , there exist two functions $\beta_h : \mathcal{H} \mapsto \mathbb{R}^d$, and $\phi_h : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^d$, such that for any $f \in \mathcal{H}$, we have:

$$d_h^{\pi_f}(s, a) = \langle \beta_h(f), \phi_h(s, a) \rangle.$$

We show that this model has Q -Bellman rank at most d . Consider any f, g and h , we have:

$$\begin{aligned} &\mathbb{E}_{s, a \sim d_h^{\pi_f}} [Q_{h, g}(s) - r(s, a) - \mathbb{E}_{s' \sim P_h(\cdot|s, a)} [V_{h+1, g}(s')]] \\ &= \beta_h(f)^\top \left(\sum_{s, a} \phi_h(s, a) [Q_{h, g}(s, a) - r(s, a) - \mathbb{E}_{s' \sim P_h(\cdot|s, a)} [V_{h+1, g}(s')]] \right), \end{aligned}$$

which shows that $W_h(g) := \sum_{s, a} \phi_h(s, a) [Q_{h, g}(s, a) - r(s, a) - \mathbb{E}_{s' \sim P_h(\cdot|s, a)} [V_{h+1, g}(s')]]$ (note that $W_h(f^*) = 0$ due to the Bellman optimality condition), and $X_h(f) := \beta_h(f)$. Note that in this model we can use any hypothesis class $\mathcal{H}$ as long as it contains f^* .

Proposition 8.7. *Any hypothesis class $\mathcal{H}$, together with the MDP that has a low-occupancy measure, has Q -Bellman rank d .*

Note that if the state distribution has low-occupancy, i.e.

$$d_h^{\pi_f}(s) = \beta_h(f)^\top \phi_h(s)$$

for some $\phi_h : \mathcal{S} \mapsto \mathbb{R}^d$, then it satisfies the V -Bellman rank condition, with rank d . In this latter case, we refer to the model as having **low (state) occupancy measure**.

8.3.2 Examples that have small V -Bellman rank

Contextual Bandit

Contextual bandit is a finite horizon MDP with $H = 1$ and finite number of actions. The contexts are states $s_0 \sim \mu$. Here our hypothesis class $\mathcal{H} = \mathcal{H}_0 = \{f : \mathcal{S} \times \mathcal{A} \mapsto [0, 1]\}$ with $r \in \mathcal{H}$. We show that the V -Bellman rank is at most A . We use the notation $V_1(s) = 0, \forall s$ (recall that $H = 1$ again). Consider any function pair $f, g \in \mathcal{H}$, note that since $H = 1$, the state distribution at $h = 0$ is independent of the policy π_f . Thus we have:

$$\mathbb{E}_{s \sim \mu} [V_{0,g}(s) - r(s, \pi_{0,g}(s))] = \sum_{a \in \mathcal{A}} \mathbb{E}_{s \sim \mu} [\mathbf{1}\{\pi_g(s) = a\} [Q_{0,g}(s, a) - r(s, a)]] .$$

This means that we can write the Bellman error of g averaged over μ as an inner product between two vectors — an all one vector, and a vector whose a -th entry is $\mathbb{E}_{s \sim \mu} [\mathbf{1}\{\pi_g(s) = a\} [Q_{0,g}(s, a) - r(s, a)]]$, i.e., we have $X_0(f) = \mathbf{1}_A$ where $\mathbf{1}_A$ represents a A -dim vector with all one, and $W_0(g) \in \mathbb{R}^A$ where the a -th entry of $W_0(g)$ is $\mathbb{E}_{s \sim \mu} [\mathbf{1}\{\pi_g(s) = a\} [Q_{0,g}(s, a) - r(s, a)]]$. Note that $W_0(f^*) = 0$ where f^* is the ground truth reward function here.

Proposition 8.8. *The hypothesis class $\mathcal{H}$ and the contextual bandit model together has a V -Bellman rank A .*

Feature Selection in Low-rank MDPs (Representation Learning)

We consider low-rank MDP where for all h , there exist $\mu^* : \mathcal{S} \mapsto \mathbb{R}^d, \phi^* : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^d$, such that for all s, s', a , we have $P_h(s'|s, a) = \mu^*(s')^\top \phi^*(s, a), r(s, a) = (\theta^*)^\top \phi^*(s, a)$. We denote $\Phi \subset \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^d$ as our feature class such that $\phi^* \in \Phi$. We assume μ^*, ϕ^*, θ^* are normalized, i.e., $\|\phi^*(s, a)\|_2 \leq 1, \forall s, a, h$, and $\|v^\top \mu^*\|_2 \leq \sqrt{d}$, for all v such that $\|v\|_\infty \leq 1, \|\theta^*\|_2 \leq \sqrt{d}$.

We denote the hypothesis class $\mathcal{H}_h := \{w^\top \phi(s, a) : \|w\|_2 \leq W, \phi \in \Phi\}$ where we can set $W = 4H\sqrt{d}$ since we can verify that for $Q_h^*(s, a)$, it is linear with respect to ϕ^* , i.e., $Q_h^*(s, a) = (w_h^*)^\top \phi(s, a)$ for some w_h^* with $\|w_h^*\|_2 \leq 2H\sqrt{d}$. Consider a pair of hypothesis (f, g) where we denote $Q_{h,g} := w_h^\top \phi$, and recall $V_{h,g}(\cdot) = \max_a Q_{h,g}(\cdot, a)$, and $\pi_{h,g}(s) := \operatorname{argmax}_a Q_{h,g}(s, a)$.

$$\mathbb{E}_{s \sim d_h^{\pi_f}} [V_{h,g}(s) - r(s, \pi_{h,g}(s)) - \mathbb{E}_{s' \sim P_h(\cdot|s, \pi_{h,g}(s))} [V_{h+1,g}(s')]] \quad (8.2)$$

$$\begin{aligned} &= \mathbb{E}_{\tilde{s}, \tilde{a} \sim d_{h-1}^{\pi_f}} \mathbb{E}_{s \sim P_{h-1}(\cdot|\tilde{s}, \tilde{a})} [V_{h,g}(s) - r(s, \pi_{h,g}(s)) - \mathbb{E}_{s' \sim P_h(\cdot|s, \pi_{h,g}(s))} [V_{h+1,g}(s')]] \\ &= \mathbb{E}_{\tilde{s}, \tilde{a} \sim d_{h-1}^{\pi_f}} \int_{\mathcal{S}} \mu^*(s)^\top \phi^*(\tilde{s}, \tilde{a}) [V_{h,g}(s) - r(s, \pi_{h,g}(s)) - \mathbb{E}_{s' \sim P_h(\cdot|s, \pi_{h,g}(s))} [V_{h+1,g}(s')]] d(s) \\ &= \left\langle \int_{\mathcal{S}} \mu^*(s) [V_{h,g}(s) - r(s, \pi_{h,g}(s)) - \mathbb{E}_{s' \sim P_h(\cdot|s, \pi_{h,g}(s))} [V_{h+1,g}(s')]] , \quad \mathbb{E}_{\tilde{s}, \tilde{a} \sim d_{h-1}^{\pi_f}} [\phi^*(\tilde{s}, \tilde{a})] \right\rangle. \quad (8.3) \end{aligned}$$

Taking $W_h(g) := \int_{\mathcal{S}} \mu^*(s) [V_{h,g}(s) - r(s, \pi_{h,g}(s)) - \mathbb{E}_{s' \sim P_h(\cdot|s, \pi_{h,g}(s))} [V_{h+1,g}(s')]]$ (note that $W_h(f^*) = 0$ due to the Bellman optimality condition) and $X_h(f) := \mathbb{E}_{\tilde{s}, \tilde{a} \sim d_{h-1}^{\pi_f}} [\phi^*(\tilde{s}, \tilde{a})]$, we have shown that:

Proposition 8.9. *The hypothesis class $\mathcal{H}$ and the low-rank MDP defined above together has V -Bellman rank d . Moreover, we have $\|X_h(f)\|_2 \leq B_X = 1$, and $\|W_h(g)\|_2 \leq B_W = 2H\sqrt{d}$.*

Block MDPs. The Block MDP has a small size discrete latent state space $\mathcal{Z}$, an emission distribution $v(\cdot; z) \in \Delta(\mathcal{S}), \forall z$, a decoder $\xi : \mathcal{S} \mapsto \mathcal{Z}$ which maps a state s to its corresponding latent state z , and a transition in latent state space $T_h(z'|z, a), \forall h$. To show that Low-rank MDP model captures it, we define $\phi^*(s, a) \in \{0, 1\}^{|\mathcal{Z}||\mathcal{A}|}$, where $\phi^*(s, a)$ is a one hot encoding vector which contains zero everywhere, except one in the entry corresponding to the latent state and action pair $(\xi(s), a)$. The corresponding $\mu^*(s') \in \mathbb{R}^{|\mathcal{Z}||\mathcal{A}|}$ is defined such that its entry corresponding to (z, a) is equal to $\sum_{z'} T(z'|z, a) v(s'; z')$. This shows that the Block MDP model is a special case of the Low-rank MDP model where the rank is the number of unique latent states.

Feature Selection in Sparse Linear MDP. A sparse linear MDP is a linear MDP where ϕ^* is known (but μ^* is unknown), and there is a subset $\mathcal{K}^* \in [d]$ with $|\mathcal{K}^*| = s$ and $s < d$, such that $P_h(s'|s, a) = \sum_{i \in \mathcal{K}^*} \mu_i^*(s') \phi_i^*(s, a)$, where we use x_i to denote the i -th element of the vector x . We can re-write the transition as $P_h(s'|s, a) = \mu_{\mathcal{K}^*}^*(s')^\top \phi_{\mathcal{K}^*}^*(s, a)$, where we denote $x_{\mathcal{K}}$ as the subvector of x that is indexed by elements in $\mathcal{K}$. Thus, this shows that a sparse linear MDP is a special case of low-rank MDP where the rank is s instead of d .

We consider the following hypothesis class. Define a representation class Φ with $|\Phi| = \binom{d}{s}$. Each $\phi \in \Phi$ corresponds to a s -size subset $\mathcal{K} \in [d]$. Given $\mathcal{K}$, we have $\phi(s, a) \in \mathbb{R}^s$, and $\phi(s, a) = \phi_{\mathcal{K}^*}^*(s, a), \forall s, a$. By the assumption that $\|\phi^*(s, a)\|_2 \leq 1$, we must have $\|\phi(s, a)\|_2 \leq 1$ for all $s, a, \phi \in \Phi$. We define $\mathcal{H}_h = \{w^\top \phi : \|w\|_2 \leq W, w \in \mathbb{R}^s, \phi \in \Phi_h, |w^\top \phi(\cdot, \cdot)| \leq H\}$. We set $W = 2H\sqrt{d}$ such that $Q_h^* \in \mathcal{H}_h$ (note that Q_h^* is a linear function with respect to $\phi_{\mathcal{K}^*}^*$ due to the fact that the MDP is a linear MDP with respect to feature $\phi_{\mathcal{K}^*}^*$).

8.4 Bilinear Classes

The Bilinear class model generalizes both the Q -Bellman rank and V -Bellman rank. We define the Bilinear class model as follows.

Definition 8.10 (Bilinear Class). Consider an MDP and a hypothesis class $\mathcal{H}$, a discrepancy function $\ell_f : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \times [H] \times \mathcal{H}$ (defined for each $f \in \mathcal{H}$), and a set of (non-stationary) estimation policy $\Pi_{est} = \{\pi_{est}(f) : f \in \mathcal{H}\}$. We say that $\{\mathcal{H}, \ell_f, \Pi_{est}, \mathcal{M}\}$ is a Bilinear class of rank d if $\mathcal{H}$ is realizable in $\mathcal{M}$, and if there exists $W_h : \mathcal{H} \mapsto \mathbb{R}^d$ and $X_h : \mathcal{H} \mapsto \mathbb{R}^d$, such that the following two properties hold for all $f \in \mathcal{H}$ and $h \in [H]$:

1. We have

$$\left| \mathbb{E}_{s, a \sim d_h^{\pi_f}, s' \sim P_h(\cdot|s, a)} [Q_{h,f}(s, a) - r(s, a) - V_{h+1,f}(s')] \right| \leq |\langle W_h(f) - W_h(f^*), X_h(f) \rangle|, \quad (8.4)$$

2. The policy $\pi_{est}(f)$ and the discrepancy ℓ_f can be used for estimation in the following sense: for any $g \in \mathcal{H}$, we have:

$$\left| \mathbb{E}_{s \sim d_h^{\pi_f}, a \sim \pi_{est,h}(s; f), s' \sim P_h(\cdot|s, a)} [\ell_f(s, a, s', h, g)] \right| = |\langle W_h(g) - W_h(f^*), X_h(f) \rangle|, \quad (8.5)$$

We suppress the h dependence on $\pi_{est,h}$ when clear from context. Typically $\pi_{est}(f)$ will be either the uniform distribution over $\mathcal{A}$ or π_f itself. In the latter case, we refer to the estimation strategy as being on-policy.

The first condition in the above definition assumes that the average Bellman error of f under π_f 's state-action distribution can be upper bounded by the value from the bilinear formulation. The second condition assumes that we have a discrepancy function that allows us to evaluate the value of the bilinear formulation. Note that the second condition permits data reuse, i.e., given a set of samples where $s \sim d_h^{\pi_f}, a \sim \pi_{est,h}(s; f), s' \sim P_h(\cdot|s, a)$, we can use the dataset to evaluate the loss for all $g \in \mathcal{H}$ simultaneously. This data reuse is the key to generalization. Also the second condition ensures that for all f , we must have $\mathbb{E}_{s \sim d_h^{\pi_f}, a \sim \pi_{est,h}(s; f), s' \sim P_h(\cdot|s, a)} [\ell_f(s, a, s', h, f^*)] = 0$.

8.4.1 Examples

Let now see how the Bilinear classes naturally generalize the Bellman rank.

Q-Bellman rank and V-Bellman rank

It is straightforward to see that the Bilinear class captures the Q -Bellman rank and V -Bellman rank models. To capture Q -Bellman rank, in Bilinear class, we will set $\ell_f := \ell$ for all f , with ℓ being defined in Eq. 8.6, and set

$\pi_{est,h}(f) = \pi_{f,h}, \forall f$. To capture V -Bellman rank, we will set $\ell_f := \ell$ for all f with ℓ being defined in Eq. 8.7, and $\pi_{est}(f) := \text{Unif}_{\mathcal{A}}$, i.e., uniform distribution over $\mathcal{A}$. More precisely, we have:

$$Q\text{-Bellman rank} : \ell(s, a, s', h, g) := Q_{h,g}(s, a) - r(s, a) - V_{h+1,g}(s'), \quad (8.6)$$

$$V\text{-Bellman rank} : \ell(s, a, s', h, g) := \frac{\mathbf{1}\{a = \pi_{h,g}(s)\}}{1/A} (Q_{h,g}(s, a) - r(s, a) - V_{h+1,g}(s')). \quad (8.7)$$

In the V -Bellman rank case, the importance weighting factor $\mathbf{1}\{a = \pi_{h,g}(s)\}/(1/A)$ ensures that given any s, g ,

$$\mathbb{E}_{a \sim \text{Unif}_{\mathcal{A}}, s' \sim P_h(\cdot|s,a)} \ell(s, a, s', g) = V_{h,g}(s) - r(s, \pi_{h,g}(s)) - \mathbb{E}_{s' \sim P_h(\cdot|s, \pi_{h,g}(s))} V_{h+1,g}(s'),$$

i.e., $\ell(s, a, s', g)$ is an unbiased estimate of the V -Bellman error of g at state s , given that $a \sim \text{Unif}_{\mathcal{A}}, s' \sim P_h(\cdot|s, a)$.

Q -Bellman and V -Bellman rank already assume the existence of two maps.

Note that by our assumption that $\|Q_{h,g}\|_{\infty} \leq H$, we have $\|\ell\|_{\infty} \leq H$ for the Q -Bellman rank case, and $\|\ell\|_{\infty} \leq AH$ for the V -Bellman rank case.

Linear mixture model

The additional f -dependent discrepancy function allows Bilinear classes to capture the following *linear mixture model*, which cannot be captured by Q or V version of the Bellman rank.

A linear mixture MDP model has a feature $\phi : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \mapsto \mathbb{R}^d$, such that $P_h(s'|s, a) = (\theta_h^*)^{\top} \phi(s, a, s')$ where we assume $\|\theta_h^*\|_2 \leq W$. We assume reward r is known.

Here, our hypothesis class $\mathcal{H}$ is a model based one, where $\mathcal{H}_h = \{(P_h, r) : P_h(s'|s, a) := \theta^{\top} \phi(s, a, s'), \|\theta\|_2 \leq W\}$. We assume that the reward function is known, and the associated Q and V function with any hypothesis is the optimal state-action value and optimal value for the associated model (as discussed in Section 8.1).

We design the discrepancy function ℓ_f as follows. Denote $g \in \mathcal{H}$ as $g = \{\theta_h^{\top} \psi(\cdot, \cdot, \cdot)\}_{h=0}^{H-1}$,

$$\ell_f(s, a, s', h, g) := \sum_{\tilde{s}} \theta_h^{\top} \phi(s, a, \tilde{s}) V_{h+1,f}(\tilde{s}) - V_{h+1,f}(s').$$

Below we show that it is a Bilinear class model. For any $f, g \in \mathcal{H}$, set $\pi_{est}(f) = \pi_f$ (i.e., on-policy), we have:

$$\begin{aligned} \mathbb{E}_{s, a \sim d_h^{\pi_f}, s' \sim P_h(\cdot|s,a)} \ell_f(s, a, s', h, g) &= \mathbb{E}_{s, a \sim d_h^{\pi_f}} \left[\sum_{\tilde{s}} \theta_h^{\top} \phi(s, a, \tilde{s}) V_{h+1,f}(\tilde{s}) - \sum_{\tilde{s}} (\theta_h^*)^{\top} \phi(s, a, \tilde{s}) V_{h+1,f}(s') \right] \\ &= (\theta_h - \theta_h^*)^{\top} \left(\mathbb{E}_{s, a \sim d_h^{\pi_f}} \left[\sum_{s'} \phi(s, a, s') \right] \right). \end{aligned}$$

Thus we have shown that $W_h(g) = \theta_h$, and $X_h(f) = \mathbb{E}_{s, a \sim d_h^{\pi_f}} [\sum_{s'} \phi(s, a, s')]$.

Proposition 8.11. *The hypothesis class $\mathcal{H}$ together with the linear mixture model is a Bilinear class.*

8.5 PAC-RL with Bounded Bilinear Rank

We now focus on the sample complexity of finding an ϵ -near optimal policy. We work in the episodic setting where we can obtain trajectories under some fixed initial state s_0 (i.e., $\mu := \delta(s_0)$). Note that generalizing to any distribution μ is straightforward.

8.5.1 Algorithm

Algorithm 7 BLin-UCB

- 1: **Input:** number of iteration T , batch size m , confidence radius R , estimation policy π_{est} , loss ℓ
- 2: **for** $t = 0 \dots T - 1$ **do**
- 3: Set f_t as the solution of the following program:

$$f_t = \operatorname{argmax}_{g \in \mathcal{H}} V_{0,g}(s_0),$$

$$\sum_{i=0}^{t-1} (\mathbb{E}_{\mathcal{D}_{t,h}} \ell_{f_t}(s, a, s', g))^2 \leq R^2, \forall h \in [0, \dots, H - 1]$$

- 4: $\forall h$, create batch data $\mathcal{D}_{t,h} = \{s^i, a^i, (s')^i\}_{i=1}^m$,
 where $s^i \sim d_h^{\pi_{f_t}}, a^i \sim \pi_{est,h}(s^i; f_t), (s')^i \sim P_h(\cdot | s^i, a^i)$ (see text for discussion).
 - 5: **end for**
 - 6: **return** $\arg \max_{\pi \in \{\pi_{f_0}, \dots, \pi_{f_{T-1}}\}} V^\pi$.
-

We present the Bilinear-UCB algorithm in Algorithm 7. Algorithm 7 uses the estimation policy $\pi_{est,h}(\cdot; f_t)$ to generate action a_t when collecting the batch $\mathcal{D}_{t,h}$ at iteration t for time step h .

Note that the samples required by Bilinear-UCB algorithm can be obtained in episodic sampling model. We simply follow π until time step h , and then use $\pi_{est}(\cdot; f_t)$ to sample the action at the timestep.

While the algorithm returns the best policy found up to time T , i.e. $\max_{t \in [T]} V^{\pi_{f_t}}$, it is also straight forward to replace this step using a sample based estimate of the best policy seen so far (with a negligible increase in the sample size).

Intuitively, BLin-UCB uses optimism for exploration. Our constraints are designed such that they eliminate functions that are not f^* . Also the threshold R will be set such that f^* is always a feasible solution with high probability. Thus, the argmax procedure in the objective function ensures that it returns an optimistic estimate, i.e., $V_{0,f_t}(s_0) \geq V_{0,f^*}(s_0)$.

8.5.2 Sample Complexity

We begin by stating the following assumption about the uniform convergence property of our hypothesis class $\mathcal{H}$.

Assumption 8.12 (Uniform Convergence). We assume that there exists a function $\varepsilon_{gen}(m, \mathcal{H}, \delta)$ such that for any distribution $\nu \in \Delta(\mathcal{S} \times \mathcal{A} \times \mathcal{S})$ and $f \in \mathcal{H}$, and any $\delta \in (0, 1)$, with probability at least $1 - \delta$ over the m i.i.d samples $\mathcal{D} := \{s_i, a_i, s'_i\}_{i=1}^m \sim \nu$, we have:

$$\sup_{g \in \mathcal{H}} |\mathbb{E}_{\mathcal{D}}[\ell_f(s, a, s', h, g)] - \mathbb{E}_{\nu}[\ell_f(s, a, s', h, g)]| \leq \varepsilon_{gen}(m, \mathcal{H}, \delta).$$

The above assumption is the standard uniform convergence result and typically we have $\varepsilon_{gen}(m, \mathcal{H}, \delta) \rightarrow 0, m \rightarrow \infty$. Below we give three examples, one for finite hypothesis class $\mathcal{H}$, one for infinite hypothesis class under the linear Bellman completion setting, and one for the infinite hypothesis class under the problem of feature selection in sparse linear MDPs.

Example 8.13 (Finite hypothesis class case). Let us consider the example where $\mathcal{H}$ is a discrete hypothesis class. In this case, for Q -Bellman rank loss, via Hoeffding's inequality and a union bound over $\mathcal{H}$, we have that with probability at least $1 - \delta$,

$$\sup_{g \in \mathcal{H}} |\mathbb{E}_{\mathcal{D}}[\ell_f(s, a, s', h, g)] - \mathbb{E}_{\nu}[\ell_f(s, a, s', h, g)]| \leq 2H \sqrt{\ln(|\mathcal{H}|/\delta)/m},$$

which means we can set

$$\varepsilon_{gen}(m, \mathcal{H}, \delta) := 2H \sqrt{\ln(|\mathcal{H}|/\delta)/m}.$$

For V -Bellman rank loss, due to the importance weighting, we have an additional A term, i.e., with probability at least $1 - \delta$,

$$\sup_{g \in \mathcal{H}} |\mathbb{E}_{\mathcal{D}}[\ell_f(s, a, s', h, g)] - \mathbb{E}_{\nu}[\ell_f(s, a, s', h, g)]| \leq 2HA \sqrt{\ln(|\mathcal{H}|/\delta)/m}.$$

Example 8.14 (Linear Bellman completion). In the linear Bellman completion model, our hypothesis class $\mathcal{H}_h = \{w^\top \phi(s, a) : \|w\|_2 \leq W, \|w^\top \phi(\cdot, \cdot)\|_\infty \leq H\}$ is not discrete. However, with the loss function associated with Q -Bellman rank, via a standard uniform convergence analysis using ϵ -net for linear functions in $\mathcal{H}$, we can show (details in Lemma A.12):

$$\sup_{g \in \mathcal{H}} |\mathbb{E}_{\mathcal{D}}[\ell_f(s, a, s', h, g)] - \mathbb{E}_{\nu}[\ell_f(s, a, s', h, g)]| \leq 3H \sqrt{(2d \ln(1 + 4Wm) + \ln(1/\delta))/m}.$$

Thus, we have

$$\varepsilon_{gen}(m, \mathcal{H}, \delta) := 3H \sqrt{\frac{2d \ln(1 + 4Wm) + \ln(1/\delta)}{m}}.$$

Example 8.15 (Feature selection for sparse linear MDP). To give another example of infinite hypothesis class case, we consider the following $\mathcal{H}$ with $\mathcal{H}_h = \{w^\top \phi : \|w\|_2 \leq 2H\sqrt{d}, w \in \mathbb{R}^s, \phi \in \Phi_h, \|w^\top \phi\|_\infty \leq H\}$ from the example of feature selection in sparse linear MDP. Recall Φ is discrete and $|\Phi| = \binom{d}{s}$. We focus on the loss function associated with V -Bellman rank. Denote $\mathcal{H}_{h,\phi} = \{w^\top \phi : \|w\|_2 \leq 2H\sqrt{d}, w \in \mathbb{R}^s, \|w^\top \phi\|_\infty \leq H\}$ for a $\phi \in \Phi$. Via a standard uniform convergence analysis using ϵ -net for linear functions in $\mathcal{H}_{h,\phi}$, we can show (details in Lemma A.12):

$$\mathbb{P} \left(\sup_{g \in \mathcal{H}_\phi} |\mathbb{E}_{\mathcal{D}}[\ell_f(s, a, s', h, g)] - \mathbb{E}_{\nu}[\ell_f(s, a, s', h, g)]| \geq 3HA \sqrt{(2s \ln(1 + 8AH\sqrt{dm}) + \ln(1/\delta))/m} \right) \leq 1 - \delta.$$

Applying a union bound over all $\phi \in \Phi$ and use the fact that $|\Phi| \leq s^d$, we have:

$$\sup_{g \in \mathcal{H}} |\mathbb{E}_{\mathcal{D}}[\ell_f(s, a, s', h, g)] - \mathbb{E}_{\nu}[\ell_f(s, a, s', h, g)]| \leq 3HA \sqrt{(2s \ln(1 + 8AH\sqrt{dm}) + s \ln(d/\delta))/m},$$

with probability at least $1 - \delta$. Thus we have

$$\varepsilon_{gen}(m, \mathcal{H}, \delta) := 3HA \sqrt{\frac{2s \ln(1 + 8AH\sqrt{dm}) + s \ln(d/\delta)}{m}}.$$

Note the polynomial dependence on s and the poly-log dependence on d .

With the above assumption, now we are ready to state the main theorem.

Theorem 8.16 (PAC RL for BLin-UCB). Fix $\delta \in (0, 1)$, batch size $m \in \mathbb{N}^+$. Suppose our hypothesis class $\mathcal{H}$ forms a Bilinear class of rank d ; that the class is realizable; and that the Bilinear-UCB algorithm has access to both $\mathcal{H}$ and the associated discrepancy function ℓ . Set the parameters as follows:

$$T = \left\lceil 2Hd \ln \left(4Hd \left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2(m, \mathcal{H}, \delta/(TH))} + 1 \right) \right) \right\rceil, \quad R = \sqrt{T} \varepsilon_{gen}(m, \mathcal{H}, \delta/(TH)).$$

Let π be the policy returned by the Bilinear-UCB algorithm (Algorithm 7). With probability at least $1 - \delta$, we have:

$$V_0^*(s_0) - V_0^\pi(s_0) \leq 5\varepsilon_{gen} \sqrt{dH^3 \ln \left(4Hd \left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2} + 1 \right) \right)}.$$

Note the total number of samples obtained is mTH .

Before proving the main theorem, we revisit the three examples above, i.e., finite hypothesis case, linear Bellman completion, and feature selection in sparse linear MDP, and derive the sample complexity bounds for these examples.

Finite hypothesis class case (Example 8.13 continued). Plugging in specific forms of $\varepsilon_{gen}(m, \mathcal{H}, \delta/(TH))$ in the above general theorem allows us to instantiate PAC bounds. Consider the Q -Bellman rank example with a discrete hypothesis class $\mathcal{H}$. In this case, as we show above, we have $\varepsilon_{gen}(m, \mathcal{H}, \delta) := 2H\sqrt{\ln(|\mathcal{H}|/\delta)/m}$. To have $V_0^*(s_0) - \max_{i \in [0, \dots, T-1]} V_0^{\pi_{f_i}}(s_0) \leq \epsilon$ for some $\epsilon \in (0, H)$, we just need to set m such that:

$$12H\sqrt{\frac{\ln(|\mathcal{H}|/\delta)}{m}}\sqrt{dH^3 \ln\left(4Hd\left(\frac{B_X^2 B_W^2 m}{4H^2 \ln(|\mathcal{H}|/\delta)} + 1\right)\right)} \leq \epsilon,$$

Using the inequality from Equation 8.9, it is suffice to set m as:

$$m = \frac{cdH^5 \ln(|\mathcal{H}|/\delta)}{\epsilon^2} \cdot \nu, \text{ where } \nu := \ln\left(\frac{dH^5}{\epsilon^2} (HdB_X^2 B_W^2 + 4Hd \ln(|\mathcal{H}|/\delta))\right),$$

and c is an absolute constant. Using the fact that $T = \left\lceil 2Hd \ln\left(4Hd\left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2(m, \mathcal{H}, \delta/(TH))} + 1\right)\right) \right\rceil$, we can reach the following corollary.

Corollary 8.17 (PAC bound for finite hypothesis $\mathcal{H}$ under Q -Bellman rank). *Fix $\epsilon, \delta \in (0, 1)$. With probability at least $1 - \delta$, BLin-UCB learns a policy π such that $V_0^*(s_0) - V_0^\pi(s_0) \leq \epsilon$, using at most*

$$\frac{cH^6 d^2 \ln(|\mathcal{H}|/\delta)}{\epsilon^2} \cdot \ln\left(4Hd\left(\frac{B_X^2 B_W^2 dH^3 \nu}{\epsilon^2} + 1\right)\right) \cdot \nu$$

many trajectories.

Linear Bellman completion (Example 8.14, continued). Plugging in the specific form of $\varepsilon_{gen}(m, \mathcal{H}, \delta/(TH))$ and $B_X = 1$ and $B_W = W$, with some linear algebra, we get:

$$\left(5\varepsilon_{gen}\sqrt{dH^3 \ln\left(4Hd\left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2} + 1\right)\right)}\right)^2 \leq c\frac{H^5 d^2}{m} \ln^2\left(\frac{H^3 d^3 W^4 m}{\delta}\right),$$

for some absolute constant c . Thus, to have $V_0^*(s_0) - \max_{i \in [0, \dots, T-1]} V_0^{\pi_{f_i}}(s_0) \leq \epsilon$ for some $\epsilon \in (0, H)$, it is suffice to set m such that:

$$c\frac{H^5 d^2}{m} \ln^2\left(\frac{H^3 d^3 W^4 m}{\delta}\right) \leq \epsilon^2.$$

Using the fact that for any positive scalars a, b , $m = 9a \ln^2(9ab)$ is a solution to the inequality $m \geq a \ln^2(bm)$, we can set m as:

$$m := \frac{c'H^5 d^2}{\epsilon^2} \cdot \nu, \text{ where } \nu := \ln^2\left(\frac{H^8 d^5 W^4}{\epsilon^2 \delta}\right).$$

Also plugging in $\varepsilon_{gen}(m, \mathcal{H}, \delta/(HT))$ into T , we get:

$$T \leq c''Hd \ln(Hd + H^6 d^3 W^2 \nu / \epsilon^2)$$

Thus, the total number of trajectories used can be upper bounded as mT . This leads to the following corollary.

Corollary 8.18 (PAC bound for linear Bellman completion). *Fix $\epsilon, \delta \in (0, 1)$. With probability at least $1 - \delta$, for the linear Bellman completion model, BLin-UCB finds a policy π such that $V_0^*(s_0) - V_0^\pi(s_0) \leq \epsilon$, using at most*

$$\frac{\tilde{c}H^6 d^3}{\epsilon^2} \cdot \nu',$$

where $\tilde{c}$ is an absolute constant, and ν' only contains log terms:

$$\nu' := \ln^2\left(\frac{H^8 d^5 W^4}{\epsilon^2 \delta}\right) \ln\left(Hd + \frac{H^6 d^3 W^2}{\epsilon^2} \ln^2\left(\frac{H^8 d^5 W^4}{\epsilon^2 \delta}\right)\right).$$

Feature Selection in Sparse linear MDP (Example 8.15, continued). Plugging in the specific form of $\varepsilon_{gen}(m, \mathcal{H}, \delta/(TH))$ and the fact that $B_X = 1$ and $B_W = 2H\sqrt{d}$, with some linear algebra, we get:

$$\left(5\varepsilon_{gen}\sqrt{dH^3\ln\left(4Hd\left(\frac{B_X^2B_W^2}{\varepsilon_{gen}^2}+1\right)\right)}\right)^2 \leq c\frac{H^5A^2s^2}{m}\ln^2\left(\frac{AH^3d^2m}{\delta}\right),$$

for some absolute constant c . Thus, to have $V_0^*(s_0) - \max_{i \in [0, \dots, T-1]} V_0^{\pi_{f_i}}(s_0) \leq \epsilon$ for some $\epsilon \in (0, H)$, it is suffice to set m such that:

$$c\frac{H^5A^2s^2}{m}\ln^2\left(\frac{AH^3d^2m}{\delta}\right) \leq \epsilon^2.$$

Using the fact that for any positive scalars a, b , $m = 9a\ln^2(9ab)$ is a solution to the inequality $m \geq a\ln^2(bm)$, we can set m as:

$$m = \frac{c'H^5A^2s^2}{\epsilon^2} \cdot \nu, \text{ where } \nu := \ln^2\left(\frac{H^8A^3s^2d^2}{\epsilon^2\delta}\right).$$

Also plugging in $\varepsilon_{gen}(m, \mathcal{H}, \delta/(HT))$ into T , we get:

$$T = c''Hs\ln(4Hs + 4H^8A^2s^2d^2\nu/\epsilon^2)$$

Note the total number of trajectories used here is mT . This leads to the following corollary.

Corollary 8.19 (PAC bound for feature selection in sparse linear MDP). *Fix $\delta, \epsilon \in (0, 1)$. With probability at least $1 - \delta$, for the sparse linear MDP model, BLin-UCB finds a policy π such that $V_0^*(s_0) - V_0^\pi(s_0) \leq \epsilon$, using total number of trajectories at most*

$$\frac{\tilde{c}H^6A^2s^3}{\epsilon^2} \cdot \nu',$$

with $\tilde{c}$ being an absolute constant, and ν' only containing log terms:

$$\nu' := \ln^2\left(\frac{H^8A^3s^2d^2}{\epsilon^2\delta}\right)\ln\left(4Hs + \frac{4H^8A^2s^2d^2}{\epsilon^2}\ln^2\left(\frac{H^8A^3s^2d^2}{\epsilon^2\delta}\right)\right).$$

Note the polynomial dependence on s instead of d (d only appears inside log-terms) in the above PAC bound, which indicates that BLin-UCB leverages the sparsity.

8.5.3 Analysis

For notational convenience, let us overload notation and write $\varepsilon_{gen} := \varepsilon_{gen}(m, \mathcal{H}, \delta/TH)$.

Lemma 8.20. *For all $h \in [0, \dots, H-1]$ and $t \in [0, \dots, T-1]$, with probability at least $1 - \delta$, we have:*

$$\sup_{g \in \mathcal{H}} \left| \mathbb{E}_{\mathcal{D}_{t,h}}[\ell_{f_t}(s, a, s', g)] - \mathbb{E}_{s \sim d_h^{\pi_{f_t}}, a \sim \pi_{est}(s), s' \sim P_h(\cdot|s,a)}[\ell_{f_t}(s, a, s', g)] \right| \leq \varepsilon_{gen}.$$

Proof. Note that the (s, a, s') triple from $\mathcal{D}_{t,h}$ is sampled as $s \sim d_h^{\pi_{f_t}}, a \sim \pi_{est}(s), s' \sim P_h(\cdot|s, a)$, in an i.i.d fashion. Thus, using assumption 8.12 and a union bound over all h and t concludes the proof. $\square$

Our next lemma is with regards to feasibility and optimism; we show that with high probability, f^* is always a feasible solution of our constrained optimization program, which implies the optimism property holds.

Lemma 8.21 (Optimism and Feasibility of f^*). *Assume the event in Lemma 8.20 holds and that $R := \sqrt{T}\varepsilon_{gen}$. We have that for all $t \in [T]$, f^* is a feasible solution of the constrained program in Alg. 7. Furthermore, we have $V_{0,f_t}(s_0) \geq V_0^*(s_0)$, for all $t \in [T]$.*

Proof. Based on the second condition in the Bilinear class (Eq. 8.5), we have that for f^* :

$$|\mathbb{E}_{s \sim d_h^{\pi_{f_t}}, a \sim \pi_{est}(s), s' \sim P_h(\cdot|s,a)} [\ell_{f_t}(s, a, s', f^*)]| = |\langle W_h(f^*) - W_h(f_t), X_h(f_t) \rangle| = 0, \forall t.$$

This and our assumption that the event in Lemma 8.20 holds imply that:

$$\begin{aligned} |\mathbb{E}_{\mathcal{D}_{t,h}} [\ell_{f_t}(s, a, s', f^*)]| &= |\mathbb{E}_{\mathcal{D}_{t,h}} [\ell_{f_t}(s, a, s', f^*)] - \mathbb{E}_{s \sim d_h^{\pi_{f_t}}, a \sim \pi_{est}(s), s' \sim P_h(\cdot|s,a)} [\ell_{f_t}(s, a, s', f^*)]| \\ &\leq \sup_{g \in \mathcal{H}} |\mathbb{E}_{\mathcal{D}_{t,h}} [\ell_{f_t}(s, a, s', g)] - \mathbb{E}_{s \sim d_h^{\pi_{f_t}}, a \sim \pi_{est}(s), s' \sim P_h(\cdot|s,a)} [\ell_{f_t}(s, a, s', g)]| \\ &\leq \varepsilon_{gen} \end{aligned}$$

This implies $\sum_{i=0}^{t-1} (\mathbb{E}_{\mathcal{D}_{i,h}} \ell_{f_i}(s, a, s', f^*))^2 \leq T\varepsilon_{gen}^2$, which completes the proof of the first claim.

For the second claim, the feasibility of f^* and the fact that f_t is the maximizer of the constrained program immediately implies the lemma. $\square$

Now we are ready to bound the per-episode regret.

Lemma 8.22. *Assume the event in Lemma 8.20 holds. For all $t \in [0, \dots, T-1]$, we have:*

$$V_0^*(s_0) - V_0^{\pi_{f_t}}(s_0) \leq \sum_{h=0}^{H-1} |\langle W_h(f_t) - W_h(f^*), X_h(f_t) \rangle|.$$

Proof. We upper bound the regret as follows. Using optimism, we have

$$\begin{aligned} V_0^*(s_0) - V_0^{\pi_{f_t}}(s_0) &\leq V_{0,f_t}(s_0) - \mathbb{E}_{s_0 \sim \mu} [V_0^{\pi_{f_t}}(s_0)] \\ &= Q_{0,f_t}(s_0, a_0) - \mathbb{E} \left[\sum_{h=0}^{H-1} r(s_h, a_h) | \pi_{f_t} \right] \\ &= \mathbb{E} \left[\sum_{h=0}^{H-1} Q_{h,f_t}(s_h, a_h) - r(s_h, a_h) + Q_{h+1,f_t}(s_{h+1}, a_{h+1}) | \pi_{f_t} \right] \\ &\leq \sum_{h=0}^{H-1} \left| \mathbb{E}_{s_h, a_h \sim d_h^{\pi_{f_t}}} [Q_{h,f_t}(s_h, a_h) - r(s_h, a_h) - \mathbb{E}_{s_{h+1} \sim P_h(\cdot|s,a)} [V_{h+1,f_t}(s_{h+1})]] \right| \\ &\leq \sum_{h=0}^{H-1} |\langle W_h(f_t) - W_h(f^*), X_h(f_t) \rangle|, \end{aligned}$$

where the first equality uses that $a_0 = \pi_{0,f_t}(s_0)$, and the fact that $\pi_{0,f_t}(s) = \operatorname{argmax}_a Q_{0,f_t}(s, a)$, the second equality uses telescoping with the definition $Q_{H,f_0}(s, a) = 0$ for all s, a , and the last equality uses the first condition in Bilinear class (Eq. 8.4) $\square$

We are now ready to prove the main theorem. The proof uses the same elliptical potential argument from Chapter 5.

Proof of Theorem 8.16. Define $\Sigma_{t,h} := \lambda I + \sum_{\tau=0}^{t-1} X_h(f_\tau) X_h^\top(f_\tau)$ (we will set λ later). First let us show that there exists an iteration t , such that for all $h \in [H]$,

$$\|X_h(f_t)\|_{\Sigma_{t,h}^{-1}}^2 \leq \exp\left(\frac{Hd}{T} \ln\left(1 + \frac{TB_X^2}{d\lambda}\right)\right) - 1, \quad \|W_h(f_t) - W_h(f^*)\|_{\Sigma_{t,h}}^2 \leq 4\lambda B_W^2 + 4T\varepsilon_{gen}^2. \quad (8.8)$$

We now prove the first claim above. Using Lemma 5.11 (from our linear bandit analysis),

$$\sum_{t=0}^{T-1} \ln\left(1 + \|X_h(f_t)\|_{\Sigma_{t,h}^{-1}}^2\right) \leq \ln \frac{\det(\Sigma_{T,h})}{\det(\lambda I)} \leq d \ln\left(1 + \frac{TB_X^2}{d\lambda}\right),$$

which holds for all h . After multiplying by $1/T$ and summing over h , leads to:

$$\frac{1}{T} \sum_{t=0}^{T-1} \sum_{h=0}^{H-1} \ln\left(1 + \|X_h(f_t)\|_{\Sigma_{t,h}^{-1}}^2\right) \leq \frac{Hd}{T} \ln\left(1 + \frac{TB_X^2}{d\lambda}\right).$$

By the intermediate value theorem, there exists a t such that $\sum_{h=0}^{H-1} \ln\left(1 + \|X_h(f_t)\|_{\Sigma_{t,h}^{-1}}^2\right) \leq \frac{Hd}{T} \ln\left(1 + TB_X^2/(d\lambda)\right)$.

This further implies that for any h in this iteration t , we have $\ln\left(1 + \|X_h(f_t)\|_{\Sigma_{t,h}^{-1}}^2\right) \leq \frac{Hd}{T} \ln\left(1 + TB_X^2/(d\lambda)\right)$. Rearranging terms proves the first claim.

Now let us prove our claim on the second term. Using the definition of $\pi_{est}(s)$ and that f_t is a feasible solution, we have that

$$\begin{aligned} \sum_{i=0}^{t-1} \left(\mathbb{E}_{s \sim d_h^{\pi_{f_i}}, a \sim \pi_{est}(s), s' \sim P_h(\cdot|s,a)} [\ell_{f_i}(s, a, s', f_t)] \right)^2 &\leq 2 \sum_{i=0}^{t-1} \left(\mathbb{E}_{\mathcal{D}_{i,h}} [\ell_{f_i}(s, a, s', f_t)] \right)^2 \\ &+ 2 \sum_{i=0}^{t-1} \left(\mathbb{E}_{s \sim d_h^{\pi_{f_t}}, a \sim \pi_{est}(s), s' \sim P_h(\cdot|s,a)} [\ell_{f_i}(s, a, s', f_t)] - \mathbb{E}_{\mathcal{D}_{i,h}} [\ell_{f_i}(s, a, s', f_t)] \right)^2 \leq 2T\varepsilon_{gen}^2 + 2T\varepsilon_{gen}^2 = 4T\varepsilon_{gen}^2, \end{aligned}$$

Using this and the second condition in the definition of Bilinear class (Eq. 8.5), we have:

$$\begin{aligned} \|W_h(f_t) - W_h(f^*)\|_{\Sigma_{t,h}}^2 &= \sum_{i=0}^{t-1} \left((W_h(f_t) - W_h(f^*))^\top X_h(f_i) \right)^2 + \lambda \|W_h(f_t) - W_h(f^*)\|_2^2 \\ &= \sum_{i=0}^{t-1} \left(\mathbb{E}_{s \sim d_h^{\pi_{f_i}}, a \sim \pi_{est}(s), s' \sim P_h(\cdot|s,a)} [\ell_{f_i}(s, a, s', f_t)] \right)^2 + \lambda \|W_h(f_t) - W_h(f^*)\|_2^2 \leq 4T\varepsilon_{gen}^2 + 4\lambda B_W^2, \end{aligned}$$

which proves our claimed bound on the second term.

Now consider the iteration t where Eqs. 8.8 hold. Using Lemma 8.22, we have:

$$\begin{aligned} V_0^*(s_0) - V_0^{\pi_{f_t}}(s_0) &\leq \sum_{h=0}^{H-1} |(W_h(f_t) - W_h(f^*))^\top X_h(f_t)| \\ &\leq \sum_{h=0}^{H-1} \|W_h(f_t) - W_h(f^*)\|_{\Sigma_{t,h}} \|X_h(f_t)\|_{\Sigma_{t,h}^{-1}} \\ &\leq H \sqrt{4\lambda B_W^2 + 4T\varepsilon_{gen}^2} \sqrt{\exp\left(\frac{Hd}{T} \ln\left(1 + \frac{TB_X^2}{d\lambda}\right)\right) - 1} \end{aligned}$$

Now let us set $1/\lambda = B_W^2/\varepsilon_{gen}^2 + 1/B_X^2$. Using this setting of λ and that $T = \left\lceil 2Hd \ln \left(4Hd \left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2} + 1 \right) \right) \right\rceil$,

$$\frac{Hd}{T} \ln \left(1 + \frac{TB_X^2}{d\lambda} \right) \leq \frac{Hd}{T} \ln \left(1 + \frac{T}{d} \cdot \left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2} + 1 \right) \right) \leq \frac{Hd}{T} \ln \left(2T \left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2} + 1 \right) \right) \leq 1,$$

where the last step follows since we can show that, for any positive a, b ,

$$\text{If } T = 2a \ln(2ab) \text{ then } a \ln(bT)/T \leq 1. \quad (8.9)$$

This implies that:

$$\begin{aligned} V_0^*(s_0) - V_0^{\pi_{f_t}}(s_0) &\leq H \sqrt{2(4\lambda B_W^2 + 4T\varepsilon_{gen}^2)} \\ &\leq H \sqrt{8\varepsilon_{gen}^2 + 16\varepsilon_{gen}^2 Hd \ln \left(4Hd \left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2} + 1 \right) \right)} \\ &\leq 5\varepsilon_{gen} \sqrt{dH^3 \ln \left(4Hd \left(\frac{B_X^2 B_W^2}{\varepsilon_{gen}^2} + 1 \right) \right)}. \end{aligned}$$

where the second inequality uses that $\lambda \leq \varepsilon_{gen}^2/B_W^2$, due to our choice of λ . This concludes the proof. $\square$

8.6 The Eluder Dimension

To be added...

8.7 Bibliographic Remarks and Further Readings

The Bellman rank was originally proposed by Jiang et al. [2017]; this original version was the V -version presented here. Both Du et al. [2021], Jin et al. [2021] noted that there are two natural versions of the Bellman rank, which we refer to as the Q and V versions. While we focus on PAC RL (i.e. finding a good policy), the work in Dong et al. [2020] showed how to obtain $O(\sqrt{T})$ regret bound for the case of the V -Bellman rank assumption; this algorithm utilized a careful sampling procedure (along with an “elimination-based” algorithm); the challenge here is that, for the V version, we do not have an “on-policy” estimation procedure, unlike for the Q version. With regards to regret bounds for the Q -version, a more direct algorithm is possible which obtains a $O(\sqrt{T})$ regret; this regret bound for the Q -version was provided by Jin et al. [2021], which essentially follows along similar lines as the original argument provided in Zanette et al. [2020] (Zanette et al. [2020] provided a $O(\sqrt{T})$ regret for the linear Bellman completion case).

The bilinear class approach was proposed in Du et al. [2021]. The algorithm and proof is inspired by Jiang et al. [2017], though it provides a more simplified analysis to obtain PAC RL bounds, using a more direct elliptical function argument (which this chapter follows).

Another generalization is provided by the Eluder dimension. The Eluder dimension was first proposed in Russo and Van Roy [2013] in a bandit setting. It was extended to RL in Osband and Roy [2014], Wang et al. [2020b], Ayoub et al. [2020a], Jin et al. [2021]. The Bellman eluder dimension and bounded bilinear rank are two different concepts. We focus on the latter one here due to that it captures nearly all the now standard parametric models which permit efficient RL, and it is relatively straightforward to verify. The Bellman eluder dimension can be thought of as specifying a more relaxed condition for when the algorithm terminates. Du et al. [2021] also shows that the Bilinear class can also capture Witness rank Sun et al. [2019a] thus capturing examples such as Factored MDPs Kearns and Koller [1999],

where Bellman rank and Bellman Eluder dimension Jin et al. [2021] could be exponentially larger than the bilinear rank.

We also add a few remarks on further readings for important special cases. The problem of feature selection in low-rank MDP was first studied in Jiang et al. [2017], and Agarwal et al. [2020b], Uehara et al. [2021] later introduced two oracle-efficient model-based algorithms, and Modi et al. [2021] introduces a model-free algorithm. The sparse linear MDP model was proposed in Hao et al. [2021] though the algorithm from Hao et al. [2021] does not perform strategic exploration. The linear mixture model was introduced and studied in Modi et al. [2020a], Ayoub et al. [2020a], Zhou et al. [2021b,a]. The linear Q^* and V^* model and the low-occupancy model were first introduced by Du et al. [2021].

Part III

Policy Optimization

Chapter 9

Policy Gradient Methods and Non-Convex Optimization

For a distribution ρ over states, define:

$$V^\pi(\rho) := \mathbb{E}_{s_0 \sim \rho}[V^\pi(s_0)],$$

where we slightly overload notation. Consider a class of parametric policies $\{\pi_\theta | \theta \in \Theta \subset \mathbb{R}^d\}$. The optimization problem of interest is:

$$\max_{\theta \in \Theta} V^{\pi_\theta}(\rho).$$

We drop the MDP subscript in this chapter.

One immediate issue is that if the policy class $\{\pi_\theta\}$ consists of deterministic policies then π_θ will, in general, not be differentiable. This motivates us to consider policy classes that are stochastic, which permit differentiability.

Example 9.1 (Softmax policies). It is instructive to explicitly consider a “tabular” policy representation, given by the *softmax policy*:

$$\pi_\theta(a|s) = \frac{\exp(\theta_{s,a})}{\sum_{a'} \exp(\theta_{s,a'})}, \quad (9.1)$$

where the parameter space is $\Theta = \mathbb{R}^{|\mathcal{S}||\mathcal{A}|}$. Note that (the closure of) the set of softmax policies contains all stationary and deterministic policies.

Example 9.2 (Log-linear policies). For any state, action pair s, a , suppose we have a feature mapping $\phi_{s,a} \in \mathbb{R}^d$. Let us consider the policy class

$$\pi_\theta(a|s) = \frac{\exp(\theta \cdot \phi_{s,a})}{\sum_{a' \in \mathcal{A}} \exp(\theta \cdot \phi_{s,a'})}$$

with $\theta \in \mathbb{R}^d$.

Example 9.3 (Neural softmax policies). Here we may be interested in working with the policy class

$$\pi_\theta(a|s) = \frac{\exp(f_\theta(s, a))}{\sum_{a' \in \mathcal{A}} \exp(f_\theta(s, a'))}$$

where the scalar function $f_\theta(s, a)$ may be parameterized by a neural network, with $\theta \in \mathbb{R}^d$.

9.1 Policy Gradient Expressions and the Likelihood Ratio Method

Let τ denote a trajectory, whose unconditional distribution $\Pr_\mu^\pi(\tau)$ under π with starting distribution μ , is

$$\Pr_\mu^\pi(\tau) = \mu(s_0)\pi(a_0|s_0)P(s_1|s_0, a_0)\pi(a_1|s_1) \cdots \quad (9.2)$$

We drop the μ subscript when it is clear from context.

It is convenient to define the discounted total reward of a trajectory as:

$$R(\tau) := \sum_{t=0}^{\infty} \gamma^t r(s_t, a_t)$$

where s_t, a_t are the state-action pairs in τ . Observe that:

$$V^{\pi_\theta}(\mu) = \mathbb{E}_{\tau \sim \Pr_\mu^{\pi_\theta}}[R(\tau)].$$

Theorem 9.4. (Policy gradients) *The following are expressions for $\nabla_\theta V^{\pi_\theta}(\mu)$:*

- *REINFORCE:*

$$\nabla V^{\pi_\theta}(\mu) = \mathbb{E}_{\tau \sim \Pr_\mu^{\pi_\theta}} \left[R(\tau) \sum_{t=0}^{\infty} \nabla \log \pi_\theta(a_t|s_t) \right]$$

- *Action value expression:*

$$\begin{aligned} \nabla V^{\pi_\theta}(\mu) &= \mathbb{E}_{\tau \sim \Pr_\mu^{\pi_\theta}} \left[\sum_{t=0}^{\infty} \gamma^t Q^{\pi_\theta}(s_t, a_t) \nabla \log \pi_\theta(a_t|s_t) \right] \\ &= \frac{1}{1-\gamma} \mathbb{E}_{s \sim d^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[Q^{\pi_\theta}(s, a) \nabla \log \pi_\theta(a|s) \right] \end{aligned}$$

- *Advantage expression:*

$$\nabla V^{\pi_\theta}(\mu) = \frac{1}{1-\gamma} \mathbb{E}_{s \sim d^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[A^{\pi_\theta}(s, a) \nabla \log \pi_\theta(a|s) \right]$$

The alternative expressions are more helpful to use when we turn to Monte Carlo estimation.

Proof. We have:

$$\begin{aligned} \nabla V^{\pi_\theta}(\mu) &= \nabla \sum_{\tau} R(\tau) \Pr_\mu^{\pi_\theta}(\tau) \\ &= \sum_{\tau} R(\tau) \nabla \Pr_\mu^{\pi_\theta}(\tau) \\ &= \sum_{\tau} R(\tau) \Pr_\mu^{\pi_\theta}(\tau) \nabla \log \Pr_\mu^{\pi_\theta}(\tau) \\ &= \sum_{\tau} R(\tau) \Pr_\mu^{\pi_\theta}(\tau) \nabla \log (\mu(s_0)\pi_\theta(a_0|s_0)P(s_1|s_0, a_0)\pi_\theta(a_1|s_1) \cdots) \\ &= \sum_{\tau} R(\tau) \Pr_\mu^{\pi_\theta}(\tau) \left(\sum_{t=0}^{\infty} \nabla \log \pi_\theta(a_t|s_t) \right) \end{aligned}$$

which completes the proof of the first claim.

For the second claim, for any state s_0

$$\begin{aligned}
& \nabla V^{\pi_\theta}(s_0) \\
&= \nabla \sum_{a_0} \pi_\theta(a_0|s_0) Q^{\pi_\theta}(s_0, a_0) \\
&= \sum_{a_0} \left(\nabla \pi_\theta(a_0|s_0) \right) Q^{\pi_\theta}(s_0, a_0) + \sum_{a_0} \pi_\theta(a_0|s_0) \nabla Q^{\pi_\theta}(s_0, a_0) \\
&= \sum_{a_0} \pi_\theta(a_0|s_0) \left(\nabla \log \pi_\theta(a_0|s_0) \right) Q^{\pi_\theta}(s_0, a_0) \\
&\quad + \sum_{a_0} \pi_\theta(a_0|s_0) \nabla \left(r(s_0, a_0) + \gamma \sum_{s_1} P(s_1|s_0, a_0) V^{\pi_\theta}(s_1) \right) \\
&= \sum_{a_0} \pi_\theta(a_0|s_0) \left(\nabla \log \pi_\theta(a_0|s_0) \right) Q^{\pi_\theta}(s_0, a_0) + \gamma \sum_{a_0, s_1} \pi_\theta(a_0|s_0) P(s_1|s_0, a_0) \nabla V^{\pi_\theta}(s_1) \\
&= \mathbb{E}_{\tau \sim \text{Pr}_{s_0}^{\pi_\theta}} [Q^{\pi_\theta}(s_0, a_0) \nabla \log \pi_\theta(a_0|s_0)] + \gamma \mathbb{E}_{\tau \sim \text{Pr}_{s_0}^{\pi_\theta}} [\nabla V^{\pi_\theta}(s_1)].
\end{aligned}$$

By linearity of expectation,

$$\begin{aligned}
& \nabla V^{\pi_\theta}(\mu) \\
&= \mathbb{E}_{\tau \sim \text{Pr}_\mu^{\pi_\theta}} [Q^{\pi_\theta}(s_0, a_0) \nabla \log \pi_\theta(a_0|s_0)] + \gamma \mathbb{E}_{\tau \sim \text{Pr}_\mu^{\pi_\theta}} [\nabla V^{\pi_\theta}(s_1)] \\
&= \mathbb{E}_{\tau \sim \text{Pr}_\mu^{\pi_\theta}} [Q^{\pi_\theta}(s_0, a_0) \nabla \log \pi_\theta(a_0|s_0)] + \gamma \mathbb{E}_{\tau \sim \text{Pr}_\mu^{\pi_\theta}} [Q^{\pi_\theta}(s_1, a_1) \nabla \log \pi_\theta(a_1|s_1)] + \dots
\end{aligned}$$

where the last step follows from recursion. This completes the proof of the second claim.

The proof of the final claim is left as an exercise to the reader. $\square$

9.2 (Non-convex) Optimization

It is worth explicitly noting that $V^{\pi_\theta}(s)$ is non-concave in θ for the softmax parameterizations, so the standard tools of convex optimization are not applicable.

Lemma 9.5. (Non-convexity) *There is an MDP M (described in Figure 9.1) such that the optimization problem $V^{\pi_\theta}(s)$ is not concave for both the direct and softmax parameterizations.*

Proof. Recall the MDP in Figure 9.1. Note that since actions in terminal states s_3 , s_4 and s_5 do not change the expected reward, we only consider actions in states s_1 and s_2 . Let the "up/above" action as a_1 and "right" action as a_2 . Note that

$$V^\pi(s_1) = \pi(a_2|s_1)\pi(a_1|s_2) \cdot r$$

Now consider

$$\theta^{(1)} = (\log 1, \log 3, \log 3, \log 1), \quad \theta^{(2)} = (-\log 1, -\log 3, -\log 3, -\log 1)$$

where θ is written as a tuple $(\theta_{a_1, s_1}, \theta_{a_2, s_1}, \theta_{a_1, s_2}, \theta_{a_2, s_2})$. Then, for the softmax parameterization, we have:

$$\pi^{(1)}(a_2|s_1) = \frac{3}{4}; \quad \pi^{(1)}(a_1|s_2) = \frac{3}{4}; \quad V^{(1)}(s_1) = \frac{9}{16}r$$

and

$$\pi^{(2)}(a_2|s_1) = \frac{1}{4}; \quad \pi^{(2)}(a_1|s_2) = \frac{1}{4}; \quad V^{(2)}(s_1) = \frac{1}{16}r.$$




Figure 9.1: (Non-concavity example) A deterministic MDP corresponding to Lemma 9.5 where $V^{\pi_\theta}(s)$ is not concave. Numbers on arrows represent the rewards for each action.

Also, for $\theta^{(\text{mid})} = \frac{\theta^{(1)} + \theta^{(2)}}{2}$,

$$\pi^{(\text{mid})}(a_2|s_1) = \frac{1}{2}; \quad \pi^{(\text{mid})}(a_1|s_2) = \frac{1}{2}; \quad V^{(\text{mid})}(s_1) = \frac{1}{4}r.$$

This gives

$$V^{(1)}(s_1) + V^{(2)}(s_1) > 2V^{(\text{mid})}(s_1),$$

which shows that V^π is non-concave. □

9.2.1 Gradient ascent and convergence to stationary points

Let us say a function $f : \mathbb{R}^d \rightarrow \mathbb{R}$ is β -smooth if

$$\|\nabla f(w) - \nabla f(w')\| \leq \beta \|w - w'\|, \quad (9.3)$$

where the norm $\|\cdot\|$ is the Euclidean norm. In other words, the derivatives of f do not change too quickly.

Gradient ascent, with a fixed stepsize η , follows the update rule:

$$\theta_{t+1} = \theta_t + \eta \nabla V^{\pi_{\theta_t}}(\mu).$$

It is convenient to use the shorthand notation:

$$\pi^{(t)} := \pi_{\theta_t}, \quad V^{(t)} := V^{\pi_{\theta_t}}$$

The next lemma is standard in non-convex optimization.

Lemma 9.6. (Convergence to Stationary Points) Assume that for all $\theta \in \Theta$, V^{π_θ} is β -smooth and bounded below by V_* . Suppose we use the constant stepsize $\eta = 1/\beta$. For all T , we have that

$$\min_{t \leq T} \|\nabla V^{(t)}(\mu)\|^2 \leq \frac{2\beta(V^*(\mu) - V^{(0)}(\mu))}{T}.$$

9.2.2 Monte Carlo estimation and stochastic gradient ascent

One difficulty is that even if we know the MDP M , computing the gradient may be computationally intensive. It turns out that we can obtain unbiased estimates of π with only simulation based access to our model, i.e. assuming we can obtain sampled trajectories $\tau \sim \Pr_{\mu}^{\pi_{\theta}}$.

With respect to a trajectory τ , define:

$$\begin{aligned}\widehat{Q}^{\pi_{\theta}}(s_t, a_t) &:= \sum_{t'=t}^{\infty} \gamma^{t'-t} r(s_{t'}, a_{t'}) \\ \widehat{\nabla V}^{\pi_{\theta}}(\mu) &:= \sum_{t=0}^{\infty} \gamma^t \widehat{Q}^{\pi_{\theta}}(s_t, a_t) \nabla \log \pi_{\theta}(a_t | s_t)\end{aligned}$$

We now show this provides an unbiased estimated of the gradient:

Lemma 9.7. (Unbiased gradient estimate) *We have :*

$$\mathbb{E}_{\tau \sim \Pr_{\mu}^{\pi_{\theta}}} [\widehat{\nabla V}^{\pi_{\theta}}(\mu)] = \nabla V^{\pi_{\theta}}(\mu)$$

Proof. Observe:

$$\begin{aligned}\mathbb{E}[\widehat{\nabla V}^{\pi_{\theta}}(\mu)] &= \mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t \widehat{Q}^{\pi_{\theta}}(s_t, a_t) \nabla \log \pi_{\theta}(a_t | s_t) \right] \\ &\stackrel{(a)}{=} \mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t \mathbb{E}[\widehat{Q}^{\pi_{\theta}}(s_t, a_t) | s_t, a_t] \nabla \log \pi_{\theta}(a_t | s_t) \right] \\ &\stackrel{(b)}{=} \mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t Q^{\pi_{\theta}}(s_t, a_t) \nabla \log \pi_{\theta}(a_t | s_t) \right]\end{aligned}$$

where (a) follows from the tower property of the conditional expectations and (b) follows from that the Markov property implies $\mathbb{E}[\widehat{Q}^{\pi_{\theta}}(s_t, a_t) | s_t, a_t] = Q^{\pi_{\theta}}(s_t, a_t)$. $\square$

Hence, the following procedure is a stochastic gradient ascent algorithm:

1. initialize θ_0 .
2. For $t = 0, 1, \dots$
 - (a) Sample $\tau \sim \Pr_{\mu}^{\pi_{\theta}}$.
 - (b) Update:

$$\theta_{t+1} = \theta_t + \eta_t \widehat{\nabla V}^{\pi_{\theta}}(\mu)$$

where η_t is the stepsize and $\widehat{\nabla V}^{\pi_{\theta}}(\mu)$ estimated with τ .

Note here that we are ignoring that τ is an infinite length sequence. It can be truncated appropriately so as to control the bias.

The following is standard result with regards to non-convex optimization. Again, with reasonably bounded variance, we will obtain a point θ_t with small gradient norm.

Lemma 9.8. (Stochastic Convergence to Stationary Points) Assume that for all $\theta \in \Theta$, V^{π_θ} is β -smooth and bounded below by V_* . Suppose the variance is bounded as follows:

$$\mathbb{E}[\|\widehat{\nabla V^{\pi_\theta}}(\mu) - \nabla V^{\pi_\theta}(\mu)\|^2] \leq \sigma^2$$

For $t \leq \beta(V^*(\mu) - V^{(0)}(\mu))/\sigma^2$, suppose we use a constant stepsize of $\eta_t = 1/\beta$, and thereafter, we use $\eta_t = \sqrt{2/(\beta T)}$. For all T , we have:

$$\min_{t \leq T} \mathbb{E}[\|\nabla V^{(t)}(\mu)\|^2] \leq \frac{2\beta(V^*(\mu) - V^{(0)}(\mu))}{T} + \sqrt{\frac{2\sigma^2}{T}}.$$

Baselines and stochastic gradient ascent

A significant practical issue is that the variance σ^2 is often large in practice. Here, a form of variance reduction is often critical in practice. A common method is as follows.

Let $f : \mathcal{S} \rightarrow \mathbb{R}$.

1. Construct f as an estimate of $V^{\pi_\theta}(\mu)$. This can be done using any previous data.
2. Sample a new trajectory τ , and define:

$$\begin{aligned} \widehat{Q^{\pi_\theta}}(s_t, a_t) &:= \sum_{t'=t}^{\infty} \gamma^{t'-t} r(s_{t'}, a_{t'}) \\ \widehat{\nabla V^{\pi_\theta}}(\mu) &:= \sum_{t=0}^{\infty} \gamma^t \left(\widehat{Q^{\pi_\theta}}(s_t, a_t) - f(s_t) \right) \nabla \log \pi_\theta(a_t | s_t) \end{aligned}$$

We often refer to $f(s)$ as a *baseline* at state s .

Lemma 9.9. (Unbiased gradient estimate with Variance Reduction) For any procedure used to construct the baseline function $f : \mathcal{S} \rightarrow \mathbb{R}$, if the samples used to construct f are independent of the trajectory τ , where $\widehat{Q^{\pi_\theta}}(s_t, a_t)$ is constructed using τ , then:

$$\mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t \left(\widehat{Q^{\pi_\theta}}(s_t, a_t) - f(s_t) \right) \nabla \log \pi_\theta(a_t | s_t) \right] = \nabla V^{\pi_\theta}(\mu)$$

where the expectation is with respect to both the random trajectory τ and the random function $f(\cdot)$.

Proof. For any function $g(s)$,

$$\mathbb{E}[\nabla \log \pi(a|s)g(s)] = \sum_a \nabla \pi(a|s)g(s) = g(s) \sum_a \nabla \pi(a|s) = g(s) \nabla \sum_a \pi(a|s) = g(s) \nabla 1 = 0$$

Using that $f(\cdot)$ is independent of τ , we have that for all t

$$\mathbb{E} \left[\sum_{t=0}^{\infty} \gamma^t f(s_t) \nabla \log \pi_\theta(a_t | s_t) \right] = 0$$

The result now follow from Lemma 9.7. □

9.3 Bibliographic Remarks and Further Readings

The REINFORCE algorithm is due to Williams [1992], which is an example of the likelihood ratio method for gradient estimation Glynn [1990].

For standard optimization results in non-convex optimization (e.g. Lemma 9.6 and 9.8), we refer the reader to Beck [2017]. Our results for convergence rates for SGD to approximate stationary points follow from Ghadimi and Lan [2013].

Chapter 10

Optimality

We now seek to understand the global convergence properties of policy gradient methods, when given exact gradients. Here, we will largely limit ourselves to the (tabular) softmax policy class in Example 9.1.

Given our a starting distribution ρ over states, recall our objective is:

$$\max_{\theta \in \Theta} V^{\pi_\theta}(\rho).$$

where $\{\pi_\theta | \theta \in \Theta \subset \mathbb{R}^d\}$ is some class of parametric policies.

While we are interested in good performance under ρ , we will see how it is helpful to optimize under a different measure μ . Specifically, we consider optimizing $V^{\pi_\theta}(\mu)$, i.e.

$$\max_{\theta \in \Theta} V^{\pi_\theta}(\mu),$$

even though our ultimate goal is performance under $V^{\pi_\theta}(\rho)$.

We now consider the softmax policy parameterization (9.1). Here, we still have a non-concave optimization problem in general, as shown in Lemma 9.5, though we do show that global optimality can be reached under certain regularity conditions. From a practical perspective, the softmax parameterization of policies is preferable to the direct parameterization, since the parameters θ are unconstrained and standard unconstrained optimization algorithms can be employed. However, optimization over this policy class creates other challenges as we study in this section, as the optimal policy (which is deterministic) is attained by sending the parameters to infinity.

This chapter will study three algorithms for this problem, for the softmax policy class. The first performs direct policy gradient ascent on the objective without modification, while the second adds a log barrier regularizer to keep the parameters from becoming too large, as a means to ensure adequate exploration. Finally, we study the natural policy gradient algorithm and establish a global optimality convergence rate, with no dependence on the dimension-dependent factors.

The presentation in this chapter largely follows the results in Agarwal et al. [2020d].

10.1 Vanishing Gradients and Saddle Points

To understand the necessity of optimizing under a distribution μ that is different from ρ , let us first give an informal argument that some condition on the state distribution of π , or equivalently μ , is necessary for stationarity to imply




Figure 10.1: (Vanishing gradient example) A deterministic, chain MDP of length $H + 2$. We consider a policy where $\pi(a|s_i) = \theta_{s_i,a}$ for $i = 1, 2, \dots, H$. Rewards are 0 everywhere other than $r(s_{H+1}, a_1) = 1$. See Proposition 10.1.

optimality. For example, in a sparse-reward MDP (where the agent is only rewarded upon visiting some small set of states), a policy that does not visit *any* rewarding states will have zero gradient, even though it is arbitrarily suboptimal in terms of values. Below, we give a more quantitative version of this intuition, which demonstrates that even if π chooses all actions with reasonable probabilities (and hence the agent will visit all states if the MDP is connected), then there is an MDP where a large fraction of the policies π have vanishingly small gradients, and yet these policies are highly suboptimal in terms of their value.

Concretely, consider the chain MDP of length $H + 2$ shown in Figure 10.1. The starting state of interest is state s_0 and the discount factor $\gamma = H/(H + 1)$. Suppose we work with the direct parameterization, where $\pi_\theta(a|s) = \theta_{s,a}$ for $a = a_1, a_2, a_3$ and $\pi_\theta(a_4|s) = 1 - \theta_{s,a_1} - \theta_{s,a_2} - \theta_{s,a_3}$. Note we do not over-parameterize the policy. For this MDP and policy structure, if we were to initialize the probabilities over actions, say deterministically, then there is an MDP (obtained by permuting the actions) where all the probabilities for a_1 will be less than $1/4$.

The following result not only shows that the gradient is exponentially small in H , it also shows that many higher order derivatives, up to $O(H/\log H)$, are also exponentially small in H .

Proposition 10.1 (Vanishing gradients at suboptimal parameters). *Consider the chain MDP of Figure 10.1, with $H + 2$ states, $\gamma = H/(H + 1)$, and with the direct policy parameterization (with $3|S|$ parameters, as described in the text above). Suppose θ is such that $0 < \theta < 1$ (componentwise) and $\theta_{s,a_1} < 1/4$ (for all states s). For all $k \leq \frac{H}{40 \log(2H)} - 1$, we have $\|\nabla_\theta^k V^{\pi_\theta}(s_0)\| \leq (1/3)^{H/4}$, where $\nabla_\theta^k V^{\pi_\theta}(s_0)$ is a tensor of the k_{th} order derivatives of $V^{\pi_\theta}(s_0)$ and the norm is the operator norm of the tensor.¹ Furthermore, $V^*(s_0) - V^{\pi_\theta}(s_0) \geq (H + 1)/8 - (H + 1)^2/3^H$.*

We do not prove this lemma here (see Section 10.5). The lemma illustrates that lack of good exploration can indeed be detrimental in policy gradient algorithms, since the gradient can be small either due to π being near-optimal, or, simply because π does not visit advantageous states often enough. Furthermore, this lemma also suggests that varied results in the non-convex optimization literature, on escaping from saddle points, do not directly imply global convergence due to that the higher order derivatives are small.

While the chain MDP of Figure 10.1, is a common example where *sample* based estimates of gradients will be 0 under random exploration strategies; there is an exponentially small in H chance of hitting the goal state under a random exploration strategy. Note that this lemma is with regards to *exact* gradients. This suggests that even with exact computations (along with using exact higher order derivatives) we might expect numerical instabilities.

10.2 Policy Gradient Ascent

Let us now return to the softmax policy class, from Equation 9.1, where:

$$\pi_\theta(a|s) = \frac{\exp(\theta_{s,a})}{\sum_{a'} \exp(\theta_{s,a'})},$$

¹The operator norm of a k_{th} -order tensor $J \in \mathbb{R}^{d^{\otimes k}}$ is defined as $\sup_{u_1, \dots, u_k \in \mathbb{R}^d} \langle J, u_1 \otimes \dots \otimes u_k \rangle$.

where the number of parameters in this policy class is $|\mathcal{S}||\mathcal{A}|$.

Observe that:

$$\frac{\partial \log \pi_\theta(a|s)}{\partial \theta_{s',a'}} = \mathbb{1}[s = s'] \left(\mathbb{1}[a = a'] - \pi_\theta(a'|s) \right)$$

where $\mathbb{1}[\mathcal{E}]$ is the indicator of $\mathcal{E}$ being true.

Lemma 10.2. *For the softmax policy class, we have:*

$$\frac{\partial V^{\pi_\theta}(\mu)}{\partial \theta_{s,a}} = \frac{1}{1-\gamma} d_\mu^{\pi_\theta}(s) \pi_\theta(a|s) A^{\pi_\theta}(s, a) \quad (10.1)$$

Proof. Using the advantage expression for the policy gradient (see Theorem 9.4),

$$\begin{aligned} \frac{\partial V^{\pi_\theta}(\mu)}{\partial \theta_{s',a'}} &= \frac{1}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[A^{\pi_\theta}(s, a) \frac{\partial \log \pi_\theta(a|s)}{\partial \theta_{s',a'}} \right] \\ &= \frac{1}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[A^{\pi_\theta}(s, a) \mathbb{1}[s = s'] \left(\mathbb{1}[a = a'] - \pi_\theta(a'|s) \right) \right] \\ &= \frac{1}{1-\gamma} d_\mu^{\pi_\theta}(s') \mathbb{E}_{a \sim \pi_\theta(\cdot|s')} \left[A^{\pi_\theta}(s', a) \left(\mathbb{1}[a = a'] - \pi_\theta(a'|s') \right) \right] \\ &= \frac{1}{1-\gamma} d_\mu^{\pi_\theta}(s') \left(\mathbb{E}_{a \sim \pi_\theta(\cdot|s')} \left[A^{\pi_\theta}(s', a) \mathbb{1}[a = a'] \right] - \pi_\theta(a'|s') \mathbb{E}_{a \sim \pi_\theta(\cdot|s')} \left[A^{\pi_\theta}(s', a) \right] \right) \\ &= \frac{1}{1-\gamma} d_\mu^{\pi_\theta}(s') \pi_\theta(a'|s') A^{\pi_\theta}(s', a') - 0, \end{aligned}$$

where the last step uses that for any policy $\sum_a \pi(a|s) A^\pi(s, a) = 0$. □

The update rule for gradient ascent is:

$$\theta^{(t+1)} = \theta^{(t)} + \eta \nabla_\theta V^{(t)}(\mu). \quad (10.2)$$

Recall from Lemma 9.5 that, even for the case of the softmax policy class (which contains all stationary policies), our optimization problem is non-convex. Furthermore, due to the exponential scaling with the parameters θ in the softmax parameterization, *any* policy that is nearly deterministic will have gradients close to 0. Specifically, for any sequence of policies π^{θ_t} that becomes deterministic, $\|\nabla V^{\pi^{\theta_t}}\| \rightarrow 0$.

In spite of these difficulties, it turns out we have a positive result that gradient ascent asymptotically converges to the global optimum for the softmax parameterization.

Theorem 10.3 (Global convergence for softmax parameterization). *Assume we follow the gradient ascent update rule as specified in Equation (10.2) and that the distribution μ is strictly positive i.e. $\mu(s) > 0$ for all states s . Suppose $\eta \leq \frac{(1-\gamma)^3}{8}$, then we have that for all states s , $V^{(t)}(s) \rightarrow V^*(s)$ as $t \rightarrow \infty$.*

The proof is somewhat technical, and we do not provide a proof here (see Section 10.5).

A few remarks are in order. Theorem 10.3 assumed that optimization distribution μ was *strictly* positive, i.e. $\mu(s) > 0$ for all states s . We conjecture that any gradient ascent may not globally converge if this condition is not met. The concern is that if this condition is not met, then gradient ascent may not globally converge due to that $d_\mu^{\pi_\theta}(s)$ effectively scales down the learning rate for the parameters associated with state s (see Equation 10.1).

Furthermore, there is strong reason to believe that the convergence rate for this is algorithm (in the worst case) is exponentially slow in some of the relevant quantities, such as in terms of the size of state space. We now turn to a regularization based approach to ensure convergence at a polynomial rate in all relevant quantities.

10.3 Log Barrier Regularization

Due to the exponential scaling with the parameters θ , policies can rapidly become near deterministic, when optimizing under the softmax parameterization, which can result in slow convergence. Indeed a key challenge in the asymptotic analysis in the previous section was to handle the growth of the absolute values of parameters as they tend to infinity. Recall that the relative-entropy for distributions p and q is defined as:

$$\text{KL}(p, q) := \mathbb{E}_{x \sim p}[-\log q(x)/p(x)].$$

Denote the uniform distribution over a set $\mathcal{X}$ by $\text{Unif}_{\mathcal{X}}$, and define the following log barrier regularized objective as:

$$\begin{aligned} L_{\lambda}(\theta) &:= V^{\pi_{\theta}}(\mu) - \lambda \mathbb{E}_{s \sim \text{Unif}_{\mathcal{S}}} \left[\text{KL}(\text{Unif}_{\mathcal{A}}, \pi_{\theta}(\cdot|s)) \right] \\ &= V^{\pi_{\theta}}(\mu) + \frac{\lambda}{|\mathcal{S}| |\mathcal{A}|} \sum_{s,a} \log \pi_{\theta}(a|s) + \lambda \log |\mathcal{A}|, \end{aligned} \quad (10.3)$$

where λ is a regularization parameter. The constant (i.e. the last term) is not relevant with regards to optimization. This regularizer is different from the more commonly utilized entropy regularizer, a point which we return to later.

The policy gradient ascent updates for $L_{\lambda}(\theta)$ are given by:

$$\theta^{(t+1)} = \theta^{(t)} + \eta \nabla_{\theta} L_{\lambda}(\theta^{(t)}). \quad (10.4)$$

We now see that any approximate first-order stationary points of the entropy-regularized objective is approximately globally optimal, provided the regularization is sufficiently small.

Theorem 10.4. (*Log barrier regularization*) Suppose θ is such that:

$$\|\nabla_{\theta} L_{\lambda}(\theta)\|_2 \leq \epsilon_{opt}$$

and $\epsilon_{opt} \leq \lambda/(2|\mathcal{S}| |\mathcal{A}|)$. Then we have that for all starting state distributions ρ :

$$V^{\pi_{\theta}}(\rho) \geq V^{\star}(\rho) - \frac{2\lambda}{1-\gamma} \left\| \frac{d_{\rho}^{\pi^{\star}}}{\mu} \right\|_{\infty}.$$

We refer to $\left\| \frac{d_{\rho}^{\pi^{\star}}}{\mu} \right\|_{\infty}$ as the *distribution mismatch coefficient*. The above theorem shows the importance of having an appropriate measure $\mu(s)$ in order for the approximate first-order stationary points to be near optimal.

Proof. The proof consists of showing that $\max_a A^{\pi_{\theta}}(s, a) \leq 2\lambda/(\mu(s)|\mathcal{S}|)$ for all states. To see that this is sufficient, observe that by the performance difference lemma (Lemma 1.16),

$$\begin{aligned} V^{\star}(\rho) - V^{\pi_{\theta}}(\rho) &= \frac{1}{1-\gamma} \sum_{s,a} d_{\rho}^{\pi^{\star}}(s) \pi^{\star}(a|s) A^{\pi_{\theta}}(s, a) \\ &\leq \frac{1}{1-\gamma} \sum_s d_{\rho}^{\pi^{\star}}(s) \max_{a \in \mathcal{A}} A^{\pi_{\theta}}(s, a) \\ &\leq \frac{1}{1-\gamma} \sum_s 2d_{\rho}^{\pi^{\star}}(s) \lambda/(\mu(s)|\mathcal{S}|) \\ &\leq \frac{2\lambda}{1-\gamma} \max_s \left(\frac{d_{\rho}^{\pi^{\star}}(s)}{\mu(s)} \right). \end{aligned}$$

which would then complete the proof.

We now proceed to show that $\max_a A^{\pi_\theta}(s, a) \leq 2\lambda/(\mu(s)|\mathcal{S}|)$. For this, it suffices to bound $A^{\pi_\theta}(s, a)$ for any state-action pair s, a where $A^{\pi_\theta}(s, a) \geq 0$ else the claim is trivially true. Consider an (s, a) pair such that $A^{\pi_\theta}(s, a) > 0$. Using the policy gradient expression for the softmax parameterization (see Equation 10.1),

$$\frac{\partial L_\lambda(\theta)}{\partial \theta_{s,a}} = \frac{1}{1-\gamma} d_\mu^{\pi_\theta}(s) \pi_\theta(a|s) A^{\pi_\theta}(s, a) + \frac{\lambda}{|\mathcal{S}|} \left(\frac{1}{|\mathcal{A}|} - \pi_\theta(a|s) \right). \quad (10.5)$$

The gradient norm assumption $\|\nabla_\theta L_\lambda(\theta)\|_2 \leq \epsilon_{\text{opt}}$ implies that:

$$\begin{aligned} \epsilon_{\text{opt}} &\geq \frac{\partial L_\lambda(\theta)}{\partial \theta_{s,a}} = \frac{1}{1-\gamma} d_\mu^{\pi_\theta}(s) \pi_\theta(a|s) A^{\pi_\theta}(s, a) + \frac{\lambda}{|\mathcal{S}|} \left(\frac{1}{|\mathcal{A}|} - \pi_\theta(a|s) \right) \\ &\geq \frac{\lambda}{|\mathcal{S}|} \left(\frac{1}{|\mathcal{A}|} - \pi_\theta(a|s) \right), \end{aligned}$$

where we have used $A^{\pi_\theta}(s, a) \geq 0$. Rearranging and using our assumption $\epsilon_{\text{opt}} \leq \lambda/(2|\mathcal{S}||\mathcal{A}|)$,

$$\pi_\theta(a|s) \geq \frac{1}{|\mathcal{A}|} - \frac{\epsilon_{\text{opt}}|\mathcal{S}|}{\lambda} \geq \frac{1}{2|\mathcal{A}|}.$$

Solving for $A^{\pi_\theta}(s, a)$ in (10.5), we have:

$$\begin{aligned} A^{\pi_\theta}(s, a) &= \frac{1-\gamma}{d_\mu^{\pi_\theta}(s)} \left(\frac{1}{\pi_\theta(a|s)} \frac{\partial L_\lambda(\theta)}{\partial \theta_{s,a}} + \frac{\lambda}{|\mathcal{S}|} \left(1 - \frac{1}{\pi_\theta(a|s)|\mathcal{A}|} \right) \right) \\ &\leq \frac{1-\gamma}{d_\mu^{\pi_\theta}(s)} \left(2|\mathcal{A}|\epsilon_{\text{opt}} + \frac{\lambda}{|\mathcal{S}|} \right) \\ &\leq 2 \frac{1-\gamma}{d_\mu^{\pi_\theta}(s)} \frac{\lambda}{|\mathcal{S}|} \\ &\leq 2\lambda/(\mu(s)|\mathcal{S}|), \end{aligned}$$

where the penultimate step uses $\epsilon_{\text{opt}} \leq \lambda/(2|\mathcal{S}||\mathcal{A}|)$ and the final step uses $d_\mu^{\pi_\theta}(s) \geq (1-\gamma)\mu(s)$. This completes the proof. $\square$

The policy gradient ascent updates for $L_\lambda(\theta)$ are given by:

$$\theta^{(t+1)} = \theta^{(t)} + \eta \nabla_\theta L_\lambda(\theta^{(t)}). \quad (10.6)$$

By combining the above theorem with the convergence of gradient ascent to first order stationary points (Lemma 9.6), we obtain the following corollary.

Corollary 10.5. (*Iteration complexity with log barrier regularization*) Let $\beta_\lambda := \frac{8\gamma}{(1-\gamma)^3} + \frac{2\lambda}{|\mathcal{S}|}$. Starting from any initial $\theta^{(0)}$, consider the updates (10.6) with $\lambda = \frac{\epsilon(1-\gamma)}{2\left\|\frac{d_\rho^{\pi^*}}{\mu}\right\|_\infty}$ and $\eta = 1/\beta_\lambda$. Then for all starting state distributions ρ ,

we have

$$\min_{t < T} \left\{ V^*(\rho) - V^{(t)}(\rho) \right\} \leq \epsilon \quad \text{whenever} \quad T \geq \frac{320|\mathcal{S}|^2|\mathcal{A}|^2}{(1-\gamma)^6 \epsilon^2} \left\| \frac{d_\rho^{\pi^*}}{\mu} \right\|_\infty^2.$$

The corollary shows the importance of balancing how the regularization parameter λ is set relative to the desired accuracy ϵ , as well as the importance of the initial distribution μ to obtain global optimality.

of Corollary 10.5. Let β_λ be the smoothness of $L_\lambda(\theta)$. A valid upper bound on β_λ is:

$$\beta_\lambda = \frac{8\gamma}{(1-\gamma)^3} + \frac{2\lambda}{|\mathcal{S}|},$$

where we leave the proof as an exercise to the reader.

Using Theorem 10.4, the desired optimality gap ϵ will follow if we set $\lambda = \frac{\epsilon(1-\gamma)}{2\left\|\frac{d\rho^*}{\mu}\right\|_\infty}$ and if $\|\nabla_\theta L_\lambda(\theta)\|_2 \leq \lambda/(2|\mathcal{S}||\mathcal{A}|)$. In order to complete the proof, we need to bound the iteration complexity of making the gradient sufficiently small.

By Lemma 9.6, after T iterations of gradient ascent with stepsize of $1/\beta_\lambda$, we have

$$\min_{t \leq T} \left\| \nabla_\theta L_\lambda(\theta^{(t)}) \right\|_2^2 \leq \frac{2\beta_\lambda(L_\lambda(\theta^*) - L_\lambda(\theta^{(0)}))}{T} \leq \frac{2\beta_\lambda}{(1-\gamma)T}, \quad (10.7)$$

where β_λ is an upper bound on the smoothness of $L_\lambda(\theta)$. We seek to ensure

$$\epsilon_{\text{opt}} \leq \sqrt{\frac{2\beta_\lambda}{(1-\gamma)T}} \leq \frac{\lambda}{2|\mathcal{S}||\mathcal{A}|}$$

Choosing $T \geq \frac{8\beta_\lambda |\mathcal{S}|^2 |\mathcal{A}|^2}{(1-\gamma)\lambda^2}$ satisfies the above inequality. Hence,

$$\begin{aligned} \frac{8\beta_\lambda |\mathcal{S}|^2 |\mathcal{A}|^2}{(1-\gamma)\lambda^2} &\leq \frac{64|\mathcal{S}|^2 |\mathcal{A}|^2}{(1-\gamma)^4 \lambda^2} + \frac{16|\mathcal{S}||\mathcal{A}|^2}{(1-\gamma)\lambda} \\ &\leq \frac{80|\mathcal{S}|^2 |\mathcal{A}|^2}{(1-\gamma)^4 \lambda^2} \\ &= \frac{320|\mathcal{S}|^2 |\mathcal{A}|^2}{(1-\gamma)^6 \epsilon^2} \left\| \frac{d\rho^*}{\mu} \right\|_\infty^2 \end{aligned}$$

where we have used that $\lambda < 1$. This completes the proof. $\square$

Entropy vs. log barrier regularization. A commonly considered regularizer is the entropy, where the regularizer would be:

$$\frac{1}{|\mathcal{S}|} \sum_s H(\pi_\theta(\cdot|s)) = \frac{1}{|\mathcal{S}|} \sum_s \sum_a -\pi_\theta(a|s) \log \pi_\theta(a|s).$$

Note the entropy is far less aggressive in penalizing small probabilities, in comparison to the log barrier, which is equivalent to the relative entropy. In particular, the entropy regularizer is always bounded between 0 and $\log |\mathcal{A}|$, while the relative entropy (against the uniform distribution over actions), is bounded between 0 and infinity, where it tends to infinity as probabilities tend to 0. Here, it can be shown that the convergence rate is asymptotically $O(1/\epsilon)$ (see Section 10.5) though it is unlikely that the convergence rate for this method is polynomial in other relevant quantities, including $|\mathcal{S}|$, $|\mathcal{A}|$, $1/(1-\gamma)$, and the distribution mismatch coefficient. The polynomial convergence rate using the log barrier (KL) regularizer crucially relies on the aggressive nature in which the relative entropy prevents small probabilities.

10.4 The Natural Policy Gradient

Observe that a policy constitutes a family of probability distributions $\{\pi_\theta(\cdot|s)|s \in \mathcal{S}\}$. We now consider a pre-conditioned gradient descent method based on this family of distributions. Recall that the Fisher information matrix

of a parameterized density $p_\theta(x)$ is defined as $\mathbb{E}_{x \sim p_\theta} [\nabla \log p_\theta(x) \nabla \log p_\theta(x)^\top]$. Now we let us define $\mathcal{F}_\rho^\theta$ as an (average) Fisher information matrix on the family of distributions $\{\pi_\theta(\cdot|s)|s \in \mathcal{S}\}$ as follows:

$$\mathcal{F}_\rho^\theta := \mathbb{E}_{s \sim d_\rho^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} [(\nabla \log \pi_\theta(a|s)) \nabla \log \pi_\theta(a|s)^\top] .$$

Note that the average is under the state-action visitation frequencies. The NPG algorithm performs gradient updates in the geometry induced by this matrix as follows:

$$\theta^{(t+1)} = \theta^{(t)} + \eta F_\rho(\theta^{(t)})^\dagger \nabla_\theta V^{(t)}(\rho), \quad (10.8)$$

where $M^\dagger$ denotes the Moore-Penrose pseudoinverse of the matrix M .

Throughout this section, we restrict to using the initial state distribution $\rho \in \Delta(\mathcal{S})$ in our update rule in (10.8) (so our optimization measure μ and the performance measure ρ are identical). Also, we restrict attention to states $s \in \mathcal{S}$ reachable from ρ , since, without loss of generality, we can exclude states that are not reachable under this start state distribution².

For the softmax parameterization, this method takes a particularly convenient form; it can be viewed as a soft policy iteration update.

Lemma 10.6. *(Softmax NPG as soft policy iteration) For the softmax parameterization (9.1), the NPG updates (10.8) take the form:*

$$\theta^{(t+1)} = \theta^{(t)} + \frac{\eta}{1-\gamma} A^{(t)} + \eta v \quad \text{and} \quad \pi^{(t+1)}(a|s) = \pi^{(t)}(a|s) \frac{\exp(\eta A^{(t)}(s, a)/(1-\gamma))}{Z_t(s)},$$

where $Z_t(s) = \sum_{a \in \mathcal{A}} \pi^{(t)}(a|s) \exp(\eta A^{(t)}(s, a)/(1-\gamma))$. Here, v is only a state dependent offset (i.e. $v_{s,a} = c_s$ for some $c_s \in \mathbb{R}$ for each state s), and, owing to the normalization $Z_t(s)$, v has no effect on the update rule.

It is important to note that while the ascent direction was derived using the gradient $\nabla_\theta V^{(t)}(\rho)$, which depends on ρ , the NPG update rule actually has no dependence on the measure ρ . Furthermore, there is no dependence on the state distribution $d_\rho^{(\pi)}$, which is due to the pseudoinverse of the Fisher information cancelling out the effect of the state distribution in NPG.

Proof. By definition of the Moore-Penrose pseudoinverse, we have that $(\mathcal{F}_\rho^\theta)^\dagger \nabla V^{\pi_\theta}(\rho) = w_*$ if and only if w_* is the minimum norm solution of:

$$\min_w \|\nabla V^{\pi_\theta}(\rho) - \mathcal{F}_\rho^\theta w\|^2 .$$

Let us first evaluate $\mathcal{F}_\rho^\theta w$. For the softmax policy parameterization, Lemma 10.1 implies:

$$w^\top \nabla_\theta \log \pi_\theta(a|s) = w_{s,a} - \sum_{a' \in \mathcal{A}} w_{s,a'} \pi_\theta(a'|s) := w_{s,a} - \bar{w}_s$$

where $\bar{w}_s$ is not a function of a . This implies that:

$$\begin{aligned} \mathcal{F}_\rho^\theta w &= \mathbb{E}_{s \sim d_\rho^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[\nabla \log \pi_\theta(a|s) \left(w^\top \nabla_\theta \log \pi_\theta(a|s) \right) \right] \\ &= \mathbb{E}_{s \sim d_\rho^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[\nabla \log \pi_\theta(a|s) \left(w_{s,a} - \bar{w}_s \right) \right] = \mathbb{E}_{s \sim d_\rho^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[w_{s,a} \nabla \log \pi_\theta(a|s) \right], \end{aligned}$$

²Specifically, we restrict the MDP to the set of states $\{s \in \mathcal{S} : \exists \pi \text{ such that } d_\rho^\pi(s) > 0\}$.

where the last equality uses that $\bar{w}_s$ is not a function of s . Again using the functional form of derivative of the softmax policy parameterization, we have:

$$\left[\mathcal{F}_\rho^\theta w \right]_{s', a'} = d^{\pi_\theta}(s') \pi_\theta(a'|s') \left(w_{s', a'} - \bar{w}_{s'} \right).$$

This implies:

$$\begin{aligned} \|\nabla V^{\pi_\theta}(\rho) - \mathcal{F}_\rho^\theta w\|^2 &= \sum_{s, a} \left(d^{\pi_\theta}(s) \pi_\theta(a|s) \left(\frac{1}{1-\gamma} A^{\pi_\theta}(s, a) - [\mathcal{F}_\rho^\theta w]_{s, a} \right) \right)^2 \\ &= \sum_{s, a} \left(d^{\pi_\theta}(s) \pi_\theta(a|s) \left(\frac{1}{1-\gamma} A^{\pi_\theta}(s, a) - w_{s, a} - \sum_{a' \in \mathcal{A}} w_{s, a'} \pi_\theta(a'|s) \right) \right)^2. \end{aligned}$$

Due to that $w = \frac{1}{1-\gamma} A^{\pi_\theta}$ leads to 0 error, the above implies that all 0 error solutions are of the form $w = \frac{1}{1-\gamma} A^{\pi_\theta} + v$, where v is only a state dependent offset (i.e. $v_{s, a} = c_s$ for some $c_s \in \mathbb{R}$ for each state s). The first claim follows due to that the minimum norm solution is one of these solutions. The proof of the second claim now follows by the definition of the NPG update rule, along with that v has no effect on the update rule due to the normalization constant $Z_t(s)$. $\square$

We now see that this algorithm enjoys a dimension free convergence rate.

Theorem 10.7 (Global convergence for NPG). *Suppose we run the NPG updates (10.8) using $\rho \in \Delta(\mathcal{S})$ and with $\theta^{(0)} = 0$. Fix $\eta > 0$. For all $T > 0$, we have:*

$$V^{(T)}(\rho) \geq V^*(\rho) - \frac{\log |\mathcal{A}|}{\eta T} - \frac{1}{(1-\gamma)^2 T}.$$

Note in the above the theorem that the NPG algorithm is directly applied to the performance measure $V^\pi(\rho)$, and the guarantees are also with respect to ρ . In particular, there is no distribution mismatch coefficient in the rate of convergence.

Now setting $\eta \geq (1-\gamma)^2 \log |\mathcal{A}|$, we see that NPG finds an ϵ -optimal policy in a number of iterations that is at most:

$$T \leq \frac{2}{(1-\gamma)^2 \epsilon},$$

which has no dependence on the number of states or actions, despite the non-concavity of the underlying optimization problem.

The proof strategy we take borrows ideas from the classical multiplicative weights algorithm (see Section 10.5).

First, the following improvement lemma is helpful:

Lemma 10.8 (Improvement lower bound for NPG). *For the iterates $\pi^{(t)}$ generated by the NPG updates (10.8), we have for all starting state distributions μ*

$$V^{(t+1)}(\mu) - V^{(t)}(\mu) \geq \frac{(1-\gamma)}{\eta} \mathbb{E}_{s \sim \mu} \log Z_t(s) \geq 0.$$

Proof. First, let us show that $\log Z_t(s) \geq 0$. To see this, observe:

$$\begin{aligned} \log Z_t(s) &= \log \sum_a \pi^{(t)}(a|s) \exp(\eta A^{(t)}(s, a)/(1-\gamma)) \\ &\geq \sum_a \pi^{(t)}(a|s) \log \exp(\eta A^{(t)}(s, a)/(1-\gamma)) = \frac{\eta}{1-\gamma} \sum_a \pi^{(t)}(a|s) A^{(t)}(s, a) = 0. \end{aligned}$$

where we have used Jensen's inequality on the concave function $\log x$ and that $\sum_a \pi^{(t)}(a|s)A^{(t)}(s, a) = 0$. By the performance difference lemma,

$$\begin{aligned}
V^{(t+1)}(\mu) - V^{(t)}(\mu) &= \frac{1}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{(t+1)}} \sum_a \pi^{(t+1)}(a|s) A^{(t)}(s, a) \\
&= \frac{1}{\eta} \mathbb{E}_{s \sim d_\mu^{(t+1)}} \sum_a \pi^{(t+1)}(a|s) \log \frac{\pi^{(t+1)}(a|s) Z_t(s)}{\pi^{(t)}(a|s)} \\
&= \frac{1}{\eta} \mathbb{E}_{s \sim d_\mu^{(t+1)}} \text{KL}(\pi_s^{(t+1)} || \pi_s^{(t)}) + \frac{1}{\eta} \mathbb{E}_{s \sim d_\mu^{(t+1)}} \log Z_t(s) \\
&\geq \frac{1}{\eta} \mathbb{E}_{s \sim d_\mu^{(t+1)}} \log Z_t(s) \geq \frac{1-\gamma}{\eta} \mathbb{E}_{s \sim \mu} \log Z_t(s),
\end{aligned}$$

where the last step uses that $d_\mu^{(t+1)} \geq (1-\gamma)\mu$ (by (??)) and that $\log Z_t(s) \geq 0$. $\square$

With this lemma, we now prove Theorem 10.7.

of Theorem 10.7. Since ρ is fixed, we use d^* as shorthand for d_ρ^* ; we also use π_s as shorthand for the vector of $\pi(\cdot|s)$. By the performance difference lemma (Lemma 1.16),

$$\begin{aligned}
V^{\pi^*}(\rho) - V^{(t)}(\rho) &= \frac{1}{1-\gamma} \mathbb{E}_{s \sim d^*} \sum_a \pi^*(a|s) A^{(t)}(s, a) \\
&= \frac{1}{\eta} \mathbb{E}_{s \sim d^*} \sum_a \pi^*(a|s) \log \frac{\pi^{(t+1)}(a|s) Z_t(s)}{\pi^{(t)}(a|s)} \\
&= \frac{1}{\eta} \mathbb{E}_{s \sim d^*} \left(\text{KL}(\pi_s^* || \pi_s^{(t)}) - \text{KL}(\pi_s^* || \pi_s^{(t+1)}) + \sum_a \pi^*(a|s) \log Z_t(s) \right) \\
&= \frac{1}{\eta} \mathbb{E}_{s \sim d^*} \left(\text{KL}(\pi_s^* || \pi_s^{(t)}) - \text{KL}(\pi_s^* || \pi_s^{(t+1)}) + \log Z_t(s) \right),
\end{aligned}$$

where we have used the closed form of our updates from Lemma 10.6 in the second step.

By applying Lemma 10.8 with d^* as the starting state distribution, we have:

$$\frac{1}{\eta} \mathbb{E}_{s \sim d^*} \log Z_t(s) \leq \frac{1}{1-\gamma} \left(V^{(t+1)}(d^*) - V^{(t)}(d^*) \right)$$

which gives us a bound on $\mathbb{E}_{s \sim d^*} \log Z_t(s)$.

Using the above equation and that $V^{(t+1)}(\rho) \geq V^{(t)}(\rho)$ (as $V^{(t+1)}(s) \geq V^{(t)}(s)$ for all states s by Lemma 10.8), we

have:

$$\begin{aligned}
V^{\pi^*}(\rho) - V^{(T-1)}(\rho) &\leq \frac{1}{T} \sum_{t=0}^{T-1} (V^{\pi^*}(\rho) - V^{(t)}(\rho)) \\
&= \frac{1}{\eta T} \sum_{t=0}^{T-1} \mathbb{E}_{s \sim d^*} (\text{KL}(\pi_s^* || \pi_s^{(t)}) - \text{KL}(\pi_s^* || \pi_s^{(t+1)})) + \frac{1}{\eta T} \sum_{t=0}^{T-1} \mathbb{E}_{s \sim d^*} \log Z_t(s) \\
&\leq \frac{\mathbb{E}_{s \sim d^*} \text{KL}(\pi_s^* || \pi^{(0)})}{\eta T} + \frac{1}{(1-\gamma)T} \sum_{t=0}^{T-1} (V^{(t+1)}(d^*) - V^{(t)}(d^*)) \\
&= \frac{\mathbb{E}_{s \sim d^*} \text{KL}(\pi_s^* || \pi^{(0)})}{\eta T} + \frac{V^{(T)}(d^*) - V^{(0)}(d^*)}{(1-\gamma)T} \\
&\leq \frac{\log |\mathcal{A}|}{\eta T} + \frac{1}{(1-\gamma)^2 T}.
\end{aligned}$$

The proof is completed using that $V^{(T)}(\rho) \geq V^{(T-1)}(\rho)$. □

10.5 Bibliographic Remarks and Further Readings

The natural policy gradient method was originally presented in Kakade [2001]; a number of arguments for this method have been provided based on information geometry [Kakade, 2001, Bagnell and Schneider, 2003, Peters and Schaal, 2008].

The convergence rates in this chapter are largely derived from Agarwal et al. [2020d]. The proof strategy for the NPG analysis has origins in the online regret framework in changing MDPs [Even-Dar et al., 2009], which would result in a worst rate in comparison to Agarwal et al. [2020d]. This observation that the proof strategy from [Even-Dar et al., 2009] provided a convergence rate for the NPG was made in Neu et al. [2017]. The faster NPG rate we present here is due to Agarwal et al. [2020d]. The analysis of the MD-MPI algorithm [Geist et al., 2019] also implies a $O(1/T)$ rate for the NPG, though with worse dependencies on other parameters.

Building on ideas in Agarwal et al. [2020d], Mei et al. [2020] showed that, for the softmax policy class, both the gradient ascent and entropy regularized gradient ascent asymptotically converge at a $O(1/t)$; it is unlikely these methods have finite rate which are polynomial in other quantities (such as the $|\mathcal{S}|$, $|\mathcal{A}|$, $1/(1-\gamma)$, and the distribution mismatch coefficient).

Mnih et al. [2016] introduces the entropy regularizer (also see Ahmed et al. [2019] for a more detailed empirical investigation).

Chapter 11

Function Approximation and the NPG

We now analyze the case of using parametric policy classes:

$$\Pi = \{\pi_\theta \mid \theta \in \mathbb{R}^d\},$$

where Π may not contain all stochastic policies (and it may not even contain an optimal policy). In contrast with the tabular results in the previous sections, the policy classes that we are often interested in are not fully expressive, e.g. $d \ll |\mathcal{S}||\mathcal{A}|$ (indeed $|\mathcal{S}|$ or $|\mathcal{A}|$ need not even be finite for the results in this section); in this sense, we are in the regime of function approximation.

We focus on obtaining *agnostic* results, where we seek to do as well as the best policy in this class (or as well as some other comparator policy). While we are interested in a solution to the (unconstrained) policy optimization problem

$$\max_{\theta \in \mathbb{R}^d} V^{\pi_\theta}(\rho),$$

(for a given initial distribution ρ), we will see that optimization with respect to a different distribution will be helpful, just as in the tabular case,

We will consider variants of the NPG update rule (10.8):

$$\theta \leftarrow \theta + \eta F_\rho(\theta)^\dagger \nabla_\theta V^\theta(\rho). \quad (11.1)$$

Our analysis will leverage a close connection between the NPG update rule (10.8) with the notion of *compatible function approximation*. We start by formalizing this connection. The compatible function approximation error also provides a measure of the expressivity of our parameterization, allowing us to quantify the relevant notion of approximation error for the NPG algorithm.

The main results in this chapter establish the effectiveness of NPG updates where there is error both due to statistical estimation (where we may not use exact gradients) and approximation (due to using a parameterized function class). We will see an precise estimation/approximation decomposition based on the compatible function approximation error.

The presentation in this chapter largely follows the results in Agarwal et al. [2020d].

11.1 Compatible function approximation and the NPG

We now introduce the notion of *compatible function approximation*, which both provides some intuition with regards to policy gradient methods and it will help us later on with regards to characterizing function approximation.

Lemma 11.1 (Gradients and compatible function approximation). *Let w^* denote the following minimizer:*

$$w^* \in \mathbb{E}_{s \sim d_\mu^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[\left(A^{\pi_\theta}(s, a) - w \cdot \nabla_\theta \log \pi_\theta(a|s) \right)^2 \right],$$

where the squared error above is referred to as the compatible function approximation. Denote the best linear predictor of $A^{\pi_\theta}(s, a)$ using $\nabla_\theta \log \pi_\theta(a|s)$ by $\hat{A}^{\pi_\theta}(s, a)$, i.e.

$$\hat{A}^{\pi_\theta}(s, a) := w^* \cdot \nabla_\theta \log \pi_\theta(a|s).$$

We have that:

$$\nabla_\theta V^{\pi_\theta}(\mu) = \frac{1}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} [\nabla_\theta \log \pi_\theta(a|s) \hat{A}^{\pi_\theta}(s, a)].$$

Proof. The first order optimality conditions for w^* imply

$$\mathbb{E}_{s \sim d_\mu^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} \left[\left(A^{\pi_\theta}(s, a) - w^* \cdot \nabla_\theta \log \pi_\theta(a|s) \right) \nabla_\theta \log \pi_\theta(a|s) \right] = 0 \quad (11.2)$$

Rearranging and using the definition of $\hat{A}^{\pi_\theta}(s, a)$,

$$\begin{aligned} \nabla_\theta V^{\pi_\theta}(\mu) &= \frac{1}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} [\nabla_\theta \log \pi_\theta(a|s) A^{\pi_\theta}(s, a)] \\ &= \frac{1}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{\pi_\theta}} \mathbb{E}_{a \sim \pi_\theta(\cdot|s)} [\nabla_\theta \log \pi_\theta(a|s) \hat{A}^{\pi_\theta}(s, a)], \end{aligned}$$

which completes the proof. $\square$

The next lemma shows that the weight vector above is precisely the NPG ascent direction. Precisely,

Lemma 11.2. *We have that:*

$$F_\rho(\theta)^\dagger \nabla_\theta V^\theta(\rho) = \frac{1}{1-\gamma} w^*, \quad (11.3)$$

where w^* is a minimizer of the following regression problem:

$$w^* \in \underset{w}{\operatorname{argmin}} \mathbb{E}_{s \sim d_\rho^{\pi_\theta}, a \sim \pi_\theta(\cdot|s)} \left[(w^\top \nabla_\theta \log \pi_\theta(\cdot|s) - A^{\pi_\theta}(s, a))^2 \right].$$

Proof. The above is a straightforward consequence of the first order optimality conditions (see Equation 11.2). Specifically, Equation 11.2, along with the advantage expression for the policy gradient (see Theorem 9.4), imply that w^* must satisfy:

$$\nabla_\theta V^\theta(\rho) = \frac{1}{1-\gamma} F_\rho(\theta) w^*$$

which completes the proof. $\square$

This lemma implies that we might write the NPG update rule as:

$$\theta \leftarrow \theta + \frac{\eta}{1-\gamma} w^*.$$

where w^* is minimizer of the compatible function approximation error (which depends on θ).

The above regression problem can be viewed as “compatible” function approximation: we are approximating $A^{\pi_\theta}(s, a)$ using the $\nabla_\theta \log \pi_\theta(\cdot|s)$ as features. We also consider a variant of the above update rule, Q -NPG, where instead of using advantages in the above regression we use the Q -values. This viewpoint provides a methodology for approximate updates, where we can solve the relevant regression problems with samples.

11.2 Examples: NPG and Q-NPG

In practice, the most common policy classes are of the form:

$$\Pi = \left\{ \pi_\theta(a|s) = \frac{\exp(f_\theta(s, a))}{\sum_{a' \in \mathcal{A}} \exp(f_\theta(s, a'))} \mid \theta \in \mathbb{R}^d \right\}, \quad (11.4)$$

where f_θ is a differentiable function. For example, the tabular softmax policy class is one where $f_\theta(s, a) = \theta_{s,a}$. Typically, f_θ is either a linear function or a neural network. Let us consider the NPG algorithm, and a variant Q-NPG, in each of these two cases.

11.2.1 Log-linear Policy Classes and Soft Policy Iteration

For any state-action pair (s, a) , suppose we have a feature mapping $\phi_{s,a} \in \mathbb{R}^d$. Each policy in the log-linear policy class is of the form:

$$\pi_\theta(a|s) = \frac{\exp(\theta \cdot \phi_{s,a})}{\sum_{a' \in \mathcal{A}} \exp(\theta \cdot \phi_{s,a'})},$$

with $\theta \in \mathbb{R}^d$. Here, we can take $f_\theta(s, a) = \theta \cdot \phi_{s,a}$.

With regards to compatible function approximation for the log-linear policy class, we have:

$$\nabla_\theta \log \pi_\theta(a|s) = \bar{\phi}_{s,a}^\theta, \text{ where } \bar{\phi}_{s,a}^\theta = \phi_{s,a} - \mathbb{E}_{a' \sim \pi_\theta(\cdot|s)}[\phi_{s,a'}],$$

that is, $\bar{\phi}_{s,a}^\theta$ is the centered version of $\phi_{s,a}$. With some abuse of notation, we accordingly also define $\bar{\phi}^\pi$ for any policy π . Here, using (11.3), the NPG update rule (11.1) is equivalent to:

$$\text{NPG: } \theta \leftarrow \theta + \eta w_\star, \quad w_\star \in \underset{w}{\operatorname{argmin}} \mathbb{E}_{s \sim d_\rho^{\pi_\theta}, a \sim \pi_\theta(\cdot|s)} \left[(A^{\pi_\theta}(s, a) - w \cdot \bar{\phi}_{s,a}^\theta)^2 \right].$$

(We have rescaled the learning rate η in comparison to (11.1)). Note that we recompute $w_\star$ for every update of θ . Here, the compatible function approximation error measures the expressivity of our parameterization in how well linear functions of the parameterization can capture the policy's advantage function.

We also consider a variant of the NPG update rule (11.1), termed *Q-NPG*, where:

$$\text{Q-NPG: } \theta \leftarrow \theta + \eta w_\star, \quad w_\star \in \underset{w}{\operatorname{argmin}} \mathbb{E}_{s \sim d_\rho^{\pi_\theta}, a \sim \pi_\theta(\cdot|s)} \left[(Q^{\pi_\theta}(s, a) - w \cdot \phi_{s,a})^2 \right].$$

Note we do not center the features for Q-NPG; observe that $Q^\pi(s, a)$ is also not 0 in expectation under $\pi(\cdot|s)$, unlike the advantage function.

(NPG/Q-NPG and Soft-Policy Iteration) We now see how we can view both NPG and Q-NPG as an incremental (soft) version of policy iteration, just as in Lemma 10.6 for the tabular case. Rather than writing the update rule in terms of the parameter θ , we can write an equivalent update rule directly in terms of the (log-linear) policy π :

$$\text{NPG: } \pi(a|s) \leftarrow \pi(a|s) \exp(w_\star \cdot \phi_{s,a}) / Z_s, \quad w_\star \in \underset{w}{\operatorname{argmin}} \mathbb{E}_{s \sim d_\rho^\pi, a \sim \pi(\cdot|s)} \left[(A^\pi(s, a) - w \cdot \bar{\phi}_{s,a}^\pi)^2 \right],$$

where Z_s is normalization constant. While the policy update uses the original features ϕ instead of $\bar{\phi}^\pi$, whereas the quadratic error minimization is in terms of the centered features $\bar{\phi}^\pi$, this distinction is not relevant due to that we may also instead use $\bar{\phi}^\pi$ (in the policy update) which would result in an equivalent update; the normalization makes the

update invariant to (constant) translations of the features. Similarly, an equivalent update for Q -NPG, where we update π directly rather than θ , is:

$$Q\text{-NPG: } \pi(a|s) \leftarrow \pi(a|s) \exp(w_\star \cdot \phi_{s,a}) / Z_s, \quad w_\star \in \operatorname{argmin}_w \mathbb{E}_{s \sim d_\rho^\pi, a \sim \pi(\cdot|s)} \left[(Q^\pi(s, a) - w \cdot \phi_{s,a})^2 \right].$$

(On the equivalence of NPG and Q -NPG) If it is the case that the compatible function approximation error is 0, then it is straightforward to verify that the NPG and Q -NPG are equivalent algorithms, in that their corresponding policy updates will be equivalent to each other.

11.2.2 Neural Policy Classes

Now suppose $f_\theta(s, a)$ is a neural network parameterized by $\theta \in \mathbb{R}^d$, where the policy class Π is of form in (11.4). Observe:

$$\nabla_\theta \log \pi_\theta(a|s) = g_\theta(s, a), \text{ where } g_\theta(s, a) = \nabla_\theta f_\theta(s, a) - \mathbb{E}_{a' \sim \pi_\theta(\cdot|s)} [\nabla_\theta f_\theta(s, a')],$$

and, using (11.3), the NPG update rule (11.1) is equivalent to:

$$\text{NPG: } \theta \leftarrow \theta + \eta w_\star, \quad w_\star \in \operatorname{argmin}_w \mathbb{E}_{s \sim d_\rho^{\pi_\theta}, a \sim \pi_\theta(\cdot|s)} \left[(A^{\pi_\theta}(s, a) - w \cdot g_\theta(s, a))^2 \right]$$

(Again, we have rescaled the learning rate η in comparison to (11.1)).

The Q -NPG variant of this update rule is:

$$Q\text{-NPG: } \theta \leftarrow \theta + \eta w_\star, \quad w_\star \in \operatorname{argmin}_w \mathbb{E}_{s \sim d_\rho^{\pi_\theta}, a \sim \pi_\theta(\cdot|s)} \left[(Q^{\pi_\theta}(s, a) - w \cdot \nabla_\theta f_\theta(s, a))^2 \right].$$

11.3 The NPG “Regret Lemma”

It is helpful for us to consider NPG more abstractly, as an update rule of the form

$$\theta^{(t+1)} = \theta^{(t)} + \eta w^{(t)}. \tag{11.5}$$

We will now provide a lemma where $w^{(t)}$ is an *arbitrary* (bounded) sequence, which will be helpful when specialized.

Recall a function $f : \mathbb{R}^d \rightarrow \mathbb{R}$ is said to be β -smooth if for all $x, x' \in \mathbb{R}^d$:

$$\|\nabla f(x) - \nabla f(x')\|_2 \leq \beta \|x - x'\|_2,$$

and, due to Taylor’s theorem, recall that this implies:

$$\left| f(x') - f(x) - \nabla f(x) \cdot (x' - x) \right| \leq \frac{\beta}{2} \|x' - x\|_2^2. \tag{11.6}$$

The following analysis of NPG draws close connections to the mirror-descent approach used in online learning (see Section 11.6), which motivates us to refer to it as a “regret lemma”.

Lemma 11.3. (NPG Regret Lemma) Fix a comparison policy $\tilde{\pi}$ and a state distribution ρ . Assume for all $s \in \mathcal{S}$ and $a \in \mathcal{A}$ that $\log \pi_\theta(a|s)$ is a β -smooth function of θ . Consider the update rule (11.5), where $\pi^{(0)}$ is the uniform distribution (for all states) and where the sequence of weights $w^{(0)}, \dots, w^{(T)}$, satisfies $\|w^{(t)}\|_2 \leq W$ (but is otherwise arbitrary). Define:

$$\text{err}_t = \mathbb{E}_{s \sim \tilde{d}} \mathbb{E}_{a \sim \tilde{\pi}(\cdot|s)} \left[A^{(t)}(s, a) - w^{(t)} \cdot \nabla_\theta \log \pi^{(t)}(a|s) \right].$$

Using $\eta = \sqrt{2 \log |\mathcal{A}| / (\beta W^2 T)}$, we have that:

$$\min_{t < T} \left\{ V^{\tilde{\pi}}(\rho) - V^{(t)}(\rho) \right\} \leq \frac{1}{1-\gamma} \left(W \sqrt{\frac{2\beta \log |\mathcal{A}|}{T}} + \frac{1}{T} \sum_{t=0}^{T-1} \text{err}_t \right).$$

This lemma is the key tool in understanding the role of function approximation of various algorithms. We will consider one example in detail with regards to the log-linear policy class (from Example 9.2).

Note that when $\text{err}_t = 0$, as will be the case with the (tabular) softmax policy class with exact gradients, we obtain a convergence rate of $O(\sqrt{1/T})$ using a learning rate of $\eta = O(\sqrt{1/T})$. Note that this is slower than the faster rate of $O(1/T)$, provided in Theorem 10.7. Obtaining a bound that leads to a faster rate in the setting with errors requires more complicated dependencies on err_t than those stated above.

Proof. By smoothness (see (11.6)),

$$\begin{aligned} \log \frac{\pi^{(t+1)}(a|s)}{\pi^{(t)}(a|s)} &\geq \nabla_{\theta} \log \pi^{(t)}(a|s) \cdot (\theta^{(t+1)} - \theta^{(t)}) - \frac{\beta}{2} \|\theta^{(t+1)} - \theta^{(t)}\|_2^2 \\ &= \eta \nabla_{\theta} \log \pi^{(t)}(a|s) \cdot w^{(t)} - \eta^2 \frac{\beta}{2} \|w^{(t)}\|_2^2. \end{aligned}$$

We use $\tilde{d}$ as shorthand for $d_{\tilde{\rho}}^{\tilde{\pi}}$ (note ρ and $\tilde{\pi}$ are fixed); for any policy π , we also use π_s as shorthand for the distribution $\pi(\cdot|s)$. Using the performance difference lemma (Lemma 1.16),

$$\begin{aligned} &\mathbb{E}_{s \sim \tilde{d}} \left(\text{KL}(\tilde{\pi}_s \| \pi_s^{(t)}) - \text{KL}(\tilde{\pi}_s \| \pi_s^{(t+1)}) \right) \\ &= \mathbb{E}_{s \sim \tilde{d}} \mathbb{E}_{a \sim \tilde{\pi}(\cdot|s)} \left[\log \frac{\pi^{(t+1)}(a|s)}{\pi^{(t)}(a|s)} \right] \\ &\geq \eta \mathbb{E}_{s \sim \tilde{d}} \mathbb{E}_{a \sim \tilde{\pi}(\cdot|s)} \left[\nabla_{\theta} \log \pi^{(t)}(a|s) \cdot w^{(t)} \right] - \eta^2 \frac{\beta}{2} \|w^{(t)}\|_2^2 \quad (\text{using previous display}) \\ &= \eta \mathbb{E}_{s \sim \tilde{d}} \mathbb{E}_{a \sim \tilde{\pi}(\cdot|s)} \left[A^{(t)}(s, a) \right] - \eta^2 \frac{\beta}{2} \|w^{(t)}\|_2^2 \\ &\quad + \eta \mathbb{E}_{s \sim \tilde{d}} \mathbb{E}_{a \sim \tilde{\pi}(\cdot|s)} \left[\nabla_{\theta} \log \pi^{(t)}(a|s) \cdot w^{(t)} - A^{(t)}(s, a) \right] \\ &= (1-\gamma) \eta \left(V^{\tilde{\pi}}(\rho) - V^{(t)}(\rho) \right) - \eta^2 \frac{\beta}{2} \|w^{(t)}\|_2^2 - \eta \text{err}_t \end{aligned}$$

Rearranging, we have:

$$V^{\tilde{\pi}}(\rho) - V^{(t)}(\rho) \leq \frac{1}{1-\gamma} \left(\frac{1}{\eta} \mathbb{E}_{s \sim \tilde{d}} \left(\text{KL}(\tilde{\pi}_s \| \pi_s^{(t)}) - \text{KL}(\tilde{\pi}_s \| \pi_s^{(t+1)}) \right) + \frac{\eta\beta}{2} W^2 + \text{err}_t \right)$$

Proceeding,

$$\begin{aligned} \frac{1}{T} \sum_{t=0}^{T-1} (V^{\tilde{\pi}}(\rho) - V^{(t)}(\rho)) &\leq \frac{1}{\eta T(1-\gamma)} \sum_{t=0}^{T-1} \mathbb{E}_{s \sim \tilde{d}} (\text{KL}(\tilde{\pi}_s \| \pi_s^{(t)}) - \text{KL}(\tilde{\pi}_s \| \pi_s^{(t+1)})) \\ &\quad + \frac{1}{T(1-\gamma)} \sum_{t=0}^{T-1} \left(\frac{\eta\beta W^2}{2} + \text{err}_t \right) \\ &\leq \frac{\mathbb{E}_{s \sim \tilde{d}} \text{KL}(\tilde{\pi}_s \| \pi^{(0)})}{\eta T(1-\gamma)} + \frac{\eta\beta W^2}{2(1-\gamma)} + \frac{1}{T(1-\gamma)} \sum_{t=0}^{T-1} \text{err}_t \\ &\leq \frac{\log |\mathcal{A}|}{\eta T(1-\gamma)} + \frac{\eta\beta W^2}{2(1-\gamma)} + \frac{1}{T(1-\gamma)} \sum_{t=0}^{T-1} \text{err}_t, \end{aligned}$$

which completes the proof. $\square$

11.4 Q -NPG: Performance Bounds for Log-Linear Policies

For a state-action distribution ν , define:

$$L(w; \theta, \nu) := \mathbb{E}_{s,a \sim \nu} \left[\left(Q^{\pi_\theta}(s, a) - w \cdot \phi_{s,a} \right)^2 \right].$$

The iterates of the Q -NPG algorithm can be viewed as minimizing this loss under some (changing) distribution ν .

We now specify an approximate version of Q -NPG. It is helpful to consider a slightly more general version of the algorithm in the previous section, where instead of optimizing under a starting state distribution ρ , we have a different starting *state-action* distribution ν . The motivation for this is similar in spirit to our log barrier regularization: we seek to maintain exploration (and estimation) over the action space even if the current policy does not have coverage over the action space.

Analogous to the definition of the state-action visitation measure $d_{s_0}^\pi$ (see Equation 1.9), we define another state-action visitation measure, d_{s_0, a_0}^π , as follows:

$$d_{s_0, a_0}^\pi(s, a) := (1 - \gamma) \sum_{t=0}^{\infty} \gamma^t \Pr^\pi(s_t = s, a_t = a | s_0, a_0) \quad (11.7)$$

where $\Pr^\pi(s_t = s, a_t = a | s_0, a_0)$ is the probability that $s_t = s$ and $a_t = a$, after starting at state s_0 , taking action a_0 , and following π thereafter. Again, we overload notation and write:

$$d_\nu^\pi(s, a) = \mathbb{E}_{s_0, a_0 \sim \nu} [d_{s_0, a_0}^\pi]$$

where ν is a distribution over $\mathcal{S} \times \mathcal{A}$.

Q -NPG will be defined with respect to the *on-policy* state action measure starting with $s_0, a_0 \sim \nu$. As per our convention, we define

$$d^{(t)} := d_\nu^{\pi^{(t)}}.$$

The approximate version of this algorithm is:

$$\text{Approx. } Q\text{-NPG: } \theta^{(t+1)} = \theta^{(t)} + \eta w^{(t)}, \quad w^{(t)} \approx \underset{\|w\|_2 \leq W}{\operatorname{argmin}} L(w; \theta^{(t)}, d^{(t)}), \quad (11.8)$$

where the above update rule also permits us to constrain the norm of the update direction $w^{(t)}$ (alternatively, we could use ℓ_2 regularization as is also common in practice). The exact minimizer is denoted as:

$$w_\star^{(t)} \in \underset{\|w\|_2 \leq W}{\operatorname{argmin}} L(w; \theta^{(t)}, d^{(t)}).$$

Note that $w_\star^{(t)}$ depends on the current parameter $\theta^{(t)}$.

Our analysis will take into account both the *excess risk* (often also referred to as estimation error) and the *approximation error*. The standard approximation-estimation error decomposition is as follows:

$$L(w^{(t)}; \theta^{(t)}, d^{(t)}) = \underbrace{L(w^{(t)}; \theta^{(t)}, d^{(t)}) - L(w_\star^{(t)}; \theta^{(t)}, d^{(t)})}_{\text{Excess risk}} + \underbrace{L(w_\star^{(t)}; \theta^{(t)}, d^{(t)})}_{\text{Approximation error}}$$

Using a sample based approach, we would expect $\epsilon_{\text{stat}} = O(1/\sqrt{N})$ or better, where N is the number of samples used to estimate $w_\star^{(t)}$. In contrast, the approximation error is due to modeling error, and does not tend to 0 with more samples. We will see how these two errors have strikingly different impact on our final performance bound.

Note that we have already considered two cases where $\epsilon_{\text{approx}} = 0$. For the tabular softmax policy class, it is immediate that $\epsilon_{\text{approx}} = 0$. A more interesting example (where the state and action space could be infinite) is provided by the linear parameterized MDP model from Chapter 7. Here, provided that we use the log-linear policy class (see Section 11.2.1) with features corresponding to the linear MDP features, it is straightforward to see that $\epsilon_{\text{approx}} = 0$ for this log-linear policy class. More generally, we will see the effect of model misspecification in our performance bounds.

We make the following assumption on these errors:

Assumption 11.4 (Approximation/estimation error bounds). Let $w^{(0)}, w^{(1)}, \dots, w^{(T-1)}$ be the sequence of iterates used by the Q -NPG algorithm. Suppose the following holds for all $t < T$:

1. (*Excess risk*) Suppose the estimation error is bounded as follows:

$$L(w^{(t)}; \theta^{(t)}, d^{(t)}) - L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \leq \epsilon_{\text{stat}}$$

2. (*Approximation error*) Suppose the approximation error is bounded as follows:

$$L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \leq \epsilon_{\text{approx}}.$$

We will also see how, with regards to our estimation error, we will need a far more mild notion of coverage. Here, with respect to any state-action distribution v , define:

$$\Sigma_v = \mathbb{E}_{s,a \sim v} [\phi_{s,a} \phi_{s,a}^\top].$$

We make the following conditioning assumption:

Assumption 11.5 (Relative condition number). Fix a state distribution ρ (this will be what ultimately be the performance measure that we seek to optimize). Consider an arbitrary comparator policy $\pi^\star$ (not necessarily an optimal policy). With respect to $\pi^\star$, define the state-action measure $d^\star$ as

$$d^\star(s, a) = d_\rho^{\pi^\star}(s) \cdot \text{Unif}_{\mathcal{A}}(a)$$

i.e. $d^\star$ samples states from the comparators state visitation measure, $d_\rho^{\pi^\star}$ and actions from the uniform distribution. Define

$$\sup_{w \in \mathbb{R}^d} \frac{w^\top \Sigma_{d^\star} w}{w^\top \Sigma_v w} = \kappa,$$

and assume that κ is finite.

We later discuss why it is reasonable to expect that κ is not a quantity related to the size of the state space.

The main result of this chapter shows how the approximation error, the excess risk, and the conditioning, determine the final performance.

Theorem 11.6. Fix a state distribution ρ ; a state-action distribution v ; an arbitrary comparator policy $\pi^\star$ (not necessarily an optimal policy). Suppose Assumption 11.5 holds with respect to these choices and that $\|\phi_{s,a}\|_2 \leq B$ for all s, a . Suppose the Q -NPG update rule (in (11.8)) starts with $\theta^{(0)} = 0$, $\eta = \sqrt{2 \log |\mathcal{A}| / (B^2 W^2 T)}$, and the (random) sequence of iterates satisfies Assumption 11.4. We have that:

$$\mathbb{E} \left[\min_{t < T} \left\{ V^{\pi^\star}(\rho) - V^{(t)}(\rho) \right\} \right] \leq \frac{BW}{1-\gamma} \sqrt{\frac{2 \log |\mathcal{A}|}{T}} + \sqrt{\frac{4|\mathcal{A}|}{(1-\gamma)^3} \left(\kappa \cdot \epsilon_{\text{stat}} + \left\| \frac{d^\star}{v} \right\|_\infty \cdot \epsilon_{\text{approx}} \right)}.$$

Note when $\epsilon_{\text{approx}} = 0$, our convergence rate is $O(\sqrt{1/T})$ plus a term that depends on the excess risk; hence, provided we obtain enough samples, then ϵ_{stat} will also tend to 0, and we will be competitive with the comparison policy π^* .

The above also shows the striking difference between the effects of estimation error and approximation error. A few remarks are now in order.

Transfer learning, distribution shift, and the approximation error. In large scale problems, the worst case distribution mismatch factor $\left\| \frac{d^*}{\nu} \right\|_\infty$ is unlikely to be small. However, this factor is ultimately due to transfer learning. Our approximation error is with respect to the fitting distribution $d^{(t)}$, where we assume that $L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \leq \epsilon_{\text{approx}}$. As the proof will show, the relevant notion of approximation error will be $L(w_\star^{(t)}; \theta^{(t)}, d^*)$, where d^* is the *fixed* comparators measure. In others words, to get a good performance bound we need to successfully have low transfer learning error to the fixed measure d^* . Furthermore, in many modern machine learning applications, this error is often is favorable, in that it is substantially better than worst case theory might suggest.

See Section 11.6 for further remarks on this point.

Dimension dependence in κ and the importance of ν . It is reasonable to think about κ as being dimension dependent (or worse), but it is not necessarily related to the size of the state space. For example, if $\|\phi_{s,a}\|_2 \leq B$, then $\kappa \leq \frac{B^2}{\sigma_{\min}(\mathbb{E}_{s,a \sim \nu}[\phi_{s,a} \phi_{s,a}^\top])}$ though this bound may be pessimistic. Here, we also see the importance of choice of ν in having a small (relative) condition number; in particular, this is the motivation for considering the generalization which allows for a starting state-action distribution ν vs. just a starting state distribution μ (as we did in the tabular case). Roughly speaking, we desire a ν which provides good coverage over the features. As the following lemma shows, there always exists a universal distribution ν , which can be constructed only with knowledge of the feature set (without knowledge of d^*), such that $\kappa \leq d$.

Lemma 11.7. ($\kappa \leq d$ is always possible) Let $\Phi = \{\phi(s,a) | (s,a) \in \mathcal{S} \times \mathcal{A}\} \subset \mathbb{R}^d$ and suppose Φ is a compact set. There always exists a state-action distribution ν , which is supported on at most d^2 state-action pairs and which can be constructed only with knowledge of Φ (without knowledge of the MDP or d^*), such that:

$$\kappa \leq d.$$

Proof. The distribution can be found through constructing the minimal volume ellipsoid containing Φ , i.e. the Löwner-John ellipsoid. **To be added...** $\square$

Direct policy optimization vs. approximate value function programming methods Part of the reason for the success of the direct policy optimization approaches is to due their more mild dependence on the approximation error. Here, our theoretical analysis has a dependence on a distribution mismatch coefficient, $\left\| \frac{d^*}{\nu} \right\|_\infty$, while approximate value function methods have even worse dependencies. See Chapter ???. As discussed earlier and as can be seen in the regret lemma (Lemma 11.3), the distribution mismatch coefficient is due to that the relevant error for NPG is a transfer error notion to a *fixed* comparator distribution, while approximate value function methods have more stringent conditions where the error has to be small under, essentially, the distribution of *any* other policy.

11.4.1 Analysis

Proof. (of Theorem 11.6) For the log-linear policy class, due to that the feature mapping ϕ satisfies $\|\phi_{s,a}\|_2 \leq B$, then it is not difficult to verify that $\log \pi_\theta(a|s)$ is a B^2 -smooth function. Using this and the NPG regret lemma

(Lemma 11.3), we have:

$$\min_{t \leq T} \left\{ V^{\pi^*}(\rho) - V^{(t)}(\rho) \right\} \leq \frac{BW}{1-\gamma} \sqrt{\frac{2 \log |\mathcal{A}|}{T}} + \frac{1}{(1-\gamma)T} \sum_{t=0}^{T-1} \text{err}_t.$$

where we have used our setting of η .

We make the following decomposition of err_t :

$$\begin{aligned} \text{err}_t &= \mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left[A^{(t)}(s, a) - w_\star^{(t)} \cdot \nabla_\theta \log \pi^{(t)}(a|s) \right] \\ &\quad + \mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left[(w_\star^{(t)} - w^{(t)}) \cdot \nabla_\theta \log \pi^{(t)}(a|s) \right]. \end{aligned}$$

For the first term, using that $\nabla_\theta \log \pi_\theta(a|s) = \phi_{s,a} - \mathbb{E}_{a' \sim \pi_\theta(\cdot|s)} [\phi_{s,a'}]$ (see Section 11.2.1), we have:

$$\begin{aligned} &\mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left[A^{(t)}(s, a) - w_\star^{(t)} \cdot \nabla_\theta \log \pi^{(t)}(a|s) \right] \\ &= \mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left[Q^{(t)}(s, a) - w_\star^{(t)} \cdot \phi_{s,a} \right] - \mathbb{E}_{s \sim d_\rho^*, a' \sim \pi^{(t)}(\cdot|s)} \left[Q^{(t)}(s, a') - w_\star^{(t)} \cdot \phi_{s,a'} \right] \\ &\leq \sqrt{\mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left(Q^{(t)}(s, a) - w_\star^{(t)} \cdot \phi_{s,a} \right)^2} + \sqrt{\mathbb{E}_{s \sim d_\rho^*, a' \sim \pi^{(t)}(\cdot|s)} \left(Q^{(t)}(s, a') - w_\star^{(t)} \cdot \phi_{s,a'} \right)^2} \\ &\leq 2\sqrt{|\mathcal{A}| \mathbb{E}_{s \sim d_\rho^*, a \sim \text{Unif}_\mathcal{A}} \left[\left(Q^{(t)}(s, a) - w_\star^{(t)} \cdot \phi_{s,a} \right)^2 \right]} = 2\sqrt{|\mathcal{A}| L(w_\star^{(t)}; \theta^{(t)}, d^*)}. \end{aligned}$$

where we have used the definition of d^* and $L(w_\star^{(t)}; \theta^{(t)}, d^*)$ in the last step. Using following crude upper bound,

$$L(w_\star^{(t)}; \theta^{(t)}, d^*) \leq \left\| \frac{d^*}{d^{(t)}} \right\|_\infty L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \leq \frac{1}{1-\gamma} \left\| \frac{d^*}{\nu} \right\|_\infty L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}),$$

(where the last step uses the definition of $d^{(t)}$, see Equation 11.7), we have that:

$$\mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left[A^{(t)}(s, a) - w_\star^{(t)} \cdot \nabla_\theta \log \pi^{(t)}(a|s) \right] \leq 2\sqrt{\frac{|\mathcal{A}|}{1-\gamma} \left\| \frac{d^*}{\nu} \right\|_\infty L(w_\star^{(t)}; \theta^{(t)}, d^{(t)})}. \quad (11.9)$$

For the second term, let us now show that:

$$\begin{aligned} &\mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left[(w_\star^{(t)} - w^{(t)}) \cdot \nabla_\theta \log \pi^{(t)}(a|s) \right] \\ &\leq 2\sqrt{\frac{|\mathcal{A}| \kappa}{1-\gamma} \left(L(w^{(t)}; \theta^{(t)}, d^{(t)}) - L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \right)} \end{aligned} \quad (11.10)$$

To see this, first observe that a similar argument to the above leads to:

$$\begin{aligned} &\mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left[(w_\star^{(t)} - w^{(t)}) \cdot \nabla_\theta \log \pi^{(t)}(a|s) \right] \\ &= \mathbb{E}_{s \sim d_\rho^*, a \sim \pi^*(\cdot|s)} \left[(w_\star^{(t)} - w^{(t)}) \cdot \phi_{s,a} \right] - \mathbb{E}_{s \sim d_\rho^*, a' \sim \pi^{(t)}(\cdot|s)} \left[(w_\star^{(t)} - w^{(t)}) \cdot \phi_{s,a'} \right] \\ &\leq 2\sqrt{|\mathcal{A}| \mathbb{E}_{s, a \sim d^*} \left[\left((w_\star^{(t)} - w^{(t)}) \cdot \phi_{s,a} \right)^2 \right]} = 2\sqrt{|\mathcal{A}| \cdot \|w_\star^{(t)} - w^{(t)}\|_{\Sigma_{d^*}}^2}, \end{aligned}$$

where we use the notation $\|x\|_M^2 := x^\top M x$ for a matrix M and a vector x . From the definition of κ ,

$$\|w_\star^{(t)} - w^{(t)}\|_{\Sigma_{d^*}}^2 \leq \kappa \|w_\star^{(t)} - w^{(t)}\|_{\Sigma_\nu}^2 \leq \frac{\kappa}{1-\gamma} \|w_\star^{(t)} - w^{(t)}\|_{\Sigma_{d^{(t)}}}^2$$

using that $(1 - \gamma)\nu \leq d_\nu^{(t)}$ (see (11.7)). Due to that $w_\star^{(t)}$ minimizes $L(w; \theta^{(t)}, d^{(t)})$ over the set $\mathcal{W} := \{w : \|w\|_2 \leq W\}$, for any $w \in \mathcal{W}$ the first-order optimality conditions for $w_\star^{(t)}$ imply that:

$$(w - w_\star^{(t)}) \cdot \nabla L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \geq 0.$$

Therefore, for any $w \in \mathcal{W}$,

$$\begin{aligned} & L(w; \theta^{(t)}, d^{(t)}) - L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \\ &= \mathbb{E}_{s,a \sim d^{(t)}} \left[(w \cdot \phi(s, a) - w_\star \cdot \phi(s, a) + w_\star \cdot \phi(s, a) - Q^{(t)}(s, a))^2 \right] - L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \\ &= \mathbb{E}_{s,a \sim d^{(t)}} \left[(w \cdot \phi(s, a) - w_\star \cdot \phi(s, a))^2 \right] + 2(w - w_\star) \mathbb{E}_{s,a \sim d^{(t)}} \left[\phi(s, a) (w_\star \cdot \phi(s, a) - Q^{(t)}(s, a)) \right] \\ &= \|w - w_\star^{(t)}\|_{\Sigma_{d^{(t)}}}^2 + (w - w_\star^{(t)}) \cdot \nabla L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \\ &\geq \|w - w_\star^{(t)}\|_{\Sigma_{d^{(t)}}}^2. \end{aligned}$$

Noting that $w^{(t)} \in \mathcal{W}$ by construction in Algorithm 11.8 yields the claimed bound on the second term in (11.10).

Using the bounds on the first and second terms in (11.9) and (11.10), along with concavity of the square root function, we have that:

$$\text{err}_t \leq 2\sqrt{\frac{|\mathcal{A}|}{1-\gamma} \left\| \frac{d^\star}{\nu} \right\|_\infty L(w_\star^{(t)}; \theta^{(t)}, d^{(t)})} + 2\sqrt{\frac{|\mathcal{A}|\kappa}{1-\gamma} \left(L(w^{(t)}; \theta^{(t)}, d^{(t)}) - L(w_\star^{(t)}; \theta^{(t)}, d^{(t)}) \right)}.$$

The proof is completed by substitution and using our assumptions on ϵ_{stat} and ϵ_{bias} . □

11.5 Q -NPG Sample Complexity

To be added...

11.6 Bibliographic Remarks and Further Readings

The notion of *compatible function approximation* was due to Sutton et al. [1999], which also proved the claim in Lemma 11.1. The close connection of the NPG update rule to compatible function approximation (Lemma 11.3) was noted in Kakade [2001].

The regret lemma (Lemma 11.3) for the NPG analysis has origins in the online regret framework in changing MDPs [Even-Dar et al., 2009]. The convergence rates in this chapter are largely derived from Agarwal et al. [2020d]. The Q-NPG algorithm for the log-linear policy classes is essentially the same algorithm as POLITEX [Abbasi-Yadkori et al., 2019], with a distinction that it is important to use a state action measure over the initial distribution. The analysis and error decomposition of Q-NPG is from Agarwal et al. [2020d], which has a more general analysis of NPG with function approximation under the regret lemma. This more general approach also permits the analysis of neural policy classes, as shown in Agarwal et al. [2020d]. Also, Liu et al. [2019] provide an analysis of the TRPO algorithm [Schulman et al., 2015] (essentially the same as NPG) for neural network parameterizations in the somewhat restrictive linearized “neural tangent kernel” regime.

Chapter 12

CPI, TRPO, and More

In this chapter, we consider conservative policy iteration (CPI) and trust-region constrained policy optimization (TRPO). Both CPI and TRPO can be understood as making small incremental update to the policy by forcing that the new policy's state action distribution is not too far away from the current policy's. We will see that CPI achieves that by forming a new policy that is a mixture of the current policy and a local greedy policy, while TRPO forcing that by explicitly adding a KL constraint (over policies' induced trajectory distributions space) in the optimization procedure. We will show that TRPO gives an equivalent update procedure as Natural Policy Gradient.

Along the way, we discuss the benefit of incremental policy update, by contrasting it to another family of policy update procedure called *Approximate Policy Iteration* (API), which performs local greedy policy search and could potentially lead to abrupt policy change. We show that API in general fails to converge or make local improvement, unless under a much stronger concentrability ratio assumption.

The algorithm and analysis of CPI is adapted from the original one in Kakade and Langford [2002], and the we follow the presentation of TRPO from Schulman et al. [2015], while making a connection to the NGP algorithm.

12.1 Conservative Policy Iteration

As the name suggests, we will now describe a more conservative version of the policy iteration algorithm, which shifts the next policy away from the current policy with a small step size to prevent drastic shifts in successive state distributions.

We consider the discounted MDP here $\{\mathcal{S}, \mathcal{A}, P, r, \gamma, \rho\}$ where ρ is the initial state distribution. Similar to Policy Gradient Methods, we assume that we have a restart distribution μ (i.e., the μ -restart setting). Throughout this section, for any policy π , we denote d_μ^π as the state-action visitation starting from $s_0 \sim \mu$ instead of ρ , and d^π the state-action visitation starting from the true initial state distribution ρ , i.e., $s_0 \sim \rho$. Similarly, we denote V_μ^π as expected discounted total reward of policy π starting at μ , while V^π as the expected discounted total reward of π with ρ as the initial state distribution. We assume $\mathcal{A}$ is discrete but $\mathcal{S}$ could be continuous.

CPI is based on the concept of *Reduction to Supervised Learning*. Specifically we will use the Approximate Greedy Policy Selector defined in Chapter ?? (Definition ??). We recall the definition of the ε -approximate Greedy Policy Selector $\mathcal{G}_\varepsilon(\pi, \Pi, \mu)$ below. Given a policy π , policy class Π , and a restart distribution μ , denote $\hat{\pi} = \mathcal{G}_\varepsilon(\pi, \Pi, \mu)$, we have that:

$$\mathbb{E}_{s \sim d_\mu^\pi} A^\pi(s, \hat{\pi}(s)) \geq \max_{\tilde{\pi} \in \Pi} \mathbb{E}_{s \sim d_\mu^\pi} A^\pi(s, \tilde{\pi}(s)) - \varepsilon.$$

Recall that in Chapter ?? we explained two approach to implement such approximate oracle: one with a reduction to classification oracle, and the other one with a reduction to regression oracle.

12.1.1 The CPI Algorithm

CPI, summarized in Alg. 8, will iteratively generate a sequence of policies π^t . Note we use $\pi_\alpha = (1-\alpha)\pi + \alpha\pi'$ to refer to a randomized policy which at any state s , chooses an action according to π with probability $1 - \alpha$ and according to π' with probability α . The greedy policy π' is computed using the ε -approximate greedy policy selector $\mathcal{G}_\varepsilon(\pi^t, \Pi, \mu)$. The algorithm is terminate when there is no significant one-step improvement over π^t , i.e., $\mathbb{E}_{s \sim d_\mu^{\pi^t}} A^{\pi^t}(s, \pi'(s)) \leq \varepsilon$.

Algorithm 8 Conservative Policy Iteration (CPI)

Input: Initial policy $\pi^0 \in \Pi$, accuracy parameter ε .

```

1: for  $t = 0, 1, 2 \dots$  do
2:    $\pi' = \mathcal{G}_\varepsilon(\pi^t, \Pi, \mu)$ 
3:   if  $\mathbb{E}_{s \sim d_\mu^{\pi^t}} A^{\pi^t}(s, \pi'(s)) \leq \varepsilon$  then
4:     Return  $\pi^t$ 
5:   end if
6:   Update  $\pi^{t+1} = (1 - \alpha)\pi^t + \alpha\pi'$ 
7: end for
```

The main intuition behind the algorithm is that the stepsize α controls the difference between state distributions of π^t and π^{t+1} . Let us look into the performance difference lemma to get some intuition on this conservative update. From PDL, we have:

$$V_\mu^{\pi^{t+1}} - V_\mu^{\pi^t} = \frac{1}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{\pi^{t+1}}} A^{\pi^t}(s, \pi^{t+1}(s)) = \frac{\alpha}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{\pi^{t+1}}} A^{\pi^t}(s, \pi'(s)),$$

where the last equality we use the fact that $\pi^{t+1} = (1-\alpha)\pi^t + \alpha\pi'$ and $A^{\pi^t}(s, \pi^t(s)) = 0$ for all s . Thus, if we can search for a policy $\pi' \in \Pi$ that maximizes $\mathbb{E}_{s \sim d_\mu^{\pi^{t+1}}} A^{\pi^t}(s, \pi'(s))$ and makes $\mathbb{E}_{s \sim d_\mu^{\pi^{t+1}}} A^{\pi^t}(s, \pi'(s)) > 0$, then we can guarantee policy improvement. However, at episode t , we do not know the state distribution of π^{t+1} and all we have access to is $d_\mu^{\pi^t}$. Thus, we explicitly make the policy update procedure to be conservative such that $d_\mu^{\pi^t}$ and the new policy's distribution $d_\mu^{\pi^{t+1}}$ is guaranteed to be not that different. Thus we can hope that $\mathbb{E}_{s \sim d_\mu^{\pi^{t+1}}} A^{\pi^t}(s, \pi'(s))$ is close to $\mathbb{E}_{s \sim d_\mu^{\pi^t}} A^{\pi^t}(s, \pi'(s))$, and the latter is something that we can manipulate using the greedy policy selector.

Below we formalize the above intuition and show that with small enough α , we indeed can ensure monotonic policy improvement.

We start from the following lemma which shows that π^{t+1} and π^t are close to each other in terms of total variation distance at any state, and $d_\mu^{\pi^{t+1}}$ and $d_\mu^{\pi^t}$ are close as well.

Lemma 12.1 (Similar Policies imply similar state visitations). *Consider any t , we have that:*

$$\|\pi^{t+1}(\cdot|s) - \pi^t(\cdot|s)\|_1 \leq 2\alpha, \forall s;$$

Further, we have:

$$\|d_\mu^{\pi^{t+1}} - d_\mu^{\pi^t}\|_1 \leq \frac{2\alpha\gamma}{1-\gamma}.$$

Proof. The first claim in the above lemma comes from the definition of policy update:

$$\|\pi^{t+1}(\cdot|s) - \pi^t(\cdot|s)\|_1 = \alpha \|\pi^t(\cdot|s) - \pi'(\cdot|s)\|_1 \leq 2\alpha.$$

Denote $\mathbb{P}_h^\pi$ as the state distribution resulting from π at time step h with μ as the initial state distribution. We consider bounding $\|\mathbb{P}_h^{\pi^{t+1}} - \mathbb{P}_h^{\pi^t}\|_1$ with $h \geq 1$.

$$\begin{aligned} \mathbb{P}_h^{\pi^{t+1}}(s') - \mathbb{P}_h^{\pi^t}(s') &= \sum_{s,a} \left(\mathbb{P}_{h-1}^{\pi^{t+1}}(s) \pi^{t+1}(a|s) - \mathbb{P}_{h-1}^{\pi^t}(s) \pi^t(a|s) \right) P(s'|s, a) \\ &= \sum_{s,a} \left(\mathbb{P}_{h-1}^{\pi^{t+1}}(s) \pi^{t+1}(a|s) - \mathbb{P}_{h-1}^{\pi^{t+1}}(s) \pi^t(a|s) + \mathbb{P}_{h-1}^{\pi^{t+1}}(s) \pi^t(a|s) - \mathbb{P}_{h-1}^{\pi^t}(s) \pi^t(a|s) \right) P(s'|s, a) \\ &= \sum_s \mathbb{P}_{h-1}^{\pi^{t+1}}(s) \sum_a \left(\pi^{t+1}(a|s) - \pi^t(a|s) \right) P(s'|s, a) \\ &\quad + \sum_s \left(\mathbb{P}_{h-1}^{\pi^{t+1}}(s) - \mathbb{P}_{h-1}^{\pi^t}(s) \right) \sum_a \pi^t(a|s) P(s'|s, a). \end{aligned}$$

Take absolute value on both sides, we get:

$$\begin{aligned} \sum_{s'} \left| \mathbb{P}_h^{\pi^{t+1}}(s') - \mathbb{P}_h^{\pi^t}(s') \right| &\leq \sum_s \mathbb{P}_{h-1}^{\pi^{t+1}}(s) \sum_a \left| \pi^{t+1}(a|s) - \pi^t(a|s) \right| \sum_{s'} P(s'|s, a) \\ &\quad + \sum_s \left| \mathbb{P}_{h-1}^{\pi^{t+1}}(s) - \mathbb{P}_{h-1}^{\pi^t}(s) \right| \sum_{s'} \sum_a \pi^t(a|s) P(s'|s, a) \\ &\leq 2\alpha + \|\mathbb{P}_{h-1}^{\pi^{t+1}} - \mathbb{P}_{h-1}^{\pi^t}\|_1 \leq 4\alpha + \|\mathbb{P}_{h-2}^{\pi^{t+1}} - \mathbb{P}_{h-2}^{\pi^t}\|_1 = 2h\alpha. \end{aligned}$$

Now use the definition of d_μ^π , we have:

$$d_\mu^{\pi^{t+1}} - d_\mu^{\pi^t} = (1 - \gamma) \sum_{h=0}^{\infty} \gamma^h \left(\mathbb{P}_h^{\pi^{t+1}} - \mathbb{P}_h^{\pi^t} \right).$$

Add ℓ_1 norm on both sides, we get:

$$\left\| d_\mu^{\pi^{t+1}} - d_\mu^{\pi^t} \right\|_1 \leq (1 - \gamma) \sum_{h=0}^{\infty} \gamma^h 2h\alpha$$

It is not hard to verify that $\sum_{h=0}^{\infty} \gamma^h h = \frac{\gamma}{(1-\gamma)^2}$. Thus, we can conclude that:

$$\left\| d_\mu^{\pi^{t+1}} - d_\mu^{\pi^t} \right\|_1 \leq \frac{2\alpha\gamma}{1-\gamma}.$$

□

The above lemma states that if π^{t+1} and π^t are close in terms of total variation distance for every state, then the total variation distance between the resulting state visitations from π^{t+1} and π^t will be small up to a effective horizon $1/(1-\gamma)$ amplification.

The above lemma captures the key of the conservative policy update. Via the conservative policy update, we make sure that $d_\mu^{\pi^{t+1}}$ and $d_\mu^{\pi^t}$ are close to each other in terms of total variation distance. Now we use the above lemma to show a monotonic policy improvement.

Theorem 12.2 (Monotonic Improvement in CPI). *Consider any episode t . Denote $\mathbb{A} = \mathbb{E}_{s \sim d_\mu^{\pi^t}} A^{\pi^t}(s, \pi'(s))$. We have:*

$$V_\mu^{\pi^{t+1}} - V_\mu^{\pi^t} \geq \frac{\alpha}{1-\gamma} \left(\mathbb{A} - \frac{2\alpha\gamma}{(1-\gamma)^2} \right)$$

Set $\alpha = \frac{\mathbb{A}(1-\gamma)^2}{4\gamma}$, we get:

$$V_\mu^{\pi^{t+1}} - V_\mu^{\pi^t} \geq \frac{\mathbb{A}^2(1-\gamma)}{8\gamma}.$$

The above lemma shows that as long as we still have positive one-step improvement, i.e., $\mathbb{A} > 0$, then we guarantee that π^{t+1} is strictly better than π^t .

Proof. Via PDL, we have:

$$V_\mu^{\pi^{t+1}} - V_\mu^{\pi^t} = \frac{1}{1-\gamma} \mathbb{E}_{s \sim d_\mu^{\pi^{t+1}}} \alpha A^{\pi^t}(s, \pi'(s)).$$

Recall Lemma 12.1, we have:

$$\begin{aligned} (1-\gamma) \left(V_\mu^{\pi^{t+1}} - V_\mu^{\pi^t} \right) &= \mathbb{E}_{s \sim d_\mu^{\pi^t}} \alpha A^{\pi^t}(s, \pi'(s)) + \mathbb{E}_{s \sim d_\mu^{\pi^{t+1}}} \alpha A^{\pi^t}(s, \pi'(s)) - \mathbb{E}_{s \sim d_\mu^{\pi^t}} \alpha A^{\pi^t}(s, \pi'(s)) \\ &\geq \mathbb{E}_{s \sim d_\mu^{\pi^t}} \alpha A^{\pi^t}(s, \pi'(s)) - \alpha \sup_{s, a, \pi} |A^\pi(s, a)| \|d_\mu^{\pi^t} - d_\mu^{\pi^{t+1}}\|_1 \\ &\geq \mathbb{E}_{s \sim d_\mu^{\pi^t}} \alpha A^{\pi^t}(s, \pi'(s)) - \frac{\alpha}{1-\gamma} \|d_\mu^{\pi^t} - d_\mu^{\pi^{t+1}}\|_1 \\ &\geq \mathbb{E}_{s \sim d_\mu^{\pi^t}} \alpha A^{\pi^t}(s, \pi'(s)) - \frac{2\alpha^2\gamma}{(1-\gamma)^2} = \alpha \left(\mathbb{A} - \frac{2\alpha\gamma}{(1-\gamma)^2} \right) \end{aligned}$$

where the first inequality we use the fact that for any two distributions P_1 and P_2 and any function f , $|\mathbb{E}_{x \sim P_1} f(x) - \mathbb{E}_{x \sim P_2} f(x)| \leq \sup_x |f(x)| \|P_1 - P_2\|_1$, for the second inequality, we use the fact that $|A^\pi(s, a)| \leq 1/(1-\gamma)$ for any π, s, a , and the last inequality uses Lemma 12.1.

For the second part of the above theorem, note that we want to maximum the policy improvement as much as possible by choosing α . So we can pick α which maximizes $\alpha(\mathbb{A} - 2\alpha\gamma/(1-\gamma)^2)$. This gives us the α we claimed in the lemma. Plug in α back into $\alpha(\mathbb{A} - 2\alpha\gamma/(1-\gamma)^2)$, we conclude the second part of the theorem. $\square$

The above theorem indicates that with the right choice of α , we guarantee that the policy is making improvement as long as $\mathbb{A} > 0$. Recall the termination criteria in CPI where we terminate CPI when $\mathbb{A} \leq \varepsilon$. Putting these results together, we obtain the following overall convergence guarantee for the CPI algorithm.

Theorem 12.3 (Local optimality of CPI). *Algorithm 8 terminates in at most $8\gamma/\varepsilon^2$ steps and outputs a policy π^t satisfying $\max_{\pi \in \Pi} \mathbb{E}_{s \sim d_\mu^{\pi^t}} A^{\pi^t}(s, \pi(s)) \leq 2\varepsilon$.*

Proof. Note that our reward is bounded in $[0, 1]$ which means that $V_\mu^{\pi^t} \in [0, 1/(1-\gamma)]$. Note that we have shown in Theorem 12.2, every iteration t , we have policy improvement at least $\frac{\mathbb{A}^2(1-\gamma)}{8\gamma}$, where recall $\mathbb{A}$ at episode t is defined as $\mathbb{A} = \mathbb{E}_{s \sim d_\mu^{\pi^t}} A^{\pi^t}(s, \pi'(s))$. If the algorithm does not terminate at episode t , then we guarantee that:

$$V_\mu^{\pi^{t+1}} \geq V_\mu^{\pi^t} + \frac{\varepsilon^2(1-\gamma)}{8\gamma}$$

Since V_μ^π is upper bounded by $1/(1-\gamma)$, so we can at most make improvement $8\gamma/\epsilon^2$ many iterations.

Finally, recall that ϵ -approximate greedy policy selector $\pi' = \mathcal{G}_\epsilon(\pi^t, \Pi, \mu)$, we have:

$$\max_{\pi \in \Pi} \mathbb{E}_{s \sim d_\mu^{\pi^t}} A^{\pi^t}(s, \pi(s)) \leq \mathbb{E}_{s \sim d_\mu^{\pi^t}} A^{\pi^t}(s, \pi'(s)) + \epsilon \leq 2\epsilon$$

This concludes the proof. $\square$

Theorem 12.3 can be viewed as a local optimality guarantee in a sense. It shows that when CPI terminates, we cannot find a policy $\pi \in \Pi$ that achieves local improvement over the returned policy more than ϵ . However, this does not necessarily imply that the value of π is close to V^* . However, similar to the policy gradient analysis, we can turn this local guarantee into a global one when the restart distribution μ covers d^{π^*} . We formalize this intuition next.

Theorem 12.4 (Global optimality of CPI). *Upon termination, we have a policy π such that:*

$$V^* - V^\pi \leq \frac{2\epsilon + \epsilon_\Pi}{(1-\gamma)^2} \left\| \frac{d^{\pi^*}}{\mu} \right\|_\infty,$$

where $\epsilon_\Pi := \mathbb{E}_{s \sim d_\mu^\pi} [\max_{a \in \mathcal{A}} A^\pi(s, a)] - \max_{\pi \in \Pi} \mathbb{E}_{s \sim d_\mu^\pi} [A^\pi(s, \pi(s))]$.

In other words, if our policy class is rich enough to approximate the policy $\max_{a \in \mathcal{A}} A^\pi(s, a)$ under d_μ^π , i.e., ϵ_Π is small, and μ covers d^{π^*} in a sense that $\left\| \frac{d^{\pi^*}}{\mu} \right\|_\infty \leq \infty$, CPI guarantees to find a near optimal policy.

Proof. By the performance difference lemma,

$$\begin{aligned} V^* - V^\pi &= \frac{1}{1-\gamma} \mathbb{E}_{s \sim d^{\pi^*}} A^\pi(s, \pi^*(s)) \\ &\leq \frac{1}{1-\gamma} \mathbb{E}_{s \sim d^{\pi^*}} \max_{a \in \mathcal{A}} A^\pi(s, a) \\ &\leq \frac{1}{1-\gamma} \left\| \frac{d^{\pi^*}}{d_\mu^\pi} \right\|_\infty \mathbb{E}_{s \sim d_\mu^\pi} \max_{a \in \mathcal{A}} A^\pi(s, a) \\ &\leq \frac{1}{(1-\gamma)^2} \left\| \frac{d^{\pi^*}}{\mu} \right\|_\infty \mathbb{E}_{s \sim d_\mu^\pi} \max_{a \in \mathcal{A}} A^\pi(s, a) \\ &= \frac{1}{(1-\gamma)^2} \left\| \frac{d^{\pi^*}}{\mu} \right\|_\infty \left[\max_{\hat{\pi} \in \Pi} \mathbb{E}_{s \sim d_\mu^{\hat{\pi}}} A^\pi(s, \hat{\pi}(s)) - \max_{\hat{\pi} \in \Pi} \mathbb{E}_{s \sim d_\mu^{\hat{\pi}}} A^\pi(s, \hat{\pi}(s)) + \mathbb{E}_{s \sim d_\mu^\pi} \max_{a \in \mathcal{A}} A^\pi(s, a) \right] \\ &\leq \frac{1}{(1-\gamma)^2} \left\| \frac{d^{\pi^*}}{\mu} \right\|_\infty (2\epsilon + \epsilon_\Pi), \end{aligned}$$

where the second inequality holds due to the fact that $\max_a A^\pi(s, a) \geq 0$, the third inequality uses the fact that $d_\mu^\pi(s) \geq (1-\gamma)\mu(s)$ for any s and π , and the last inequality uses the definition ϵ_Π and Theorem 12.3. $\square$

It is informative to contrast CPI and policy gradient algorithms due to the similarity of their guarantees. Both provide local optimality guarantees. For CPI, the local optimality always holds, while for policy gradients it requires a smooth value function as a function of the policy parameters. If the distribution mismatch between an optimal policy and the output of the algorithm is not too large, then both algorithms further yield a near optimal policy. The similarities are not so surprising. Both algorithms operate by making local improvements to the current policy at each iteration, by inspecting its advantage function. The changes made to the policy are controlled using a stepsize parameter in both the approaches. It is the actual mechanism of the improvement which differs in the two cases. Policy gradients assume that the policy's reward is a differentiable function of the parameters, and hence make local improvements through

gradient ascent. The differentiability is certainly an assumption and does not necessarily hold for all policy classes. An easy example is when the policy itself is not an easily differentiable function of its parameters. For instance, if the policy is parametrized by regression trees, then performing gradient updates can be challenging.

In CPI, on the other hand, the basic computational primitive required on the policy class is the ability to maximize the advantage function relative to the current policy. Notice that Algorithm 8 does not necessarily restrict to a policy class, such as a set of parametrized policies as in policy gradients. Indeed, due to the reduction to supervised learning approach (e.g., using the weighted classification oracle CO), we can parameterize policy class via decision tree, for instance. This property makes CPI extremely attractive. Any policy class over which efficient supervised learning algorithms exist can be adapted to reinforcement learning with performance guarantees.

A second important difference between CPI and policy gradients is in the notion of locality. Policy gradient updates are local in the parameter space, and we hope that this makes small enough changes to the state distribution that the new policy is indeed an improvement on the older one (for instance, when we invoke the performance difference lemma between successive iterates). While this is always true in expectation for correctly chosen stepsizes based on properties of stochastic gradient ascent on smooth functions, the variance of the algorithm and lack of robustness to suboptimal stepsizes can make the algorithm somewhat finicky. Indeed, there are a host of techniques in the literature to both lower the variance (through control variates) and explicitly control the state distribution mismatch between successive iterates of policy gradients (through trust region techniques). On the other hand, CPI explicitly controls the amount of perturbation to the state distribution by carefully mixing policies in a manner which does not drastically alter the trajectories with high probability. Indeed, this insight is central to the proof of CPI, and has been instrumental in several follow-ups, both in the direct policy improvement as well as policy gradient literature.

12.2 Trust Region Methods and Covariant Policy Search

So far we have seen policy gradient methods and CPI which all uses a small step-size to ensure incremental update in policies. Another popular approach for incremental policy update is to explicitly forcing small change in policies' distribution via a trust region constraint. More specifically, let us go back to the general policy parameterization π_θ . At iteration t with the current policy π_{θ_t} , we are interested in the following local trust-region constrained optimization:

$$\begin{aligned} & \max_{\theta} \mathbb{E}_{s \sim d_{\mu}^{\pi_{\theta_t}}} \mathbb{E}_{a \sim \pi_{\theta}(\cdot|s)} A^{\pi_{\theta_t}}(s, a) \\ & \text{s.t., } KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right) \leq \delta, \end{aligned}$$

where recall $\Pr_{\mu}^{\pi}(\tau)$ is the trajectory distribution induced by π starting at $s_0 \sim \mu$, and $KL(P_1 \parallel P_2)$ are KL-divergence between two distribution P_1 and P_2 . Namely we explicitly perform local policy search with a constraint forcing the new policy not being too far away from $\Pr_{\mu}^{\pi_{\theta_t}}$ in terms of KL divergence.

As we are interested in small local update in parameters, we can perform sequential quadratic programming here, i.e., we can further linearize the objective function at θ_t and quadraticize the KL constraint at θ_t to form a local quadratic programming:

$$\max_{\theta} \left\langle \mathbb{E}_{s \sim d_{\mu}^{\pi_{\theta_t}}} \mathbb{E}_{a \sim \pi_{\theta_t}(\cdot|s)} \nabla_{\theta} \ln \pi_{\theta_t}(a|s) A^{\pi_{\theta_t}}(s, a), \theta \right\rangle \quad (12.1)$$

$$\text{s.t., } \langle \nabla_{\theta} KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right) |_{\theta=\theta_t}, \theta - \theta_t \rangle + \frac{1}{2}(\theta - \theta_t)^{\top} \left(\nabla_{\theta}^2 KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right) |_{\theta=\theta_t} \right) (\theta - \theta_t) \leq \delta, \quad (12.2)$$

where we denote $\nabla^2 KL|_{\theta=\theta_t}$ as the Hessian of the KL constraint measured at θ_t . Note that KL divergence is not a valid metric as it is not symmetric. However, its local quadratic approximation can serve as a valid local distance metric, as we prove below that the Hessian $\nabla^2 KL|_{\theta=\theta_t}$ is a positive semi-definite matrix. Indeed, we will show that the Hessian of the KL constraint is exactly equal to the fisher information matrix, and the above quadratic programming

exactly reveals a Natural Policy Gradient update. Hence Natural policy gradient can also be interpreted as performing sequential quadratic programming with KL constraint over policy's trajectory distributions.

To match to the practical algorithms in the literature (e.g., TRPO), below we focus on episode finite horizon setting again (i.e., an MDP with horizon H).

Claim 12.5. *Consider a finite horizon MDP with horizon H . Consider any fixed θ_t . We have:*

$$\begin{aligned}\nabla_{\theta} KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right) |_{\theta=\theta_t} &= 0, \\ \nabla_{\theta}^2 KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right) |_{\theta=\theta_t} &= H \mathbb{E}_{s,a \sim d^{\pi_{\theta_t}}} \nabla \ln \pi_{\theta_t}(a|s) (\nabla \ln \pi_{\theta_t}(a|s))^{\top}.\end{aligned}$$

Proof. We first recall the trajectory distribution in finite horizon setting.

$$\Pr_{\mu}^{\pi}(\tau) = \mu(s_0) \prod_{h=0}^{H-1} \pi(a_h|s_h) P(s_{h+1}|s_h, a_h).$$

We first prove that the gradient of KL is zero. First note that:

$$\begin{aligned}KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right) &= \sum_{\tau} \Pr_{\mu}^{\pi_{\theta_t}}(\tau) \ln \frac{\Pr_{\mu}^{\pi_{\theta_t}}(\tau)}{\Pr_{\mu}^{\pi_{\theta}}(\tau)} \\ &= \sum_{\tau} \Pr_{\mu}^{\pi_{\theta_t}}(\tau) \left(\sum_{h=0}^{H-1} \ln \frac{\pi_{\theta_t}(a_h|s_h)}{\pi_{\theta}(a_h|s_h)} \right) = \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim \mathbb{P}_h^{\pi_{\theta_t}}} \ln \frac{\pi_{\theta_t}(a_h|s_h)}{\pi_{\theta}(a_h|s_h)}.\end{aligned}$$

Thus, for $\nabla_{\theta} KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right)$, we have:

$$\begin{aligned}\nabla KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right) |_{\theta=\theta_t} &= \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim \mathbb{P}_h^{\pi_{\theta_t}}} -\nabla \ln \pi_{\theta_t}(a_h|s_h) \\ &= -\sum_{h=0}^{H-1} \mathbb{E}_{s_h \sim \mathbb{P}_h^{\pi_{\theta_t}}} \mathbb{E}_{a_h \sim \pi_{\theta_t}(\cdot|s_h)} \nabla \ln \pi_{\theta_t}(a_h|s_h) = 0,\end{aligned}$$

where we have seen the last step when we argue the unbiased nature of policy gradient with an action independent baseline.

Now we move to the Hessian.

$$\begin{aligned}\nabla^2 KL\left(\Pr_{\mu}^{\pi_{\theta_t}} \parallel \Pr_{\mu}^{\pi_{\theta}}\right) |_{\theta=\theta_t} &= -\sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim \mathbb{P}_h^{\pi_{\theta_t}}} \nabla^2 \ln \pi_{\theta}(a_h|s_h) |_{\theta=\theta_t} \\ &= -\sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim \mathbb{P}_h^{\pi_{\theta_t}}} \left(\nabla \left(\frac{\nabla \pi_{\theta}(a|s)}{\pi_{\theta}(a|s)} \right) \right) \\ &= -\sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim \mathbb{P}_h^{\pi_{\theta_t}}} \left(\frac{\nabla^2 \pi_{\theta}(a_h|s_h)}{\pi_{\theta}(a_h|s_h)} - \frac{\nabla \pi_{\theta}(a_h|s_h) \nabla \pi_{\theta}(a_h|s_h)^{\top}}{\pi_{\theta}^2(a_h|s_h)} \right) \\ &= \sum_{h=0}^{H-1} \mathbb{E}_{s_h, a_h \sim \mathbb{P}_h^{\pi_{\theta_t}}} \nabla_{\theta} \ln \pi_{\theta}(a_h|s_h) \nabla_{\theta} \ln \pi_{\theta}(a_h|s_h)^{\top},\end{aligned}$$

where in the last equation we use the fact that $\mathbb{E}_{s_h, a_h \sim \mathbb{P}_h^{\pi_{\theta_t}}} \frac{\nabla^2 \pi_{\theta}(a_h|s_h)}{\pi_{\theta}(a_h|s_h)} = 0$. □

The above claim shows that a second order Taylor expansion of the KL constraint over trajectory distribution gives a local distance metric at θ_t :

$$(\theta - \theta_t)F_{\theta_t}(\theta - \theta_t),$$

where again $F_{\theta_t} := H\mathbb{E}_{s,a \sim d^{\pi_{\theta_t}}} \nabla \ln \pi_{\theta_t}(a|s) (\nabla \ln \pi_{\theta_t}(a|s))^\top$ is proportional to the fisher information matrix. Note that F_{θ_t} is a PSD matrix and thus $d(\theta, \theta_t) := (\theta - \theta_t)F_{\theta_t}(\theta - \theta_t)$ is a valid distance metric. By sequential quadratic programming, we are using local geometry information of the trajectory distribution manifold induced by the parameterization θ , rather the naive Euclidean distance in the parameter space. Such a method is sometimes referred to as *Covariant Policy Search*, as the policy update procedure will be invariant to linear transformation of parameterization (See Section 12.3 for further discussion).

Now using the results from Claim 12.5, we can verify that the local policy optimization procedure in Eq. 12.2 exactly recovers the NPG update, where the step size is based on the trust region parameter δ . Denote $\Delta = \theta - \theta_t$, we have:

$$\begin{aligned} & \max_{\Delta} \langle \Delta, \nabla_{\theta} V^{\pi_{\theta_t}} \rangle, \\ & \text{s.t.}, \Delta^\top F_{\theta_t} \Delta \leq \delta, \end{aligned}$$

which gives the following update procedure:

$$\theta_{t+1} = \theta_t + \Delta = \theta_t + \sqrt{\frac{\delta}{(\nabla V^{\pi_{\theta_t}})^\top F_{\theta_t}^{-1} \nabla V^{\pi_{\theta_t}}}} \cdot F_{\theta_t}^{-1} \nabla V^{\pi_{\theta_t}},$$

where note that we use the self-normalized learning rate computed using the trust region parameter δ .

12.2.1 Proximal Policy Optimization

Here we consider an ℓ_∞ style trust region constraint:

$$\max_{\theta} \mathbb{E}_{s \sim d_{\mu}^{\pi_{\theta_t}}} \mathbb{E}_{a \sim \pi_{\theta}(\cdot|s)} A^{\pi_{\theta_t}}(s, a) \quad (12.3)$$

$$\text{s.t.}, \sup_s \|\pi_{\theta}(\cdot|s) - \pi_{\theta_t}(\cdot|s)\|_{tv} \leq \delta, \quad (12.4)$$

Namely, we restrict the new policy such that it is close to π_{θ_t} at every state s under the total variation distance. Recall the CPI's update, CPI indeed makes sure that the new policy will be close the old policy at every state. In other words, the new policy computed by CPI is a feasible solution of the constraint Eq. 12.4, but is not the optimal solution of the above constrained optimization program. Also one downside of the CPI algorithm is that one needs to keep all previous learned policies around, which requires large storage space when policies are parameterized by large deep neural networks.

Proximal Policy Optimization (PPO) aims to directly optimize the objective Eq. 12.3 using multiple steps of gradient updates, and approximating the constraints Eq. 12.4 via a clipping trick. We first rewrite the objective function using importance weighting:

$$\max_{\theta} \mathbb{E}_{s \sim d_{\mu}^{\pi_{\theta_t}}} \mathbb{E}_{a \sim \pi_{\theta_t}(\cdot|s)} \frac{\pi_{\theta}(a|s)}{\pi_{\theta_t}(a|s)} A^{\pi_{\theta_t}}(s, a), \quad (12.5)$$

where we can easily approximate the expectation $\mathbb{E}_{s \sim d_{\mu}^{\pi_{\theta_t}}} \mathbb{E}_{a \sim \pi_{\theta_t}(\cdot|s)}$ via finite samples $s \sim d^{\pi_{\theta_t}}, a \sim \pi_{\theta_t}(\cdot|s)$.

To make sure $\pi_{\theta}(a|s)$ and $\pi_{\theta_t}(a|s)$ are not that different, PPO modifies the objective function by clipping the density ratio $\pi_{\theta}(a|s)$ and $\pi_{\theta_t}(a|s)$:

$$L(\theta) := \mathbb{E}_{s \sim d_{\mu}^{\pi_{\theta_t}}} \mathbb{E}_{a \sim \pi_{\theta_t}(\cdot|s)} \min \left\{ \frac{\pi_{\theta}(a|s)}{\pi_{\theta_t}(a|s)} A^{\pi_{\theta_t}}(s, a), \text{clip} \left(\frac{\pi_{\theta}(a|s)}{\pi_{\theta_t}(a|s)}; 1 - \epsilon, 1 + \epsilon \right) A^{\pi_{\theta_t}}(s, a) \right\}, \quad (12.6)$$

where $\text{clip}(x; 1 - \epsilon, 1 + \epsilon) = \begin{cases} 1 - \epsilon & x \leq 1 - \epsilon \\ 1 + \epsilon & x \geq 1 + \epsilon \\ x & \text{else} \end{cases}$. The clipping operator ensures that for π_θ , at any state action pair

where $\pi^\theta(a|s)/\pi^{\theta_t}(a|s) \notin [1 - \epsilon, 1 + \epsilon]$, we get zero gradient, i.e., $\nabla_\theta \left[\text{clip} \left(\frac{\pi^\theta(a|s)}{\pi^{\theta_t}(\cdot|s)}; 1 - \epsilon, 1 + \epsilon \right) A^{\pi^{\theta_t}}(s, a) \right] = 0$. The outer min makes sure the objective function $L(\theta)$ is a lower bound of the original objective. PPO then proposes to collect a dataset (s, a) with $s \sim d_\mu^{\pi^{\theta_t}}$ and $a \sim \pi^{\theta_t}(\cdot|s)$, and then perform multiple steps of mini-batch stochastic gradient ascent on $L(\theta)$.

One of the key difference between PPO and other algorithms such as NPG is that PPO targets to optimize objective Eq. 12.5 via multiple steps of mini-batch stochastic gradient ascent with mini-batch data from $d_\mu^{\pi^{\theta_t}}$ and π^{θ_t} , while algorithm such as NPG indeed optimizes the first order Taylor expansion of Eq. 12.5 at θ_t , i.e.,

$$\max_{\theta} \left\langle (\theta - \theta_t), \mathbb{E}_{s, a \sim d_\mu^{\pi^{\theta_t}}} \nabla_\theta \ln \pi^{\theta_t}(a|s) A^{\pi^{\theta_t}}(s, a) \right\rangle,$$

upper to some trust region constraints (e.g., $\|\theta - \theta_t\|_2 \leq \delta$ in policy gradient, and $\|\theta - \theta_t\|_{F_{\theta_t}}^2 \leq \delta$ for NPG).

12.3 Bibliographic Remarks and Further Readings

The analysis of CPI is adapted from the original one in Kakade and Langford [2002]. There have been a few further interpretations of CPI. One interesting perspective is that CPI can be treated as a boosting algorithm Scherrer and Geist [2014].

More generally, CPI and NPG are part of family of *incremental* algorithms, including Policy Search by Dynamic Programming (PSDP) Bagnell et al. [2004] and MD-MPI Geist et al. [2019]. PSDP operates in a finite horizon setting and optimizes a sequence of time-dependent policies; from the last time step to the first time step, every iteration of, PSDP only updates the policy at the current time step while holding the future policies fixed — thus making incremental update on the policy. See Scherrer [2014] for more a detailed discussion and comparison of some of these approaches. Mirror Descent-Modified Policy Iteration (MD-MPI) algorithm [Geist et al., 2019] is a family of actor-critic style algorithms which is based on regularization and is incremental in nature; with negative entropy as the Bregman divergence (for the tabular case), MD-MPI recovers the NPG the tabular case (for the softmax parameterization).

Broadly speaking, these incremental algorithms can improve upon the stringent concentrability conditions for approximate value iteration methods, presented in Chapter ?? . Scherrer [2014] provide a more detailed discussion of bounds which depend on these density ratios. As discussed in the last chapter, the density ratio for NPG can be interpreted as a factor due to transfer learning to a single, *fixed* distribution.

The interpretation of NPG as Covariant Policy Search is due to Bagnell and Schneider [2003], as the policy update procedure will be invariant to linear transformations of the parameterization; see Bagnell and Schneider [2003] for a more detailed discussion on this.

The TRPO algorithm is due to Schulman et al. [2015]. The original TRPO analysis provides performance guarantees, largely relying on a reduction to the CPI guarantees. In this Chapter, we make a sharper connection of TRPO to NPG, which was subsequently observed by a number of researchers; this connection provides a sharper analysis for the generalization and approximation behavior of TRPO (e.g. via the results presented in Chapter 11). In practice, a popular variant is the Proximal Policy Optimization (PPO) algorithm Schulman et al. [2017].

Part IV

Further Topics

Chapter 13

Imitation Learning

In this chapter, we study imitation learning. Unlike the Reinforcement Learning setting, in Imitation Learning, we do not have access to the ground truth reward function (or cost function), but instead, we have expert demonstrations. We often assume that the expert is a policy that approximately optimizes the underlying reward (or cost) functions. The goal is to leverage the expert demonstrations to learn a policy that performs as good as the expert.

We consider three settings of imitation learning: (1) pure offline where we only have expert demonstrations and no more real world interaction is allowed, (2) hybrid where we have expert demonstrations, and also is able to interact with the real world (e.g., have access to the ground truth transition dynamics); (3) interactive setting where we have an interactive expert and also have access to the underlying reward (cost) function.

13.1 Setting

We will focus on finite horizon MDPs $\mathcal{M} = \{\mathcal{S}, \mathcal{A}, r, \mu, P, H\}$ where r is the reward function but is unknown to the learner. We represent the expert as a closed-loop policy $\pi^* : \mathcal{S} \mapsto \Delta(\mathcal{A})$. For analysis simplicity, we assume the expert π^* is indeed the optimal policy of the original MDP $\mathcal{M}$ with respect to the ground truth reward r . Again, our goal is to learn a policy $\hat{\pi} : \mathcal{S} \mapsto \Delta(\mathcal{A})$ that performs as well as the expert, i.e., $V^{\hat{\pi}}$ needs to be close to V^* , where V^π denotes the expected total reward of policy π under the MDP $\mathcal{M}$. We denote d^π as the state-action visitation of policy π under $\mathcal{M}$.

We assume we have a pre-collected expert dataset in the format of $\{s_i^*, a_i^*\}_{i=1}^M$ where $s_i^*, a_i^* \sim d^{\pi^*}$.

13.2 Offline IL: Behavior Cloning

We study offline IL here. Specifically, we study the classic Behavior Cloning algorithm.

We consider a policy class $\Pi = \{\pi : \mathcal{S} \mapsto \Delta(\mathcal{A})\}$. We consider the following realizable assumption.

Assumption 13.1. We assume Π is rich enough such that $\pi^* \in \Pi$.

For analysis simplicity, we assume Π is discrete. But our sample complexity will only scale with respect to $\ln(|\Pi|)$.

Behavior cloning is one of the simplest Imitation Learning algorithm which only uses the expert data $\mathcal{D}^*$ and does not require any further interaction with the MDP. It computes a policy via a reduction to supervised learning. Specifically,

we consider a reduction to Maximum Likelihood Estimation (MLE):

$$\text{Behavior Cloning (BC): } \hat{\pi} = \operatorname{argmax}_{\pi \in \Pi} \sum_{i=1}^N \ln \pi(a_i^* | s_i^*). \quad (13.1)$$

Namely we try to find a policy from Π that has the maximum likelihood of fitting the training data. As this is a reduction to MLE, we can leverage the existing classic analysis of MLE (e.g., Chapter 7 in Geer and van de Geer [2000]) to analyze the performance of the learned policy.

Theorem 13.2 (MLE Guarantee). *Consider the MLE procedure (Eq. 13.1). With probability at least $1 - \delta$, we have:*

$$\mathbb{E}_{s \sim d^{\pi^*}} \|\hat{\pi}(\cdot | s) - \pi^*(\cdot | s)\|_{tv}^2 \leq \frac{2 \ln(|\Pi|/\delta)}{M}.$$

We refer readers to Section E, Theorem 21 in Agarwal et al. [2020b] for detailed proof of the above MLE guarantee.

Now we can transfer the average divergence between $\hat{\pi}$ and π^* to their performance difference $V^{\hat{\pi}}$ and V^{π^*} .

One thing to note is that BC only ensures that the learned policy $\hat{\pi}$ is close to π^* under d^{π^*} . Outside of d^{π^*} 's support, we have no guarantee that $\hat{\pi}$ and π^* will be close to each other. The following theorem shows that a compounding error occurs when we study the performance of the learned policy $V^{\hat{\pi}}$.

Theorem 13.3 (Sample Complexity of BC). *With probability at least $1 - \delta$, BC returns a policy $\hat{\pi}$ such that:*

$$V^* - V^{\hat{\pi}} \leq \frac{3}{(1 - \gamma)^2} \sqrt{\frac{\ln(|\Pi|/\delta)}{M}}.$$

Proof. We start with the performance difference lemma and the fact that $\mathbb{E}_{a \sim \pi(\cdot | s)} A^\pi(s, a) = 0$:

$$\begin{aligned} (1 - \gamma) (V^* - V^{\hat{\pi}}) &= \mathbb{E}_{s \sim d^{\pi^*}} \mathbb{E}_{a \sim \pi^*(\cdot | s)} A^{\hat{\pi}}(s, a) \\ &= \mathbb{E}_{s \sim d^{\pi^*}} \mathbb{E}_{a \sim \pi^*(\cdot | s)} A^{\hat{\pi}}(s, a) - \mathbb{E}_{s \sim d^{\pi^*}} \mathbb{E}_{a \sim \hat{\pi}(\cdot | s)} A^{\hat{\pi}}(s, a) \\ &\leq \mathbb{E}_{s \sim d^{\pi^*}} \frac{1}{1 - \gamma} \|\pi^*(\cdot | s) - \hat{\pi}(\cdot | s)\|_1 \\ &\leq \frac{1}{1 - \gamma} \sqrt{\mathbb{E}_{s \sim d^{\pi^*}} \|\pi^*(\cdot | s) - \hat{\pi}(\cdot | s)\|_1^2} \\ &= \frac{1}{1 - \gamma} \sqrt{4 \mathbb{E}_{s \sim d^{\pi^*}} \|\pi^*(\cdot | s) - \hat{\pi}(\cdot | s)\|_{tv}^2}. \end{aligned}$$

where we use the fact that $\sup_{s, a, \pi} |A^\pi(s, a)| \leq \frac{1}{1 - \gamma}$, and the fact that $(\mathbb{E}[x])^2 \leq \mathbb{E}[x^2]$.

Using Theorem 13.2 and rearranging terms conclude the proof. $\square$

For Behavior cloning, from the supervised learning error the quadratic polynomial dependency on the effect horizon $1/(1 - \gamma)$ is not avoidable in worst case Ross and Bagnell [2010]. This is often referred as the distribution shift issue in the literature. Note that $\hat{\pi}$ is trained under d^{π^*} , but during execution, $\hat{\pi}$ makes prediction on states that are generated by itself, i.e., $d^{\hat{\pi}}$, instead of the training distribution d^{π^*} .

13.3 The Hybrid Setting: Statistical Benefit and Algorithm

The question we want to answer here is that if we know the underlying MDP's transition P (but the reward is still unknown), can we improve Behavior Cloning? In other words:

what is the benefit of the known transition in addition to the expert demonstrations?

Instead of a quadratic dependency on the effective horizon, we should expect a linear dependency on the effective horizon. The key benefit of the known transition is that we can test our policy using the known transition to see how far away we are from the expert's demonstrations, and then use the known transition to plan to move closer to the expert demonstrations.

In this section, we consider a statistical efficient, but computationally intractable algorithm, which we use to demonstrate that informationally theoretically, by interacting with the underlying known transition, we can do better than Behavior Cloning. In the next section, we will introduce a popular and computationally efficient algorithm Maximum Entropy Inverse Reinforcement Learning (MaxEnt-IRL) which operates under this setting (i.e., expert demonstrations with a known transition).

We start from the same policy class Π as we have in the BC algorithm, and again we assume realizability (Assumption 13.1) and Π is discrete.

Since we know the transition P , information theoretically, for any policy π , we have d^π available (though it is computationally intractable to compute d^π for large scale MDPs). We have $(s_i^*, a_i^*)_{i=1}^M \sim d^{\pi^*}$.

Below we present an algorithm which we called Distribution Matching with Scheffé Tournament (DM-ST).

For any two policies π and π' , we denote $f_{\pi, \pi'}$ as the following witness function:

$$f_{\pi, \pi'} := \operatorname{argmax}_{f: \|f\|_\infty \leq 1} \left[\mathbb{E}_{s, a \sim d^\pi} f(s, a) - \mathbb{E}_{s, a \sim d^{\pi'}} f(s, a) \right].$$

We denote the set of witness functions as:

$$\mathcal{F} = \{f_{\pi, \pi'} : \pi, \pi' \in \Pi, \pi \neq \pi'\}.$$

Note that $|\mathcal{F}| \leq |\Pi|^2$.

DM-ST selects $\hat{\pi}$ using the following procedure:

$$\text{DM-ST: } \hat{\pi} \in \operatorname{argmin}_{\pi \in \Pi} \left[\max_{f \in \mathcal{F}} \left[\mathbb{E}_{s, a \sim d^\pi} f(s, a) - \frac{1}{M} \sum_{i=1}^M f(s_i^*, a_i^*) \right] \right].$$

The following theorem captures the sample complexity of DM-ST.

Theorem 13.4 (Sample Complexity of DM-ST). *With probability at least $1 - \delta$, DM-ST finds a policy $\hat{\pi}$ such that:*

$$V^* - V^{\hat{\pi}} \leq \frac{4}{1 - \gamma} \sqrt{\frac{2 \ln(|\Pi|) + \ln\left(\frac{1}{\delta}\right)}{M}}.$$

Proof. The proof basically relies on a uniform convergence argument over $\mathcal{F}$ of which the size is $|\Pi|^2$. First we note that for all policy $\pi \in \Pi$:

$$\max_{f \in \mathcal{F}} [\mathbb{E}_{s, a \sim d^\pi} f(s, a) - \mathbb{E}_{s, a \sim d^*} f(s, a)] = \max_{f: \|f\|_\infty \leq 1} [\mathbb{E}_{s, a \sim d^\pi} f(s, a) - \mathbb{E}_{s, a \sim d^*} f(s, a)] = \|d^\pi - d^{\pi^*}\|_1,$$

where the first equality comes from the fact that $\mathcal{F}$ includes $\arg \max_{f: \|f\|_\infty \leq 1} [\mathbb{E}_{s,a \sim d^\pi} f(s, a) - \mathbb{E}_{s,a \sim d^\star} f(s, a)]$.

Via Hoeffding's inequality and a union bound over $\mathcal{F}$, we get that with probability at least $1 - \delta$, for all $f \in \mathcal{F}$:

$$\left| \frac{1}{M} \sum_{i=1}^M f(s_i^\star, a_i^\star) - \mathbb{E}_{s,a \sim d^\star} f(s, a) \right| \leq 2\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}} := \epsilon_{stat}.$$

Denote $\hat{f} := \arg \max_{f \in \mathcal{F}} [\mathbb{E}_{s,a \sim d^{\hat{\pi}}} f(s, a) - \mathbb{E}_{s,a \sim d^\star} f(s, a)]$, and $\tilde{f} := \arg \max_{f \in \mathcal{F}} [\mathbb{E}_{s,a \sim d^{\hat{\pi}}} f(s, a) - \frac{1}{M} \sum_{i=1}^M f(s_i, a_i)]$. Hence, for $\hat{\pi}$, we have:

$$\begin{aligned} \|d^{\hat{\pi}} - d^\star\|_1 &= \mathbb{E}_{s,a \sim d^{\hat{\pi}}} \hat{f}(s, a) - \mathbb{E}_{s,a \sim d^\star} \hat{f}(s, a) \leq \mathbb{E}_{s,a \sim d^{\hat{\pi}}} \hat{f}(s, a) - \frac{1}{M} \sum_{i=1}^M \hat{f}(s_i^\star, a_i^\star) + \epsilon_{stat} \\ &\leq \mathbb{E}_{s,a \sim d^{\hat{\pi}}} \tilde{f}(s, a) - \frac{1}{M} \sum_{i=1}^M \tilde{f}(s_i, a_i) + \epsilon_{stat} \\ &\leq \mathbb{E}_{s,a \sim d^{\pi^\star}} \tilde{f}(s, a) - \frac{1}{M} \sum_{i=1}^M \tilde{f}(s_i, a_i) + \epsilon_{stat} \\ &\leq \mathbb{E}_{s,a \sim d^{\pi^\star}} \tilde{f}(s, a) - \mathbb{E}_{s,a \sim d^\star} \tilde{f}(s, a) + 2\epsilon_{stat} = 2\epsilon_{stat}, \end{aligned}$$

where in the third inequality we use the optimality of $\hat{\pi}$.

Recall that $V^\pi = \mathbb{E}_{s,a \sim d^\pi} r(s, a)/(1 - \gamma)$, we have:

$$V^{\hat{\pi}} - V^\star = \frac{1}{1 - \gamma} (\mathbb{E}_{s,a \sim d^{\hat{\pi}}} r(s, a) - \mathbb{E}_{s,a \sim d^\star} r(s, a)) \leq \frac{\sup_{s,a} |r(s, a)|}{1 - \gamma} \|d^{\hat{\pi}} - d^\star\|_1 \leq \frac{2}{1 - \gamma} \epsilon_{stat}.$$

This concludes the proof. $\square$

Note that above theorem confirms the statistical benefit of having the access to a known transition: comparing to the classic Behavior Cloning algorithm, the approximation error of DM-ST only scales linearly with respect to horizon $1/(1 - \gamma)$ instead of quadratically.

13.3.1 Extension to Agnostic Setting

So far we focused on agnostic learning setting. What would happen if $\pi^\star \notin \Pi$? We can still run our DM-ST algorithm as is. We state the sample complexity of DM-ST in agnostic setting below.

Theorem 13.5 (Agnostic Guarantee of DM-ST). *Assume Π is finite, but $\pi^\star \notin \Pi$. With probability at least $1 - \delta$, DM-ST learns a policy $\hat{\pi}$ such that:*

$$V^\star - V^{\hat{\pi}} \leq \frac{1}{1 - \gamma} \|d^\star - d^{\hat{\pi}}\|_1 \leq \frac{3}{1 - \gamma} \min_{\pi \in \Pi} \|d^\pi - d^\star\|_1 + \tilde{O} \left(\frac{1}{1 - \gamma} \sqrt{\frac{\ln(|\Pi| + \ln(1/\delta))}{M}} \right).$$

Proof. We first define some terms below. Denote $\tilde{\pi} := \arg \min_{\pi \in \Pi} \|d^\pi - d^\star\|_1$. Let us denote:

$$\begin{aligned} \tilde{f} &= \arg \max_{f \in \mathcal{F}} [\mathbb{E}_{s,a \sim d^{\tilde{\pi}}} f(s, a) - \mathbb{E}_{s,a \sim d^\star} f(s, a)], \\ \bar{f} &= \arg \max_{f \in \mathcal{F}} \left[\mathbb{E}_{s,a \sim d^{\tilde{\pi}}} f(s, a) - \frac{1}{M} \sum_{i=1}^M f(s_i^\star, a_i^\star) \right], \\ f' &= \arg \max_{f \in \mathcal{F}} \left[\mathbb{E}_{s,a \sim d^{\tilde{\pi}}} [f(s, a)] - \frac{1}{M} \sum_{i=1}^M f(s_i^\star, a_i^\star) \right]. \end{aligned}$$

Starting with a triangle inequality, we have:

$$\begin{aligned}
\|d^{\hat{\pi}} - d^{\pi^*}\|_1 &\leq \|d^{\hat{\pi}} - d^{\tilde{\pi}}\|_1 + \|d^{\tilde{\pi}} - d^{\pi^*}\|_1 \\
&= \mathbb{E}_{s,a \sim d^{\hat{\pi}}} [\tilde{f}(s,a)] - \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} [\tilde{f}(s,a)] + \|d^{\tilde{\pi}} - d^{\pi^*}\|_1 \\
&= \mathbb{E}_{s,a \sim d^{\hat{\pi}}} [\tilde{f}(s,a)] - \frac{1}{M} \sum_{i=1}^M \tilde{f}(s_i^*, a_i^*) + \frac{1}{M} \sum_{i=1}^M \tilde{f}(s_i^*, a_i^*) - \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} [\tilde{f}(s,a)] + \|d^{\tilde{\pi}} - d^{\pi^*}\|_1 \\
&\leq \mathbb{E}_{s,a \sim d^{\hat{\pi}}} [\tilde{f}(s,a)] - \frac{1}{M} \sum_{i=1}^M \tilde{f}(s_i^*, a_i^*) + \frac{1}{M} \sum_{i=1}^M \tilde{f}(s_i^*, a_i^*) - \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} [\tilde{f}(s,a)] + \|d^{\tilde{\pi}} - d^{\pi^*}\|_1 \\
&\quad + \left[\mathbb{E}_{s,a \sim d^{\tilde{\pi}}} \tilde{f}(s,a) - \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} [\tilde{f}(s,a)] \right] + \|d^{\tilde{\pi}} - d^{\pi^*}\|_1 \\
&\leq \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} [f'(s,a)] - \frac{1}{M} \sum_{i=1}^M f'(s_i^*, a_i^*) + 2\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}} + 2\|d^{\tilde{\pi}} - d^{\pi^*}\|_1 \\
&\leq \mathbb{E}_{s,a \sim d^{\tilde{\pi}}} [f'(s,a)] - \mathbb{E}_{s,a \sim d^{\pi^*}} [f'(s,a)] + 4\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}} + 2\|d^{\tilde{\pi}} - d^{\pi^*}\|_1 \\
&\leq 3\|d^{\pi^*} - d^{\tilde{\pi}}\|_1 + 4\sqrt{\frac{\ln(|\mathcal{F}|/\delta)}{M}},
\end{aligned}$$

where the first inequality uses the definition of $\tilde{f}$, the second inequality uses the fact that $\hat{\pi}$ is the minimizer of $\max_{f \in \mathcal{F}} \mathbb{E}_{s,a \sim d^{\hat{\pi}}} f(s,a) - \frac{1}{M} \sum_{i=1}^M f(s_i^*, a_i^*)$, along the way we also use Hoeffding's inequality where $\forall f \in \mathcal{F}$, $|\mathbb{E}_{s,a \sim d^{\tilde{\pi}}} f(s,a) - \frac{1}{M} \sum_{i=1}^M f(s_i^*, a_i^*)| \leq 2\sqrt{\ln(|\mathcal{F}|/\delta)/M}$, with probability at least $1 - \delta$. $\square$

As we can see, comparing to the realizable setting, here we have an extra term that is related to $\min_{\pi \in \Pi} \|d^{\pi} - d^{\pi^*}\|_1$. Note that the dependency on horizon also scales linearly in this case. In general, the constant 3 in front of $\min_{\pi \in \Pi} \|d^{\pi} - d^{\pi^*}\|_1$ is not avoidable in Scheffé estimator Devroye and Lugosi [2012].

13.4 Maximum Entropy Inverse Reinforcement Learning

Similar to Behavior cloning, we assume we have a dataset of state-action pairs from expert $\mathcal{D}^* = \{s_i^*, a_i^*\}_{i=1}^N$ where $s_i^*, a_i^* \sim d^{\pi^*}$. Different from Behavior cloning, here we assume that we have access to the underlying MDP's transition, i.e., we assume transition is known and we can do planning if we were given a cost function.

We assume that we are given a state-action feature mapping $\phi : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^d$ (this can be extended infinite dimensional feature space in RKHS, but we present finite dimensional setting for simplicity). We assume the true ground truth cost function as $c(s,a) := \theta^* \cdot \phi(s,a)$ with $\|\theta^*\|_2 \leq 1$ and θ^* being unknown.

The goal of the learner is to compute a policy $\pi : \mathcal{S} \mapsto \Delta(\mathcal{A})$ such that when measured under the true cost function, it performs as good as the expert, i.e., $\mathbb{E}_{s,a \sim d^{\pi}} \theta^* \cdot \phi(s,a) \approx \mathbb{E}_{s,a \sim d^{\pi^*}} \theta^* \cdot \phi(s,a)$.

We will focus on finite horizon MDP setting in this section. We denote $\rho^{\pi}(\tau)$ as the trajectory distribution induced by π and d^{π} as the average state-action distribution induced by π .

13.4.1 MaxEnt IRL: Formulation and The Principle of Maximum Entropy

MaxEnt IRL uses the principle of Maximum Entropy and poses the following policy optimization program:

$$\begin{aligned} \max_{\pi} & - \sum_{\tau} \rho^{\pi}(\tau) \ln \rho^{\pi}(\tau), \\ \text{s.t.}, & \mathbb{E}_{s,a \sim d^{\pi}} \phi(s, a) = \sum_{i=1}^N \phi(s_i^*, a_i^*)/N. \end{aligned}$$

Note that $\sum_{i=1}^N \phi(s_i^*, a_i^*)/N$ is an unbiased estimate of $\mathbb{E}_{s,a \sim d^{\pi^*}} \phi(s, a)$. MaxEnt-IRL searches for a policy that maximizes the entropy of its trajectory distribution subject to a moment matching constraint.

Note that there could be many policies that satisfy the moment matching constraint, i.e., $\mathbb{E}_{s,a \sim d^{\pi}} \phi(s, a) = \mathbb{E}_{s,a \sim d^{\pi^*}} \phi(s, a)$, and any feasible solution is guaranteed to achieve the same performance of the expert under the ground truth cost function $\theta^* \cdot \phi(s, a)$. The maximum entropy objective ensures that the solution is unique.

Using the Markov property, we notice that:

$$\operatorname{argmax}_{\pi} - \sum_{\tau} \rho^{\pi}(\tau) \ln \rho^{\pi}(\tau) = \operatorname{argmax}_{\pi} - \mathbb{E}_{s,a \sim d^{\pi}} \ln \pi(a|s).$$

This, we can rewrite the MaxEnt-IRL as follows:

$$\min_{\pi} \mathbb{E}_{s,a \sim d^{\pi}} \ln \pi(a|s), \tag{13.2}$$

$$\text{s.t.}, \mathbb{E}_{s,a \sim d^{\pi}} \phi(s, a) = \sum_{i=1}^N \phi(s_i^*, a_i^*)/N. \tag{13.3}$$

13.4.2 Algorithm

To better interpret the objective function, below we replace $\sum_i \phi(s_i^*, a_i^*)/N$ by its expectation $\mathbb{E}_{s,a \sim d^{\pi^*}} \phi(s, a)$. Note that we can use standard concentration inequalities to bound the difference between $\sum_i \phi(s_i^*, a_i^*)/N$ and $\mathbb{E}_{s,a \sim d^{\pi^*}} \phi(s, a)$.

Using Lagrange multipliers, we can rewrite the constrained optimization program in Eq. 13.2 as follows:

$$\min_{\pi} \mathbb{E}_{s,a \sim d^{\pi}} \ln \pi(a|s) + \max_{\theta} \mathbb{E}_{s,a \sim d^{\pi}} \theta^{\top} \phi(s, a) - \mathbb{E}_{s,a \sim d^{\pi^*}} \theta^{\top} \phi(s, a).$$

The above objective conveys a clear goal of our imitation learning problem: we are searching for π that minimizes the MMD between d^{π} and d^{π^*} with a (negative) entropy regularization on the trajectory distribution of policy π .

To derive an algorithm that optimizes the above objective, we first again swap the min max order via the minimax theorem:

$$\max_{\theta} \left(\min_{\pi} \mathbb{E}_{s,a \sim d^{\pi}} \theta^{\top} \phi(s, a) - \mathbb{E}_{s,a \sim d^{\pi^*}} \theta^{\top} \phi(s, a) + \mathbb{E}_{s,a \sim d^{\pi}} \ln \pi(a|s) \right).$$

The above objective proposes a natural algorithm where we perform projected gradient ascent on θ , while perform best response update on π , i.e., given θ , we solve the following planning problem:

$$\operatorname{argmin}_{\pi} \mathbb{E}_{s,a \sim d^{\pi}} \theta^{\top} \phi(s, a) + \mathbb{E}_{s,a \sim d^{\pi}} \ln \pi(a|s). \tag{13.4}$$

Note that the above objective can be understood as planning with cost function $\theta^\top \phi(s, a)$ with an additional negative entropy regularization on the trajectory distribution. On the other hand, given π , we can compute the gradient of θ , which is simply the difference between the expected features:

$$\mathbb{E}_{s,a \sim d^\pi} \phi(s, a) - \mathbb{E}_{s,a \sim d^{\pi^*}} \phi(s, a),$$

which gives the following gradient ascent update on θ :

$$\theta := \theta + \eta \left(\mathbb{E}_{s,a \sim d^\pi} \phi(s, a) - \mathbb{E}_{s,a \sim d^{\pi^*}} \phi(s, a) \right). \quad (13.5)$$

Algorithm of MaxEnt-IRL MaxEnt-IRL updates π and θ alternatively using Eq. 13.4 and Eq. 13.5, respectively. We summarize the algorithm in Alg. 9. Note that for the stochastic gradient of θ_t , we see that it is the empirical average feature difference between the current policy π_t and the expert policy π^* .

Algorithm 9 MaxEnt-IRL

Input: Expert data $\mathcal{D}^* = \{s_i^*, a_i^*\}_{i=1}^M$, MDP $\mathcal{M}$, parameters β, η, N .

- 1: Initialize θ_0 with $\|\theta_0\|_2 \leq 1$.
 - 2: **for** $t = 1, 2, \dots$, **do**
 - 3: Entropy-regularized Planning with cost $\theta_t^\top \phi(s, a)$: $\pi_t \in \operatorname{argmin}_\pi \mathbb{E}_{s,a \sim d^\pi} [\theta_t^\top \phi(s, a) + \beta \ln \pi(a|s)]$.
 - 4: Draw samples $\{s_i, a_i\}_{i=1}^N \sim d^{\pi_t}$ by executing π_t in $\mathcal{M}$.
 - 5: Stochastic Gradient Update: $\theta' = \theta_t + \eta \left[\frac{1}{N} \sum_{i=1}^N \phi(s_i, a_i) - \frac{1}{M} \sum_{i=1}^M \phi(s_i^*, a_i^*) \right]$.
 - 6: **end for**
-

Note that Alg. 9 uses an entropy-regularized planning oracle. Below we discuss how to implement such entropy-regularized planning oracle via dynamic programming.

13.4.3 Maximum Entropy RL: Implementing the Planning Oracle in Eq. 13.4

The planning oracle in Eq. 13.4 can be implemented in a value iteration fashion using Dynamic Programming. We denote $c(s, a) := \theta \cdot \phi(s, a)$.

We are interested in implementing the following planning objective:

$$\operatorname{argmin}_\pi \mathbb{E}_{s,a \sim d^\pi} [c(s, a) + \ln \pi(a|s)]$$

The subsection has its own independent interests beyond the framework of imitation learning. This maximum entropy regularized planning formulation is widely used in RL as well and it is well connected to the framework of RL as Inference.

As usually, we start from the last time step $H - 1$. For any policy π and any state-action (s, a) , we have the cost-to-go $Q_{H-1}^\pi(s, a)$:

$$Q_{H-1}^\pi(s, a) = c(s, a) + \ln \pi(a|s), \quad V_{H-1}^\pi(s) = \sum_a \pi(a|s) (c(s, a) + \ln \pi(a|s)).$$

We have:

$$V_{H-1}^*(s) = \min_{\rho \in \Delta(\mathcal{A})} \sum_a \rho(a) c(s, a) + \rho(a) \ln \rho(a). \quad (13.6)$$

Take gradient with respect to ρ , set it to zero and solve for ρ , we get:

$$\pi_{H-1}^*(a|s) \propto \exp(-c(s, a)), \forall s, a.$$

Substitute π_{H-1}^* back to the expression in Eq. 13.6, we get:

$$V_{H-1}^*(s) = -\ln \left(\sum_a \exp(-c(s, a)) \right),$$

i.e., we apply a softmin operator rather than the usual min operator (recall here we are minimizing cost).

With V_{h+1}^* , we can continue to h . Denote $Q^*(s, a)$ as follows:

$$Q_h^*(s, a) = r(s, a) + \mathbb{E}_{s' \sim P(\cdot|s, a)} V_{h+1}^*(s').$$

For V_h^* , we have:

$$V_h^*(s) = \min_{\rho \in \Delta(\mathcal{A})} \sum_a \rho(a) (c(s, a) + \ln \rho(a) + \mathbb{E}_{s' \sim P(\cdot|s, a)} V_{h+1}^*(s')).$$

Again we can show that the minimizer of the above program has the following form:

$$\pi_h^*(a|s) \propto \exp(-Q_h^*(s, a)). \quad (13.7)$$

Substitute π_h^* back to Q_h^* , we can show that:

$$V_h^*(s) = -\ln \left(\sum_a \exp(-Q_h^*(s, a)) \right),$$

where we see again that V_h^* is based on a softmin operator on Q^* .

Thus the *soft value iteration* can be summarized below:

Soft Value Iteration:

$$Q_{H-1}^*(s, a) = c(s, a), \quad \pi_{H-1}^*(a|s) \propto \exp(-Q_{H-1}^*(s, a)), \quad V_{H-1}^*(s) = -\ln \left(\sum_a \exp(-Q_{H-1}^*(s, a)) \right), \forall s.$$

We can continue the above procedure to $h = 0$, which gives us the optimal policies, all in the form of Eq. 13.7

13.5 Interactive Imitation Learning: AggreVaTe and Its Statistical Benefit over Offline IL Setting

We study the Interactive Imitation Learning setting where we have an expert policy that can be queried at any time during training, and we also have access to the ground truth reward signal.

We present AggreVaTe (Aggregate Values to Imitate) first and then analyze its sample complexity under the realizable setting.

Again we start with a realizable policy class Π that is discrete. We denote $\Delta(\Pi)$ as the convex hull of Π and each policy $\pi \in \Delta(\Pi)$ is a mixture policy represented by a distribution $\rho \in \mathbb{R}^{|\Pi|}$ with $\rho[i] \geq 0$ and $\|\rho\|_1 = 1$. With

this parameterization, our decision space simply becomes $\Delta(|\Pi|)$, i.e., any point in $\Delta(|\Pi|)$ corresponds to a mixture policy. Notation wise, given $\rho \in \Delta(|\Pi|)$, we denote π_ρ as the corresponding mixture policy. We denote π_i as the i -th policy in Π . We denote $\rho[i]$ as the i -th element of the vector ρ .

AggreVaTe assumes an interactive expert from whom I can query for action feedback. Basically, given a state s , let us assume that expert returns us the advantages of all actions, i.e., *one query of expert oracle at any state s returns $A^*(s, a), \forall a \in \mathcal{A}$.*¹

Algorithm 10 AggreVaTe

Input: The interactive expert, regularization λ

- 1: Initialize ρ_0 to be a uniform distribution.
 - 2: **for** $t = 0, 2, \dots$, **do**
 - 3: Sample $s_t \sim d^{\pi_{\rho_t}}$
 - 4: Query expert to get $A^*(s_t, a)$ for all $a \in \mathcal{A}$
 - 5: Policy update: $\rho_{t+1} = \operatorname{argmax}_{\rho \in \Delta(|\Pi|)} \sum_{j=0}^t \sum_{i=1}^{|\Pi|} \rho[i] (\mathbb{E}_{a \sim \pi_i(\cdot|s_t)} A^*(s_t, a)) - \lambda \sum_{i=1}^{|\Pi|} \rho[i] \ln(\rho[i])$
 - 6: **end for**
-

The algorithm is summarized in Alg. 10.

To analyze the algorithm, let us introduce some additional notations. Let us denote $\ell_t(\rho) = \sum_{i=1}^{|\Pi|} \rho[i] \mathbb{E}_{a \sim \pi_i(\cdot|s_t)} A^*(s_t, a)$, which is dependent on state s_t generated at iteration t , and is a linear function with respect to decision variable ρ . AggreVaTe is essentially running the specific online learning algorithm, Follow-the-Regularized Leader (FTRL) (e.g., see Shalev-Shwartz [2011]) with Entropy regularization:

$$\rho_{t+1} = \operatorname{argmax}_{\rho \in \Delta(|\Pi|)} \sum_{i=0}^t \ell_t(\rho) + \lambda \operatorname{Entropy}(\rho).$$

Denote $c = \max_{s,a} A^*(s, a)$. This implies that $\sup_{\rho,t} \|\ell_t(\rho)\| \leq c$. FTRL with linear loss functions and entropy regularization gives the following deterministic regret guarantees (Shalev-Shwartz [2011]):

$$\max_{\rho} \sum_{t=0}^{T-1} \ell_t(\rho) - \sum_{t=0}^{T-1} \ell_t(\rho_t) \leq c \sqrt{\log(|\Pi|)T}. \quad (13.8)$$

We will analyze AggreVaTe's sample complexity using the above result.

Theorem 13.6 (Sample Complexity of AggreVaTe). *Denote $c = \sup_{s,a} |A^*(s, a)|$. Let us denote ϵ_Π and ϵ_{stat} as follows:*

$$\epsilon_\Pi := \max_{\rho \in \Delta(|\Pi|)} \frac{1}{M} \sum_{t=0}^{M-1} \ell_t(\rho^*), \quad \epsilon_{stat} := \sqrt{\frac{\ln(|\Pi|)/\delta}{M}} + 2\sqrt{\frac{\ln(1/\delta)}{M}}.$$

With probability at least $1 - \delta$, after M iterations (i.e., M calls of expert oracle), AggreVaTe finds a policy $\hat{\pi}$ such that:

$$V^* - V^{\hat{\pi}} \leq \frac{c}{1 - \gamma} \epsilon_{stat} - \frac{1}{1 - \gamma} \epsilon_\Pi.$$

Proof. At each iteration t , let us define $\tilde{\ell}_t(\rho_t)$ as follows:

$$\tilde{\ell}_t(\rho_t) = \mathbb{E}_{s \sim d^{\pi_{\rho_t}}} \sum_{i=1}^{|\Pi|} \rho_t[i] \mathbb{E}_{a \sim \pi_i(\cdot|s)} A^*(s, a)$$

¹Technically one cannot use one query to get $A^*(s, a)$ for all a . But one can use importance weighting to get an unbiased estimate of $A^*(s, a)$ for all a via just one expert roll-out. For analysis simplicity, we assume one expert query at s returns the whole vector $A^*(s, \cdot) \in \mathbb{R}^{|\mathcal{A}|}$.

Denote $\mathbb{E}_t[\ell_t(\rho_t)]$ as the conditional expectation of $\ell_t(\rho_t)$, conditioned on all history up and including the end of iteration $t - 1$. Thus, we have $\mathbb{E}_t[\ell_t](\rho_t) = \tilde{\ell}_t(\rho_t)$ as ρ_t only depends on the history up to the end of iteration $t - 1$. Also note that $|\ell_t(\rho)| \leq c$. Thus by Azuma-Hoeffding inequality (Theorem A.5), we get:

$$\left| \frac{1}{M} \sum_{t=0}^{M-1} \tilde{\ell}_t(\rho_t) - \frac{1}{T} \sum_{t=0}^{M-1} \ell_t(\rho_t) \right| \leq 2c\sqrt{\frac{\ln(1/\delta)}{M}},$$

with probability at least $1 - \delta$. Now use Eq. 13.8, and denote $\rho^* = \operatorname{argmin}_{\rho \in \Delta(\Pi)} \frac{1}{M} \sum_{t=0}^{M-1} \ell_t(\rho)$, i.e., the best minimizer that minimizes the average loss $\sum_{t=0}^{M-1} \ell_t(\rho)/M$. we get:

$$\frac{1}{M} \sum_{t=0}^{M-1} \tilde{\ell}_t(\rho_t) \geq \frac{1}{M} \sum_{t=0}^{M-1} \ell_t(\rho_t) - 2c\sqrt{\frac{\ln(1/\delta)}{M}} \geq \frac{1}{M} \sum_{t=0}^{M-1} \ell_t(\rho^*) - c\sqrt{\frac{\ln(|\Pi|)}{M}} - 2c\sqrt{\frac{\ln(1/\delta)}{M}},$$

which means that there must exist a $\hat{t} \in \{0, \dots, M-1\}$, such that:

$$\tilde{\ell}_{\hat{t}}(\rho_{\hat{t}}) \geq \frac{1}{M} \sum_{t=0}^{M-1} \ell_t(\rho^*) - c\sqrt{\frac{\ln(|\Pi|)}{M}} - 2c\sqrt{\frac{\ln(1/\delta)}{M}}.$$

Now use Performance difference lemma, we have:

$$\begin{aligned} (1 - \gamma)(-V^* + V^{\pi_{\rho_{\hat{t}}}}) &= \mathbb{E}_{s \sim d^{\pi_{\rho_{\hat{t}}}}} \sum_{i=1}^{|\Pi|} \rho_{\hat{t}}[i] \mathbb{E}_{a \sim \pi_i(\cdot|s)} A^*(s, a) = \ell_{\hat{t}}(\rho_{\hat{t}}) \\ &\geq \frac{1}{M} \sum_{t=0}^{M-1} \ell_t(\rho^*) - c\sqrt{\frac{\ln(|\Pi|)}{T}} - 2c\sqrt{\frac{\ln(1/\delta)}{T}}. \end{aligned}$$

Rearrange terms, we get:

$$V^* - V^{\pi_{\rho_{\hat{t}}}} \leq -\frac{1}{1 - \gamma} \left[\frac{1}{M} \sum_{t=0}^{M-1} \ell_t(\rho^*) \right] + \frac{c}{1 - \gamma} \left[\sqrt{\frac{\ln(|\Pi|)/\delta}{M}} + 2\sqrt{\frac{\ln(1/\delta)}{M}} \right],$$

which concludes the proof. $\square$

Remark We analyze the ϵ_{Π} by discussing realizable setting and non-realizable setting separately. When Π is realizable, i.e., $\pi^* \in \Pi$, by the definition of our loss function ℓ_t , we immediately have $\sum_{i=1}^M \ell_t(\rho^*) \geq 0$ since $A^*(s, \pi^*(s)) = 0$ for all $s \in \mathcal{S}$. Moreover, when π^* is not the globally optimal policy, it is possible that $\epsilon_{\Pi} := \sum_{i=1}^M \ell_t(\rho^*)/M > 0$, which implies that when $M \rightarrow \infty$ (i.e., $\epsilon_{stat} \rightarrow 0$), AggreVaTe indeed can learn a policy that outperforms the expert policy π^* . In general when $\pi^* \notin \Pi$, there might not exist a mixture policy ρ that achieves positive advantage against π^* under the M training samples $\{s_0, \dots, s_{M-1}\}$. In this case, $\epsilon_{\Pi} < 0$.

Does AggreVaTe avoids distribution shift? Under realizable setting, note that the bound explicitly depends on $\sup_{s,a} |A^*(s, a)|$ (i.e., it depends on $|\ell_t(\rho_t)|$ for all t). In worst case, it is possible that $\sup_{s,a} |A^*(s, a)| = \Theta(1/(1 - \gamma))$, which implies that AggreVaTe could suffer a quadratic horizon dependency, i.e., $1/(1 - \gamma)^2$. Note that DM-ST provably scales linearly with respect to $1/(1 - \gamma)$, but DM-ST requires a stronger assumption that the transition P is known.

When $\sup_{s,a} |A^*(s, a)| = o(1/(1 - \gamma))$, then AggreVaTe performs strictly better than BC. This is possible when the MDP is mixing quickly under π^* , or Q^* is L -Lipschitz continuous, i.e., $|Q^*(s, a) - Q^*(s, a')| \leq L\|a - a'\|$, with bounded range in action space, e.g., $\sup_{a,a'} \|a - a'\| \leq \beta \in \mathbb{R}^+$. In this case, if L and β are independent of $1/(1 - \gamma)$, then $\sup_{s,a} |A^*(s, a)| \leq L\beta$, which leads to a $\frac{\beta L}{1 - \gamma}$ dependency.

When $\pi^* \notin \Pi$, the agnostic result of AggreVaTe and the agnostic result of DM-ST is not directly comparable. Note that the model class error that DM-ST suffers is algorithmic-independent, i.e., it is $\min_{\pi \in \Pi} \|d^\pi - d^{\pi^*}\|_1$ and it only depends on π^* and Π , while the model class ϵ_Π in AggreVaTe is algorithmic path-dependent, i.e., in addition to π^* and Π , it depends the policies $\pi_1, \pi_2, \dots$ computed during the learning process. Another difference is that $\min_{\pi \in \Pi} \|d^\pi - d^{\pi^*}\|_1 \in [0, 2]$, while ϵ_Π indeed could scale linearly with respect to $1/(1 - \gamma)$, i.e., $\epsilon_\pi \in [-\frac{1}{1-\gamma}, 0]$ (assume π^* is the globally optimal policy for simplicity).

13.6 Bibliographic Remarks and Further Readings

Behavior cloning was used in autonomous driving back in 1989 Pomerleau [1989], and the distribution shift and compounding error issue was studied by Ross and Bagnell [2010]. Ross and Bagnell [2010], Ross et al. [2011] proposed using interactive experts to alleviate the distribution shift issue.

MaxEnt-IRL was proposed by Ziebart et al. [2008]. The original MaxEnt-IRL focuses on deterministic MDPs and derived distribution over trajectories. Later Ziebart et al. [2010] proposed the Principle of Maximum Causal Entropy framework which captures MDPs with stochastic transition. MaxEnt-IRL has been widely used in real applications (e.g., Kitani et al. [2012], Ziebart et al. [2009]).

To the best of our knowledge, the algorithm Distribution Matching with Scheffé Tournament introduced in this chapter is new here and is the first to demonstrate the statistical benefit (in terms of sample complexity of the expert policy) of the hybrid setting over the pure offline setting with general function approximation.

Recently, there are approaches that extend the linear cost functions used in MaxEnt-IRL to deep neural networks which are treated as discriminators to distinguish between experts datasets and the datasets generated by the policies. Different distribution divergences have been proposed, for instance, JS-divergence Ho and Ermon [2016], general f-divergence which generalizes JS-divergence Ke et al. [2019], and Integral Probability Metric (IPM) which includes Wasserstein distance Sun et al. [2019b]. While these adversarial IL approaches are promising as they fall into the hybrid setting, it has been observed that empirically, adversarial IL sometimes cannot outperform simple algorithms such as Behavior cloning which operates in pure offline setting (e.g., see experiments results on common RL benchmarks from Brantley et al. [2019]).

Another important direction in IL is to combine expert demonstrations and reward functions together (i.e., perform Imitation together with RL). There are many works in this direction, including learning with pre-collected expert data Hester et al. [2017], Rajeswaran et al. [2017], Cheng et al. [2018], Le et al. [2018], Sun et al. [2018], learning with an interactive expert Daumé et al. [2009], Ross and Bagnell [2014], Chang et al. [2015], Sun et al. [2017], Cheng et al. [2020], Cheng and Boots [2018]. The algorithm AggreVaTe was originally introduced in Ross and Bagnell [2014]. A policy gradient and natural policy gradient version of AggreVaTe are introduced in Sun et al. [2017]. The precursor of AggreVaTe is the algorithm Data Aggregation (DAgger) Ross et al. [2011], which leverages interactive experts and a reduction to no-regret online learning, but without assuming access to the ground truth reward signals.

The maximum entropy RL formulation has been widely used in RL literature as well. For instance, Guided Policy Search (GPS) (and its variants) use maximum entropy RL formulation as its planning subroutine Levine and Koltun [2013], Levine and Abbeel [2014]. We refer readers to the excellent survey from Levine [2018] for more details of Maximum Entropy RL formulation and its connections to the framework of RL as Probabilistic Inference.

Chapter 14

Linear Quadratic Regulators

This chapter will introduce some of the fundamentals of optimal control for the linear quadratic regulator model. This model is an MDP, with continuous states and actions. While the model itself is often inadequate as a global model, it can be quite effective as a locally linear model (provided our system does not deviate away from the regime where our linear model is reasonable approximation).

The basics of optimal control theory can be found in any number of standards text Anderson and Moore [1990], Evans [2005], Bertsekas [2017]. The treatment of Gauss-Newton and the NPG algorithm are due to Fazel et al. [2018].

14.1 The LQR Model

In the standard optimal control problem, a dynamical system is described as

$$x_{t+1} = f_t(x_t, u_t, w_t),$$

where f_t maps a state $x_t \in \mathbb{R}^d$, a control (the action) $u_t \in \mathbb{R}^k$, and a disturbance w_t , to the next state $x_{t+1} \in \mathbb{R}^d$, starting from an initial state x_0 . The objective is to find the control policy π which minimizes the long term cost,

$$\begin{aligned} \text{minimize} \quad & \mathbb{E}_\pi \left[\sum_{t=0}^H c_t(x_t, u_t) \right] \\ \text{such that} \quad & x_{t+1} = f_t(x_t, u_t, w_t) \quad t = 0, \dots, H. \end{aligned}$$

where H is the time horizon (which can be finite or infinite).

In practice, this is often solved by considering the linearized control (sub-)problem where the dynamics are approximated by

$$x_{t+1} = A_t x_t + B_t u_t + w_t,$$

with the matrices A_t and B_t are derivatives of the dynamics f and where the costs are approximated by a quadratic function in x_t and u_t .

This chapter focuses on an important special case: finite and infinite horizon problem referred to as the linear quadratic regulator (LQR) problem. We can view this model as being an local approximation to non-linear model. However, we will analyze these models under the assumption that they are globally valid.

Finite Horizon LQRs. The finite horizon LQR problem is given by

$$\begin{aligned} \text{minimize} \quad & \mathbb{E} \left[x_H^\top Q x_H + \sum_{t=0}^{H-1} (x_t^\top Q x_t + u_t^\top R u_t) \right] \\ \text{such that} \quad & x_{t+1} = A_t x_t + B_t u_t + w_t, \quad x_0 \sim \mathcal{D}, \quad w_t \sim N(0, \sigma^2 I), \end{aligned}$$

where initial state $x_0 \sim \mathcal{D}$ is assumed to be randomly distributed according to distribution $\mathcal{D}$; the disturbance $w_t \in \mathbb{R}^d$ follows the law of a multi-variate normal with covariance $\sigma^2 I$; the matrices $A_t \in \mathbb{R}^{d \times d}$ and $B_t \in \mathbb{R}^{d \times k}$ are referred to as system (or transition) matrices; $Q \in \mathbb{R}^{d \times d}$ and $R \in \mathbb{R}^{k \times k}$ are both positive definite matrices that parameterize the quadratic costs. Note that this model is a finite horizon MDP, where the $\mathcal{S} = \mathbb{R}^d$ and $\mathcal{A} = \mathbb{R}^k$.

Infinite Horizon LQRs. We also consider the infinite horizon LQR problem:

$$\begin{aligned} \text{minimize} \quad & \lim_{H \rightarrow \infty} \frac{1}{H} \mathbb{E} \left[\sum_{t=0}^H (x_t^\top Q x_t + u_t^\top R u_t) \right] \\ \text{such that} \quad & x_{t+1} = A x_t + B u_t + w_t, \quad x_0 \sim \mathcal{D}, \quad w_t \sim N(0, \sigma^2 I). \end{aligned}$$

Note that here we are assuming the dynamics are time homogenous. We will assume that the optimal objective function (i.e. the optimal average cost) is finite; this is referred to as the system being *controllable*. This is a special case of an MDP with an average reward objective.

Throughout this chapter, we assume A and B are such that the optimal cost is finite. Due to the geometric nature of the system dynamics (say for a controller which takes controls u_t that are linear in the state x_t), there may exist linear controllers with infinite costs. This instability of LQRs (at least for some A and B and some controllers) leads to that the theoretical analysis often makes various assumptions on A and B in order to guarantee some notion of stability. In practice, the finite horizon setting is more commonly used in practice, particularly due to that the LQR model is only a good local approximation of the system dynamics, where the infinite horizon model tends to be largely of theoretical interest. See Section 14.6.

The infinite horizon discounted case? The infinite horizon discounted case tends not to be studied for LQRs. This is largely due to that, for the undiscounted case (with the average cost objective), we have may infinite costs (due to the aforementioned geometric nature of the system dynamics); in such cases, discounting will not necessarily make the average cost finite.

14.2 Bellman Optimality: Value Iteration & The Algebraic Riccati Equations

A standard result in optimal control theory shows that the optimal control input can be written as a linear function in the state. As we shall see, this is a consequence of the Bellman equations.

14.2.1 Planning and Finite Horizon LQRs

Slightly abusing notation, it is convenient to define the value function and state-action value function with respect to the costs as follows: For a policy π , a state x , and $h \in \{0, \dots, H-1\}$, we define the value function $V_h^\pi : \mathbb{R}^d \rightarrow \mathbb{R}$ as

$$V_h^\pi(x) = \mathbb{E} \left[x_H^\top Q x_H + \sum_{t=h}^{H-1} (x_t^\top Q x_t + u_t^\top R u_t) \mid \pi, x_h = x \right],$$

where again expectation is with respect to the randomness of the trajectory, that is, the randomness in state transitions. Similarly, the state-action value (or Q-value) function $Q_h^\pi : \mathbb{R}^d \times \mathbb{R}^k \rightarrow \mathbb{R}$ is defined as

$$Q_h^\pi(x, u) = \mathbb{E} \left[x_H^\top Q x_H + \sum_{t=h}^{H-1} (x_t^\top Q x_t + u_t^\top R u_t) \mid \pi, x_h = x, u_h = u \right].$$

We define V^* and Q^* analogously.

The following theorem provides a characterization of the optimal policy, via the algebraic Riccati equations. These equations are simply the value iteration algorithm for the special case of LQRs.

Theorem 14.1. (*Value Iteration and the Riccati Equations*). *Suppose R is positive definite. The optimal policy is a linear controller specified by:*

$$\pi^*(x_t) = -K_t^* x_t$$

where

$$K_t^* = (B_t^\top P_{t+1} B_t + R)^{-1} B_t^\top P_{t+1} A_t.$$

Here, P_t can be computed iteratively, in a backwards manner, using the following algebraic Riccati equations, where for $t \in [H]$,

$$\begin{aligned} P_t &:= A_t^\top P_{t+1} A_t + Q - A_t^\top P_{t+1} B_t (B_t^\top P_{t+1} B_t + R)^{-1} B_t^\top P_{t+1} A_t \\ &= A_t^\top P_{t+1} A_t + Q - (K_{t+1}^*)^\top (B_t^\top P_{t+1} B_t + R) K_{t+1}^* \end{aligned}$$

and where $P_H = Q$. (The above equation is simply the value iteration algorithm).

Furthermore, for $t \in [H]$, we have that:

$$V_t^*(x) = x^\top P_t x + \sigma^2 \sum_{h=t+1}^H \text{Trace}(P_h).$$

We often refer to K_t^* as the *optimal control gain matrices*. It is straightforward to generalize the above when $\sigma \geq 0$.

We have assumed that R is strictly positive definite, to avoid have to working with the pseudo-inverse; the theorem is still true when $R = 0$, provided we use a pseudo-inverse.

Proof. By the Bellman optimality conditions (Theorem ?? for episodic MDPs), we know the optimal policy (among all possibly history dependent, non-stationary, and randomized policies), is given by a deterministic stationary policy which is only a function of x_t and t . We have that:

$$\begin{aligned} Q_{H-1}(x, u) &= \mathbb{E}[(A_{H-1}x + B_{H-1}u + w_{H-1})^\top Q(A_{H-1}x + B_{H-1}u + w_{H-1})] + x^\top Q x + u^\top R u \\ &= (A_{H-1}x + B_{H-1}u)^\top Q(A_{H-1}x + B_{H-1}u) + \sigma^2 \text{Trace}(Q) + x^\top Q x + u^\top R u \end{aligned}$$

due to that $x_H = A_{H-1}x + B_{H-1}u + w_{H-1}$, and $\mathbb{E}[w_{H-1}^\top Q w_{H-1}] = \text{Trace}(\sigma^2 Q)$. Due to that this is a quadratic function of u , we can immediately derive that the optimal control is given by:

$$\pi_{H-1}^*(x) = -(B_{H-1}^\top Q B_{H-1} + R)^{-1} B_{H-1}^\top Q A_{H-1} x = -K_{H-1}^* x,$$

where the last step uses that $P_H := Q$.

For notational convenience, let $K = K_{H-1}^*$, $A = A_{H-1}$, and $B = B_{H-1}$. Using the optimal control at x , i.e. $u = -K_{H-1}^*x$, we have:

$$\begin{aligned}
V_{H-1}^*(x) &= Q_{H-1}(x, -K_{H-1}^*x) \\
&= x^\top \left((A - BK)^\top Q (A - BK) + Q + K^\top R K \right) x + \sigma^2 \text{Trace}(Q) \\
&= x^\top \left(AQA + Q - 2K^\top B^\top QA + K^\top (B^\top QB + R)K \right) x + \sigma^2 \text{Trace}(Q) \\
&= x^\top \left(AQA + Q - 2K^\top (B^\top QB + R)K + K^\top (B^\top QB + R)K \right) x + \sigma^2 \text{Trace}(Q) \\
&= x^\top \left(AQA + Q - K^\top (B^\top QB + R)K \right) x + \sigma^2 \text{Trace}(Q) \\
&= x^\top P_{H-1}x + \sigma^2 \text{Trace}(Q).
\end{aligned}$$

where the fourth step uses our expression for $K = K_{H-1}^*$. This proves our claim for $t = H - 1$.

This implies that:

$$\begin{aligned}
Q_{H-2}^*(x, u) &= \mathbb{E}[V_{H-1}^*(A_{H-2}x + B_{H-2}u + w_{H-2})] + x^\top Qx + u^\top Ru \\
&= (A_{H-2}x + B_{H-2}u)^\top P_{H-1} (A_{H-2}x + B_{H-2}u) + \sigma^2 \text{Trace}(P_{H-1}) + \sigma^2 \text{Trace}(Q) + x^\top Qx + u^\top Ru.
\end{aligned}$$

The remainder of the proof follows from a recursive argument, which can be verified along identical lines to the $t = H - 1$ case. $\square$

14.2.2 Planning and Infinite Horizon LQRs

Theorem 14.2. *Suppose that the optimal cost is finite and that R is positive definite. Let P be a solution to the following algebraic Riccati equation:*

$$P = A^\top P A + Q - A^\top P B (B^\top P B + R)^{-1} B^\top P A. \quad (14.1)$$

(Note that P is a positive definite matrix). We have that the optimal policy is:

$$\pi^*(x) = -K^*x$$

where the optimal control gain is:

$$K^* = -(B^\top P B + R)^{-1} B^\top P A. \quad (14.2)$$

We have that P is unique and that the optimal average cost is $\sigma^2 \text{Trace}(P)$.

As before, P parameterizes the optimal value function. We do not prove this theorem here though it follows along similar lines to the previous proof, via a limiting argument.

To find P , we can again run the recursion:

$$P \leftarrow Q + A^\top P A - A^\top P B (R + B^\top P B)^{-1} B^\top P A$$

starting with $P = Q$, which can be shown to converge to the unique positive semidefinite solution of the Riccati equation (since one can show the fixed-point iteration is contractive). Again, this approach is simply value iteration.

14.3 Convex Programs to find P and K^*

For the infinite horizon LQR problem, the optimization may be formulated as a convex program. In particular, the LQR problem can also be expressed as a semidefinite program (SDP) with variable P , for the infinite horizon case. We now present this primal program along with the dual program.

Note that these programs are the analogues of the linear programs from Section ?? for MDPs. While specifying these linear programs for an LQR (as an LQR is an MDP) would result in infinite dimensional linear programs, the special structure of the LQR implies these primal and dual programs have a more compact formulation when specified as an SDP.

14.3.1 The Primal for Infinite Horizon LQR

The primal optimization problem is given as:

$$\begin{aligned} & \text{maximize} && \sigma^2 \text{Trace}(P) \\ & \text{subject to} && \begin{bmatrix} A^T P A + Q - P & A^T P B \\ B^T P A & B^T P B + R \end{bmatrix} \succeq 0, \quad P \succeq 0, \end{aligned}$$

where the optimization variable is P . This SDP has a unique solution, P^* , which satisfies the algebraic Riccati equations (Equation 14.1); the optimal average cost of the infinite horizon LQR is $\sigma^2 \text{Trace}(P^*)$; and the optimal policy is given by Equation 14.2.

The SDP can be derived by relaxing the equality in the Riccati equation to an inequality, then using the Schur complement lemma to rewrite the resulting Riccati inequality as linear matrix inequality. In particular, we can consider the relaxation where P must satisfy:

$$A^T P A + Q - A^T P B (B^T P B + R)^{-1} B^T P A \succeq P.$$

That the solution to this relaxed optimization problem leads to the optimal P^* is due to the Bellman optimality conditions.

Now the Schur complement lemma for positive semi-definiteness is as follows: define

$$X = \begin{bmatrix} D & E \\ E^T & F \end{bmatrix}.$$

(for matrices D , E , and F of appropriate size, with D and F being square symmetric matrices). We have that X is PSD if and only if

$$D - E^T F^{-1} E \succeq 0.$$

This shows that the constraint set is equivalent to the above relaxation.

14.3.2 The Dual

The dual optimization problem is given as:

$$\begin{aligned} & \text{minimize} && \text{Trace} \left(\Sigma \cdot \begin{bmatrix} Q & 0 \\ 0 & R \end{bmatrix} \right) \\ & \text{subject to} && \Sigma_{xx} = (A \ B) \Sigma (A \ B)^T + \sigma^2 I, \quad \Sigma \succeq 0, \end{aligned}$$

where the optimization variable is a symmetric matrix Σ , which is a $(d+k) \times (d+k)$ matrix with the block structure:

$$\Sigma = \begin{bmatrix} \Sigma_{xx} & \Sigma_{xu} \\ \Sigma_{ux} & \Sigma_{uu} \end{bmatrix}.$$

The interpretation of Σ is that it is the covariance matrix of the stationary distribution. This is analogous to the state-visitation measure for an MDP.

This SDP has a unique solution, say Σ^* . The optimal gain matrix is then given by:

$$K^* = -\Sigma_{ux}^* (\Sigma_{xx}^*)^{-1}.$$

14.4 Policy Iteration, Gauss Newton, and NPG

Note that the noise variance σ^2 does not impact the optimal policy, in either the discounted case or in the infinite horizon case.

Here, when we examine local search methods, it is more convenient to work with case where $\sigma = 0$. In this case, we can work with cumulative cost rather than the average cost. Precisely, when $\sigma = 0$, the infinite horizon LQR problem takes the form:

$$\min_K C(K), \text{ where } C(K) = \mathbb{E}_{x_0 \sim \mathcal{D}} \left[\sum_{t=0}^H (x_t^\top Q x_t + u_t^\top R u_t) \right],$$

where the dynamics evolves as

$$x_{t+1} = (A - BK)x_t.$$

Note that we have directly parameterized our policy as a linear policy in terms of the gain matrix K , due to that we know the optimal policy is linear in the state. Again, we assume that $C(K^*)$ is finite; this assumption is referred to as the system being *controllable*.

We now examine local search based approaches, where we will see a close connection to policy iteration. Again, we have a non-convex optimization problem:

Lemma 14.3. (Non-convexity) *If $d \geq 3$, there exists an LQR optimization problem, $\min_K C(K)$, which is not convex or quasi-convex.*

Regardless, we will see that gradient based approaches are effective. For local search based approaches, the importance of (some) randomization, either in x_0 or noise through having a disturbance, is analogous to our use of having a wide-coverage distribution μ (for MDPs).

14.4.1 Gradient Expressions

Gradient descent on $C(K)$, with a fixed stepsize η , follows the update rule:

$$K \leftarrow K - \eta \nabla C(K).$$

It is helpful to explicitly write out the functional form of the gradient. Define P_K as the solution to:

$$P_K = Q + K^\top R K + (A - BK)^\top P_K (A - BK).$$

and, under this definition, it follows that $C(K)$ can be written as:

$$C(K) = \mathbb{E}_{x_0 \sim \mathcal{D}} x_0^\top P_K x_0.$$

Also, define Σ_K as the (un-normalized) state correlation matrix, i.e.

$$\Sigma_K = \mathbb{E}_{x_0 \sim \mathcal{D}} \sum_{t=0}^{\infty} x_t x_t^\top.$$

Lemma 14.4. (*Policy Gradient Expression*) *The policy gradient is:*

$$\nabla C(K) = 2 \left((R + B^\top P_K B)K - B^\top P_K A \right) \Sigma_K$$

For convenience, define E_K to be

$$E_K = \left((R + B^\top P_K B)K - B^\top P_K A \right),$$

as a result the gradient can be written as $\nabla C(K) = 2E_K \Sigma_K$.

Proof. Observe:

$$\begin{aligned} C_K(x_0) &= x_0^\top P_K x_0 = x_0^\top (Q + K^\top R K) x_0 + x_0^\top (A - BK)^\top P_K (A - BK) x_0 \\ &= x_0^\top (Q + K^\top R K) x_0 + C_K((A - BK)x_0). \end{aligned}$$

Let ∇ denote the gradient with respect to K ; note that $\nabla C_K((A - BK)x_0)$ has two terms as function of K , one with respect to K in the subscript and one with respect to the input $(A - BK)x_0$. This implies

$$\begin{aligned} \nabla C_K(x_0) &= 2RKx_0x_0^\top - 2B^\top P_K(A - BK)x_0x_0^\top + \nabla C_K(x_1)|_{x_1=(A-BK)x_0} \\ &= 2 \left((R + B^\top P_K B)K - B^\top P_K A \right) \sum_{t=0}^{\infty} x_t x_t^\top \end{aligned}$$

where we have used recursion and that $x_1 = (A - BK)x_0$. Taking expectations completes the proof. $\square$

The natural policy gradient. Let us now motivate a version of the natural gradient. The natural policy gradient follows the update:

$$\theta \leftarrow \theta - \eta F(\theta)^{-1} \nabla C(\theta), \text{ where } F(\theta) = \mathbb{E} \left[\sum_{t=0}^{\infty} \nabla \log \pi_\theta(u_t | x_t) \nabla \log \pi_\theta(u_t | x_t)^\top \right],$$

where $F(\theta)$ is the Fisher information matrix. A natural special case is using a linear policy with additive Gaussian noise, i.e.

$$\pi_K(x, u) = \mathcal{N}(Kx, \sigma^2 I) \quad (14.3)$$

where $K \in \mathbb{R}^{k \times d}$ and σ^2 is the noise variance. In this case, the natural policy gradient of K (when σ is considered fixed) takes the form:

$$K \leftarrow K - \eta \nabla C(\pi_K) \Sigma_K^{-1} \quad (14.4)$$

Note a subtlety here is that $C(\pi_K)$ is the randomized policy.

To see this, one can verify that the Fisher matrix of size $kd \times kd$, which is indexed as $[G_K]_{(i,j),(i',j')}$ where $i, i' \in \{1, \dots, k\}$ and $j, j' \in \{1, \dots, d\}$, has a block diagonal form where the only non-zeros blocks are $[G_K]_{(i,\cdot),(i,\cdot)} = \Sigma_K$ (this is the block corresponding to the i -th coordinate of the action, as i ranges from 1 to k). This form holds more generally, for any diagonal noise.

14.4.2 Convergence Rates

We consider three exact rules, where we assume access to having exact gradients. As before, we can also estimate these gradients through simulation. For gradient descent, the update is

$$K_{n+1} = K_n - \eta \nabla C(K_n). \quad (14.5)$$

For natural policy gradient descent, the direction is defined so that it is consistent with the stochastic case, as per Equation 14.4, in the exact case the update is:

$$K_{n+1} = K_n - \eta \nabla C(K_n) \Sigma_{K_n}^{-1} \quad (14.6)$$

One show that the Gauss-Newton update is:

$$K_{n+1} = K_n - \eta (R + B^\top P_{K_n} B)^{-1} \nabla C(K_n) \Sigma_{K_n}^{-1}. \quad (14.7)$$

(Gauss-Newton is non-linear optimization approach which uses a certain Hessian approximation. It can be show that this leads to the above update rule.) Interestingly, for the case when $\eta = 1$, the Gauss-Newton method is equivalent to the policy iteration algorithm, which optimizes a one-step deviation from the current policy.

The Gauss-Newton method requires the most complex oracle to implement: it requires access to $\nabla C(K)$, Σ_K , and $R + B^\top P_K B$; as we shall see, it also enjoys the strongest convergence rate guarantee. At the other extreme, gradient descent requires oracle access to only $\nabla C(K)$ and has the slowest convergence rate. The natural policy gradient sits in between, requiring oracle access to $\nabla C(K)$ and Σ_K , and having a convergence rate between the other two methods.

In this theorem, $\|M\|_2$ denotes the spectral norm of a matrix M .

Theorem 14.5. (*Global Convergence of Gradient Methods*) Suppose $C(K_0)$ is finite and, for μ defined as

$$\mu := \sigma_{\min}(\mathbb{E}_{x_0 \sim \mathcal{D}} x_0 x_0^\top),$$

suppose $\mu > 0$.

- *Gauss-Newton case:* Suppose $\eta = 1$, the Gauss-Newton algorithm (Equation 14.7) enjoys the following performance bound:

$$C(K_N) - C(K^*) \leq \epsilon, \text{ for } N \geq \frac{\|\Sigma_{K^*}\|_2}{\mu} \log \frac{C(K_0) - C(K^*)}{\epsilon}.$$

- *Natural policy gradient case:* For a stepsize $\eta = 1/(\|R\|_2 + \frac{\|B\|_2^2 C(K_0)}{\mu})$, natural policy gradient descent (Equation 14.6) enjoys the following performance bound:

$$C(K_N) - C(K^*) \leq \epsilon, \text{ for } N \geq \frac{\|\Sigma_{K^*}\|_2}{\mu} \left(\frac{\|R\|_2}{\sigma_{\min}(R)} + \frac{\|B\|_2^2 C(K_0)}{\mu \sigma_{\min}(R)} \right) \log \frac{C(K_0) - C(K^*)}{\epsilon}.$$

- *Gradient descent case:* For any starting policy K_0 , there exists a (constant) stepsize η (which could be a function of K_0), such that:

$$C(K_N) \rightarrow C(K^*), \text{ as } N \rightarrow \infty.$$

14.4.3 Gauss-Newton Analysis

We only provide a proof for the Gauss-Newton case (see 14.6 for further readings).

We overload notation and let K denote the policy $\pi(x) = Kx$. For the infinite horizon cost function, define:

$$\begin{aligned} V_K(x) &:= \sum_{t=0}^{\infty} (x_t^\top Q x_t + u_t^\top R u_t) \\ &= x^\top P_K x, \end{aligned}$$

and

$$Q_K(x, u) := x^\top Q x + u^\top R u + V_K(Ax + Bu),$$

and

$$A_K(x, u) = Q_K(x, u) - V_K(x).$$

The next lemma is identical to the performance difference lemma.

Lemma 14.6. (*Cost difference lemma*) Suppose K and K' have finite costs. Let $\{x'_t\}$ and $\{u'_t\}$ be state and action sequences generated by K' , i.e. starting with $x'_0 = x$ and using $u'_t = -K'x'_t$. It holds that:

$$V_{K'}(x) - V_K(x) = \sum_t A_K(x'_t, u'_t).$$

Also, for any x , the advantage is:

$$A_K(x, K'x) = 2x^\top (K' - K)^\top E_K x + x^\top (K' - K)^\top (R + B^\top P_K B)(K' - K)x. \quad (14.8)$$

Proof. Let c'_t be the cost sequence generated by K' . Telescoping the sum appropriately:

$$\begin{aligned} V_{K'}(x) - V_K(x) &= \sum_{t=0}^{\infty} c'_t - V_K(x) = \sum_{t=0}^{\infty} (c'_t + V_K(x'_t) - V_K(x'_t)) - V_K(x) \\ &= \sum_{t=0}^{\infty} (c'_t + V_K(x'_{t+1}) - V_K(x'_t)) = \sum_{t=0}^{\infty} A_K(x'_t, u'_t) \end{aligned}$$

which completes the first claim (the third equality uses the fact that $x = x_0 = x'_0$).

For the second claim, observe that:

$$V_K(x) = x^\top (Q + K^\top R K) x + x^\top (A - BK)^\top P_K (A - BK) x$$

And, for $u = K'x$,

$$\begin{aligned} A_K(x, u) &= Q_K(x, u) - V_K(x) \\ &= x^\top (Q + (K')^\top R K') x + x^\top (A - BK')^\top P_K (A - BK') x - V_K(x) \\ &= x^\top (Q + (K' - K + K)^\top R (K' - K + K)) x + \\ &\quad x^\top (A - BK - B(K' - K))^\top P_K (A - BK - B(K' - K)) x - V_K(x) \\ &= 2x^\top (K' - K)^\top ((R + B^\top P_K B)K - B^\top P_K A) x + \\ &\quad x^\top (K' - K)^\top (R + B^\top P_K B)(K' - K)x, \end{aligned}$$

which completes the proof. □

We have the following corollary, which can be viewed analogously to a smoothness lemma.

Corollary 14.7. (“Almost” smoothness) $C(K)$ satisfies:

$$C(K') - C(K) = -2\text{Trace}(\Sigma_{K'}(K - K')^\top E_K) + \text{Trace}(\Sigma_{K'}(K - K')^\top (R + B^\top P_K B)(K - K'))$$

To see why this is related to smoothness (recall the definition of a smooth function in Equation 11.6), suppose K' is sufficiently close to K so that:

$$\Sigma_{K'} \approx \Sigma_K + O(\|K - K'\|) \quad (14.9)$$

and the leading order term $2\text{Trace}(\Sigma_{K'}(K' - K)^\top E_K)$ would then behave as $\text{Trace}((K' - K)^\top \nabla C(K))$.

Proof. The claim immediately results from Lemma 14.6, by using Equation 14.8 and taking an expectation. $\square$

We now use this cost difference lemma to show that $C(K)$ is gradient dominated.

Lemma 14.8. (*Gradient domination*) Let K^* be an optimal policy. Suppose K has finite cost and $\mu > 0$. It holds that:

$$\begin{aligned} C(K) - C(K^*) &\leq \|\Sigma_{K^*}\| \text{Trace}(E_K^\top (R + B^\top P_K B)^{-1} E_K) \\ &\leq \frac{\|\Sigma_{K^*}\|}{\mu^2 \sigma_{\min}(R)} \text{Trace}(\nabla C(K)^\top \nabla C(K)) \end{aligned}$$

Proof. From Equation 14.8 and by completing the square,

$$\begin{aligned} A_K(x, K'x) &= Q_K(x, K'x) - V_K(x) \\ &= 2\text{Trace}(xx^\top (K' - K)^\top E_K) + \text{Trace}(xx^\top (K' - K)^\top (R + B^\top P_K B)(K' - K)) \\ &= \text{Trace}(xx^\top (K' - K + (R + B^\top P_K B)^{-1} E_K)^\top (R + B^\top P_K B) (K' - K + (R + B^\top P_K B)^{-1} E_K)) \\ &\quad - \text{Trace}(xx^\top E_K^\top (R + B^\top P_K B)^{-1} E_K) \\ &\geq -\text{Trace}(xx^\top E_K^\top (R + B^\top P_K B)^{-1} E_K) \end{aligned} \quad (14.10)$$

with equality when $K' = K - (R + B^\top P_K B)^{-1} E_K$.

Let x_t^* and u_t^* be the sequence generated under K^* . Using this and Lemma 14.6,

$$\begin{aligned} C(K) - C(K^*) &= -\mathbb{E} \sum_t A_K(x_t^*, u_t^*) \leq \mathbb{E} \sum_t \text{Trace}(x_t^* (x_t^*)^\top E_K^\top (R + B^\top P_K B)^{-1} E_K) \\ &= \text{Trace}(\Sigma_{K^*} E_K^\top (R + B^\top P_K B)^{-1} E_K) \leq \|\Sigma_{K^*}\| \text{Trace}(E_K^\top (R + B^\top P_K B)^{-1} E_K) \end{aligned}$$

which completes the proof of first inequality. For the second inequality, observe:

$$\begin{aligned} \text{Trace}(E_K^\top (R + B^\top P_K B)^{-1} E_K) &\leq \|(R + B^\top P_K B)^{-1}\| \text{Trace}(E_K^\top E_K) \leq \frac{1}{\sigma_{\min}(R)} \text{Trace}(E_K^\top E_K) \\ &= \frac{1}{\sigma_{\min}(R)} \text{Trace}(\Sigma_K^{-1} \nabla C(K)^\top \nabla C(K) \Sigma_K^{-1}) \leq \frac{1}{\sigma_{\min}(\Sigma_K)^2 \sigma_{\min}(R)} \text{Trace}(\nabla C(K)^\top \nabla C(K)) \\ &\leq \frac{1}{\mu^2 \sigma_{\min}(R)} \text{Trace}(\nabla C(K)^\top \nabla C(K)) \end{aligned}$$

which completes the proof of the upper bound. Here the last step is because $\Sigma_K \succeq \mathbb{E}[x_0 x_0^\top]$. $\square$

The next lemma bounds the one step progress of Gauss-Newton.

Lemma 14.9. (*Gauss-Newton Contraction*) Suppose that:

$$K' = K - \eta(R + B^\top P_K B)^{-1} \nabla C(K) \Sigma_K^{-1}, .$$

If $\eta \leq 1$, then

$$C(K') - C(K^*) \leq \left(1 - \frac{\eta \mu}{\|\Sigma_{K^*}\|}\right) (C(K) - C(K^*))$$

Proof. Observe that for PSD matrices A and B , we have that $\text{Trace}(AB) \geq \sigma_{\min}(A)\text{Trace}(B)$. Also, observe $K' = K - \eta(R + B^\top P_K B)^{-1} E_K$. Using Lemma 14.7 and the condition on η ,

$$\begin{aligned} C(K') - C(K) &= -2\eta \text{Trace}(\Sigma_{K'} E_K^\top (R + B^\top P_K B)^{-1} E_K) + \eta^2 \text{Trace}(\Sigma_{K'} E_K^\top (R + B^\top P_K B)^{-1} E_K) \\ &\leq -\eta \text{Trace}(\Sigma_{K'} E_K^\top (R + B^\top P_K B)^{-1} E_K) \\ &\leq -\eta \sigma_{\min}(\Sigma_{K'}) \text{Trace}(E_K^\top (R + B^\top P_K B)^{-1} E_K) \\ &\leq -\eta \mu \text{Trace}(E_K^\top (R + B^\top P_K B)^{-1} E_K) \\ &\leq -\eta \frac{\mu}{\|\Sigma_{K^*}\|} (C(K) - C(K^*)), \end{aligned}$$

where the last step uses Lemma 14.8. □

With this lemma, the proof of the convergence rate of the Gauss Newton algorithm is immediate.

Proof. (of Theorem 14.5, Gauss-Newton case) The theorem is due to that $\eta = 1$ leads to a contraction of $1 - \frac{\mu}{\|\Sigma_{K^*}\|}$ at every step. □

14.5 System Level Synthesis for Linear Dynamical Systems

We demonstrate another parameterization of controllers which admits convexity. Specifically in this section, we consider finite horizon setting, i.e.,

$$x_{t+1} = Ax_t + Bu_t + w_t, \quad x_0 \sim \mathcal{D}, w_t \sim \mathcal{N}(0, \sigma^2 I), \quad t \in [0, 1, \dots, H-1].$$

Instead of focusing on quadratic cost function, we consider general convex cost function $c(x_t, u_t)$, and the goal is to optimize:

$$\mathbb{E}_\pi \left[\sum_{t=0}^{H-1} c_t(x_t, u_t) \right],$$

where π is a time-dependent policy.

While we relax the assumption on the cost function from quadratic cost to general convex cost, we still focus on linearly parameterized policy, i.e., we are still interested in searching for a sequence of time-dependent linear controllers $\{-K_t^*\}_{t=0}^{H-1}$ with $u_t = -K_t^* x_t$, such that it minimizes the above objective function. We again assume the system is controllable, i.e., the expected total cost under $\{-K_t^*\}_{t=0}^{H-1}$ is finite.

Note that due to the fact that now the cost function is not quadratic anymore, the Riccati equation we studied before does not hold, and it is not necessarily true that the value function of any linear controllers will be a quadratic function.

We present another parameterization of linear controllers which admit convexity in the objective function with respect to parameterization (recall that the objective function is non-convex with respect to linear controllers $-K_t$). With the new parameterization, we will see that due to the convexity, we can directly apply gradient descent to find the globally optimal solution.

Consider any fixed time-dependent linear controllers $\{-K_t\}_{t=0}^{H-1}$. We start by rolling out the linear system under the controllers. Note that during the rollout, once we observe x_{t+1} , we can compute w_t as $w_t = x_{t+1} - Ax_t - Bu_t$. With

$x_0 \sim \mu$, we have that at time step t :

$$\begin{aligned}
u_t &= -K_t x_t = -K_t (Ax_{t-1} - BK_{t-1}x_{t-1} + w_{t-1}) \\
&= -K_t w_{t-1} - K_t (A - BK_{t-1})x_{t-1} \\
&= -K_t w_{t-1} - K_t (A - BK_{t-1})(Ax_{t-2} - BK_{t-2}x_{t-2} + w_{t-2}) \\
&= \underbrace{-K_t}_{:=M_{t-1;t}} w_{t-1} - \underbrace{K_t (A - BK_{t-1})}_{:=M_{t-2;t}} w_{t-2} - \underbrace{K_t (A - BK_{t-1})(A - BK_{t-2})}_{:=M_{t-3;t}} x_{t-2} \\
&= -K_t \left(\prod_{\tau=1}^t (A - BK_{t-\tau}) \right) x_0 - \sum_{\tau=0}^{t-1} K_t \prod_{h=1}^{t-1-\tau} (A - BK_{t-h}) w_\tau
\end{aligned}$$

Note that we can equivalently write u_t using x_0 and the noises $w_0, \dots, w_{t-1}$. Hence for time step t , let us do the following re-parameterization. Denote

$$M_t := -K_t \left(\prod_{\tau=1}^t (A - BK_{t-\tau}) \right), \quad M_{\tau;t} := -K_t \prod_{h=1}^{t-1-\tau} (A - BK_{t-h}), \text{ where } \tau = [0, \dots, t-1].$$

Now we can express the control u_t using $M_{\tau;t}$ for $\tau \in [0, \dots, t-1]$ and M_t as follows:

$$u_t = M_t x_0 + \sum_{\tau=0}^{t-1} M_{\tau;t} w_\tau,$$

which is equal to $u_t = -K_t x_t$. Note that above we only reasoned time step t . We can repeat the same calculation for all $t = 0 \rightarrow H-1$.

The above calculation basically proves the following claim.

Claim 14.10. *For any linear controllers $\pi := \{-K_0, \dots, -K_{H-1}\}$, there exists a parameterization, $\tilde{\pi} := \{\{M_t, M_{0;t}, \dots, M_{t-1;t}\}\}_{t=0}^{H-1}$, such that when execute π and $\tilde{\pi}$ under any initialization x_0 , and any sequence of noises $\{w_t\}_{t=0}^{H-1}$, they generate exactly the same state-control trajectory.*

We can execute $\tilde{\pi} := \{\{M_t, M_{0;t}, \dots, M_{t-1;t}\}\}_{t=0}^{H-1}$ in the following way. Given any x_0 , we execute $u_0 = M_0 x_0$ and observe x_1 ; at time step t with the observed x_t , we calculate $w_{t-1} = x_t - Ax_{t-1} - Bu_{t-1}$, and execute the control $u_t = M_t x_0 + \sum_{\tau=0}^{t-1} M_{\tau;t} w_\tau$. We repeat until we execute the last control u_{H-1} and reach x_H .

What is the benefit of the above parameterization? Note that for any t , this is clearly over-parameterized: the simple linear controllers $-K_t$ has $d \times k$ many parameters, while the new controller $\{M_t; \{M_{\tau;t}\}_{\tau=0}^{t-1}\}$ has $t \times d \times k$ many parameters. The benefit of the above parameterization is that the objective function now is convex! The following claim formally shows the convexity.

Claim 14.11. *Given $\tilde{\pi} := \{\{M_t, M_{0;t}, \dots, M_{t-1;t}\}\}_{t=0}^{H-1}$ and denote its expected total cost as $J(\tilde{\pi}) := \mathbb{E} \left[\sum_{t=0}^{H-1} c(x_t, u_t) \right]$, where the expectation is with respect to the noise $w_t \sim \mathcal{N}(0, \sigma^2 I)$ and the initial state $x_0 \sim \mu$, and c is any convex function with respect to x, u . We have that $J(\tilde{\pi})$ is convex with respect to parameters $\{\{M_t, M_{0;t}, \dots, M_{t-1;t}\}\}_{t=0}^{H-1}$.*

Proof. We consider a fixed x_0 and a fixed sequence of noises $\{w_t\}_{t=0}^{H-1}$. Recall that for u_t , we can write it as:

$$u_t = M_t x_0 + \sum_{\tau=0}^{t-1} M_{\tau;t} w_\tau,$$

which is clearly linear with respect to the parameterization $\{M_t; M_{0;t}, \dots, M_{t-1;t}\}$.

For x_t , we can show by induction that it is linear with respect to $\{M_\tau; M_{0;\tau}, \dots, M_{\tau-1;\tau}\}_{\tau=0}^{t-1}$. Note that it is clearly true for x_0 which is independent of any parameterizations. Assume this claim holds for x_t with $t \geq 0$, we now check x_{t+1} . We have:

$$x_{t+1} = Ax_t + Bu_t = Ax_t + BM_t x_0 + \sum_{\tau=0}^{t-1} BM_{\tau;t} w_\tau$$

Note that by inductive hypothesis x_t is linear with respect to $\{M_\tau; M_{0;\tau}, \dots, M_{\tau-1;\tau}\}_{\tau=0}^{t-1}$, and the part $BM_t x_0 + \sum_{\tau=0}^{t-1} BM_{\tau;t} w_\tau$ is clearly linear with respect to $\{M_t; M_{0;t}, \dots, M_{t-1;t}\}$. Together, this implies that x_{t+1} is linear with respect to $\{M_\tau; M_{0;\tau}, \dots, M_{\tau-1;\tau}\}_{\tau=0}^t$, which concludes that for any x_t with $t = 0, \dots, H-1$, we have x_t is linear with respect to $\{M_\tau; M_{0;\tau}, \dots, M_{\tau-1;\tau}\}_{\tau=0}^{H-1}$.

Note that the trajectory total cost is $\sum_{t=0}^{H-1} c(x_t, u_t)$. Since c_t is convex with respect to x_t and u_t , and x_t and u_t are linear with respect to $\{M_\tau; M_{0;\tau}, \dots, M_{\tau-1;\tau}\}_{\tau=0}^{H-1}$, we have that $\sum_{t=0}^{H-1} c_t(x_t, u_t)$ is convex with respect to $\{M_\tau; M_{0;\tau}, \dots, M_{\tau-1;\tau}\}_{\tau=0}^{H-1}$.

In last step we can simply take expectation with respect to x_0 and $w_1, \dots, w_{H-1}$. By linearity of expectation, we conclude the proof. $\square$

The above immediately suggests that (sub) gradient-based algorithms such as projected gradient descent on parameters $\{M_t, M_{0;t}, \dots, M_{t-1;t}\}_{t=0}^{H-1}$ can converge to the globally optimal solutions for any convex function c_t . Recall that the best linear controllers $\{-K_t^*\}_{t=0}^{H-1}$ has its own corresponding parameterization $\{M_t^*, M_{0;t}^*, \dots, M_{t-1;t}^*\}_{t=0}^{H-1}$. Thus gradient-based optimization (with some care of the boundness of the parameters $\{M_t^*, M_{0;t}^*, \dots, M_{t-1;t}^*\}_{t=0}^{H-1}$) can find a solution that at least as good as the best linear controllers $\{-K_t^*\}_{t=0}^{H-1}$.

Remark The above claims easily extend to time-dependent transition and cost function, i.e., A_t, B_t, c_t are time-dependent. One can also extend it to episodic online control setting with adversarial noises w_t and adversarial cost functions using no-regret online convex programming algorithms Shalev-Shwartz [2011]. In episodic online control, every episode k , an adversary determines a sequence of bounded noises $w_0^k, \dots, w_{H-1}^k$, and cost function $c^k(x, u)$; the learner proposes a sequence of controllers $\tilde{\pi}^k = \{M_t^k, M_{0;t}^k, \dots, M_{t-1;t}^k\}_{t=0}^{H-1}$ and executes them (learner does not know the cost function c^k until the end of the episode, and the noises are revealed in a way when she observes x_t^k and calculates w_{t-1}^k as $x_t^k - Ax_{t-1}^k - Bu_{t-1}^k$); at the end of the episode, learner observes c^k and suffers total cost $\sum_{t=0}^{H-1} c^k(x_t^k, u_t^k)$. The goal of the episodic online control is to be no-regret with respect to the best linear controllers in hindsight:

$$\sum_{k=0}^{K-1} \sum_{t=0}^{H-1} c^k(x_t^k, u_t^k) - \min_{\{-K_t^*\}_{t=0}^{H-1}} \sum_{k=0}^{K-1} J^k(\{-K_t^*\}_{t=0}^{H-1}) = o(K),$$

where we denote $J^k(\{-K_t^*\}_{t=0}^{H-1})$ as the total cost of executing $\{-K_t^*\}_{t=0}^{H-1}$ in episodic k under c^k and noises $\{w_t^k\}$, i.e., $\sum_{t=0}^{H-1} c(x_t, u_t)$ with $u_t = -K_t^* x_t$ and $x_{t+1} = Ax_t + Bu_t + w_t^k$, for all t .

14.6 Bibliographic Remarks and Further Readings

The basics of optimal control theory can be found in any number of standards text Anderson and Moore [1990], Evans [2005], Bertsekas [2017]. The primal and dual formulations for the continuous time LQR are derived in Balakrishnan and Vandenberghe [2003], while the dual formulation for the discrete time LQR, that we use here, is derived in Cohen et al. [2019].

The treatment of Gauss-Newton, NPG, and PG algorithm are due to Fazel et al. [2018]. We have only provided the proof for the Gauss-Newton case based; the proofs of convergence rates for NPG and PG can be found in Fazel et al. [2018].

For many applications, the finite horizon LQR model is widely used as a model of locally linear dynamics, e.g. Ahn et al. [2007], Todorov and Li [2005], Tedrake [2009], Perez et al. [2012]. The issue of instabilities are largely due to model misspecification and in the accuracy of the Taylor’s expansion; it is less evident how the infinite horizon LQR model captures these issues. In contrast, for MDPs, practice tends to deal with stationary (and discounted) MDPs, due that stationary policies are more convenient to represent and learn; here, the non-stationary, finite horizon MDP model tends to be more of theoretical interest, due to that it is straightforward (and often more effective) to simply incorporate temporal information into the state. Roughly, if our policy is parametric, then practical representational constraints leads us to use stationary policies (incorporating temporal information into the state), while if we tend to use non-parametric policies (e.g. through some rollout based procedure, say with “on the fly” computations like in model predictive control, e.g. Williams et al. [2017]), then it is often more effective to work with finite horizon, non-stationary models.

Sample Complexity and Regret for LQRs. We have not treated the sample complexity of learning in an LQR (see Dean et al. [2017], Simchowitz et al. [2018], Mania et al. [2019] for rates). Here, the basic analysis follows from the online regression approach, which was developed in the study of linear bandits Dani et al. [2008], Abbasi-Yadkori et al. [2011]; in particular, the self-normalized bound for vector-valued martingales [Abbasi-Yadkori et al., 2011] (see Theorem A.9) provides a direct means to obtain sharp confidence intervals for estimating the system matrices A and B from data from a single trajectory (e.g. see Simchowitz and Foster [2020]).

Another family of work provides regret analyses of online LQR problems [Abbasi-Yadkori and Szepesvári, 2011, Dean et al., 2018, Mania et al., 2019, Cohen et al., 2019, Simchowitz and Foster, 2020]. Here, naive random search suffices for sample efficient learning of LQRs [Simchowitz and Foster, 2020]. For the learning and control of more complex nonlinear dynamical systems, one would expect this is insufficient, where strategic exploration is required for sample efficient learning; just as in the case for MDPs (e.g. the UCB-VI algorithm).

Convex Parameterization of Linear Controllers The convex parameterization in Section 14.5 is based on Agarwal et al. [2019] which is equivalent to the System Level Synthesis (SLS) parameterization Wang et al. [2019]. Agarwal et al. [2019] uses SLS parameterization in the infinite horizon online control setting and leverages a reduction to online learning with memory. Note that in episodic online control setting, we can just use classic no-regret online learner such as projected gradient descent Zinkevich [2003]. For partial observable linear systems, the classic Youla parameterization Youla et al. [1976] introduces a convex parameterization. We also refer readers to Simchowitz et al. [2020] for more detailed discussion about Youla parameterization and the generalization of Youla parameterization. Moreover, using the performance difference lemma, the exact optimal control policy for adversarial noise with full observations can be exactly characterized Foster and Simchowitz [2020], Goel and Hassibi [2020] and yields a form reminiscent of the SLS parametrization Wang et al. [2019].

Appendix A

Concentration

This appendix collects a few standard concentration inequalities used throughout the monograph.

A.1 Scalar concentration

Lemma A.1 (Hoeffding's inequality). *Suppose $X_1, \dots, X_n$ are independent, identically distributed random variables with mean μ . Let $\bar{X}_n := \frac{1}{n} \sum_{i=1}^n X_i$. If $X_i \in [b_-, b_+]$ almost surely, then for any $\epsilon > 0$,*

$$\Pr(\bar{X}_n - \mu \geq \epsilon) \leq \exp\left(-\frac{2n\epsilon^2}{(b_+ - b_-)^2}\right), \quad \Pr(\mu - \bar{X}_n \geq \epsilon) \leq \exp\left(-\frac{2n\epsilon^2}{(b_+ - b_-)^2}\right).$$

Equivalently,

$$\Pr(|\bar{X}_n - \mu| \geq \epsilon) \leq 2 \exp\left(-\frac{2n\epsilon^2}{(b_+ - b_-)^2}\right).$$

In particular, inverting the two-sided bound yields: with probability at least $1 - \delta$,

$$|\bar{X}_n - \mu| \leq (b_+ - b_-) \sqrt{\frac{\log(2/\delta)}{2n}}.$$

A.2 Sub-Gaussian random variables

Definition A.2 (Sub-Gaussian random variable). A real-valued random variable X is σ -sub-Gaussian if for all $\lambda \in \mathbb{R}$,

$$\mathbb{E}[\exp(\lambda(X - \mathbb{E}X))] \leq \exp\left(\frac{\lambda^2 \sigma^2}{2}\right).$$

A centered Gaussian $X \sim \mathcal{N}(0, \sigma^2)$ is σ -sub-Gaussian.

Theorem A.3 (Sub-Gaussian tail bound). *If X is σ -sub-Gaussian, then for all $\epsilon > 0$,*

$$\Pr(X - \mathbb{E}X \geq \epsilon) \leq \exp\left(-\frac{\epsilon^2}{2\sigma^2}\right), \quad \Pr(|X - \mathbb{E}X| \geq \epsilon) \leq 2 \exp\left(-\frac{\epsilon^2}{2\sigma^2}\right).$$

Lemma A.4 (Stability under scaling and sums). *If X is σ -sub-Gaussian then for any $c \in \mathbb{R}$, cX is $|c|\sigma$ -sub-Gaussian. If X_1 and X_2 are independent and σ_1 - and σ_2 -sub-Gaussian respectively, then $X_1 + X_2$ is $\sqrt{\sigma_1^2 + \sigma_2^2}$ -sub-Gaussian.*

A.3 Martingale concentration

Theorem A.5 (Hoeffding–Azuma inequality (conditional sub-Gaussian form)). *Let $(\mathcal{F}_t)_{t \geq 0}$ be a filtration and $(X_t)_{t=1}^N$ a martingale difference sequence, i.e. X_t is $\mathcal{F}_t$ -measurable and $\mathbb{E}[X_t \mid \mathcal{F}_{t-1}] = 0$. Assume X_t is conditionally σ_t -sub-Gaussian given $\mathcal{F}_{t-1}$, meaning that for all $\lambda \in \mathbb{R}$,*

$$\mathbb{E}[\exp(\lambda X_t) \mid \mathcal{F}_{t-1}] \leq \exp\left(\frac{\lambda^2 \sigma_t^2}{2}\right) \quad \text{a.s.}$$

Then for all $\epsilon > 0$,

$$\Pr\left(\sum_{t=1}^N X_t \geq \epsilon\right) \leq \exp\left(-\frac{\epsilon^2}{2 \sum_{t=1}^N \sigma_t^2}\right), \quad \Pr\left(\left|\sum_{t=1}^N X_t\right| \geq \epsilon\right) \leq 2 \exp\left(-\frac{\epsilon^2}{2 \sum_{t=1}^N \sigma_t^2}\right).$$

Lemma A.6 (Bernstein's inequality (i.i.d.)). *Let $X_1, \dots, X_n$ be independent random variables with $\mu := \mathbb{E}[X_i]$ and $\text{Var}(X_i) \leq \sigma^2$ for all i . Assume $|X_i - \mu| \leq b$ almost surely. Then for all $\epsilon > 0$,*

$$\Pr(\bar{X}_n - \mu \geq \epsilon) \leq \exp\left(-\frac{n\epsilon^2}{2\sigma^2 + \frac{2}{3}b\epsilon}\right), \quad \Pr(|\bar{X}_n - \mu| \geq \epsilon) \leq 2 \exp\left(-\frac{n\epsilon^2}{2\sigma^2 + \frac{2}{3}b\epsilon}\right).$$

In particular, with probability at least $1 - \delta$,

$$|\bar{X}_n - \mu| \leq \sqrt{\frac{2\sigma^2 \log(2/\delta)}{n}} + \frac{2b \log(2/\delta)}{3n}.$$

Lemma A.7 (Freedman's inequality (martingale Bernstein)). *Let $(X_t)_{t=1}^n$ be a martingale difference sequence w.r.t. a filtration $(\mathcal{F}_t)_{t \geq 0}$ and assume $|X_t| \leq M$ almost surely. Define the predictable quadratic variation*

$$V_n := \sum_{t=1}^n \mathbb{E}[X_t^2 \mid \mathcal{F}_{t-1}].$$

Then for all $t > 0$,

$$\Pr\left(\sum_{i=1}^n X_i \geq t\right) \leq \exp\left(-\frac{t^2}{2(V_n + Mt/3)}\right).$$

A.4 A discrete distribution concentration bound

The following bound is a standard application of bounded-differences/McDiarmid (e.g. [McDiarmid, 1989]).

Proposition A.8 (Concentration for discrete distributions). *Let Z be a discrete random variable supported on $\{1, \dots, d\}$ with distribution $q \in \Delta([d])$, and let $\hat{q}$ be the empirical distribution from N i.i.d. samples. Then with probability at least $1 - \delta$,*

$$\|\hat{q} - q\|_2 \leq \frac{1}{\sqrt{N}} + \sqrt{\frac{\log(1/\delta)}{2N}}.$$

Consequently,

$$\|\hat{q} - q\|_1 \leq \sqrt{d} \left(\frac{1}{\sqrt{N}} + \sqrt{\frac{\log(1/\delta)}{2N}} \right).$$

A.5 Self-normalized bounds and least squares

Lemma A.9 (Self-normalized bound for vector-valued martingales; [Abbasi-Yadkori et al., 2011]). *Let $(\varepsilon_t)_{t \geq 1}$ be a real-valued process adapted to a filtration $(\mathcal{F}_t)_{t \geq 0}$ such that $\mathbb{E}[\varepsilon_t | \mathcal{F}_{t-1}] = 0$ and ε_t is conditionally σ -sub-Gaussian given $\mathcal{F}_{t-1}$. Let $(X_t)_{t \geq 1}$ be an $\mathbb{R}^d$ -valued adapted process, and let $V_0 \in \mathbb{R}^{d \times d}$ be positive definite. Define*

$$V_t := V_0 + \sum_{i=1}^t X_i X_i^\top.$$

Then for any $\delta \in (0, 1)$, with probability at least $1 - \delta$, simultaneously for all $t \geq 1$,

$$\left\| \sum_{i=1}^t X_i \varepsilon_i \right\|_{V_t^{-1}} \leq \sigma \sqrt{2 \log \left(\frac{\det(V_t)^{1/2} \det(V_0)^{-1/2}}{\delta} \right)}.$$

Equivalently, squaring both sides,

$$\left\| \sum_{i=1}^t X_i \varepsilon_i \right\|_{V_t^{-1}}^2 \leq 2\sigma^2 \log \left(\frac{\det(V_t)^{1/2} \det(V_0)^{-1/2}}{\delta} \right).$$

The following OLS bound above can be derived by writing $\hat{\theta} - \theta^* = \Lambda^{-1} \sum_i x_i \varepsilon_i$ and observing that $\|\hat{\theta} - \theta^*\|_\Lambda = \|\Lambda^{-1/2} \sum_i x_i \varepsilon_i\|_2$ is the Euclidean norm of a d -dimensional sub-Gaussian vector (e.g. see also [Hsu et al., 2008]).

Theorem A.10 (OLS with a fixed design). *Consider a fixed design $\{x_i\}_{i=1}^N \subset \mathbb{R}^d$ and responses $y_i = \langle \theta^*, x_i \rangle + \varepsilon_i$, where $\varepsilon_1, \dots, \varepsilon_N$ are independent, mean-zero, σ -sub-Gaussian random variables. Let*

$$\Lambda := \sum_{i=1}^N x_i x_i^\top$$

and assume Λ is invertible. The ordinary least squares estimator is

$$\hat{\theta} := \Lambda^{-1} \sum_{i=1}^N x_i y_i.$$

Then for any $\delta \in (0, 1)$, with probability at least $1 - \delta$,

$$\|\hat{\theta} - \theta^*\|_\Lambda \leq \sigma \left(\sqrt{d} + \sqrt{2 \log(1/\delta)} \right),$$

and hence

$$\|\hat{\theta} - \theta^*\|_\Lambda^2 \leq \sigma^2 \left(d + 2\sqrt{2d \log(1/\delta)} + 2 \log(1/\delta) \right).$$

The following is a standard “fast-rate” bound for squared-loss ERM over a finite function class (e.g. Györfi et al. [2002]), which we include for completeness.

Lemma A.11 (Least-squares generalization bound (finite class)). *Let $(X_1, Y_1), \dots, (X_n, Y_n)$ be i.i.d. with $X_i \sim \nu$ on $\mathcal{X}$ and $Y_i \in [0, B]$ almost surely for some $B > 0$. Let*

$$f^*(x) := \mathbb{E}[Y | X = x]$$

and assume $f^(x) \in [0, B]$ for all x . Let $\mathcal{F} \subseteq \{f : \mathcal{X} \rightarrow [0, B]\}$ be finite and define*

$$\epsilon_{\text{approx}} := \min_{f \in \mathcal{F}} \|f - f^*\|_{2, \nu}^2.$$

Let $\hat{f} \in \operatorname{argmin}_{f \in \mathcal{F}} \sum_{i=1}^n (f(X_i) - Y_i)^2$ be a squared-loss ERM. Then for any $\delta \in (0, 1)$, with probability at least $1 - \delta$,

$$\|\hat{f} - f^*\|_{2,\nu}^2 \leq \frac{20 B^2 \ln(2|\mathcal{F}|/\delta)}{n} + 3 \epsilon_{\text{approx}}.$$

Proof. For $f \in \mathcal{F}$ define

$$z_i^f := (f(X_i) - Y_i)^2 - (f^*(X_i) - Y_i)^2.$$

A direct expansion gives

$$z_i^f = (f(X_i) - f^*(X_i))(f(X_i) + f^*(X_i) - 2Y_i).$$

Since $f, f^*, Y_i \in [0, B]$, we have $|z_i^f| \leq B^2$ almost surely. Moreover, using $\mathbb{E}[Y_i | X_i] = f^*(X_i)$,

$$\mathbb{E}[z_i^f | X_i] = (f(X_i) - f^*(X_i))^2, \quad \text{so} \quad \mathbb{E}[z_i^f] = \|f - f^*\|_{2,\nu}^2 =: u_f.$$

Finally,

$$(z_i^f)^2 \leq (f(X_i) - f^*(X_i))^2 \cdot (2B)^2 \Rightarrow \operatorname{Var}(z_i^f) \leq \mathbb{E}[(z_i^f)^2] \leq 4B^2 u_f.$$

Let $L := \ln(2|\mathcal{F}|/\delta)$. Applying Bernstein's inequality to z_i^f and to $-z_i^f$, and taking a union bound over $f \in \mathcal{F}$, yields that with probability at least $1 - \delta$, simultaneously for all $f \in \mathcal{F}$,

$$\left| \frac{1}{n} \sum_{i=1}^n z_i^f - u_f \right| \leq \sqrt{\frac{8B^2 u_f L}{n}} + \frac{2B^2 L}{3n}. \quad (\text{A.1})$$

Let $\tilde{f} \in \operatorname{argmin}_{f \in \mathcal{F}} \|f - f^*\|_{2,\nu}^2$, so $u_{\tilde{f}} = \epsilon_{\text{approx}}$. Since $\hat{f}$ minimizes the empirical squared loss,

$$\frac{1}{n} \sum_{i=1}^n z_i^{\hat{f}} \leq \frac{1}{n} \sum_{i=1}^n z_i^{\tilde{f}}.$$

Using (A.1) twice (once for $\hat{f}$, once for $\tilde{f}$), we get

$$u_{\hat{f}} \leq u_{\tilde{f}} + \sqrt{\frac{8B^2 u_{\tilde{f}} L}{n}} + \frac{4B^2 L}{3n} + \sqrt{\frac{8B^2 u_{\hat{f}} L}{n}}.$$

Let $\alpha := \frac{8B^2 L}{n}$ and $\beta := \frac{2B^2 L}{3n}$, and write $u := u_{\hat{f}}$ and $\epsilon := u_{\tilde{f}} = \epsilon_{\text{approx}}$. Then

$$u \leq \epsilon + \sqrt{\alpha \epsilon} + 2\beta + \sqrt{\alpha u}.$$

Using $\sqrt{\alpha u} \leq \frac{u}{2} + \frac{\alpha}{2}$ gives

$$u \leq 2\epsilon + 2\sqrt{\alpha \epsilon} + 4\beta + \alpha.$$

Using $2\sqrt{\alpha \epsilon} \leq \epsilon + \alpha$ yields

$$u \leq 3\epsilon + 2\alpha + 4\beta.$$

Finally,

$$2\alpha + 4\beta = \left(16 + \frac{8}{3}\right) \frac{B^2 L}{n} = \frac{56}{3} \frac{B^2 L}{n} \leq 20 \frac{B^2 L}{n},$$

which completes the proof. $\square$

A.6 Other Bounds

Lemma A.12 (Uniform convergence for Bellman error under linear function hypothesis class). *Given a feature $\phi : \mathcal{S} \times \mathcal{A} \mapsto \mathbb{R}^d$ with $\|\phi(s, a)\|_2 \leq 1, \forall s, a$. Define $\mathcal{H}_h = \{w^\top \phi(s, a) : \|w\|_2 \leq W, w \in \mathbb{R}^d, \|w^\top \phi(\cdot, \cdot)\|_\infty \leq H\}$. Given $g \in \mathcal{H}$, denote $\ell(s, a, s', g)$ as follows:*

$$\ell(s, a, s', h, g) = \frac{\mathbf{1}\{\pi_{h,g}(s) = a\}}{1/A} \left(w_h^\top \phi(s, a) - r(s, a) - \max_{a'} w_{h+1}^\top \phi(s', a') \right).$$

For any distribution $\nu \in \Delta(\mathcal{S})$, with probability $1 - \delta$ over the randomness of the m i.i.d triples $\{s_i, a_i, s'_i\}_{i=1}^m$ with $s_i \sim \nu, a_i \sim \text{Unif}_{\mathcal{A}}, s'_i \sim P_h(\cdot | s_i, a_i)$, we have:

$$\max_{g \in \mathcal{H}} \left| \mathbb{E}_{s \sim \nu, a \sim \text{Unif}_{\mathcal{A}}, s' \sim P_h(\cdot | s, a)} [\ell(s, a, s', h, g)] - \sum_{i=1}^m \ell(s_i, a_i, s'_i, h, g) / m \right| \leq 3HA \sqrt{\frac{2d \ln(1 + 4AWm) + \ln(1/\delta)}{m}}.$$

Similarly, when $\ell(s, a, s', g)$ is defined as:

$$\ell(s, a, s', h, g) = w_h^\top \phi(s, a) - r(s, a) - \max_{a'} w_{h+1}^\top \phi(s', a'),$$

for any distribution $\nu \in \Delta(\mathcal{S} \times \mathcal{A})$, with probability $1 - \delta$ over randomness of the m i.i.d triples $\{s_i, a_i, s'_i\}_{i=1}^m$ with $s_i, a_i \sim \nu, s'_i \sim P_h(\cdot | s_i, a_i)$, we have:

$$\max_{g \in \mathcal{H}} \left| \mathbb{E}_{s \sim \nu, a \sim \text{Unif}_{\mathcal{A}}, s' \sim P_h(\cdot | s, a)} [\ell(s, a, s', h, g)] - \sum_{i=1}^m \ell(s_i, a_i, s'_i, h, g) / m \right| \leq 3H \sqrt{\frac{2d \ln(1 + 4Wm) + \ln(1/\delta)}{m}}.$$

Proof. The proof uses the standard ϵ -net argument. Define $\mathcal{N}_\epsilon$ as the ϵ -net for $\mathcal{W} = \{w : w \in \mathbb{R}^d, \|w\|_2 \leq W, w^\top \phi(\cdot, \cdot) \in \mathcal{H}\}$. Standard ϵ -net argument shows that $|\mathcal{N}_\epsilon| \leq (1 + W/\epsilon)^d$. Denote $g' = \{(w'_h)^\top \phi\}_{h=0}^{H-1}$, we have:

$$\begin{aligned} |\ell(s, a, s', h, g) - \ell(s, a, s', h, g')| &\leq \frac{\mathbf{1}\{\pi_{h,g}(s) = a\}}{1/A} \left[|w_h^\top \phi(s, a) - (w'_h)^\top \phi(s, a)| + \max_{a'} |w_{h+1}^\top \phi(s', a') - (w'_{h+1})^\top \phi(s', a')| \right] \\ &\leq A \sup_{s, a} |w_h^\top \phi(s, a) - (w'_h)^\top \phi(s, a)| + A \sup_{s, a} |w_{h+1}^\top \phi(s, a) - (w'_{h+1})^\top \phi(s, a)| \\ &\leq A \|w_h - w'_h\|_2 + A \|w_{h+1} - w'_{h+1}\|_2. \end{aligned}$$

Thus, if $\|w_h - w'_h\|_2 \leq \epsilon, \|w_{h+1} - w'_{h+1}\|_2 \leq \epsilon$, we have $|\ell(s, a, s', h, g) - \ell(s, a, s', h, g')| \leq 2A\epsilon$.

Consider a $w_h \in \mathcal{N}_\epsilon, w_{h+1} \in \mathcal{N}_\epsilon$, via Hoeffding's inequality, we have that with probability at least $1 - \delta$:

$$|\mathbb{E}[\ell(s, a, s', h, (w_h, w_{h+1}))] - \bar{\mathbb{E}}[\ell(s, a, s', h, (w_h, w_{h+1}))]| \leq 2HA \sqrt{\ln(1/\delta)/m}.$$

where for notation simplicity, we denote $\bar{\mathbb{E}}$ as the empirical average over the m data triples. Apply a union bound over all $w_h \in \mathcal{N}_\epsilon$ and $w_{h+1} \in \mathcal{N}_\epsilon$, we have that with probability at least $1 - \delta$:

$$\forall w_h \in \mathcal{N}_\epsilon, w_{h+1} \in \mathcal{N}_\epsilon : |\mathbb{E}[\ell(s, a, s', h, (w_h, w_{h+1}))] - \bar{\mathbb{E}}[\ell(s, a, s', h, (w_h, w_{h+1}))]| \leq 2HA \sqrt{2 \ln(|\mathcal{N}_\epsilon|/\delta)/m}.$$

Thus for any $w_h \in \mathcal{W}, w_{h+1} \in \mathcal{W}$, we have:

$$|\mathbb{E}[\ell(s, a, s', h, (w_h, w_{h+1}))] - \bar{\mathbb{E}}[\ell(s, a, s', h, (w_h, w_{h+1}))]| \leq 2HA \sqrt{2 \ln(|\mathcal{N}_\epsilon|/\delta)/m} + 4A\epsilon.$$

Set $\epsilon = 1/(4Am)$, we have:

$$\begin{aligned} |\mathbb{E}[\ell(s, a, s', h, (w_h, w_{h+1}))] - \bar{\mathbb{E}}[\ell(s, a, s', h, (w_h, w_{h+1}))]| &\leq 2HA \sqrt{(2d \ln(1 + 4AWm) + \ln(1/\delta))/m} + 1/m \\ &\leq 3HA \sqrt{\frac{2d \ln(1 + 4AWm) + \ln(1/\delta)}{m}}. \end{aligned}$$

This proves the first claim in the lemma.

The second claim in the lemma can be proved in a similar way, noting that without the importance weighting term on the loss ℓ , we have:

$$|\ell(s, a, s', h, g) - \ell(s, a, s', h, g')| \leq \|w_h - w'_h\|_2 + \|w_{h+1} - w'_{h+1}\|_2.$$

□

Appendix B

Linearly realizable Q^* is exponentially hard

This appendix records a (trajectory-tree) hard instance in which Q^* is *exactly* linear in a given feature map, yet identifying a near-optimal policy requires exponentially many queries in $\min\{d, H\}$ (once the action set is taken to be exponentially large in d).

Theorem B.1 (Linear Q^* realizability can be exponentially hard (generative model)). *Fix integers $d \geq 1$ and $H \geq 1$. Consider any algorithm $\mathcal{A}$ that has access to a generative model and is given as input a feature map $\phi : \mathcal{S} \times \mathcal{A} \times [H] \rightarrow \mathbb{R}^d$. There exist absolute constants $c, C > 0$ and a finite-horizon MDP M with horizon H and action set size $|\mathcal{A}| = \exp(cd)$, together with a feature map ϕ , such that Assumption 3.9 holds (i.e. for each $h \in [H]$, $Q_h^*(\cdot, \cdot)$ is linear in $\phi(\cdot, \cdot, h)$), and the following is true.*

If $\mathcal{A}$ outputs a policy π satisfying

$$V_0^\pi(s_0) \geq V_0^*(s_0) - 0.05$$

with probability at least 0.1, then $\mathcal{A}$ must make at least

$$\exp(\Omega(\min\{d, H\}))$$

calls to the generative model.

The construction presented here follows from that in Weisz et al. [2021a].

B.1 Construction

Fix a horizon $H \geq 1$ and a feature dimension d . Let $\rho \in (0, 1/6]$ be a constant and set $A := |\mathcal{A}|$.

Nearly orthogonal vectors. Assume we are given unit vectors $\{v(a)\}_{a \in [A]} \subset \mathbb{R}^d$ such that

$$\forall a \neq a', \quad |\langle v(a), v(a') \rangle| \leq \rho.$$

Such a set exists for $A \leq \exp(c_0 \rho^2 d)$ for an absolute constant c_0 (e.g. a standard spherical packing / JL-type argument). We will take $A = \lfloor \exp(cd) \rfloor$ with c small enough.

State space. For each layer $h \in \{0, 1, \dots, H\}$, define the set of nonterminal states

$$\mathcal{S}_h^{\text{nt}} := \{\overline{a_{1:h}} : a_1, \dots, a_h \in [A] \text{ are all distinct}\},$$

with $\mathcal{S}_0^{\text{nt}} = \{\bar{\emptyset}\}$. Let f be an absorbing terminal state and set $\mathcal{S}_h := \mathcal{S}_h^{\text{nt}} \cup \{f\}$. The action space is $\mathcal{A} = [A]$, and the initial state is $s_0 = \bar{\emptyset}$.

MDP family. The family is indexed by $a^* \in [A]$. We write $\mathcal{M}_{a^*}$ for the MDP with distinguished index a^* .

Transitions. For each $h \leq H-1$: if $s_h = f$ then $s_{h+1} = f$ surely. If $s_h = \overline{a_{1:h}}$ is nonterminal and the agent chooses $a \in [A]$, then

$$s_{h+1} := \begin{cases} f, & a \in \{a_1, \dots, a_h\} \quad (\text{repeat an action already on the path}) \\ f, & a = a^* \quad (\text{the distinguished action}) \\ \overline{a_{1:h}a}, & \text{otherwise.} \end{cases}$$

Thus along any *nonterminal* trajectory, actions are distinct and never equal to a^* .

Bias sequence. Set $b_0 := 1$ and define recursively for $h = 0, 1, \dots, H-1$,

$$b_{h+1} := 3\rho b_h, \quad \text{so that} \quad b_h = (3\rho)^h,$$

and note $3\rho \leq 1/2$ when $\rho \leq 1/6$.

Feature map. Define $\phi_h : \mathcal{S}_h \times \mathcal{A} \rightarrow \mathbb{R}^d$ recursively as follows. For the terminal state, set $\phi_h(f, a) = 0$ for all h and a . For the root,

$$\phi_0(\bar{\emptyset}, a_1) := b_0 v(a_1) = v(a_1).$$

For $h \geq 1$ and a nonterminal state $s_h = \overline{a_{1:h}}$, define for each $a \in [A]$,

$$\phi_h(\overline{a_{1:h}}, a) := \begin{cases} 0, & a \in \{a_1, \dots, a_h\} \\ \left(\langle \phi_{h-1}(\overline{a_{1:h-1}}, a_h), v(a) \rangle + b_h \right) v(a), & a \notin \{a_1, \dots, a_h\}. \end{cases}$$

We view the global feature map as $\phi(s, a, h) := \phi_h(s, a)$.

Candidate parameter and Q . Fix $a^* \in [A]$ and set $\theta^* := v(a^*)$. Define

$$\tilde{Q}_h(s, a) := \langle \phi_h(s, a), \theta^* \rangle, \quad h = 0, 1, \dots, H-1,$$

and $\tilde{V}_h(s) := \max_{a \in \mathcal{A}} \tilde{Q}_h(s, a)$, with $\tilde{V}_H \equiv 0$.

Mean rewards. Define deterministic mean rewards $r_h : \mathcal{S}_h \times \mathcal{A} \rightarrow \mathbb{R}$ as follows. For each $h = 0, 1, \dots, H-2$,

$$r_h(s, a) := \begin{cases} \tilde{Q}_h(s, a), & \text{if the transition sends } s_{h+1} = f, \\ -b_{h+1}, & \text{if the transition sends } s_{h+1} \in \mathcal{S}_{h+1}^{\text{nt}}. \end{cases}$$

For the last layer $h = H-1$, set

$$r_{H-1}(s, a) := \tilde{Q}_{H-1}(s, a).$$

Observed rewards (Gaussian noise). When the learner queries (s, a, h) , the generative model returns the next state according to the deterministic transition above and a noisy reward

$$R_h = r_h(s, a) + \xi_h, \quad \xi_h \sim \mathcal{N}(0, 1) \text{ i.i.d.},$$

independently across all queries.

B.2 Key inequalities: a^* is greedy everywhere

Lemma B.2 (Fresh-direction correlation bound). *For any $t \in \{0, 1, \dots, H-1\}$, any nonterminal $\overline{a_{1:t}} \in \mathcal{S}_t^{\text{nt}}$, any action $a_{t+1} \notin \{a_1, \dots, a_t\}$, and any $a' \notin \{a_1, \dots, a_t, a_{t+1}\}$, we have*

$$|\langle \phi_t(\overline{a_{1:t}}, a_{t+1}), v(a') \rangle| \leq \frac{1}{2} b_{t+1}.$$

Proof. We proceed by induction on t .

Base case $t = 0$. $\phi_0(\overline{\emptyset}, a_1) = v(a_1)$, hence for $a' \neq a_1$,

$$|\langle \phi_0(\overline{\emptyset}, a_1), v(a') \rangle| = |\langle v(a_1), v(a') \rangle| \leq \rho = \frac{1}{3} b_1 \leq \frac{1}{2} b_1,$$

since $b_1 = 3\rho$.

Inductive step. Assume the claim holds for $t-1 \geq 0$. Let $a' \notin \{a_1, \dots, a_{t+1}\}$. By definition (and since a_{t+1} is not a repeat),

$$\phi_t(\overline{a_{1:t}}, a_{t+1}) = \left(\langle \phi_{t-1}(\overline{a_{1:t-1}}, a_t), v(a_{t+1}) \rangle + b_t \right) v(a_{t+1}).$$

Thus

$$\begin{aligned} |\langle \phi_t(\overline{a_{1:t}}, a_{t+1}), v(a') \rangle| &= |\langle v(a_{t+1}), v(a') \rangle| \left| \langle \phi_{t-1}(\overline{a_{1:t-1}}, a_t), v(a_{t+1}) \rangle + b_t \right| \\ &\leq \rho \left(\frac{1}{2} b_t + b_t \right) = \frac{3}{2} \rho b_t = \frac{1}{2} b_{t+1}, \end{aligned}$$

using the induction hypothesis (with $a' = a_{t+1}$ at level $t-1$) and the recursion $b_{t+1} = 3\rho b_t$. $\square$

Lemma B.3 (Greedy action is a^* everywhere). *For every $h \in \{0, 1, \dots, H-1\}$ and every nonterminal state $s_h \in \mathcal{S}_h^{\text{nt}}$,*

$$\tilde{Q}_h(s_h, a^*) \geq \frac{1}{2} b_h \quad \text{and} \quad \max_{a \neq a^*} \tilde{Q}_h(s_h, a) \leq \frac{1}{4} b_h,$$

hence $a^* \in \arg\max_a \tilde{Q}_h(s_h, a)$.

Proof. Fix h and $s_h = \overline{a_{1:h}} \in \mathcal{S}_h^{\text{nt}}$.

Lower bound for a^ .* If $h = 0$, then $\tilde{Q}_0(\overline{\emptyset}, a^*) = \langle v(a^*), v(a^*) \rangle = 1 = b_0$. If $h \geq 1$, then along any nonterminal path we have $a^* \notin \{a_1, \dots, a_h\}$, so

$$\tilde{Q}_h(s_h, a^*) = \langle \phi_h(s_h, a^*), v(a^*) \rangle = \langle \phi_{h-1}(\overline{a_{1:h-1}}, a_h), v(a^*) \rangle + b_h.$$

By Lemma B.2 applied at time $t = h-1$ with $a_{t+1} = a_h$ and $a' = a^*$, $|\langle \phi_{h-1}(\overline{a_{1:h-1}}, a_h), v(a^*) \rangle| \leq \frac{1}{2} b_h$. Hence $\tilde{Q}_h(s_h, a^*) \geq \frac{1}{2} b_h$.

Upper bound for $a \neq a^*$. Let $a \neq a^*$. If $a \in \{a_1, \dots, a_h\}$, then $\phi_h(s_h, a) = 0$ by construction, so $\tilde{Q}_h(s_h, a) = 0 \leq \frac{1}{4}b_h$.

Otherwise $a \notin \{a_1, \dots, a_h\}$, and

$$\tilde{Q}_h(s_h, a) = \langle \phi_h(s_h, a), v(a^*) \rangle = \left(\langle \phi_{h-1}(\overline{a_{1:h-1}}, a_h), v(a) \rangle + b_h \right) \langle v(a), v(a^*) \rangle.$$

By Lemma B.2 (with $t = h - 1$, $a_{t+1} = a_h$, $a' = a$), $|\langle \phi_{h-1}(\overline{a_{1:h-1}}, a_h), v(a) \rangle| \leq \frac{1}{2}b_h$. Also $|\langle v(a), v(a^*) \rangle| \leq \rho$. Therefore,

$$\tilde{Q}_h(s_h, a) \leq \left(\frac{1}{2}b_h + b_h \right) \rho = \frac{3}{2}\rho b_h \leq \frac{1}{4}b_h,$$

using $\rho \leq 1/6$. □

B.3 Realizability and Bellman optimality

Lemma B.4 (Bellman optimality of $\tilde{Q}$). *In $\mathcal{M}_{a^*}$, the function $\tilde{Q}$ satisfies the Bellman optimality equations: for all $h \in \{0, \dots, H - 1\}$ and $(s, a) \in \mathcal{S}_h \times \mathcal{A}$,*

$$\tilde{Q}_h(s, a) = r_h(s, a) + \mathbb{E} \left[\tilde{V}_{h+1}(s_{h+1}) \mid s_h = s, a_h = a \right].$$

Consequently, $\tilde{Q} = Q^*$ and the greedy policy is optimal.

Proof. We verify the Bellman equation case-by-case.

If $h = H - 1$, then $\tilde{V}_H \equiv 0$ and $r_{H-1}(s, a) = \tilde{Q}_{H-1}(s, a)$ by definition.

Now fix $h \leq H - 2$. If the transition sends $s_{h+1} = f$, then $\tilde{V}_{h+1}(f) = 0$ and $r_h(s, a) = \tilde{Q}_h(s, a)$ by definition.

Otherwise $s_{h+1} \in \mathcal{S}_{h+1}^{\text{nt}}$. By Lemma B.3, the greedy action at s_{h+1} is a^* , hence

$$\tilde{V}_{h+1}(s_{h+1}) = \tilde{Q}_{h+1}(s_{h+1}, a^*) = \langle \phi_{h+1}(s_{h+1}, a^*), \theta^* \rangle.$$

By the feature recursion and $\theta^* = v(a^*)$,

$$\langle \phi_{h+1}(s_{h+1}, a^*), \theta^* \rangle = \langle \phi_h(s, a), \theta^* \rangle + b_{h+1} = \tilde{Q}_h(s, a) + b_{h+1}.$$

Therefore, using $r_h(s, a) = -b_{h+1}$ on this branch,

$$r_h(s, a) + \tilde{V}_{h+1}(s_{h+1}) = (-b_{h+1}) + (\tilde{Q}_h(s, a) + b_{h+1}) = \tilde{Q}_h(s, a).$$

This establishes Bellman optimality, hence $\tilde{Q} = Q^*$. □

B.4 Proof sketch of Theorem B.1

Proof sketch of Theorem B.1. We instantiate M as $\mathcal{M}_{a^*}$ with a^* drawn uniformly from $[A]$. The feature map ϕ is shared across all instances; the instance index a^* only appears through the parameter $\theta^* = v(a^*)$ (and hence through the mean rewards $r_h(s, a) = \langle \phi_h(s, a), \theta^* \rangle$ at the last layer and on terminal transitions).

Step 1: Near-optimality forces identifying a^* at the root. By Lemma B.3, at the start state $s_0 = \bar{\emptyset}$ we have

$$Q_0^*(s_0, a^*) = \tilde{Q}_0(s_0, a^*) = 1, \quad \max_{a \neq a^*} Q_0^*(s_0, a) = \max_{a \neq a^*} \tilde{Q}_0(s_0, a) \leq \rho \leq \frac{1}{6}.$$

Thus any policy that fails to choose a^* at s_0 suffers a constant value gap (at least $1 - \rho \geq 5/6$ at the root). In particular, producing a 0.05-optimal policy with constant probability requires outputting a^* at s_0 with constant probability, i.e. identifying a^* with constant probability.

Step 2: Unless the algorithm ever queries a^* before the last layer, the transcript depends on a^* only through last-layer rewards. Let Z denote the full transcript of T generative-model queries and observations. Define the event

$$E := \{\text{the algorithm makes at least one query with action } a = a^* \text{ at some } h \leq H - 2\}.$$

We claim that on the complementary event E^c , all observations from layers $h \leq H - 2$ are independent of a^* . Indeed, fix any query (s, a, h) with $h \leq H - 2$ and $a \neq a^*$:

- If a repeats an action already on the path encoded by s , then by construction $\phi_h(s, a) = 0$, the next state is f , and the (mean) reward is $r_h(s, a) = \tilde{Q}_h(s, a) = 0$, independent of a^* .
- Otherwise (a fresh action $a \neq a^*$), the transition is to a nonterminal state and the mean reward is the constant $r_h(s, a) = -b_{h+1}$, again independent of a^* .

Thus, conditioned on E^c , the only dependence of Z on a^* comes from queries at the last layer $h = H - 1$ (where the mean reward is $\tilde{Q}_{H-1}(s, a) = \langle \phi_{H-1}(s, a), \theta^* \rangle$).

Step 3: Hitting a^* early costs $\Omega(A)$ queries. Let N_{a^*} be the number of times the algorithm queries action a^* at layers $h \leq H - 2$. Then $\mathbf{1}_E \leq N_{a^*}$, so

$$\Pr(E) \leq \mathbb{E}[N_{a^*}].$$

Averaging over the uniform draw of a^* and using $\sum_{a=1}^A N_a \leq T$,

$$\mathbb{E}[N_{a^*}] = \frac{1}{A} \sum_{a=1}^A \mathbb{E}[N_a] \leq \frac{T}{A}.$$

Hence if $T \ll A$, then $\Pr(E)$ is small: with high probability the algorithm never queries a^* at any layer $h \leq H - 2$.

Step 4: Conditioned on E^c , learning a^* from last-layer “leakage” costs $\Omega((\log A)/b_{H-1}^2)$ queries. On E^c , the entire a^* -dependence comes from last-layer reward observations. In our construction rewards are observed with i.i.d. $\mathcal{N}(0, 1)$ noise, so each last-layer query yields an observation distributed as $\mathcal{N}(\mu_{a^*}, 1)$ where $\mu_{a^*} = \langle \phi_{H-1}(s, a), v(a^*) \rangle$.

Moreover, by the feature recursion and Lemma B.2, whenever $\phi_{H-1}(s, a) \neq 0$ its norm is on the order of b_{H-1} (in fact $\|\phi_{H-1}(s, a)\|_2 \leq \frac{3}{2}b_{H-1}$), so for any two instances $a^* \neq a^{*'}$ and any fixed last-layer query we have

$$|\mu_{a^*} - \mu_{a^{*'}}| = |\langle \phi_{H-1}(s, a), v(a^*) - v(a^{*'}) \rangle| \leq 3b_{H-1}.$$

Thus the per-query KL divergence between the two corresponding Gaussians is

$$\text{KL}(\mathcal{N}(\mu_{a^*}, 1) \parallel \mathcal{N}(\mu_{a^{*'}}, 1)) = \frac{(\mu_{a^*} - \mu_{a^{*'}})^2}{2} \leq O(b_{H-1}^2).$$

By the chain rule for KL (or mutual information) and adaptivity, the total information in T queries satisfies $\text{KL}(P_{a^*}^Z \parallel P_{a^{*'}}^Z) \leq O(Tb_{H-1}^2)$ for all $a^* \neq a^{*'}$. A standard Fano-type bound then implies that to identify a^* among A possibilities with constant probability, it is necessary that

$$T \gtrsim \frac{\log A}{b_{H-1}^2}.$$

Since $b_{H-1} = (3\rho)^{H-1} \leq 2^{-(H-1)}$ (for $\rho \leq 1/6$), this term is $\exp(\Omega(H))$ up to polynomial factors.

Step 5: Combine and conclude. Putting Steps 3–4 together yields a lower bound of the form

$$T \geq \Omega\left(\min\left\{A, \frac{\log A}{b_{H-1}^2}\right\}\right).$$

With $A = \exp(\Theta(d))$ (from the packing argument) and $b_{H-1} = (3\rho)^{H-1}$, this implies

$$T \geq \exp(\Omega(\min\{d, H\})) \quad (\text{up to polynomial factors}).$$

In particular, taking $H = \Theta(d)$ recovers $T \geq \exp(\Omega(d))$ as stated. By Step 1, such a sample size is necessary for producing a 0.05-optimal policy with constant probability. $\square$

Bibliography

- Yasin Abbasi-Yadkori and Csaba Szepesvári. Regret bounds for the adaptive control of linear quadratic systems. In *Conference on Learning Theory*, pages 1–26, 2011.
- Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. In *Advances in Neural Information Processing Systems*, pages 2312–2320, 2011.
- Yasin Abbasi-Yadkori, Peter Bartlett, Kush Bhatia, Nevena Lazic, Csaba Szepesvari, and Gellért Weisz. POLITEX: Regret bounds for policy iteration using expert prediction. In *International Conference on Machine Learning*, pages 3692–3702, 2019.
- Naoki Abe and Philip M. Long. Associative reinforcement learning using linear probabilistic concepts. In *Proc. 16th International Conf. on Machine Learning*, pages 3–11. Morgan Kaufmann, San Francisco, CA, 1999.
- Alekh Agarwal, Mikael Henaff, Sham Kakade, and Wen Sun. Pc-pg: Policy cover directed exploration for provable policy gradient learning. *NeurIPS*, 2020a.
- Alekh Agarwal, Sham Kakade, Akshay Krishnamurthy, and Wen Sun. Flambe: Structural complexity and representation learning of low rank mdps. *NeurIPS*, 2020b.
- Alekh Agarwal, Sham Kakade, and Lin F. Yang. Model-based reinforcement learning with a generative model is minimax optimal. In *COLT*, volume 125, pages 67–83, 2020c.
- Alekh Agarwal, Sham M. Kakade, Jason D. Lee, and Gaurav Mahajan. On the theory of policy gradient methods: Optimality, approximation, and distribution shift, 2020d.
- Naman Agarwal, Brian Bullins, Elad Hazan, Sham M Kakade, and Karan Singh. Online control with adversarial disturbances. *arXiv preprint arXiv:1902.08721*, 2019.
- Zafarali Ahmed, Nicolas Le Roux, Mohammad Norouzi, and Dale Schuurmans, editors. *Understanding the impact of entropy on policy optimization*, 2019. URL <https://arxiv.org/abs/1811.11214>.
- Hyo-Sung Ahn, YangQuan Chen, and Kevin L. Moore. Iterative learning control: Brief survey and categorization. *IEEE Transactions on Systems, Man, and Cybernetics, Part C (Applications and Reviews)*, 37(6):1099–1121, 2007.
- Brian D. O. Anderson and John B. Moore. *Optimal Control: Linear Quadratic Methods*. Prentice-Hall, Inc., Upper Saddle River, NJ, USA, 1990. ISBN 0-13-638560-5.
- András Antos, Csaba Szepesvári, and Rémi Munos. Learning near-optimal policies with bellman-residual minimization based fitted policy iteration and a single sample path. *Machine Learning*, 71(1):89–129, 2008.
- P. Auer, N. Cesa-Bianchi, and P. Fischer. Finite-time analysis of the multiarmed bandit problem. *Mach. Learn.*, 47(2-3):235–256, 2002. ISSN 0885-6125.

- Alex Ayoub, Zeyu Jia, Csaba Szepesvari, Mengdi Wang, and Lin Yang. Model-based reinforcement learning with value-targeted regression. In *International Conference on Machine Learning*, pages 463–474. PMLR, 2020a.
- Alex Ayoub, Zeyu Jia, Csaba Szepesvári, Mengdi Wang, and Lin F. Yang. Model-based reinforcement learning with value-targeted regression. *arXiv preprint arXiv:2006.01107*, 2020b. URL <https://arxiv.org/abs/2006.01107>.
- Mohammad Gheshlaghi Azar, Rémi Munos, and Hilbert J Kappen. Minimax pac bounds on the sample complexity of reinforcement learning with a generative model. *Machine learning*, 91(3):325–349, 2013.
- Mohammad Gheshlaghi Azar, Ian Osband, and Rémi Munos. Minimax regret bounds for reinforcement learning. In Doina Precup and Yee Whye Teh, editors, *Proceedings of Machine Learning Research*, volume 70, pages 263–272, International Convention Centre, Sydney, Australia, 06–11 Aug 2017. PMLR.
- J. Andrew Bagnell and Jeff Schneider. Covariant policy search. *Proceedings of the 18th International Joint Conference on Artificial Intelligence*, pages 1019–1024, 2003. URL <http://dl.acm.org/citation.cfm?id=1630659.1630805>.
- J Andrew Bagnell, Sham M Kakade, Jeff G Schneider, and Andrew Y Ng. Policy search by dynamic programming. In *Advances in neural information processing systems*, pages 831–838, 2004.
- V. Balakrishnan and L. Vandenberghe. Semidefinite programming duality and linear time-invariant systems. *IEEE Transactions on Automatic Control*, 48(1):30–41, 2003.
- A. Beck. *First-Order Methods in Optimization*. Society for Industrial and Applied Mathematics, Philadelphia, PA, 2017. doi: 10.1137/1.9781611974997.
- Richard Bellman. Dynamic programming and Lagrange multipliers. *Proceedings of the National Academy of Sciences*, 42(10):767–769, 1956.
- Richard Bellman and Stuart Dreyfus. Functional approximations and dynamic programming. *Mathematical Tables and Other Aids to Computation*, 13(68):247–251, 1959.
- Dimitri P. Bertsekas. *Dynamic Programming and Optimal Control*. Athena Scientific, 2017.
- Ronen I Brafman and Moshe Tennenholtz. R-max-a general polynomial time algorithm for near-optimal reinforcement learning. *Journal of Machine Learning Research*, 3(Oct):213–231, 2002.
- Kianté Brantley, Wen Sun, and Mikael Henaff. Disagreement-regularized imitation learning. In *International Conference on Learning Representations*, 2019.
- Kai-Wei Chang, Akshay Krishnamurthy, Alekh Agarwal, Hal Daume, and John Langford. Learning to search better than your teacher. In *International Conference on Machine Learning*, pages 2058–2066. PMLR, 2015.
- Jinglin Chen and Nan Jiang. Information-theoretic considerations in batch reinforcement learning. In *International Conference on Machine Learning*, pages 1042–1051, 2019.
- Ching-An Cheng and Byron Boots. Convergence of value aggregation for imitation learning. *arXiv preprint arXiv:1801.07292*, 2018.
- Ching-An Cheng, Xinyan Yan, Nolan Wagener, and Byron Boots. Fast policy learning through imitation and reinforcement. *arXiv preprint arXiv:1805.10413*, 2018.
- Ching-An Cheng, Andrey Kolobov, and Alekh Agarwal. Policy improvement from multiple experts. *arXiv preprint arXiv:2007.00795*, 2020.
- Alon Cohen, Tomer Koren, and Yishay Mansour. Learning linear-quadratic regulators efficiently with only $\sqrt{T}$ regret. In *International Conference on Machine Learning*, pages 1300–1309, 2019.

- Varsha Dani, Thomas P Hayes, and Sham M Kakade. Stochastic linear optimization under bandit feedback. In *COLT*, pages 355–366, 2008.
- Christoph Dann and Emma Brunskill. Sample complexity of episodic fixed-horizon reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 2818–2826, 2015.
- Christoph Dann, Tor Lattimore, and Emma Brunskill. Unifying pac and regret: Uniform pac bounds for episodic reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 5713–5723, 2017.
- Hal Daumé, John Langford, and Daniel Marcu. Search-based structured prediction. *Machine learning*, 75(3):297–325, 2009.
- S. Dean, H. Mania, N. Matni, B. Recht, and S. Tu. On the sample complexity of the linear quadratic regulator. *ArXiv e-prints*, 2017.
- Sarah Dean, Horia Mania, Nikolai Matni, Benjamin Recht, and Stephen Tu. Regret bounds for robust adaptive control of the linear quadratic regulator. In *Advances in Neural Information Processing Systems*, pages 4188–4197, 2018.
- Luc Devroye and Gábor Lugosi. *Combinatorial methods in density estimation*. Springer Science & Business Media, 2012.
- Kefan Dong, Jian Peng, Yining Wang, and Yuan Zhou. Root-n-regret for learning in markov decision processes with function approximation and low bellman rank. In *Conference on Learning Theory*, pages 1554–1557. PMLR, 2020.
- Simon S Du, Sham M Kakade, Ruosong Wang, and Lin F Yang. Is a good representation sufficient for sample efficient reinforcement learning? In *International Conference on Learning Representations*, 2019.
- Simon S. Du, Sham M. Kakade, Jason D. Lee, Shachar Lovett, Gaurav Mahajan, Wen Sun, and Ruosong Wang. Bilinear classes: A structural framework for provable generalization in RL. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*. PMLR, 2021.
- Lawrence C. Evans. An introduction to mathematical optimal control theory. *University of California, Department of Mathematics*, page 126, 2005. ISSN 14712334.
- Eyal Even-Dar, Sham M Kakade, and Yishay Mansour. Online Markov decision processes. *Mathematics of Operations Research*, 34(3):726–736, 2009.
- Maryam Fazel, Rong Ge 0001, Sham M. Kakade, and Mehran Mesbahi. Global Convergence of Policy Gradient Methods for the Linear Quadratic Regulator. In *Proceedings of the 35th International Conference on Machine Learning*, pages 1466–1475. PMLR, 2018.
- Dylan J Foster and Max Simchowitz. Logarithmic regret for adversarial online control. *arXiv preprint arXiv:2003.00189*, 2020.
- Sara A Geer and Sara van de Geer. *Empirical Processes in M-estimation*, volume 6. Cambridge university press, 2000.
- Matthieu Geist, Bruno Scherrer, and Olivier Pietquin. A theory of regularized markov decision processes. *arXiv preprint arXiv:1901.11275*, 2019.
- Saeed Ghadimi and Guanghui Lan. Stochastic first- and zeroth-order methods for nonconvex stochastic programming. *SIAM Journal on Optimization*, 23(4):2341–2368, 2013.
- Peter W. Glynn. Likelihood ratio gradient estimation for stochastic systems. *Commun. ACM*, 33(10):75–84, 1990. ISSN 0001-0782.
- Gautam Goel and Babak Hassibi. The power of linear controllers in lqr control. *arXiv preprint arXiv:2002.02574*, 2020.

- László Györfi, Michael Kohler, Adam Krzyżak, and Harro Walk. A distribution-free theory of nonparametric regression. In *Springer Series in Statistics*, 2002.
- Botao Hao, Tor Lattimore, Csaba Szepesvári, and Mengdi Wang. Online sparse reinforcement learning. In *International Conference on Artificial Intelligence and Statistics*, pages 316–324. PMLR, 2021.
- Todd Hester, Matej Vecerik, Olivier Pietquin, Marc Lanctot, Tom Schaul, Bilal Piot, Dan Horgan, John Quan, Andrew Sendonaris, Gabriel Dulac-Arnold, et al. Deep q-learning from demonstrations. *arXiv preprint arXiv:1704.03732*, 2017.
- Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *Advances in neural information processing systems*, pages 4565–4573, 2016.
- Daniel Hsu, Sham Kakade, and Tong Zhang. A spectral algorithm for learning hidden markov models. *Journal of Computer and System Sciences*, 78, 11 2008.
- Thomas Jaksch, Ronald Ortner, and Peter Auer. Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research*, 11(Apr):1563–1600, 2010.
- Zeyu Jia, Lin Yang, Csaba Szepesvari, and Mengdi Wang. Model-based reinforcement learning with value-targeted regression. *Proceedings of Machine Learning Research*, 120:666–686, 2020.
- Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, John Langford, and Robert E. Schapire. Contextual decision processes with low Bellman rank are PAC-learnable. In *International Conference on Machine Learning*, 2017.
- Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I Jordan. Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, pages 2137–2143, 2020.
- Chi Jin, Qinghua Liu, and Sobhan Miryoosefi. Bellman eluder dimension: New rich classes of rl problems, and sample-efficient algorithms. *arXiv preprint arXiv:2102.00815*, 2021.
- Fritz John. Extremum problems with inequalities as subsidiary conditions. In *Studies and Essays : Courant Anniversary Volume*, pages 187–204. John Wiley & Sons : Interscience Division, 1948.
- S. Kakade. A natural policy gradient. In *NIPS*, 2001.
- Sham Kakade and John Langford. Approximately Optimal Approximate Reinforcement Learning. In *Proceedings of the 19th International Conference on Machine Learning*, volume 2, pages 267–274, 2002.
- Sham Machandranath Kakade. *On the sample complexity of reinforcement learning*. PhD thesis, University of College London, 2003.
- Liyiming Ke, Matt Barnes, Wen Sun, Gilwoo Lee, Sanjiban Choudhury, and Siddhartha Srinivasa. Imitation learning as f -divergence minimization. *arXiv preprint arXiv:1905.12888*, 2019.
- Michael Kearns and Daphne Koller. Efficient reinforcement learning in factored mdps. In *IJCAI*, volume 16, pages 740–747, 1999.
- Michael Kearns and Satinder Singh. Near-optimal reinforcement learning in polynomial time. *Machine Learning*, 49 (2-3):209–232, 2002.
- Michael J Kearns and Satinder P Singh. Finite-sample convergence rates for q-learning and indirect algorithms. In *Advances in neural information processing systems*, pages 996–1002, 1999.
- Michael J. Kearns, Yishay Mansour, and Andrew Y. Ng. Approximate planning in large pomdps via reusable trajectories. In S. A. Solla, T. K. Leen, and K. Müller, editors, *Advances in Neural Information Processing Systems 12*, pages 1001–1007. MIT Press, 2000.

- J. Kiefer and Jacob Wolfowitz. The equivalence of two extremum problems. *Canadian Journal of Mathematics*, 12: 363 – 366, 1960.
- Kris M Kitani, Brian D Ziebart, James Andrew Bagnell, and Martial Hebert. Activity forecasting. In *European Conference on Computer Vision*, pages 201–214. Springer, 2012.
- Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.
- Alessandro Lazaric, Mohammad Ghavamzadeh, and Rémi Munos. Analysis of classification-based policy iteration algorithms. *The Journal of Machine Learning Research*, 17(1):583–612, 2016.
- Hoang M Le, Nan Jiang, Alekh Agarwal, Miroslav Dudík, Yisong Yue, and Hal Daumé III. Hierarchical imitation and reinforcement learning. *arXiv preprint arXiv:1803.00590*, 2018.
- Sergey Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review. *arXiv preprint arXiv:1805.00909*, 2018.
- Sergey Levine and Pieter Abbeel. Learning neural network policies with guided policy search under unknown dynamics. In *Advances in Neural Information Processing Systems*, pages 1071–1079, 2014.
- Sergey Levine and Vladlen Koltun. Guided policy search. In *International Conference on Machine Learning*, pages 1–9, 2013.
- Gen Li, Yuting Wei, Yuejie Chi, Yuntao Gu, and Yuxin Chen. Breaking the sample size barrier in model-based reinforcement learning with a generative model. *CoRR*, abs/2005.12900, 2020.
- Boyi Liu, Qi Cai, Zhuoran Yang, and Zhaoran Wang. Neural proximal/trust region policy optimization attains globally optimal policy. *CoRR*, abs/1906.10306, 2019. URL <http://arxiv.org/abs/1906.10306>.
- Thodoris Lykouris, Max Simchowitz, Aleksandrs Slivkins, and Wen Sun. Corruption robust exploration in episodic reinforcement learning. *arXiv preprint arXiv:1911.08689*, 2019.
- Horia Mania, Stephen Tu, and Benjamin Recht. Certainty equivalent control of LQR is efficient. *arXiv preprint arXiv:1902.07826*, 2019.
- Yishay Mansour and Satinder Singh. On the complexity of policy iteration. *UAI*, 01 1999.
- C. McDiarmid. On the method of bounded differences. In *Surveys in Combinatorics*, pages 148–188. Cambridge University Press, 1989.
- Jincheng Mei, Chenjun Xiao, Csaba Szepesvari, and Dale Schuurmans. On the global convergence rates of softmax policy gradient methods, 2020.
- Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pages 1928–1937, 2016.
- Aditya Modi, Nan Jiang, Ambuj Tewari, and Satinder Singh. Sample complexity of reinforcement learning using linearly combined model ensembles. In *International Conference on Artificial Intelligence and Statistics*, pages 2010–2020. PMLR, 2020a.
- Aditya Modi, Nan Jiang, Ambuj Tewari, and Satinder P. Singh. Sample complexity of reinforcement learning using linearly combined model ensembles. In *The 23rd International Conference on Artificial Intelligence and Statistics, AISTATS*, volume 108 of *Proceedings of Machine Learning Research*, 2020b.
- Aditya Modi, Jinglin Chen, Akshay Krishnamurthy, Nan Jiang, and Alekh Agarwal. Model-free representation learning and exploration in low-rank mdps. *arXiv preprint arXiv:2102.07035*, 2021.

- Rémi Munos. Error bounds for approximate policy iteration. In *ICML*, volume 3, pages 560–567, 2003.
- Rémi Munos. Error bounds for approximate value iteration. In *AAAI*, 2005.
- Gergely Neu, Anders Jonsson, and Vicenç Gómez. A unified view of entropy-regularized markov decision processes. *CoRR*, abs/1705.07798, 2017.
- Ian Osband and Benjamin Van Roy. Model-based reinforcement learning and the eluder dimension. In *Proceedings of the 27th International Conference on Neural Information Processing Systems-Volume 1*, pages 1466–1474, 2014.
- Ian Osband and Benjamin Van Roy. On lower bounds for regret in reinforcement learning. *ArXiv*, abs/1608.02732, 2016.
- Alejandro Perez, Robert Platt, George Konidaris, Leslie Kaelbling, and Tomas Lozano-Perez. LQR-RRT*: Optimal sampling-based motion planning with automatically derived extension heuristics. In *IEEE International Conference on Robotics and Automation*, pages 2537–2542, 2012.
- Jan Peters and Stefan Schaal. Natural actor-critic. *Neurocomput.*, 71(7-9):1180–1190, 2008. ISSN 0925-2312.
- Dean A Pomerleau. Alvin: An autonomous land vehicle in a neural network. In *Advances in neural information processing systems*, pages 305–313, 1989.
- Martin Puterman. *Markov Decision Processes: Discrete Stochastic Dynamic Programming*. Wiley-Interscience, 1994.
- Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning complex dexterous manipulation with deep reinforcement learning and demonstrations. *arXiv preprint arXiv:1709.10087*, 2017.
- H. Robbins. Some aspects of the sequential design of experiments. In *Bulletin of the American Mathematical Society*, volume 55, 1952.
- Stéphane Ross and Drew Bagnell. Efficient reductions for imitation learning. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 661–668, 2010.
- Stephane Ross and J Andrew Bagnell. Reinforcement and imitation learning via interactive no-regret learning. *arXiv preprint arXiv:1406.5979*, 2014.
- Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pages 627–635, 2011.
- Daniel Russo and Benjamin Van Roy. Eluder dimension and the sample complexity of optimistic exploration. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 26. Curran Associates, Inc., 2013. URL <https://proceedings.neurips.cc/paper/2013/file/41bfd20a38bb1b0bec75acf0845530a7-Paper.pdf>.
- Bruno Scherrer. Approximate policy iteration schemes: a comparison. In *International Conference on Machine Learning*, pages 1314–1322, 2014.
- Bruno Scherrer and Matthieu Geist. Local policy search in a convex space and conservative policy iteration as boosted policy search. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pages 35–50. Springer, 2014.
- John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International Conference on Machine Learning*, pages 1889–1897, 2015.
- John Schulman, F. Wolski, Prafulla Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *ArXiv*, abs/1707.06347, 2017.

- Shai Shalev-Shwartz. Online learning and online convex optimization. *Foundations and Trends in Machine Learning*, 4(2):107–194, 2011.
- Claude E. Shannon. Programming a computer playing chess. *Philosophical Magazine*, Ser.7, 41(312), 1959.
- Aaron Sidford, Mengdi Wang, Xian Wu, Lin F. Yang, and Yinyu Ye. Near-optimal time and sample complexities for solving discounted markov decision process with a generative model. In *Advances in Neural Information Processing Systems 31*, 2018.
- Max Simchowitz and Dylan J Foster. Naive exploration is optimal for online LQR. *arXiv preprint arXiv:2001.09576*, 2020.
- Max Simchowitz, Horia Mania, Stephen Tu, Michael I Jordan, and Benjamin Recht. Learning without mixing: Towards a sharp analysis of linear system identification. In *COLT*, 2018.
- Max Simchowitz, Karan Singh, and Elad Hazan. Improper learning for non-stochastic control. *arXiv preprint arXiv:2001.09254*, 2020.
- Satinder Singh and Richard Yee. An upper bound on the loss from approximate optimal-value functions. *Machine Learning*, 16(3):227–233, 1994.
- Wen Sun, Arun Venkatraman, Geoffrey J Gordon, Byron Boots, and J Andrew Bagnell. Deeply aggravated: Differentiable imitation learning for sequential prediction. *arXiv preprint arXiv:1703.01030*, 2017.
- Wen Sun, J Andrew Bagnell, and Byron Boots. Truncated horizon policy search: Combining reinforcement learning & imitation learning. *arXiv preprint arXiv:1805.11240*, 2018.
- Wen Sun, Nan Jiang, Akshay Krishnamurthy, Alekh Agarwal, and John Langford. Model-based rl in contextual decision processes: Pac bounds and exponential improvements over model-free approaches. In *Conference on Learning Theory*, pages 2898–2933, 2019a.
- Wen Sun, Anirudh Vemula, Byron Boots, and J Andrew Bagnell. Provably efficient imitation learning from observation alone. *arXiv preprint arXiv:1905.10948*, 2019b.
- Richard S Sutton, David A McAllester, Satinder P Singh, and Yishay Mansour. Policy gradient methods for reinforcement learning with function approximation. In *Advances in Neural Information Processing Systems*, volume 99, pages 1057–1063, 1999.
- Csaba Szepesvári and Rémi Munos. Finite time bounds for sampling based fitted value iteration. In *Proceedings of the 22nd international conference on Machine learning*, pages 880–887. ACM, 2005.
- Russ Tedrake. LQR-trees: Feedback motion planning on sparse randomized trees. *The International Journal of Robotics Research*, 35, 2009.
- Emanuel Todorov and Weiwei Li. A generalized iterative LQG method for locally-optimal feedback control of constrained nonlinear stochastic systems. In *American Control Conference*, pages 300–306, 2005.
- Masatoshi Uehara, Xuezhou Zhang, and Wen Sun. Representation learning for online and offline rl in low-rank mdps, 2021.
- Ruosong Wang, Dean P. Foster, and Sham M. Kakade. What are the statistical limits of offline rl with linear function approximation?, 2020a.
- Ruosong Wang, Russ R Salakhutdinov, and Lin Yang. Reinforcement learning with general value function approximation: Provably efficient approach via bounded eluder dimension. *Advances in Neural Information Processing Systems*, 33, 2020b.

- Yuanhao Wang, Ruosong Wang, and Sham M. Kakade. An exponential lower bound for linearly-realizable mdps with constant suboptimality gap. *CoRR*, abs/2103.12690, 2021. URL <https://arxiv.org/abs/2103.12690>.
- Yuh-Shyang Wang, Nikolai Matni, and John C Doyle. A system-level approach to controller synthesis. *IEEE Transactions on Automatic Control*, 64(10):4079–4093, 2019.
- Gellért Weisz, Philip Amortila, and Csaba Szepesvári. Exponential lower bounds for planning in mdps with linearly-realizable optimal action-value functions. In *Algorithmic Learning Theory, 16-19 March 2021, Virtual Conference, Worldwide*, volume 132 of *Proceedings of Machine Learning Research*, 2021a.
- Gellért Weisz, Csaba Szepesvári, and András György. Tensorplan and the few actions lower bound for planning in mdps under linear realizability of optimal value functions, 2021b.
- Zheng Wen and Benjamin Van Roy. Efficient reinforcement learning in deterministic systems with value function generalization. *Mathematics of Operations Research*, 42(3):762–782, 2017.
- Grady Williams, Andrew Aldrich, and Evangelos A. Theodorou. Model predictive path integral control: From theory to parallel computation. *Journal of Guidance, Control, and Dynamics*, 40(2):344–357, 2017.
- Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.
- Lin F Yang and Mengdi Wang. Reinforcement leaning in feature space: Matrix bandit, kernels, and regret bound. *arXiv preprint arXiv:1905.10389*, 2019a.
- Lin F. Yang and Mengdi Wang. Sample-optimal parametric q-learning using linearly additive features. In *International Conference on Machine Learning*, pages 6995–7004, 2019b.
- Yinyu Ye. A new complexity result on solving the markov decision problem. *Math. Oper. Res.*, 30:733–749, 08 2005.
- Yinyu Ye. The simplex and policy-iteration methods are strongly polynomial for the markov decision problem with a fixed discount rate. *Math. Oper. Res.*, 36(4):593–603, 2011.
- Ming Yin, Yu Bai, and Yu-Xiang Wang. Near optimal provable uniform convergence in off-policy evaluation for reinforcement learning. *ArXiv*, abs/2007.03760, 2021.
- Dante Youla, Hamid Jabr, and Jr Bongiorno. Modern wiener-hopf design of optimal controllers–part ii: The multi-variable case. *IEEE Transactions on Automatic Control*, 21(3):319–338, 1976.
- Andrea Zanette. Exponential lower bounds for batch reinforcement learning: Batch RL can be exponentially harder than online RL. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, Proceedings of Machine Learning Research. PMLR, 2021.
- Andrea Zanette, Alessandro Lazaric, Mykel Kochenderfer, and Emma Brunskill. Learning near optimal policies with low inherent bellman error. In *International Conference on Machine Learning*, pages 10978–10989. PMLR, 2020.
- Dongruo Zhou, Jiafan He, and Quanquan Gu. Provably efficient reinforcement learning for discounted mdps with feature mapping. *arXiv preprint arXiv:2006.13165*, 2020.
- Dongruo Zhou, Quanquan Gu, and Csaba Szepesvari. Nearly minimax optimal reinforcement learning for linear mixture markov decision processes. In *Conference on Learning Theory*, pages 4532–4576. PMLR, 2021a.
- Dongruo Zhou, Jiafan He, and Quanquan Gu. Provably efficient reinforcement learning for discounted mdps with feature mapping. In *International Conference on Machine Learning*, pages 12793–12802. PMLR, 2021b.
- Brian D Ziebart, Andrew L Maas, J Andrew Bagnell, and Anind K Dey. Maximum entropy inverse reinforcement learning. In *AAAI*, pages 1433–1438, 2008.

- Brian D Ziebart, Nathan Ratliff, Garratt Gallagher, Christoph Mertz, Kevin Peterson, J Andrew Bagnell, Martial Hebert, Anind K Dey, and Siddhartha Srinivasa. Planning-based prediction for pedestrians. In *2009 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 3931–3936. IEEE, 2009.
- Brian D Ziebart, J Andrew Bagnell, and Anind K Dey. Modeling interaction via the principle of maximum causal entropy. In *Proceedings of the 27th International Conference on Machine Learning (ICML-10)*. Carnegie Mellon University, 2010.
- Martin Zinkevich. Online convex programming and generalized infinitesimal gradient ascent. In *Proceedings of the 20th international conference on machine learning (icml-03)*, pages 928–936, 2003.