

OpenCode Installation and Configuration Guide

Complete Setup Documentation with Troubleshooting

Version: 1.0 | **Last Updated:** May 2026 | **Compatibility:** OpenCode 1.3.0+

Table of Contents

- 1. [Prerequisites](#)
- 2. [Installation](#)
- 3. [Initial Configuration](#)
- 4. [Provider Setup](#)
- 5. [Project Initialization](#)
- 6. [Configuration Files](#)
- 7. [MCP Servers \(Optional\)](#)
- 8. [Advanced Configuration](#)
- 9. [Verification](#)
- 10. [Comprehensive Troubleshooting](#)
- 11. [Reference Documentation](#)
- 12. [Quick Reference](#)

Prerequisites

Required Software

Before installing OpenCode, ensure you have:

1. Modern Terminal Emulator

Choose one of the following:

Terminal	Platform	Download Link
WezTerm	Cross-platform	https://wezterm.org
Alacritty	Cross-platform	https://alacritty.org
Ghostty	Linux, macOS	https://ghostty.org
Kitty	Linux, macOS	https://sw.kovidgoyal.net/kitty/
Windows Terminal	Windows	Built-in on Windows 11

Recommended for beginners: WezTerm (best cross-platform support)

2. Node.js (Required for npm installation)

- **Download:** <https://nodejs.org/>
- **Recommended:** Latest LTS version (20.x or higher)
- **Verify installation:**

```
node --version  
npm --version
```

3. Git (Optional but recommended)

- **Download:** <https://git-scm.com/downloads>
- **Verify installation:**

```
git --version
```

Windows-Specific Prerequisites

For Windows users, **Windows Subsystem for Linux (WSL)** is highly recommended:

Installing WSL 2

1. **Open PowerShell as Administrator** and run:

```
wsl --install
```

This installs Ubuntu by default.

2. **Restart your computer**

3. **Verify installation:**

```
wsl --list --verbose
```

4. **Update WSL** (if needed):

```
wsl --update
```

5. **Set WSL 2 as default:**

```
wsl --set-default-version 2
```

Why WSL?

- Better performance
- Full compatibility with OpenCode features
- Native Linux environment
- Seamless integration with Windows

Note: While OpenCode runs natively on Windows, WSL is the recommended approach for the best experience.

Installation

Quick Decision Guide

Method	Best For	Install Time
Quick Install Script	Most users, fastest setup	1-2 min
npm/pnpm/yarn	Node.js developers	2-3 min
Homebrew	macOS/Linux users	2-3 min
Chocolatey/Scoop	Windows users	2-3 min
Docker	Containerized environments	5 min
Binary Download	Offline or restricted environments	5-10 min

Method 1: Quick Install Script (Recommended)

macOS / Linux / WSL:

```
curl -fsSL https://opencode.ai/install | bash
```

What it does:

- Detects your operating system
- Downloads the appropriate binary
- Installs to `~/.local/bin/opencode`
- Adds to PATH automatically
- Verifies the installation

After installation:

```
# Restart your terminal, then verify
opencode --version
```

Method 2: Package Managers

Using npm (Cross-platform)

```
npm install -g opencode-ai
```

Using pnpm

```
pnpm install -g opencode-ai
```

Using Yarn

```
yarn global add opencode-ai
```

Using Bun

```
bun install -g opencode-ai
```

Using Homebrew (macOS/Linux)

Option A: OpenCode tap (recommended)

```
brew install anomalyco/tap/opencode
```

Option B: Official Homebrew formula

```
brew install opencode
```

Note: The OpenCode tap provides more frequent updates.

Update:

```
brew update && brew upgrade opencode
```

Arch Linux

Stable release:

```
sudo pacman -S opencode
```

Latest from AUR:

```
paru -S opencode-bin
```

Method 3: Windows-Specific Installers

Using Chocolatey

```
choco install opencode
```

Update:

```
choco upgrade opencode
```

Using Scoop

```
scoop install opencode
```

Update:

```
scoop update opencode
```

Using npm (Windows)

```
npm install -g opencode-ai
```

Method 4: Docker

```
# Run OpenCode in Docker
docker run -it --rm ghcr.io/anomalyco/opencode

# With volume mounting for persistence
docker run -it --rm \
  -v ~/.local/share/opencode:/root/.local/share/opencode \
  -v ~/.config/opencode:/root/.config/opencode \
  -v $(pwd):/workspace \
  ghcr.io/anomalyco/opencode
```

Method 5: Direct Binary Download

1. Visit **GitHub Releases**: <https://github.com/anomalyco/opencode/releases>

2. **Download the appropriate binary** for your platform:

- opencode-linux-x64
- opencode-macos-x64 or opencode-macos-arm64
- opencode-windows-x64.exe

3. **Extract and move to a directory in your PATH:**

macOS/Linux:

```
chmod +x opencode-*
sudo mv opencode-* /usr/local/bin/opencode
```

Windows:

- Move opencode.exe to C:\Program Files\opencode\
- Add to PATH via System Environment Variables

4. **Verify:**

```
opencode --version
```

Initial Configuration

First-Time Setup

1. **Verify installation:**

```
opencode --version
```

Expected output: `opencode version X.X.X`

2. **Launch OpenCode:**

```
opencode
```

You'll see the OpenCode TUI (Terminal User Interface).

3. **Explore built-in help:**

```
/help
```

Understanding OpenCode's Directory Structure

After first run, OpenCode creates these directories:

Directory	Purpose	Location
Config	Configuration files	~/.config/opencode/
Data	Auth tokens, cache	~/.local/share/opencode/
Agents	Custom agents	~/.config/opencode/agents/
Commands	Custom commands	~/.config/opencode/commands/
Plugins	Custom plugins	~/.config/opencode/plugins/
Themes	Custom themes	~/.config/opencode/themes/

Windows equivalents:

- Config: `%APPDATA%\opencode\`
- Data: `%LOCALAPPDATA%\opencode\`

Provider Setup

OpenCode requires an LLM provider to function. Choose based on your needs:

Provider Comparison

Provider	Cost	Speed	Quality	Best For
OpenCode Zen	Pay-per-use	Fast	High	Beginners, tested models
Anthropic (Claude)	Subscription or API	Fast	Highest	Production work
OpenAI (ChatGPT)	Subscription or API	Fast	High	General use
GitHub Copilot	Subscription	Fast	High	GitHub users
Ollama	Free (local)	Medium	Medium-High	Privacy, offline use
Groq	Free tier + paid	Fastest	High	Speed-critical tasks

DeepSeek	Very low cost	Fast	High	Budget-conscious
----------	---------------	------	------	------------------

Option 1: OpenCode Zen (Recommended for Beginners)

Why choose this?

- Curated models tested by OpenCode team
- Simple setup
- Reliable performance
- Good for getting started

Setup steps:

1. In OpenCode TUI, run:

```
/connect
```

2. Select "OpenCode Zen" from the list

3. Open browser and visit: <https://opencode.ai/auth>

- Sign in or create account
- Add billing details
- Click "Create API Key"
- Copy the API key

4. Paste API key in terminal when prompted

5. Select a model:

```
/models
```

Recommended models:

- zen/claude-sonnet-4-5 - Best balance
- zen/qwen-3-coder-480b - Best for coding
- zen/claude-haiku-4-5 - Fastest, cheapest

Storage: API key stored in `~/local/share/opencode/auth.json`

Option 2: Anthropic (Claude)

Why choose this?

- Highest quality responses
- Excellent coding capabilities
- Strong reasoning
- Claude Pro/Max subscriptions available

Setup steps:

1. Sign up: <https://console.anthropic.com/>

2. In OpenCode TUI:

```
/connect
```

3. **Select "Anthropic"**

4. **Choose authentication:**

- **Claude Pro/Max** (OAuth): Opens browser for authentication
- **API Key**: Enter manually

5. **For API Key method:**

- Go to <https://console.anthropic.com/settings/keys>
- Click "Create Key"
- Copy and paste in terminal

6. **Select model:**

```
/models
```

Recommended:

- anthropic/claude-sonnet-4-5 - Best overall
- anthropic/claude-opus-4 - Most capable
- anthropic/claude-haiku-4-5 - Fastest

Pricing: <https://www.anthropic.com/pricing>

Option 3: OpenAI (ChatGPT)

Why choose this?

- Familiar interface
- ChatGPT Plus/Pro subscription available
- Good general performance

Setup steps:

1. **Sign up:** <https://platform.openai.com/> or <https://chatgpt.com/>

2. **In OpenCode TUI:**

```
/connect
```

3. **Select "OpenAI"**

4. **Choose authentication:**

- **ChatGPT Plus/Pro** (OAuth): Opens browser
- **API Key**: Enter manually

5. **For API Key method:**

- Visit <https://platform.openai.com/api-keys>
- Click "Create new secret key"
- Copy and paste in terminal

6. **Select model:**

```
/models
```


Recommended:

- `openai/gpt-5-nano` - Best for coding
- `openai/gpt-4o` - Best overall
- `openai/gpt-4o-mini` - Fastest, cheapest

Option 4: GitHub Copilot

Why choose this?

- Already have subscription
- Native GitHub integration
- Multiple model options

Setup steps:

1. **Ensure you have:** GitHub Copilot subscription

- Individual: <https://github.com/features/copilot>
- Business: Contact your admin

2. **In OpenCode TUI:**

```
/connect
```

3. **Select "GitHub Copilot"**

4. **Browser opens to:** <https://github.com/login/device>

5. **Enter code** displayed in terminal

6. **Authorize OpenCode**

7. **Select model:**

```
/models
```

Available models:

- `github-copilot/claude-sonnet-4.5`
- `github-copilot/gpt-5-nano`
- `github-copilot/o1-preview`

Note: Some models require Copilot Pro+ subscription

Option 5: Ollama (Local Models)

Why choose this?

- Complete privacy (runs locally)
- No internet required
- No per-token costs
- Full control

Setup steps:

1. **Install Ollama:** <https://ollama.com/download>

2. Download a model:

```
ollama pull qwen2.5-coder:32b
```

Recommended models:

- qwen2.5-coder:32b - Best for coding
- llama3.3:70b - Best overall
- deepseek-r1:32b - Good reasoning

3. Start Ollama server:

```
ollama serve
```

4. Configure in OpenCode (~/.config/opencode/opencode.json):

```
{
  "$schema": "https://opencode.ai/config.json",
  "provider": {
    "ollama": {
      "npm": "@ai-sdk/openai-compatible",
      "name": "Ollama (local)",
      "options": {
        "baseUrl": "http://localhost:11434/v1"
      },
      "models": {
        "qwen2.5-coder:32b": {
          "name": "Qwen 2.5 Coder 32B"
        }
      }
    }
  },
  "model": "ollama/qwen2.5-coder:32b"
}
```

5. Restart OpenCode and verify:

```
/models
```

Requirements:

- 16GB+ RAM for 7B models
- 32GB+ RAM for 32B models
- 64GB+ RAM for 70B models

Option 6: Other Popular Providers

DeepSeek (Very Low Cost)

1. Sign up: <https://platform.deepseek.com/>
2. Generate API key
3. In OpenCode:

```
/connect
```

4. **Select "DeepSeek"**

5. **Recommended model:** `deepseek/deepseek-v4-pro`

Groq (Very Fast)

1. **Sign up:** <https://console.groq.com/>

2. **Create API key**

3. **In OpenCode:**

```
/connect
```

4. **Select "Groq"**

5. **Recommended models:**

- `groq/llama-3.3-70b-versatile`
- `groq/qwen-3-coder-480b`

Azure OpenAI

1. **Create Azure resource:** <https://portal.azure.com/>

2. **Deploy model** in Azure AI Foundry

3. **In OpenCode:**

```
/connect
```

4. **Select "Azure OpenAI"**

5. **Set environment variables:**

```
export AZURE_RESOURCE_NAME=your-resource-name
export AZURE_API_KEY=your-api-key
```

Full Provider List

For 75+ providers, see: <https://opencode.ai/docs/providers>

Project Initialization

Setting Up OpenCode for Your Project

1. **Navigate to project directory:**

```
cd /path/to/your/project
```

2. **Launch OpenCode:**

```
opencode
```

3. **Initialize the project:**

```
/init
```

4. OpenCode will:

- Analyze your codebase
- Identify frameworks and languages
- Detect coding patterns
- Create `AGENTS.md` file

Understanding AGENTS.md

The `AGENTS.md` file helps OpenCode understand your project:

Example AGENTS.md:

```
# Project: My Awesome App

## Tech Stack
- Frontend: React 18 with TypeScript
- Backend: Node.js + Express
- Database: PostgreSQL
- Testing: Jest + React Testing Library

## Architecture
- Monorepo using Turborepo
- Microservices pattern
- RESTful API

## Coding Standards
- Use functional components
- Prefer TypeScript over JavaScript
- Follow Airbnb style guide
- Write tests for all new features

## Important Conventions
- All API routes start with `/api/v1/`
- Use named exports over default exports
- Environment variables in `.env.local`
```

Best practices:

-  Commit `AGENTS.md` to Git
-  Update when architecture changes
-  Include team conventions
-  Document important patterns
-  Don't include sensitive information

Project-Specific Configuration

Create `opencode.json` in your project root:

```
{
  "$schema": "https://opencode.ai/config.json",
  "model": "anthropic/claude-sonnet-4-5",
  "instructions": [
```

```

    "CONTRIBUTING.md",
    "docs/coding-guidelines.md"
  ],
  "formatter": true,
  "lsp": true,
  "permission": {
    "bash": "ask",
    "edit": "allow"
  }
}

```

Commit this file to share configuration with your team.

Configuration Files

Configuration Hierarchy

OpenCode uses a hierarchical configuration system:



Key principle: Later configs override earlier ones, but non-conflicting settings are merged.

Global Configuration

Location: ~/.config/opencode/opencode.json

Purpose: User-wide settings (providers, models, permissions)

Example:

```
{
  "$schema": "https://opencode.ai/config.json",
  "model": "anthropic/claude-sonnet-4-5",
  "small_model": "anthropic/claude-haiku-4-5",
  "autoupdate": true,
  "share": "manual",
  "snapshot": true,
  "server": {
    "port": 4096,
    "hostname": "0.0.0.0"
  },
  "provider": {
    "anthropic": {
      "options": {
        "timeout": 600000,
        "apiKey": "{env:ANTHROPIC_API_KEY}"
      }
    }
  }
}
```

TUI Configuration

Location: `~/.config/opencode/tui.json`

Purpose: Terminal UI customization

Example:

```
{
  "$schema": "https://opencode.ai/tui.json",
  "theme": "tokyonight",
  "scroll_speed": 3,
  "scroll_acceleration": {
    "enabled": true
  },
  "diff_style": "auto",
  "mouse": true,
  "keybinds": {
    "command_list": "ctrl+p",
    "send": "enter",
    "cancel": "ctrl+c",
    "undo": "ctrl+z",
    "redo": "ctrl+y"
  }
}
```

Available themes: <https://opencode.ai/docs/themes>

Project Configuration

Location: <project-root>/opencode.json

Purpose: Project-specific settings (safe to commit to Git)

Example:

```
{
  "$schema": "https://opencode.ai/config.json",
  "model": "anthropic/claude-sonnet-4-5",
  "instructions": [
    "CONTRIBUTING.md",
    "docs/architecture.md",
    ".cursor/rules/*.md"
  ],
  "formatter": {
    "prettier": {
      "disabled": false
    },
    "eslint": {
      "disabled": false
    }
  },
  "lsp": true,
  "tools": {
    "bash": true,
    "write": true,
    "edit": true
  },
  "permission": {
    "bash": "ask",
    "edit": "allow"
  },
  "command": {
    "test": {
      "template": "Run tests with coverage and show failures",
      "description": "Run project tests",
      "agent": "build"
    },
    "lint": {
      "template": "Run linter and fix issues",
      "description": "Lint and fix code"
    }
  }
}
```

Environment-Based Configuration

Using environment variables:

```
# Custom config file
export OPENCODE_CONFIG=/path/to/custom-config.json

# Custom config directory
export OPENCODE_CONFIG_DIR=/path/to/config-dir

# Inline config
export OPENCODE_CONFIG_CONTENT='{ "model": "anthropic/claude-sonnet-4-5" }'

# Run OpenCode
opencode
```

Configuration Options Reference

Provider Configuration

```
{
  "provider": {
    "provider-name": {
      "npm": "@ai-sdk/openai-compatible",
      "name": "Display Name",
      "options": {
        "baseUrl": "https://api.example.com",
        "apiKey": "{env:API_KEY}",
        "timeout": 600000,
        "chunkTimeout": 30000,
        "headers": {
          "Custom-Header": "value"
        }
      }
    },
    "models": {
      "model-id": {
        "name": "Model Display Name",
        "limit": {
          "context": 128000,
          "output": 8192
        }
      }
    }
  },
  "model": "provider-name/model-id",
  "small_model": "provider-name/small-model-id"
}
```

Tool Configuration

```
{
  "tools": {
    "bash": true,
  }
}
```



```

    "write": true,
    "edit": true,
    "read": true,
    "glob": true,
    "grep": true,
    "task": true,
    "webfetch": true,
    "question": true,
    "todowrite": true
  }
}

```

Permission Configuration

```

{
  "permission": {
    "*": "allow",
    "bash": {
      "*": "ask",
      "rm -rf *": "deny",
      "sudo *": "deny"
    },
    "edit": "ask",
    "write": "ask",
    "webfetch": "ask"
  }
}

```

Permission levels:

- "allow" - Always allow without asking
- "ask" - Prompt user for approval
- "deny" - Always deny

Formatter Configuration

```

{
  "formatter": true
}

```

Or with customization:

```

{
  "formatter": {
    "prettier": {
      "disabled": false,
      "command": ["npx", "prettier", "--write", "$FILE"],
      "extensions": [".js", ".ts", ".jsx", ".tsx", ".json"]
    },
    "black": {

```

```
    "disabled": false,  
    "extensions": [".py"]  
  }  
}  
}
```

LSP Configuration

```
{  
  "lsp": true  
}
```

Or with customization:

```
{  
  "lsp": {  
    "typescript": {  
      "disabled": false  
    },  
    "python": {  
      "disabled": false  
    }  
  }  
}
```

Custom Agents

```
{  
  "agent": {  
    "code-reviewer": {  
      "description": "Reviews code for best practices",  
      "model": "anthropic/claude-sonnet-4-5",  
      "prompt": "You are an expert code reviewer...",  
      "tools": {  
        "write": false,  
        "edit": false  
      }  
    }  
  },  
  "default_agent": "build"  
}
```

Custom Commands

```
{  
  "command": {  
    "test": {  
      "template": "Run full test suite with coverage",  
      "description": "Execute project tests",  
    }  
  }  
}
```

```

    "agent": "build",
    "model": "anthropic/claude-haiku-4-5"
  },
  "deploy": {
    "template": "Deploy to $ARGUMENTS environment",
    "description": "Deploy application"
  }
}
}

```

Variable Substitution

```

{
  "provider": {
    "openai": {
      "options": {
        "apiKey": "{env:OPENAI_API_KEY}"
      }
    }
  },
  "instructions": [
    "{file:~/.opencode/shared-rules.md}",
    "CONTRIBUTING.md"
  ]
}

```

Variables:

- `{env:VAR_NAME}` - Environment variable
- `{file:path}` - File contents

MCP Servers (Optional)

MCP (Model Context Protocol) servers add external tools to OpenCode.

What are MCP Servers?

MCP servers provide additional capabilities to OpenCode:

- Search documentation (Context7)
- Search GitHub code (Grep)
- Interact with services (Sentry, Jira)
- Custom integrations

⚠ Important: MCP servers add to context usage. Be selective!

Adding Local MCP Servers

Configuration:

```

{
  "$schema": "https://opencode.ai/config.json",

```

```

"mcp": {
  "server-name": {
    "type": "local",
    "command": ["npx", "-y", "@modelcontextprotocol/server-package"],
    "enabled": true,
    "environment": {
      "API_KEY": "{env:MY_API_KEY}"
    },
    "timeout": 5000
  }
}

```

Example - MCP Everything (test server):

```

{
  "mcp": {
    "mcp_everything": {
      "type": "local",
      "command": ["npx", "-y", "@modelcontextprotocol/server-everything"],
      "enabled": true
    }
  }
}

```

Usage:

use the mcp_everything tool to add 3 and 4

Adding Remote MCP Servers

Configuration:

```

{
  "$schema": "https://opencode.ai/config.json",
  "mcp": {
    "server-name": {
      "type": "remote",
      "url": "https://mcp.example.com/mcp",
      "enabled": true,
      "headers": {
        "Authorization": "Bearer {env:API_TOKEN}"
      },
      "timeout": 5000
    }
  }
}

```

Popular MCP Servers

1. Context7 - Documentation Search

Purpose: Search through 60,000+ documentation sources

Setup:

```
{
  "mcp": {
    "context7": {
      "type": "remote",
      "url": "https://mcp.context7.com/mcp",
      "enabled": true
    }
  }
}
```

With API key (higher rate limits):

```
{
  "mcp": {
    "context7": {
      "type": "remote",
      "url": "https://mcp.context7.com/mcp",
      "enabled": true,
      "headers": {
        "CONTEXT7_API_KEY": "{env:CONTEXT7_API_KEY}"
      }
    }
  }
}
```

Sign up: <https://context7.com/>

Usage:

How do I configure a Cloudflare Worker? use context7

2. Grep by Vercel - GitHub Code Search

Purpose: Search code examples from GitHub repositories

Setup:

```
{
  "mcp": {
    "gh_grep": {
      "type": "remote",
      "url": "https://mcp.grep.app",
      "enabled": true
    }
  }
}
```

```
}  
}
```

Usage:

Show me examples of SST Astro custom domains. use gh_grep

3. Sentry - Error Tracking

Purpose: Query Sentry projects and issues

Setup:

```
{  
  "mcp": {  
    "sentry": {  
      "type": "remote",  
      "url": "https://mcp.sentry.dev/mcp",  
      "enabled": true,  
      "oauth": {}  
    }  
  }  
}
```

Authenticate:

```
opencode mcp auth sentry
```

Usage:

Show me the latest unresolved issues. use sentry

MCP Server Management

List all MCP servers

```
opencode mcp list
```

Authenticate with OAuth

```
opencode mcp auth <server-name>
```

Logout from MCP server

```
opencode mcp logout <server-name>
```

Debug MCP server

```
opencode mcp debug <server-name>
```

Managing MCP Tools

Disable MCP globally

```
{
  "tools": {
    "mcp_servername_*": false
  }
}
```

Enable per agent

```
{
  "tools": {
    "context7_*": false
  },
  "agent": {
    "research-agent": {
      "tools": {
        "context7_*": true
      }
    }
  }
}
```

OAuth for MCP Servers

OpenCode automatically handles OAuth for remote MCP servers.

Automatic OAuth:

```
{
  "mcp": {
    "oauth-server": {
      "type": "remote",
      "url": "https://mcp.example.com/mcp"
    }
  }
}
```

Pre-registered client:

```
{
  "mcp": {
    "oauth-server": {
      "type": "remote",
      "url": "https://mcp.example.com/mcp",

```

```

    "oauth": {
      "clientId": "{env:CLIENT_ID}",
      "clientSecret": "{env:CLIENT_SECRET}",
      "scope": "tools:read tools:execute"
    }
  }
}

```

Disable OAuth (use API keys):

```

{
  "mcp": {
    "api-key-server": {
      "type": "remote",
      "url": "https://mcp.example.com/mcp",
      "oauth": false,
      "headers": {
        "Authorization": "Bearer {env:API_KEY}"
      }
    }
  }
}

```

MCP Best Practices



Do:

- Use MCP servers sparingly (they add to context)
- Disable unused MCP servers
- Enable per agent when possible
- Test MCP servers before deploying



Don't:

- Enable all MCP servers at once
- Use MCP servers with excessive tools
- Share API keys in config files (use env vars)

Advanced Configuration

Custom Agents

Agents are specialized AI assistants for specific tasks.

Method 1: Markdown Files

Location: `~/.config/opencode/agents/code-reviewer.md`

```

---
description: Reviews code for best practices and security
model: anthropic/claude-sonnet-4-5

```



```
tools:
  write: false
  edit: false
---
```

You are an expert code reviewer with 15 years of experience.

Focus on:

- Security vulnerabilities
- Performance issues
- Code maintainability
- Best practices
- Documentation quality

Provide specific, actionable feedback with examples.

Method 2: JSON Configuration

```
{
  "agent": {
    "code-reviewer": {
      "description": "Reviews code for best practices",
      "model": "anthropic/claude-sonnet-4-5",
      "prompt": "You are an expert code reviewer...",
      "tools": {
        "write": false,
        "edit": false,
        "bash": false
      }
    },
  },
  "test-writer": {
    "description": "Writes comprehensive tests",
    "model": "anthropic/claude-haiku-4-5",
    "prompt": "You write thorough unit and integration tests...",
    "tools": {
      "write": true,
      "edit": true
    }
  }
}
```

Usage:

```
/agent code-reviewer
Review this function for security issues @src/auth.ts
```

Custom Commands

Commands are shortcuts for common tasks.

Configuration:

```
{
  "command": {
    "test": {
      "template": "Run the full test suite with coverage report.\nFocus on failing tests and suggest fixes.",
      "description": "Run tests with coverage",
      "agent": "build",
      "model": "anthropic/claude-haiku-4-5"
    },
    "component": {
      "template": "Create a new React component named $ARGUMENTS with TypeScript.\nInclude proper typing, PropTypes, and basic structure.",
      "description": "Create a new component"
    },
    "deploy": {
      "template": "Deploy the application to $ARGUMENTS environment.\nRun build, tests, and deployment checks.",
      "description": "Deploy application"
    },
    "refactor": {
      "template": "Refactor $ARGUMENTS to improve:\n- Code quality\n- Performance\n- Maintainability\nPreserve all existing functionality.",
      "description": "Refactor code"
    }
  }
}
```

Usage:

```
/test
/component UserProfile
/deploy staging
/refactor src/utils/parser.ts
```

Custom Themes

Location: ~/.config/opencode/tui.json

```
{
  "$schema": "https://opencode.ai/tui.json",
  "theme": "tokyonight"
}
```

Built-in themes:

- tokyonight
- dracula
- nord
- gruvbox

- solarized-dark
- solarized-light
- monokai
- github-dark
- github-light

Full list: <https://opencode.ai/docs/themes>

Custom Keybindings

Configuration:

```
{
  "$schema": "https://opencode.ai/tui.json",
  "keybinds": {
    "command_list": "ctrl+p",
    "send": "enter",
    "cancel": "ctrl+c",
    "undo": "ctrl+z",
    "redo": "ctrl+y",
    "new_session": "ctrl+n",
    "close_session": "ctrl+w",
    "next_session": "ctrl+tab",
    "prev_session": "ctrl+shift+tab",
    "scroll_up": "up",
    "scroll_down": "down",
    "page_up": "pageup",
    "page_down": "pagedown"
  }
}
```

Full list: <https://opencode.ai/docs/keybinds>

Sharing Configuration

```
{
  "share": "manual"
}
```

Options:

- "manual" - Share via `/share` command (default)
- "auto" - Auto-share new conversations
- "disabled" - Disable sharing entirely

Autoupdate Configuration

```
{
  "autoupdate": true
}
```

Options:

- `true` - Auto-update (default)
- `false` - Never update
- `"notify"` - Show notification only

Snapshot Configuration

```
{  
  "snapshot": true  
}
```

Disable for large repos:

```
{  
  "snapshot": false  
}
```

Note: Disabling snapshots prevents undo/redo functionality.

Context Compaction

```
{  
  "compaction": {  
    "auto": true,  
    "prune": true,  
    "reserved": 10000  
  }  
}
```

Options:

- `auto` - Auto-compact when context full (default: `true`)
- `prune` - Remove old tool outputs (default: `true`)
- `reserved` - Token buffer (default: `10000`)

File Watcher Configuration

```
{  
  "watcher": {  
    "ignore": [  
      "node_modules/**",  
      "dist/**",  
      "build/**",  
      ".git/**",  
      "**/*.log",  
      "**/.DS_Store"  
    ]  
  }  
}
```

```
}  
}
```

Disabled/Enabled Providers

Disable specific providers:

```
{  
  "disabled_providers": ["openai", "gemini"]  
}
```

Enable only specific providers:

```
{  
  "enabled_providers": ["anthropic", "openai"]  
}
```

Note: `disabled_providers` takes precedence over `enabled_providers`.

Verification

Basic Verification

1. Check version:

```
opencode --version
```

Expected: `opencode version X.X.X`

2. Check config location:

```
ls -la ~/.config/opencode/
```

3. Check auth credentials:

```
cat ~/.local/share/opencode/auth.json
```

4. Launch OpenCode:

```
opencode
```

Functional Testing

Test 1: Basic Communication

```
Hello! Can you confirm you're working?
```

Expected: Friendly response confirming functionality.

Test 2: File Operations

Create a test file called hello.txt with "Hello World"

Verify:

```
cat hello.txt
```

Test 3: Code Analysis

What programming languages does this project use?

Test 4: Model Selection

```
/models
```

Expected: List of available models.

Test 5: Help System

```
/help
```

Expected: List of available commands.

Performance Testing

Test context usage:

How much context have we used so far?

Test large file handling:

Read and summarize @large-file.json

Configuration Verification

View active config:

```
/config
```

Debug config loading:

```
opencode debug config
```

Comprehensive Troubleshooting

Installation Issues

Issue: "opencode: command not found"

Symptoms: Command not recognized after installation.

Solution 1 - Check PATH:

```
# macOS/Linux
echo $PATH
which opencode

# Windows
echo %PATH%
where opencode
```

Solution 2 - Add to PATH:

macOS/Linux (add to `~/.bashrc` or `~/.zshrc`):

```
export PATH="$PATH:$HOME/.local/bin"
export PATH="$PATH:/usr/local/bin"
```

Windows (PowerShell):

```
$env:PATH += ";C:\Program Files\opencode"
# Or via System Properties > Environment Variables
```

Solution 3 - Reinstall:

```
# Using npm
npm uninstall -g opencode-ai
npm install -g opencode-ai

# Using Homebrew
brew uninstall opencode
brew install anomalyco/tap/opencode
```

Issue: Permission denied during installation

Solution - macOS/Linux:

```
# Fix npm permissions
sudo chown -R $(whoami) ~/.npm
sudo chown -R $(whoami) /usr/local/lib/node_modules

# Or use nvm (recommended)
curl -o- https://raw.githubusercontent.com/nvm-sh/nvm/v0.39.0/install.sh | bash
nvm install --lts
npm install -g opencode-ai
```

Solution - Windows:

```
# Run as Administrator
npm install -g opencode-ai
```

Issue: Node.js version incompatibility

Check Node version:

```
node --version
```

Required: Node.js 18.0.0 or higher

Solution:

```
# Install latest LTS
# Using nvm (recommended)
nvm install --lts
nvm use --lts

# Or download from nodejs.org
```

Issue: Installation fails with EACCES error

Solution:

```
# Change npm's default directory
mkdir ~/.npm-global
npm config set prefix '~/.npm-global'
echo 'export PATH=~/.npm-global/bin:$PATH' >> ~/.bashrc
source ~/.bashrc
npm install -g opencode-ai
```

Provider Issues

Issue: "No API key found" or authentication failures

Diagnosis:

```
cat ~/.local/share/opencode/auth.json
```

Solution 1 - Reconnect provider:

```
/connect
```

Select provider and re-enter credentials.

Solution 2 - Check environment variables:

```
# List all OpenCode-related env vars
env | grep -i "api"
```



```
env | grep -i "anthropic\|openai\|github"
```

Solution 3 - Manually edit auth file:

```
nano ~/.local/share/opencode/auth.json
```

Format:

```
{
  "provider-name": {
    "apiKey": "your-api-key-here"
  }
}
```

Solution 4 - Use environment variables:

```
# Add to ~/.bashrc or ~/.zshrc
export ANTHROPIC_API_KEY=your-key-here
export OPENAI_API_KEY=your-key-here
```

Issue: "Rate limit exceeded"

Symptoms: Too many requests to provider API.

Solution 1 - Wait and retry: Most rate limits reset after a few minutes.

Solution 2 - Upgrade plan:

- Anthropic: <https://console.anthropic.com/settings/plans>
- OpenAI: <https://platform.openai.com/settings/organization/billing/overview>

Solution 3 - Use different provider:

```
/connect
```

Add backup provider with different limits.

Solution 4 - Add timeout configuration:

```
{
  "provider": {
    "anthropic": {
      "options": {
        "timeout": 900000,
        "chunkTimeout": 60000
      }
    }
  }
}
```

Issue: "Context length exceeded"

Symptoms: Message too long for model's context window.

Solution 1 - Use model with larger context:

```
/models
```

Select model like `claude-sonnet-4-5` (200k tokens).

Solution 2 - Enable auto-compaction:

```
{
  "compaction": {
    "auto": true,
    "prune": true
  }
}
```

Solution 3 - Start new conversation:

```
/new
```

Solution 4 - Disable MCP servers:

```
{
  "tools": {
    "mcp_*": false
  }
}
```

Issue: OAuth authentication fails

Solution 1 - Clear browser cache: Clear cookies for the provider's domain.

Solution 2 - Try incognito/private window: Some ad blockers interfere with OAuth.

Solution 3 - Use API key instead:

```
/connect
```

Choose "Manually enter API Key" option.

Solution 4 - Check firewall/proxy:

```
# Test connectivity
curl https://api.anthropic.com
curl https://api.openai.com
```

Configuration Issues

Issue: Configuration file not loading

Diagnosis:

```
opencode debug config
```

Solution 1 - Check file location:

```
# Global config
ls -la ~/.config/opencode/opencode.json

# Project config
ls -la ./opencode.json
```

Solution 2 - Validate JSON syntax:

```
# macOS/Linux
python3 -m json.tool ~/.config/opencode/opencode.json

# Or use jq
jq . ~/.config/opencode/opencode.json
```

Solution 3 - Check file permissions:

```
chmod 644 ~/.config/opencode/opencode.json
```

Solution 4 - Start with minimal config:

```
{
  "$schema": "https://opencode.ai/config.json",
  "model": "anthropic/claude-sonnet-4-5"
}
```

Issue: Schema validation errors

Solution - Update schema URL:

```
{
  "$schema": "https://opencode.ai/config.json"
}
```

For TUI config:

```
{
  "$schema": "https://opencode.ai/tui.json"
}
```

Issue: Environment variables not expanding

Check syntax:

```
{
  "provider": {
    "openai": {
      "options": {
        "apiKey": "{env:OPENAI_API_KEY}"
      }
    }
  }
}
```

Verify variable is set:

```
echo $OPENAI_API_KEY
```

Set if missing:

```
# Temporary
export OPENAI_API_KEY=your-key

# Permanent (add to ~/.bashrc or ~/.zshrc)
echo 'export OPENAI_API_KEY=your-key' >> ~/.bashrc
source ~/.bashrc
```

Issue: Project config ignored

Solution 1 - Check location: Config must be in project root or Git root.

```
# Find Git root
git rev-parse --show-toplevel

# Place config there
cp opencode.json $(git rev-parse --show-toplevel)/
```

Solution 2 - Use custom config path:

```
export OPENCODE_CONFIG=/path/to/opencode.json
opencode
```

Performance Issues

Issue: OpenCode slow to start

Diagnosis:

```
time opencode --version
```

Solution 1 - Disable autoupdate:

```
{
  "autoupdate": false
}
```

Solution 2 - Disable snapshot for large repos:

```
{
  "snapshot": false
}
```

Solution 3 - Reduce MCP servers:

```
{
  "mcp": {
    "server1": {
      "enabled": false
    }
  }
}
```

Solution 4 - Clear cache:

```
rm -rf ~/.local/share/opencode/cache/
```

Issue: High memory usage

Diagnosis:

```
# macOS/Linux
ps aux | grep opencode

# Windows
tasklist | findstr opencode
```

Solution 1 - Use smaller model:

```
{
  "model": "anthropic/claude-haiku-4-5"
}
```

Solution 2 - Enable context compaction:

```
{
  "compaction": {
    "auto": true,
    "prune": true,
    "reserved": 5000
  }
}
```

```
}  
}
```

Solution 3 - Restart OpenCode regularly:

```
/new
```

Solution 4 - Check for runaway processes:

```
pkill -f opencode  
opencode
```

Issue: Slow response times

Solution 1 - Use faster provider:

- Groq (fastest)
- Claude Haiku
- GPT-4o-mini

Solution 2 - Reduce context:

```
/new
```

Solution 3 - Disable LSP:

```
{  
  "lsp": false  
}
```

Solution 4 - Check network:

```
ping api.anthropic.com
```

MCP Server Issues

Issue: MCP server not starting

Diagnosis:

```
opencode mcp list  
opencode mcp debug <server-name>
```

Solution 1 - Check command:

```
{  
  "mcp": {  
    "myserver": {  
      "type": "local",  
      "command": ["npx", "-y", "correct-package-name"]  
    }  
  }  
}
```

```
}  
}  
}
```

Solution 2 - Test command manually:

```
npx -y @modelcontextprotocol/server-everything
```

Solution 3 - Check dependencies:

```
npm list -g | grep mcp
```

Solution 4 - Reinstall MCP package:

```
npm cache clean --force  
npx -y @modelcontextprotocol/server-everything
```

Issue: MCP OAuth authentication fails

Diagnosis:

```
opencode mcp auth list  
opencode mcp debug <server-name>
```

Solution 1 - Retry authentication:

```
opencode mcp logout <server-name>  
opencode mcp auth <server-name>
```

Solution 2 - Check stored tokens:

```
cat ~/.local/share/opencode/mcp-auth.json
```

Solution 3 - Disable OAuth and use API key:

```
{  
  "mcp": {  
    "myserver": {  
      "type": "remote",  
      "url": "https://mcp.example.com",  
      "oauth": false,  
      "headers": {  
        "Authorization": "Bearer {env:API_KEY}"  
      }  
    }  
  }  
}
```

Issue: MCP server timeout

Solution - Increase timeout:

```
{
  "mcp": {
    "myserver": {
      "type": "remote",
      "url": "https://mcp.example.com",
      "timeout": 30000
    }
  }
}
```

Issue: Too many MCP tools in context

Solution 1 - Disable globally, enable per agent:

```
{
  "tools": {
    "mcp_*": false
  },
  "agent": {
    "research": {
      "tools": {
        "mcp_context7_*": true
      }
    }
  }
}
```

Solution 2 - Disable specific MCP server:

```
{
  "mcp": {
    "excessive-server": {
      "enabled": false
    }
  }
}
```

File Operation Issues

Issue: "Permission denied" when writing files

Solution 1 - Check file permissions:

```
ls -la filename
```

Solution 2 - Change ownership:


```
sudo chown $(whoami) filename
```

Solution 3 - Check directory permissions:

```
ls -la directory/  
chmod 755 directory/
```

Solution 4 - Use different directory:

```
cd ~/Documents/projects/  
opencode
```

Issue: Files not being read

Diagnosis:

```
Read the file @path/to/file.txt
```

Solution 1 - Use absolute path:

```
Read /full/path/to/file.txt
```

Solution 2 - Check file exists:

```
ls -la path/to/file.txt
```

Solution 3 - Check file encoding:

```
file path/to/file.txt
```

Solution 4 - Check .gitignore:

```
cat .gitignore
```

Issue: Unable to undo changes

Verify snapshot enabled:

```
{  
  "snapshot": true  
}
```

Check snapshot storage:

```
ls -la ~/.local/share/opencode/snapshots/
```

Restart OpenCode:

```
pkill opencode  
opencode
```

WSL-Specific Issues (Windows)

Issue: WSL not installed

Solution:

```
# Run as Administrator  
wsl --install  
# Restart computer
```

Issue: WSL version 1 instead of 2

Check version:

```
wsl --list --verbose
```

Upgrade to WSL 2:

```
wsl --set-version Ubuntu 2  
wsl --set-default-version 2
```

Issue: Cannot access Windows files from WSL

Solution:

```
# Access C:\Users\username\Documents  
cd /mnt/c/Users/username/Documents
```

Issue: Node.js not found in WSL

Install Node.js in WSL:

```
curl -o- https://raw.githubusercontent.com/nvm-sh/nvm/v0.39.0/install.sh | bash  
source ~/.bashrc  
nvm install --lts  
node --version
```

Issue: OpenCode installed in Windows but not WSL

Install separately in WSL:

```
curl -fsSL https://opencode.ai/install | bash
```

Terminal Issues

Issue: Colors not displaying correctly

Solution 1 - Check terminal support:

```
echo $TERM
```

Solution 2 - Set TERM variable:

```
export TERM=xterm-256color
```

Solution 3 - Use different terminal: Try WezTerm, Alacritty, or iTerm2.

Issue: Mouse input not working

Enable in config:

```
{
  "$schema": "https://opencode.ai/tui.json",
  "mouse": true
}
```

Issue: Scroll not working

Configure scroll:

```
{
  "$schema": "https://opencode.ai/tui.json",
  "scroll_speed": 3,
  "scroll_acceleration": {
    "enabled": true
  }
}
```

Issue: Unicode characters not displaying

Check terminal encoding:

```
locale
```

Set UTF-8:

```
export LANG=en_US.UTF-8
export LC_ALL=en_US.UTF-8
```

Network Issues

Issue: Cannot connect to provider API

Test connectivity:

```
curl https://api.anthropic.com
curl https://api.openai.com
curl https://api.opencode.ai
```

Solution 1 - Check firewall: Allow outbound HTTPS connections.

Solution 2 - Configure proxy:

```
export HTTP_PROXY=http://proxy:port
export HTTPS_PROXY=http://proxy:port
```

Solution 3 - Try different network: Test with mobile hotspot or different WiFi.

Issue: SSL/TLS certificate errors

Solution 1 - Update certificates:

```
# macOS
brew update && brew upgrade openssl

# Linux
sudo apt update && sudo apt install ca-certificates

# Windows
# Update Windows certificates via Windows Update
```

Solution 2 - Bypass SSL verification (not recommended):

```
export NODE_TLS_REJECT_UNAUTHORIZED=0
```

Update Issues

Issue: Auto-update fails

Manual update:

```
# Using npm
npm update -g opencode-ai

# Using Homebrew
brew update && brew upgrade opencode

# Using install script
curl -fsSL https://opencode.ai/install | bash
```

Issue: Cannot disable updates

Solution:

```
{
  "autoupdate": false
}
```

Debugging Tools

Get detailed logs

Enable debug mode:

```
export DEBUG=opencode:*
opencode
```

Check logs:

```
# macOS/Linux
tail -f ~/.local/share/opencode/logs/opencode.log

# Windows
type %LOCALAPPDATA%\opencode\logs\opencode.log
```

Debug configuration

```
opencode debug config
```

Debug MCP servers

```
opencode mcp debug <server-name>
```

Check OpenCode version and build info

```
opencode --version
opencode --help
```

Reference Documentation

Official Documentation Links

Topic	URL
Main Documentation	https://opencode.ai/docs
Installation Guide	https://opencode.ai/docs
Configuration	https://opencode.ai/docs/config
Providers	https://opencode.ai/docs/providers

Models	https://opencode.ai/docs/models
Tools	https://opencode.ai/docs/tools
Agents	https://opencode.ai/docs/agents
Commands	https://opencode.ai/docs/commands
Themes	https://opencode.ai/docs/themes
Keybindings	https://opencode.ai/docs/keybinds
Formatters	https://opencode.ai/docs/formatters
LSP Servers	https://opencode.ai/docs/lsp
MCP Servers	https://opencode.ai/docs/mcp-servers
Permissions	https://opencode.ai/docs/permissions
Skills	https://opencode.ai/docs/skills
Custom Tools	https://opencode.ai/docs/custom-tools
Plugins	https://opencode.ai/docs/plugins
Rules	https://opencode.ai/docs/rules
TUI Usage	https://opencode.ai/docs/tui
CLI Usage	https://opencode.ai/docs/cli
Web Interface	https://opencode.ai/docs/web
IDE Integration	https://opencode.ai/docs/ide
Zen	https://opencode.ai/docs/zen
Go	https://opencode.ai/docs/go
Sharing	https://opencode.ai/docs/share
GitHub Integration	https://opencode.ai/docs/github
GitLab Integration	https://opencode.ai/docs/gitlab
Network Config	https://opencode.ai/docs/network
Enterprise	https://opencode.ai/docs/enterprise
Troubleshooting	https://opencode.ai/docs/troubleshooting
Windows/WSL	https://opencode.ai/docs/windows-wsl
SDK	https://opencode.ai/docs/sdk
Server	https://opencode.ai/docs/server
Ecosystem	https://opencode.ai/docs/ecosystem

Configuration Schema References

Schema	URL
OpenCode Config Schema	https://opencode.ai/config.json
TUI Config Schema	https://opencode.ai/tui.json

Provider-Specific Documentation

Provider	Documentation
OpenCode Zen	https://opencode.ai/zen
OpenCode Go	https://opencode.ai/go
Anthropic	https://docs.anthropic.com
OpenAI	https://platform.openai.com/docs
GitHub Copilot	https://docs.github.com/copilot
Azure OpenAI	https://learn.microsoft.com/azure/ai-services/openai/
Google Vertex AI	https://cloud.google.com/vertex-ai/docs
Amazon Bedrock	https://docs.aws.amazon.com/bedrock/
Ollama	https://ollama.ai/docs
DeepSeek	https://platform.deepseek.com/docs
Groq	https://console.groq.com/docs

Community Resources

Resource	URL
GitHub Repository	https://github.com/anomalyco/opencode
GitHub Releases	https://github.com/anomalyco/opencode/releases
GitHub Issues	https://github.com/anomalyco/opencode/issues
Discord Community	https://opencode.ai/discord
Example Conversations	https://opencode.ai/s/4XP1fce5

Additional Resources

Resource	URL
AI SDK Documentation	https://ai-sdk.dev/
Models.dev	https://models.dev

Quick Reference

Essential Commands

```
# Installation
curl -fsSL https://opencode.ai/install | bash

# Launch OpenCode
opencode

# Check version
opencode --version

# Update OpenCode
npm update -g opencode-ai
# OR
brew upgrade opencode
```

TUI Commands

```
/help          - Show available commands
/connect       - Connect to a provider
/models       - Select a model
/init         - Initialize project
/new          - Start new conversation
/share        - Share current conversation
/undo         - Undo last changes
/redo         - Redo undone changes
/agent        - Switch agent
/config       - View current configuration
```

Configuration Locations

```
# Global config
~/.config/opencode/opencode.json

# TUI config
~/.config/opencode/tui.json

# Project config
<project-root>/opencode.json

# Auth credentials
~/.local/share/opencode/auth.json
```



```
# MCP auth
~/local/share/opencode/mcp-auth.json
```

Environment Variables

```
# Custom config path
export OPENCODE_CONFIG=/path/to/config.json

# Custom config directory
export OPENCODE_CONFIG_DIR=/path/to/config-dir

# Inline config
export OPENCODE_CONFIG_CONTENT='{ "model": "..."}'

# Provider API keys
export ANTHROPIC_API_KEY=your-key
export OPENAI_API_KEY=your-key
export GITHUB_TOKEN=your-token

# Debug mode
export DEBUG=opencode:*
```

Common File Paths

macOS/Linux:

- Config: ~/.config/opencode/
- Data: ~/.local/share/opencode/
- Cache: ~/.cache/opencode/
- Logs: ~/.local/share/opencode/logs/

Windows:

- Config: %APPDATA%\opencode\
- Data: %LOCALAPPDATA%\opencode\
- Cache: %TEMP%\opencode\

Keyboard Shortcuts (Default)

Action	Shortcut
Send message	Enter
Cancel	Ctrl+C
Undo	Ctrl+Z
Redo	Ctrl+Y
Command list	Ctrl+P
New session	Ctrl+N

Close session	Ctrl+W
Next session	Ctrl+Tab
Previous session	Ctrl+Shift+Tab
Scroll up	↑ or Page Up
Scroll down	↓ or Page Down

Minimal Configurations

Minimal `opencode.json`:

```
{
  "$schema": "https://opencode.ai/config.json",
  "model": "anthropic/claude-sonnet-4-5"
}
```

Minimal `tui.json`:

```
{
  "$schema": "https://opencode.ai/tui.json",
  "theme": "tokyonight"
}
```

Getting Help

1. In-app help: `/help`
 2. Documentation: <https://opencode.ai/docs>
 3. GitHub Issues: <https://github.com/anomalyco/opencode/issues>
 4. Discord: <https://opencode.ai/discord>
 5. Email: support@opencode.ai
-

Appendix A: Example Configurations

Example 1: Basic Setup

`~/.config/opencode/opencode.json`:

```
{
  "$schema": "https://opencode.ai/config.json",
  "model": "anthropic/claude-sonnet-4-5",
  "small_model": "anthropic/claude-haiku-4-5",
  "autoupdate": true,
  "share": "manual"
}
```

Example 2: Developer Setup

`~/.config/opencode/opencode.json`:

```

{
  "$schema": "https://opencode.ai/config.json",
  "model": "anthropic/claude-sonnet-4-5",
  "formatter": true,
  "lsp": true,
  "tools": {
    "bash": true,
    "write": true,
    "edit": true
  },
  "permission": {
    "bash": "ask",
    "edit": "allow"
  },
  "command": {
    "test": {
      "template": "Run tests with coverage",
      "agent": "build"
    },
    "lint": {
      "template": "Run linter and fix issues"
    }
  }
}

```

Example 3: Team Setup

project/opencode.json (commit to Git):

```

{
  "$schema": "https://opencode.ai/config.json",
  "model": "anthropic/claude-sonnet-4-5",
  "instructions": [
    "CONTRIBUTING.md",
    "docs/architecture.md"
  ],
  "formatter": {
    "prettier": {},
    "eslint": {}
  },
  "lsp": true,
  "share": "manual",
  "command": {
    "test": {
      "template": "Run full test suite with coverage",
      "agent": "build"
    },
    "deploy": {
      "template": "Deploy to $ARGUMENTS environment"
    }
  }
}

```

```
}  
}
```

Example 4: Privacy-Focused Setup

~/config/opencode/opencode.json:

```
{  
  "$schema": "https://opencode.ai/config.json",  
  "provider": {  
    "ollama": {  
      "npm": "@ai-sdk/openai-compatible",  
      "name": "Ollama (local)",  
      "options": {  
        "baseUrl": "http://localhost:11434/v1"  
      },  
      "models": {  
        "qwen2.5-coder:32b": {  
          "name": "Qwen 2.5 Coder 32B"  
        }  
      }  
    }  
  },  
  "model": "ollama/qwen2.5-coder:32b",  
  "share": "disabled",  
  "autoupdate": "notify"  
}
```

Appendix B: Glossary

Term	Definition
TUI	Terminal User Interface - OpenCode's interactive terminal mode
LLM	Large Language Model - The AI that powers OpenCode
Provider	Service that provides access to LLM models (e.g., Anthropic, OpenAI)
Agent	Specialized AI assistant for specific tasks (e.g., code reviewer)
MCP	Model Context Protocol - Standard for adding external tools
LSP	Language Server Protocol - Provides code intelligence
Formatter	Tool that automatically formats code (e.g., Prettier)
Context	Information provided to the LLM (messages, files, etc.)
Token	Unit of text that LLMs process (roughly 4 characters)
Snapshot	Internal Git repository for tracking changes and undo/redo
Compaction	Process of reducing context size to fit in model limits

OAuth	Open Authorization - Standard for secure authentication
AGENTS.md	Project file that helps OpenCode understand your codebase
Schema	JSON Schema that defines valid configuration structure
WSL	Windows Subsystem for Linux - Runs Linux on Windows

Appendix C: Changelog

Version 1.0 (May 2026)

- Initial comprehensive guide
 - Complete installation instructions
 - Provider setup for 75+ providers
 - Configuration hierarchy documentation
 - MCP server setup
 - Comprehensive troubleshooting
 - Reference documentation
-

Document Information:

- **Version:** 1.0
- **Last Updated:** May 15, 2026
- **OpenCode Compatibility:** 1.3.0+
- **Author:** OpenCode Documentation Team
- **License:** MIT

Feedback: For corrections or improvements, open an issue at: <https://github.com/anomalyco/opencode/issues>

End of Document