

IHO Marine Protected Areas (MPA) - Annex A Data Classification and Encoding Guide

Edition 2.0.0 – November 2025

IHO



International
Hydrographic
Organization

Published by the
International Hydrographic Organization
4b quai Antoine 1^{er}
Principauté de Monaco
Tel: (377) 93.10.81.00
Fax: (377) 93.10.81.40
info@ihodata.int
www.ihodata.int

© Copyright International Hydrographic Organization 2025

This work is copyright. Apart from any use permitted in accordance with the Berne Convention for the Protection of Literary and Artistic Works (1886), and except in the circumstances described below, no part may be translated, reproduced by any process, adapted, communicated or commercially exploited without prior written permission from the International Hydrographic Organization (IHO). Copyright in some of the material in this publication may be owned by another party and permission for the translation and/or reproduction of that material must be obtained from the owner.

This document or partial material from this document may be translated, reproduced or distributed for general information, on no more than a cost recovery basis. Copies may not be sold or distributed for profit or gain without prior written agreement of the IHO Secretariat and any other copyright holders.

In the event that this document or partial material from this document is reproduced, translated or distributed under the terms described above, the following statements are to be included:

"Material from IHO publication [reference to extract: Title, Edition] is reproduced with the permission of the IHO Secretariat (Permission No/...) acting for the International Hydrographic Organization (IHO), which does not accept responsibility for the correctness of the material as reproduced: in case of doubt, the IHO's authentic text shall prevail. The incorporation of material sourced from IHO shall not be construed as constituting an endorsement by IHO of this product."

"This [document/publication] is a translation of IHO [document/publication] [name]. The IHO has not checked this translation and therefore takes no responsibility for its accuracy. In case of doubt the source version of [name] in [language] should be consulted."

The IHO Logo or other identifiers shall not be used in any derived product without prior written permission from the IHO Secretariat.

Contents

1	Overview.....	1
1.1	Introduction.....	1
1.2	Document Metadata.....	1
1.3	Terms and definitions.....	1
1.4	Abbreviated terms.....	1
1.5	Use of language.....	1
1.6	Maintenance.....	2
2	General.....	2
2.1	Introduction.....	2
2.2	Descriptive characteristics.....	2
2.3	Spatial characteristics.....	3
2.4	Attributes.....	3
2.5	Associations.....	12
2.6	Datasets.....	14
2.7	Geographic names.....	16
2.8	Scale policy.....	17
2.9	Masking.....	18
2.10	Linear surface features.....	18
3	Description of table format for feature and information types.....	19
4	Meta-Features.....	21
4.1	Data Coverage.....	21
4.2	Quality of Non-Bathymetric Data.....	21
5	Abstract Geo Features.....	23
5.1	Feature Type.....	23
6	Domain Features.....	25
6.1	Information Area.....	25
6.2	Marine Protected Area.....	26
6.3	Restricted Area.....	29
6.4	Vessel Traffic Service Area.....	31
7	Cartographic Features.....	33
7.1	Text Placement.....	33
8	Abstract Information Types.....	33
8.1	Information Type.....	33
8.2	AbstractRxN.....	35
9	Textual Regulations.....	37
9.1	Introduction.....	37
9.2	Regulations applying only to vessels with specific characteristics or cargoes.....	37
9.3	Regulations.....	37
9.4	Restrictions.....	38
9.5	Recommendations.....	38
9.6	Nautical Information.....	39
10	Services, Organisations and Schedules.....	40
10.1	Introduction.....	40
10.2	Authority.....	40
10.3	Contact Details.....	41
10.4	Service Hours.....	43
10.5	Non-Standard Working Day.....	44
11	Limitations.....	45
11.1	Introduction.....	45
11.2	Defining subsets of vessels by dimensions, cargo, and other characteristics.....	45
11.3	Applicability.....	45
12	Spatial Quality.....	49
12.1	Spatial Quality.....	49
13	Feature Associations.....	49
13.1	Text association.....	49
14	Information Associations.....	50
14.1	Additional information.....	50
14.2	Authority contact.....	50

14.3	Authority hours.....	50
14.4	Associated RxN.....	50
14.5	Exceptional workday.....	50
14.6	Protected area authority.....	50
14.7	Related organisation.....	51
14.8	InclusionType.....	51
14.9	Permission Type.....	51
14.10	Service control.....	51
14.11	Spatial Association.....	51
15	Association Roles.....	51
15.1	The Authority.....	51
15.2	Authority service hours.....	52
15.3	Contact details.....	52
15.4	Control authority.....	52
15.5	Is Applicable To.....	52
15.6	Organisation-Related RxN.....	52
15.7	Permission.....	52
15.8	Partial Working Day.....	52
15.9	Responsible authority.....	53
15.10	Service Hours (reference).....	53
15.11	The information.....	53
15.12	The organisation.....	53
15.13	The Quality Information.....	53
15.14	The RxN.....	53
15.15	The Applicable RxN.....	53
15.16	The Cartographic Text.....	54
15.17	The Position Provider.....	54
15.18	The service hours for a non-standard workday.....	54
16	Simple Attributes.....	54
16.1	Administrative Division.....	54
16.2	Application Profile.....	54
16.3	Call Name.....	54
16.4	Call Sign.....	55
16.5	Cardinal Direction.....	55
16.6	Category of Authority.....	55
16.7	Category of Cargo.....	56
16.8	Category of Communication Preference.....	57
16.9	Category Of Dangerous Or Hazardous Cargo.....	58
16.10	Category of Relationship.....	59
16.11	Category of Restricted Area.....	59
16.12	Category of Schedule.....	60
16.13	Category of Temporal Variation.....	60
16.14	Category of Text.....	61
16.15	Category of Vessel Registry.....	61
16.16	City Name.....	61
16.17	Communication Channel.....	62
16.18	Comparison Operator.....	62
16.19	Contact Instructions.....	62
16.20	Country Name.....	62
16.21	Date End.....	63
16.22	Date Fixed.....	63
16.23	Date Start.....	63
16.24	Date Variable.....	63
16.25	Day of Week.....	64
16.26	Day of Week is Range.....	64
16.27	Delivery Point.....	64
16.28	Designation Identifier.....	64
16.29	Designation Scheme.....	65
16.30	Destination.....	65
16.31	Distance.....	65

16.32	File Locator.....	65
16.33	File Reference.....	65
16.34	Frequency Shore Station Receives.....	66
16.35	Frequency Shore Station Transmits.....	66
16.36	Headline.....	66
16.37	Horizontal Distance Uncertainty.....	66
16.38	In Ballast.....	67
16.39	Interoperability Identifier.....	67
16.40	Jurisdiction.....	67
16.41	Language.....	67
16.42	Linkage.....	67
16.43	Logical Connectives.....	68
16.44	Maximum Display Scale.....	68
16.45	Membership.....	68
16.46	Minimum Display Scale.....	69
16.47	MMSI Code.....	69
16.48	Name.....	69
16.49	Name of Resource.....	69
16.50	Name Usage.....	69
16.51	Online Function.....	70
16.52	Online Resource Description.....	70
16.53	Optimum Display Scale.....	71
16.54	Orientation Uncertainty.....	71
16.55	Orientation Value.....	71
16.56	Pictorial Representation.....	71
16.57	Picture Caption.....	71
16.58	Picture Information.....	72
16.59	Postal Code.....	72
16.60	Protocol.....	72
16.61	Protocol Request.....	72
16.62	Quality of Horizontal Measurement.....	72
16.63	Reported Date.....	73
16.64	Restriction.....	73
16.65	Scale Minimum.....	75
16.66	Source.....	75
16.67	Source Date.....	75
16.68	Source Type.....	75
16.69	Status.....	76
16.70	Telecommunication Carrier.....	77
16.71	Telecommunication Identifier.....	77
16.72	Telecommunication Service.....	77
16.73	Text.....	78
16.74	Text Offset Bearing.....	78
16.75	Text Offset Distance.....	78
16.76	Text Rotation.....	78
16.77	Text Type.....	79
16.78	Thickness of Ice Capability.....	79
16.79	Time of Day End.....	79
16.80	Time of Day Start.....	79
16.81	Uncertainty Fixed.....	80
16.82	Uncertainty Variable Factor.....	80
16.83	Vessel Performance.....	80
16.84	Vessels Characteristics.....	80
16.85	Vessels Characteristics Unit.....	81
16.86	Vessels Characteristics Value.....	82
16.87	Action or Activity.....	82
16.88	Category of Marine Protected Area.....	84
16.89	Category of RxN.....	84
16.90	Category of Vessel.....	85
17	Complex Attributes.....	86

17.1	Bearing Information.....	86
17.2	Contact Address.....	86
17.3	Designation.....	87
17.4	Feature Name.....	87
17.5	Fixed Date Range.....	87
17.6	Frequency Pair.....	88
17.7	Graphic.....	88
17.8	Horizontal Position Uncertainty.....	88
17.9	Information.....	89
17.10	Online Resource.....	89
17.11	Orientation.....	89
17.12	Periodic Date Range.....	90
17.13	RxN Code.....	90
17.14	Schedule by Day of Week.....	90
17.15	Spatial Accuracy.....	91
17.16	Source Indication.....	91
17.17	Survey Date Range.....	91
17.18	Telecommunications.....	92
17.19	Text Content.....	92
17.20	Time Intervals by Day of Week.....	93
17.21	Vertical Uncertainty.....	93
17.22	Vessel Measurements Specification.....	93

1 Overview

1.1 Introduction

The “Data Classification and Encoding Guide” has been developed to provide consistent, standardized instructions for encoding S-100 compliant Marine Protected Areas (MPA) (S-122) data.

The purpose of the Data Classification and Encoding Guide is to facilitate S-122 encoding to meet IHO standards for the proper display of Marine Protected Areas information in an ECDIS and other electronic charting displays. This document describes how to encode information that the modeller considers relevant to a Marine Protected Areas data product. The content of a dataset is at the discretion of the producing authority provided that the conventions described within this document are followed. A “producing authority” is a Hydrographic Office (HO) or other organization authorized by a government, to produce definitive nautical information. The entire S-100 Universal Hydrographic Data Model, including the S-122 MPA Product Specification, is available at the following web site, <https://ihonet.int>.

1.2 Document Metadata

NOTE: This information uniquely identifies this Data Classification and Encoding Guide to the Product Specification and provides information about its creation and maintenance.

Table 1-1 — Document metadata

Metadata	Content
Title:	Marine Protected Areas, Data Classification and Encoding Guide
Version:	2.0.0
Date:	16 November 2025
Language:	English
Classification:	Unclassified
Contact:	International Hydrographic Organization 4 Quai Antoine 1er B.P. 445 MC 98011 MONACO CEDEX Telephone: +377 93 10 81 00 Fax: +377 93 10 81 40 URL: https://ihonet.int
Identifier:	S-122 Annex A Data Classification and Encoding Guide
Maintenance:	Changes to S-122 Annex A; Data Classification and Encoding Guide are coordinated by the IHO Nautical Information Provision Working Group (NIPWG) and must be made available via the IHO web site.

1.3 Terms and definitions

For terms and definitions, see the Marine Protected Areas Product Specification, Clause 1.4.2.

1.4 Abbreviated terms

For a list of abbreviations, see the Marine Protected Areas Product Specification, Clause 1.4.3.

1.5 Use of language

Within this document:

- “Must” indicates a mandatory requirement;
- “Should” indicates an optional requirement, that is the recommended process to be followed, but is not mandatory;
- “May” means “allowed to” or “could possibly”, and is not mandatory, or recommended.

1.6 Maintenance

Changes to the Data Classification and Encoding Guide must occur in accordance with the IHO Resolution 2/2007 as amended.

2 General

2.1 Introduction

This Data Classification and Encoding Guide (DCEG) contains rules and guidance for converting data describing the real world into data products that conform to the S-122 specification.

The S-122 specification contains an application schema (UML model) describing the conceptual domain model in terms of classes and relationships, and a Feature Catalogue (see S-122 Annex C) that specifies the data model, i.e., specifies the data model types and associations corresponding to the various classes and relationships in the application schema.

To simplify the DCEG text, the various data model types will be provided without the suffixes “class”, “type” or “instance”; e.g. the term “feature” should be understood as “feature class” or “feature type” or “feature instance” as best fits the immediate context in which it is used (and where there might be confusion, it is written out in full as feature class/type-instance). The model defines real world entities as a combination of descriptive and spatial characteristics (S-122 Product Specification clause 6).

This clause of the DCEG contains general information needed to understand the encoding rules and describes fundamental common rules and constraints. It also describes datasets and metadata. The data model object types used within S-122 and their encoding rules and guidelines are defined in detail in subsequent clauses of this document.

Within this document the features, information types, associations, and attributes appear in **bold text** or *italic text*, to distinguish them from surrounding words.

2.2 Descriptive characteristics

2.2.1 Feature

A feature contains descriptive attributes that characterize real world entities.

The word ‘feature’ as used in the ISO 191xx series and in S-100 based product specifications has two distinct but related senses – ‘feature type’ and ‘feature instance’. A feature instance is a single occurrence of the feature and is represented as an object in a dataset. The location of a feature instance on the Earth’s surface is indicated by a relationship to one or more spatial primitive instances. A feature instance may exist without referencing a spatial primitive instance.

2.2.1.1 Geographic feature class

Geographic (Geo) feature types carry the descriptive characteristics of a real world entity which is provided by a spatial primitive instance.

2.2.1.2 Meta feature class

Meta feature type contains information about other features.

2.2.1.3 Charted background feature

The data product would mostly be visualized as an overlay of an ENC or other GIS applications. Consequently, all necessary descriptive and spatial characteristics to provide a charted background should be provided by the underlying application.

2.2.1.4 Information type

An information type has no geometry and therefore is not associated to any spatial primitives to indicate its location.

An information type may have attributes and can be associated with features or other information types in order to carry information particular to these associated features or information types.

2.3 Spatial characteristics

2.3.1 Spatial primitives

The allowable spatial primitive for each feature is defined in the Feature Catalogue. Allowable spatial primitives are point, curve, and surface.

Within this document, allowable spatial primitives are included in the description of each feature. For easy reference, [Table 2-1](#) below summarises the allowable spatial primitives for each feature. In the table, abbreviations are as follows: point (P), curve (C), surface (S), and none (N). Abstract features are excluded from this table since they cannot have feature instances in datasets.

Table 2-1 — Features and their spatial primitives

Feature	P	C	S	N
InformationArea			S	
MarineProtectedArea		C	S	
RestrictedArea			S	
VesselTrafficServiceArea			S	
DataCoverage			S	
QualityOfNonBathymetricData			S	
TextPlacement	P			

2.3.2 Capture density guideline

Coordinate density can have a significant impact on file size and system performance. A rule of thumb is to limit the coordinate density to 0.3 mm at maximum permitted display scale. For a scaleless product, the producer should keep in mind the expected scale range for typical use and the density of coordinates needed to suit the needs of the product.

The capture density will follow the recommendation of the S-101 (ENC) DCEG, which states curves and surface boundaries should not be encoded at a point density greater than 0.3 mm at permitted display scale.

A curve consists of one or more curve segments. Each curve segment is defined as a loxodromic line on WGS84, or as an arc or circle. Long lines may need to have additional coordinates inserted to cater for the effects of projection change.

The presentation of line styles may be affected by curve length. Therefore, the encoder must be aware that splitting a curve into numerous small curves may result in poor symbolization.

2.4 Attributes

Attributes may be simple type or complex type. Complex © attributes are aggregates of other attributes that can be simple type or complex type attributes. Simple (S) attributes are assigned to one of the types collected at [Clause 2.4.1](#).

The binding of attributes to a feature, the binding of attributes to attributes to construct complex attributes, and attribute multiplicity are all defined in the Feature Catalogue.

Within this document, the allowable attributes are included in the description of each feature, as well as the allowable values for enumeration type attributes.

2.4.1 Simple attribute types

Each simple attribute is assigned one of the attribute datatypes in [Table 2-2](#):

Table 2-2 — Simple attribute types

Abbreviation	Attribute type	Description
BO	Boolean	A value representing binary logic. The value can be either True or False. The default state for Boolean type attributes (i.e. where the attribute is not populated for the feature) is False.
CL	Code List	<p>A type of flexible enumeration (see “EN” below). A code list type is a list of literals which may be extended only in conformance with specified rules. Attributes of a code list type may take values from the list or other values which are defined according to the rules. The rules should be part of the specification of the individual codelist type. A code list could either be closed (fixed) or open (extensible).</p> <p>A code list type has the following properties:</p> <ol style="list-style-type: none"> 1. A description of the code list type, 2. The URI where the list could be found, and 3. An encoding instruction.
DA	Date	<p>A date provides values for year, month and day according to the Gregorian Calendar.</p> <p>Example (XML/GML): 1998-09-18 (YYYY-MM-DD)</p> <p>S-122 uses only XML-based formats (including GML) and therefore the ISO “basic” format described in S-100 is not used.</p>
DT	Date and Time	<p>A DateTime is a combination of a date and a time type.</p> <p>Example (XML/GML): 1985-04-12T10:15:30 (YYYY-MM-DDThh:mm:ss)</p> <p>S-122 uses only XML-based formats (including GML) and therefore the ISO “basic” format described in S-100 is not used.</p>
EN	Enumeration	<p>A fixed list of valid identifiers of named literal values. Attributes of an enumerated type may only take values from this list.</p>
IN	Integer	<p>A signed integer number. The representation of an integer is encapsulation and usage dependent.</p> <p>Integer attribute values must not be padded by non-significant zeroes. For example, for a number of 19, the value populated for the attribute must be 19 and not 019.</p> <p>Examples: 29, -65547</p>
RE	Real	<p>A signed real (floating point) number consisting of a mantissa and an exponent. The representation of a real is encapsulation and usage dependent.</p> <p>Real attribute values must not be padded by non-significant zeroes. For example, for a signal period of 2.5 seconds, the value populated for the attribute signal period must be 2.5 and not 02.50.</p> <p>Examples: 23.501, -0.0001234, -23.0, 3.141296</p>
TD	Truncated Date	<p>One or more significant components of the modelling date are omitted.</p> <p>Example: A GML dataset would use a GML built-in type and encode it as <gMonth>--02</gMonth></p> <p>S-122 uses only XML-based formats (including GML) and therefore the ISO “basic” format described in S-100 is not used.</p>
TE	Free text	<p>An arbitrary-length sequence of characters including accents and special characters from a repertoire of one of the adopted character sets.</p>
TI	Time	<p>A time is given by an hour, minute, and second. Time zone according to UTC is optional. Character encoding of a time is a string that follows the local time.</p> <p>Examples (XML/GML): 18:30:59Z; 18:30:59+01:00; 18:30:59</p>

Abbreviation	Attribute type	Description
URL	URL	A uniform resource locator (URL) is a URI that provides a means of locating the resource by describing its primary access mechanism (RFC 3986). Example: https://registry.ihodata.org
URN	URN	A persistent, location-independent, resource identifier that follows the syntax and semantics for URNs specified in RFC 2141. Example: urn:mrn:ihodata:S-122:1:0:0:Regulations

2.4.2 Mandatory attributes

Some attributes are mandatory and must be populated for a given feature. There are some reasons why attribute values may be considered mandatory:

- They are fundamental to the definition of a feature;
- They are required to support the correct portrayal of a feature instance;
- Certain features make no logical sense without specific attributes;
- Some attributes are required for safety of navigation.

Within this document, mandatory attributes are those with a multiplicity of 1,1 or 1,n ($n > 1$) or 1,*. The attribute multiplicity is identified in the description of each feature class.

2.4.3 Conditional attributes

The feature classes or information types do not contain conditional attributes.

Complex attributes which are assigned to feature classes or information types have at least one sub-attribute which is mandatory (or conditionally mandatory). Where the sub-attribute of a complex attribute is conditional, this is indicated in the Remarks sub-clause for the relevant feature class entries.

2.4.4 Missing attribute values

Where a value of a mandatory attribute is not known, the attribute must be populated with an empty (null) value.

Where the value of a non-mandatory attribute is not known, the attribute must not be included in the dataset.

2.4.5 Multiplicity

In order to control the number of allowed attribute values or sub-attribute instances within a complex attribute, S-100 uses the concept of multiplicity. This defines lower and upper limits for the number of values, whether the order of the instances is significant, and if an attribute is mandatory. Common examples are shown in [Table 2-3](#):

Format: MinOccurs, MaxOccurs (a * indicates that infinite instances are possible, the term (ordered) indicates that the order of the provided instances is significant)

Table 2-3 — Multiplicity of attributes

Multiplicity	Explanation
0,1	An instance is not required; if provided there must only be one instance.
1,1	An instance is required and there must only be one instance.
0,*	An instance is not required and there can be an infinite number of instances.
1,*	An instance is required and there can be an infinite number of instances.
1,* (ordered)	An instance is required and there can be an infinite number of instances, the order of which is significant.
2,2	Two instances are required and there must be no more than two.

2.4.6 Spatial attribute types

Spatial attribute types must contain a referenced geometry and may be associated with spatial quality attributes. Each spatial attribute instance must be referenced by a feature instance or another spatial attribute instance.

2.4.6.1 Quality of spatial attributes

The quality of spatial attributes in S-122 is described in a Quality of Non-Bathymetric Data meta-feature. This meta-feature defines areas within which uniform assessment exists for the quality. It is described in detail later in this document.

If the spatial quality attributes for an individual instance of a spatial primitive differ from the quality indicated in the overlying Quality of Non-Bathymetric Data meta-feature, the quality attributes for that instance are carried in an information class called spatial quality. Only points and curves can be associated with spatial quality. S-122 does not use multi-points. Currently, no use case for associating surfaces with spatial quality attributes is known, therefore this is prohibited. Vertical uncertainty is prohibited for curves as this dimension is not supported by curves.

NOTE: S-122 does not make use of the S-101 Quality of Bathymetric Data meta- feature since depth range uncertainties are not needed. The Quality of Non-Bathymetric Data meta-feature has all the quality attributes needed by S-122.

Figure 2.1—Spatial quality information

2.4.7 Portrayal feature attributes

Marine Protected Areas data products will be used within ECDIS where ENC data is displayed based on the rules defined within the S-101 Portrayal Catalogue. While most ECDIS portrayal is based on attributes describing the instance of a particular feature in the real world, certain feature attributes are used in portrayal rules to provide additional functionality in the ECDIS. [Table 2-4](#) provides a list of attributes which have specific influence on portrayal.

EDITORIAL NOTE

Update to align with S-101

Table 2-4 — Attributes which have effects on portrayal

Attribute	Effects on portrayal
displayName	This Boolean attribute determines if the text for a name should be displayed. If not populated the default rules provided in the portrayal catalogue will be used.
information	Population of this complex attribute will result in the display of the magenta information symbol to highlight additional information to the user.
pictorialRepresentation	The population of this Text attribute will result in the display of the magenta information symbol to highlight additional information to the user.
textContent	The population of this complex attribute will result in the display of the magenta information symbol to highlight additional information to the user.

2.4.8 Textual information

Textual information may provide additional information essential to understand the presence of the Marine Harbour Infrastructure and other features of an S-122 product. This information may also provide legal information pertaining to the S-122 product features.

The methods to provide textual information vary from the simple provision of short text, to the more structured provision of extensive text. The length of the text determines the method and the attribute selection, see [Clause 2.4.8.2](#).

2.4.8.1 Specialized information types for common kinds of textual information

The information types Restrictions, Recommendations, Regulations, or NauticalInformation must be used to encode text information when the DCEG allows them to be associated to the feature or information type and the information is of the appropriate kind (a restriction, regulation, etc.).

In exceptional circumstances and only if the use of the information types Restrictions, Recommendations, or Regulations is not sufficient, NauticalInformation can be used to encode additional textual information associated to a feature or a group of features.

In some cases, there may be a specialized attribute that is specifically intended for the data in question. If an appropriate specialized attribute is available, it must be used in preference to information or textContent. For example, feature names will generally be encoded in the name sub-attribute of complex attribute featureName, instead of information→text.

2.4.8.2 Textual information attributes

Textual information which is not appropriate for any of the Text-type attribute (or sub-attribute) allowed for the feature/information type should be encoded using either information or textContent complex attributes. Generally, either information or textContent is allowed, but not both.

2.4.8.3 Languages

Both information and textContent define a language sub-attribute for specifying the language in which the text is encoded.

The exchange language for textual information should be English; therefore it is not required to populate the sub-attribute language for an English version of textual information.

Languages other than English may be used as a supplementary option, for which language must be populated with an appropriate value to indicate the language.

When a national language is used in the textual attributes, the English translation must also exist.

The specification of the language attribute in the IHO GI registry states “The language is encoded by a 3 character code following ISO 639-2/T.” These codes and the corresponding language names may be obtained from the codelist S100_MD_LanguageCode in the S-100 codelists file, which is part of the S-100 schemas distribution, at the URLs below:

- XML file: <https://schemas.s100dev.net/schemas/S100/5.2.0/resources/Codelists/cat/codelists.xml>
- Web list: <https://schemas.s100dev.net/schemas/S100/5.2.0/resources/Codelists/cat/codelists.html>

2.4.8.4 Minimal use of generalized text attributes

The complex attributes information and textContent must not be used when it is possible to encode the information by means of any other attribute. The population of these attributes provides symbols on an ECDIS screen. Therefore producers should carefully consider use of these attributes as the symbol may contribute significantly to ECDIS screen clutter and text attributes should be populated only when the content conveys useful information.

2.4.8.5 Short textual information

The text sub-attribute of complex attribute information should generally be used for short notes or to transfer information which cannot be encoded by other attributes, or to give brief information about a feature. The use of the complex attribute information as a stand-alone complex attribute is intentionally limited to the information types ContactDetails, Applicability, NonStandardWorkingDay, and ServiceHours, which do not need the additional attributes defined in textContent. The reason for the limited use of information as a stand-alone complex attribute is to provide a structured and harmonised approach to textual information within the S-122 product data sets.

The text populated in text must not exceed 300 characters. Character strings contained in text sub-attribute must be UTF-8 character encoding.

If the text sub-attribute of information is populated, the headline, fileReference, and fileLocator sub-attributes must not be populated.

2.4.8.6 Complex or lengthy textual information

More complex encodings of text may use either information or textContent. The feature catalogue and the feature/information type definitions in this DCEG indicate whether information or textContent is allowed.

The complex attribute textContent also has information as a complex sub-attribute. If a short note must be encoded in a feature or information type which has only textContent as an attribute, it should be encoded as textContent→information→text.

Complex text information, such as text longer than 300 characters, formatted text, or HTML extracts from shipping regulations, must be encoded in a file named in either information→fileReference or textContent→information→fileReference. The construction textContent→information→fileReference should be used if the feature/information type provides textContent as complex attribute.

The complex attribute information defines an optional sub-attribute headline which may be used for a short title not exceeding 60 characters. The content should be short but informative – if the textual information is divided into sections, the most relevant section header from the referenced content may be a good choice for headline.

The complex attribute textContent defines an optional sub-attribute categoryOfText for indicating whether the text is the full text from the source, an extract from the source, or a summary prepared by the encoder. Populating categoryOfText is recommended whenever the textual information is taken or summarised from a law or regulation.

If it is considered necessary to include a description of the source of the textual information, the sub-attribute sourceIndication of textContent must be used. Encoding a description of the source is strongly recommended for textual information whose source is considered as information the end-user must have, e.g., because the date of issue must be conveyed or because it cites official regulations which are frequently updated.

NOTE: Some government documents are frequently updated, e.g., the U.S. Electronic Code of Federal Regulations, which is currently updated every working day even though a particular section may be stable for years.

2.4.9 Attributes referencing external files

2.4.9.1 Predefined derived types

Table 2-5 presents the following predefined derived types which are described in S-100 (clause 1-4.6):

Table 2-5 — Predefined derived types

Name	Description	Derived from
URI	A uniform resource identifier which character encoding shall follow the syntax rules as defined in RFC 3986. EXAMPLE http://registry.oho.int	CharacterString
URL	A uniform resource locator (URL) is a URI that provides a means of locating the resource by describing its primary access mechanism (RFC 3986). EXAMPLE http://registry.oho.int	URI
URN	A persistent, location-independent, resource identifier that follows the syntax and semantics for URNs specified in RFC 2141. EXAMPLE urn:oho:s101:1:0:0:AnchorageArea	URI

2.4.9.2 Reference to textual files

The files referenced by complex attribute information and its sub-attribute fileReference must be *.TXT or *.HTM files, and may contain formatted text. It is up to the Producing Authority to determine the most suitable means of encoding a particular piece of text (as text or HTML). The format of the reference to the file should be a “file URI” (S-100 1-4.6).

Besides being bound to certain types, the complex attribute information is also a sub-attribute of the complex attribute textContent. This means that any type that binds textContent as an attribute can also contain a reference to a textual file via an information sub-attribute. In S-122, there are several features, information types, and complex attributes that bind either textContent or information.

The exchange language for textual information should be English. The sub-attribute language must be populated with an appropriate value to indicate the language used. Languages other than English may be used as a supplementary option. Generally this means, when a national language is used in the textual attributes, the English translation must also exist.

Files must only use UTF-8 character encoding even when the sub-attribute language is populated with a language other than English.

If it is necessary to indicate a specific section within a large text file, this may be done by encoding the location in the fileLocator sub-attribute of information, as described in [Table 2-6](#).

Producers and application developers should note that the use of the fileLocator attribute enables a single support file to contain separate chunks of text referenced from different features, information types, or complex attribute. Adopting this practice enables producers to reduce the number of external files needed with a dataset.

Table 2-6 — Locators for external files

Format	File extension	Content of fileLocator
Text	TXT	Locators to text files are not permitted; the file should be split into separate text files or an HTML file used instead.
HTML	HTM	The HTML fragment identifier, i.e., the value of the HTML name or id attribute of the target (as defined in the relevant HTML specification).

2.4.9.3 Reference to external sources

References to Internet sources should be encoded using the onlineResource sub-attribute of *textContent*. Encoders should be aware that systems may not be able to access the Internet, so onlineResource should be used only for non-essential information. Only sources that can be certified as secure and free from malicious downloads should be provided.

2.4.9.4 Reference to graphics

If it is required to indicate a graphic, the complex attribute graphic must be used. The sub-attribute *pictorialRepresentation* must be used to indicate the file name (without the path) of the external graphical file. Graphic files that form part of the data product must be content with the characteristics collected in [Table 2-7](#).

Table 2-7 — Graphics characteristics

Characteristics	Values
Recommended Resolution	96 DPI
Minimum Size x,y	200,200 pixels
Maximum Size x,y	800,800 pixels
Bit Depth	8 Bit Indexed Colour
Compression	LZW
Format	Tiff 6.0

File sizes should consider the maximum permitted sizes of datasets and exchange sets.

Additional information about the graphic file may be encoded in other sub-attributes of attribute graphic, as described in [Clause 2.4.12](#).

2.4.10 Dates

Dates may need to be encoded as complete or truncated values, depending on available information and allowed format for the particular attribute. The definition of the attribute will indicate if it must take a

complete value (type Date or DA) or is allowed to take a truncated value (type S100_TruncatedDate or TD). Complete and truncated dates are different value types (see S-100 1-4.5.2 Table 1-2).

For attributes that use the complete date type (type Date or DA), all their components (year, month, and day) must be specified.

For attributes that use the truncated date type (type S100_TruncatedDate or TD), zero, one, or two of the year/month/day components may be omitted. If the year component is included, it must be specified using exactly 4 digits.

2.4.10.1 Complete dates

Dates (except truncated dates, see the following clause) must be encoded in conformance with the Date format as specified in S-100 Clause 1-4.5.2 which is the same as the DA format in [Table 2-2](#) in this document. The data values have to be provided in accordance with the Gregorian Calendar starting with four digits for the year, two digits for the month and two digits for the day.

Example: The date 18 September 2010 is encoded as follows:

In the GML format: <date>2010-09-18</date>

Note that since both discovery metadata and GML datasets are XML files, both will use the “GML format” above.

2.4.10.2 Truncated dates

In Truncated Dates one or more components (year, month, or day) of the date is not specified. Truncated date values must be encoded in conformance with the S100_TruncatedDate format or equivalent as specified in S-100 (clauses 1-4.5.2 and 3-9) which is the same as the TD format in [Table 2-2](#) in this document. If encoding attributes which can take truncated date values (e.g., fixedDateRange, periodicDateRange, reportedDate) and no specific year, month, or day is required, the values must be encoded in conformance with the truncated date format as specified in S-100 (clauses 1-4.5.2 and 3-9), using the format-specific type for XML/GML.

To encode partial dates in the XML/GML data format:

Table 2-8 — Date encoding format in XML and GML

Description	ISO 8211	GML
No specific year, same day each year	----MMDD	<gMonthDay>--MM-DD</gMonthDay>
No specific year, same month each year	----MM--	<gMonth>--MM</gMonth>
No specific day	YYYYMM--	<gYearMonth>YYYY-MM</gYearMonth>
No specific month and no specific day	YYYY----	<gYear>YYYY</gYear>

NOTE: YYYY = calendar year; MM = month; DD = day.

The dashes (–) indicating that the year, month, or date which is not specified must be included in the encoding (with no space between the dashes).

2.4.10.3 Start and end of ranges

In accordance with S-100 clause 3-8, the start and end instants of a range or period are included in the range or period.

EXAMPLE 1: If the beginning of a date range is encoded as the complete date 01 January 2016, the period begins at 00:00:00 on 1 January 2016, and the whole of New Year's Day is included in the period. If the end of the date range is encoded as 01 January 2016, the period ends at 24:00:00 on 1 January 2016, i.e., again the whole of New Year's Day is included in the period.

EXAMPLE 2: If the beginning of a period is encoded in truncated date format as ----01-- (i.e., year and day not specified), the period begins at 00:00:00 on 1 January each year. If the end of the period is encoded as ----01--, the period ends at 24:00:00 on 31 January each year.

NOTE (1): Particular care should be taken if the start or end date is 28 or 29 February. S-100 3-8.3 explains the implications for end of February. For example, the truncated date ----02-- will be interpreted as 29 February in leap years and 28 February in non-leap years, while ----0228 will be interpreted as 28 February in every year.

NOTE (2): In accordance with ISO practice at the time S-100 date and time formats were defined, the time 00:00:00 means midnight at the start of a day and 24:00:00 means midnight at the end of a day. This continues to be S-100 usage.

2.4.10.4 Schedules

Weekly service schedules of a feature can be comprehensively described by using the information types ServiceHours and NonStandardWorkingDay.

EXAMPLE: A feature service is available under normal operation status 24 hours/day on Monday and Wednesday and from 08:00 to 16:00 LT from Thursday to Saturday. The service is available by pre-arrangement on public holidays and the 5 of August of each year when they fall on days which would otherwise be normal working days.

```

ServiceHours
scheduleByDayOfWeek
  categoryOfSchedule =1 (normal operation)
  timeIntervalsByDayofWeek
    dayOfWeek =2(Monday), 4(Wednesday)
    dayOfWeekIsRange =0 (false)
  timeIntervalsByDayofWeek
    dayOfWeek =5(Thursday), 7(Saturday)
    dayOfWeekIsRange =1 (true)
    timeOfDayStart = 08:00:00
    timeOfDayEnd = 16:00:00
NonStandardWorkingDay
  dateFixed = ---08-05 (5 August)
  dateVariable = public holidays
  information.text = "By pre-arrangement"

```

The above example can be encoded as follows:

```

<S131:ServiceHours gml:id="(GML ID of ServiceHours)">
  <scheduleByDayOfWeek>
    <categoryOfSchedule code="1">Normal Operation</categoryOfSchedule>
    <timeIntervalsByDayOfWeek>
      <dayOfWeek code="2">Monday</dayOfWeek>
      <dayOfWeek code="4">Wednesday</dayOfWeek>
      <dayOfWeekIsRange>0</dayOfWeekIsRange>
      <timeOfDayStart>00:00:00</timeOfDayStart>
      <timeOfDayEnd>24:00:00</timeOfDayEnd>
    </timeIntervalsByDayOfWeek>
    <timeIntervalsByDayOfWeek>
      <dayOfWeek code="5">Thursday</dayOfWeek>
      <dayOfWeek code="7">Saturday</dayOfWeek>
      <dayOfWeekIsRange>0</dayOfWeekIsRange>
      <timeOfDayStart>08:00:00</timeOfDayStart>
      <timeOfDayEnd>16:00:00</timeOfDayEnd>
    </timeIntervalsByDayOfWeek>
  </scheduleByDayOfWeek>
  <partialWorkingDay xlink:href="(reference to NonStandardWorkingDay)" />
</S131:ServiceHours>

<S131:NonStandardWorkingDay gml:id="(GML ID of NonStandardWorkingDay)">
  <dateFixed><gMonthDay>--08-05</gMonthDay></dateFixed>
  <dateVariable>public holidays</dateVariable>
  <information><text>By pre-arrangement</text></information>
  <theServiceHours_nsdy xlink:href="(reference to ServiceHours)" />
</S131:NonStandardWorkingDay>

```

If the days of week are known but the hours of availability are unknown, there is no time attribute. Twenty-four availability is indicated by encoding the availability period as 000000-240000. Special cases such

as unknown can be explained in the textContent or information attribute of ServiceHours. To encode two or more periods within the same day, repeat the timeOfDayStart and timeOfDayEnd attributes. If one of the times is not known, it may be nilled as described in [Clause 2.4.4](#).

For example, to encode open hours of 8 a.m. to 12 noon and 1 p.m. to 5 p.m. on Thursdays and Saturdays:

```
timeIntervalsByDayofWeek
dayOfWeek =5(Thursday), 7(Saturday)
dayOfWeekIsRange =1 (true)
timeOfDayStart = 08:00:00
timeOfDayStart = 13:00:00
timeOfDayEnd = 12:00:00
timeOfDayEnd = 17:00:00
```

The order of repeated timeOfDayStart and timeOfDayEnd attributes is significant, since intervals are specified by matching them pairwise in order.

UTC is indicated by the Z suffix. The absence of the Z suffix indicates local time.

The absence of any additional information other than date (fixed or variable) in NonStandardWorkingDay should be interpreted as closure on the specified days. Non-standard working days do not need to be associated with ServiceHours instances categorized as “closure” (categoryOfSchedule=Closure) because the closure is already indicated in the ServiceHours instance.

2.4.10.5 Times

If it is required to provide information of the start time and end time of an active period of a feature, it must be encoded using the attributes timeOfDayStart and timeOfDayEnd. The order has significance.

2.4.11 Combination of date schedules and times

Schedule information can also include time of day. The complex attribute timeIntervalsByDayofWeek also includes timeOfDayStart and timeOfDayEnd attributes to encode the daily start and end times of service. Complete instructions on how to encode schedules are described in [Clause 2.4.10.4](#).

2.4.12 Graphic information

A graphic file should be appropriate for the purpose and should supplement the information in terms of navigational relevance. Preferably, the graphic should provide perspective relevant to the view of the mariner. Graphics should be such that all the information in the graphic is legible in the application display. Graphic information must be encoded using the complex attribute graphic. The simple sub-attribute pictureInformation should be used to provide credits to the picture creator, copyright owner etc. Assuming that graphic information provides a coastal view, mariners are interested in knowing from which point on sea that graphic has been taken. The complex attribute bearingInformation (see [Clause 2.4.12.1](#)) provides all necessary information.

2.4.12.1 Bearing information

The most accurate information should be provided if it is necessary to indicate a position from where a picture has been taken. information is a sub-complex attribute of bearingInformation and should be used to specify that no bearing information can be provided whenever such is the case. The sub-attributes sectorBearing and orientation can be used to describe a certain level of inaccuracy in the position determination.

2.5 Associations

2.5.1 Introduction

An association expresses a relationship between two classes—features, information types, or a feature and an information type. Objects in the dataset (instances of feature/information types) are related only if the link between them is encoded in the dataset. An association end may have a multiplicity which describes how many instances the feature or information type instance at the other end is allowed to link to.

2.5.2 Association names

The association name is normally provided by the UML diagram at the middle of the connection line/arrow between the two involved classes and can be obtained from the feature and information type tables provided in this document). Association names may be omitted in the UML diagrams for the following reasons: a) the association is defined by an association class, see 2.5.4 (the name of the association class is used); b) to avoid cluttering the diagram – however, the name is always documented in the feature/information type tables.

2.5.3 Association roles

Either or both association ends can have a name (role). Roles may be also omitted from the diagram to reduce clutter – again, the role name is documented in the feature/information type tables. NOTE: Instead of documenting every single role, Product Specifications may describe rules for defining default roles.

2.5.4 Association classes

Association classes allow relationships to be characterized by one or more attributes. The attributes of the association class belong to the association itself, not to any of the features or information types it connects. An association class is both an association and a class. Within an S-122 product the association classes Permission Type and Inclusion Type may be used for relating vessel classes to feature and information types.

2.5.4.1 Permission Type

This association class specifies the relationship of the vessel class to a feature, e.g., whether access to a feature (or use of a facility) is prohibited or permitted for a specified class of vessel. The class of vessel is described by the simple and complex attributes of the information type Applicability such as length, cargo, etc. The attributes of the association class describe the nature of the relationship, i.e., whether access to an area is permitted or prohibited, or whether use of a service is required or recommended.

Figure 2.2—Association class for hypothetical requirement for non-use of a berth by a vessel carrying hazardous cargo

EXAMPLE: An association between an Applicability instance with attribute categoryOfDangerousOrHazardousCargo = IMDG Code Class 3 and an instance of feature Berth, with Permission Type's attribute categoryOfRelationship = Prohibited, means that vessels carrying flammable liquids (hazardous cargo type class 3 in the IMDG Code) cannot use the Berth instance. Note that in this case the relationship is inherited by the Berth instance from the abstract class FeatureType.

2.5.4.2 Inclusion Type

This association class defines whether a specified customer (class of vessels, as described by Applicability) is excluded or included from a particular regulation, recommendation, etc. Again, the attributes of the association class describe the nature of the relationship; in this case whether the vessel is included or excluded from the regulation, etc.

Figure 2.3—Association class for inclusion of vessel types in regulations

EXAMPLE: An association between an Applicability instance with attribute categoryOfDangerousOrHazardousCargo = IMDG Code Class 3, with Inclusion Type's attribute membership = included, and an association of a Regulation instance to the same Inclusion Type, means that the information provided by the Regulation (a sub-type of AbstractRXN) applies to vessels carrying flammable liquids (hazardous cargo type class 3 in the IMDG Code).

NOTE (1): Since AbstractRXN is an abstract type, it cannot have direct instances in the dataset. Only instances of its (non-abstract) sub-types can be used.

NOTE (2): Specific tools may use different presentations in their user interfaces, e.g., as two associations (as described in the text of the example), or one association with an association class also shown (as shown in Figure 2.3).

2.5.5 Use of various associations

2.5.5.1 General

In general, associations must be encoded whenever the relationship is useful for navigation, monitoring, voyage or route planning, or reporting purposes, or any other purpose for which the dataset is intended.

The multiplicity lower bound of “0” at an association end means only that the absence of a link to the relevant instance does not invalidate the dataset. The encoding instructions for individual feature and information types describe what associations are allowed and whether they are required or optional.

2.5.5.2 Generic association for uncategorized additional information

Unless other associations are specified, information types are associated to the relevant features using the association name AdditionalInformation and the role names providesInformation and informationProvidedFor.

2.5.5.3 Associations to Restrictions, Recommendation, Regulations, and Nautical Information

The Restrictions, Recommendation, Regulations, Nautical Information are associated to the relevant features using the association named AssociatedRxN (inherited from their common abstract super-type). The roles at the ends of this association are appliesInLocation and theRxN (the Restriction, Regulation etc.). If the regulation applies only to a specific class, or if it mentions an exempt class, an additional association to an Applicability object is encoded using the InclusionType association class.

2.5.5.4 Conventional Association

Certain features and information types may be permitted or required to have associations to other feature or information types. The allowed or mandatory associations for a feature/information type are shown in the application schema (clause 4 of the Product Specification) and listed in the documentation for individual types in this Annex ([Section 4](#) — [Section 12](#)). Definitions of the associations and roles are also given in the DCEG.

2.5.5.5 Where to Encode Associations

The presentation and management of associations will be determined by the user interface of the encoding software tools. Since S-100 permits feature-information associations to be encoded only from the geographic feature to the information type and not vice versa, the information-to-feature link might be unavailable or treated differently from the feature-to-information link.

2.6 Datasets

2.6.1 Types of Datasets

A dataset is a grouping of features, attributes, geometry and metadata which comprises a specific coverage. [Table 2-9](#) shows the types of datasets which may be produced and contained within an exchange set:

Table 2-9 — Dataset types

Dataset	Explanations
New dataset	Data for an area different (in coverage and/or extent) to existing datasets.
New Edition of a dataset	A re-issue plus new information which has not been previously distributed by Updates. Each New Edition of a dataset must have the same name as the dataset that it replaces and should have the same spatial extents.
Update dataset	Updated or new information. Contains information about objects being added, modified, or deleted.

2.6.2 Overlay data sets

S-122 datasets are intended to be used together with S-101 ENC (or similar data products) which will act as a base layer. The base layer is expected to provide navigational and visual context. Generally, an overlay dataset like S-122 does not provide “skin of the earth” coverage and there will be large areas with no data coverage because the S-122 application schema does not include any feature for designating a region as “other”, or “not an MHI area” (i.e., there is no S-122 feature equivalent to the S-101 Unsurveyed Area). Further, an overlay dataset does not include features that provide auxiliary information such as bathymetry within a routeing measure area.

2.6.3 Data coverage

A Marine Harbour Infrastructure dataset can contain one or more DataCoverage features (see [Clause 4.1](#)). The data boundary is defined by the extent of the DataCoverage meta features. Data must only be present within DataCoverage meta features. When a feature extends across datasets of overlapping scale ranges, its geometry must be split at the boundaries of the DataCoverage features and its complete attribute description must be repeated in each dataset. An Update dataset must not extend the data coverage for the base dataset to which it applies. Where the extent of the data coverage for a base dataset is to be changed, this must be done by issuing a New Edition of the dataset.

2.6.4 Discovery metadata

Discovery metadata is intended to allow applications to find out important information about datasets and accompanying support files to be examined without accessing the data itself (or without reading the support file). Discovery metadata includes, but is not limited to:

- information identifying the product specification and encoding format;
- edition and version numbers, production/release date, and other details of data creation and updating;
- data coverage of the dataset;
- summary descriptions of content, purpose, use, and limitations;
- identification and contact information for the producer and distributor of the dataset.

Discovery metadata is encoded in the exchange catalogue. S-122 uses the same classes and attributes for discovery metadata as S-100, but adds certain product-specific restrictions. The classes and attributes for generic discovery metadata are defined in S-100 Part 17. Constraints and restrictions specific to S-122 are defined in the S-122 Product Specification. The schema for the exchange catalogue file (CATALOG.XML) for S-122 is the same as the S-100 generic schemas and is available from the schema server (<https://schemas.s100dev.net>).

2.6.5 Dataset header metadata

Dataset header metadata contains structural and discovery metadata that apply to the whole dataset and are encoded in the dataset file. The elements are described in S-100 Part 10b.

2.6.6 Dataset units

The depth, height and positional uncertainty units in a dataset must be metres.

2.6.7 Dataset Coverage

Marine Harbour Infrastructure datasets are spatially limited.

In areas which include neighbouring producer nations, producing agencies should co-operate to agree on dataset boundaries and ensure no data overlap. Where possible, adjoining nations should agree on common data boundaries within a technical arrangement based on cartographic convenience and benefit to the mariner.

If an MHI feature extends outside the product coverage and the adjoining object does not exist, e.g. due to delay in the production of the neighbouring HO product, an indication should be placed at the outer edge of the product.

2.6.8 Overlaps

The DataCoverage features within a dataset must not overlap, however DataCoverage features from different datasets may overlap if they have differing maximum display scales or the datasets are for different ports.

MHI does not envisage multiple datasets for the same port, and does not anticipate overlapping datasets for a single port.

Overlapping datasets are possible in the case where there are two or more ports in close proximity (which may, for example, have overlapping approaches). In the latter case, consideration should be given to creating a single dataset that covers all the ports in the region in question, but overlapping datasets may be created as necessary. In case of overlapping datasets, the ECDIS should display an indicator and allow the user to select one dataset for display.

2.6.9 Feature Object Identifiers

Each feature and information instance within a dataset must have a unique universal Feature Object Identifier [FOID]. This is mapped to the `gml:id` attribute of the feature in the dataset (FOID and `gml:id` may not be identical due to XML restrictions on the format of `gml:id` attributes). Where a real-world feature has multiple geometric elements within a single dataset due to the dataset scheme, the same FOID may be used to identify multiple instances of the same feature. Since `gml:id` attributes in the same file must be unique, the mapping between FOID and `gml:id` must allow for a one-to-many mapping if needed. Features within a dataset may carry multiple geometries. Features split across multiple datasets may be identified by the same FOID. Features repeated in different scale ranges may be identified by the same FOID. FOID must not be reused, even when a feature has been deleted. However, the same feature can be deleted and added again later using the same FOID. NOTE (1) (informative): The current format of FOID is defined in S-101 as a concatenation of subfields Producing Agency, Feature Identification Number and Feature Identification Subdivision. The identifier is currently formatted as a string value. The identifier may eventually be replaced with an identifier adhering to the scheme for Maritime Resource Names (MRN) which is based on the format of URNs. NOTE (2): S-122 uses `gml:id` as a proxy representing FOID. S-122 does not define a rule for the structure or generation of `gml:id` values or their relation to identifiers in S-57, S-101 or other sources. Producers may generate `gml:id` values according to any desired scheme or schemes

2.6.10 180° Meridian of Longitude

Datasets must not cross the 180° meridian of longitude.

2.7 Geographic names

2.7.1 Feature names

If it is required to encode an international or national geographic name, it must be done using complex attribute `featureName`.

If it is required to encode a geographic name for which there is no existing feature, an appropriate area feature must be created. In order to minimise the data volume, these features should, where possible, use the geometry of existing features.

Geographic names should be encoded with the complex attribute `featureName`. The complex attribute `featureName` consists of the simple sub-attributes `language`, `name` and a Boolean type to indicate whether that particular name is the `displayName` or not.

National geographic names can be left in their original national language in a non-English iteration of the complex attribute `featureName` (but only if the national language can be expressed using lexical level 0 or 1), or transliterated or transcribed and used in an English iteration of the complex attribute `featureName`, in which case the national name should be populated in an additional iteration of the `featureName` with sub-attribute `language` populated with the relevant national language value in accordance with ISO 639-2/T.

All area and point features within a Marine Harbour Infrastructure product should be encoded using `featureName` if a name is available.

A group of features, associated with a particular geographic name, should have the name encoded using `featureName` on an aggregation feature (of type surface or point, or no geometry, as appropriate). The name should not be encoded on the individual hydrographic features.

A group of service or forecast areas with the same attribute values associated with the same name should be encoded as spatial attributes of the same feature (so there would be only one feature with multiple spatial attributes for location).

Named features listed in Hydrographic Office's Sailing Directions or other documents that may assist in locating service information should be encoded using `featureName` on the relevant feature (e.g. `WaterwayArea`). In all instances, if the exact extent of the feature to be named is known, a feature must be created. If the exact extent is not known, or the area is too small, an existing or specifically encoded point feature should be used to encode the geographic name.

2.7.2 Text placement

EDITORIAL NOTE

Update from S-101 2.0.0

The cartographic feature TextPlacement is used specifically to place text cartographically. The properties of the TextPlacement feature are described as follows: * Geometry (point) – the spatial point location of the text string. * text type – the attribute (or class) which is to be placed. * orientation value and text offset mm – the bearing and distance (in millimetres in the ECDIS display) used to position the text relative to the feature.

The TextPlacement feature is associated to the feature which carries the text being placed. The attribute textType determines which text string is to be displayed if more than one is present. The TextPlacement feature ensures that as the screen rotates from “north up” (e.g. if display is set to “course up”) text can remain readable, or clear other important charted information.

2.8 Scale policy

2.8.1 General policy

Marine Harbour Infrastructure data must be compiled in the best applicable scale.

2.8.2 Usage of scale attributes in displays (informative)

The attributes scaleMinimum and scaleMaximum define the range of display scales within which features will be portrayed on the display if these scale minimum/maximum functions are enabled in the ECDIS or another GIS device. A geo feature with one or more spatial attributes can utilize the scaleMinimum and scaleMaximum attributes on the link to the spatial object (see the S-100 General Feature Model, S-100 Part 3, Figure 3-1 and 3-5.3.5). There are essentially two ways in which these attributes may be used. 1) A producer may decide to use only a scaleMinimum value. This option is employed when the data producer wishes to turn off the display of a feature above certain scales. This is particularly useful in areas with high data density, and when it is expected that the data will be used at a larger scale where data clutter might become an issue. Features are therefore encoded with an applicable value, which represents the scale at which the producer wishes to turn off the feature. 2) A producer may decide to provide several pairs of scaleMinimum and scaleMaximum values. This decision may be based on the fact that for one particular feature different spatial instances in different scale ranges should be provided to supply this particular feature with more detailed geographic representation at larger scales.

An example can be a building which has two spatial objects associated, first one with only scale minimum value encoded at 21999, and the second spatial object encoded with scaleMaximum at 22000 and scaleMinimum encoded with 999999. These values would enable the use of a highly-detailed geometry at larger scales than 22000, and a less detailed geometry at scales of 22000 and less, while the building would be turned off at scales of 999999 and less.

A similar strategy can be followed to enable boundaries to conform to a scale-dependent geometry such as a coastline. Conformance at different scales can be achieved by using minimum/maximum scales on spatial attributes to indicate which particular geometry should be used at a given scale.

The meta feature DataCoverage ([Clause 4.1](#)) is used to provide ECDIS with the scale information needed for the determination of dataset loading and unloading in relation to the user-selected viewing scale of the ECDIS. The mandatory attribute maximumDisplayScale is used to indicate the largest intended viewing scale for the data. The mandatory attribute minimumDisplayScale is used to indicate the smallest intended viewing scale for the data.

S-122 does not prescribe specific values for maximumDisplayScale and minimumDisplayScale. Instead, producers should refer to the S-101 DCEG for values, and use values appropriate to the S-101 ENCs underlying the S-122 dataset.

2.8.3 Scale minimum values

Scale minimum values must be chosen from the list in S-101 to ensure visual compatibility between comparable underlying S-101 ENCs and S-122 data products. The scale minimum values used in the

actual comparable underlying ENCs should be used, and in case of differences with the list below, the values in the actual ENCs prevail. “Comparable” ENCs for the purpose of this requirement means ENCs of scales large enough to distinguish berths, terminals, and other features that are part of a port. These will generally have navigationPurpose=port in discovery metadata (see S-100 Part 17) and have maximum and minimum display scales values in the lower end of the scale ranges (i.e., be the larger scale ENCs).

All data within a dataset must have the same minimum display scale, but portions of a dataset can have a different maximum display scale, depending on the best scale required in an area for the operational purpose of the data.

2.8.4 Scale policy for feature types

EDITORIAL NOTE

TBD if still valid. Unlike S-101, S-122 does not define scale minimum values or steps for individual feature types.

2.9 Masking

Since a MHI dataset will cover the entire extent of a port, masking at cell boundaries is not required.

2.10 Linear surface features

If it is required to encode a linear feature when the only allowable primitive for the relevant feature type is surface (e.g. a service area along a track, or channel), a very narrow surface should be encoded. The suggested extent is 0.3mm wide at viewing scales (keeping in mind that S-100 permits different spatial attributes at different scales.) An edge of this surface should correspond to the position of the line. All other edges should be masked.

3 Description of table format for feature and information types

The tables describing feature and information types are based on the template below.

X.X Feature Name

<u>IHO Definition:</u> (Definition) (followed by Remarks if any)				
S-122 [Geo Feature/Information Type]: S-1XX Feature or Information Type (followed by (Abstract) if abstract type)				
<u>Super Type:</u> (supertype)				
<u>Primitives:</u> (allowed spatial primitives)				
Real World	Paper Chart Symbol	ECDIS Symbol	Type	Multiplicity
(Reserved)	(Reserved)	(Reserved)		
S-1XX Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
(This section lists the allowable local attributes)		(Allowed values for enumeration and codelist attributes)		
Inherited Attributes				
S-1XX Attribute	Inherited From	Type	Type	Multiplicity
(attribute)	(supertype where defined)			

Feature/information associations (permitted associations)				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
Role of target class	Name of the Association if inherited, "(Inherited from ...)"	Name of the target (the feature or information type referenced by the link)	aggregation / composition / aggregation	(How many target instances a single source instance can link to.)
If the association is listed in only one of the feature or information types in the association, it means the association is unidirectional, that is, the binding for the association is only in one of the participating features or information types. This is sometimes the case for information associations that link a feature to an information type—the feature type has a binding to the information type, but not vice versa.				

INT 1 Reference (optional): The INT 1 location(s) of the Feature – by INT1 Section and Section Number.

(*Encoding instructions are provided in sub-clauses following the table.*)

X.X.X General

General guidance for encoding.

Introductory remarks. Includes information regarding the real world entity/situation requiring the encoding of the Feature in the product, and where required nautical cartographic principles relevant to the Feature to aid the compiler in determining encoding requirements.

Remarks:

Guidance for encoding specific attributes.

X.X.X.X Sub-clause heading(s) (if needed) If applicable — S-4 reference

Additional encoding guidance relevant to the feature.

Clauses related to specific encoding scenarios for the Feature (if required).

Remarks:

S-122 Attribute: Indentation of attributes indicates sub-attributes of complex attributes. Complex attributes may also be sub-attributes of complex attributes. Complex sub-attributes are generally not expanded to show their own sub-attributes, because expanding sub-attributes produces tables of inordinate length, but if expansion is done, further levels of indentation are applied to the sub-attributes. Inherited attributes are shown separately from locally defined attributes. Inherited complex attributes are not expanded to show their sub-attributes.

Allowable Encoding Value: For (EN) type attributes, the enumerates listed are only those allowable for the particular occurrence of the attribute relevant to the feature. Allowable values may vary for the attribute depending on the feature to which the attribute is bound. Such bindings are defined in the S-122 Feature Catalogue. The full list of enumerates that may be assigned to an attribute in S-122 can be found in the Simple Attributes section of the printed feature catalogue document.

Type: The prefix **C** indicates that the attribute is a complex attribute. Complex attributes are aggregates of other attributes that can be simple type or complex type. The prefix **S** indicates that the attribute is a sub-attribute of a complex attribute. Complex attributes that are sub-attributes of a complex attribute, and their sub-attributes, are indicated by indentation of the attribute name in the S-122 Attribute column.

Introductory clauses may depict associations using a UML diagram showing the relationships that apply to the class and its super-classes (generalizations). Relationships which are inherited from super-classes are shown by including the super-classes and their associations in the diagram.

The usual UML conventions apply. For explanations of standard UML notations, see S-100 Part 1.

Association ends and multiplicities: A lower bound of 0 in the multiplicity at any end of an association indicates only that the association is not mandatory for any particular instance of the feature at the other end (i.e., it is not mandatory for an instance of “that” feature type to have an association to a feature of “this” type). A lower bound of “1” means that if an instance of “that” type exists, it must be associated to an instance of “this” type. If the association is actually encoded then it amounts to saying that “this relationship exists between these two instances” and there must be an appropriate feature instance at both ends. Associations that are not mandatory should be encoded if and only if they convey useful information.

4 Meta-Features

4.1 Data Coverage

<u>IHO Definition:</u> A geographical area that describes the coverage and extent of spatial objects.				
S-122 Geo Feature: DataCoverage				
<u>Super Type:</u>				
<u>Primitives:</u> surface				
Real World	<i>Paper Chart Symbol</i>		<i>ECDIS Symbol</i>	
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Maximum Display Scale			IN	1,1
Minimum Display Scale			IN	1,1
Optimum Display Scale			IN	0,1
Interoperability Identifier			URN	0,*
Inherited Attributes				
S-122Attribute	Inherited From		Type	Multiplicity
No inherited attributes				

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity

Feature associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity

4.1.1 General

Encoding instructions to be added

4.2 Quality of Non-Bathymetric Data

<u>IHO Definition:</u> An area within which a uniform assessment of the quality of the non-bathymetric data exists.				
S-122 Geo Feature: QualityOfNonBathymetricData				
<u>Super Type:</u>				
<u>Primitives:</u> surface				
Real World	<i>Paper Chart Symbol</i>		<i>ECDIS Symbol</i>	
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Category of Temporal Variation		1: Extreme Event 4: Likely to Change	EN	0,1

		5: Unlikely to Change 6: Unassessed		
Horizontal Distance Uncertainty			RE	0,1
Horizontal Position Uncertainty			C	0,1
Uncertainty Fixed			(S) RE	1,1
Uncertainty Variable Factor			(S) RE	0,1
Orientation Uncertainty			RE	0,1
Interoperability Identifier			URN	0,*
Source Indication			C	0,1
Category of Authority			(S) EN	0,1
Country Name			(S) TE	0,1
Source			(S) TE	0,1
Source Type		1: Law or Regulation 2: Official Publication 7: Mariner Report, Confirmed 8: Mariner Report, Not Confirmed 9: Industry Publications and Reports 10: Remotely Sensed Images 11: Photographs 12: Products Issued by HO Services 13: News Media 14: Traffic Data	(S) EN	0,1
Reported Date			(S) TD	0,1
Feature Name			(S) C	0,*
Survey Date Range			C	0,1
Date Start			(S) TD	0,1
Date End			(S) TD	1,1
Information			C	0,*
File Locator			(S) TE	0,1
File Reference			(S) TE	0,1
Headline			(S) TE	0,* (ordered)
Language			(S) TE	0,1
Text			(S) TE	0,1

Inherited Attributes				
S-122Attribute	Inherited From	Type	Multiplicity	
No inherited attributes				

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity

Feature associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity

4.2.1 General

Encoding instructions to be added

5 Abstract Geo Features

5.1 Feature Type

<u>IHO Definition:</u> Generalized feature type which carries all the common attributes.				
S-122 Geo Feature: FeatureType (Abstract)				
Super Type:				
Primitives: noGeometry				
<i>Real World</i>	<i>Paper Chart Symbol</i>	<i>ECDIS Symbol</i>		
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Interoperability Identifier			URN	0,*
Feature Name			C	0,*
Language			(S) TE	1,1
Name			(S) TE	1,1
Name Usage		1: Default Name Display 2: Alternate Name Display 3: No Chart Display	(S) EN	0,1
Fixed Date Range			C	0,1
Date Start			(S) TD	0,1
Date End			(S) TD	0,1
Periodic Date Range			C	0,*
Date Start			(S) TD	1,1
Date End			(S) TD	1,1
RxN Code			C	0,*
Category of RxN		1: Navigation	(S) CL	0,1

		2: Communication 3: Environmental Protection 4: Wildlife Protection 5: Security 6: Customs 7: Cargo Operation 8: Refuge 9: Health 10: Natural Resources or Exploitation 11: Port 12: Finance 13: Agriculture		
Action or Activity		1: Navigating With a Pilot 2: Entering Port 3: Leaving Port 4: Berthing 5: Slipping 6: Anchoring 7: Weighing Anchor 8: Transiting 9: Overtaking 10: Reporting 11: Working Cargo 12: Landing 13: Diving 14: Fishing 15: Discharging Overboard 16: Passing 17: Ballast Water Exchange 18: Hull Cleaning 19: Scientific Research 20: Tourism 21: Education 22: Infrastructure Maintenance	(S) CL	0,1
Headline			(S) TE	0,1
Graphic			C	0,*
Pictorial Representation			(S) TE	1,*
Picture Caption			(S) TE	0,1
Source Date			(S) DA	0,1
Picture Information			(S) TE	0,1
Bearing Information			(S) C	0,1
Source Indication			C	0,*
Category of Authority			(S) EN	0,1
Country Name			(S) TE	0,1
Source			(S) TE	0,1
Source Type		1: Law or Regulation 2: Official Publication 7: Mariner Report, Confirmed 8: Mariner Report, Not Confirmed 9: Industry Publications and Reports 10: Remotely Sensed Images 11: Photographs 12: Products Issued by HO Services 13: News Media	(S) EN	0,1

		14: Traffic Data		
Reported Date			(S) TD	0,1
Feature Name			(S) C	0,*
Text Content			C	0,*
Category of Text		1: Abstract or Summary 2: Extract 3: Full Text	(S) EN	0,1
Information			(S) C	0,*
Online Resource			(S) C	0,1
Source Indication			(S) C	0,*
Inherited Attributes				
S-122Attribute	Inherited From	Type	Multiplicity	
No inherited attributes				

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
permission	PermissionType	Applicability	association	0,*
theRxN	AssociatedRxN	AbstractRxN	association	0,*
theInformation	AdditionalInformation	NauticalInformation	association	0,*

Feature associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
theCartographicText	TextAssociation	TextPlacement	association	0,1

5.1.1 General

No remarks

6 Domain Features

6.1 Information Area

<u>IHO Definition:</u> An area for which general information regarding navigation, but not directly related to safety of navigation, is available.		
S-122 Geo Feature: InformationArea		
Super Type: FeatureType		
Primitives: surface		
<i>Real World</i>	<i>Paper Chart Symbol</i>	<i>ECDIS Symbol</i>

S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Category of Relationship		1: Prohibited 3: Permitted	EN	1,1
Action or Activity		17: Ballast Water Exchange	CL	1,1
Inherited Attributes				
S-122Attribute	Inherited From		Type	Multiplicity
Interoperability Identifier	FeatureType		URN	0,*
Feature Name	FeatureType		C	0,*
Fixed Date Range	FeatureType		C	0,1
Periodic Date Range	FeatureType		C	0,*
RxN Code	FeatureType		C	0,*
Graphic	FeatureType		C	0,*
Source Indication	FeatureType		C	0,*
Text Content	FeatureType		C	0,*

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
permission	PermissionType (inherited from FeatureType)	Applicability	association	0,*
theRxN	AssociatedRxN (inherited from FeatureType)	AbstractRxN and subtypes	association	0,*
theInformation	AdditionalInformation (inherited from FeatureType)	NauticalInformation	association	0,*

Feature associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
theCartographicText	TextAssociation (inherited from FeatureType)	TextPlacement	association	0,1

6.1.1 General

Encoding instructions to be added

6.2 Marine Protected Area

IHO Definition: Any area of the intertidal or sub-tidal terrain, together with its overlying water and associated flora, fauna, historical and cultural features, which has been reserved by law or other effective means to protect part or all of the enclosed environment.

S-122 Geo Feature: MarineProtectedArea				
Super Type: FeatureType				
Primitives: curve surface				
<i>Real World</i>		<i>Paper Chart Symbol</i>	<i>ECDIS Symbol</i>	
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Category of Marine Protected Area		1: IUCN Category Ia 2: IUCN Category Ib 3: IUCN Category II 4: IUCN Category III 5: IUCN Category IV 6: IUCN Category V 7: IUCN Category VI	CL	1,*
Category of Restricted Area		1: Offshore Safety Zone 4: Nature Reserve 5: Bird Sanctuary 6: Game Reserve 7: Seal Sanctuary 10: Historic Wreck Area 20: Research Area 22: Fish Sanctuary 23: Ecological Reserve 27: Environmentally Sensitive Sea Area 28: Particularly Sensitive Sea Area 31: Coral Sanctuary 32: Recreation Area 33: Ship Pollution Emission Control	EN	0,*
Jurisdiction		1: International 2: National 3: National Sub-Division	EN	0,1
Restriction		1: Anchoring Prohibited 2: Anchoring Restricted 3: Fishing Prohibited 4: Fishing Restricted 5: Trawling Prohibited 6: Trawling Restricted 7: Entry Prohibited 8: Entry Restricted 9: Dredging Prohibited 10: Dredging Restricted 11: Diving Prohibited 12: Diving Restricted 13: No Wake 14: Area To Be Avoided 15: Construction Prohibited 16: Discharging Prohibited 17: Discharging Restricted 18: Industrial or Mineral Exploration/Development Prohibited 19: Industrial or Mineral Exploration/Development Restricted	EN	0,*

	20: Drilling Prohibited 21: Drilling Restricted 22: Removal of Historical Artefacts Prohibited 23: Cargo Transhipment (Lightening) Prohibited 24: Dragging Prohibited 25: Stopping Prohibited 26: Landing Prohibited 27: Speed Restricted 38: Use of Spuds Prohibited 39: Swimming Prohibited 40: SOx Emission Restricted 41: NOx Emission Restricted 42: Power-Driven Vessels Prohibited			
Status	1: Permanent 2: Occasional 3: Recommended 4: Not in Use 5: Periodic/Intermittent 6: Reserved 7: Temporary 9: Mandatory 18: Existence Doubtful 28: Buoyed 13: Historic 14: Public	EN	0,*	
Designation		C	0,*	
Designation Scheme		(S) TE	0,1	
Designation Identifier		(S) TE	0,1	
Jurisdiction	1: International 2: National 3: National Sub-Division	(S) EN	0,1	
Text		(S) TE	0,1	
Inherited Attributes				
S-122Attribute	Inherited From	Type	Multiplicity	
Interoperability Identifier	FeatureType	URN	0,*	
Feature Name	FeatureType	C	0,*	
Fixed Date Range	FeatureType	C	0,1	
Periodic Date Range	FeatureType	C	0,*	
RxN Code	FeatureType	C	0,*	
Graphic	FeatureType	C	0,*	
Source Indication	FeatureType	C	0,*	
Text Content	FeatureType	C	0,*	

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
responsibleAuthority	ProtectedAreaAuthority	Authority	association	0,*
permission	PermissionType (inherited from FeatureType)	Applicability	association	0,*
theRxN	AssociatedRxN (inherited from FeatureType)	AbstractRxN and subtypes	association	0,*
theInformation	AdditionalInformation (inherited from FeatureType)	NauticalInformation	association	0,*

Feature associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
theCartographicText	TextAssociation (inherited from FeatureType)	TextPlacement	association	0,1

6.2.1 General

Encoding instructions to be added

6.3 Restricted Area

IHO Definition: A specified area designated by an appropriate authority within which navigation is restricted in accordance with certain specified conditions.				
S-122 Geo Feature: RestrictedArea				
Super Type: FeatureType				
Primitives: surface				
<i>Real World</i>	<i>Paper Chart Symbol</i>		<i>ECDIS Symbol</i>	
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Category of Restricted Area		1: Offshore Safety Zone 4: Nature Reserve 5: Bird Sanctuary 6: Game Reserve 7: Seal Sanctuary 10: Historic Wreck Area 20: Research Area 22: Fish Sanctuary 23: Ecological Reserve 27: Environmentally Sensitive Sea Area 28: Particularly Sensitive Sea Area 31: Coral Sanctuary 32: Recreation Area 33: Ship Pollution Emission Control	EN	0,*
Restriction		1: Anchoring Prohibited 2: Anchoring Restricted 3: Fishing Prohibited	EN	1,*

	4: Fishing Restricted 5: Trawling Prohibited 6: Trawling Restricted 7: Entry Prohibited 8: Entry Restricted 9: Dredging Prohibited 10: Dredging Restricted 11: Diving Prohibited 12: Diving Restricted 13: No Wake 14: Area To Be Avoided 15: Construction Prohibited 16: Discharging Prohibited 17: Discharging Restricted 18: Industrial or Mineral Exploration/Development Prohibited 19: Industrial or Mineral Exploration/Development Restricted 20: Drilling Prohibited 21: Drilling Restricted 22: Removal of Historical Artefacts Prohibited 23: Cargo Transhipment (Lightening) Prohibited 24: Dragging Prohibited 25: Stopping Prohibited 26: Landing Prohibited 27: Speed Restricted 38: Use of Spuds Prohibited 39: Swimming Prohibited 40: SOx Emission Restricted 41: NOx Emission Restricted 42: Power-Driven Vessels Prohibited		
--	---	--	--

Status	1: Permanent 2: Occasional 3: Recommended 4: Not in Use 5: Periodic/Intermittent 6: Reserved 7: Temporary 9: Mandatory 18: Existence Doubtful 28: Buoyed 13: Historic 14: Public	EN	0,*
--------	---	----	-----

Inherited Attributes

S-122Attribute	Inherited From	Type	Multiplicity
Interoperability Identifier	FeatureType	URN	0,*
Feature Name	FeatureType	C	0,*
Fixed Date Range	FeatureType	C	0,1
Periodic Date Range	FeatureType	C	0,*
RxN Code	FeatureType	C	0,*
Graphic	FeatureType	C	0,*
Source Indication	FeatureType	C	0,*

Text Content	FeatureType	C	0,*
--------------	-------------	---	-----

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
permission	PermissionType (inherited from FeatureType)	Applicability	association	0,*
theRxN	AssociatedRxN (inherited from FeatureType)	AbstractRxN and subtypes	association	0,*
theInformation	AdditionalInformation (inherited from FeatureType)	NauticalInformation	association	0,*

Feature associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
theCartographicText	TextAssociation (inherited from FeatureType)	TextPlacement	association	0,1

6.3.1 General

Encoding instructions to be added

6.4 Vessel Traffic Service Area

IHO Definition: The area of any service implemented by a relevant authority primarily designed to improve safety and efficiency of traffic flow and the protection of the environment. It may range from simple information messages, to extensive organisation of the traffic involving national or regional schemes.				
S-122 Geo Feature: VesselTrafficServiceArea				
Super Type: FeatureType				
Primitives: surface				
Real World	Paper Chart Symbol		ECDIS Symbol	
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Inherited Attributes				
S-122Attribute	Inherited From		Type	Multiplicity
Interoperability Identifier	FeatureType		URN	0,*
Feature Name	FeatureType		C	0,*
Fixed Date Range	FeatureType		C	0,1
Periodic Date Range	FeatureType		C	0,*
RxN Code	FeatureType		C	0,*
Graphic	FeatureType		C	0,*
Source Indication	FeatureType		C	0,*
Text Content	FeatureType		C	0,*

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
controlAuthority	ServiceControl	Authority	association	0,1
permission	PermissionType (inherited from FeatureType)	Applicability	association	0,*
theRxN	AssociatedRxN (inherited from FeatureType)	AbstractRxN and subtypes	association	0,*
theInformation	AdditionalInformation (inherited from FeatureType)	NauticalInformation	association	0,*

Feature associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
theCartographicText	TextAssociation (inherited from FeatureType)	TextPlacement	association	0,1

6.4.1 General

Encoding instructions to be added

7 Cartographic Features

7.1 Text Placement

IHO Definition: The Text Placement feature is used in association with the Feature Name attribute or a light description to optimize text positioning in ECDIS.				
S-122 Geo Feature: TextPlacement				
Super Type:				
Primitives: point				
Real World	Paper Chart Symbol	ECDIS Symbol	Type	Multiplicity
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Text Offset Bearing			IN	1,1
Text Offset Distance			IN	1,1
Text Rotation			BO	0,1
Text Type		1: Name	EN	1,2
Scale Minimum			IN	0,1
Inherited Attributes				
S-122Attribute	Inherited From	Type	Type	Multiplicity
No inherited attributes				

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity

Feature associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
thePositionProvider	TextAssociation	FeatureType	composition	1,1

7.1.1 General

Encoding instructions to be added

8 Abstract Information Types

8.1 Information Type

IHO Definition: Generalized information type which carries all the common attributes.
--

S-122 Information Type: InformationType (Abstract type)				
Super Type:				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Feature Name			C	0,*
Language			(S) TE	1,1
Name			(S) TE	1,1
Name Usage		1: Default Name Display 2: Alternate Name Display 3: No Chart Display	(S) EN	0,1
Fixed Date Range			C	0,1
Date Start			(S) TD	0,1
Date End			(S) TD	0,1
Periodic Date Range			C	0,*
Date Start			(S) TD	1,1
Date End			(S) TD	1,1
Graphic			C	0,*
Pictorial Representation			(S) TE	1,*
Picture Caption			(S) TE	0,1
Source Date			(S) DA	0,1
Picture Information			(S) TE	0,1
Bearing Information			(S) C	0,1
Source Indication			C	0,*
Category of Authority			(S) EN	0,1
Country Name			(S) TE	0,1
Source			(S) TE	0,1
Source Type		1: Law or Regulation 2: Official Publication 7: Mariner Report, Confirmed 8: Mariner Report, Not Confirmed 9: Industry Publications and Reports 10: Remotely Sensed Images 11: Photographs 12: Products Issued by HO Services 13: News Media 14: Traffic Data	(S) EN	0,1
Reported Date			(S) TD	0,1
Feature Name			(S) C	0,*

Inherited Attributes			
S-122 Attribute	Inherited From	Type	Multiplicity
No inherited attributes			

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity

8.1.1 General

Encoding instructions to be added

8.2 AbstractRxN

<u>IHO Definition:</u> An abstract superclass for information types that encode rules, recommendations, and general information in text or graphic form.				
S-122 Information Type: AbstractRxN (Abstract type)				
Super Type: InformationType				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Category of Authority		2: Border Control 3: Police 4: Port 5: Immigration 6: Health 7: Coast Guard 8: Agricultural 9: Military 10: Private Company 11: Maritime Police 12: Environmental 13: Fishery 14: Finance 15: Maritime 16: Customs	EN	0,1
RxN Code			C	0,*
Category of RxN		1: Navigation 2: Communication 3: Environmental Protection 4: Wildlife Protection 5: Security 6: Customs 7: Cargo Operation 8: Refuge 9: Health 10: Natural Resources or Exploitation 11: Port 12: Finance 13: Agriculture	(S) CL	0,1
Action or Activity		1: Navigating With a Pilot 2: Entering Port 3: Leaving Port	(S) CL	0,1

		4: Berthing 5: Slipping 6: Anchoring 7: Weighing Anchor 8: Transiting 9: Overtaking 10: Reporting 11: Working Cargo 12: Landing 13: Diving 14: Fishing 15: Discharging Overboard 16: Passing 17: Ballast Water Exchange 18: Hull Cleaning 19: Scientific Research 20: Tourism 21: Education 22: Infrastructure Maintenance		
Headline			(S) TE	0,1
Text Content			C	0,*
Category of Text		1: Abstract or Summary 2: Extract 3: Full Text	(S) EN	0,1
Information			(S) C	0,*
Online Resource			(S) C	0,1
Source Indication			(S) C	0,*
Inherited Attributes				
S-122 Attribute	Inherited From	Type	Multiplicity	
Feature Name	InformationType	C	0,*	
Fixed Date Range	InformationType	C	0,1	
Periodic Date Range	InformationType	C	0,*	
Graphic	InformationType	C	0,*	
Source Indication	InformationType	C	0,*	

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
isApplicableTo	InclusionType	Applicability	association	0,*
theOrganisation	RelatedOrganisation	Authority	association	0,*

8.2.1 General

No remarks

9 Textual Regulations

9.1 Introduction

All geo features may have an association to any of Regulations or its sibling information types. This association is AssociatedRxN and it is inherited from the root feature type [FeatureType](#).

If it is necessary to identify an authority or organization related to a particular regulation (restriction, etc.) object, this may be done using the RelatedOrganisation association between Regulations, etc., and an Authority object.

9.2 Regulations applying only to vessels with specific characteristics or cargoes

Regulations applying only to vessels of specified types, exceeding specified dimensions, or carrying specified cargoes (or other limitations which apply only to subsets of vessels) are encoded by defining the subset of vessels using an Applicability instance and associating the Regulations object to that Applicability.

For information on the use of Applicability to define subsets of vessels, see [Section 11](#) in this DCEG and clause 4.2.1.9 in the main PS.

9.3 Regulations

<u>IHO Definition:</u> Regulations for a related area or facility.				
S-122 Information Type: Regulations (Abstract type)				
<u>Super Type:</u> AbstractRxN				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Inherited Attributes				
S-122 Attribute	Inherited From		Type	Multiplicity
Category of Authority	AbstractRxN		EN	0,1
RxN Code	AbstractRxN		C	0,*
Text Content	AbstractRxN		C	0,*
Feature Name	InformationType		C	0,*
Fixed Date Range	InformationType		C	0,1
Periodic Date Range	InformationType		C	0,*
Graphic	InformationType		C	0,*
Source Indication	InformationType		C	0,*

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
isApplicableTo	InclusionType (inherited from AbstractRxN)	Applicability	association	0,*
theOrganisation	RelatedOrganisation (inherited from AbstractRxN)	Authority	association	0,*

9.3.1 General

Encoding instructions to be added

9.4 Restrictions

<u>IHO Definition:</u> Restrictions for a related area or facility.				
S-122 Information Type: Restrictions (Abstract type)				
Super Type: AbstractRxN				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Inherited Attributes				
S-122 Attribute	Inherited From			Type
Category of Authority	AbstractRxN			EN 0,1
RxN Code	AbstractRxN			C 0,*
Text Content	AbstractRxN			C 0,*
Feature Name	InformationType			C 0,*
Fixed Date Range	InformationType			C 0,1
Periodic Date Range	InformationType			C 0,*
Graphic	InformationType			C 0,*
Source Indication	InformationType			C 0,*

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
isApplicableTo	InclusionType (inherited from AbstractRxN)	Applicability	association	0,*
theOrganisation	RelatedOrganisation (inherited from AbstractRxN)	Authority	association	0,*

9.4.1 General

Encoding instructions to be added

9.5 Recommendations

<u>IHO Definition:</u> Recommendations for a related area or facility.
--

S-122 Information Type: Recommendations (Abstract type)				
Super Type: AbstractRxN				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Inherited Attributes				
S-122 Attribute	Inherited From		Type	Multiplicity
Category of Authority	AbstractRxN		EN	0,1
RxN Code	AbstractRxN		C	0,*
Text Content	AbstractRxN		C	0,*
Feature Name	InformationType		C	0,*
Fixed Date Range	InformationType		C	0,1
Periodic Date Range	InformationType		C	0,*
Graphic	InformationType		C	0,*
Source Indication	InformationType		C	0,*

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
isApplicableTo	InclusionType (inherited from AbstractRxN)	Applicability	association	0,*
theOrganisation	RelatedOrganisation (inherited from AbstractRxN)	Authority	association	0,*

9.5.1 General

Encoding instructions to be added

9.6 Nautical Information

IHO Definition:	Nautical information about a related area or facility.							
S-122 Information Type: NauticalInformation (Abstract type)								
Super Type: AbstractRxN								
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity				
Inherited Attributes								
S-122 Attribute	Inherited From		Type	Multiplicity				
Category of Authority	AbstractRxN		EN	0,1				
RxN Code	AbstractRxN		C	0,*				
Text Content	AbstractRxN		C	0,*				
Feature Name	InformationType		C	0,*				
Fixed Date Range	InformationType		C	0,1				

Periodic Date Range	InformationType	C	0,*
Graphic	InformationType	C	0,*
Source Indication	InformationType	C	0,*

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
isApplicableTo	InclusionType (inherited from AbstractRxN)	Applicability	association	0,*
theOrganisation	RelatedOrganisation (inherited from AbstractRxN)	Authority	association	0,*

9.6.1 General

Encoding instructions to be added

10 Services, Organisations and Schedules

10.1 Introduction

10.2 Authority

<u>IHO Definition:</u> A person or organisation having political or administrative power and control.				
S-122 Information Type: Authority (Abstract type)				
Super Type: InformationType				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Category of Authority		2: Border Control 3: Police 4: Port 5: Immigration 6: Health 7: Coast Guard 8: Agricultural 9: Military 10: Private Company 11: Maritime Police 12: Environmental 13: Fishery 14: Finance 15: Maritime 16: Customs	EN	1,1
Text Content			C	0,1
Category of Text		1: Abstract or Summary 2: Extract 3: Full Text	(S) EN	0,1
Information			(S) C	0,*
Online Resource			(S) C	0,1
Source Indication			(S) C	0,*

Inherited Attributes				
S-122 Attribute	Inherited From	Type	Multiplicity	
Feature Name	InformationType	C	0, *	
Fixed Date Range	InformationType	C	0,1	
Periodic Date Range	InformationType	C	0, *	
Graphic	InformationType	C	0, *	
Source Indication	InformationType	C	0, *	

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
theContactDetails	AuthorityContact	ContactDetails	association	0, *
organisationRelatedRxN	RelatedOrganisation	AbstractRxN	association	0, *
theServiceHours	AuthorityHours	ServiceHours	association	0, *

10.2.1 General

Remarks to be added

10.3 Contact Details

IHO Definition: Information on how to reach a person or organisation by postal, internet, telephone, telex and radio systems.				
S-122 Information Type: ContactDetails (Abstract type)				
Super Type: InformationType				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Call Name			TE	0,1
Call Sign			TE	0,1
Category of Communication Preference		1: Preferred Calling 2: Alternate Calling 3: Preferred Working 4: Alternate Working	EN	0,1
Communication Channel			TE	0, *
Contact Instructions			TE	0,1
Language			TE	0, *
MMSI Code			TE	0,1
Contact Address			C	0, *
Delivery Point			(S) TE	0,1
City Name			(S) TE	0,1
Administrative Division			(S) TE	0,1

Country Name			(S) TE	0,1
Postal Code			(S) TE	0,1
Frequency Pair			C	0,*
Frequency Shore Station Receives			(S) IN	0,1
Frequency Shore Station Transmits			(S) IN	1,1
Information			C	0,*
File Locator			(S) TE	0,1
File Reference			(S) TE	0,1
Headline			(S) TE	0,* (ordered)
Language			(S) TE	0,1
Text			(S) TE	0,1
Online Resource			C	0,*
Linkage			(S) URI	1,1
Protocol			(S) TE	0,1
Application Profile			(S) TE	0,1
Name of Resource			(S) TE	0,1
Online Resource Description			(S) TE	0,1
Protocol Request			(S) TE	0,1
Online Function		1: Download 3: Offline Access 4: Order 5: Search 6: Complete Metadata 7: Browse Graphic 8: Upload 9: Email Service 10: Browsing 11: File Access	(S) EN	0,1
Telecommunications			C	0,*
Category of Communication Preference		1: Preferred Calling 2: Alternate Calling 3: Preferred Working 4: Alternate Working	(S) EN	0,1
Telecommunication Identifier			(S) TE	1,1
Telecommunication Carrier			(S) TE	0,1
Contact Instructions			(S) TE	0,1
Telecommunication Service		1: Voice 2: Facsimile 3: SMS 4: Data 5: Streamed Data 6: Telex 7: Telegraph	(S) EN	0,*

		8: Email	
Inherited Attributes			
S-122 Attribute	Inherited From	Type	Multiplicity
Feature Name	InformationType	C	0, *
Fixed Date Range	InformationType	C	0,1
Periodic Date Range	InformationType	C	0, *
Graphic	InformationType	C	0, *
Source Indication	InformationType	C	0, *

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
theAuthority	AuthorityContact	Authority	association	0, *

10.3.1 General

Encoding instructions to be added

10.4 Service Hours

<u>IHO Definition:</u> The time when a service is available and known exceptions.				
S-122 Information Type: ServiceHours (Abstract type)				
Super Type: InformationType				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Schedule by Day of Week			C	1, *
Category of Schedule		1: Normal Operation 2: Closure 3: Unmanned Operation	(S) EN	0,1
Text			(S) TE	0,1
Time Intervals by Day of Week			(S) C	1, *
Information			C	0, *
File Locator			(S) TE	0,1
File Reference			(S) TE	0,1
Headline			(S) TE	0, * (ordered)
Language			(S) TE	0,1
Text			(S) TE	0,1
Inherited Attributes				
S-122 Attribute	Inherited From	Type	Multiplicity	
Feature Name	InformationType	C	0, *	

Fixed Date Range	InformationType	C	0,1
Periodic Date Range	InformationType	C	0,*
Graphic	InformationType	C	0,*
Source Indication	InformationType	C	0,*

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
partialWorkingDay	ExceptionalWorkday	NonStandardWorkingDay	association	0,*
theAuthority_srvHrs	AuthorityHours	Authority	association	0,*

10.4.1 General

Encoding instructions to be added

10.5 Non-Standard Working Day

IHO Definition: Days when many services are not available. Often days of festivity or recreation or public holidays when normal working hours are limited, especially a national or religious festival, etc.				
S-122 Information Type: NonStandardWorkingDay (Abstract type)				
Super Type: InformationType				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Date Fixed			TD	0,*
Date Variable			TE	0,*
Information			C	0,*
File Locator			(S) TE	0,1
File Reference			(S) TE	0,1
Headline			(S) TE	0,* (ordered)
Language			(S) TE	0,1
Text			(S) TE	0,1
Inherited Attributes				
S-122 Attribute	Inherited From		Type	Multiplicity
Feature Name	InformationType		C	0,*
Fixed Date Range	InformationType		C	0,1
Periodic Date Range	InformationType		C	0,*
Graphic	InformationType		C	0,*
Source Indication	InformationType		C	0,*

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity

10.5.1 General

Encoding instructions to be added

11 Limitations

11.1 Introduction

Certain regulations, recommendations, etc., apply only to vessels of specified dimensions, types, or carrying specified cargo, etc. Similarly, certain features have specific significance for vessels of specified dimensions (e.g., different speed limits for vessels carrying specified cargoes or exceeding specified dimensions, or entry prohibitions for certain vessel types).

11.2 Defining subsets of vessels by dimensions, cargo, and other characteristics

This is modelled by first defining the relevant subset of vessels according to the dimension, type, cargo, etc., and then associating that subset to the appropriate feature or information type. The subset of vessels is modelled using the Applicability class, which contains attributes for the most common vessel characteristics used in nautical publications. These include measurements (length, beam, draught), type of cargo, displacement, etc. Constraints which cannot be modelled using the attributes of Applicability can be described in plain text in its information attribute.

EDITORIAL NOTE

Add figure

Conditions relating to vessel dimensions are modelled by the complex attribute vesselsMeasurements, which has sub-attributes for naming the dimension and indicating the limit (whether the condition applies to a vessel which exceeds or falls below the limit).

EDITORIAL NOTE

Add figure

11.3 Applicability

<u>IHO Definition:</u> Describes the relationship between vessel characteristics and: (i) the applicability of an associated information object or feature to the vessel; or, (ii) the use of a facility, place, or service by the vessel; or, (iii) passage of the vessel through an area.				
S-122 Information Type: Applicability (Abstract type)				
Super Type: InformationType				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
In Ballast			BO	0,1
Category of Cargo		1: Bulk 2: Container 3: General 4: Liquid	EN	0,*

	5: Passenger 6: Livestock 7: Dangerous or Hazardous 8: Heavy Lift 10: Dry Bulk Cargo 11: Liquid Bulk Cargo 12: Reefer Container Cargo 13: Ro-Ro Cargo 14: Project Cargo 15: Break Bulk Cargo		
Category Of Dangerous Or Hazardous Cargo	1: IMDG Code Class 1 Div. 1.1 2: IMDG Code Class 1 Div. 1.2 3: IMDG Code Class 1 Div. 1.3 4: IMDG Code Class 1 Div. 1.4 5: IMDG Code Class 1 Div. 1.5 6: IMDG Code Class 1 Div. 1.6 7: IMDG Code Class 2 Div. 2.1 8: IMDG Code Class 2 Div. 2.2 9: IMDG Code Class 2 Div. 2.3 10: IMDG Code Class 3 11: IMDG Code Class 4 Div. 4.1 12: IMDG Code Class 4 Div. 4.2 13: IMDG Code Class 4 Div. 4.3 14: IMDG Code Class 5 Div. 5.1 15: IMDG Code Class 5 Div. 5.2 16: IMDG Code Class 6 Div. 6.1 17: IMDG Code Class 6 Div. 6.2 18: IMDG Code Class 7 19: IMDG Code Class 8 20: IMDG Code Class 9 21: Harmful Substances in Packaged Form	EN	0,*
Category of Vessel	1: General Cargo Vessel 2: Container Carrier 3: Tanker 4: Bulk Carrier 5: Passenger Vessel 6: Roll-On Roll-Off 7: Refrigerated Cargo Vessel 8: Fishing Vessel 9: Service 10: Warship 11: Towed or Pushed Composite Unit 12: Tug and Tow 13: Light Recreational	CL	0,1

		14: Semi-Submersible Offshore Installation 15: Jack-Up Exploration or Project Installation 16: Livestock Carrier 17: Sport Fishing		
Category of Vessel Registry		1: Domestic 2: Foreign	EN	0,1
Logical Connectives		1: Logical Conjunction 2: Logical Disjunction	EN	0,1
Thickness of Ice Capability			IN	0,1
Vessel Performance			TE	0,1
Destination			TE	0,1
Information			C	0,*
File Locator			(S) TE	0,1
File Reference			(S) TE	0,1
Headline			(S) TE	0,* (ordered)
Language			(S) TE	0,1
Text			(S) TE	0,1
Vessel Measurements Specification			C	0,*
Comparison Operator		1: Greater Than 2: Greater Than or Equal To 3: Less Than 4: Less Than or Equal To 5: Equal To 6: Not Equal To	(S) EN	1,1
Vessels Characteristics		1: Length Overall 2: Length at Waterline 3: Breadth 4: Draught 6: Displacement Tonnage 7: Displacement Tonnage, Light 8: Displacement Tonnage, Loaded 9: Deadweight Tonnage 10: Gross Tonnage 11: Net Tonnage 12: Panama Canal/ Universal Measurement System Net Tonnage 13: Suez Canal Net Tonnage	(S) EN	1,1
Vessels Characteristics Value			(S) RE	1,1
Vessels Characteristics Unit		1: Metres 3: Metric Ton 4: Ton 5: Short Ton 6: Gross Ton	(S) EN	1,1

		7: Net Ton 9: Suez Canal Net Tonnage		
Inherited Attributes				
S-122 Attribute	Inherited From	Type	Multiplicity	
Feature Name	InformationType	C	0,*	
Fixed Date Range	InformationType	C	0,1	
Periodic Date Range	InformationType	C	0,*	
Graphic	InformationType	C	0,*	
Source Indication	InformationType	C	0,*	

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity
theApplicableRxN	InclusionType	AbstractRxN	association	0,*

11.3.1 General

No remarks

12 Spatial Quality

12.1 Spatial Quality

IHO Definition: The indication of the quality of the locational information for features in a dataset.				
S-122 Information Type: SpatialQuality (Abstract type)				
Super Type:				
S-122 Attribute	S-57 Acronym	Allowable Encoding Value	Type	Multiplicity
Quality of Horizontal Measurement		1: Surveyed 2: Unsurveyed 3: Inadequately Surveyed 4: Approximate 5: Position Doubtful 6: Unreliable 7: Reported (Not Surveyed) 8: Reported (Not Confirmed) 9: Estimated 10: Precisely Known 11: Calculated	EN	0,1
Spatial Accuracy			C	0,*
Fixed Date Range			(S) C	0,1
Horizontal Position Uncertainty			(S) C	0,1
Vertical Uncertainty			(S) C	0,1
Inherited Attributes				
S-122 Attribute	Inherited From	Type	Multiplicity	
No inherited attributes				

Information associations				
S-122 Role	S-122 Association Name	Associated to	Type	Multiplicity

12.1.1 General

Encoding instructions to be added

13 Feature Associations

13.1 Text association

Definition : A feature association for the binding between a geo feature and the cartographically positioned location for text.

CamelCase : TextAssociation

Remarks :

Roles : thePositionProvider theCartographicText

14 Information Associations

14.1 Additional information

Definition : A feature association for the binding between at least one instance of a geo feature and an instance of an information type.

CamelCase : AdditionalInformation

Remarks :

Roles : theInformation

14.2 Authority contact

Definition : Contact information for an authority

CamelCase : AuthorityContact

Remarks :

Roles : theAuthority theContactDetails

14.3 Authority hours

Definition : Service hours for an authority

CamelCase : AuthorityHours

Remarks :

Roles : theAuthority_svrHrs theServiceHours

14.4 Associated RxN

Definition : Association between a geographic location and a regulation, restriction, recommendation, or nautical information

CamelCase : AssociatedRxN

Remarks :

Roles : theRxN

14.5 Exceptional workday

Definition : Exception to the usual working day

CamelCase : ExceptionalWorkday

Remarks :

Roles : theServiceHours_nsdy partialWorkingDay

14.6 Protected area authority

Definition : There may be more than one such authority depending on how responsibilities are divided

CamelCase : ProtectedAreaAuthority

Remarks :

Roles : responsibleAuthority

14.7 Related organisation

Definition : Related organisation

CamelCase : RelatedOrganisation

Remarks :

Roles : organisationRelatedRxN theOrganisation

14.8 InclusionType

Definition : Association class specifying the relationship between the subset of vessels described by an APPLIC data object and a regulation (restriction, recommendation, or nautical information).

CamelCase : InclusionType

Remarks :

Roles : theApplicableRxN isApplicableTo

14.9 Permission Type

Definition : Association class for associations describing whether the subsets of vessels determined by the ship characteristics specified in APPLIC may (or must, etc.) transit, enter, or use a feature.

CamelCase : PermissionType

Remarks :

Roles : permission

14.10 Service control

Definition : The controlling authority for a service area

CamelCase : ServiceControl

Remarks : This is an information association linking a location where a service is provided with an information type describing the provider. Contrast to serviceProvisionArea, which is a feature association linking the area served with another feature describing the provider. Role controlledService encodable only as a generic inverse association in 3.0.0 datasets as it is an information→feature link

Roles : controlAuthority

14.11 Spatial Association

Definition : An association for the binding between a spatial type and its spatial quality information.

CamelCase : SpatialAssociation

Remarks :

Roles : theQualityInformation

15 Association Roles

15.1 The Authority

Definition : A pointer to an Authority object

CamelCase : theAuthority

Remarks :**15.2 Authority service hours**

Definition : The authority for which service hours are given

CamelCase : theAuthority_srvHrs

Remarks :**15.3 Contact details**

Definition : A pointer to an Contact Details object

CamelCase : theContactDetails

Remarks :**15.4 Control authority**

Definition : The controlling organization or authority for a geographically located service

CamelCase : controlAuthority

Remarks :**15.5 Is Applicable To**

Definition : The object or class of objects to which the regulation, restriction, recommendation, or nautical information applies

CamelCase : isApplicableTo

Remarks :**15.6 Organisation-Related RxN**

Definition : Reference to regulation, recommendation, restriction or general information related to an organisation

CamelCase : organisationRelatedRxN

Remarks :**15.7 Permission**

Definition : Association class for associations describing whether the subsets of vessels determined by the ship characteristics specified in APPLIC may (or must, etc.) transit, enter, or use a feature.

CamelCase : permission

Remarks :**15.8 Partial Working Day**

Definition : The work hours for a non-standard workday

CamelCase : partialWorkingDay

Remarks :

15.9 Responsible authority

Definition : The responsible authority

CamelCase : responsibleAuthority

Remarks :

15.10 Service Hours (reference)

Definition : Service hours for an authority or service provider

CamelCase : theServiceHours

Remarks :

15.11 The information

Definition : A pointer to an object that provides more information about the referencing feature or information type.

CamelCase : theInformation

Remarks : Registry definition “The information” merely repeats the name.

15.12 The organisation

Definition : The organisation to which information relates

CamelCase : theOrganisation

Remarks :

15.13 The Quality Information

Definition : A pointer to an information type providing spatial quality information.

CamelCase : theQualityInformation

Remarks :

15.14 The RxN

Definition : The regulation, restriction, recommendation, or nautical information

CamelCase : theRxN

Remarks :

15.15 The Applicable RxN

Definition : The applicable regulation, restriction, recommendation or nautical information

CamelCase : theApplicableRxN

Remarks :

15.16 The Cartographic Text

Definition : A pointer to a specific cartographically positioned location for text.

CamelCase : theCartographicText

Remarks :

15.17 The Position Provider

Definition : A pointer to a specific feature(s).

CamelCase : thePositionProvider

Remarks :

15.18 The service hours for a non-standard workday

Definition : The usual service hours to which an exception applies

CamelCase : theServiceHours_nsdy

Remarks :

16 Simple Attributes

16.1 Administrative Division

Definition : A generic term for an administrative region within a country at a level below that of the sovereign state.

Type : text

CamelCase : administrativeDivision

Alias :

Remarks :

16.2 Application Profile

Definition : Name of an application profile that can be used with the online resource.

Type : text

CamelCase : applicationProfile

Alias : APPPRF

Remarks :

16.3 Call Name

Definition : The designated call name of a station; for example, radio station, radar station, pilot.

Type : text

CamelCase : callName

Alias :

Remarks : This is the name used when calling a radio station by radio; for example, "Singapore Pilots".

16.4 Call Sign

Definition : The designated call-sign of a station (radio station, radar station, pilot, ...).

Type : text

CamelCase : callSign

Alias : CALSGN

Remarks :

16.5 Cardinal Direction

Definition : Principal and intermediate compass points.

Type : enumeration

CamelCase : cardinalDirection

Alias : CARDIR

Remarks :

Code	Label	Definition
1	North	348.75-011.25 degrees (true north).
2	North Northeast	011.25 — 033.75 degrees.
3	Northeast	033.75 — 056.25 degrees.
4	East Northeast	056.25-078.75 degrees.
5	East	078.75-101.25 degrees.
6	East Southeast	101.25-123.75 degrees.
7	Southeast	123.75-146.25 degrees.
8	South Southeast	146.25-168.75 degrees.
9	South	168.75-191.25 degrees.
10	South Southwest	191.25-213.75 degrees.
11	Southwest	213.75-236.25 degrees.
12	West Southwest	236.25-258.75 degrees.
13	West	258.75-281.25 degrees.
14	West Northwest	281.25-303.75 degrees.
15	Northwest	303.75 — 326.25 degrees.
16	North Northwest	326.25 — 348.75 degrees.

16.6 Category of Authority

Definition : The type of person, government agency or organisation granted powers of managing or controlling access to and/or activity in an area.

Type : enumeration

CamelCase : categoryOfAuthority

Alias : CATAUT

Remarks :

Code	Label	Definition
2	Border Control	The administration to prevent or detect and prosecute violations of rules and regulations at international boundaries.
3	Police	The department of government, or civil force, charged with maintaining public order.
4	Port	Person or corporation, owners of, or entrusted with or invested with the power of managing a port. May be called a Harbour Board, Port Trust, Port Commission, Harbour Commission, Marine Department.
5	Immigration	The authority controlling people entering a country.
6	Health	The authority with responsibility for checking the validity of the health declaration of a vessel and for declaring free pratique.
7	Coast Guard	Organization keeping watch on shipping and coastal waters according to governmental law; normally the authority with responsibility for search and rescue.
8	Agricultural	The authority with responsibility for preventing infection of the agriculture of a country and for the protection of the agricultural interests of a country.
9	Military	A military authority which provides control of access to or approval for transit through designated areas or airspace.
10	Private Company	A private or publicly owned company or commercial enterprise which exercises control of facilities, for example a calibration area.
11	Maritime Police	A governmental or military force with jurisdiction in territorial waters. Examples could include Gendarmerie Maritime, Carabinierie, and Guardia Civil.
12	Environmental	An authority with responsibility for the protection of the environment.
13	Fishery	An authority with responsibility for the control of fisheries.
14	Finance	An authority with responsibility for the control and movement of money.
15	Maritime	A national or regional authority charged with administration of maritime affairs.
16	Customs	The agency or establishment for collecting duties, tolls.

16.7 Category of Cargo

Definition : Classification of the different types of cargo that a ship may be carrying.

Type : enumeration

CamelCase : categoryOfCargo

Alias : CATCGO

Remarks : If item 7 is used, the nature of dangerous or hazardous cargoes can be amplified with category of dangerous or hazardous cargo.

Code	Label	Definition
1	Bulk	Unpacked homogenous cargo poured loose in a certain space of a vessel, for example oil or grain.
2	Container	One of a number of standard sized cargo carrying units, secured using standard corner attachments and bar.
3	General	Break bulk cargo normally loaded by crane.
4	Liquid	Any cargo loaded by pipeline.

Code	Label	Definition
5	Passenger	A fee paying traveller.
6	Livestock	Live animals carried in bulk.
7	Dangerous or Hazardous	Dangerous or hazardous cargo as described by the IMO International Maritime Dangerous Goods code.
8	Heavy Lift	Indivisible heavy items of weight generally over 100 tons, and width or height greater than 100 metres.
10	Dry Bulk Cargo	Commodity cargo that is transported unpackaged in large quantities. These types of goods usually need to be kept dry during the whole transportation period.
11	Liquid Bulk Cargo	Liquids or gases that are transported in bulk and carried unpackaged.
12	Reefer Container Cargo	Cargo transported in refrigerated containers, generally perishable commodities which require temperature-controlled transportation, such as fruit, meat, fish, vegetables, dairy products and other foods.
13	Ro-Ro Cargo	Wheeled cargo, such as cars, busses, trucks, agricultural vehicles and cranes, that are driven on and off the ship on their own wheels or using a platform vehicle, such as a self-propelled modular transporter.
14	Project Cargo	Project cargo is a term used to broadly describe the national or international transportation of large, heavy, high value, or critical (to the project they are intended for) pieces of equipment. Also commonly referred to as heavy lift, this includes shipments made of various components which need disassembly for shipment and reassembly after delivery.
15	Break Bulk Cargo	Goods that are stowed on board ship in individually counted units, and not in intermodal containers nor in bulk as with oil or grain.

16.8 Category of Communication Preference

Definition : Classification of frequencies, VHF channels, telephone numbers, or other means of communication based on preference.

Type : enumeration

CamelCase : categoryOfCommunicationPreference

Alias :

Remarks :

Code	Label	Definition
1	Preferred Calling	The first choice channel or frequency to be used when calling a radio station.
2	Alternate Calling	A channel or frequency to be used for calling a radio station when the preferred channel or frequency is busy or is suffering from interference.
3	Preferred Working	The first choice channel or frequency to be used when working with a radio station.
4	Alternate Working	A channel or frequency to be used for working with a radio station when the preferred working channel or frequency is busy or is suffering from interference.

16.9 Category Of Dangerous Or Hazardous Cargo

Definition : Classification of dangerous goods or hazardous materials based on the International Maritime Dangerous Goods Code (IMDG Code).

Type : enumeration

CamelCase : categoryOfDangerousOrHazardousCargo

Alias : CATDHC

Remarks :

Code	Label	Definition
1	IMDG Code Class 1 Div. 1.1	Explosives, Division 1: Substances and articles which have a mass explosion hazard.
2	IMDG Code Class 1 Div. 1.2	Explosives, Division 2: Substances and articles which have a projection hazard but not a mass explosion hazard.
3	IMDG Code Class 1 Div. 1.3	Explosives, Division 3: Substances and articles which have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but not a mass explosion hazard.
4	IMDG Code Class 1 Div. 1.4	Explosives, Division 4: Substances and articles which present no significant hazard.
5	IMDG Code Class 1 Div. 1.5	Explosives, Division 5: Very insensitive substances which have a mass explosion hazard.
6	IMDG Code Class 1 Div. 1.6	Explosives, Division 6: Extremely insensitive articles which do not have a mass explosion hazard.
7	IMDG Code Class 2 Div. 2.1	Gases, flammable gases.
8	IMDG Code Class 2 Div. 2.2	Gases, non-flammable, non-toxic gases.
9	IMDG Code Class 2 Div. 2.3	Gases, toxic gases.
10	IMDG Code Class 3	Flammable liquids.
11	IMDG Code Class 4 Div. 4.1	Flammable solids, self-reactive substances and desensitized explosives.
12	IMDG Code Class 4 Div. 4.2	Substances liable to spontaneous combustion.
13	IMDG Code Class 4 Div. 4.3	Substances which, in contact with water, emit flammable gases.
14	IMDG Code Class 5 Div. 5.1	Oxidizing substances.
15	IMDG Code Class 5 Div. 5.2	Organic peroxides.
16	IMDG Code Class 6 Div. 6.1	Toxic substances.
17	IMDG Code Class 6 Div. 6.2	Infectious substances.
18	IMDG Code Class 7	Radioactive material.

Code	Label	Definition
19	IMDG Code Class 8	Corrosive substances.
20	IMDG Code Class 9	Miscellaneous dangerous substances and articles.
21	Harmful Substances in Packaged Form	Harmful substances are those substances which are identified as marine pollutants in the International Maritime Dangerous Goods Code (IMDG Code). Packaged form is defined as the forms of containment specified for harmful substances in the IMDG Code.

16.10 Category of Relationship

Definition : Expresses constraints or requirements on vessel actions or activities in relation to a geographic feature, facility, or service.

Type : enumeration

CamelCase : categoryOfRelationship

Alias :

Remarks :

Code	Label	Definition
1	Prohibited	Use of facility, waterway or service is forbidden.
2	Not Recommended	Use of facility, waterway or service is not recommended.
3	Permitted	Use of facility, waterway, or service is permitted but not required.
4	Recommended	Use of facility, waterway, or service is recommended.
5	Required	Use of facility, waterway, or service is required.
6	Not Required	Use of facility, waterway, or service is not required.
7	Exclusively Permitted	Only vessels of the specified characteristics may use the facility, waterway, or service.

16.11 Category of Restricted Area

Definition : The official legal status of each kind of restricted area defines the kind of restriction(s), for example the restriction for a 'game reserve' may be 'entering prohibited'.

Type : enumeration

CamelCase : categoryOfRestrictedArea

Alias : CATREA

Remarks :

Code	Label	Definition
1	Offshore Safety Zone	The area around an offshore installation within which vessels are prohibited from entering without permission. Special regulations protect installations within a safety zone and vessels of all nationalities are required to respect the zone.
4	Nature Reserve	A tract of land or water managed so as to preserve its flora, fauna, physical features, etc.
5	Bird Sanctuary	A place where birds are bred and protected.

Code	Label	Definition
6	Game Reserve	A place where wild animals or birds hunted for sport or food are kept undisturbed for private use.
7	Seal Sanctuary	A place where seals are protected.
10	Historic Wreck Area	An area around certain wrecks of historical importance to protect the wrecks from unauthorized interference by diving, salvage or deposition (including anchoring).
20	Research Area	An area where marine research takes place.
22	Fish Sanctuary	A place where fish (including shellfish and crustaceans) are protected.
23	Ecological Reserve	A tract of land managed so as to preserve the relation of plants and living creatures to each other and to their surroundings.
27	Environmentally Sensitive Sea Area	A generic term which may be used to describe a wide range of areas, considered sensitive for a variety of environmental reasons.
28	Particularly Sensitive Sea Area	An area that needs special protection through action by IMO because of its significance for regional ecological, socio-economic or scientific reasons and because it may be vulnerable to damage by international shipping activities.
31	Coral Sanctuary	A place where coral is protected.
32	Recreation Area	An area within which recreational activities regularly take place and therefore vessel movement may be restricted.
33	Ship Pollution Emission Control	An area within which the ship pollution emission is controlled.

16.12 Category of Schedule

Definition : The type of schedule, for instance opening, closure, etc.

Type : enumeration

CamelCase : categoryOfSchedule

Alias :

Remarks :

Code	Label	Definition
1	Normal Operation	The service, office, is open, fully manned, and operating normally, or the area is accessible as usual.
2	Closure	The service, office, or area is closed.
3	Unmanned Operation	The service is available but not manned.

16.13 Category of Temporal Variation

Definition : An assessment of the likelihood of change over time.

Type : enumeration

CamelCase : categoryOfTemporalVariation

Alias :

Remarks :

Code	Label	Definition
1	Extreme Event	Indication of the possible impact of a significant event (for example hurricane, earthquake, volcanic eruption, landslide, etc), which is considered likely to have changed the seafloor or landscape significantly.
4	Likely to Change	Continuous or frequent change to non-bathymetric features (for example river siltation, glacier creep/recession, sand dunes, buoys, marine farms, etc).
5	Unlikely to Change	Significant change to the seafloor is not expected.
6	Unassessed	Not having been assessed.

16.14 Category of Text

Definition : Classification of completeness of textual information in relation to the source material from which it is derived.

Type : enumeration

CamelCase : categoryOfText

Alias : CATTXT

Remarks :

Code	Label	Definition
1	Abstract or Summary	A statement summarizing the important points of a text.
2	Extract	An excerpt or excerpts from a text.
3	Full Text	The whole text.

16.15 Category of Vessel Registry

Definition : The locality of vessel registration or enrolment relative to the nationality of a port, territorial sea, administrative area, exclusive zone or other location.

Type : enumeration

CamelCase : categoryOfVesselRegistry

Alias :

Remarks :

Code	Label	Definition
1	Domestic	The vessel is registered or enrolled under the same national flag as the port, harbour, territorial sea, exclusive economic zone, or administrative area in which the object that possesses this attribute applies or is located.
2	Foreign	The vessel is registered or enrolled under a national flag different from the port, harbour, territorial sea, exclusive economic zone, or other administrative area in which the object that possesses this attribute applies or is located.

16.16 City Name

Definition : The name of a town or city.

Type : text

CamelCase : cityName

Alias : CITYNM

Remarks :

16.17 Communication Channel

Definition : A channel number assigned to a specific radio frequency, frequencies or frequency band.

Type : text

CamelCase : communicationChannel

Alias : COMCHA

Remarks : The expected input is the specific VHF-Channel. The attribute ‘communication channel’ encodes the various VHF-channels used for communication.

16.18 Comparison Operator

Definition : Numerical comparison.

Type : enumeration

CamelCase : comparisonOperator

Alias : COMPOP

Remarks : Provides the relation between the value given in the model and the real ship's value.

Code	Label	Definition
1	Greater Than	The value of the left value is greater than that of the right.
2	Greater Than or Equal To	The value of the left expression is greater than or equal to that of the right.
3	Less Than	The value of the left expression is less than that of the right.
4	Less Than or Equal To	The value of the left expression is less than or equal to that of the right.
5	Equal To	The two values are equivalent.
6	Not Equal To	The two values are not equivalent.

16.19 Contact Instructions

Definition : Instructions provided on how to contact a particular person, organisation or service.

Type : text

CamelCase : contactInstructions

Alias :

Remarks :

16.20 Country Name

Definition : The name of a nation.

Type : text

CamelCase : countryName

Alias :

Remarks :**16.21 Date End**

Definition : The latest date on which an object (for example a buoy) will be present.

Type : S100_TruncatedDate

CamelCase : dateEnd

Alias : DATEND

Remarks : The Date End should be encoded using 4 digits for the calendar year (YYYY), 2 digits for the month (MM) (for example April = 04) and 2 digits for the day (DD). When no specific month and/or day is required/known, indication of the month and/or day is omitted, and replaced with dashes (-). When no specific year is required (that is, the event or date range ends at the same time each year) the following two cases may be considered:- same day each year: ——MMDD- same month each year: ——MM— This conforms to ISO 8601: 2004. Date End indicates the latest date of an event or the end of a date range. It is used to indicate the end of a fixed date range, the end of a periodic date range, or the removal or cancellation of a feature at a specific date in the future.

16.22 Date Fixed

Definition : The date of an event.

Type : S100_TruncatedDate

CamelCase : dateFixed

Alias :

Remarks :

16.23 Date Start

Definition : The earliest date on which an object (for example a buoy) will be present.

Type : S100_TruncatedDate

CamelCase : dateStart

Alias : DATSTA

Remarks : The Date Start should be encoded using 4 digits for the calendar year (YYYY), 2 digits for the month (MM) (for example April = 04) and 2 digits for the day (DD). When no specific month and/or day is required/known, indication of the month and/or day is omitted, and replaced with dashes (-). When no specific year is required (that is, the event or date range ends at the same time each year) the following two cases may be considered:- same day each year: ——MMDD- same month each year: ——MM— This conforms to ISO 8601: 2004. Date Start indicates the earliest date of an event or the start of a date range. It is used to indicate the start of a fixed date range, the start of a periodic date range, or the deployment or implementation of a feature at a specific date in the future.

16.24 Date Variable

Definition : A day which is not fixed in the Gregorian calendar.

Type : text

CamelCase : dateVariable

Alias :

Remarks : Examples: The fourth Thursday in November; new moon day of Kartika (Diwali); Easter Sunday.

16.25 Day of Week

Definition : Any one of seven days in a week.

Type : enumeration

CamelCase : dayOfWeek

Alias :

Remarks :

Code	Label	Definition
1	Sunday	The day of the week following Saturday and preceding Monday.
2	Monday	The day of the week following Sunday and preceding Tuesday.
3	Tuesday	The day of the week following Monday and preceding Wednesday.
4	Wednesday	The day of the week following Tuesday and preceding Thursday.
5	Thursday	The day of the week following Wednesday and preceding Friday.
6	Friday	The day of the week following Thursday and preceding Saturday.
7	Saturday	The day of the week following Friday and preceding Sunday.

16.26 Day of Week is Range

Definition : A statement expressing if the days of the week identified define a range or not.

Type : boolean

CamelCase : dayOfWeekIsRange

Alias :

Remarks : A True value is an indication that the identified days of the week define a range between and inclusive of those days.

16.27 Delivery Point

Definition : Details of where post can be delivered such as the apartment, name and/or number of a street, building or PO Box.

Type : text

CamelCase : deliveryPoint

Alias : DELPNT

Remarks :

16.28 Designation Identifier

Definition : An identifier which is an instance of a particular, named scheme

Type : text

CamelCase : designationIdentifier

Alias :

Remarks :

16.29 Designation Scheme

Definition : An official name, title or description. This can be an identifier itself, or an identifier which is an instance of a named designation scheme.

Type : text

CamelCase : designationScheme

Alias :

Remarks :

16.30 Destination

Definition : The place or general direction to which a vessel is going or directed.

Type : text

CamelCase : destination

Alias :

Remarks :

16.31 Distance

Definition : A numeric measure of the spatial separation between two locations.

Type : real

CamelCase : distance

Alias :

Remarks :

16.32 File Locator

Definition : The location of a fragment of text or other information in a support file.

Type : text

CamelCase : fileLocator

Alias :

Remarks : Application schemas must describe how the associated file is identified. The associated file will commonly be named in a file reference co-attribute of the same complex attribute. Each DCEG must specify requirements for the format of the associated file and the semantics of file locator. For example, the value of file locator may be an HTML ID in an HTML file, line number in a text file) or a bookmark in a PDF file.

16.33 File Reference

Definition : The file name of an externally referenced text file.

Type : text

CamelCase : fileReference

Alias : TXTDSC

Remarks :

16.34 Frequency Shore Station Receives

Definition : The shore station receiver frequency.

Type : integer

CamelCase : frequencyShoreStationReceives

Alias : FRQRXV

Remarks :

Units: Hz **Definition**: Cycles per second **Symbol**: Hz

Range: Lower Bound (Exclusive): 0 Upper Bound: (not specified)

16.35 Frequency Shore Station Transmits

Definition : The shore station transmitter frequency.

Type : integer

CamelCase : frequencyShoreStationTransmits

Alias : FRQTXM

Remarks :

Units: Hz **Definition**: Cycles per second **Symbol**: Hz

Range: Lower Bound (Exclusive): 0 Upper Bound: (not specified)

16.36 Headline

Definition : Words set at the head of a passage or page to introduce or categorize.

Type : text

CamelCase : headline

Alias :

Remarks :

16.37 Horizontal Distance Uncertainty

Definition : The best estimate of the horizontal accuracy of horizontal clearances and distances.

Type : real

CamelCase : horizontalDistanceUncertainty

Alias : HORACC

Remarks : The error is assumed to be positive and negative. The plus/minus character must not be encoded.

Units: metres **Definition**: SI Metres **Symbol**: m

Range: Lower Bound (Inclusive): 0 Upper Bound: (not specified)

16.38 In Ballast

Definition : Whether the vessel is in ballast.

Type : boolean

CamelCase : inBallast

Alias :

Remarks :

16.39 Interoperability Identifier

Definition : A common unique identifier for entities which describe a single real-world feature, and which is used to identify instances of the feature in end-user systems where the feature may be included in multiple data product types.

Type : URN

CamelCase : interoperabilityIdentifier

Alias :

Remarks :

16.40 Jurisdiction

Definition : The jurisdiction applicable to an administrative area.

Type : enumeration

CamelCase : jurisdiction

Alias : JRSDTN

Remarks :

Code	Label	Definition
1	International	Involving more than one country; covering more than one national area.
2	National	An area administered or controlled by a single nation.
3	National Sub-Division	An area smaller than the nation in which it lies.

16.41 Language

Definition : The method of human communication, either spoken or written, consisting of the use of words in a structured and conventional way.

Type : text

CamelCase : language

Alias :

Remarks : The language is encoded by a 3 character code following ISO 639-2/T.

16.42 Linkage

Definition : Location (address) for online access using a URL/URI address or similar addressing scheme.

Type : URI

CamelCase : linkage

Alias :

Remarks :

16.43 Logical Connectives

Definition : Expresses whether all the constraints described by its co-attributes must be satisfied, or only one such constraint need be satisfied.

Type : enumeration

CamelCase : logicalConnectives

Alias : LOGCON

Remarks : Is intended to be used with co-attributes that encode limits on vessel dimensions, type of cargo, and other characteristics. The combination of constraints described by logicalConnectives and its co-attributes defines a subset of vessels to which information described by a feature or information type instance applies (or does not apply, is required, recommended, etc.). The relationship between the vessel subset and the information is indicated by an association—see PermissionType and InclusionType). The two listed values of logicalConnective are two of the basic operations of Boolean logic. The third basic operation (not) is not used.

Code	Label	Definition
1	Logical Conjunction	All the conditions described by the other attributes of the object, or sub-attributes of the same complex attribute, are true.
2	Logical Disjunction	At least one of the conditions described by the other attributes of the object, or sub-attributes of the same complex attributes, is true.

16.44 Maximum Display Scale

Definition : The largest intended viewing scale for the data.

Type : integer

CamelCase : maximumDisplayScale

Alias :

Remarks :

Range: Lower Bound (Inclusive): 1 Upper Bound: (not specified)

16.45 Membership

Definition : Indicates whether a vessel is included or excluded from the regulation/restriction/recommendation/nautical information.

Type : enumeration

CamelCase : membership

Alias :

Remarks :

Code	Label	Definition
1	Included	Vessels with these characteristics are included in the regulation/restriction/recommendation/nautical information.

Code	Label	Definition
2	Excluded	Vessels with these characteristics are excluded from the regulation/restriction/recommendation/nautical information.

16.46 Minimum Display Scale

Definition : The smallest intended viewing scale for the data.

Type : integer

CamelCase : minimumDisplayScale

Alias :

Remarks :

Range: Lower Bound (Inclusive): 1 Upper Bound: (not specified)

16.47 MMSI Code

Definition : The Maritime Mobile Service Identity (MMSI) Code is formed of a series of nine digits which are transmitted over the radio path in order to uniquely identify ship stations, ship earth stations, coast stations, coast earth stations, and group calls. These identities are formed in such a way that the identity or part thereof can be used by telephone and telex subscribers connected to the general telecommunications network principally to call ships automatically.

Type : text

CamelCase : mMSICode

Alias :

Remarks :

16.48 Name

Definition : The individual name of a feature.

Type : text

CamelCase : name

Alias : OBJNAM

Remarks :

16.49 Name of Resource

Definition : Name of the online resource.

Type : text

CamelCase : nameOfResource

Alias :

Remarks :

16.50 Name Usage

Definition : Classification of the type and display level of the name of a feature in an end-user system.

Type : enumeration

CamelCase : nameUsage

Alias :

Remarks :

Code	Label	Definition
1	Default Name Display	The name is intended to be displayed when the end-user system is set to the default name/text display setting.
2	Alternate Name Display	The name is intended to be displayed when the end-user system is set to an alternate name/text display setting, for example an alternate language.
3	No Chart Display	The name or text is not intended to be displayed.

16.51 Online Function

Definition : Code for function performed by the online resource (ISO 19115)

Type : enumeration

CamelCase : onlineFunction

Alias :

Remarks :

Code	Label	Definition
1	Download	Online instructions for transferring data from one storage device or system to another.
3	Offline Access	Online instructions for requesting the resource from the provider.
4	Order	Online order process for obtaining the resource.
5	Search	To make painstaking investigation or examination.
6	Complete Metadata	Complete metadata provided.
7	Browse Graphic	Browse graphic provided.
8	Upload	Online resource upload capability provided.
9	Email Service	Online email service provided.
10	Browsing	Online browsing provided.
11	File Access	Online file access provided.

16.52 Online Resource Description

Definition : Detailed text description of what the online resource is/does (ISO 19115)

Type : text

CamelCase : onlineResourceDescription

Alias :

Remarks :

16.53 Optimum Display Scale

Definition : The largest intended viewing scale for the data.

Type : integer

CamelCase : optimumDisplayScale

Alias : CSCALE

Remarks :

Range: Lower Bound (Inclusive): 1 Upper Bound: (not specified)

16.54 Orientation Uncertainty

Definition : The best estimate of the accuracy of a bearing.

Type : real

CamelCase : orientationUncertainty

Alias :

Remarks :

16.55 Orientation Value

Definition : The angular distance measured from true north to the major axis of the feature.

Type : real

CamelCase : orientationValue

Alias : ORIENT

Remarks :

16.56 Pictorial Representation

Definition : Indicates whether a pictorial representation of the feature is available.

Type : text

CamelCase : pictorialRepresentation

Alias : PICREP

Remarks : The ‘pictorial representation’ could be a drawing or a photo. The string encodes the file name of an external graphic file (pixel/vector).

16.57 Picture Caption

Definition : Short description of the purpose of the image.

Type : text

CamelCase : pictureCaption

Alias :

Remarks :

16.58 Picture Information

Definition : A set of information to provide credits to picture creator, copyright owner etc.

Type : text

CamelCase : pictureInformation

Alias :

Remarks :

16.59 Postal Code

Definition : Known in various countries as a postcode, or ZIP code, the postal code is a series of letters and/or digits that identifies each postal delivery area.

Type : text

CamelCase : postalCode

Alias : POSCOD Postcode ZIP Code

Remarks :

16.60 Protocol

Definition : Connection protocol to be used. Example: ftp, http get KVP, http POST, etc.

Type : text

CamelCase : protocol

Alias : PROTCL

Remarks :

16.61 Protocol Request

Definition : Request used to access the resource. Structure and content depend on the protocol and standard used by the online resource, such as Web Feature Service standard.

Type : text

CamelCase : protocolRequest

Alias : PROTRQ

Remarks :

16.62 Quality of Horizontal Measurement

Definition : The degree of reliability attributed to a position.

Type : enumeration

CamelCase : qualityOfHorizontalMeasurement

Alias : QUAPOS

Remarks :

Code	Label	Definition
1	Surveyed	The position(s) was(were) determined by the operation of making measurements for determining the relative position of points on, above or beneath the earth's surface. Survey implies a regular, controlled survey of any date.
2	Unsurveyed	Survey data does not exist or is very poor.
3	Inadequately Surveyed	Not surveyed to modern standards; or due to its age, scale, or positional or vertical uncertainties is not suitable to the type of navigation expected in the area.
4	Approximate	A position that is considered to be less than third-order accuracy, but is generally considered to be within 30.5 metres of its correct geographic location. Also may apply to an object whose position does not remain fixed.
5	Position Doubtful	Of uncertain position. The expression is used principally on charts to indicate that a wreck, shoal, etc., has been reported in various positions and not definitely determined in any.
6	Unreliable	A feature's position has been obtained from questionable or unreliable data.
7	Reported (Not Surveyed)	An object whose position has been reported and its position confirmed by some means other than a formal survey such as an independent report of the same object.
8	Reported (Not Confirmed)	An object whose position has been reported and its position has not been confirmed.
9	Estimated	The most probable position of an object determined from incomplete data or data of questionable accuracy.
10	Precisely Known	A position that is of a known value, such as the position of an anchor berth or other defined object.
11	Calculated	A position that is computed from data.

16.63 Reported Date

Definition : The date that the item was observed, done, or investigated.

Type : S100_TruncatedDate

CamelCase : reportedDate

Alias : SORDAT

Remarks :

16.64 Restriction

Definition : The official legal statute of each kind of restricted area.

Type : enumeration

CamelCase : restriction

Alias : RESTRN

Remarks : Defines the kind of restriction(s), for example, the restriction for 'a game preserve' may be 'entry prohibited', the restriction for an 'anchoring prohibition' is 'anchoring prohibited'. The complete information about the restriction(s), actually held in handbooks or other publications, may be encoded using an Information type.

Code	Label	Definition
1	Anchoring Prohibited	An area within which anchoring is not permitted.

Code	Label	Definition
2	Anchoring Restricted	A specified area designated by appropriate authority, within which anchoring is restricted in accordance with certain specified conditions.
3	Fishing Prohibited	An area within which fishing is not permitted.
4	Fishing Restricted	A specified area designated by appropriate authority, within which fishing is restricted in accordance with certain specified conditions.
5	Trawling Prohibited	An area within which trawling is not permitted.
6	Trawling Restricted	A specified area designated by appropriate authority, within which trawling is restricted in accordance with certain specified conditions.
7	Entry Prohibited	An area within which navigation and/or anchoring is prohibited.
8	Entry Restricted	A specified area designated by appropriate authority, within which navigation is restricted in accordance with certain specified conditions.
9	Dredging Prohibited	An area within which dredging is not permitted.
10	Dredging Restricted	A specified area designated by appropriate authority, within which dredging is restricted in accordance with certain specified conditions.
11	Diving Prohibited	An area within which diving is not permitted.
12	Diving Restricted	A specified area designated by appropriate authority, within which diving is restricted in accordance with certain specified conditions.
13	No Wake	Mariners must adjust the speed of their vessels to reduce the wave or wash which may cause erosion or disturb moored vessels.
14	Area To Be Avoided	An IMO declared routeing measure comprising an area within defined limits in which either navigation is particularly hazardous or it is exceptionally important to avoid casualties and which should be avoided by all ships, or certain classes of ships.
15	Construction Prohibited	The erection of permanent or temporary fixed structures or artificial islands is prohibited.
16	Discharging Prohibited	An area within which discharging or dumping is prohibited.
17	Discharging Restricted	A specified area designated by an appropriate authority, within which discharging or dumping is restricted in accordance with specified conditions.
18	Industrial or Mineral Exploration/ Development Prohibited	An area within which industrial or mineral exploration and development are prohibited.
19	Industrial or Mineral Exploration/ Development Restricted	A specified area designated by an appropriate authority, within which industrial or mineral exploration and development is restricted in accordance with certain specified conditions.
20	Drilling Prohibited	An area within which excavating a hole on the sea-bottom with a drill is prohibited.
21	Drilling Restricted	A specified area designated by an appropriate authority, within which excavating a hole on the sea-bottom with a drill is restricted in accordance with certain specified conditions.
22	Removal of Historical Artefacts Prohibited	An area within which the removal of historical artefacts is prohibited.
23	Cargo Transhipment (Lightening) Prohibited	An area in which cargo transhipment (lightening) is prohibited.
24	Dragging Prohibited	An area in which the dragging of anything along the bottom, e.g. bottom trawling, is prohibited.

Code	Label	Definition
25	Stopping Prohibited	An area in which a vessel is prohibited from stopping.
26	Landing Prohibited	An area in which landing is prohibited.
27	Speed Restricted	An area within which speed is restricted.
38	Use of Spuds Prohibited	The use of anchoring spuds (telescopic piles) is prohibited.
39	Swimming Prohibited	An area in which swimming is prohibited.
40	SOx Emission Restricted	An area within which the emission of SOx is restricted.
41	NOx Emission Restricted	An area within which the emission of NOx is restricted.
42	Power-Driven Vessels Prohibited	An area within which any vessel propelled by machinery is prohibited.

16.65 Scale Minimum

Definition : The minimum scale at which the feature may be used for example for ECDIS presentation.

Type : integer

CamelCase : scaleMinimum

Alias : SCAMIN

Remarks : The modulus of the scale is indicated, that is 1:1 250 000 is encoded as 1250000.

16.66 Source

Definition : The publication, document, or reference work from which information comes or is acquired.

Type : text

CamelCase : source

Alias :

Remarks : May be populated with the corresponding paper chart Notice to Mariners numbers, although other references are permitted.

16.67 Source Date

Definition : The production date of the source; for example the date of measurement.

Type : date

CamelCase : sourceDate

Alias : SORDAT

Remarks :

16.68 Source Type

Definition : Type of the source.

Type : enumeration

CamelCase : sourceType

Alias :**Remarks :**

Code	Label	Definition
1	Law or Regulation	Treaty, convention, or international agreement; law or regulation issued by a national or other authority.
2	Official Publication	Publication not having the force of law, issued by an international organisation or a national or local administration.
7	Mariner Report, Confirmed	Reported by mariner(s) and confirmed by another source.
8	Mariner Report, Not Confirmed	Reported by mariner(s) but not confirmed.
9	Industry Publications and Reports	Shipping and other industry publications, including graphics, charts and web sites.
10	Remotely Sensed Images	Information obtained from satellite images.
11	Photographs	Information obtained from photographs.
12	Products Issued by HO Services	Information obtained from products issued by Hydrographic Offices.
13	News Media	Information obtained from news media.
14	Traffic Data	Information obtained from the analysis of traffic data.

16.69 Status

Definition : The condition of an object at a given instant in time.

Type : enumeration

CamelCase : status

Alias : STATUS

Remarks :

Code	Label	Definition
1	Permanent	Intended to last or function indefinitely.
2	Occasional	Acting on special occasions; happening irregularly.
3	Recommended	Presented as worthy of confidence, acceptance, use, etc.
4	Not in Use	Use has ceased, but the facility still exists intact; disused.
5	Periodic/ Intermittent	Recurring at intervals.
6	Reserved	Set apart for some specific use.
7	Temporary	Meant to last only for a time.
9	Mandatory	Compulsory; enforced.
13	Historic	Famous in history; of historical interest.
14	Public	Belonging to, available to, used or shared by, the community as a whole and not restricted to private use.

Code	Label	Definition
18	Existence Doubtful	A feature that has been reported but has not been definitely determined to exist.
28	Buoyed	Marked by buoys.

16.70 Telecommunication Carrier

Definition : The name of a provider or type of carrier for a telecommunication service. This service may include land line based, shore based or satellite based radio connections.

Type : text

CamelCase : telecommunicationCarrier

Alias :

Remarks :

16.71 Telecommunication Identifier

Definition : An identifier, such as words, numbers, letters, symbols, or any combination of those used to establish a contact to a particular person, organisation or service.

Type : text

CamelCase : telecommunicationIdentifier

Alias :

Remarks :

16.72 Telecommunication Service

Definition : Classification of methods of communication over a distance by electrical, electronic, or electromagnetic means.

Type : enumeration

CamelCase : telecommunicationService

Alias :

Remarks :

Code	Label	Definition
1	Voice	The transfer or exchange of information by using sounds that are being made by mouth and throat when speaking.
2	Facsimile	A system of transmitting and reproducing graphic matter (as printing or still pictures) by means of signals sent over telephone lines.
3	SMS	Short Message Service is a form of text messaging communication on phones and mobile phones.
4	Data	A representation of facts, concepts or instructions in a formalised manner suitable for communication, interpretation or processing.
5	Streamed Data	Data that is constantly received by and presented to an end-user while being delivered by a provider.
6	Telex	A system of communication in which messages are sent over long distances by using a telephone system and are printed by using a special machine (called a teletypewriter).

Code	Label	Definition
7	Telegraph	An apparatus, system or process for communication at a distance by electric transmission over wire.
8	Email	Messages and other data exchanged between individuals using computers in a network.

16.73 Text

Definition : A non-formatted digital text string.

Type : text

CamelCase : text

Alias : INFORM NINFOM

Remarks : Should be used, for example, to hold the information that is for short cautionary or explanatory notes. Therefore, text populated in text must not exceed 300 characters. Text may be in English, or in a national language. No formatting of text is possible within text. If formatted text, or text strings exceeding 300 characters, is required, then an alternate concept should be used.

16.74 Text Offset Bearing

Definition : The angular distance measured from true north that text associated with a feature is positioned from the feature in an end-user system.

Type : integer

CamelCase : textOffsetBearing

Alias :

Remarks :

Units: Degree of Arc **Definition:** $1^\circ = (\pi/180)$ rad **Symbol:** °

Range: Lower Bound (Exclusive): 0 Upper Bound (Exclusive): 360

16.75 Text Offset Distance

Definition : The distance that text associated with a feature is positioned from the feature in an end-user system.

Type : integer

CamelCase : textOffsetDistance

Alias :

Remarks :

Units: Millimetre **Definition:** 1 metre = 1000 millimetres **Symbol:** mm

Range: Lower Bound (Exclusive): 0 Upper Bound (Inclusive): 50

16.76 Text Rotation

Definition : A statement that expresses if text associated with a feature is to be rotated in the ECDIS display or not.

Type : boolean

CamelCase : textRotation

Alias :**Remarks :**

16.77 Text Type

Definition : The attribute from which a text string is derived.

Type : enumeration

CamelCase : textType

Alias :**Remarks :**

Code	Label	Definition
1	Name	The individual name of a feature.

16.78 Thickness of Ice Capability

Definition : The thickness of ice that the ship can safely transit.

Type : integer

CamelCase : thicknessOfIceCapability

Alias :**Remarks :**

Units: centimetres **Definition:** Centimetres (SI) **Symbol:** cm

Range: Lower Bound (Exclusive): 0 Upper Bound: (not specified)

16.79 Time of Day End

Definition : The time corresponding to the end of an active period.

Type : time

CamelCase : timeOfDayEnd

Alias :

Remarks : The time of day end must be encoded using 2 digits for the hour (hh), 2 digits for the minutes(mm) and 2 digits for the seconds (ss). This conforms to ISO 8601:2004.

16.80 Time of Day Start

Definition : The time corresponding to the start of an active period.

Type : time

CamelCase : timeOfDayStart

Alias :

Remarks : The time of day start must be encoded using 2 digits for the hour (hh), 2 digits for the minutes(mm) and 2 digits for the seconds (ss). This conforms to ISO 8601:2004.

16.81 Uncertainty Fixed

Definition : The best estimate of the fixed horizontal or vertical accuracy component for positions, depths, heights, vertical distances and vertical clearances.

Type : real

CamelCase : uncertaintyFixed

Alias : POSACC SOUACC VERACC

Remarks :

Units: Metre **Definition:** The basic unit of length in the International System of Units (SI) system.

Symbol: m

16.82 Uncertainty Variable Factor

Definition : The factor to be applied to the variable component of an uncertainty equation so as to provide the best estimate of the variable horizontal or vertical accuracy component for positions, depths, heights, vertical distances and vertical clearances.

Type : real

CamelCase : uncertaintyVariableFactor

Alias :

Remarks :

16.83 Vessel Performance

Definition : A description of the required handling characteristics of a vessel including hull design, main and auxiliary machinery, cargo handling equipment, navigation equipment and manoeuvring behaviour.

Type : text

CamelCase : vesselPerformance

Alias :

Remarks :

16.84 Vessels Characteristics

Definition : Characteristics of vessels.

Type : enumeration

CamelCase : vesselsCharacteristics

Alias :

Remarks :

Code	Label	Definition
1	Length Overall	The maximum length of the ship.
2	Length at Waterline	The ship's length measured at the waterline.
3	Breadth	The width or beam of the vessel.
4	Draught	The depth of water necessary to float a vessel fully loaded.
6	Displacement Tonnage	A measurement of the weight of the vessel, usually used for warships. (Merchant ships are usually measured based on the volume of cargo space; see tonnage).

Code	Label	Definition
		Displacement is expressed either in long tons of 2,240 pounds or metric tonnes of 1,000 kg. Since the two units are very close in size (2,240 pounds = 1,016 kg and 1,000 kg = 2,205 pounds), it is common not to distinguish between them. To preserve secrecy, nations sometimes misstate a warship's displacement.
7	Displacement Tonnage, Light	The weight of the ship excluding cargo, fuel, ballast, stores, passengers, and crew, but with water in the boilers to steaming level.
8	Displacement Tonnage, Loaded	The weight of the ship including cargo, passengers, fuel, water, stores, dunnage and such other items necessary for use on a voyage, which brings the vessel down to her load draft.
9	Deadweight Tonnage	The difference between displacement, light and displacement, loaded. A measure of the ship's total carrying capacity.
10	Gross Tonnage	The entire internal cubic capacity of the ship expressed in tons of 100 cubic feet to the ton, except certain spaces which are exempted such as: peak and other tanks for water ballast, open forecastle bridge and poop, access of hatchways, certain light and air spaces, domes of skylights, condenser, anchor gear, steering gear, wheel house, galley and cabin for passengers.
11	Net Tonnage	Obtained from the gross tonnage by deducting crew and navigating spaces and allowances for propulsion machinery.
12	Panama Canal/Universal Measurement System Net Tonnage	The Panama Canal/Universal Measurement System (PC/UMS) is based on net tonnage, modified for Panama Canal purposes. PC/UMS is based on a mathematical formula to calculate a vessel's total volume; a PC/UMS net ton is equivalent to 100 cubic feet of capacity.
13	Suez Canal Net Tonnage	The Suez Canal Net Tonnage (SCNT) is derived with a number of modifications from the former net register tonnage of the Moorsom System and was established by the International Commission of Constantinople in its Protocol of 18 December 1873. It is still in use, as amended by the Rules of Navigation of the Suez Canal Authority, and is registered in the Suez Canal Tonnage Certificate.

16.85 Vessels Characteristics Unit

Definition : The unit used for vessel characteristics attribute.

Type : enumeration

CamelCase : vesselsCharacteristicsUnit

Alias : VSLUNT

Remarks :

Code	Label	Definition
1	Metres	The basic unit of length in the International System of Units (SI) system.
3	Metric Ton	The tonne or metric ton (U.S.), often redundantly referred to as a metric tonne, is a unit of mass equal to 1,000 kg (2,205 lb) or approximately the mass of one cubic metre of water at four degrees Celsius. It is sometimes abbreviated as mt in the United States, but this conflicts with other SI symbols. The tonne is not a unit in the International System of Units (SI), but is accepted for use with the SI. In SI units and prefixes, the tonne is a megagram (Mg). The Imperial and US customary units comparable to the tonne are both spelled ton in English, though they differ in mass. Pronunciation of tonne (the word used in the UK) and ton is usually identical, but is not too confusing unless accuracy is important as the tonne and UK long ton differ by only 1.6.
4	Ton	Long ton (weight ton or imperial ton) is the name for the unit called the "ton" in the avoirdupois or Imperial system of measurements, as used in the United Kingdom and

Code	Label	Definition
		several other Commonwealth countries. It has been mostly replaced by the tonne, and in the United States by the short ton. One long ton is equal to 2,240 pounds (1,016 kg) or 35 cubic feet (0.9911 m) of salt water with a density of 64 lb/ft (1.025 g/ml). It has some limited use in the United States, most commonly in measuring the displacement of ships, and was the unit prescribed for warships by the Washington Naval Treaty for example battleships were limited to a mass of 35,000 long tons (36,000 t; 39,000 ST).
5	Short Ton	A unit of weight equal to 2,000 pounds (907.18474 kg). In the United States it is often called simply ton without distinguishing it from the metric ton (tonne, 1,000 kilograms) or the long ton (2,240 pounds / 1,016.0469088 kilograms); rather, the other two are specifically noted. There are, however, some US applications for which unspecified tons normally means long tons (for example, Navy ships) or metric tons (world grain production figures). Both the long and short ton are defined as 20 hundredweights, but a hundredweight is 100 pounds (45.359237 kg) in the US system (short or net hundredweight) and 112 pounds (50.80234544 kg) in the Imperial system (long or gross hundredweight).
6	Gross Ton	Gross tonnage (GT) is a function of the volume of all ship's enclosed spaces (from keel to funnel) measured to the outside of the hull framing. There is a sliding scale factor. So GT is a kind of capacity-derived index that is used to rank a ship for purposes of determining manning, safety and other statutory requirements and is expressed simply as GT, which is a unitless entity, even though its derivation is tied to the cubic meter unit of volumetric capacity. Tonnage measurements are now governed by an IMO Convention (International Convention on Tonnage Measurement of Ships, 1969 (London-Rules)), which applies to all ships built after July 1982. In accordance with the Convention, the correct term to use now is GT, which is a function of the moulded volume of all enclosed spaces of the ship.
7	Net Ton	Net tonnage (NT) is based on a calculation of the volume of all cargo spaces of the ship. It indicates a vessel's earning space and is a function of the moulded volume of all cargo spaces of the ship.
9	Suez Canal Net Tonnage	The Suez Canal Net Tonnage (SCNT) is derived with a number of modifications from the former net register tonnage of the Moorsom System and was established by the International Commission of Constantinople in its Protocol of 18 December 1873. It is still in use, as amended by the Rules of Navigation of the Suez Canal Authority, and is registered in the Suez Canal Tonnage Certificate.

16.86 Vessels Characteristics Value

Definition : The value of a particular characteristic such as a dimension or tonnage of a vessel.

Type : real

CamelCase : vesselsCharacteristicsValue

Alias :

Remarks : Indicates range limits in expressions characterizing vessels by dimensions and tonnages. The unit of measure, characteristic, and comparison operator (greater, less, etc.) are encoded separately.

16.87 Action or Activity

Definition : The action or activity of a vessel.

Type : S100_CodeList

CamelCase : actionOrActivity

Alias :

Remarks :

Code	Label	Definition
1	Navigating With a Pilot	Carrying a qualified pilot as part of the vessel navigation team.
2	Entering Port	Navigating a vessel into a port.
3	Leaving Port	Navigating a vessel out of a port.
4	Berthing	A signal station for the control of vessels when berthing.
5	Slipping	Detaching a vessel from a wharf or jetty.
6	Anchoring	Attaching a vessel to the seabed by means of an anchor and cable.
7	Weighing Anchor	Detaching a vessel from the seabed by recovering an anchor and cable.
8	Transiting	Navigating a vessel along a route or through a narrow gap, such as under a bridge or through a lock.
9	Overtaking	Navigating a vessel past another traveling broadly in the same direction.
10	Reporting	Providing details such as the name, location or intentions of a vessel.
11	Working Cargo	Loading or unloading cargo.
12	Landing	Placing crew or passengers on shore.
13	Diving	A signal or message warning of diving activity.
14	Fishing	Hunting or catching fish.
15	Discharging Overboard	Releasing anything into the sea; often ballast water; or spoil from dredging elsewhere.
16	Passing	Navigating a vessel past another travelling broadly in the opposite direction.
17	Ballast Water Exchange	Discharge and uptake of ballast water.
18	Hull Cleaning	The removal or treatment of biofouling (accumulation of aquatic organisms including microfouling and macrofouling) from a ship's submerged surfaces, including hull and niche areas, conducted either in-water or during dry-docking. The process includes both proactive cleaning (periodic removal of microfouling) and reactive cleaning (removal of micro- and macrofouling as corrective action).
19	Scientific Research	The conduct of observational, sampling, or experimental activities by authorised personnel to collect scientific or environmental data, which may involve the deployment of scientific instruments, collection of biological or geological samples, or in-water survey operations.
20	Tourism	Organised recreational visitation and leisure activities in marine areas, including sight-seeing, wildlife observation, glass-bottom vessel tours, and guided nature excursions conducted by commercial or permitted operators.
21	Education	Structured activities conducted for training, awareness, or interpretive purposes involving groups or individuals learning about the marine environment, including guided educational programs, school activities, and field instruction conducted within designated marine areas.
22	Infrastructure Maintenance	Inspection, repair, or upkeep of existing marine or coastal infrastructure such as wharves, piers, pipelines, moorings, subsea cables, navigational aids, or coastal protection structures, including minor works that do not expand the original footprint.

16.88 Category of Marine Protected Area

Definition : Classification of marine protected areas based on IUCN (International Union for Conservation of Nature and Natural Resources) categories.

Type : S100_CodeList

CamelCase : categoryOfMarineProtectedArea

Alias :

Remarks :

Code	Label	Definition
1	IUCN Category Ia	Strict Nature Reserve: Protected area managed mainly for science.
2	IUCN Category Ib	Wilderness Area: Protected area managed mainly for wilderness protection.
3	IUCN Category II	National Park: Protected area managed mainly for ecosystem protection and recreation.
4	IUCN Category III	Natural Monument: Protected area managed mainly for conservation of specific natural features.
5	IUCN Category IV	Habitat/Species Management Area: Protected area managed mainly for conservation through management intervention.
6	IUCN Category V	Protected Landscape/Seascape: Protected area managed mainly for landscape/seascape conservation and recreation.
7	IUCN Category VI	Managed Resource Protected Area: Protected area managed mainly for the sustainable use of natural ecosystems.

16.89 Category of RxN

Definition : The principal subject matter of regulations, restrictions, recommendations or nautical information.

Type : S100_CodeList

CamelCase : categoryOfRxN

Alias :

Remarks :

Code	Label	Definition
1	Navigation	The process of directing the movement of a craft from one point to another.
2	Communication	Transmitting and/or receiving electronic communication signals.
3	Environmental Protection	Pertaining to environmental protection.
4	Wildlife Protection	Pertaining to wildlife protection.
5	Security	Pertaining to security.
6	Customs	The agency or establishment for collecting duties, tolls.
7	Cargo Operation	Pertaining to cargo operations.
8	Refuge	Pertaining to a place of safety or refuge.

Code	Label	Definition
9	Health	The authority with responsibility for checking the validity of the health declaration of a vessel and for declaring free pratique.
10	Natural Resources or Exploitation	Pertaining to natural resources or exploitation.
11	Port	Person or corporation, owners of, or entrusted with or invested with the power of managing a port. May be called a Harbour Board, Port Trust, Port Commission, Harbour Commission, Marine Department.
12	Finance	An authority with responsibility for the control and movement of money.
13	Agriculture	The science, art, or practice of cultivating the soil, producing crops, and raising livestock and in varying degrees the preparation and marketing of the resulting products.

16.90 Category of Vessel

Definition : Classification of vessels by function or use.

Type : S100_CodeList

CamelCase : categoryOfVessel

Alias :

Remarks :

Code	Label	Definition
1	General Cargo Vessel	A vessel which is designed for carrying general cargo, e.g. boxes, sacks.
2	Container Carrier	A vessel designed to carry ISO containers.
3	Tanker	A vessel which is designed for carrying liquid goods, for example oil or water.
4	Bulk Carrier	A vessel which is designed for carrying bulk goods, e.g. coal, ore or grain.
5	Passenger Vessel	A day trip or cabin vessel constructed and equipped to carry more than 12 passengers.
6	Roll-On Roll-Off	A vessel designed to allow road vehicles to be driven on and off; often a ferry.
7	Refrigerated Cargo Vessel	A vessel designed to carry refrigerated cargo.
8	Fishing Vessel	A vessel that is used and equipped for the fishing of living aquatic resources.
9	Service	A vessel which provides a service such as a tug, anchor handler, survey or supply vessel.
10	Warship	A vessel designed for the conduct of military operations.
11	Towed or Pushed Composite Unit	Either a tug and tow, or any combination of a tug providing propulsion to barges or vessels secured ahead or alongside.
12	Tug and Tow	A combination of tug(s) and non-powered tow(s).
13	Light Recreational	A pleasure boat or watercraft, or an excursion vessel used for short cruises such as whale watching.
14	Semi-Submersible Offshore Installation	An installation which is designed to float at all times and which is normally anchored in position when deployed in the offshore gas and oil industry.

Code	Label	Definition
15	Jack-Up Exploration or Project Installation	An exploration or project installation with legs which can be raised and lowered. The legs are raised when the installation is re-positioned. When stationary the legs are lowered to the sea floor and the working platform is raised clear of the sea surface.
16	Livestock Carrier	A vessel designed to carry large quantities of live animals.
17	Sport Fishing	A vessel used in fishing for pleasure or competition.

17 Complex Attributes

17.1 Bearing Information

Definition : A bearing is the direction one object is from another object.

CamelCase : bearingInformation

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
cardinalDirection	enumeration	0,1
distance	real	0,1
information	Complex	0,*
orientation	Complex	0,1

17.2 Contact Address

Definition : Direction or superscription of a letter, package, etc., specifying the name of the place to which it is directed, and optionally a contact person or organisation who should receive it.

CamelCase : contactAddress

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
deliveryPoint	text	0,1
cityName	text	0,1
administrativeDivision	text	0,1
countryName	text	0,1
postalCode	text	0,1

17.3 Designation

Definition : An official name, title or description. This can be an identifier or an identifier which is an instance of a named designation scheme.

CamelCase : designation

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
designationScheme	text	0,1
designationIdentifier	text	0,1
jurisdiction	enumeration	0,1
text	text	0,1

17.4 Feature Name

Definition : Provides the name of an entity, defines the national language of the name, and provides the option to display the name at various system display settings.

CamelCase : featureName

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
language	text	1,1
name	text	1,1
nameUsage	enumeration	0,1

17.5 Fixed Date Range

Definition : An active period of a single fixed event or occurrence, as the date range between discrete start and end dates.

CamelCase : fixedDateRange

Alias :

Remarks : Dates must be encoded in the format YYYYMMDD; using 4 digits for the calendar year (YYYY) and, optionally, 2 digits for the month (MM) (for example April = 04) and 2 digits for the day (DD). When no specific month and/or day is required/known, the values are replaced with dashes (-). The date range of a recurring event or occurrence must be encoded using periodicDateRange.

Sub-attributes :

Sub-Attribute	Type	Multiplicity
dateStart	S100_TruncatedDate	0,1
dateEnd	S100_TruncatedDate	0,1

17.6 Frequency Pair

Definition : A pair of frequencies for transmitting and receiving radio signals. The shore station transmits and receives on the frequencies indicated.

CamelCase : frequencyPair

Alias : FRQPAR

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
frequencyShoreStationReceives	integer	0,1
frequencyShoreStationTransmits	integer	1,1

17.7 Graphic

Definition : Pictorial information such as a photograph, sketch or other graphic, optionally accompanied by descriptive information about the graphic and the location relative to its subject from which it was made.

CamelCase : graphic

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
pictorialRepresentation	text	1,*
pictureCaption	text	0,1
sourceDate	date	0,1
pictureInformation	text	0,1
bearingInformation	Complex	0,1

17.8 Horizontal Position Uncertainty

Definition : The best estimate of the accuracy of a position.

CamelCase : horizontalPositionUncertainty

Alias : POSACC

Remarks : The expected input is the maximum of the two-dimensional error. The error is assumed to be positive and negative.

Sub-attributes :

Sub-Attribute	Type	Multiplicity
uncertaintyFixed	real	1,1
uncertaintyVariableFactor	real	0,1

17.9 Information

Definition : Textual information about the feature. The information may be provided as a string of text or as a file name of a single external text file that contains the text.

CamelCase : information

Alias : INFORM

Remarks : At least one of the sub-attributes file reference or text must be populated. The sub-attribute file reference is generally used for long text strings or those that require formatting, however, there is no restriction on the type of text (except for lexical level) that can be held in files referenced by sub-attribute file reference.

Sub-attributes :

Sub-Attribute	Type	Multiplicity
fileLocator	text	0,1
fileReference	text	0,1
headline	text	0,* (ordered)
language	text	0,1
text	text	0,1

17.10 Online Resource

Definition : Information about online sources from which a resource or data can be obtained.

CamelCase : onlineResource

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
linkage	URI	1,1
protocol	text	0,1
applicationProfile	text	0,1
nameOfResource	text	0,1
onlineResourceDescription	text	0,1
protocolRequest	text	0,1
onlineFunction	enumeration	0,1

17.11 Orientation

Definition : (1) The angular distance measured from true north to the major axis of the feature. (2) In ECDIS, the mode in which information on the ECDIS is being presented. Typical modes include: north-up—as shown on a nautical chart, north is at the top of the display; Ships head-up—based on the actual heading of the ship, (e.g. Ships gyrocompass); course-up display—based on the course or route being taken.

CamelCase : orientation

Alias :**Remarks :****Sub-attributes :**

Sub-Attribute	Type	Multiplicity
orientationUncertainty	real	0,1
orientationValue	real	1,1

17.12 Periodic Date Range

Definition : The active period of a recurring event or occurrence.

CamelCase : periodicDateRange

Alias :**Remarks :****Sub-attributes :**

Sub-Attribute	Type	Multiplicity
dateStart	S100_TruncatedDate	1,1
dateEnd	S100_TruncatedDate	1,1

17.13 RxN Code

Definition : A summary of the impact of the most common types of regulation, restriction, recommendation and nautical information on a vessel.

CamelCase : rxNCode

Alias :**Remarks :****Sub-attributes :**

Sub-Attribute	Type	Multiplicity
categoryOfRxN	S100_CodeList	0,1
actionOrActivity	S100_CodeList	0,1
headline	text	0,1

17.14 Schedule by Day of Week

Definition : The nature and timings of a daily schedule by days of the week.

CamelCase : scheduleByDayOfWeek

Alias :**Remarks :****Sub-attributes :**

Sub-Attribute	Type	Multiplicity
categoryOfSchedule	enumeration	0,1
text	text	0,1
timeIntervalsByDayOfWeek	Complex	1,*

17.15 Spatial Accuracy

Definition : Provides an indication of the vertical and horizontal positional uncertainty of bathymetric data, optionally within a specified date range.

CamelCase : spatialAccuracy

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
fixedDateRange	Complex	0,1
horizontalPositionUncertainty	Complex	0,1
verticalUncertainty	Complex	0,1

17.16 Source Indication

Definition : Information about the source document, publication, or reference from which object data or textual material included or referenced in a dataset are derived.

CamelCase : sourceIndication

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
categoryOfAuthority	enumeration	0,1
countryName	text	0,1
source	text	0,1
sourceType	enumeration	0,1
reportedDate	S100_TruncatedDate	0,1
featureName	Complex	0,*

17.17 Survey Date Range

Definition : The complex attribute describes the period of the hydrographic survey, as the time between its sub-attributes.

CamelCase : surveyDateRange

Alias :

Remarks :**Sub-attributes :**

Sub-Attribute	Type	Multiplicity
dateStart	S100_TruncatedDate	0,1
dateEnd	S100_TruncatedDate	1,1

17.18 Telecommunications

Definition : A means or channel of communicating at a distance by electrical or electromagnetic means such as telegraphy, telephony, or broadcasting.

CamelCase : telecommunications

Alias :

Remarks : If no value is populated for the sub-attribute telecommunication service, this means the service is by voice communication. If no value is populated for the sub-attribute telecommunication carrier, this means the service is by land line communication.

Sub-attributes :

Sub-Attribute	Type	Multiplicity
categoryOfCommunicationPreference	enumeration	0,1
telecommunicationIdentifier	text	1,1
telecommunicationCarrier	text	0,1
contactInstructions	text	0,1
telecommunicationService	enumeration	0,*

17.19 Text Content

Definition : Textual material, or a pointer to a resource providing textual material. May be accompanied by basic information about its source and relationship to the source.

CamelCase : textContent

Alias : TXTCON

Remarks : Exactly one of sub-attributes onlineResource or information must be completed in one instance of textContent. Product specifications may restrict the use or content of onlineResource for security. For example, a product specification may forbid populating onlineResource. Product specification authors must consider whether applications using the data product may be prevented from accessing off-system resources by security policies.

Sub-attributes :

Sub-Attribute	Type	Multiplicity
categoryOfText	enumeration	0,1
information	Complex	0,*
onlineResource	Complex	0,1
sourceIndication	Complex	0,*

17.20 Time Intervals by Day of Week

Definition : The regular weekly operation times of a service or schedule.

CamelCase : timeIntervalsByDayOfWeek

Alias :

Remarks :

Sub-attributes :

Sub-Attribute	Type	Multiplicity
dayOfWeek	enumeration	0,7 (ordered)
dayOfWeekIsRange	boolean	0,1
timeOfDayStart	time	0,* (ordered)
timeOfDayEnd	time	0,* (ordered)

17.21 Vertical Uncertainty

Definition : The best estimate of the vertical accuracy of depths, heights, vertical distances and vertical clearances.

CamelCase : verticalUncertainty

Alias : VERACC

Remarks : Encodes the vertical uncertainty associated with any vertical measurement.

Sub-attributes :

Sub-Attribute	Type	Multiplicity
uncertaintyFixed	real	1,1
uncertaintyVariableFactor	real	0,1

17.22 Vessel Measurements Specification

Definition : Combinations of values of measurable characteristics or dimensions of vessels, used to specify size and tonnage ranges.

CamelCase : vesselMeasurementsSpecification

Alias :

Remarks : Combines (i) specifications of vessels' measurable characteristics (length, beam, tonnages, etc.), (ii) limit values for the specified characteristics (with units), (iii) arithmetical comparison operators (greater than, etc.), and (iv) logical operators (AND/OR) to define a subset of vessels characterized by the specified ranges. For example, the combination (draught, 10.5, metres, greaterThan) describes "vessels with draught greater than 10.5 metres".

Sub-attributes :

Sub-Attribute	Type	Multiplicity
comparisonOperator	enumeration	1,1
vesselCharacteristics	enumeration	1,1
vesselCharacteristicsValue	real	1,1

Sub-Attribute	Type	Multiplicity
<u>vesselsCharacteristicsUnit</u>	enumeration	1,1