

COMP 474 UU,COMP 6741 UU 2214

[Home](#) / [My courses](#) / [COMP-474-2214-UU](#) / 13 February - 19 February / [Lab Session #05](#)

Lab Session #05

Introduction

Welcome to Lab #05. This week we will continue working with SPARQL and knowledge graphs, moving up to the application layer.

Note: All instructions below assume you run *Linux*, your experience on MacOS or Windows may vary.

Follow-up Lab #04

Example solutions to the DBpedia queries from last week:

1. All *universities located in Canada*, with their city and *optionally* (if it exists) their home page:

```
SELECT ?university ?city ?homepage WHERE {  
    ?university a dbo:University .  
    ?university dbo:country dbr:Canada .  
    ?university dbo:city ?city .  
    OPTIONAL {?university foaf:homepage ?homepage} .  
}  
ORDER BY ?city
```

2. All people who *studied at Concordia University* (and are listed in DBpedia), together with their description (in English):

```
SELECT ?name ?comment WHERE {  
    ?cuperson dbo:almaMater dbr:Concordia_University .  
    ?cuperson foaf:name ?name .  
    ?cuperson rdfs:comment ?comment .  
    FILTER (LANG(?comment) = 'en') .  
}  
ORDER BY ?name
```

You might be surprised that you can run these queries even without any **PREFIX** declarations: That's because there are a [number of pre-defined prefixes](#) in the DBpedia query interface.

As discussed with Worksheet #3, unfortunately the property `dbo:city` is not used consistently at the moment (this is related to the DBpedia generation process from the Wikipedia infoboxes as discussed in the last lecture, as well as the ongoing replacement of manually updated Wikipedia infoboxes with automated Wikidata queries). In practice, when querying DBpedia, make sure what you are looking for is represented consistently.

Solution Task #2.2 (Learning SPARQL with Fuseki)

Here's an [example](#) solution for the SPARQL with Apache Fuseki from the previous lab. You can play around with different SPARQL queries.

Solution Task #3 (SPARQL with Python)

Here's an [example](#) solution for the SPARQL with Python from the previous lab. Of course, your solution might look slightly different.

If you're confused about any part of it, just ask in the Moodle Discussion forum!

Task #1: Linked Open Data



















As you've seen, many [Linked Open Data](#) knowledge graphs provide a public SPARQL interface (a so-called *SPARQL endpoint*), for example:

- [DBpedia](#)
- [Wikidata](#)
- [NextProt](#)

Some only offer a dataset for download or have other restrictions (such as registering an API key).

Task #1.1: Wikidata

Try out some of the [query examples for Wikidata](#) provided at the top of the query page:

Type to filter	326
Entertainment	
Rock bands that start with "M" 	 
Winner of the Academy Awards by Award and Time 	 
Academy award data 	 
People that received both Academy Award and Nobel Prize 	 
Number of handed out academy awards per award type 	 
Film directors ranked by number of sitelinks multiplied by their number of films 	 

Note that Wikidata's SPARQL server offers a number of different result formats (click on the "Play" button on the left to run the query), e.g.:

1. [List of parliament buildings with pictures by country](#) (image grid)

```
#defaultView:ImageGrid
SELECT ?building ?buildingLabel ?country ?countryLabel ?picture
WHERE
{
    ?building wdt:P31 wd:Q7138926 .
    ?building wdt:P18 ?picture .
    OPTIONAL { ?building wdt:P17 ?country } .    #if available
    SERVICE wikibase:label {
        bd:serviceParam wikibase:language "en" .
    }
}
ORDER BY ?countryLabel
LIMIT 188
```

2. [Locations of Pablo Picasso works](#) (map view)

```
#defaultView:Map
SELECT ?label ?coord ?subj
WHERE
{
    ?subj wdt:P170 wd:Q5593 .
    OPTIONAL {
        ?subj wdt:P276 ?loc .
        ?loc wdt:P625 ?coord } .
    ?subj rdfs:label ?label filter (lang(?label) = "en")
}
```

Now it's your turn, write your own queries to:

1. List all the *member countries of the EU* with their name (look at the example queries above to see how to filter the label for a specific language in Wikidata)
2. Same as above, but print out the *capital* of each country on a map (look at the second example query above to see how to retrieve and render coordinates using a map view)

Task #1.2: Get your Protein fix here

Biomedical research was one of the first domains to adopt semantic technologies, since the huge amounts of data from experiments and publications is too much handle for human scientists: That's why you find so many life-science related datasets and ontologies on the LOD cloud.

Simple search ☒ Advanced search (SPARQL)

proteins ▼ 1 Put your SPARQL query here Search

e.g.: Search for MSH6 in proteins, Search for author Doolittle in publications, Search for liver in terms

Summary Details

Tags ▼ search in 146 queries (ex: liver) New Query X

Proteins phosphorylated and located in the cytoplasm	NXQ_00001	
Proteins that are located in both the nucleus and in the cytoplasm	NXQ_00002	
Proteins with 7 transmembrane regions	NXQ_00003	
Proteins expressed in brain with IHC expression level: "high" but not expressed in testis	NXQ_00004	

Try experimenting with a few example queries provided at the [NextProt](#) SPARQL endpoint to see how a domain-specific LOD dataset looks like.

Task #2: Entity Tagging with DBpedia-Spotlight

Your next task is to experiment with the [DBpedia-Spotlight](#) service discussed in the lecture. We already worked using the web-based demo interface during the lecture exercises, now your task is to understand it's [API](#): Spotlight has a restful interface that you can access like this:

```
curl -X GET "https://api.dbpedia-spotlight.org/en/annotate?text=Concordia%20advanced%20six%20spots%20to%2010th%20place%20among%20Canada%E2%80%99s%20engineering%20schools%20in%20the%20M" -H "accept: application/json"
```

The result is in JSON format:

```

{
  "@text": "Concordia advanced six spots to 10th place among Canada's engineering schools in the Maclean's 2018 Program
Rankings, while computer science advanced three spots into 11th position this year.",
  "@confidence": "0.5",
  "@support": "0",
  "@types": "",
  "@sparql": "",
  "@policy": "whitelist",
  "Resources": [
    {
      "@URI": "http://dbpedia.org/resource/Concordia_University",
      "@support": "1835",
      "@types":
"Wikidata:Q43229,Wikidata:Q3918,Wikidata:Q24229398,DUL:SocialPerson,DUL:Agent,Schema:Organization,Schema:EducationalOrganizat

      "@surfaceForm": "Concordia",
      "@offset": "0",
      "@similarityScore": "0.9999782207698248",
      "@percentageOfSecondRank": "1.995676280252352E-5"
    },
    {
      "@URI": "http://dbpedia.org/resource/Canada",
      "@support": "220739",
      "@types":
"Wikidata:Q6256,Schema:Place,Schema:Country,DBpedia:PopulatedPlace,DBpedia:Place,DBpedia:Location,DBpedia:Country",
      "@surfaceForm": "Canada",
      "@offset": "49",
      "@similarityScore": "0.9997965603941569",
      "@percentageOfSecondRank": "1.318801347665404E-4"
    },
    {
      "@URI": "http://dbpedia.org/resource/Computer_science",
      "@support": "11027",
      "@types": "",
      "@surfaceForm": "computer science",
      "@offset": "124",
      "@similarityScore": "0.9999981246676802",
      "@percentageOfSecondRank": "6.422167580532429E-7"
    }
  ]
}

```

Make sure you understand the conceptual difference between the *surface form*, which appears in the text you are analyzing, and the link (URI) itself. This is where ambiguities need to be resolved: for example, the surface form "Hilton" could be linked to the company or the person "Paris Hilton", depending on the context.

Try writing a simple Python program that accepts a query string, sends a REST request and displays the detected entities.

Note that for frequent requests, you should setup your own Spotlight server. An easy way to install one is to use the provided *Docker* image, which you can find on its [Github page](#).

Task #3: Even Smarter University Agent

Now you are ready to spruce up your intelligent university agent from the previous week: Give it a simple natural language interface that, for now, only recognizes the pattern "*Who is <X>*". Obtain *<X>* using some simple regex-pattern matching from the input string and create a SPARQL query that extracts the answer from your knowledge graph. You can then have a dialog like this:

```
Hello, I am your smart university agent. How can I help you?  
> Who is Joe?  
  
Joe is 22 years old and has the email address joe@example.com.
```

Bonus task: Also support the query "*What is <X>*", where you search for *<X>* using a suitable SPARQL query on DBpedia, printing out the comment:

```
Hello, I am your smart university agent. How can I help you?  
> What is Concordia University?  
  
Concordia University (commonly referred to as Concordia) is a public comprehensive university located in  
Montreal, Quebec, Canada. Founded in 1974 following the merger of Loyola College and Sir George Williams University...
```

Now you are *almost* as good as the Google Assistant!

That's all for this lab!

Last modified: Tuesday, 15 February 2022, 9:38 AM

[◀ Worksheet #05](#)

Jump to...

[Lecture Slides #07 ▶](#)

You are logged in as Wasim Boughattas (Log out)

COMP-474-2214-UU

Academic Integrity

Academic Assessment Tool

English (en)

Deutsch (de)

English (en)

Español - Internacional (es)

Français (Canada) (fr_ca)

Français (fr)

Italiano (it)

العربية (ar)