rebase

```
## why rebase?
#
                     master
# ---o---x
# \ / /
# A---B---x---C topic
(topic)
$ git commit
$ git commit
$ git merge master
$ git commit
(master)
$ git merge topic
# merge commits do not add value
# difficult to read history
(topic)
$ git rebase master
                 master
# ---0---0
# \ A---B---C A'---B'---C' topic
```

```
## rebase -i
# Commit often, perfect later.
#
               master
# ---0---0
#
                 A---B---C---D topic
#
(topic)
$ git rebase -i master|head~4
pick A
pick B
pick C
pick D
# Commands:
# p, pick = use commit
# r, reword = use commit, but edit the commit message
# e, edit = use commit, but stop for amending
# s, squash = use commit, but meld into previous
commit
# f, fixup = like "squash", but discard this commit's
log message
# x, exec = run command (the rest of the line) using
shell
# d, drop = remove commit
```

```
# scenario 1: edit, pick, drop
edit A
pick B
drop C
drop D
stopped at A...
(some changes...)
$ git add .
$ git rebase --continue
#
                 master
   ---0---0
#
                |\
| A---B---C---D
\
A'--B' topic
#
#
#
#
# scenario 2: reorder commits
pick A
pick C
pick B
pick D
#
                 master
# ---0---0
                |\
| A---B---C---D
\
A'--C'--B'--D' topic
#
#
#
```

```
# scenario 3: pick, fixup, reorder, drop
pick A
fixup C
pick B
#edit D (dropping D by commenting)
# results in
AC (commits A+C)
B (commit B)
#
              master
#
   ---0---0
#
              AC'--B' topic
#
#
#
```

push after rebase

```
(topic)
$ git push
$ git fetch
$ git rebase master
#
             master
# ---0---0
       #
         A---B topic{-1}
#
               origin/topic
#
$ git push topic
rejected (non-fast-forward)
do a pull/merge first
$ git push -f
#
             master
   ---0---0
             A'---B' topic origin/topic
         A---B
#
```

```
# golden rule of rebase
# I normally don't rebase a branch,
# but when I do, I do master.
     - The Most Interesting Rebaser in the World
       #yolo
#
# don't rebase public branches
      last hotfix
#
# ---0---0
#
        A---B master (me, others)
# I rebase master
(master)
$ git rebase hotfix
$ git push -f
              hotfix origin/master
#
# ---o---o---A'---B' master (me)
        A---B master (others)
```

```
# Others merge origin/master
(master)
$ git merge origin/master
$ git push
              hotfix
#
# ---o---o---A'---B'
#
     \ origin/master A---B-----x master (me, others)
# Merge is better compared to rebase
# I merge master
(master)
$ git merge hotfix
$ git push
              hotfix
#
# ---0---0
        A---B---x master (me, others)
#
                  origin/master
#
# Others can fast-forward master now
```

```
## rebase -r
```

```
3019cac - Tue 28-May-2019 23:05 (3 weeks ago)
         Merge branch 'jwt' into next
    | * 9261fc7 - Tue 28-May-2019 23:03 (3 weeks ago)
#
    | | jwt: Use 'commonName' from 'sub' or 'iss'
        a5d4754 - Thu 13-Jun-2019 21:04 (2 days ago)
   *
           Merge branch 'gitconfig' into next
   | * | 0bc00d0 - Thu 13-Jun-2019 21:03 (2 days ago)
    * | 5b1d6be - Sun 19-May-2019 12:34 (4 weeks ago)
#
   \\ Merge branch 'scite' into next
   * b4056ac - Sun 19-May-2019 12:19 (4 weeks ago)
#
      Merge branch 'next'
(next)
$ git rebase -ir @~2
label onto
# Branch gitconfig
reset b4056ac # Merge branch 'next'
pick 0bc00d0 gitconfig: Use pull.rebase 'merges'
label gitconfig
# Branch jwt
reset b4056ac # Merge branch 'next'
pick 9261fc7 jwt: Use 'commonName' from 'sub' or 'iss'
label jwt
reset onto
merge -C a5d4754 gitconfig # Merge branch 'gitconfig' into next
merge -C 3019cac jwt # Merge branch 'jwt' into next
```