19

20

19 Using the flash on the camera, you can clearly see that I am mostly cutting air. The counterweight is on the back of the faceplate keeping it well out of the way of my gouge

20 I found the wood was tearing out and pushing the bark off on the trailing edges of the 'wings', so superglue came to the rescue

21 Ensure that you can move the gouge smoothly from the start to the end of the cut, as picking a cut up is more difficult when you are turning so much air

21

22

22 As the wings get thinner, they need more support. Cut a small cork faceplate into thirds and screw them on the back of the faceplate. This will enable you to continue cutting with the grain to the tips. Never press on regardless; if you can modify your jigs part way through the job to make it easier or safer it is usually well worthwhile

23 You can power-sand initially (I used my favourite angle drill) work through to 400 grit. Areas that can't be reached by power sanding have to be done by hand, rolling the abrasive into a suitable shape. In any case sand with the grain by hand before changing grits. Use a strong lamp to check for sanding marks before moving on to finer abrasives. Alternatively, wander outside into daylight

23

24

24 For an organic feel, use a coat of sanding sealer on the turned surfaces, and cut back with 600 grit. You can leave your piece 'naked' at this stage. My piece isn't really a bowl, or even intended to hold anything. Rather it's meant to be a conversational piece, so to me it needed a little something extra

25 It just seemed right to wrap the finished piece with the ivy removed at the start, though it needed a bit of encouragement with superglue to stay in place

26 & 27 The final piece looked like this

25

26

27

WT_291_61_65_HOLLY_CROTCH_BOWL_NEW.indd 65 03/03/2016 15:02