

Cloudflare Pages — Setup Guide

Connect `rmccaskie/galinggear` to Cloudflare Pages and point `galinggear.com` and `galinggear.ph` at it.

1. Create a Pages project

1. Log in to the [Cloudflare dashboard](#).
2. In the left sidebar, choose **Workers & Pages** → **Create application** → **Pages**.
3. Select **Connect to Git**.
4. Authorise Cloudflare to access your GitHub account if prompted.
5. Choose the repository **rmccaskie/galinggear**.
6. Click **Begin setup**.

2. Build settings

Setting	Value
Framework preset	Astro
Build command	<code>npm run build</code>
Build output directory	<code>dist</code>
Root directory	(leave blank)
Node.js version	20 (set under Environment variables or in <code>.nvmrc</code>)

3. Environment variables

Add these in **Settings** → **Environment variables** for the **Production** environment (and optionally **Preview** if you want the subscribe form to work in preview deploys):

Variable	Where to find the value
<code>SUPABASE_URL</code>	Supabase project → Settings → API → Project URL
<code>SUPABASE_ANON_KEY</code>	Supabase project → Settings → API → anon public key

Note: These variables are server-only (no `PUBLIC_` prefix) because the subscribe endpoint is a server-side API route. The anon key is safe for server use with RLS: it grants INSERT-only access to the `subscribers` table.

4. Deploy

Click **Save and Deploy**. Cloudflare will clone the repo, run `npm run build`, and publish `dist/`.

The first deploy URL will be something like `galingear.pages.dev`.

5. Custom domains

galinggear.com

1. In the Pages project, go to **Custom domains** → **Set up a custom domain**.
2. Enter `galinggear.com` and confirm.
3. Cloudflare will detect that the domain is already on your account and add the CNAME automatically.
4. Repeat for `www.galinggear.com` if you want the `www` subdomain to also resolve.

galinggear.ph

1. Add `galinggear.ph` the same way.
2. Cloudflare will add the CNAME `galinggear.ph` → `galinggear.pages.dev` automatically.

Both domains should be active within a few minutes. SSL certificates are provisioned automatically.

6. Hybrid mode — why the adapter is required

The site uses `output: 'static'` with one server-rendered route: `src/pages/api/subscribe.ts` (opt-out with `export const prerender = false`). The `@astrojs/cloudflare` adapter converts that route into a Cloudflare Worker function. Without the adapter, the API route will not work in production.

The adapter is already configured in `astro.config.mjs` — no changes needed.

7. Branches and preview deploys

By default, Cloudflare Pages builds every branch push and creates a preview URL. Production builds come from `main`. No additional configuration is needed.

8. Troubleshooting

Problem	Fix
Build fails with “Cannot find module”	Check Node.js version is set to 20
Subscribe form returns 500	Verify <code>SUPABASE_URL</code> and <code>SUPABASE_ANON_KEY</code> are set in environment variables
Custom domain shows “Invalid SSL”	Wait up to 24 hours for DNS propagation; Cloudflare usually resolves this automatically
<code>galingear.ph</code> not resolving	<code>.ph</code> domains may need additional nameserver verification; contact your registrar if the domain was recently transferred