

Algorithms Portfolio

Curated Algorithmic Solutions with Correctness and Complexity Analysis

Ryan McMillan, MCompSci (cand.)

Master of Computer Science — University of New England

C++ Primary • Python Secondary

January 12, 2026

Contents

1	Introduction	2
2	Arrays & Hashing	2
2.1	Demo 0000: Triangular Number (Pipeline Test)	2

1 Introduction

This document is a curated portfolio of algorithmic solutions. Each selected problem includes:

- a brief problem summary,
- the key idea,
- an algorithm outline,
- a correctness sketch,
- time and space complexity,
- a reference C++ implementation.

The focus is on clarity, correctness, and reasoning.

2 Arrays & Hashing

2.1 Demo 0000: Triangular Number (Pipeline Test)

Problem. Given an integer $n \geq 0$, compute

$$T(n) = \sum_{i=1}^n i.$$

Return $T(n)$.

Key idea. Use the closed-form identity

$$T(n) = \frac{n(n+1)}{2}.$$

This avoids iteration and directly demonstrates asymptotic reasoning.

Algorithm. Compute $\frac{n(n+1)}{2}$ using integer arithmetic.

Correctness sketch. We use the classical identity:

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}.$$

Therefore the algorithm returns exactly $T(n)$ for all $n \geq 0$.

Complexity. Time: $O(1)$, Space: $O(1)$. For comparison, the iterative approach

$$\sum_{i=1}^n i$$

runs in $O(n)$ time and $O(1)$ space. As $n \rightarrow \infty$, the closed-form approach dominates asymptotically.

```
#include <bits/stdc++.h>
using namespace std;

/*
  Demo problem for the portfolio PDF pipeline.

  Task: Given  $n \geq 0$ , compute  $\sum_{i=1..n} i = n(n+1)/2$ .

  Purpose: Exercise code inclusion and asymptotic discussion.
*/

long long triangular_number(long long n) {
    //  $O(1)$  time,  $O(1)$  space
    return n * (n + 1) / 2;
}

int main() {
    ios::sync_with_stdio(false);
    cin.tie(nullptr);

    long long n;
    if (!(cin >> n)) return 0;
    cout << triangular_number(n) << "\n";
    return 0;
}
```