MYSQL FOUNDATIONS · QUICK SETUP

Get Ready in Half an Hour

Before the first session: install **MySQL 9.7 LTS**, set a strong root password, make a course folder, run the check. You need a laptop you can install software on, 1.5 GB free, and a plain-text editor (VS Code). Ask for 9.7 by name ("latest" is a 26.x innovation release, Ubuntu's own package is 8.0, XAMPP is MariaDB) and stop any other MySQL/MariaDB server first. Stuck? The full **Setup Guide** covers every path and problem.

1 · INSTALL MYSQL 9.7 (PICK ONE)

WINDOWS

dev.mysql.com/downloads/mysql ▸ 9.7.x LTS ▸ Windows **MSI Installer**. Run it (Typical); in **MySQL Configurator** choose Development, port 3306, a **strong root password**, Windows Service. Add `C:\Program Files\MySQL\MySQL Server 9.7\bin` to your user **Path** and open a new PowerShell.

MACOS (HOMEBREW)

```
brew install mysql@9.7
echo 'export PATH="$(brew --prefix)/opt/mysql@9.7/bin:$PATH"' >> ~/.zshrc
source ~/.zshrc
brew services start mysql@9.7
mysql_secure_installation
```

The last line sets the root password (answer **y**). No Homebrew? Use the **DMG** for your processor.

UBUNTU / DEBIAN (FEDORA, RHEL, ROCKY, ALMA: MYSQL'S YUM REPOSITORY, SEE THE FULL GUIDE)

Get `mysql-apt-config_…_all.deb` from **dev.mysql.com/downloads/repo/apt**, choose **9.7 LTS** in its menu, set the root password when asked.

```
sudo dpkg -i ~/Downloads/mysql-apt-config_*_all.deb
sudo apt update
sudo apt install mysql-server
```

DOCKER (ANY SYSTEM)

```
docker run --name mysql97 -e MYSQL_ROOT_PASSWORD='choose-a-strong-password' \
  -p 3306:3306 -v mysql97-data:/var/lib/mysql -d mysql:9.7
docker exec -it mysql97 mysql -u root -p
```

PowerShell: one line. After a reboot: `docker start mysql97`.

2 · LOG IN AND CHECK THE VERSION

```
mysql -u root -p
SELECT VERSION();
```

The password does not show as you type. **9.7.x** is right (8.4.x is fine); 8.0, 26.x or MariaDB means a different server than you meant. Leave with `exit`. Never "fix" a login with `mysql_native_password`: MySQL 9 removed it.

3 · MAKE THE COURSE FOLDER

```
mkdir -p ~/mysql-course && cd ~/mysql-course          # macOS / Linux
mkdir $HOME\mysql-course; cd $HOME\mysql-course       # Windows PowerShell
```

Put the three check files from your instructor in `labs/module-01/l1_0-orientation/` inside `mysql-course`. Always start the mysql client from inside this folder. Do **not** load `bookstore.sql` yet: you build the bookstore yourself in Lesson 2.1.

4 · RUN THE CHECK

SYSTEM	FROM INSIDE `MYSQL-COURSE`, RUN
macOS, Linux, WSL	`bash labs/module-01/l1_0-orientation/check_environment.sh`
Windows	`powershell -ExecutionPolicy Bypass -File labs\module-01\l1_0-orientation\check_environment.ps1`
Docker	`docker exec -i mysql97 sh -c 'exec mysql -uroot -p"$MYSQL_ROOT_PASSWORD" --table' < labs/module-01/l1_0-orientation/check_environment.sql`

> ✅ **DONE WHEN THE LAST TABLE SAYS READY FOR MYSQL FOUNDATIONS**
>
> Send that table to your instructor. **READY WITH NOTES** (8.4 or MariaDB) is fine. **NOT READY**? The line above it says what failed: see the full guide's problems table, or bring the output to Session 1's install clinic.

Quick Setup · v1.0 · © 2026 Ray de la Paz