






- 1. 4 layer PCB with standard stack up for 1.6mm total thickness.
- 3. Minimum clearance is 6 mil.
- 4. Minimum trace width is 8 mil.
- 5. Minimum hole size is 22mil finished to 12 mil.
- 6. Vcuts are drawn in mechanical layer 2.
- 7. Pb free HAL finish.
















- 1. 4 layer PCB with standard stack up for 1.6mm total thickness.
- 3. Minimum clearance is 6 mil.
- 4. Minimum trace width is 8 mil.
- 5. Minimum hole size is 22mil finished to 12 mil.
- 6. Vcuts are drawn in mechanical layer 2.
- 7. Pb free HAL finish.
















- 1. 4 layer PCB with standard stack up for 1.6mm total thickness.
- 3. Minimum clearance is 6 mil.
- 4. Minimum trace width is 8 mil.
- 5. Minimum hole size is 22mil finished to 12 mil.
- 6. Vcuts are drawn in mechanical layer 2.
- 7. Pb free HAL finish.











- 1. 4 layer PCB with standard stack up for 1.6mm total thickness.
- 3. Minimum clearance is 6 mil.
- 4. Minimum trace width is 8 mil.
- 5. Minimum hole size is 22mil finished to 12 mil.
- 6. Vcuts are drawn in mechanical layer 2.
- 7. Pb free HAL finish.