

# Technical Specification:

|                           |                                           |                                                                                     |
|---------------------------|-------------------------------------------|-------------------------------------------------------------------------------------|
| FW-mid                    |                                           |  |
| Mechanical Specifications | Dimension(L*W*H)                          | 680*550*437mm                                                                       |
|                           | Weight                                    | 68kg                                                                                |
|                           | Drive form                                | 4 Wheels Swerve Steering and Motor Drive                                            |
|                           | Structure material                        | Aluminum Alloy                                                                      |
|                           | Ground clearance                          | 90mm                                                                                |
|                           | Wheel base                                | 400mm                                                                               |
|                           | Wheel track                               | 420mm                                                                               |
|                           | Tire diameter                             | 240mm                                                                               |
| Basic Information         | Motor power                               | 350W*4 Servo Motor                                                                  |
|                           | Battery power                             | Lithium battery 48V/20AH, with BMS                                                  |
|                           | Charging time                             | 3-4h                                                                                |
|                           | Charging mode                             | 48V/5A manually charger                                                             |
|                           | Battery output power for external devices | 24V-10A/12V-15A                                                                     |
|                           | Braking                                   | Motor Braking                                                                       |
|                           | Parking                                   | Motor Parking                                                                       |
| Security Setting          | Emergency stop                            | √                                                                                   |
|                           | Instruction verification                  | √                                                                                   |
|                           | Heartbeat protection                      | √                                                                                   |
|                           | Current protection                        | √                                                                                   |
|                           | Temperature protection                    | √                                                                                   |
| VCU Information           | CPU basic frequency                       | 168MHz                                                                              |
|                           | Interface                                 | CAN Interface                                                                       |
|                           | Communication module                      | CAN 2.0B                                                                            |
|                           | Kinematic analysis                        | √                                                                                   |
|                           | Remote control distance                   | 100m                                                                                |
| Performance               | Payload                                   | 50kg                                                                                |
|                           | Max speed                                 | 0-5.4km/h                                                                           |
|                           | Mileage                                   | 40km                                                                                |
|                           | Turning radius                            | 0m                                                                                  |
|                           | Wading depth                              | 100mm                                                                               |
|                           | Climbing capacity                         | 15° with load                                                                       |
|                           | Obstacle surmounting height               | 50mm(full load)                                                                     |
|                           | Span width                                | 120mm                                                                               |
|                           | IP Rating                                 | IP33                                                                                |
|                           | Working temperature                       | -20°C~50°C                                                                          |