

Static website with Microsoft Entra ID authentication on Azure Static Web Apps

Two complementary patterns for hosting a public-facing site whose protected pages require sign-in: a Free-plan pattern with per-user invitations, and a Standard-plan pattern with group-based access via a custom app registration and a role-assignment function.

Audience: CTO, Architecture, Security Operations (SecOps).

Status: Reference / Demo — not yet production-deployed with real data.

Document version: 0.1 — 2026-05-15

Source repository: github.com/rmjoia/static-entra-id-auth-example

Contents

1. Executive summary
2. System context
3. Free-tier architecture
4. Standard-tier architecture
5. Authentication and authorization flows
6. Security model & trust boundaries
7. Conditional Access integration
8. Deployment and CI/CD
9. Hardening roadmap
10. Cost summary
11. Operations
12. Plan limits
13. References

1. Executive summary

This document describes a reference implementation for hosting a static website on **Azure Static Web Apps** (SWA) where some pages are public and others require authenticated access through **Microsoft Entra ID**. The pattern is intended for use cases such as board reports, investor updates, partner-only documents, or any site that needs a public marketing surface paired with a private members-only area, without operating a traditional web server.

Two parallel implementations are provided in the same source repository:

- **Free plan** Uses the platform's pre-configured Microsoft Entra ID provider. Access to protected pages is granted via per-user invitation links. Suitable for fixed audiences of up to 25 users. No app registration is required; the authentication provider is multi-tenant by default.
- **Standard plan** Uses a custom Microsoft Entra ID app registration scoped to a specific tenant, with role assignment driven by membership in an Entra ID security group. Authorization is computed by a serverless function at sign-in. Suitable for audiences that fluctuate, exceed 25 members, or are managed by existing identity-governance processes.

Both implementations share a common front-end (Bootstrap 5 + Chart.js, Microsoft-branded "Contoso annual review" demo). They differ only in `staticwebapp.config.json` and, for the Standard variant, the presence of a `GetRoles` Azure Function under the `/api` path.

The reference is deployed via GitHub Actions workflows generated by the Azure portal. Each Static Web App instance owns its own workflow file; path-scoped triggers ensure that pushes affecting only one tier do not redeploy the other.

Headline recommendations

1. For demo and small fixed audiences, deploy as Free-tier. No additional security work is required for the platform itself.
2. For audiences managed through Entra groups, deploy as Standard-tier. Combined with Conditional Access (MFA, compliant device) on the underlying app registration, this is suitable for sensitive but not regulated content.
3. Before exposing real confidential data: replace the client secret with a Key Vault-stored certificate fetched by the SWA's managed identity, and enable Conditional Access policies on the app registration covering MFA and (where applicable) device compliance.
4. For regulated, highly sensitive, or partner-only content: pair Standard-tier with either a private endpoint (intranet-only) or Azure Front Door Premium with WAF (public-internet but filtered). Both options are documented in this paper.

2. System context

Figure 1 shows the high-level interactions among the principal actors and systems. The same end user can be served by either tier; the differences are in which Azure subscription hosts the website, which Entra-ID configuration is used, and how access is granted.




Figure 1. System context: two Static Web Apps fed from one GitHub repo, each integrating with a different Entra ID configuration.

2.1 Principal actors

Actor	Role	Notes
End user	Visitor / member	Holds a Microsoft account (work, school, or personal).
Site administrator	Grants access	For Free: issues invitations from the portal. For Standard: manages Entra group membership.
Repository maintainer	Authors content	Pushes to <code>main</code> . CI/CD redeploys automatically.
Entra tenant administrator	Provides identity infrastructure	Owens the app registration (Standard only), security group, Conditional Access policies.

2.2 Principal components

Component	Free tier	Standard tier
Azure Static Web App	Free plan SKU	Standard plan SKU
Authentication provider	Pre-configured (multi-tenant)	Custom Entra app registration (single-tenant)

Authorization mechanism	Per-user invitation, max 25 users	Function-driven, sources roles from group claims
API surface	None	Single function: <code>POST /api/GetRoles</code>
Configuration file	<code>free-tier/src/staticwebapp.config.json</code>	<code>standard-tier/src/staticwebapp.config.json</code>
CI/CD workflow	<code>.github/workflows/azure-static-web-apps-black-glacier-*.yaml</code> , path-scoped to <code>free-tier/**</code>	<code>.github/workflows/azure-static-web-apps-green-sea-*.yaml</code> , path-scoped to <code>standard-tier/**</code>

3. Free-tier architecture

The Free-tier implementation is the minimum-configuration variant. It relies entirely on platform-provided defaults for both authentication and authorization, and requires no app registration in Entra ID.




Figure 2. Free-tier component view: a single SWA with the pre-configured Entra provider and invitation-based authorization.

3.1 Trust posture

- **Authentication.** The pre-configured provider is multi-tenant. Any holder of a Microsoft account — personal or work, in any tenant — can complete the sign-in handshake. This means authentication is not, by itself, an access barrier.
- **Authorization.** Protected routes (`/report.html` , `/strategy.html`) carry an `allowedRoles:` `[ "boardmember" ]` rule. The custom role `boardmember` is granted only by invitation, generated from the

SWA's Role management blade.

- **Capacity.** The invitation system is capped at **25 users per app** on both Free and Standard plans. To exceed this, the Standard-tier pattern is required.
- **Revocation.** Removing a user from Role management invalidates their permissions on the next sign-in; the SWA's session cookie continues to honour previously assigned roles until expiry.

3.2 What this pattern is good for

- Fixed, small audiences (board of directors, investor short-list, partner pilot).
- Reference architectures and demonstrations.
- Content whose value does not justify the operational overhead of an app registration.

3.3 What this pattern is not suitable for

- Audiences larger than 25 members.
- Audiences whose composition changes frequently (joiners/leavers, conditional access requirements).
- Use cases requiring restriction to a specific Entra tenant at the sign-in level.
- Use cases requiring an SLA on uptime.

4. Standard-tier architecture

The Standard-tier implementation replaces the pre-configured provider with a custom Entra ID app registration owned by the organisation. Authorization is decoupled from the invitation system and instead derived from Entra group claims, evaluated by a small serverless function deployed alongside the static site.




Figure 3. Standard-tier component view. The dashed component is added during the hardening phase (see §9); it is not part of the minimum deployment.

4.1 Components and ownership

Component	Owner	Configuration location
App registration	Entra tenant admin	Entra portal — App registrations
Security group	Group owner	Entra portal — Groups
SWA configuration	Repository maintainer	standard-tier/src/staticwebapp.config.json

Role-assignment logic	Repository maintainer	<code>standard-tier/api/src/functions/GetRoles.js</code>
Client secret / cert	Entra tenant admin / Key Vault admin	SWA application settings (secret) or Key Vault (cert)
Group ID	Repository maintainer (configures), Group owner (controls members)	SWA application setting <code>BOARD_GROUP_ID</code>
Conditional Access policies	Entra tenant admin / SecOps	Entra portal — Security — Conditional Access

4.2 Required app registration settings

- **Supported account types:** Single tenant. Restricts sign-in to the org's own users.
- **Redirect URI:** Web platform — `https://<swa-host>.azurestaticapps.net/.auth/login/aad/callback`.
- **Implicit grant and hybrid flows: ID tokens enabled.** Without this, sign-in fails with `AADSTS700054: response_type 'id_token' is not enabled for the application`.
- **Optional claims (ID token):** `groups` claim added. Type: Security groups (or All groups, depending on operational preference).
- **API permissions:** default `Microsoft Graph – User.Read (delegated)` is sufficient.
- **Credentials:** client secret in *Phase 1*; certificate stored in Key Vault in *Phase 2* hardening.

4.3 The GetRoles function

The function is Node.js, Azure Functions v4 programming model. It receives the platform's POST at every sign-in, with the user's identity and claims in the body. It is internal-only by virtue of being declared as `rolesSource`; the platform automatically blocks external HTTP requests to it.

```
// standard-tier/api/src/functions/GetRoles.js (excerpt)
app.http("GetRoles", {
  methods: ["POST"],
  authLevel: "anonymous", // platform-only invocation
  handler: async (request, context) => {
    const body = await request.json();
    const groupIds = new Set(
      (body.claims || []).
        .filter(c => c.typ === "groups")
        .map(c => c.val)
    );
    const boardGroupId = process.env.BOARD_GROUP_ID;
    const roles = [];
    if (boardGroupId && groupIds.has(boardGroupId)) {
      roles.push("boardmember");
    }
    return { status: 200, jsonBody: { roles } };
  }
});
```

Group claim overage. If a user belongs to more than ~150 Entra groups, Microsoft omits the `groups` claim from the token and emits `_claim_names` / `_claim_sources` pointing to Microsoft Graph instead. The reference implementation does not include the Graph fallback. For small teams this is irrelevant; for large organisations, see the Microsoft Learn "Assign roles via Graph" tutorial (§13).

5. Authentication and authorization flows

The Standard-tier sign-in is the more interesting case. The Free-tier flow follows the same shape but with role determination via the invitation system rather than the function.




Figure 4. End-to-end sign-in and authorization, Standard tier. The Conditional Access step is optional but recommended (see §7).

5.1 Source of truth for runtime authorization

The Static Web App platform's `/auth/me` endpoint returns the active `clientPrincipal`, including the `userRoles` applied to the current session. This is the authoritative value used by the platform for route evaluation. The Role management blade and the function's return value *determine* what is written to a new cookie; once a cookie is issued, its claims hold until the cookie expires or is invalidated.

Operational consequence: a change in group membership (Standard) or invitation roles (Free) does not affect existing sessions. Users must sign out and back in to receive an updated role set. This is documented in Operations (§11).

5.2 Edge propagation

Role changes propagate across the Static Web Apps edge network with a typical latency of several minutes (documented by Microsoft as "a few minutes"). During the propagation window, different geographically distributed edge nodes may return different `userRoles` for the same user on parallel requests. The

behaviour stabilises once propagation completes and is irreversible (the new value, once observed, persists).

6. Security model & trust boundaries

The diagram below shows the trust boundaries crossed by various data and credentials in the Standard-tier deployment. Each box represents a security boundary controlled by a distinct authentication / authorisation mechanism.




Figure 5. Trust boundaries. To reach the protected content (green), an attacker would need to cross at least two independent boundaries.

6.1 What is publicly visible

- The `staticwebapp.config.json` file and the `GetRoles` function source code — both reside in a public GitHub repository.
- The tenant ID, embedded in the `openIdIssuer` URL within the config file. Microsoft treats tenant IDs as discoverable, not secret.
- The SWA's public hostname.
- The role name(s) defined in `allowedRoles`.

Important note: SWA does not serve `staticwebapp.config.json` as a static file. Requests to `https://<site>/staticwebapp.config.json` return 404. The file is read at build/deploy time and consumed by the platform; it is not exposed at runtime.

6.2 What is not visible

Artefact	Where it lives	Required to read
----------	----------------	------------------

Client secret	SWA application settings	Contributor on SWA or higher
Certificate private key (after hardening)	Azure Key Vault	Key Vault access policy / RBAC role granting Get on certificates and secrets
Group Object ID (<code>BOARD_GROUP_ID</code>)	SWA application settings	Same as client secret
Group membership	Microsoft Entra ID	Group reader or owner; member-of for one's own account only

6.3 Threat model summary

Threat	Likelihood	Impact	Mitigation
Direct request to <code>/api/GetRoles</code> with fabricated claims	Low	Would grant arbitrary role	Platform blocks external HTTP to functions declared as <code>rolesSource</code> ; internal-only.
Brute-force guessing of <code>BOARD_GROUP_ID</code>	Negligible	Would only grant access to the configured group, not arbitrary access	128-bit GUID; computationally infeasible.
Client secret leak (screenshot, log, paste)	Moderate (humans)	App impersonation; cannot grant <code>boardmember</code> to self directly	Phase 2 hardening (cert in Key Vault) substantially reduces exposure surface.
Phishing of a group member's account	Moderate	Attacker can sign in as the member; gains <code>boardmember</code> role	Conditional Access — MFA, compliant-device requirements (§7).
Compromise of group owner	Low (with proper Entra hygiene)	Attacker can add their own account to the group	Privileged Identity Management (PIM) just-in-time for group ownership; audit alerts on membership changes.
Compromise of Entra tenant admin	Low (with proper Entra hygiene)	Total compromise of identity surface	Out of scope for this design; standard tenant-hygiene practices.
Public-internet probing / DDoS on sign-in endpoint	Moderate (continuous)	Resource consumption, no data exposure	Phase 3 hardening — AFD with WAF (§9) or IP restrictions / private endpoint.

7. Conditional Access integration

The Static Web App and Conditional Access (CA) are decoupled. CA is enforced by Entra ID at sign-in, before any token reaches the SWA. The application is unaware of CA policies; they are configured on the underlying app registration and evaluated by the identity provider.




Figure 6. Conditional Access overlays the sign-in step. Failed evaluation never reaches the SWA.

7.1 Prerequisite licensing

- **Microsoft Entra ID P1** — required for Conditional Access. Included with Microsoft 365 Business Premium, E3, E5, and a number of other bundles. Standalone \$6/user/month at time of writing.
- **Microsoft Intune** — required only for the "compliant device" condition. Also included with E3 / E5 / Business Premium.

7.2 Recommended baseline policy

Minimum viable policy that materially raises the security floor:

Name	Require MFA for board report site
Users — Include	security-group-board-members
Users — Exclude	At least one break-glass admin account
Target resources	The SWA's Entra app registration
Grant	Require multi-factor authentication
Enable	Report-only initially, then On after verification

7.3 Stronger policies (incremental)

Add-on	What it does	Prerequisite
--------	--------------	--------------

Require compliant device	Sign-in fails unless device is Intune-enrolled and meets the compliance baseline (encryption, OS version, anti-malware, etc.)	Intune licensing + enrolled devices + compliance policies defined
Require app protection policy	Mobile-specific. Requires Intune App Protection enrolment on the user's device	Intune + Microsoft 365 mobile apps
Block legacy authentication	Disables basic-auth / older protocols that bypass MFA	None (recommended unconditionally)
Trusted location bypass	Skip MFA when on the corporate network; require it elsewhere	Named Locations defined with corporate IP ranges
Sign-in risk $\geq$ medium → require password change	Triggers password reset on suspicious sign-ins (impossible travel, anonymous IP, etc.)	Entra ID P2 for Identity Protection

7.4 What changes in the SWA when CA is added?

Nothing. The website's configuration, code, and behaviour are unchanged. A sign-in that fails CA never produces a token; the SWA's authentication endpoint simply never sees a success and the browser remains on a Microsoft-hosted block page. The website's `/403.html` is shown only when sign-in succeeds but the resulting roles are insufficient — this remains the same after CA is introduced.

8. Deployment and CI/CD

Both Static Web Apps are deployed from a single GitHub repository via the platform-generated GitHub Actions workflows. Each SWA owns its own workflow file, secret, and deployment token. Workflow triggers are path-scoped so that changes to one tier do not redeploy the other.




Figure 7. CI/CD topology. Path filters mean a README-only change triggers neither pipeline; a free-tier asset change deploys only to the Free SWA; a standard-tier code or function change deploys only to the Standard SWA.

8.1 Workflow generation

Each workflow file is generated by the Azure portal at SWA creation time. The portal injects a deployment token as a GitHub repository secret named `AZURE_STATIC_WEB_APPS_API_TOKEN_<NAME>`. The workflow uses `Azure/static-web-apps-deploy@v1` to upload the build output. Path filters were added manually after the portal-generated baseline.

8.2 Operational characteristics

- **Build time:** 1–3 minutes for an unchanged-dependencies deployment. The static assets are tiny and the API folder has no native dependencies.
- **Deployment model:** blue-green via SWA's staging environments. Pull requests automatically create a preview environment per the workflow's `close_pull_request_job`; merging to `main` rolls the preview to production.
- **Rollback:** revert the offending commit on `main`. The next push redeploys the previous content. SWA does not maintain historical builds.
- **Branch protection:** not enforced in the reference; production deployments should require a pull-request review and a passing status check before merge to `main`.

9. Hardening roadmap

The reference implementation is a starting point. The phases below describe a progression of incremental security improvements, each with a clear marginal cost and benefit. Phase 1 is the current state; Phases 2–5 are independent — you can adopt any subset.

Phase 1 Reference deployment (as-is)

Standard-tier SWA, custom Entra app with client secret, GetRoles function, group-based access. No Conditional Access. Public DNS resolves the SWA URL.

- Authentication: custom Entra ID, single-tenant.
- Credential: client secret in SWA application settings.
- Authorization: `boardmember` role assigned by GetRoles based on `BOARD_GROUP_ID`.
- Network: public internet; basic platform DDoS protection only.

Suitable for: reference / demo with non-sensitive content.

Phase 2 Replace client secret with Key Vault certificate

Eliminates the plaintext credential from SWA application settings. Cert is generated and held inside Azure Key Vault; the SWA accesses it via a system-assigned managed identity.

- Generate certificate in Key Vault. Private key never leaves the vault except into SWA runtime memory.
- Upload public key (.cer) to the Entra app registration.
- Grant the SWA's managed identity Get/List on certificates and secrets in Key Vault.
- Replace `clientSecretSettingName` with `clientSecretCertificateKeyVaultReference` in `staticwebapp.config.json`.
- Remove the `AZURE_CLIENT_SECRET` application setting.

Effort: 30–60 minutes. Recurring cost: negligible (Key Vault operations are below 100 per month).

Suitable for: production with any meaningful confidentiality.

Phase 3 Conditional Access policies on the app registration

Require MFA at minimum. Optionally require a compliant device. Optionally restrict to trusted locations.

- Create CA policy targeting the SWA's app registration and the board-members group.
- Grant: Require MFA. Optionally + compliant device.
- Roll out in Report-only mode for several days; verify in Insights; then switch to On.

Effort: 1–3 days including verification. Recurring cost: Entra ID P1 per user (typically already owned). Intune per user if device compliance is enforced. Suitable for: any deployment with internal organisational users.

Phase 4 Network restrictions

Choose one (or combine):

- **IP restrictions** (Standard plan, free) — allow-list up to 25 IP ranges. Blocks all other traffic at the platform.
- **Private endpoint** (Standard plan, free, but requires a VNet) — SWA URL only resolves from within the connected VNet. Pair with VPN or ExpressRoute for remote users.
- **Azure Front Door Premium with WAF** — keeps public DNS but filters traffic against the OWASP Core Rule Set, applies rate limiting, geo-blocking, bot protection. Material monthly cost (see §10).

Effort: half a day to several days depending on option. Recurring cost: zero (IP restrictions / private endpoint) to several hundred dollars per month (AFD Premium). Suitable for: regulated content or content with substantial value.

Phase 5 Operational maturity

Monitoring, alerting, repo hygiene, and incident-response readiness.

- Application Insights integration for sign-in telemetry and function logs.
- Alerts on anomalous sign-in volume, function errors, or role assignment patterns.
- GitHub: branch protection on `main`, secret scanning + push protection, periodic rotation of SWA deployment tokens.
- Entra: enable group-membership audit alerts via Azure Monitor; consider Privileged Identity Management (PIM) for group ownership.

Effort: 1–2 days initial, ongoing low effort. Recurring cost: negligible. Suitable for: any deployment expected to last longer than 6 months.

10. Cost summary

Prices below are indicative as of 2026 and should be verified against the relevant Microsoft pricing page before commitment.

Component	Phase 1	Phase 2	Phase 3	Phase 4 (PE)	Phase 4 (AFD)
Azure Static Web App (Free)	\$0	—	—	—	—
Azure Static Web App (Standard)	~\$9/site/mo	~\$9	~\$9	~\$9	~\$9
Key Vault operations	—	<\$0.10/mo	<\$0.10/mo	<\$0.10/mo	<\$0.10/mo
Entra ID P1 (per board member)	—	—	~\$6/user/mo *	~\$6/user/mo *	~\$6/user/mo *
Intune (per board member, if compliant-device required)	—	—	~\$8/user/mo *	~\$8/user/mo *	~\$8/user/mo *
Private endpoint	—	—	—	~\$10/mo + data	—
Azure Front Door Premium + WAF	—	—	—	—	~\$330/mo base + requests
Estimated baseline / 10 users	~\$9/mo	~\$9/mo	\$9 + bundle**	~\$20/mo + bundle**	~\$340/mo + bundle**

* Typically included in Microsoft 365 Business Premium, E3, E5 bundles. Many organisations already pay for these for unrelated reasons. ** Bundle: Entra P1 + (optional) Intune, paid per relevant user.

The free-tier site adds zero direct cost; the only operational cost is the time to manage invitations.

11. Operations

11.1 Onboarding a new user

Step	Free tier	Standard tier
Where	Azure portal — SWA — Role management	Entra admin centre — Groups — security-group-board-members
Action	Generate invitation link for their Microsoft account email; send to the user	Add user as group member
User action required?	Yes — click link, sign in, accept	None — takes effect on next sign-in
Time to live	Indefinite (until removed)	Indefinite (until removed)

11.2 Offboarding a user

Step	Free tier	Standard tier
Where	Role management blade	Group membership
Action	Tick the user row → Delete	Remove user from group
Effect on existing session	None until cookie expires	None until cookie expires
Force-revoke active sessions	Not available at SWA level	Entra: Users — revoke sessions — forces re-auth on next request

11.3 Credential rotation (Standard, client-secret pattern)

1. Entra portal — App registrations — your app — Certificates & secrets — New client secret. Generate with a new expiry; copy the Value.
2. SWA — Environment variables — update `AZURE_CLIENT_SECRET` with the new Value.
3. Verify sign-in works (incognito test).
4. Once verified, return to Entra and delete the old client secret entry.

11.4 Credential rotation (Standard, certificate pattern)

1. Key Vault — Certificates — your cert — New version (if auto-rotation is not configured).
2. Download the new .cer from Key Vault.
3. Entra portal — App registrations — Certificates & secrets — Certificates — Upload the new .cer.
4. Verify sign-in works (incognito test). Because `clientSecretCertificateThumbprint` is `"*"`, the runtime auto-picks the latest version.

5. Optionally delete the previous cert version after the verification window.

11.5 Monitoring

- Application Insights connected to the Standard SWA captures GetRoles invocations via `context.Log(...)`. Use this to detect anomalies (unusual user volume, unexpected groupCount values, etc.).
- Entra sign-in logs (Entra portal — Sign-in logs) show all sign-in attempts including CA evaluations, MFA outcomes, and policy hits.
- Configure alerts in Azure Monitor for: function error rate exceeding threshold, sign-in failure rate spikes, unusual geographic sign-in patterns.

11.6 Disaster scenarios

Scenario	Response
Client secret leaked	1. Revoke the secret in Entra immediately. 2. Generate a new one. 3. Update the SWA application setting. 4. Audit sign-in logs for anomalous activity in the leak window.
Tenant admin compromised	Out of scope for this design; follow organisational IR procedures. Rotate all app credentials and review CA policies once contained.
Group owner compromised	Audit group membership immediately; revoke any unauthorised members; rotate group owner; review sign-in logs for the affected window.
SWA misconfigured (e.g., wrong tenant ID in config), no users can sign in	Revert the offending commit on <code>main</code> ; next deploy restores previous state. SWA has no built-in rollback.

12. Plan limits

Source: *Azure Static Web Apps quotas*, Microsoft Learn.

Limit	Free	Standard
Bandwidth included per month	100 GB	100 GB
Overage bandwidth	Not available (app stops serving until reset)	\$0.20 per GB
Apps per subscription	10	100
Preview environments per app	3	10
Total storage (all environments)	500 MB	2 GB
Storage per environment	250 MB	500 MB
File count per app	15,000	15,000
Custom domains per app	2	6
Private endpoint	Not available	1
IP range restrictions	Not available	25
Authorisation via invitations	25 users	25 users
Authorisation via serverless function	Not available	Unlimited
Max request size	30 MB	30 MB
SLA	None	99.95%

Notes:

- The 25-user invitation cap applies to both plans equally. Standard plan only escapes it by switching to the serverless-function authorisation path.
- The Free plan never auto-bills. If 100 GB is exceeded in a calendar month, the app stops serving until the next month.

13. References

Microsoft Learn

- Azure Static Web Apps — Quotas. learn.microsoft.com/en-us/azure/static-web-apps/quotas
- Authenticate and authorize Static Web Apps. learn.microsoft.com/en-us/azure/static-web-apps/authentication-authorization
- Custom authentication in Azure Static Web Apps. learn.microsoft.com/en-us/azure/static-web-apps/authentication-custom
- Configuration (staticwebapp.config.json). learn.microsoft.com/en-us/azure/static-web-apps/configuration
- Tutorial — Assign roles via Microsoft Graph (group-overage scenario). learn.microsoft.com/en-us/azure/static-web-apps/assign-roles-microsoft-graph
- Pricing — Static Web Apps. azure.microsoft.com/en-us/pricing/details/app-service/static/
- Azure Front Door — configure with Static Web Apps. learn.microsoft.com/en-us/azure/static-web-apps/front-door-manual
- Microsoft Entra Conditional Access overview. learn.microsoft.com/en-us/entra/identity/conditional-access/overview
- Microsoft Intune device compliance policies. learn.microsoft.com/en-us/intune/intune-service/protect/device-compliance-get-started

Source repository

github.com/rmjoia/static-entra-id-auth-example — contains both tier implementations, GitHub Actions workflows, and a step-by-step README aimed at non-technical implementers.

Document history

Version	Date	Notes
0.1	2026-05-15	Initial draft for internal architecture review.