
Pentaho Data Integration (PDI) - Kettle - short guide

- I. Creating new transformation
- II. Opening existing template transformations for manual design approach
 - a. Template for requirement 1
 - b. Template for requirement 2
- III. Adding operations (steps) into transformation.
 - a. Transformation
 - Sort Rows
 - Select values
 - Filter rows
 - Modified Java Script Value
 - Join Rows
 - Group By
- IV. Creating edges between operations (hops)


I. Creating new transformation




II. Opening existing template transformations for manual design approach

To open existing template transformation (template1.ktr or template2.ktr) choose File -> Open...

a) Template for requirement 1





b) Template for requirement 2





III. Adding operations (steps) into transformation.


After you open the provided template transformations, in the tab "Design" you may find the complete palette of the operations supported by Kettle. The operations are divided into different groups and they are easily added to an ETL design by dragging them from the palette into the transformation canvas. In the following figures, you may see different operations in the Spoon design palette. The ones that should be used for this round of the case study are marked with orange rectangle and further explained.















a) Transformation operations (steps)



Select values



This Select values step is useful for selecting (projection), renaming, changing data types and configuring the length and precision of the fields on the stream. These operations are organized into different categories:

- Select & Alter Specify the exact order and name in which the fields have to be placed in the output rows
- Remove Specify the fields that have to be removed from the output rows
- Meta-data Change the name, type, length and precision (the meta-data) of one or more fields

∨ ⊢ I	LECT	Г&А	LTER
JL		1 CX 7	

Option	Description	
Step name	Name of the step; this name has to be unique in a single transformation	
Fields	Allows you to rename a field and specify the length and precision	
Get fields to select	Click to insert fields from all input steams to the step	

Filter revue	The Filter rows step allows you to filter rows based on conditions and comparisons. Once this step is connected to a previous step (one or more and receiving input), you can click on the " <field>", "=" and "<value>" areas to construct a condition. Click the Add condition icon to add conditions. Add condition converts the original condition to a sub-condition and adds a new condition. Click a sub-condition to edit it (go down one level into the condition tree).</value></field>	
Option	Description	
Step name	Name of the step; this name has to be unique in a single transformation.	
Send 'true' data to step	The rows for which the condition specified is true are sent to this step	
Send 'false' data to step	The rows for which the condition specified are false are sent to this step	


Click on the <Field> buttons to select from a list of fields from the input stream(s) to build your condition(s).

Click the 'NOT' button in the upper left to negate the condition.

To delete a condition, right-click and select Delete Condition


Click on the <value> button to enter a specific value into your condition(s).

The Condition



For example, you can define a java script function to derive a new value (e.g., derived measure). Function can be parameterized with the input fields of this step.

The derived value (measure) need to be defined as the output field of the step in section "Fields". Provided java script needs to have the definition of the value for the output fields. However, you can define an arbitrary java script to calculate desired value from the input fields and assign it to the output field defined in section "Fields".



Join Rows Join Rows (cartesian product)	The Join rows step allows you to produce combinations (Cartesian product) of all rows in the input streams with additional condition to perform different kinds of joins.	
Option	Description	
Step name	Name of the step; this name has to be unique in a single transformation	
IIMain sten to read from	Specifies the step from which to read most of the data; while the data from other steps are cached or spooled to disk, the data from this step is not.	
The Condition(s)	You can enter a complex condition to limit the number of output row. Note: The fields in the condition must have unique names in each of the streams.	

Group By Group by	This step allows you to calculate values over a defined group of fields. Note: This step requires inputs to be ordered by the group by fields (attributes). Sort Rows operation needs to precede it.		
Option	Description		
Step name	Name of the step; this name has to be unique in a single transformation		
Include all rows?	Enable if you want all rows in the output, not just the aggregation; to differentiate between the two types of rows in the output, a flag is required in the output. You must specify the name of the flag field in that case (the type is boolean).		
Group fields table	Specify the fields over which you want to group. Click Get Fields to add all fields from the input stream(s).		
Aggregates table	Specify the fields that must be aggregated, the method and the name of the resulting new field. Here are the available aggregation methods: Sum Average (Mean) Minimum Maximum Number of values (N) Concatenate strings separated by , (comma) First non-null value Last non-null value First value (including null) Last value (including null) Cumulative sum (all rows option only!) Cumulative average (all rows option only!) Cumulative average (all rows option only!) Concatenate strings separated by <value>: specify the separator in the Value column Number of distinct values The metadata injection values for the aggregation type are (in respective order): SUM, AVERAGE, MIN, MAX, COUNT_ALL, CONCAT_COMMA, FIRST, LAST, FIRST_INCL_NULL, LAST_INCL_NULL, CUM_SUM, CUM_AVG, STD_DEV, CONCAT_STRING, COUNT_DISTINCT</value>		

IV. Creating edges between operations (hops)

- 1) Hover the mouse pointer over the source operation node. You should be able to see the options like in figure (1) below.
- 2) Press&hold the option pointing to the right (see Figure below (1)) to create the output edge from the given operation node.
- 3) Drag the mouse pointer to the operation node you want to be the destination of the edge.





