

```

package com.robert;

public class HandsOn
{
    public static void main(String[] args)
    {
        // TODO Auto-generated method stub

    }
}

class Person
{
    private String firstName;
    private String lastName;
    private int age;

    // constructor
    public Person()
    {
        firstName = "";
        lastName = "";
        age = 0;
    }

    // overload constructor
    public Person(String firstName)
    {
        this.firstName = firstName;
        lastName = "";
        age = 0;
    }

    // overload constructor
    public Person(String firstName, String lastName)
    {
        this.firstName = firstName;
        this.lastName = lastName;
        age = 0;
    }

    // overload constructor
    public Person(String firstName, String lastName, int age)
    {
        this.firstName = firstName;
        this.lastName = lastName;
        this.age = age;
    }

    // public Person(String firstName, String lastName, int age) {
    // this.firstName = firstName;

```

```

//      this.lastName = lastName;
//      this.age = age;
//      validAge();
//  }

    // valid age?
    private void validAge()
    {
        if (age < 0)
        {
            age = 0;
            System.out.println("Attempted to set age to an invalid value. Setting age to 0 instead.");
        }
    }

//      setters and getters

    public String getFirstName()
    {
        return firstName;
    }

    public void setFirstName(String FirstName)
    {
        firstName = FirstName;
    }

    public String getLastName()
    {
        return lastName;
    }

    public void setLastName(String LastName)
    {
        lastName = LastName;
    }

    public int getAge()
    {
        return age;
    }

    public void setAge(int age)
    {
        this.age = age;
        validAge();
    }

}

```