

Admin Web Error Handling and Troubleshooting

Admin access and operational failure playbook.



This document explains its subject first in plain language, then in engineering detail. It is grounded in the Craves repository snapshot and deliberately separates current implementation, legacy/reference code, milestone foundations and repository gaps so readers do not mistake aspiration for proof.

Version 1.0 | Evidence date: 14 August 2026 | Repository: [rmorampudi09-arch/Craves-Build-platform](#) | Snapshot commit: [3225f7fa531a6b07185fb5e034f7930f8bd8b571](#)

admin surface boundary - plain-language purpose

Plain-English explanation

Craves includes a governed semantic meal concierge for assisted discovery rather than an authority that can bypass commerce rules.

How it works technically

Recent main history and [apps/customer-web-next/docs/signalr-ai-concierge.md](#) describe SignalR semantic concierge work. Recommendations still rely on governed product data and ordinary catalog, quote, authorization and order paths for transactions.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The ai boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: [apps/customer-web-next/docs/signalr-ai-concierge.md](#); commit 71e795b. Snapshot: main @ 3225f7fa531a (14 August 2026).

admin surface boundary - technical architecture

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

admin surface boundary - end-to-end flow

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

admin surface boundary - errors and edge cases

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

admin surface boundary - deployment, security and operational validation

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

legacy apps/admin - plain-language purpose

Plain-English explanation

Craves includes a governed semantic meal concierge for assisted discovery rather than an authority that can bypass commerce rules.

How it works technically

Recent main history and apps/customer-web-next/docs/signalr-ai-concierge.md describe SignalR semantic concierge work. Recommendations still rely on governed product data and ordinary catalog, quote, authorization and order paths for transactions.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The ai boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Legacy/reference. Evidence: apps/customer-web-next/docs/signalr-ai-concierge.md; commit 71e795b. Snapshot: main @ 3225f7fa531a (14 August 2026).

legacy apps/admin - technical architecture

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Legacy/reference. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

legacy apps/admin - end-to-end flow

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Legacy/reference. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

legacy apps/admin - errors and edge cases

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Legacy/reference. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

legacy apps/admin - deployment, security and operational validation

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Legacy/reference. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

new admin shell - plain-language purpose

Plain-English explanation

Craves includes a governed semantic meal concierge for assisted discovery rather than an authority that can bypass commerce rules.

How it works technically

Recent main history and [apps/customer-web-next/docs/signalr-ai-concierge.md](#) describe SignalR semantic concierge work. Recommendations still rely on governed product data and ordinary catalog, quote, authorization and order paths for transactions.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The ai boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: [apps/customer-web-next/docs/signalr-ai-concierge.md](#); commit 71e795b. Snapshot: main @ 3225f7fa531a (14 August 2026).

new admin shell - technical architecture

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

new admin shell - end-to-end flow

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

new admin shell - errors and edge cases

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

new admin shell - deployment, security and operational validation

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

APIM admin product - plain-language purpose

Plain-English explanation

Azure API Management is the intended policy and routing front door between clients/BFFs and backend services.

How it works technically

The APIM README describes craves-customer without APIM subscription requirement and craves-admin with subscription required, JWT validation against Entra and operation-level role checks from named values. Its cited OpenAPI path was not resolvable on the reviewed main snapshot and is documented as a gap.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The apim boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

APIM admin product - technical architecture

Plain-English explanation

Azure API Management is the intended policy and routing front door between clients/BFFs and backend services.

How it works technically

The APIM README describes craves-customer without APIM subscription requirement and craves-admin with subscription required, JWT validation against Entra and operation-level role checks from named values. Its cited OpenAPI path was not resolvable on the reviewed main snapshot and is documented as a gap.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The apim boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

APIM admin product - end-to-end flow

Plain-English explanation

Azure API Management is the intended policy and routing front door between clients/BFFs and backend services.

How it works technically

The APIM README describes craves-customer without APIM subscription requirement and craves-admin with subscription required, JWT validation against Entra and operation-level role checks from named values. Its cited OpenAPI path was not resolvable on the reviewed main snapshot and is documented as a gap.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The apim boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

APIM admin product - errors and edge cases

Plain-English explanation

Azure API Management is the intended policy and routing front door between clients/BFFs and backend services.

How it works technically

The APIM README describes craves-customer without APIM subscription requirement and craves-admin with subscription required, JWT validation against Entra and operation-level role checks from named values. Its cited OpenAPI path was not resolvable on the reviewed main snapshot and is documented as a gap.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The apim boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

APIM admin product - deployment, security and operational validation

Plain-English explanation

Azure API Management is the intended policy and routing front door between clients/BFFs and backend services.

How it works technically

The APIM README describes craves-customer without APIM subscription requirement and craves-admin with subscription required, JWT validation against Entra and operation-level role checks from named values. Its cited OpenAPI path was not resolvable on the reviewed main snapshot and is documented as a gap.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The apim boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

subscription protection - plain-language purpose

Plain-English explanation

Subscriptions support repeat service and entitlements on top of one-off ordering.

How it works technically

subscription-service migrations cover plans, subscriptions, payment identifiers/tokens, idempotency, request fingerprints and usage counters. The latest observed main commit adds shared entitlements and gated services.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The subscription boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/subscription-service/README.md; apps/customer-web-next/src/components/plans/; apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Snapshot: main @ 3225f7fa531a (14 August 2026).

subscription protection - technical architecture

Plain-English explanation

Subscriptions support repeat service and entitlements on top of one-off ordering.

How it works technically

subscription-service migrations cover plans, subscriptions, payment identifiers/tokens, idempotency, request fingerprints and usage counters. The latest observed main commit adds shared entitlements and gated services.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The subscription boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/subscription-service/README.md; apps/customer-web-next/src/components/plans/; apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Snapshot: main @ 3225f7fa531a (14 August 2026).

subscription protection - end-to-end flow

Plain-English explanation

Subscriptions support repeat service and entitlements on top of one-off ordering.

How it works technically

subscription-service migrations cover plans, subscriptions, payment identifiers/tokens, idempotency, request fingerprints and usage counters. The latest observed main commit adds shared entitlements and gated services.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The subscription boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/subscription-service/README.md; apps/customer-web-next/src/components/plans/; apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Snapshot: main @ 3225f7fa531a (14 August 2026).

subscription protection - errors and edge cases

Plain-English explanation

Subscriptions support repeat service and entitlements on top of one-off ordering.

How it works technically

subscription-service migrations cover plans, subscriptions, payment identifiers/tokens, idempotency, request fingerprints and usage counters. The latest observed main commit adds shared entitlements and gated services.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The subscription boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/subscription-service/README.md; apps/customer-web-next/src/components/plans/; apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Snapshot: main @ 3225f7fa531a (14 August 2026).

subscription protection - deployment, security and operational validation

Plain-English explanation

Subscriptions support repeat service and entitlements on top of one-off ordering.

How it works technically

subscription-service migrations cover plans, subscriptions, payment identifiers/tokens, idempotency, request fingerprints and usage counters. The latest observed main commit adds shared entitlements and gated services.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The subscription boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/subscription-service/README.md; apps/customer-web-next/src/components/plans/; apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Snapshot: main @ 3225f7fa531a (14 August 2026).

role policy - plain-language purpose

Plain-English explanation

Craves includes a governed semantic meal concierge for assisted discovery rather than an authority that can bypass commerce rules.

How it works technically

Recent main history and [apps/customer-web-next/docs/signalr-ai-concierge.md](#) describe SignalR semantic concierge work. Recommendations still rely on governed product data and ordinary catalog, quote, authorization and order paths for transactions.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The ai boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: [apps/customer-web-next/docs/signalr-ai-concierge.md](#); commit 71e795b. Snapshot: main @ 3225f7fa531a (14 August 2026).

role policy - technical architecture

Plain-English explanation

Security is layered: identity proof, token validation, role/ownership checks, secret isolation, provider-signature checks and deployment gates address different failure modes.

How it works technically

APIM adds gateway policy, services re-check authorization, web uses secure cookies, mobile milestones use secure token storage, Razorpay callbacks use HMAC verification, and local starter secrets are prohibited in deployed Azure profiles where documented.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The security boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: [infra/apim/README.md](#); [services/user-chef-service/README.md](#); [services/order-service/README.md](#); [apps/customer-web-next/README.md](#). Snapshot: main @ 3225f7fa531a (14 August 2026).

role policy - end-to-end flow

Plain-English explanation

Security is layered: identity proof, token validation, role/ownership checks, secret isolation, provider-signature checks and deployment gates address different failure modes.

How it works technically

APIM adds gateway policy, services re-check authorization, web uses secure cookies, mobile milestones use secure token storage, Razorpay callbacks use HMAC verification, and local starter secrets are prohibited in deployed Azure profiles where documented.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The security boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: [infra/apim/README.md](#); [services/user-chef-service/README.md](#); [services/order-service/README.md](#); [apps/customer-web-next/README.md](#). Snapshot: main @ 3225f7fa531a (14 August 2026).

role policy - errors and edge cases

Plain-English explanation

Security is layered: identity proof, token validation, role/ownership checks, secret isolation, provider-signature checks and deployment gates address different failure modes.

How it works technically

APIM adds gateway policy, services re-check authorization, web uses secure cookies, mobile milestones use secure token storage, Razorpay callbacks use HMAC verification, and local starter secrets are prohibited in deployed Azure profiles where documented.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The security boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: [infra/apim/README.md](#); [services/user-chef-service/README.md](#); [services/order-service/README.md](#); [apps/customer-web-next/README.md](#). Snapshot: main @ 3225f7fa531a (14 August 2026).

role policy - deployment, security and operational validation

Plain-English explanation

The repository has broad CI/CD references across backend, frontend, mobile, APIM, data, privacy, security, smoke and release controls.

How it works technically

customer-web-next README describes ACR build/push, Container App revision deployment, readiness checks and restoration of the prior image/revision on failed readiness. Pipeline names not resolvable at their cited path are classified as reference-only instead of assigned invented triggers.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The devops boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/customer-web-next/README.md; repository YAML search; docs/handover/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef review - plain-language purpose

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-mode/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef review - technical architecture

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-mode/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef review - end-to-end flow

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-mode/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef review - errors and edge cases

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-mode/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef review - deployment, security and operational validation

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-model/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef verification - plain-language purpose

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-mode/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef verification - technical architecture

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-mode/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef verification - end-to-end flow

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-mode/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef verification - errors and edge cases

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-mode/. Snapshot: main @ 3225f7fa531a (14 August 2026).

chef verification - deployment, security and operational validation

Plain-English explanation

Chef mode is the supply side of the marketplace: onboarding, verification, menus, kitchen/order operations and earnings.

How it works technically

user-chef-service persists chef profiles and verification state. The frontend can switch context, but the server remains the authority: showing Chef mode never grants a CHEF role by itself.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The chef boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-model/. Snapshot: main @ 3225f7fa531a (14 August 2026).

catalog admin - plain-language purpose

Plain-English explanation

Catalog is the source of browseable meal and cuisine information used by discovery and commerce validation.

How it works technically

catalog-service is a Spring Boot/Flyway service with JWT controls. The web contains discovery, meals, search and selector modules. Administrative catalog operations are described by APIM guidance, including bulk pause/import and SHA-256 integrity checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The catalog boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

catalog admin - technical architecture

Plain-English explanation

Catalog is the source of browseable meal and cuisine information used by discovery and commerce validation.

How it works technically

catalog-service is a Spring Boot/Flyway service with JWT controls. The web contains discovery, meals, search and selector modules. Administrative catalog operations are described by APIM guidance, including bulk pause/import and SHA-256 integrity checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The catalog boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

catalog admin - end-to-end flow

Plain-English explanation

Catalog is the source of browseable meal and cuisine information used by discovery and commerce validation.

How it works technically

catalog-service is a Spring Boot/Flyway service with JWT controls. The web contains discovery, meals, search and selector modules. Administrative catalog operations are described by APIM guidance, including bulk pause/import and SHA-256 integrity checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The catalog boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

catalog admin - errors and edge cases

Plain-English explanation

Catalog is the source of browseable meal and cuisine information used by discovery and commerce validation.

How it works technically

catalog-service is a Spring Boot/Flyway service with JWT controls. The web contains discovery, meals, search and selector modules. Administrative catalog operations are described by APIM guidance, including bulk pause/import and SHA-256 integrity checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The catalog boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

catalog admin - deployment, security and operational validation

Plain-English explanation

Catalog is the source of browseable meal and cuisine information used by discovery and commerce validation.

How it works technically

catalog-service is a Spring Boot/Flyway service with JWT controls. The web contains discovery, meals, search and selector modules. Administrative catalog operations are described by APIM guidance, including bulk pause/import and SHA-256 integrity checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The catalog boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

bulk pause/import - plain-language purpose

Plain-English explanation

Craves includes a governed semantic meal concierge for assisted discovery rather than an authority that can bypass commerce rules.

How it works technically

Recent main history and [apps/customer-web-next/docs/signalr-ai-concierge.md](#) describe SignalR semantic concierge work. Recommendations still rely on governed product data and ordinary catalog, quote, authorization and order paths for transactions.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The ai boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: [apps/customer-web-next/docs/signalr-ai-concierge.md](#); commit 71e795b. Snapshot: main @ 3225f7fa531a (14 August 2026).

bulk pause/import - technical architecture

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

bulk pause/import - end-to-end flow

Plain-English explanation

Administrative tooling lets authorized staff review marketplace state unavailable to ordinary customers and chefs.

How it works technically

The repository contains legacy apps/admin plus newer customer-web-next admin/support/chef-review modules. APIM guidance places admin operations in a subscription-protected product with additional role checks.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The admin boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

bulk pause/import - errors and edge cases

Plain-English explanation

A useful failure model separates user input/state conflicts, identity/permission failures, dependency outages, data faults and deployment/configuration incidents.

How it works technically

order-service documents Problem Details fields and codes including ORDER_NOT_FOUND, ORDER_IDEMPOTENCY_CONFLICT, INVALID_STATUS, CANCELLATION_NOT_ALLOWED, REFUND_FAILED, UNAUTHORIZED, FORBIDDEN, BACKEND_CHANGE_DISABLED and BACKEND_UNAVAILABLE. Diagnostics should start from request/correlation evidence.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The errors boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/order-service/README.md; services/notification-service/README.md; apps/customer-web-next/README.md. Snapshot: main @ 3225f7fa531a (14 August 2026).

bulk pause/import - deployment, security and operational validation

Plain-English explanation

The repository has broad CI/CD references across backend, frontend, mobile, APIM, data, privacy, security, smoke and release controls.

How it works technically

customer-web-next README describes ACR build/push, Container App revision deployment, readiness checks and restoration of the prior image/revision on failed readiness. Pipeline names not resolvable at their cited path are classified as reference-only instead of assigned invented triggers.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The devops boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: apps/customer-web-next/README.md; repository YAML search; docs/handover/. Snapshot: main @ 3225f7fa531a (14 August 2026).

order admin - plain-language purpose

Plain-English explanation

Order management is the transactional spine of Craves: create, retrieve, status, cancellation/refund, delivery state, ETA/shortage, proof and administrative controls.

How it works technically

order-service documents idempotency, structured Problem Details errors, reconciliation, provider integration and controlled multi-database routing. Supported roles include customer, chef, admin and delivery-partner contexts with ownership enforcement.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The order boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/order-service/README.md; apps/customer-web-next/src/components/order-history/; apps/customer-web-next/src/components/order-tracking/. Snapshot: main @ 3225f7fa531a (14 August 2026).

order admin - technical architecture

Plain-English explanation

Order management is the transactional spine of Craves: create, retrieve, status, cancellation/refund, delivery state, ETA/shortage, proof and administrative controls.

How it works technically

order-service documents idempotency, structured Problem Details errors, reconciliation, provider integration and controlled multi-database routing. Supported roles include customer, chef, admin and delivery-partner contexts with ownership enforcement.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The order boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/order-service/README.md; apps/customer-web-next/src/components/order-history/; apps/customer-web-next/src/components/order-tracking/. Snapshot: main @ 3225f7fa531a (14 August 2026).

order admin - end-to-end flow

Plain-English explanation

Order management is the transactional spine of Craves: create, retrieve, status, cancellation/refund, delivery state, ETA/shortage, proof and administrative controls.

How it works technically

order-service documents idempotency, structured Problem Details errors, reconciliation, provider integration and controlled multi-database routing. Supported roles include customer, chef, admin and delivery-partner contexts with ownership enforcement.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The order boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/order-service/README.md; apps/customer-web-next/src/components/order-history/; apps/customer-web-next/src/components/order-tracking/. Snapshot: main @ 3225f7fa531a (14 August 2026).

order admin - errors and edge cases

Plain-English explanation

Order management is the transactional spine of Craves: create, retrieve, status, cancellation/refund, delivery state, ETA/shortage, proof and administrative controls.

How it works technically

order-service documents idempotency, structured Problem Details errors, reconciliation, provider integration and controlled multi-database routing. Supported roles include customer, chef, admin and delivery-partner contexts with ownership enforcement.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The order boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/order-service/README.md; apps/customer-web-next/src/components/order-history/; apps/customer-web-next/src/components/order-tracking/. Snapshot: main @ 3225f7fa531a (14 August 2026).

order admin - deployment, security and operational validation

Plain-English explanation

Order management is the transactional spine of Craves: create, retrieve, status, cancellation/refund, delivery state, ETA/shortage, proof and administrative controls.

How it works technically

order-service documents idempotency, structured Problem Details errors, reconciliation, provider integration and controlled multi-database routing. Supported roles include customer, chef, admin and delivery-partner contexts with ownership enforcement.

Flow described in words

1. Actor starts the capability with the appropriate identity/context. 2. Client/BFF validates local prerequisites and sends an API request. 3. APIM and the owning service enforce identity, role, ownership and business-state rules. 4. The domain service reads/writes authoritative state and calls providers only through defined boundaries. 5. The caller receives authoritative result or a traceable error; support uses request/correlation evidence rather than secrets.

Errors, edge cases and controls

- Stale UI/cache must not override server state.
- UI visibility is not authorization evidence.
- Retries of money/state-changing operations require idempotency awareness.
- Provider/configuration outages should preserve core domain consistency where safe.
- Missing repository proof is reported as a gap rather than converted into a production claim.

Diagnostic and validation steps

1. Capture time, environment, operation, expected/actual result and a user-safe identifier. 2. Capture HTTP status, stable error code and request/correlation ID; never copy OTPs, passwords, access tokens or provider secrets. 3. Verify caller role/ownership and current authoritative state before retrying. 4. Check owning service health, then its provider/dependency after local/configuration causes are excluded. 5. If a release is implicated, compare artifact/config marker with prior known-good revision and validate rollback compatibility.

Data, security and deployment impact

The order boundary owns its authoritative state; clients request or display changes but do not become the source of truth. Secrets and unnecessary personal data stay outside logs and PDFs. Releases must keep API, policy, schema and artifact compatible, with health/readiness evidence and rollback/backout appropriate to the change.

Evidence status

Implemented on main. Evidence: services/order-service/README.md; apps/customer-web-next/src/components/order-history/; apps/customer-web-next/src/components/order-tracking/. Snapshot: main @ 3225f7fa531a (14 August 2026).