

Backend API Reference

API families, auth, errors and contract evidence.



Summary

This document explains the subject in straightforward professional English, then adds the engineering detail needed to build, operate, troubleshoot or review it. Claims are based on the repository evidence snapshot; missing source details are called out instead of guessed.

Document details

Edition 2.0 | Evidence date: 14 August 2026 | Repository:
rmorampudi09-arch/Craves-Build-platform | Product evidence snapshot: main @
3225f7fa531a6b07185fb5e034f7930f8bd8b571

Summary and how to use this document

API families, auth, errors and contract evidence. The purpose is to make the system understandable to a new team member while still giving engineers enough detail to trace ownership, data flow, deployment impact and failure handling.

Current implementation

Direct code, README, migration, pipeline or commit evidence exists on the reviewed main snapshot.

Foundation / partial

Useful groundwork exists, but the repository does not prove a complete production runtime for every part.

Legacy / reference

Older implementation is retained for history or compatibility and is not treated as the preferred runtime.

Needs source confirmation


A referenced artifact or exact value could not be verified and is therefore not invented.

Reading order

- Start with the summary to understand the responsibility in normal language.
- Use process diagrams to follow requests across client, APIM, services, data and providers.
- Use the troubleshooting sections to diagnose by evidence rather than by retrying blindly.
- Use deployment and validation sections before or after changing a component.
- Use evidence status to separate proven behavior from gaps and future work.

How the request moves through Craves

The exact components depend on the feature, but the normal pattern is consistent. The user interface starts the request, the gateway and owning service enforce trust, the service writes authoritative state, and provider integrations remain behind controlled boundaries.



Key rule

A screen can hide or show an action for usability, but that is not security. APIM and the owning backend still validate the caller, role, ownership and current business state. Likewise, provider success is not accepted as Craves state until the backend verifies and records the result.

GET /actuator/health

Purpose

Service health

Access

Service-specific


Summary

Used by engineers and deployment validation to confirm the application is running.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Service health is down: Database/config/dependency/startup failure. Resolution: Inspect health/readiness and recent deployment/config changes.

Request rejected: Validation, role, ownership or state rule failed. Resolution: Use stable error code/request ID and correct the actual failing rule.

Evidence

Source evidence: services/auth-service/README.md; services/user-chef-service/README.md; services/catalog-service/README.md; services/order-service/README.md; services/subscription-service/README.md; services/integration-service/README.md; services/notification-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/customer/profile

Purpose

Read customer profile

Access

USER


Summary

Returns the authenticated customer profile.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Service health is down: Database/config/dependency/startup failure. Resolution: Inspect health/readiness and recent deployment/config changes.

Request rejected: Validation, role, ownership or state rule failed. Resolution: Use stable error code/request ID and correct the actual failing rule.

Evidence

Source evidence: services/auth-service/README.md; services/user-chef-service/README.md; services/catalog-service/README.md; services/order-service/README.md; services/subscription-service/README.md; services/integration-service/README.md; services/notification-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

PUT /api/v1/customer/profile

Purpose

Update customer profile

Access

USER


Summary

Updates supported customer profile fields.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Service health is down: Database/config/dependency/startup failure. Resolution: Inspect health/readiness and recent deployment/config changes.

Request rejected: Validation, role, ownership or state rule failed. Resolution: Use stable error code/request ID and correct the actual failing rule.

Evidence

Source evidence: services/auth-service/README.md; services/user-chef-service/README.md; services/catalog-service/README.md; services/order-service/README.md; services/subscription-service/README.md; services/integration-service/README.md; services/notification-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/customer/addresses

Purpose

List saved addresses

Access

USER


Summary

Returns active saved delivery addresses owned by the customer.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Current location unavailable: Permission/device/geocoder failed. Resolution: Allow manual saved-address entry and keep checkout dependent on a valid saved address.

Address rejected at checkout: Address is missing ownership/required fields/coordinates. Resolution: Fix the saved address in User-Chef before placing the order.

Evidence

Source evidence: apps/customer-web-next/src/components/location/; apps/customer-web-next/src/components/maps/; apps/customer-web-next/src/lib/location/; docs/handover/2026-08-06-customer-chef-precise-ui-address-dialog.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/customer/addresses

Purpose

Create saved address

Access

USER


Summary

Requires recipient, address, area, city/state/postal code and valid coordinates.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Current location unavailable: Permission/device/geocoder failed. Resolution: Allow manual saved-address entry and keep checkout dependent on a valid saved address.

Address rejected at checkout: Address is missing ownership/required fields/coordinates. Resolution: Fix the saved address in User-Chef before placing the order.

Evidence

Source evidence: apps/customer-web-next/src/components/location/; apps/customer-web-next/src/components/maps/; apps/customer-web-next/src/lib/location/; docs/handover/2026-08-06-customer-chef-precise-ui-address-dialog.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

PUT /api/v1/customer/addresses/{addressId}

Purpose

Update saved address

Access

USER / owner


Summary

Updates an owned active address and maintains default-address rules.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Current location unavailable: Permission/device/geocoder failed. Resolution: Allow manual saved-address entry and keep checkout dependent on a valid saved address.

Address rejected at checkout: Address is missing ownership/required fields/coordinates. Resolution: Fix the saved address in User-Chef before placing the order.

Evidence

Source evidence: apps/customer-web-next/src/components/location/; apps/customer-web-next/src/components/maps/; apps/customer-web-next/src/lib/location/; docs/handover/2026-08-06-customer-chef-precise-ui-address-dialog.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

DELETE /api/v1/customer/addresses/{addressId}

Purpose

Remove saved address

Access

USER / owner


Summary

Soft deletes the address and promotes another default when needed.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Current location unavailable: Permission/device/geocoder failed. Resolution: Allow manual saved-address entry and keep checkout dependent on a valid saved address.

Address rejected at checkout: Address is missing ownership/required fields/coordinates. Resolution: Fix the saved address in User-Chef before placing the order.

Evidence

Source evidence: apps/customer-web-next/src/components/location/; apps/customer-web-next/src/components/maps/; apps/customer-web-next/src/lib/location/; docs/handover/2026-08-06-customer-chef-precise-ui-address-dialog.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/customer/addresses/recommendation

Purpose

Recommend saved address from GPS

Access

USER


Summary

Returns SAVED_ADDRESS when a nearby saved address matches; otherwise LIVE_GPS.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Current location unavailable: Permission/device/geocoder failed. Resolution: Allow manual saved-address entry and keep checkout dependent on a valid saved address.

Address rejected at checkout: Address is missing ownership/required fields/coordinates. Resolution: Fix the saved address in User-Chef before placing the order.

Evidence

Source evidence: apps/customer-web-next/src/components/location/; apps/customer-web-next/src/components/maps/; apps/customer-web-next/src/lib/location/; docs/handover/2026-08-06-customer-chef-precise-ui-address-dialog.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET

/internal/v1/customer-addresses/{addressId}?identityId={identityId}

Purpose

Internal checkout address lookup

Access

Internal service


Summary

Validates active address ownership for Order Service. Uses a service credential, never a client credential.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Checkout rejected: Saved address, cart or catalog state is not valid. Resolution: Reload authoritative cart/address/catalog state and correct the failing condition.

Displayed total changed: Backend revalidated price or availability. Resolution: Show the backend quote; do not preserve a client-calculated amount.

Evidence

Source evidence: apps/customer-web-next/README.md; apps/customer-web-next/src/components/cart/; apps/customer-web-next/src/components/checkout/; services/order-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/chef/application

Purpose

Read chef application

Access

Authenticated user


Summary

Returns current chef application state.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md;
 apps/customer-web-next/src/components/chef/;
 apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/chef/application

Purpose

Submit chef application

Access

Authenticated user


Summary

Creates or updates chef onboarding information.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md;
 apps/customer-web-next/src/components/chef/;
 apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/chef/application/proof-files

Purpose

Upload chef proof files

Access

Authenticated user


Summary

Uploads KYC/proof files through the documented storage boundary.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md;
apps/customer-web-next/src/components/chef/;
apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/backoffice/chef-reviews?status=PENDING

Purpose

List chef reviews

Access

ADMIN


Summary

Backoffice review queue.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md;
 apps/customer-web-next/src/components/chef/;
 apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST

/api/v1/backoffice/chef-reviews/{applicationId}/approve

Purpose

Approve chef

Access

ADMIN


Summary

Approves eligible application and changes protected chef state.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md; apps/customer-web-next/src/components/chef/; apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST

/api/v1/backoffice/chef-reviews/{applicationId}/reject

Purpose

Reject chef

Access

ADMIN


Summary

Rejects an application using the protected review flow.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md;
apps/customer-web-next/src/components/chef/;
apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/discovery/kitchens

Purpose

Nearby kitchens

Access

Customer


Summary

Requires latitude, longitude, radiusMeters; PostGIS orders eligible kitchens by distance.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius. Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution: Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/discovery/menu-items

Purpose

Nearby menu items

Access

Customer


Summary

Returns sellable nearby items with kitchen, package and primary-image metadata.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius.

Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution:

Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/catalog/kitchens

Purpose

Public kitchen catalog

Access

Customer


Summary

Compatibility route for existing clients.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius.

Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution:

Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/catalog/kitchens/{kitchenId}/menu-items

Purpose

Kitchen menu

Access

Customer


Summary

Returns menu items for a selected kitchen.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius.

Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution:

Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/kitchens/me

Purpose

Read own kitchen

Access

CHEF


Summary

Returns the approved chef's kitchen profile.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius.

Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution:

Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

PUT /api/v1/kitchens/me

Purpose

Update own kitchen

Access

CHEF


Summary

Creates/updates the chef-owned kitchen profile.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius.

Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution:

Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/kitchens/me/menu-items

Purpose

List own menu items

Access

CHEF


Summary

Returns menu items owned by the chef kitchen.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius.

Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution:

Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/kitchens/me/menu-items

Purpose

Create menu item

Access

CHEF


Summary

Requires sellable details including package weight and thermobox decision.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius.

Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution:

Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

PATCH

/api/v1/kitchens/me/menu-items/{menuItemId}/availability

Purpose

Change availability

Access

CHEF / owner


Summary

Changes only an owned menu item.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Nearby results empty: No active geocoded kitchen with sellable items in query radius.

Resolution: Confirm kitchen coordinates, active menu items and caller radius.

Menu item cannot sell: Packaging/availability/status metadata incomplete. Resolution:

Chef must provide valid required metadata and make the item available.

Evidence

Source evidence: services/catalog-service/README.md; apps/customer-web-next/src/components/discovery/; apps/customer-web-next/src/components/meals/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/cart

Purpose

Read cart

Access

USER


Summary

Returns backend-authoritative cart state.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Checkout rejected: Saved address, cart or catalog state is not valid. Resolution: Reload authoritative cart/address/catalog state and correct the failing condition.

Displayed total changed: Backend revalidated price or availability. Resolution: Show the backend quote; do not preserve a client-calculated amount.

Evidence

Source evidence: apps/customer-web-next/README.md;
 apps/customer-web-next/src/components/cart/;
 apps/customer-web-next/src/components/checkout/; services/order-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/cart/items

Purpose

Add cart item

Access

USER


Summary

Adds a valid sellable catalog item.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Checkout rejected: Saved address, cart or catalog state is not valid. Resolution: Reload authoritative cart/address/catalog state and correct the failing condition.

Displayed total changed: Backend revalidated price or availability. Resolution: Show the backend quote; do not preserve a client-calculated amount.

Evidence

Source evidence: apps/customer-web-next/README.md;
 apps/customer-web-next/src/components/cart/;
 apps/customer-web-next/src/components/checkout/; services/order-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

PUT /api/v1/cart/items/{cartItemId}

Purpose

Change cart quantity

Access

USER / owner


Summary

Updates quantity after validation.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Checkout rejected: Saved address, cart or catalog state is not valid. Resolution: Reload authoritative cart/address/catalog state and correct the failing condition.

Displayed total changed: Backend revalidated price or availability. Resolution: Show the backend quote; do not preserve a client-calculated amount.

Evidence

Source evidence: apps/customer-web-next/README.md;
 apps/customer-web-next/src/components/cart/;
 apps/customer-web-next/src/components/checkout/; services/order-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

DELETE /api/v1/cart/items/{cartItemId}

Purpose

Remove cart item

Access

USER / owner


Summary

Removes one cart item.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Checkout rejected: Saved address, cart or catalog state is not valid. Resolution: Reload authoritative cart/address/catalog state and correct the failing condition.

Displayed total changed: Backend revalidated price or availability. Resolution: Show the backend quote; do not preserve a client-calculated amount.

Evidence

Source evidence: apps/customer-web-next/README.md;
 apps/customer-web-next/src/components/cart/;
 apps/customer-web-next/src/components/checkout/; services/order-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/cart/validate

Purpose

Validate cart

Access

USER


Summary

Re-checks current catalog state before checkout.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Checkout rejected: Saved address, cart or catalog state is not valid. Resolution: Reload authoritative cart/address/catalog state and correct the failing condition.

Displayed total changed: Backend revalidated price or availability. Resolution: Show the backend quote; do not preserve a client-calculated amount.

Evidence

Source evidence: apps/customer-web-next/README.md;
 apps/customer-web-next/src/components/cart/;
 apps/customer-web-next/src/components/checkout/; services/order-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/checkout

Purpose

Create checkout

Access

USER


Summary

Requires saved deliveryAddressId; creates immutable drop-off/pickup and item/package snapshots.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Checkout rejected: Saved address, cart or catalog state is not valid. Resolution: Reload authoritative cart/address/catalog state and correct the failing condition.

Displayed total changed: Backend revalidated price or availability. Resolution: Show the backend quote; do not preserve a client-calculated amount.

Evidence

Source evidence: apps/customer-web-next/README.md;
 apps/customer-web-next/src/components/cart/;
 apps/customer-web-next/src/components/checkout/; services/order-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/checkout/{checkoutId}

Purpose

Read checkout

Access

USER / owner


Summary

Returns an owned checkout.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Checkout rejected: Saved address, cart or catalog state is not valid. Resolution: Reload authoritative cart/address/catalog state and correct the failing condition.

Displayed total changed: Backend revalidated price or availability. Resolution: Show the backend quote; do not preserve a client-calculated amount.

Evidence

Source evidence: apps/customer-web-next/README.md;
 apps/customer-web-next/src/components/cart/;
 apps/customer-web-next/src/components/checkout/; services/order-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/orders

Purpose

List customer orders

Access

USER


Summary

Returns customer-owned orders.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Order not found: Wrong ID or ownership mismatch. Resolution: Verify ID and caller context; never expose another user's order.

State change rejected: Transition is not valid from the current state. Resolution: Reload order state and use only the supported next action.

Evidence

Source evidence: services/order-service/README.md;
apps/customer-web-next/src/components/order-history/;
apps/customer-web-next/src/components/order-tracking/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/orders/{orderId}

Purpose

Read order

Access

USER / owner


Summary

Returns one owned order.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Order not found: Wrong ID or ownership mismatch. Resolution: Verify ID and caller context; never expose another user's order.

State change rejected: Transition is not valid from the current state. Resolution: Reload order state and use only the supported next action.

Evidence

Source evidence: services/order-service/README.md;
apps/customer-web-next/src/components/order-history/;
apps/customer-web-next/src/components/order-tracking/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/chef/orders

Purpose

List chef orders

Access

CHEF


Summary

Returns chef-owned order work.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md;
apps/customer-web-next/src/components/chef/;
apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/chef/orders/{orderId}/accept

Purpose

Accept chef order

Access

CHEF / owner


Summary

Requires positive prepTimeMinutes and persists ready_at.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md;
 apps/customer-web-next/src/components/chef/;
 apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/chef/orders/{orderId}/ready-for-pickup

Purpose

Mark ready for pickup

Access

CHEF / owner


Summary

Moves an eligible accepted order to the ready state.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

User sees stale state: Client cache/local state differs from backend. Resolution: Reload from the owning service.

Dependency failure: Provider or downstream is unavailable. Resolution: Preserve domain consistency and retry only when safe.

Evidence

Source evidence: services/user-chef-service/README.md;
 apps/customer-web-next/src/components/chef/;
 apps/customer-web-next/src/components/chef-model/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/admin/charge-policy/current

Purpose

Read current charge policy

Access

ADMIN


Summary

Reads the active order charge policy.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Admin action denied: Caller lacks admin role/product permission. Resolution: Use approved staff access process and least privilege.

Operation changes unexpected data: Wrong record/state selected. Resolution: Stop, capture audit/request evidence and follow the documented recovery path.

Evidence

Source evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/admin/charge-policy

Purpose

Create charge policy

Access

ADMIN


Summary

Protected finance/operations configuration; current seeded V1 fees are zero unless changed.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Admin action denied: Caller lacks admin role/product permission. Resolution: Use approved staff access process and least privilege.

Operation changes unexpected data: Wrong record/state selected. Resolution: Stop, capture audit/request evidence and follow the documented recovery path.

Evidence

Source evidence: apps/admin/README.md; apps/customer-web-next/src/features/admin/; apps/customer-web-next/src/features/chef-review/; infra/apim/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/subscriptions/plans

Purpose

List subscription plans

Access

Authenticated customer


Summary

Lists available plan foundations.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Lifecycle action rejected: Current subscription state does not allow it. Resolution: Reload current state and use a supported transition.

Commercial rule missing: Product/Finance decision is intentionally not defined. Resolution: Document the decision before implementing it.

Evidence

Source evidence: services/subscription-service/README.md;
 apps/customer-web-next/src/components/plans/;
 apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /api/v1/subscriptions

Purpose

Create subscription

Access

USER


Summary

Creates a customer subscription subject to current lifecycle rules.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Lifecycle action rejected: Current subscription state does not allow it. Resolution: Reload current state and use a supported transition.

Commercial rule missing: Product/Finance decision is intentionally not defined. Resolution: Document the decision before implementing it.

Evidence

Source evidence: services/subscription-service/README.md;
apps/customer-web-next/src/components/plans/;
apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/subscriptions

Purpose

List subscriptions

Access

USER


Summary

Returns customer subscriptions.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Lifecycle action rejected: Current subscription state does not allow it. Resolution: Reload current state and use a supported transition.

Commercial rule missing: Product/Finance decision is intentionally not defined. Resolution: Document the decision before implementing it.

Evidence

Source evidence: services/subscription-service/README.md;
 apps/customer-web-next/src/components/plans/;
 apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

PATCH /api/v1/subscriptions/{subscriptionId}/pause

Purpose

Pause subscription

Access

USER / owner


Summary

Applies supported pause transition.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Lifecycle action rejected: Current subscription state does not allow it. Resolution: Reload current state and use a supported transition.

Commercial rule missing: Product/Finance decision is intentionally not defined. Resolution: Document the decision before implementing it.

Evidence

Source evidence: services/subscription-service/README.md;
 apps/customer-web-next/src/components/plans/;
 apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

PATCH /api/v1/subscriptions/{subscriptionId}/cancel

Purpose

Cancel subscription

Access

USER / owner


Summary

Applies supported cancellation transition.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Lifecycle action rejected: Current subscription state does not allow it. Resolution: Reload current state and use a supported transition.

Commercial rule missing: Product/Finance decision is intentionally not defined. Resolution: Document the decision before implementing it.

Evidence

Source evidence: services/subscription-service/README.md;
 apps/customer-web-next/src/components/plans/;
 apps/customer-web-next/src/components/subscriptions/; commit 3225f7fa. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /internal/v1/notifications

Purpose

Create notification

Access

Internal service


Summary

Creates an audited notification request; external channels can remain PENDING until provider adapters are enabled.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

External channel stays pending: Provider adapter is disabled or unavailable. Resolution: Check channel configuration and delivery-attempt state.

Duplicate delivery: Retry did not reuse the event/request key. Resolution: Use idempotency evidence before resending.

Evidence

Source evidence: services/notification-service/README.md; apps/customer-web-next/src/components/notifications/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /api/v1/notifications/in-app

Purpose

In-app inbox

Access

Authenticated identity


Summary

Current foundation requires trusted resolved identity; public exposure must stay behind gateway JWT/identity injection.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

External channel stays pending: Provider adapter is disabled or unavailable. Resolution: Check channel configuration and delivery-attempt state.

Duplicate delivery: Retry did not reuse the event/request key. Resolution: Use idempotency evidence before resending.

Evidence

Source evidence: services/notification-service/README.md; apps/customer-web-next/src/components/notifications/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /internal/v1/delivery-intelligence/providers

Purpose

Register delivery provider

Access

Internal service


Summary

Registers provider capabilities without fabricating rider data.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Order not found: Wrong ID or ownership mismatch. Resolution: Verify ID and caller context; never expose another user's order.

State change rejected: Transition is not valid from the current state. Resolution: Reload order state and use only the supported next action.

Evidence

Source evidence: services/order-service/README.md;
apps/customer-web-next/src/components/order-history/;
apps/customer-web-next/src/components/order-tracking/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /internal/v1/delivery-intelligence/assignments

Purpose

Rank delivery candidates

Access

Internal service


Summary

Idempotent by chefSubOrderId; retries return the persisted decision.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Order not found: Wrong ID or ownership mismatch. Resolution: Verify ID and caller context; never expose another user's order.

State change rejected: Transition is not valid from the current state. Resolution: Reload order state and use only the supported next action.

Evidence

Source evidence: services/order-service/README.md; apps/customer-web-next/src/components/order-history/; apps/customer-web-next/src/components/order-tracking/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /internal/v1/delivery-intelligence/outcomes

Purpose

Record delivery outcome

Access

Internal service


Summary

Idempotent by deliveryId and updates delivery intelligence state once.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Order not found: Wrong ID or ownership mismatch. Resolution: Verify ID and caller context; never expose another user's order.

State change rejected: Transition is not valid from the current state. Resolution: Reload order state and use only the supported next action.

Evidence

Source evidence: services/order-service/README.md;
apps/customer-web-next/src/components/order-history/;
apps/customer-web-next/src/components/order-tracking/. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

POST /auth/firebase/exchange

Purpose

Exchange Firebase identity

Access

Browser BFF / Auth


Summary

Current web sign-in contract; BFF keeps Craves tokens in secure HTTP-only cookies.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Sign-in fails: OTP/session/token is invalid, expired or misconfigured. Resolution: Use the supported sign-in or refresh path and check issuer/audience/configuration.

403 after sign-in: Caller lacks the required role or ownership. Resolution: Confirm intended access; do not bypass authorization.

Evidence

Source evidence: apps/customer-web-next/README.md; services/user-chef-service/README.md; services/order-service/README.md; docs/handover/2026-07-30-customer-mobile-auth-foundation.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

GET /auth/me

Purpose

Read current session identity

Access

Browser BFF / Auth


Summary

Returns current authenticated identity state without exposing tokens to browser JavaScript.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Sign-in fails: OTP/session/token is invalid, expired or misconfigured. Resolution: Use the supported sign-in or refresh path and check issuer/audience/configuration.

403 after sign-in: Caller lacks the required role or ownership. Resolution: Confirm intended access; do not bypass authorization.

Evidence

Source evidence: apps/customer-web-next/README.md; services/user-chef-service/README.md; services/order-service/README.md; docs/handover/2026-07-30-customer-mobile-auth-foundation.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

Contract rules /api/v1/**

Purpose

Shared API contract

Access

Authenticated caller


Summary

JWT/role/ownership, Problem Details, idempotency and correlation are cross-cutting requirements.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Service health is down: Database/config/dependency/startup failure. Resolution: Inspect health/readiness and recent deployment/config changes.

Request rejected: Validation, role, ownership or state rule failed. Resolution: Use stable error code/request ID and correct the actual failing rule.

Evidence

Source evidence: services/auth-service/README.md; services/user-chef-service/README.md; services/catalog-service/README.md; services/order-service/README.md; services/subscription-service/README.md; services/integration-service/README.md; services/notification-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

Hosted payment boundary Cashfree hosted checkout

Purpose

Payment entry

Access

Customer


Summary

Sensitive payment fields stay on the provider-hosted experience; Craves receives only the provider/session result needed by the backend.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Payment result is unclear: Provider status/callback is delayed or ambiguous. Resolution: Verify through the backend/provider reconciliation path before retrying.

Webhook rejected: Signature validation failed. Resolution: Verify the raw body with the server secret; never disable signature checks.

Evidence

Source evidence: apps/customer-web-next/README.md; apps/customer-web-next/src/lib/cashfree/; services/order-service/README.md; services/integration-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

Razorpay callback verification Provider webhook

Purpose

Payment callback

Access

Server-to-server


Summary

Order Service documentation requires HMAC SHA-256 verification over the raw body with the configured server secret.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Payment result is unclear: Provider status/callback is delayed or ambiguous. Resolution: Verify through the backend/provider reconciliation path before retrying.

Webhook rejected: Signature validation failed. Resolution: Verify the raw body with the server secret; never disable signature checks.

Evidence

Source evidence: apps/customer-web-next/README.md; apps/customer-web-next/src/lib/cashfree/; services/order-service/README.md; services/integration-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

APIM customer product craves-customer

Purpose

Gateway product

Access

Customer client


Summary

Customer operations are routed through the customer API product and backend services remain authoritative.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

401 at gateway: JWT validation failed. Resolution: Verify token source, issuer/audience and APIM policy.

403 at gateway: Role/product policy denied the caller. Resolution: Verify admin/customer product and operation role rules.

Evidence

Source evidence: [infra/apim/README.md](#). Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

APIM admin product craves-admin

Purpose

Gateway product

Access

Authorized admin


Summary

Admin product requires stronger gateway controls and operation-level role enforcement.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

401 at gateway: JWT validation failed. Resolution: Verify token source, issuer/audience and APIM policy.

403 at gateway: Role/product policy denied the caller. Resolution: Verify admin/customer product and operation role rules.

Evidence

Source evidence: [infra/apim/README.md](#). Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

Problem Details HTTP error response

Purpose

Stable error contract

Access

API caller


Summary

Use stable code, status and request/correlation identifiers for diagnosis rather than parsing display text.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

401 Unauthorized: Authentication is missing/expired/invalid. Resolution: Use supported identity/refresh flow and capture request ID.

5xx/upstream unavailable: Service/database/provider/deployment is unhealthy. Resolution: Use correlation evidence to isolate the boundary and rollback if release-related.

Evidence

Source evidence: services/order-service/README.md; services/notification-service/README.md; apps/customer-web-next/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

Contract rules /api/v1/**

Purpose

Shared API contract

Access

Authenticated caller


Summary

JWT/role/ownership, Problem Details, idempotency and correlation are cross-cutting requirements.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Service health is down: Database/config/dependency/startup failure. Resolution: Inspect health/readiness and recent deployment/config changes.

Request rejected: Validation, role, ownership or state rule failed. Resolution: Use stable error code/request ID and correct the actual failing rule.

Evidence

Source evidence: services/auth-service/README.md; services/user-chef-service/README.md; services/catalog-service/README.md; services/order-service/README.md; services/subscription-service/README.md; services/integration-service/README.md; services/notification-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

Hosted payment boundary Cashfree hosted checkout

Purpose

Payment entry

Access

Customer


Summary

Sensitive payment fields stay on the provider-hosted experience; Craves receives only the provider/session result needed by the backend.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Payment result is unclear: Provider status/callback is delayed or ambiguous. Resolution: Verify through the backend/provider reconciliation path before retrying.

Webhook rejected: Signature validation failed. Resolution: Verify the raw body with the server secret; never disable signature checks.

Evidence

Source evidence: apps/customer-web-next/README.md; apps/customer-web-next/src/lib/cashfree/; services/order-service/README.md; services/integration-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

Razorpay callback verification Provider webhook

Purpose

Payment callback

Access

Server-to-server


Summary

Order Service documentation requires HMAC SHA-256 verification over the raw body with the configured server secret.

Request and validation

- Send the request only through the documented client/BFF/APIM path for this operation.
- Include authenticated context required by the route. Internal routes use service credentials and must never be exposed to browser/mobile clients.
- Validate identifiers, ownership and current business state. Input convenience in the UI does not replace backend validation.
- Do not send secrets or payment credentials in logs, screenshots or support tickets.

Processing flow



Errors and troubleshooting

Payment result is unclear: Provider status/callback is delayed or ambiguous. Resolution: Verify through the backend/provider reconciliation path before retrying.

Webhook rejected: Signature validation failed. Resolution: Verify the raw body with the server secret; never disable signature checks.

Evidence

Source evidence: apps/customer-web-next/README.md; apps/customer-web-next/src/lib/cashfree/; services/order-service/README.md; services/integration-service/README.md. Exact request/response fields should be taken from the current service source or README for the endpoint; this reference does not invent fields that the repository does not define.

Operational checklist and documented gaps

Before making a change

- Confirm the intended actor and environment.
- Confirm the current authoritative state before changing anything.
- Capture HTTP status, stable error code and request/correlation ID without secrets.
- Validate the owning component health and required dependency/configuration.
- After the action, reload the state from the backend and confirm the expected result.

Repository gaps that must stay visible

- APIM README cites `infra/apim/craves-openapi.yaml`, but that literal artifact was not resolvable on main during this evidence snapshot.
- `customer-web-next` README names `azure-pipelines-customer-web-next.yml`, but that literal root path was not resolvable; deployment behavior described by the README is retained while trigger/variable details are not invented.
- Native mobile has strong milestone identity/API/CI evidence, but a clearly complete runnable React Native application was not established on the reviewed main snapshot.
- Legacy preview URLs prove historical deployment references rather than current production routing.
- Commercial values such as commissions, payout percentages, subscription pricing, catering thresholds and SLAs are not fabricated where source is silent.

Definition of done

A change is complete only when the intended behavior works, authorization still fails closed, authoritative data is correct, health/readiness are good, monitoring or correlation evidence is available, the rollback path remains valid, and the documentation has been updated if the contract or operating procedure changed.