

Each diversity branch i has
 $A_{i,k}$: Channel gain (complex)
 $W_{i,k}$: AWGN sample (complex)
 $Y_{i,k}$: MF output (complex)

$$A_{i,k} = \alpha_{i,k} e^{-j\phi_{i,k}}$$

(as in textbook)

- Three popular techniques to combine the outputs:

1. Selection combining (SC):

$$Y_{\text{SC}} = \arg \max \{|Y_i|\}$$

(Worst performance)

2. Equal-gain combining (EGC):

$$Y_{\text{EGC}} = \sum_{i=1}^D Y_i e^{j\varphi_i}$$

3. Maximal-ratio combining (MRC):

$$Y_{\text{MRC}} = \sum_{i=1}^D \alpha_i Y_i e^{j\varphi_i}$$

(Best performance)

For best performance, need **CHANNEL ESTIMATION**

Improvement in *post-combiner* average E_s / N_0 [1]

- SC:

$$\frac{\gamma_{\text{SC}}}{\gamma_0} = \sum_{i=1}^D \frac{1}{i}$$


- EGC:

$$\frac{\gamma_{\text{EGC}}}{\gamma_0} = 1 + \frac{\pi}{4}(D - 1)$$

- MRC:

$$\frac{\gamma_{\text{MRC}}}{\gamma_0} = D$$

1. P.M. Shankar, *Introduction to Wireless Systems*, Wiley, 2002.



Matlab script: *combiners_improvement.m*