

RADIATIVE TRANSFER IN GALAXIES

RADIATIVE TRANSFER IN GALAXIES

By

RORY WOODS, B.Sc., M.Sc.

A Thesis

Submitted to the School of Graduate Studies

in Partial Fulfillment of the Requirements

for the Degree of

Doctor of Philosophy

McMaster University

© Rory Woods, August 2015

DOCTOR OF PHILOSOPHY (2015)
(Physics and Astronomy)

McMaster University
Hamilton, Ontario

TITLE: Radiative Transfer in Galaxy Formation

AUTHOR: Rory Woods, B.Sc. (Mount Allison University), M.Sc. (McMaster University)

SUPERVISOR: Professor James Wadsley

NUMBER OF PAGES: 1

Abstract

In this thesis, we present a novel algorithm for computing the radiation field in astrophysical simulations.

Dedicated to...

Acknowledgements

Thank you to all that helped.

“Some sort of quote?”

ALBERT EINSTEIN (1879-1955)

Table of Contents

Abstract	iii
Acknowledgments	vi
List of Figures	x
List of Tables	xi
Chapter 1	
Introduction	1
Chapter 2	
Numerical Methods	2
Chapter 3	
The Numerical Method	3
3.1 Tree Data Structures	5
3.1.1 kd-Tree	5
3.2 Building a Radiation Tree	5
3.2.1 Criteria for Opening Cells	5
3.2.2 Accumulating Cell Properties	5
3.3 The Simple Case - No Absorption	5
3.3.1 Exchanging Radiation	5
3.4 Adding Absorption	5
3.4.1 Making Use of the Tree	5
3.5 Refinement	5
3.5.1 Criteria to Refine	5
3.6 Resolving the Sending and Receiving Cells	5

Chapter 4	
Discussion	6
Chapter 5	
Conclusions	7
Chapter A	
Appendix A	8
Bibliography	8

List of Figures

List of Tables

Chapter 1

Introduction

Chapter 2

Numerical Methods

Chapter 3

The Numerical Method

In the absence of absorbing material, the problem of radiative transfer reduces down to that of gravity. As such, the tree-algorithm for calculating gravity can be used (?).

- A tree can be used to partition space.
- Each level of the tree holds finer partitions of the volume. See figure ??
- Each node of the tree contains accumulated information about the tree below it (total mass, etc.).
- In order to calculate gravity on a particular leaf (bucket), you can interact with the moment of another cell (??).
- To decide what level of the tree to interact with, you can define an opening angle/radius, θ . If a cell is smaller than this opening angle (the distribution of matter inside the cell is contained within a small enough angle on the sky), the entire cell can be used in the force calculation. If not, you must consider the child nodes separately. See equation ??.

- On average, the number of interactions a each particle will have is $\log N$, where N is the total number of particles. Thus, the force calculation for the whole simulation scales as $N \log N$. Note that lowering θ shifts the number of calculations that are approximated by large cells to smaller cells, and thus if θ is very small, the code approached scaling of order N^2 .
- In the case of radiation, the math is very similar (See eq ??). However, since radiation does not cancel like forces, the dipole moment does not disappear and a rougher approximation is possible (wording wrong, fix this).
- In this case, the interaction scales as $N_{\text{sink}} \log N_{\text{source}}$. However, assuming the full tree is still used, the tree-build still scales as $N \log N$.

3.1 Tree Data Structures

3.1.1 kd-Tree

3.2 Building a Radiation Tree

3.2.1 Criteria for Opening Cells

3.2.2 Accumulating Cell Properties

3.3 The Simple Case - No Absorption

3.3.1 Exchanging Radiation

3.4 Adding Absorption

3.4.1 Making Use of the Tree

3.5 Refinement

3.5.1 Criteria to Refine

3.6 Resolving the Sending and Receiving Cells

Chapter 4

Discussion

Chapter 5

Conclusions

Appendix A

Appendix A