Comment	Description	Designator	Footprint	LibRef	Quantity
4.3PF	Capacitor, 4.3pF,±0.25pF,50V,C0G,0603	C1, C4	CAPC1608X85N	C0603C200J5GACTU	2
C0603C200J5GACTU	Capacitor Ceramic C0G 0603 50V 20pF | KEMET C0603C200J5GACTU	C2, C5	CAPC1608X85N	C0603C200J5GACTU	2
100NF	0603 C 100nF Ceramic Multilayer Capacitor, 25 V, +125degC, X7R Dielectric, +/-5% | KEMET C0603C104J3RACTU	C3, C6, C7, C9, C10, C11, C14, C15, C16, C17, C18, C28, C29, C30, C31, C32, C33, C34	CAPC1608X90	C0603C104J3RACTU	18
4.7UF	4.7 µF ±10% 16V Ceramic Capacitor X7R 0805 (2012 Metric) 4.7µF A±10% 10V Ceramic Capacitor X7R 0805 (2012 Metric)	C8, C23	CAPC2012X135N	C1218225KPFNNNG	2
2.2UF	2.2 AµF A±10% 10V Ceramic Capacitor X7R 0805 (2012 Metric)	C12, C13	CAPC2012X135N	C1218225KPFNNNG	2
22NF	0603 C 22nF Ceramic Multilayer Capacitor, 25 V, +125degC, X7R Dielectric, +/-5% | KEMET C0603C104J3RACTU	C19	CAPC1608X90	C0603C104J3RACTU	1
6.8NF	0603 C 6.8nF Ceramic Multilayer Capacitor, 25 V, +125degC, X7R Dielectric, +/-5% | KEMET C0603C104J3RACTU	C20, C22	CAPC1608X90	C0603C104J3RACTU	2
4.7NF	0603 C 4.7 nF Ceramic Multilayer Capacitor, 25 V, +125degC, X7R Dielectric, +/-5% | KEMET C0603C104J3RACTU	C21	CAPC1608X90	C0603C104J3RACTU	1
10NF	0603 C 10nF Ceramic Multilayer Capacitor, 25 V, +125degC, X7R Dielectric, +/-5% | KEMET C0603C104J3RACTU	C24, C25	CAPC1608X90	C0603C104J3RACTU	2
18PF	18 pF ±5% 50V Ceramic Capacitor C0G, NP0 0603 (1608 Metric)	C26, C27	CAPC1608X85N	C0603C200J5GACTU	2
10UF	10 µF A±10% 10V Ceramic Capacitor X7R 0805 (2012 Metric)	C35	CAPC2012X135N	C1218225KPFNNNG	1
SS34	3A, 40V, Schottky Rectifier	D1, D2	DIO_SS34	SS34	2
Header 6		J1, J4	SAMTEC_MTLW-106-06-G-S-180	MTLW-106-06-G-S-180	2
Header 3	Connector Unshrouded Header 3 Position 2.54mm Solder Straight Through Hole	J2, J3	SAMTEC_HMT3W-103-XX-X-S-XX-X-S-XXX	HMT3W-103-XX-X-S-XXX	2
AC1206FR-070RL	0 Ohms Jumper Chip Resistor 1206 (3216 Metric) Automotive AEC-Q200 Thick Film	R1, R2, R3, R4	RESC3116X65N	AC1206FR-070RL	4
0 ohms	0 Ohms Jumper Chip Resistor 1206 (3216 Metric) Automotive AEC-Q200 Thick Film	R5	RESC3116X65N	AC1206FR-070RL	1
10k	10 kOhms ±5% 0.125W, 1/8W Chip Resistor 0805 (2012 Metric) Moisture Resistant Thick Film	R6	RESC2012X60N	CR0805-JW-331ELF	1
10k	10 kOhms ±1% 0.25W, 1/4W Chip Resistor 1206 (3216 Metric) Moisture Resistant Thick Film	R7, R11, R12, R13, R20, R21, R22, R23, R25, R26	RESC3116X65N	AC1206FR-070RL	10
49.9	49.9 Ohms ±1% 0.25W, 1/4W Chip Resistor 1206 (3216 Metric) Moisture Resistant Thick Film	R8	RESC3116X65N	AC1206FR-070RL	1
49.9 R	49.9 Ohms ±1% 0.25W, 1/4W Chip Resistor 1206 (3216 Metric) Moisture Resistant Thick Film	R9	RESC3116X65N	AC1206FR-070RL	1
10R	10 Ohms ±1% 0.25W, 1/4W Chip Resistor 1206 (3216 Metric) Moisture Resistant Thick Film	R10	RESC3116X65N	AC1206FR-070RL	1
75R	75 Ohms Jumper Chip Resistor 1206 (3216 Metric) Automotive AEC-Q200 Thick Film	R14, R19	RESC3116X65N	AC1206FR-070RL	2
12.4K	12.4 kOhms ±1% 0.25W, 1/4W Chip Resistor 1206 (3216 Metric) Moisture Resistant Thick Film	R15	RESC3116X65N	AC1206FR-070RL	1
150R	150 Ohms Jumper Chip Resistor 1206 (3216 Metric) Automotive AEC-Q200 Thick Film	R16, R24	RESC3116X65N	AC1206FR-070RL	2
82R	82 Ohms ±1% 0.25W, 1/4W Chip Resistor 1206 (3216 Metric) Moisture Resistant Thick Film	R17, R18	RESC3116X65N	AC1206FR-070RL	2
1M	1 MOhms ±1% 0.25W, 1/4W Chip Resistor 1206 (3216 Metric) Moisture Resistant Thick Film	R27	RESC3116X65N	AC1206FR-070RL	1
OHM	0 Ohms Jumper Chip Resistor 1206 (3216 Metric) Automotive AEC-Q200 Thick Film	R28	RESC3116X65N	AC1206FR-070RL	1
SWITCH	6 x 6.7 mm, 4.3 mm Actuator Height, 260 gf, Black, Surface Mount, SPST, Tactile Switch	S1, S2	SW_T007-667-43-BK-260-SMT-TR	T007-667-43-BK-260-SMT-TR	2
T007-667-43-BK-260-SMT-TR	6 x 6.7 mm, 4.3 mm Actuator Height, 260 gf, Black, Surface Mount, SPST, Tactile Switch	S3	SW_T007-667-43-BK-260-SMT-TR	T007-667-43-BK-260-SMT-TR	1
H1102NL	- Isolation and Data Interface (Encapsulated) Pulse Transformer 1:1 Transmitter, 1:1 Receiver Surface Mount	T1	H1102NL	H1102NL	1
STM32F411RET6	ARM® Cortex®-M4 STM32F4 Mikrodenetleyici IC 32 Bit Tek Çekirdek 100MHz 512KB (512K x 8) FLASH 64-LQFP (10x10)	U1	QFP50P1200X1200X160-64N	STM32F411RET6	1
ADXL345BCCZ	3-Axis, ±2 g/±4 g/±8 g/±16 g Digital Accelerometer	U2	IC_ADXL345BCCZ	ADXL345BCCZ	1
W5500	Hardwired TCP/IP embedded Ethernet controller	U3	QFP50P900X900X160-48N	W5500	1
ABS2S-32.768KHZ-6-T	32.768 kHz A±20ppm Crystal 6pF 50 kOhms 4-SGJ, 5.50mm pitch	Y1	XTAL_ABS2S-32.768KHZ-6-T	ABS2S-32.768KHZ-6-T	1
LFXTAL003151	8 MHz A±30ppm Crystal 16pF 40 Ohms HC-49/US	Y2	WE-XTAL_HC49/4HSMX	LFXTAL003151	1
ABM8G-25.000MHZ-18-D2Y-T	25 MHz A±20ppm Crystal 18pF 60 Ohms 4-SMD, No Lead	Y3	XTAL_ABM8G-25.000MHZ-18-D2Y-T	ABM8G-25.000MHZ-18-D2Y-T	1