

Comment	Description	Designator	Footprint	LibRef	Quantity
10 UF	CAP CER 10UF 16V XSR 1206	C1, C2	CAPC3216X180N	C3216X5R1E106M160 AB	2
100UF	Capacitor, aluminum, 25 V, ±20%, 100 µF, 0.328 x 0.390 inch, Capacitor, aluminum, 10 V, 20%, FC series, 100 µF, 0.335 x 0.374	C3, C7, C12	CAP_EEEFC1E101P	EEEF1E101P	3
0.033uF	Capacitor, ceramic, 25 V, X7R, 20%, .033 µF, 0603	C4, C5	CAPC1608X90	C0603C104J3RACTU	2
470 PF	Capacitor, ceramic, 25 V, X7R, 20%, 470 pF, 0603	C6, C11	CAPC1608X90	C0603C104J3RACTU	2
0.1UF	Capacitor, ceramic, 10 V, X7R, 20%, 0.1 µF, 0603	C8, C15	CAPC1608X90	C0603C104J3RACTU	2
10UF	Capacitor, ceramic, 6.3 V, X5R, 20%, 10 µF, 0805	C9, C10, C13, C14	CAPC2012X140N	0805ZD474MAT2A	4
4.7UF	Capacitor, ceramic, 10 V, X5R, 20%, 4.7 µF, 0805	C16	CAPC2012X140N	0805ZD474MAT2A	1
10NF	Capacitor, ceramic, 25 V, X7R, 20%, 10 nF, 0603	C17	CAPC1608X90	C0603C104J3RACTU	1
6.8NF	Capacitor, ceramic, 25 V, X7R, 20%, 6.8 nF, 0603	C18	CAPC1608X90	C0603C104J3RACTU	1
Schottky Diode	Diode Schottky 30 V 3A Surface Mount SMC	D1, D2	DIOM7959X261N	MBRS330T3G	2
Header 3	Connector Unshrouded Header 3 Position 2.54mm Solder Straight Through Hole	J1, J2, J4, J6, J7	SAMTEC_HMTSW-103-XX-X-S-XXX	HMTSW-103-XX-X-S-XXX	5
Header 6		J3	SAMTEC_MTLW-106-06-G-S-180	MTLW-106-06-G-S-180	1
Header 2	Connector, dc jack 5.5x2.1 mm, PCB mount, 90 degrees, silver plated, thru hole	J5	TENSILITY_54-00129	54-00129	1
22UH	Inductor, Power, 6.8 A, 0.038 Ω, 22 µH, 0.484 x 0.484 inch	L1, L2	IND_MSS1278-223MLB	MSS1278-223MLB	2
L0603R	LED, Red, 0603, Vf=2V, - 40 to +100°C	LD1	LED_0603_R	ASMT-RR45-AQ902	1
L0603A	LED, Amber, 0603, Vf=2V, - 40 to +100°C	LD2	LED_0603_Y	ASMT-RA45-AP932	1
L0603G	LED, Yellow Green, 0603, Vf=2V, - 40 to +100°C	LD3	LED_0603_G	ASMT-RF45-AN002	1
0 ohms	Resistor, chip, 1/16 W, 5%, 0 Ω, 0603	R1, R2, R3	RESC1608X55N	RC0603JR-0751RL	3
10R	Resistor, chip, 1/16 W, 5%, 10 Ω, 0603	R4, R5	RESC1608X55N	RC0603JR-0751RL	2
51R	Resistor, chip, 1/16 W, 5%, 51 Ω, 0603	R6, R9	RESC1608X55N	RC0603JR-0751RL	2
20K	Resistor, chip, 1/16 W, 1%, 20 kΩ, 0603	R7, R8	RESC1608X55N	RC0603JR-0751RL	2
6.34K	Resistor, chip, 1/16 W, 1%, 6.34 kΩ, 0603	R10	RESC1608X55N	RC0603JR-0751RL	1
3.83R	Resistor, chip, 1/16 W, 1%, 3.83 kΩ, 0603	R11	RESC1608X55N	RC0603JR-0751RL	1
845R	Resistor, chip, 1/16 W, 1%, 845 Ω, 0603	R12	RESC1608X55N	RC0603JR-0751RL	1
1.21K	Resistor, chip, 1/16 W, 1%, 1.21 kΩ, 0603	R13	RESC1608X55N	RC0603JR-0751RL	1
10K	Resistor, ±1%, 0.05W	R14	RESC0603X03L_C	R0201-1k0	1
1k	Resistor, ±1%, 0.05W	R15	RESC0603X03L_C	R0201-1k0	1
330R	Resistor, ±1%, 0.05W	R16	RESC0603X03L_C	R0201-1k0	1
TPS54383PWPR		U1	IC_TPS27S100BPWPR	TPS54383PWPR	1